

四层转发 /v1/streams

获取四层转发列表

GET	/v1/streams	调试
page	当前页码	1
integer		
limit	单页显示数量	10
integer		
listen_port	监听的端口	
integer		
listen_protocol	监听的协议, 可选为tcp、udp	
string		
backend_ip	源IP, 模糊匹配	
string		
group	所属的转发组	
integer		
id	转发ID	
integer		
user_package	所属的套餐	
integer		
enable	启用或禁用	▼
boolean		
state	四层转发状态, 可选为200、512、513、514。200是正常, 512是套餐过期, 513是流量超限, 514是被锁定	
string		

返回结果

```
{
  "code": 0,
  "count": 2,
```

```

"backend": "[{"state": "up", "addr": "1.1.1.1", "weight": 1}]",
"backend_port": "99",
"backup_node_group": null,
"backup_node_group_name": null,
"balance_way": "rr",
"cname_domain": "cdnfly.com",
"cname_hostname": "cbsjyv4m",
"cname_mode": "site",
"cname_state": "done",
"cname_task_id": 120525,
"conn_limit": "",
"create_at": null,
"create_at2": "2021-11-26 19:06:02",
"enable": 1,
"enable_backup_group": 0,
"id": 42,
"listen": [{"protocol": "tcp", "port": "999"}]",
"name": "jason",
"node_group_id": 490,
"node_group_name": null,
"package_name": "ff",
"proxy_protocol": 0,
"record_id": "732094354142733312",
"region_id": 646,
"region_name": "test",
"s.cname_domain": "cdnfly.com",
"s.cname_hostname": "cbsjyv4m",
"s.cname_mode": "site",
"state": "200",
"stream_state": "200",
"sync_state": "done",
"task_id": 120524,
"uid": 2,
"up_cname_domain": "cdnfly.com",
"up_cname_hostname": "v325sf8j-u",
"update_at": null,
"update_at2": "2021-11-26 19:06:02",
"user_package": 425,
"version": 1
},
{
  "acl": "{}",
  "backend": "[{"state": "up", "addr": "1.1.1.1", "weight": 1}]",
  "backend_port": "88",
  "backup_node_group": null,
  "backup_node_group_name": null,
  "balance_way": "rr",
  "cname_domain": "cdnfly.com",

```



```
    "cname_task_id": 120502,
    "conn_limit": "",
    "create_at": null,
    "create_at2": "2021-11-26 18:57:16",
    "enable": 1,
    "enable_backup_group": 0,
    "id": 41,
    "listen": "[{\"protocol\": \"tcp\", \"port\": \"88\"}]",
    "name": "jason",
    "node_group_id": 490,
    "node_group_name": null,
    "package_name": "ff",
    "proxy_protocol": 0,
    "record_id": "732093253135826944",
    "region_id": 646,
    "region_name": "test",
    "s.cname_domain": "cdnfly.com",
    "s.cname_hostname": "knw42svf",
    "s.cname_mode": "site",
    "state": "200",
    "stream_state": "200",
    "sync_state": "done",
    "task_id": 120501,
    "uid": 2,
    "up_cname_domain": "cdnfly.com",
    "up_cname_hostname": "v325sf8j-u",
    "update_at": null,
    "update_at2": "2021-11-26 18:57:16",
    "user_package": 425,
    "version": 1
  }
]
```

新增一个或多个转发（多个时，数据格式为数组）

POST /v1/streams		调试
user_package integer	required 绑定的套餐	
listen	required 监听的协议和端口，格式为json 数组，如	

balance_way string	源站负载均衡方式，可选为 ip_hash、rr、least_conn、 random	
proxy_protocol boolean	回源是否使用proxy protocol协议	
backend_port integer	required 回源端口	
backend json	required 源IP设置，格式为json数组，如 [{"addr":"1.1.1.1","weight":1,"state":"up"}], state可选为up、down、backup	
conn_limit integer	连接数限制	
acl json	acl配置，格式为json，如 { "default_action": "allow", "rule": [{"ip": "1.1.1.1", "action": "deny"}] } default_action可选为allow、 deny；rule中的action可选为 allow,deny。	

返回结果

提交内容

```
{  
  "code": 0,  
  "data": "",  
  "msg": "四层转发添加成功"  
}
```

批量修改四层转发（数据格式为数组）

PUT	/v1/streams	调试
id integer	required 四层转发ID	
user_package integer	绑定的套餐	

json	<code>[{"protocol":"tcp","port":"88"}]</code> , protocol可选为tcp或udp	
balance_way string	源站负载均衡方式, 可选为 ip_hash、rr、least_conn、 random	
proxy_protocol boolean	回源是否使用proxy protocol协议	
backend_port integer	回源端口	
backend json	源IP设置, 格式为json数组, 如 <code>[{"addr":"1.1.1.1","weight":1,"state":"up"}]</code> , state可选为up、down、backup	
conn_limit integer	连接数限制	
acl json	acl配置, 格式为json, 如 <code>{"default_action":"allow","rule": [{"ip":"1.1.1.1","action":"deny"}]}</code> , default_action可选为allow、 deny; rule中的action可选为 allow,deny。	
enable boolean	启用或禁用	

返回结果

提交内容

```
{
  "code": 0,
  "data": "",
  "msg": "更新转发成功"
}
```

获取指定四层转发

GET /v1/streams/41

调试

返回结果

```

"data": {
  "acl": "{}",
  "backend": "[{\"state\": \"up\", \"addr\": \"1.1.1.1\", \"weight\": 1}]",
  "backend_port": "88",
  "backup_node_group": null,
  "balance_way": "rr",
  "cname_domain": "cdnfly.com",
  "cname_hostname": "knw42svf",
  "cname_mode": "site",
  "cname_state": "done",
  "cname_task_id": 120502,
  "conn_limit": "",
  "create_at": null,
  "create_at2": "2021-11-26 18:57:16",
  "enable": 1,
  "enable_backup_group": 0,
  "end_at": "2021-12-16 14:47:38",
  "groups": null,
  "id": 41,
  "listen": "[{\"protocol\": \"tcp\", \"port\": \"88\"}]",
  "name": "jason",
  "node_group_id": 490,
  "node_group_name": null,
  "package_name": "ff",
  "proxy_protocol": 0,
  "record_id": "732093253135826944",
  "region_id": 646,
  "s.cname_domain": "cdnfly.com",
  "s.cname_hostname": "knw42svf",
  "s.cname_mode": "site",
  "state": "200",
  "stream_state": "200",
  "sync_state": "done",
  "task_id": 120501,
  "uid": 2,
  "up_cname_domain": "cdnfly.com",
  "up_cname_hostname": "v325sf8j-u",
  "update_at": null,
  "update_at2": "2021-11-26 18:57:16",
  "user_package": 425,
  "version": 1
},
"msg": ""
}

```

修改指定四层转发

user_package integer	绑定的套餐	
listen json	监听的协议和端口，格式为json数组，如 [{"protocol":"tcp","port":"88"}], protocol可选为tcp或udp	
balance_way string	源站负载均衡方式，可选为 ip_hash、rr、least_conn、 random	
proxy_protocol boolean	回源是否使用proxy protocol协议	
backend_port integer	回源端口	
backend json	源IP设置，格式为json数组，如 [{"addr":"1.1.1.1","weight":1,"state":"up"}], state可选为up、down、backup	
conn_limit integer	连接数限制	
acl json	acl配置，格式为json，如 { "default_action": "allow", "rule": [{ "ip": "1.1.1.1", "action": "deny" }] }, default_action可选为allow、deny；rule中的action可选为allow,deny。	
enable boolean	启用或禁用	

返回结果

提交内容

```
{
  "code": 0,
  "data": "",
  "msg": "更新转发成功"
}
```



返回结果

```
{
  "code": 0,
  "data": "",
  "msg": "四层转发删除成功"
}
```

上一篇: [四层相关](#)

下一篇: [转发分组 /v1/stream-groups](#)