

Arcodex - Contract Verification Report

Arc mainnet (chainId 5042) | generated 2026-08-03

1. Executive Summary

All deployed Arcodex contracts were verified by recompiling the exact deployment source with the exact compiler settings and comparing the resulting bytecode against the on-chain code (eth_getCode). Verification is bytecode-level (cryptographic proof), independent of any block explorer. Results: 3/3 deployed contracts verified (ArcodexFeeRouter matches EXACTLY; ArcodexBondingCurve and BondingCurveToken match after immutable-value substitution, which is the correct semantics for Solidity immutables).

2. Compiler Settings (identical to deployment)

```
solc version      : 0.8.24
optimizer        : enabled, runs = 200
viaIR            : true
evmVersion       : paris
dependencies     : @openzeppelin/contracts 5.0.2
```

3. Verification Results

ArcodexBondingCurve	0x0264BebE36b68C0F6694D5f3dC233DFC2bbdF4d0	
PASS	ArcodexBondingCurve	23348 B runtime - match after 7 immu
PASS	ArcodexFeeRouter	3568 B runtime - EXACT bytecode match
PASS	BondingCurveToken (ARCT)	1925 B runtime - match after 2
N/A	ArcodexPool	no instance deployed yet - factory deploys a

Immutable values embedded in the deployed runtime bytecode are patched by the constructor at deploy time; the compiler artifact carries zero placeholders. The 7 + 2 patched positions correspond exactly to the USDC address (curve) and the factory address (token) respectively.

4. Constructor Arguments (read from chain)

ArcodexBondingCurve	(usdc, platformTreasury)
usdc	0x3600 (native USDC)
platformTreasury	0x04FA941F3fa799f86fE9207D1c77eE4F3331B2f3
owner	0x04FA941F3fa799f86fE9207D1c77eE4F3331B2f3
tokenCount	1 (ARCT)
ArcodexFeeRouter	(platformTreasury)
platformTreasury	0x04FA941F3fa799f86fE9207D1c77eE4F3331B2f3
feeBps	150 (1.50%)
owner	0x04FA941F3fa799f86fE9207D1c77eE4F3331B2f3
BondingCurveToken (ARCT)	("Arcodex Test", "ARCT", factory, mint 1e24)
supply	1,000,000 (1e24 wei)
factory	0x0264BebE36b68C0F6694D5f3dC233DFC2bbdF4d0

5. Verification Artifacts

Ready for one-click explorer verification once an Arc mainnet explorer supports source verification (arcscan.app is not yet public):

```
contracts/verify/arcodex-standard-input.json - exact solc standard JSON input (10 sources)
contracts/verify/verify_bytecode.js          - reproducible bytecode verification script
contracts/                                     - original multi-file sources (identical to deploy)
```

6. Methodology Notes

- eth_getCode fetched via the public Arc RPCs (arcanine + Railway fallback), same sources that built the deployed bytecode (verified

identical to the repository copies).

- solc's trailing CBOR metadata hash (43 bytes) is stripped from both sides before comparison; it encodes IPFS metadata and legitimately differs per compile environment.

- Arc mainnet has no public block explorer yet (arcscan.app resolves to a private address; arc.blockscout.com returns 404; chainlist lists no explorer for 5042). Source verification on an explorer was therefore not possible at the time of writing; the bytecode-level proof above is equivalent and explorer-independent.