Can an AI rubric distinguish two similar Cantonese expressions?

One approved matched scenario • one fixed five-construct rubric

JAN｜「忍一忍先。」	TAIHOI｜「睇開啲。」

What the demonstration does

1. Shows one approved matched scenario.
2. Keeps the person, event, relationship, motive and intended action constant.
3. Changes only the final self-talk.
4. Applies five independent 1–7 ratings and returns a rationale.

Five fixed constructs

Expressive suppression • Experiential avoidance • Acceptance • Cognitive reappraisal • Distress tolerance

How to use it

Predict → test connection → run once → compare scores and rationale.

If a 403 or timeout appears, open the saved output for the same scenario. Do not troubleshoot on stage.

Live access requirements

Internet, a disposable OpenRouter API key, and a model permitted in the current region. The saved output works offline.

Saved output from the exact demo scenario

Construct	JAN	TAIHOI
Expressive suppression	6	5
Experiential avoidance	3	3
Acceptance	4	4
Cognitive reappraisal	1	4
Distress tolerance	6	6

Interpretation: in this saved pair, the clearest difference is cognitive reappraisal. Scores are model-generated conceptual ratings, not diagnoses or estimates of how Cantonese speakers think or feel.

What this is—and is not

This is a local HTML interface that calls a remotely hosted AI evaluator through the OpenRouter API. It is not a locally installed or locally developed LLM. No audience names, votes or research data are collected. Human, expert and cultural validation remain essential.

Open the public demonstration

https://hikariumi39.github.io/a20-cantonese-ai-demo/