Create a single, self-contained, and exceptionally creative 10-slide HTML presentation file in English about "The Secret Language of Emojis and Generational Interpretations" (how emojis evolve and change meanings across Gen Z, Millennials, Gen X, and Boomers).

The output must strictly be a single HTML file containing all HTML, CSS, JavaScript, and embedded libraries.

Key Requirements:
1. Direction & Structure:
- Must be strictly LTR (Left-to-Right layout, text alignment, and reading flow).
- Exactly 10 distinct, beautifully structured content slides covering the evolution, cultural shifts, irony, and modern semiotics of emojis across generations.

2. Design & Aesthetics (FANCY & Out-of-the-Box):
- High-end, futuristic, and creative UI/UX with smooth transitions, glassmorphism, glowing gradients, and dark-mode aesthetics.
- Unique animations and interactive layout components.

3. Interactivity & Navigation (JavaScript):
- Fully functional navigation buttons (Next, Previous, and direct slide indicators/dots).
- Keyboard support (Arrow keys to navigate slides).
- Interactive elements on slides (e.g., hover effects, clickable generational translation dictionaries, or interactive emoji sentiment meters).

4. 3D Elements (Three.js):
- Integrate Three.js via CDN to render interactive 3D elements directly inside the presentation (e.g., floating 3D emoji geometry, rotating particles, or interactive 3D text/cubes representing emoji evolution stages).

5. Python Integration Elements:
- Include visual references, data structures, or code-block widgets demonstrating how a Python backend or script (e.g., using sentiment analysis or emoji mapping algorithms) processes and categorizes generational emoji slang.

Generate the complete, fully working HTML file without placeholders.

—---
Modify the existing single-file HTML presentation titled "The Secret Language of Emojis and Generational Interpretations" (LTR, English). Replace the raw Python code slides with highly engaging, interactive, and gamified content slides that fit the overarching narrative of generational emoji evolution.

The single HTML file must include all HTML, CSS, JavaScript, and Three.js 3D elements, structured into 10 cohesive, story-driven slides:

Key Updates & New Slide Requirements:
1. Narrative & Structure (10 Slides Total, LTR):
  - Maintain a smooth, futuristic, glassmorphic UI with Three.js 3D background elements and seamless navigation (buttons + keyboard arrows).
  - Ensure the flow tells a logical, engaging story: from the birth of digital symbols to modern generational clashes (Boomers vs. Gen Z irony).

2. Interactive Mini-Games & Special Slides to Replace Python Slides:
  - **Slide (Generational Memory Game):** An interactive matching memory game where users match modern slang emojis to their correct generational meanings (divided or toggleable by generation: Gen Z, Millennials, Boomers).
  - **Slide (Emoji Translation Dictionary / Rosetta Stone):** An interactive "Emoji Translator" card grid where hovering/clicking individual emojis reveals their literal meaning vs. their ironic/generational meaning with fun explanations.
  - **Slide (Emoji Trivia Challenge):** A multiple-choice trivia game testing users on generational emoji etiquette and hidden meanings, with instant score tracking and feedback.
  - **Slide (Emoji Wordle):** A fully playable, custom Wordle mini-game built directly into the slide using 5-character emoji combinations or emoji-related terms, complete with virtual keyboard or click inputs and win/loss states.

3. Design & Execution:
  - Keep everything self-contained within the single HTML file.
  - Ensure high interactivity, clean CSS animations, and polished UI design for all embedded games so they work right inside the presentation slides.

Generate the complete, fully functional updated HTML file directly.
—----------
Modify the existing single-file HTML presentation titled "The Secret Language of Emojis and Generational Semiotics" (LTR, English). Add a dedicated interactive slide (Slide 11) demonstrating a Python backend script and sentiment analysis engine that processes and categorizes generational emoji slang.

Key Requirements for the Python Slide:
1. Include an interactive Python code-block widget styled with a dark terminal aesthetic, showing a clean Python script using libraries like NLTK or TextBlob and custom dictionaries to classify emoji texts into generational cohorts (Gen Z, Millennial, Boomer).
2. Add an interactive live simulation box where users can type a sentence with emojis, and a simulated Python processing engine instantly computes and outputs the detected sentiment score, dominant generation syntax, and irony probability.
3. Ensure the slide matches the existing futuristic glassmorphism design, works seamlessly within the single HTML file, and preserves all navigation buttons and Three.js elements.
—------

Modify the existing index.html file in-place. Do not create a new file. Update one of the existing slides (ideally Slide 10 or Slide 4) to seamlessly integrate a Python element: add an interactive Python code-block widget and a live simulated Python sentiment analysis terminal card that processes generational emoji text. Ensure all single-file HTML, CSS, JavaScript, and Three.js structures remain intact without increasing the total slide count beyond 10.
—----

Modify the existing single-file HTML presentation named "emoji_presentation.html" in-place. Do not create a new file. Ensure strict LTR layout, a high-end FANCY futuristic UI/UX design, fully working JavaScript navigation buttons and interactive elements, Three.js 3D elements, and incorporate Python logic behind-the-scenes (for data processing/game structures without displaying raw Python code blocks on screen).

Strictly structure the presentation into exactly 10 cohesive slides with the following updated content and interactive mechanics:

- Slide 1: Title & Hero. Display a 3D smiling emoji rendered via Three.js that rotates 360 degrees and whose eyes/gaze track the user's mouse movement across the screen.
- Slide 2: Emoji Dictionary. Grid of interactive cards showing a single emoji per card with dual generational interpretations: Gen Z vs. Gen X perspective.
- Slide 3: Memory Game. An interactive memory matching mini-game pairing emojis with their correct cultural interpretations, complete with moves counter and restart.
- Slide 4: Popular Emoji Analytics. A graphical statistical bar chart showing global usage percentages of top emojis, rendered cleanly with HTML/CSS data viz.
- Slide 5: Emoji Wordle. A fully playable Wordle-style mini-game where users guess emoji-related terms using text descriptions as clues instead of pictures.
- Slide 6: Guess the Country by Emoji. An interactive trivia game where up to 3 emojis describe a specific country, users type/guess the answer, and a random new puzzle is generated each round.
- Slide 7: Emoji Avatar Builder. An interactive customizer where users select a base emoji face and layer decorative items like hats or glasses to generate a custom emoji avatar.
- Slide 8: Trivia Challenge. Multiple-choice trivia game testing users on generational emoji etiquette and hidden subtext meanings with instant scoring and feedback.
- Slide 9: Historical Evolution. Informational slide explaining how emojis were originally created in Japan (DoCoMo) and evolved into a global standard.
- Slide 10: "Catch the Emoji" Mini-Game. An interactive arcade game built into the slide where emojis fall from top to bottom, users click/tap to catch as many as possible while dodging a bomb penalty, with live score tracking.
- Slide 11 (Closing/Thank You): Thank You screen featuring animated floating thank-you emojis and glowing hearts scattered across the canvas in a gorgeous glassmorphism layout.

Preserve all existing Three.js integrations, make sure everything runs smoothly inside the single HTML file, and maintain the exact 10-slide count structure.
—----------

Modify the existing single-file HTML presentation named "emoji_presentation.html" in-place. Do not create a new file.
Ensure strict LTR layout, a high-end FANCY futuristic UI/UX design, fully working JavaScript navigation buttons and
interactive elements, Three.js 3D elements, and incorporate Python logic behind-the-scenes (for data processing/game
structures without displaying raw Python code blocks on screen).

Strictly structure the presentation into exactly 10 cohesive slides with the following updated content and interactiv
mechanics:

- Slide 1: Title & Hero. Display a 3D smiling emoji rendered via Three.js that rotates 360 degrees and whose eyes/gaz
track the user's mouse movement across the screen.
- Slide 2: Emoji Dictionary. Grid of interactive cards showing a single emoji per card with dual generational
interpretations: Gen Z vs. Gen X perspective.
- Slide 3: Memory Game. An interactive memory matching mini-game pairing emojis with their correct cultural
interpretations, complete with moves counter and restart.
- Slide 4: Popular Emoji Analytics. A graphical statistical bar chart showing global usage percentages of top emojis,
rendered cleanly with HTML/CSS data viz.
- Slide 5: Emoji Wordle. A fully playable Wordle-style mini-game where users guess emoji-related terms using text
descriptions as clues instead of pictures.
- Slide 6: Guess the Country by Emoji. An interactive trivia game where up to 3 emojis describe a specific country,
users type/guess the answer, and a random new puzzle is generated each round.
- Slide 7: Emoji Avatar Builder. An interactive customizer where users select a base emoji face and layer decorative
items like hats or glasses to generate a custom emoji avatar.
- Slide 8: Trivia Challenge. Multiple-choice trivia game testing users on generational emoji etiquette and hidden
subtext meanings with instant scoring and feedback.
- Slide 9: Historical Evolution. Informational slide explaining how emojis were originally created in Japan (DoCoMo)
and evolved into a global standard.
- Slide 10: "Catch the Emoji" Mini-Game. An interactive arcade game built into the slide where emojis fall from top to

bottom, users click/tap to catch as many as possible while dodging a bomb penalty, with live score tracking.
- Slide 11 (Closing/Thank You): Thank You screen featuring animated floating thank-you emojis and glowing hearts
scattered across the canvas in a gorgeous glassmorphism layout.

Preserve all existing Three.js integrations, make sure everything runs smoothly inside the single HTML file, and
maintain the exact 10-slide count structure.C:\biu01\HW1\emoji_presentation.html

○ Thought for 7m 55s (JavaScript syntax appears valid. The next step involves checking for broken links, missing ima...
● Explored 1 file (emoji_presentation.html)
● Ran (node -v; python --version) failed
… 16 more actions (2 edits, 14 commands: 2 failed) …
● Edited 1 file (emoji_presentation.html)
● Ran 6 commands (+4 · git status: failed · Get-ChildItem -Path "C:\biu01\HW1") (ctrl+o to expand)

▸ Thought for 10s

The single-file HTML presentation emoji_presentation.html has been updated in-place with a futuristic UI/UX design,
strict LTR alignment, and interactive mechanics across all slides.

Key Implementations & Enhancements

1. Slide 1: Title & Hero (Three.js 3D Smiling Emoji with Gaze Tracking)
   • Custom 3D smiling emoji rendered in Three.js with glossy yellow sphere geometry, eye sockets, pupils, glints,
   blushing cheeks, and curved smile.
   • Continuous 360-degree rotation plus interactive drag support.
   • Real-time mouse gaze tracking: pupils and eye groups dynamically orient toward the user's mouse pointer across
   the screen.
2. Slide 2: Emoji Dictionary (Gen Z vs. Gen X Perspectives)
   • Interactive card grid presenting one glyph per card (👍, 🙂, 💀, 🧢, 🤡, 💅, 🫠, ☕).
   • Side-by-side color-coded comparative panels: Amber for Gen X literal pragmatism vs. Neon Green for Gen Z post-
   ironic subversion.
   • Real-time search filter and category tabs (Workplace Hazards, Youth Inversions, Sass & Praise).
3. Slide 3: Generational Memory Game

• 12-card interactive memory matching mini-game pairing modern emojis (💀, 🧢, 👍, 🤡, 💅, 🫠) with their
authentic generational meanings.
• Smooth 3D card-flip animations, live moves counter, timer, match counter, celebratory victory banner, and
restart button.

4. Slide 4: Popular Emoji Analytics (Graphical Bar Chart Data Viz)
• Animated HTML/CSS horizontal bar charts showing global usage percentages of top emojis (😂, ❤️, 🤣, 👍, 😭, 🙏,
💀, 🥰).
• Category toggles: All-Time Global, Gen Z Peak, and Workplace Slack Frequency.
• Contextual insight cards explaining the Semiotic Inflation Law, legal contract precedents, and demographic
variance.
5. Slide 5: Emoji Wordle (Text Descriptions as Clues)
• Fully playable Wordle game with 6 rows of 5 letter tiles, virtual QWERTY keyboard, and physical keyboard
support.
• Text clues guide the player (e.g., "Gen Z's supreme token for laughing until they expire" for SKULL).
• Standard Wordle coloring (🟩 Correct, 🟨 Present, ⬛ Absent) with pop and flip animations.
6. Slide 6: Guess the Country by Emoji Triad
• Interactive geographic trivia game displaying up to 3 emojis representing a country (e.g., 🗼🥖🍷 for France,
🍣🗻🗾 for Japan, 🍕🏛️🛵 for Italy).
• Text guess input supporting Enter key submission, alias recognition (e.g. "USA" / "United States"), streak
tracking, hints (continent & capital), and random puzzle generation.
7. Slide 7: Interactive Emoji Avatar Builder
• Real-time composite avatar canvas layering base faces (😀, 😎, 😉, 😆, 😐, 🤯, 💀, 👽, 🐱), headwear (🥳, 🎩,
👑, 🤠, 🧢, 🎓, 🎧), eyewear (🕶️, 👓, 🧐, 🥽, ⭐), and decorative accents (✨, 🔥, ❤️, 💧, 🥸).
• Includes 🎲 Randomize and 📋 Copy Glyph Stack actions.
8. Slide 8: Generational Trivia Challenge
• Multiple-choice quiz covering workplace communication hazards, court contract rulings, and hidden subtext
meanings.
• Instant green/red feedback, streak multiplier, point scoring, educational breakdowns, and final rank badge
evaluation.
9. Slide 9: Historical Evolution (NTT DoCoMo to Unicode)

• 4-stage narrative timeline detailing Shigetaka Kurita's original 176 12x12 pictograms (1999), Unicode 6.0
standardization (2010), Apple/Android smartphone boom (2011–2015), and MoMA permanent collection acquisition.
• Interactive toggle button simulating 1999 monochrome 12px pixelated rendering.
10. Slide 10: "Catch the Emoji" Arcade Mini-Game
• High-frame-rate arcade game where emojis fall from top to bottom.
• Catch positive emojis (💖 +30, ⭐ +20, 💀 +15, 😂 +10, 🔥 +25) to build combo multipliers.
• Dodge bombs (💣 -50 pts, lose a heart, screen shake).
• Features a 30-second timer, 3 hearts/lives, high-score tracking, floating score popups, and a game-over modal.
11. Slide 11: Closing & Thank You Finale
• High-end glassmorphism card with frosted backdrop blur and glowing gradient border.
to handle statistical data distributions and non-repeating trivia puzzle pools without rendering raw code blocks on
screen, coupled with client-side JavaScript fallbacks for offline stability.
• Three.js Ambient Particles: Preserved across the entire deck with dynamic point-light shifts per slide.
• Audio Synthesizer: Built-in Web Audio API generating procedural UI sounds (whooshes, clicks, flips, catches, bomb
explosions, and victory chimes) with a mute toggle.

None

```
>_ OpenAI Codex (v0.166.0)
   C:\biu01\HW1

To get started, describe a task or try one of these commands:

/init - create an AGENTS.md file with instructions for Codex
/status - show current session configuration
/permissions - choose what Codex is allowed to do
/model - choose what model and reasoning effort to use
/review - review any changes and find issues
```

Create **Version 2** of the existing `emoji_presentation.html` file located in the current working directory.

First inspect the existing HTML file, then create a new file named `emoji_presentation_v2.html` in the same directory, keeping the original file completely unchanged.

Maintain the existing design, animations, and functionality, except for the following modifications:

1. Global Changes
- Update the slide counter on all slides from `[Current Slide] / 10` to `[Current Slide] / 11`.
- Remove the header **"Emoji Semiotics Generational Lexicon & Interactive Arcade"** wherever it appears.
- Remove the section header **"01 // Cultural Semiotics & Generational Linguistics"** wherever it appears.
- **Slide 9:** Completely remove the "Toggle 12px Pixel View" button.

2. Slide 6 – Country Guessing Game
- Replace the existing free-text input with a searchable combobox that supports both typing and selecting from a dropdown containing all countries worldwide.
- Filter country suggestions dynamically as the user types.
- Keep the existing answer validation and game functionality.
- Add at least 15 new creative emoji country puzzles, with varying difficulty levels, while preserving the existing puzzles.

3. Slide 8 – Trivia Quiz
- Shuffle answer options so that the correct answer is not always Option 2.
- Ensure the correct answer is accurately identified regardless of its displayed position.
- Preserve the existing scoring and feedback functionality.

Final Instructions
- Make only the requested changes; avoid unnecessary redesign or refactoring.
- Keep the entire presentation in a **single, self-contained HTML file**, without creating additional files or folders.
- Verify that slide navigation, the country game, and trivia quiz still function correctly.
- Confirm that the new HTML file was created successfully and provide its location.

I'll inspect the HTML, make the requested changes in a separate Version 2 file, and check navigation and both games while leaving the original untouched.

None

```
• Ran Get-Location; rg --files -g AGENTS.md -g
emoji_presentation.html -g package.json -g '*playwright*' -g
'*puppeteer…
  └ C:\biu01\HW1
```

```
• Explored
  └ Read emoji_presentation.html
• Exited (status 1) Get-ChildItem -Force; Get-Command
node,python,chrome,msedge -ErrorAction SilentlyContinue | Select-…
  └


• Ran rg -n -C 5 'country|Country|slide-counter|/
10|Semiotics|Cultural Semiotics|docomo-toggle|keydown|totalSlides'
em…
  └ 3903-      updateSlideUI();
    3904-    });
    3905-  </script>
• Ran node -e "for (const m of
['playwright','puppeteer','@playwright/test']) {try
{console.log(m,require.resolve(m))}c…
  └ C:/Users/shire/node_modules false
    C:/biu01/node_modules false

73c016c17f39fafc0dccd2424d8145f9594f23ac0a2c88a384c214e68f47f635
• Ran $lines = Get-Content -Encoding UTF8 emoji_presentation.html;
$lines[1587..1606]; $lines[2248..2394]; $lines[3309.…
  └ .text-green { color: #39FF14; }
    ```
    v24.20.0
```

The deck already has 11 slides, but its counter shows 10 on slides 1–10. I also found two country puzzle pools—JavaScript and Python—so I'll add the new puzzles to both and keep them available whichever engine runs. The country field will use a native searchable dropdown, and trivia answers will be shuffled while retaining their correctness flags.

```
None
• Exited (status 1) @' …
  └   at Socket.<anonymous>
(node:internal/process/execution:205:5)
```
```

```
    Node.js v24.20.0
• Ran $OutputEncoding = [System.Text.UTF8Encoding]::new(); @' …
  └ Created V2 with 18 additional puzzles in both engines.
• Ran $OutputEncoding = [System.Text.UTF8Encoding]::new(); @' …
  └ Original SHA256 unchanged; JavaScript syntax valid; slides: 11
• Ran @' …
  └ stderr
[35944:23364:1105/181354.392:ERROR:components\viz\host\persistent_c
ache_sandboxed_file_factory.cc:153] Faile…

    exit 2147483651 null
```

Version 2 is created with 18 additional puzzles, bringing each pool to 30. The original file's hash is unchanged, and the new JavaScript passes syntax checks. I'm checking the interactions in Chrome next, including quiz scoring after shuffling and feedback after a restart.

None

```
You approved codex to run $OutputEncoding =
[System.Text.UTF8Encoding]::new(); @' ... this time
• Ran $OutputEncoding = [System.Text.UTF8Encoding]::new(); @' …
  └ BOOT
{"countries":250,"puzzles":30,"three":"object","bridge":false}
    PASS: navigation across all 11 slides, country list, hints,
correct/incorrect guesses, auto next round, aliases, tr…
    PAGE ERRORS []
• Ran @' …
  └
{"file":"C:\\biu01\\HW1\\emoji_presentation_v2.html","bytes":148013
,"puzzlesPerEngine":30,"originalPuzzlesPreserved…
```

Created emoji_presentation_v2.html (emoji_presentation_v2.html) with the requested changes, including a searchable country dropdown, 18 new puzzles, and shuffled trivia answers.

Verified all 11 slides navigate correctly and both games retain scoring and feedback. The original file remains unchanged.

```
None
  Worked for 6m 1s • 18:16
```

Update the existing `emoji_presentation_v2.html` file in the current directory.

Correction to the previous instructions:

The request to remove the section header `"01 // Cultural Semiotics & Generational Linguistics"` was intended to apply to **all section headers following the same pattern**, not just this specific text.

- Remove all headers formatted as `[Slide Number] // [Section Title]` throughout the entire presentation (e.g., `01 // ...`, `02 // ...`, `03 // ...`, etc.).
 - Remove the corresponding header elements and any unnecessary empty spacing.
 - Preserve all other slide titles, content, layout, and functionality.
 - Make this change directly in `emoji_presentation_v2.html`. Do not create a new version or modify the original `emoji_presentation.html`.

Verify that no headers matching this pattern remain on any slide.

Make no other changes.

I'll remove the numbered section headers from Version 2, then verify that none remain and no other content changed.

```
None
• Exited (status 1) rg -n -C 2 '\d+\s*//|slide-tag'
emoji_presentation_v2.html; rg --files -g AGENTS.md
  └ 2128:            <div class="slide-tag" style="margin:0 auto
12px auto;">11 // Presentation Finale</div>
    2129-            <h2 class="slide-title" style="font-size:32px;
margin-bottom:12px;">
    2130-              Thank You for <span
class="glow-gradient">Exploring!</span>
• Ran @' …
  └ Removed 10 complete section-header lines, including their
margins. Verified no numbered section headers remain. All…
```

Updated emoji_presentation_v2.html (emoji_presentation_v2.html), removing all 10 remaining numbered section headers and their spacing.

Verified no matching headers remain. All other content is unchanged, and the original HTML was not modified.

Create a new file: Version 3 of the C:\biu01\HW1\emoji_presentation_v2.html presentation. Update the design according to the instructions in the attached MD file C:\biu01\HW1\emoji_presentation_design_guide.md

I'll read the design guide and Version 2, then create `emoji_presentation_v3.html` with the updated design.

```
None
• Ran Get-Location; rg --files -g AGENTS.md -g '*emoji*' -g
'package.json'
  └ C:\biu01\HW1


• Ran Get-Content emoji_presentation_design_guide.md; Get-Content
emoji_presentation_v2.html
  └   </script>
    </body>
    </html>
```

The guide calls for Unkempt headings, Space Grotesk body text, neon accents, and light backgrounds for dense slides. I'll apply those styles across the deck while preserving its content and interactive features. I'm using the presentation skill to check the result.

```
None
• Ran Get-Content
'C:/Users/shire/.codex/plugins/cache/openai-primary-runtime/present
ations/26.1105.12137/skills/presen…
  └
        .floating-bg-item {
          position: absolute;
```

```
• Ran Get-Content
'C:/Users/shire/.codex/plugins/cache/openai-primary-runtime/present
ations/26.1105.12137/skills/presen…
  └ 3668:            <div style="font-size:38px;
margin-bottom:8px;">🎖️</div>
    3669:            <div style="font-size:16px; font-weight:800;
color:#38bdf8; margin-bottom:6px;">${rankTitle}</div>
    3670:            <p style="font-size:12px;
color:var(--text-muted); margin-bottom:16px;">
• Exited (status 1) Get-Command node,python,msedge,chrome
-ErrorAction SilentlyContinue | Select-Object Name,Source; rg…
  └ python.exe
C:\Users\shire\AppData\Local\Microsoft\WindowsApps\python.exe


• Ran Get-Content
'C:/Users/shire/.codex/plugins/cache/openai-bundled/computer-use/26
.1103.31037/skills/computer-use/SK…
  └           nextSlide();
              return;
            } else if (e.key === 'ArrowLeft' || e.key === 'PageUp')
{
• Ran Get-Item 'C:/Program Files
(x86)/Microsoft/Edge/Application/msedge.exe','C:/Program
Files/Google/Chrome/Applicati…
  └     .chart-category-bar {


• Failed Checking browser preview tools
  └ The requested module './index.js' does not provide an export
named 'default'
```

I'll use light backgrounds for the dictionary, analytics, and history slides, and keep the title and games dark. I'll also update the cards, controls, charts, and game states so the new palette is consistent throughout.

None

```
• Ran Get-Content emoji_presentation_v2.html -Encoding UTF8 |
Select-Object -Skip 1730 -First 56; Get-Content emoji_pre…
  └            SLIDE 10: "CATCH THE EMOJI" ARCADE MINI-GAME

================================================================
-->
    v24.20.0
• Added redesign.cjs (+150 -0)
+const fs = require('fs');
+let html = fs.readFileSync('emoji_presentation_v2.html', 'utf8');
+html = html.replace('<title>', '<title>Version 3 — ')
• Ran node redesign.cjs
  └ Created emoji_presentation_v3.html
• Added verify-v3.cjs (+32 -0)
+const fs = require('fs');
+const {spawn} = require('child_process');
+const {setTimeout: delay} = require('timers/promises');
```

Version 3 is created. I'm checking it in the browser for font loading, readable light slides, working controls, and narrow-screen layout issues.

None

```
• Exited (status 1) Get-ChildItem $env:TEMP/emoji-v3-*.png
-ErrorAction SilentlyContinue | Select-Object FullName; git …
  └ fatal: not a git repository (or any of the parent directories):
.git
• Ran Invoke-RestMethod http://127.0.0.1:9234/json | ConvertTo-Json
-Depth 3
  └              ],
       "Count":  4
    }
• Exited (status 1) node verify-v3.cjs
  └ Source slide count: 0
• Ran node -e "const fs=require('fs'),vm=require('vm');let
h=fs.readFileSync('emoji_presentation_v3.html','utf8');let s…
  └ JavaScript syntax valid; sections: 11
```

```
    UTF-8 emoji preserved: true
• Ran (Get-Content verify-v3.cjs
-Raw).Replace('tabs[0].webSocketDebuggerUrl',"tabs.find(t=>t.type==
='page').webSocketD…
  └ }
    Interactions undefined
    Mobile
[{"slide":1,"overflowX":false},{"slide":2,"overflowX":false},{"slid
e":4,"overflowX":false},{"slide":5,"overf…
• Ran rg -n
'brython|window\.|python|py_|bridge|initThree|updateAmbientThreeLig
ht|bgLight' emoji_presentation_v3.html
  └ 3496:          puzzle = window.PythonBridge.getCountry();
    4043:    window.addEventListener('DOMContentLoaded', () => {
    4044:      initThreeBackground();
• Ran Write-Output $env:TEMP
  └ C:\Users\shire\AppData\Local\Temp
• Viewed image emoji-v3-9.png
```

The slides fit at desktop and phone widths. Browser testing also found an existing issue: when the external 3D library fails to load, it prevents the games from initializing. I'm adding a fallback so the deck remains usable in that case.

None

```
• Edited redesign.cjs (+16 -0)
+html = html.replace('onload="brython(1)"', 'onload="if (typeof
brython === \'function\') brython(1)"');
+html = html.replace('      initThreeBackground();\r\n
initHeroThreeScene();', `      // Optional 3D assets must not block
the dictionary and games.
• Ran rg -n 'Optional 3D|font-family|<body onload'
emoji_presentation_v3.html | Select-Object -Last 8
  └ 1981:            <div style="font-size:11px;
font-family:var(--font-mono); color:#00F0FF;
text-transform:uppercase;…
```

```
    2015:              <strong style="color:#39FF14;
font-family:var(--font-mono);" id="country-solved-count">0</strong>
    2019:              <strong style="color:#FFE600;
font-family:var(--font-mono);" id="country-streak-count">🔥 x0</st…
• Viewed image emoji-v3-1.png
• Edited redesign.cjs (+1 -1)
-html = html.replace('      initThreeBackground();\r\n
initHeroThreeScene();', `      // Optional 3D assets must not block
the dictionary and games.
+html = html.replace(/      initThreeBackground\(\);\r?\n
initHeroThreeScene\(\);/, `      // Optional 3D a
• Ran node redesign.cjs; node verify-v3.cjs
  └ }
    Interactions undefined
    Mobile
[{"slide":1,"overflowX":false},{"slide":2,"overflowX":false},{"slid
e":4,"overflowX":false},{"slide":5,"overf…
• Ran rg -n 'Optional 3D' emoji_presentation_v3.html; Get-Item
emoji_presentation_v3.html | Select-Object Name,Length
  └ emoji_presentation_v3.html 156213


• Ran node redesign.cjs; node verify-v3.cjs
  └   quiz: "✓ CORRECT! 💀 ('I'm dead') is the supreme Gen Z token
for extreme laughter, derived from the idiom 'dying …
    }
    Mobile
[{"slide":1,"overflowX":false},{"slide":2,"overflowX":false},{"slid
e":4,"overflowX":false},{"slide":5,"overf…
• Viewed image emoji-v3-1.png
• Viewed image emoji-v3-2.png
• Viewed image emoji-v3-4.png
• Ran Get-Content emoji_presentation_v3.html -Encoding UTF8 |
Select-Object -Skip 2990 -First 42
  └         const filtered = dictionaryDatabase.filter(item =>
item.category === category);
```

```
            renderDictionaryCards(filtered);
          }
```

The redesigned deck passes the layout checks, and I verified dictionary filtering, avatar randomization, and quiz feedback. The fallback also lets the games initialize when the 3D library is unavailable. I'm finishing the contrast adjustments and removing temporary check files.

```
None
• Edited 3 files (+2 -200)
  └ emoji_presentation_v3.html (+2 -1)
-    .slide-light .dict-tag { color: #121214; background: #FFE600;
}
+    .slide-light .dict-badge { color: #121214; font-weight: 700; }
+    .slide-light .dict-grid { max-height: none; overflow: visible;
}

  └ redesign.cjs (+0 -166)
-const fs = require('fs');
-let html = fs.readFileSync('emoji_presentation_v2.html', 'utf8');
-html = html.replace('<title>', '<title>Version 3 — ')

  └ verify-v3.cjs (+0 -33)
-const fs = require('fs');
-const {spawn} = require('child_process');
-const {setTimeout: delay} = require('timers/promises');
• Ran node -e "const fs=require('fs'),vm=require('vm');const
h=fs.readFileSync('emoji_presentation_v3.html','utf8');for…
  └ Final HTML verified: 11 slides; JavaScript syntax valid.
```

Created emoji_presentation_v3.html (/C:/biu01/HW1/emoji_presentation_v3.html) with the guide's fonts, neon palette, rounded cards, and light backgrounds for dense slides.

Preserved all 11 slides and interactive features. Checked desktop and mobile layouts. Version 2 remains unchanged

—--

Please generate and update a professional, comprehensive README.md file in the root of this repository for our academic project "The Secret Language of Emojis" (developed for Bar-Ilan University, course on Generative AI & Agents, Dr. Yoram Segal).

Make sure the README includes the following sections and meets all strict academic requirements:
1. Project Overview & Core Vision: Explain the semiotic and generational differences in emoji interpretation (Gen X vs Gen Z) implemented across the interactive HTML presentation deck.
2. Technical Architecture & Layers: Detail the 3 layers used (HTML5 structure, CSS3 dark neon styling, JavaScript interactivity & Three.js 3D rendering). Mention the behind-the-scenes Python integration via Brython.
3. Interactive Features & Mini-Games: Describe the 11 slides, including the Memory Match game, Emoji Wordle, Country Triad Decoder, Emoji Roulette, Trivia Challenge, and the "Catch the Emoji" arcade mini-game.
4. Visuals & Screenshots Section: Create clear placeholders and Markdown formatting for screenshots/visual illustrations showcasing the 3D Three.js emoji helix, interactive UI cards, and gameplay stages.
5. Setup & Execution Instructions: Clear step-by-step guidance on how to open and run the single-file presentation directly in any modern browser.
6. Engineering Workflow: Document the use of PRD.md, prompt engineering process, and iterative Git commits/pushes.

Write the README.md file directly into the root directory of the project repository.
—--
Please stage, commit, and push the updated README.md file to the remote GitHub repository (hilaabay123-droid/emoji_presentation). Use the commit message "Update README.md with professional documentation and requirements".