

3. Time series decomposition

3.2 Time series components

OTexts.org/fpp3/

Rob J Hyndman
George Athanasopoulos

FORECASTING

PRINCIPLES AND PRACTICE

A comprehensive introduction to the latest forecasting methods using R. Learn to improve your forecast accuracy using dozens of real data examples.



3RD EDITION

oTexts
OPEN. AFFORDABLE. ACCESS. EVERYWHERE.

Time series patterns

Recall

Trend pattern exists when there is a long-term increase or decrease in the data.

Cyclic pattern exists when data exhibit rises and falls that are *not of fixed period* (duration usually of at least 2 years).

Seasonal pattern exists when a series is influenced by seasonal factors (e.g., the quarter of the year, the month, or day of the week).

Time series decomposition

$$y_t = f(S_t, T_t, R_t)$$

where y_t = data at period t

T_t = trend-cycle component at period t

S_t = seasonal component at period t

R_t = remainder component at period t

Time series decomposition

$$y_t = f(S_t, T_t, R_t)$$

where y_t = data at period t

T_t = trend-cycle component at period t

S_t = seasonal component at period t

R_t = remainder component at period t

Additive decomposition: $y_t = S_t + T_t + R_t$.

Multiplicative decomposition: $y_t = S_t \times T_t \times R_t$.

Time series decomposition

- Additive model appropriate if magnitude of seasonal fluctuations does not vary with level.
- If seasonal are proportional to level of series, then multiplicative model appropriate.
- Multiplicative decomposition more prevalent with economic series
- Alternative: use a Box-Cox transformation, and then use additive decomposition.
- Logs turn multiplicative relationship into an additive relationship:

$$y_t = S_t \times T_t \times R_t \quad \Rightarrow \quad \log y_t = \log S_t + \log T_t + \log R_t.$$


US Retail Employment

```
us_retail_employment <- us_employment |>
  filter(year(Month) >= 1990, Title == "Retail Trade") |>
  select(-Series_ID)
us_retail_employment
```

```
## # A tsibble: 357 x 3 [1M]
##       Month Title      Employed
##       <mth> <chr>      <dbl>
## 1 1990 Jan Retail Trade 13256.
## 2 1990 Feb Retail Trade 12966.
## 3 1990 Mar Retail Trade 12938.
## 4 1990 Apr Retail Trade 13012.
## 5 1990 May Retail Trade 13108.
## 6 1990 Jun Retail Trade 13183.
## 7 1990 Jul Retail Trade 13170.
## 8 1990 Aug Retail Trade 13160.
## 9 1990 Sep Retail Trade 13113.
```

US Retail Employment

```
us_retail_employment |>  
  autoplot(Employed) +  
  labs(y = "Persons (thousands)", title = "Total employment in US retail")
```



US Retail Employment

```
us_retail_employment |>  
  model(stl = STL(Employed))
```

```
## # A mable: 1 x 1  
##      stl  
##    <model>  
## 1    <STL>
```



US Retail Employment

```
dcmp <- us_retail_employment |>
  model(stl = STL(Employed))
components(dcmp)
```

```
## # A dable: 357 x 7 [1M]
## # Key:      .model [1]
## # :        Employed = trend + season_year + remainder
##   .model      Month Employed  trend season_year remainder season_adjust
##   <chr>       <mth>    <dbl>  <dbl>      <dbl>      <dbl>      <dbl>
## 1 stl        1990 Jan    13256. 13288.    -33.0      0.836     13289.
## 2 stl        1990 Feb    12966. 13269.   -258.     -44.6     13224.
## 3 stl        1990 Mar    12938. 13250.   -290.     -22.1     13228.
## 4 stl        1990 Apr    13012. 13231.   -220.      1.05     13232.
## 5 stl        1990 May    13108. 13211.   -114.     11.3     13223.
## 6 stl        1990 Jun    13183. 13192.   -24.3     15.5     13207.
## 7 stl        1990 Jul    13170. 13172.   -23.2     21.6     13193. 8
## 8 stl        1990 Aug    13168. 13151.    -17.0     17.0     13168.
```


US Retail Employment

```
components(dcmp) |> autoplot()
```




US Retail Employment

```
us_retail_employment |>  
  autoplot(Employed, color = "gray") +  
  autolayer(components(dcmp), trend, color = "#D55E00") +  
  labs(y = "Persons (thousands)", title = "Total employment in US retail")
```



US Retail Employment

```
components(dcmp) |> gg_subseries(season_year)
```



Seasonal adjustment

- Useful by-product of decomposition: an easy way to calculate seasonally adjusted data.
- Additive decomposition: seasonally adjusted data given by


$$y_t - S_t = T_t + R_t$$

- Multiplicative decomposition: seasonally adjusted data given by

$$y_t/S_t = T_t \times R_t$$

US Retail Employment

```
us_retail_employment |>  
  autoplot(Employed, color = "gray") +  
  autolayer(components(dcmp), season_adjust, color = "#0072B2") +  
  labs(y = "Persons (thousands)", title = "Total employment in US retail")
```



Seasonal adjustment

- We use estimates of S based on past values to seasonally adjust a current value.
- Seasonally adjusted series reflect **remainders** as well as **trend**. Therefore they are not “smooth” and “downturns” or “upturns” can be misleading.
- It is better to use the trend-cycle component to look for turning points.