

Appendix A — Sample SalesReq payload (POST /invoices)

Reference: UJX-TIS-KRA-ARCH-2026-001 **Applies to:** UjenziXform TIS → KRA eTIMS (upon sandbox assignment) **Source in codebase:** `buildEtimsInvoiceBodyFromPurchaseOrder()` in `src/lib/etims/purchaseOrderEtims.ts`

All PINs, names, and item codes below are **anonymised illustrations** for KRA architecture review.

A.1 HTTP call (via etims-proxy)

Item	Value
Method	POST
Path	invoices
Upstream (after sandbox assignment)	https://etims-api-sbx.kra.go.ke/.../invoices
Auth	HTTP Basic (KRA-issued sandbox credentials in Edge secrets)
Content-Type	application/json

Proxy invocation (browser → Edge):

```
{
  "method": "POST",
  "path": "invoices",
  "body": { "... SalesReq – see A.2 ..." }
}
```

A.2 Sample sales invoice body (receipt type S)

Built from a UjenziXform PO with two construction-material lines (cement bags + steel bars). Full JSON: [APPE NDIX SAMPLE SALESREQ.json](#) .

```
{
  "traderInvoiceNo": "PO-2026-004821",
  "totalAmount": 48750.0,
  "paymentType": "01",
  "salesTypeCode": "N",
  "receiptTypeCode": "S",
  "salesStatusCode": "01",
  "salesDate": "20260603143000",
  "currency": "KES",
  "exchangeRate": 1,
  "salesItems": [
    {
      "itemCode": "KE2BSG0000123",
      "taxCode": "B",
      "qty": 50,
      "unitPrice": 750.0,
      "amount": 37500.0,
      "discountAmount": 0
    },
    {
      "itemCode": "KE2MTL0000456",
      "taxCode": "B",
      "qty": 25,
      "unitPrice": 450.0,
      "amount": 11250.0,
      "discountAmount": 0
    }
  ],
  "customerPin": "P000000000A",
  "customerName": "Example Builders Ltd",
  "traderTin": "P000000000B",
  "traderName": "Example Hardware Supplies Ltd"
}
```

Field notes

Field	UjenziXform source
traderInvoiceNo	purchase_orders.po_number
traderTin / sellerPin	suppliers.kra_pin (issuing vendor)
traderName	suppliers.legal_business_name
customerPin	profiles.kra_pin (buyer)
customerName	Buyer billing / company name from profile
salesItems[].itemCode	PO line or catalog etims_item_code
salesDate	Generated at submit (yyyyMMddHHmmss)
receiptTypeCode	S = sale

TIS may also emit duplicate snake_case keys (trader_tin , item_code) for integrator deserializers — see full JSON file.

A.3 Sample credit note body (receipt type R)

Same endpoint; references original sale:

```
{
  "traderInvoiceNo": "PO-2026-004821-CN1",
  "traderOrgInvoiceNo": "PO-2026-004821",
  "totalAmount": 48750.0,
  "paymentType": "01",
  "salesTypeCode": "N",
  "receiptTypeCode": "R",
  "salesStatusCode": "01",
  "salesDate": "20260604100000",
  "currency": "KES",
  "exchangeRate": 1,
  "salesItems": [ "... " ],
  "customerPin": "P000000000A",
  "customerName": "Example Builders Ltd",
  "traderTin": "P000000000B",
  "traderName": "Example Hardware Supplies Ltd"
}
```

Requires prior successful sale on the PO (etims_validated_at , etims_trader_invoice_no).

A.4 Illustrative success response (shape may vary per KRA spec)

Stored on purchase_orders.etims_response and used for fiscal receipt UI:

```
{
  "traderInvoiceNo": "PO-2026-004821",
  "invoiceVerificationUrl": "https://etims.kra.go.ke/common/link/etims/receipt/...",
  "scuInvoiceNo": "...",
  "receiptSignature": "...",
  "internalData": "..."
}
```

Exact field names depend on KRA sandbox response schema. TIS extracts verification URL and trader reference via `pickEtimsPersistFields()`.

A.5 Mapping from purchase order (before POST)

PO / catalog field	SalesReq field
<code>po_number</code>	<code>traderInvoiceNo</code>
<code>total_amount</code>	<code>totalAmount</code> (reconciled to lines)
<code>items[].quantity</code>	<code>salesItems[].qty</code>
<code>items[].unit_price</code>	<code>salesItems[].unitPrice</code>
<code>items[].etims_item_code</code>	<code>salesItems[].itemCode</code>
<code>items[].tax_code</code>	<code>salesItems[].taxCode</code>
Supplier row	<code>traderTin</code> , <code>traderName</code>
Buyer profile	<code>customerPin</code> , <code>customerName</code>

If any line lacks `etims_item_code`, TIS **blocks** POST and records `etims_error` on the PO.