

Lead & Form Automation Hub

Mock RFP Response — github.com/him-agni/lead-form-automation-hub

Written as a practice exercise: technical answers a Solutions Engineer would give during a buyer evaluation, based on the architecture actually implemented in this project.

Q: How does the platform verify that incoming form submissions from Tally are actually from Tally, and not a spoofed request?

A: Each inbound Tally webhook is validated against an HMAC-SHA256 signature using a constant-time comparison before any downstream processing happens. Requests that fail signature verification are rejected immediately, so a fake submission can't get injected into your CRM or your team's alert channel.

Q: If one of our destinations — say Discord — is down or rate-limited, does that also delay the submission from reaching Airtable and Google Sheets?

A: No. Each destination is handled independently with its own retry loop and exponential backoff. If Discord is down, only Discord is retried — the Airtable record and Google Sheets row still land in real time, so a vendor issue on one channel never blocks the other channels.

Q: Tally retries webhooks if it thinks the initial delivery timed out. How do you prevent that from creating duplicate leads in our CRM?

A: Every submission is deduplicated by the Tally submission ID, so a retried delivery updates the existing submission record rather than creating a duplicate Airtable row, duplicate Sheets row, or duplicate Discord alert.

Q: Can we evaluate the platform end-to-end without connecting our live Tally form or exposing our local environment through a tunnel?

A: Yes. A 'Fire Test Submission' control in the dashboard sends a synthetic submission through the real fanout pipeline — the same code path that handles a live Tally webhook — so the whole flow can be demoed end-to-end without a live form or an ngrok tunnel.

Q: What visibility does our team get into what actually happened with each submission across our destinations?

A: A live dashboard shows every submission with its per-destination status: Airtable, Discord, and Google Sheets each report success, failure, or retry state independently. If a lead didn't reach Discord, an ops user can see that specifically without opening a ticket.

Q: How is authentication with Google Sheets handled, and do we need to give the platform access to a user's personal Google account?

A: Google Sheets uses a dedicated service account, not a user account, so access can be scoped to a single spreadsheet and revoked cleanly at any time. There's a documented setup guide for creating the service account, granting sheet access, and rotating credentials.