ASSIGNMENT – 15

T.HimaBindhu| 2303A52050 | Batch – 38

Task Descriptor-1: (Setup Fast API Backend)
Instructions:

• Install Fas tAPI and Uvicorn.
• Use AI to generate a basic FastAPI application with one endpoint
Sample Code:

```
from fastapi import FastAPI
app = FastAPI()
@app.get("/")
def read_root():
return {"message": "Welcome to AI-powered FastAPI"}
```

Expected Output:
Running the server and accessing:
http://127.0.0.1:8000/
Response:
{"message": "Welcome to AI-powered FastAPI"}

Prompt:-
Generate a simple FastAPI application in Python.
Requirements:
- Import FastAPI
- Create FastAPI app
- Create one GET endpoint "/"
- The endpoint should return JSON message:
  {"message": "Welcome to AI-powered FastAPI"}

The code should run using uvicorn and be beginner friendly.

Output:-



Task Descriptor- 2: (API – Create and Read Items)

Instructions:

- Implement endpoints to add and retrieve products.
- Use a Python list as temporary storage.

Sample Code:

```
items = []
@app.get("/items")
def get_items():
return items
@app.post("/items")
def add_item(item: dict):
items.append(item)
return {"message": "Item created", "item": item}
```

Expected Output:

GET /items → []

POST /items with {"name":"Pen","price":20}

→ {"message":"Item created","item":{"name":"Pen","price":20}}



Task Descriptor- 3: (Update Existing Item)
Instructions:
• Use AI to generate an endpoint to update an item using its index.
Sample Code:

```
@app.put("/items/{index}")
def update_item(index: int, item: dict):
if index >= len(items):
return {"error": "Item not found"}
items[index] = item
return {"message": "Item updated", "item": item}
```

Expected Output:
PUT /items/0 with {"name":"Pencil","price":10}
→ {"message":"Item updated","item":{"name":"Pencil","price":10}}



Task Descriptor- 4: (Delete Item)
Instructions:
• Implement deletion of an item by index.
Sample Code: @app.delete("/items/{index}")
def delete_item(index: int):
if index >= len(items):
return {"error": "Item not found"}
removed = items.pop(index)
return {"message": "Item removed", "item": removed}
Expected Output:
DELETE /items/0
→ {"message":"Item removed","item":{"name":"Pencil","price":10}}



Task Descriptor -5: (Add Auto-Generated Documentation)
Instructions:
• Use AI to add inline comments and docstrings for all endpoints.
• Optionally, integrate Swagger / Flask-RESTX to auto-generate API documentation.
Sample Code:

```
@app.route('/items', methods=['GET'])
def get_items():
"""

GET /items
Returns a list of all items in the store.
"""
return jsonify(items)
```

Expected Output:
• Clear documentation for all endpoints, e.g., via /docs if using Swagger.
• Students should be able to see endpoint description, methods, and sample payloads.


Items API
1.0.0
OAS 3.0
Simple CRUD API for managing items
Servers
http://localhost:3000
default
GET /items Get all items
POST /items Create a new item
PUT /items/{index} Update an item
DELETE /items/{index} Delete an item
11:43 PM
3/14/26