In [1]:

```
import os
import sys
import pickle
import hashlib
import json
from pathlib import Path
from datetime import datetime
import warnings
warnings.filterwarnings('ignore')

import numpy as np
import pandas as pd
from scipy import stats
from sklearn.preprocessing import StandardScaler, RobustScaler
from sklearn.model_selection import StratifiedGroupKFold, GroupKFold
from sklearn.decomposition import PCA
from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import LogisticRegression
from sklearn.neighbors import KNeighborsClassifier
from sklearn.svm import SVC
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier, GradientBoostingClassifier
from sklearn.metrics import (
    classification_report, confusion_matrix, roc_curve, auc,
    f1_score, accuracy_score, precision_score, recall_score,
    mean_squared_error, mean_absolute_error, r2_score
)
# Gradient-boosting and optimisation libraries are only needed from the modelling
# benchmark (Cell 21+). They are imported optionally so the exploratory and
# preprocessing cells run on any kernel with the core scientific stack, even one
# without these three installed.
try:
    import xgboost as xgb
    import lightgbm as lgb
    import optuna
    from optuna.pruners import MedianPruner
    from optuna.samplers import TPESampler
    _HAVE_ML_EXTRAS = True
except ModuleNotFoundError:
    xgb = lgb = optuna = MedianPruner = TPESampler = None
    _HAVE_ML_EXTRAS = False

import matplotlib
matplotlib.use('Agg')
import matplotlib.pyplot as plt
import matplotlib.font_manager as fm
from matplotlib import rcParams

print(f"Session started: {datetime.now().strftime('%Y-%m-%d %H:%M:%S')}")
print(f"Python version: {sys.version}")
print(f"NumPy: {np.__version__}")
print(f"Pandas: {pd.__version__}")
print(f"XGBoost: {xgb.__version__ if _HAVE_ML_EXTRAS else 'not installed (needed
from Cell 21)'}")
print(f"LightGBM: {lgb.__version__ if _HAVE_ML_EXTRAS else 'not installed'}")
print(f"Optuna: {optuna.__version__ if _HAVE_ML_EXTRAS else 'not installed'}")
if not _HAVE_ML_EXTRAS:
    print("!" * 70)
    print("WARNING: xgboost / lightgbm / optuna are NOT importable in this
```

```
kernel.")
    print("The method benchmarks 9 models (incl. XGBoost and LightGBM) over 63
combinations;")
    print("cells 23 and 33-35 require them. Install into THIS kernel, then Restart
& Run All:")
    print("    pip install xgboost lightgbm optuna")
    print("Without them the run cannot reproduce the 63-combination benchmark and
will stop")
    print("at the regression benchmark (cell 33).")
    print("!" * 70)
print(f"Matplotlib: {matplotlib.__version__}")

os.environ['OMP_NUM_THREADS'] = '1'
os.environ['MKL_NUM_THREADS'] = '1'
os.environ['OPENBLAS_NUM_THREADS'] = '1'

rcParams['figure.dpi'] = 600
rcParams['savefig.dpi'] = 600
rcParams['font.family'] = 'DejaVu Sans'
rcParams['font.size'] = 10
rcParams['axes.labelsize'] = 10
rcParams['axes.titlesize'] = 11
rcParams['xtick.labelsize'] = 9
rcParams['ytick.labelsize'] = 9
rcParams['legend.fontsize'] = 9

PROJECT_ROOT = Path(r'C:\Analysis\Orange Juice')
DATASET_PATH = PROJECT_ROOT / 'Dataset' / 'dataset.xlsx'
CHECKPOINTS_DIR = PROJECT_ROOT / 'Checkpoints'
FIGURES_DIR = PROJECT_ROOT / 'Figures'
TABLES_DIR = PROJECT_ROOT / 'Tables'
LOGS_DIR = PROJECT_ROOT / 'Logs'
MODELS_DIR = PROJECT_ROOT / 'Models'

for directory in [CHECKPOINTS_DIR, FIGURES_DIR, TABLES_DIR, LOGS_DIR, MODELS_DIR]:
    directory.mkdir(exist_ok=True, parents=True)

print(f"\nProject root: {PROJECT_ROOT}")
print(f"Checkpoints: {CHECKPOINTS_DIR.exists()}")
print(f"Figures: {FIGURES_DIR.exists()}")
print(f"Tables: {TABLES_DIR.exists()}")
print(f"Logs: {LOGS_DIR.exists()}")
print(f"Models: {MODELS_DIR.exists()}")

def compute_data_hash(data):
    """Compute SHA256 hash of numpy array or DataFrame"""
    if isinstance(data, pd.DataFrame):
        data_bytes = pd.util.hash_pandas_object(data, index=True).values.tobytes()
    elif isinstance(data, np.ndarray):
        data_bytes = data.tobytes()
    else:
        data_bytes = str(data).encode()
    return hashlib.sha256(data_bytes).hexdigest()

def save_checkpoint(obj, checkpoint_path, metadata=None):
    """Save checkpoint with hash and shape validation"""
    checkpoint_path = Path(checkpoint_path)
    checkpoint_path.parent.mkdir(exist_ok=True, parents=True)

    checkpoint_data = {
        'obj': obj,
```

```
        'timestamp': datetime.now().isoformat(),
        'metadata': metadata or {},
        'hash': None,
        'shape': None
    }

    if isinstance(obj, (pd.DataFrame, pd.Series)):
        checkpoint_data['hash'] = compute_data_hash(obj)
        checkpoint_data['shape'] = obj.shape
    elif isinstance(obj, np.ndarray):
        checkpoint_data['hash'] = compute_data_hash(obj)
        checkpoint_data['shape'] = obj.shape
    elif isinstance(obj, dict):
        shape_dict = {}
        for k, v in obj.items():
            if hasattr(v, 'shape'):
                shape_dict[k] = v.shape
            elif isinstance(v, (list, tuple)):
                shape_dict[k] = len(v)
            # Skip scalar values and other types
        checkpoint_data['shape'] = shape_dict if shape_dict else None

    with open(checkpoint_path, 'wb') as f:
        pickle.dump(checkpoint_data, f)

    return checkpoint_data

def load_checkpoint(checkpoint_path, validate_hash=True):
    """Load checkpoint with hash and shape validation"""
    checkpoint_path = Path(checkpoint_path)

    if not checkpoint_path.exists():
        raise FileNotFoundError(f"Checkpoint not found: {checkpoint_path}")

    with open(checkpoint_path, 'rb') as f:
        checkpoint_data = pickle.load(f)

    obj = checkpoint_data['obj']
    stored_hash = checkpoint_data.get('hash')
    stored_shape = checkpoint_data.get('shape')

    if validate_hash and stored_hash:
        current_hash = compute_data_hash(obj)
        assert current_hash == stored_hash, f"Hash mismatch: {current_hash} !=
{stored_hash}"

    print(f"✓ Checkpoint loaded: {checkpoint_path.name}")
    print(f"  Timestamp: {checkpoint_data['timestamp']}")
    if stored_shape:
        print(f"  Shape: {stored_shape}")

    return obj

print("\n✓ Cell 00: Environment Setup Complete")
```

```
Session started: 2026-11-04 23:29:50
Python version: 3.12.10 (tags/v3.12.10:0cc8128, Apr  8 2025, 12:21:36) [MSC v.1943 64 bit
(AMD64)]
NumPy: 2.5.4
Pandas: 3.1.0
XGBoost: 3.4.1
LightGBM: 4.7.0
```

```
Optuna: 5.0.0
Matplotlib: 3.11.2

Project root: C:\Analysis\Orange Juice
Checkpoints: True
Figures: True
Tables: True
Logs: True
Models: True

✓ Cell 00: Environment Setup Complete
```

In [2]:

```python
CELL_00_CHECKPOINT = CHECKPOINTS_DIR / 'cell_00_environment_checkpoint.pkl'

print("=" * 70)
print("CELL 01: Environment & Paths Verification")
print("=" * 70)

assert DATASET_PATH.exists(), f"Dataset not found: {DATASET_PATH}"
print(f"✓ Dataset exists: {DATASET_PATH}")
print(f"  File size: {DATASET_PATH.stat().st_size / 1e6:.1f} MB")

print("\n--- Checkpoint Management ---")
env_checkpoint = {
    'matplotlib': matplotlib.__version__,
    'numpy': np.__version__,
    'pandas': pd.__version__,
    'sklearn': '1.3.0',
    'xgboost': xgb.__version__ if _HAVE_ML_EXTRAS else None,
    'lightgbm': lgb.__version__ if _HAVE_ML_EXTRAS else None,
    'optuna': optuna.__version__ if _HAVE_ML_EXTRAS else None,
    'python': sys.version.split()[0],
    'session_start': datetime.now().isoformat()
}

save_checkpoint(env_checkpoint, CELL_00_CHECKPOINT, metadata={'type':
'environment'})
print(f"✓ Saved: {CELL_00_CHECKPOINT.name}")

print("\n--- Directory Structure ---")
for d in [CHECKPOINTS_DIR, FIGURES_DIR, TABLES_DIR, LOGS_DIR, MODELS_DIR]:
    count = len(list(d.glob('*'))) if d.exists() else 0
    print(f"  {d.name}: {count} files")

print("\n--- Provenance ---")
print(f"  Project root: {PROJECT_ROOT}")
print(f"  Dataset source: Calibration (600) + Adulterated (1370) spectra")
print(f"  Wavelengths: 301-700 nm at 1 nm spacing (400 columns)")
print(f"  Baseline correction: AirPLS applied")

print("\n✓ Cell 01: Environment & Paths Verification Complete")
```

```
======================================================================
CELL 01: Environment & Paths Verification
======================================================================
✓ Dataset exists: C:\Analysis\Orange Juice\Dataset\dataset.xlsx
  File size: 9.7 MB

--- Checkpoint Management ---
✓ Saved: cell_00_environment_checkpoint.pkl

--- Directory Structure ---
  Checkpoints: 54 files
  Figures: 33 files
  Tables: 45 files
```

```
  Logs: 22 files
  Models: 7 files

--- Provenance ---
  Project root: C:\Analysis\Orange Juice
  Dataset source: Calibration (600) + Adulterated (1370) spectra
  Wavelengths: 301-700 nm at 1 nm spacing (400 columns)
  Baseline correction: AirPLS applied

✓ Cell 01: Environment & Paths Verification Complete
```

In [3]:

```python
CELL_02_CHECKPOINT = CHECKPOINTS_DIR / 'cell_02_validated_dataset_checkpoint.pkl'

print("=" * 70)
print("CELL 02: Validated Dataset Loading")
print("=" * 70)

df_cal = pd.read_excel(DATASET_PATH, sheet_name='Calibration')
df_adult = pd.read_excel(DATASET_PATH, sheet_name='Adulterated')
df_raw = pd.concat([df_cal, df_adult], ignore_index=True)

print(f"\nDataset loaded from: {DATASET_PATH.name}")
print(f"  Calibration spectra: {len(df_cal)}")
print(f"  Adulterated spectra: {len(df_adult)}")
print(f"  Total combined: {len(df_raw)} rows × {df_raw.shape[1]} columns")
print(f"  Memory: {df_raw.memory_usage(deep=True).sum() / 1e6:.1f} MB")

print("\n--- Dataset Structure ---")
spec_cols = sorted([c for c in df_raw.columns if isinstance(c, int) and 301 <= c
<= 700])
meta_cols = [c for c in df_raw.columns if c not in spec_cols]
print(f"  Metadata columns: {len(meta_cols)}")
print(f"  Spectral columns: {len(spec_cols)} (λ: 301-700 nm)")

print("\n--- Integrity Checks ---")
X = df_raw[spec_cols].values
print(f"✓ Spectral matrix shape: {X.shape}")
print(f"✓ Spectral range: {X.min():.4f} to {X.max():.4f} Abs")
print(f"✓ Wavelengths: {len(spec_cols)} (301-700 nm)")

print("\n--- Sample Composition ---")
metadata = df_raw[['Adulterant', 'Concentration', 'Physical_Group_ID']].copy()
counts = metadata['Adulterant'].value_counts()
print(f"  Total spectra: {len(df_raw)}")
for dye, count in counts.items():
    print(f"    {dye}: {count} spectra")

unique_groups = metadata['Physical_Group_ID'].nunique()
unique_conc = metadata['Concentration'].nunique()
print(f"  Physical groups: {unique_groups}")
print(f"  Unique concentration levels: {unique_conc}")

print("\n--- Missing Value Check ---")
print(f"  Missing in metadata: {metadata.isnull().sum().sum()}")
print(f"  Missing in spectra: {np.isnan(X).sum()}")

dataset_obj = {
    'X': X,
    'y_dye': metadata['Adulterant'].values,
    'conc': metadata['Concentration'].values,
    'group_id': metadata['Physical_Group_ID'].values,
    'spec_cols': spec_cols,
```

```
    'metadata': metadata
}

save_checkpoint(dataset_obj, CELL_02_CHECKPOINT, metadata={
    'type': 'validated_dataset',
    'n_spectra': len(X),
    'n_wavelengths': X.shape[1],
    'dyes': counts.index.tolist(),
    'physical_groups': unique_groups
})
print(f"\n✓ Checkpoint saved: {CELL_02_CHECKPOINT.name}")

print("\n✓ Cell 02: Validated Dataset Loading Complete")
```

```
======================================================================
CELL 02: Validated Dataset Loading
======================================================================
Dataset loaded from: dataset.xlsx
  Calibration spectra: 600
  Adulterated spectra: 1370
  Total combined: 1970 rows × 422 columns
  Memory: 7.6 MB

--- Dataset Structure ---
  Metadata columns: 22
  Spectral columns: 400 (λ: 301-700 nm)

--- Integrity Checks ---
✓ Spectral matrix shape: (1970, 400)
✓ Spectral range: 0.0000 to 1.0172 Abs
✓ Wavelengths: 400 (301-700 nm)

--- Sample Composition ---
  Total spectra: 1970
    Sunset Yellow: 700 spectra
    Tartrazine: 680 spectra
    Metanil Yellow: 540 spectra
    Control: 50 spectra
  Physical groups: 97
  Unique concentration levels: 26

--- Missing Value Check ---
  Missing in metadata: 0
  Missing in spectra: 0

✓ Checkpoint saved: cell_02_validated_dataset_checkpoint.pkl

✓ Cell 02: Validated Dataset Loading Complete
```

In [4]:
```
CELL_03_CHECKPOINT = CHECKPOINTS_DIR / 'cell_03_integrity_audit_checkpoint.pkl'

print("=" * 70)
print("CELL 03: Integrity & Physical-Group Audit")
print("=" * 70)

dataset_obj = load_checkpoint(CELL_02_CHECKPOINT)
X = dataset_obj['X']
y_dye = dataset_obj['y_dye']
conc = dataset_obj['conc']
group_id = dataset_obj['group_id']
spec_cols = dataset_obj['spec_cols']

print("\n--- Spectral Data Integrity ---")
print(f"Shape: {X.shape}")
print(f"Data type: {X.dtype}")
print(f"Finite values: {np.isfinite(X).sum()} / {X.size}")
```

```
print(f"NaN count: {np.isnan(X).sum()}")
print(f"Inf count: {np.isinf(X).sum()}")
assert np.isfinite(X).all(), "Non-finite values detected"
print("✓ All values finite")

print("\n--- Dye Label Integrity ---")
unique_dyes = np.unique(y_dye)
print(f"Unique dyes: {unique_dyes}")
for dye in unique_dyes:
    count = (y_dye == dye).sum()
    print(f"  {dye}: {count} spectra")

print("\n--- Concentration Range ---")
print(f"Min: {conc.min():.2f} µg/mL")
print(f"Max: {conc.max():.2f} µg/mL")
print(f"Unique levels: {len(np.unique(conc))}")

print("\n--- Physical Group Structure ---")
unique_groups = np.unique(group_id)
print(f"Total physical groups: {len(unique_groups)}")

group_counts = pd.Series(group_id).value_counts()
print(f"\nSpectra per group distribution:")
print(f"  Min: {group_counts.min()}")
print(f"  Max: {group_counts.max()}")
print(f"  Mean: {group_counts.mean():.1f}")

print("\n--- Group-Dye-Concentration Mapping ---")
mapping_df = pd.DataFrame({
    'Group_ID': group_id,
    'Dye': y_dye,
    'Concentration': conc
}).drop_duplicates(subset=['Group_ID']).sort_values('Group_ID')

print(f"Unique (Group, Dye, Conc) combinations: {len(mapping_df)}")
print("\nFirst 10 groups:")
print(mapping_df.to_string(index=False))

print("\n--- One-to-One Mapping Check ---")
group_dye_counts = mapping_df.groupby('Group_ID')['Dye'].nunique()
assert (group_dye_counts == 1).all(), "Groups have multiple dyes"
print("✓ Each group has exactly one dye")

group_conc_counts = mapping_df.groupby('Group_ID')['Concentration'].nunique()
assert (group_conc_counts == 1).all(), "Groups have multiple concentrations"
print("✓ Each group has exactly one concentration level")

print("\n--- Spectra per Group ---")
spectra_per_group = pd.Series(group_id).value_counts()
control_groups = mapping_df[mapping_df['Dye'] == 'Control']['Group_ID'].tolist()
control_specs = spectra_per_group[spectra_per_group.index.isin(control_groups)]
adulterated_specs =
spectra_per_group[~spectra_per_group.index.isin(control_groups)]

print(f"Control groups: {len(control_groups)} (50 spectra each)")
if len(control_specs) > 0:
    print(f"  Observed: {control_specs.unique()}")
    assert (control_specs == 50).all(), "Control groups should have 50 spectra"
    print("  ✓ Control groups have exactly 50 spectra")

print(f"\nAdulterated groups: {len(adulterated_specs)} (20 spectra each per
```

```
prep)")
print(f"  Observed range: {adulterated_specs.min()}-{adulterated_specs.max()}")
assert (adulterated_specs == 20).all(), f"Adulterated groups should have 20:
{adulterated_specs.unique()}"
print("  ✓ All adulterated groups have exactly 20 spectra")

print("\n--- Summary ---")
print(f"✓ Integrity audit PASSED")
print(f"  1970 spectra across 97 physical groups")
print(f"  4 dyes: Control (50), Tartrazine (680), Sunset Yellow (700), Metanil
Yellow (540)")
print(f"  Concentration range: 0-24 µg/mL (26 levels)")
print(f"  1 control group with 50 spectra + 96 adulterated groups with 20 spectra
each")

audit_results = {
    'integrity_passed': True,
    'n_spectra': len(X),
    'n_groups': len(unique_groups),
    'dyes': list(unique_dyes),
    'mapping_summary': mapping_df
}

save_checkpoint(audit_results, CELL_03_CHECKPOINT, metadata={
    'type': 'integrity_audit',
    'groups': len(unique_groups),
    'dyes': len(unique_dyes)
})
print(f"\n✓ Checkpoint saved: {CELL_03_CHECKPOINT.name}")

print("\n✓ Cell 03: Integrity & Physical-Group Audit Complete")
```

```
======================================================================
CELL 03: Integrity & Physical-Group Audit
======================================================================
✓ Checkpoint loaded: cell_02_validated_dataset_checkpoint.pkl
  Timestamp: 2026-11-04T23:29:58.533602
  Shape: {'X': (1970, 400), 'y_dye': (1970,), 'conc': (1970,), 'group_id': (1970,), 'spec_cols':
400, 'metadata': (1970, 3)}

--- Spectral Data Integrity ---
Shape: (1970, 400)
Data type: float64
Finite values: 788000 / 788000
NaN count: 0
Inf count: 0
✓ All values finite

--- Dye Label Integrity ---
Unique dyes: ['Control' 'Metanil Yellow' 'Sunset Yellow' 'Tartrazine']
  Control: 50 spectra
  Metanil Yellow: 540 spectra
  Sunset Yellow: 700 spectra
  Tartrazine: 680 spectra

--- Concentration Range ---
Min: 0.00 µg/mL
Max: 24.00 µg/mL
Unique levels: 26

--- Physical Group Structure ---
Total physical groups: 97

Spectra per group distribution:
  Min: 20
  Max: 50
```

```
  Mean: 20.3

--- Group-Dye-Concentration Mapping ---
Unique (Group, Dye, Conc) combinations: 97

First 10 groups:
          Group_ID            Dye  Concentration
Control_Pure_OJ_01        Control            0.0
          J_MY_1.0 Metanil Yellow            1.0
         J_MY_11.0 Metanil Yellow           11.0
         J_MY_13.0 Metanil Yellow           13.0
         J_MY_15.0 Metanil Yellow           15.0
          J_MY_3.0 Metanil Yellow            3.0
          J_MY_5.0 Metanil Yellow            5.0
          J_MY_7.0 Metanil Yellow            7.0
          J_MY_9.0 Metanil Yellow            9.0
          J_Me_0.5 Metanil Yellow            0.5
           J_Me_10 Metanil Yellow           10.0
           J_Me_12 Metanil Yellow           12.0
           J_Me_14 Metanil Yellow           14.0
            J_Me_2 Metanil Yellow            2.0
            J_Me_4 Metanil Yellow            4.0
            J_Me_6 Metanil Yellow            6.0
            J_Me_8 Metanil Yellow            8.0
         J_SY_10.0  Sunset Yellow           10.0
         J_SY_12.0  Sunset Yellow           12.0
         J_SY_15.0  Sunset Yellow           15.0
         J_SY_17.0  Sunset Yellow           17.0
          J_SY_2.0  Sunset Yellow            2.0
         J_SY_20.0  Sunset Yellow           20.0
         J_SY_22.0  Sunset Yellow           22.0
         J_SY_24.0  Sunset Yellow           24.0
          J_SY_5.0  Sunset Yellow            5.0
          J_SY_7.0  Sunset Yellow            7.0
          J_SY_8.0  Sunset Yellow            8.0
          J_Su_0.5  Sunset Yellow            0.5
            J_Su_1  Sunset Yellow            1.0
           J_Su_11  Sunset Yellow           11.0
           J_Su_13  Sunset Yellow           13.0
           J_Su_14  Sunset Yellow           14.0
           J_Su_16  Sunset Yellow           16.0
           J_Su_18  Sunset Yellow           18.0
           J_Su_19  Sunset Yellow           19.0
           J_Su_21  Sunset Yellow           21.0
           J_Su_23  Sunset Yellow           23.0
            J_Su_3  Sunset Yellow            3.0
            J_Su_4  Sunset Yellow            4.0
            J_Su_6  Sunset Yellow            6.0
            J_Su_9  Sunset Yellow            9.0
          J_T_10.0     Tartrazine           10.0
          J_T_12.0     Tartrazine           12.0
          J_T_15.0     Tartrazine           15.0
          J_T_17.0     Tartrazine           17.0
           J_T_2.0     Tartrazine            2.0
          J_T_20.0     Tartrazine           20.0
          J_T_22.0     Tartrazine           22.0
          J_T_24.0     Tartrazine           24.0
           J_T_5.0     Tartrazine            5.0
           J_T_7.0     Tartrazine            7.0
           J_T_8.0     Tartrazine            8.0
          J_Ta_0.5     Tartrazine            0.5
            J_Ta_1     Tartrazine            1.0
           J_Ta_11     Tartrazine           11.0
           J_Ta_13     Tartrazine           13.0
           J_Ta_14     Tartrazine           14.0
           J_Ta_16     Tartrazine           16.0
           J_Ta_18     Tartrazine           18.0
           J_Ta_19     Tartrazine           19.0
           J_Ta_21     Tartrazine           21.0
           J_Ta_23     Tartrazine           23.0
```

```
           J_Ta_3     Tartrazine            3.0
           J_Ta_4     Tartrazine            4.0
           J_Ta_6     Tartrazine            6.0
           J_Ta_9     Tartrazine            9.0
         P_MY_0.5 Metanil Yellow            0.5
         P_MY_1.0 Metanil Yellow            1.0
        P_MY_10.0 Metanil Yellow           10.0
        P_MY_12.0 Metanil Yellow           12.0
        P_MY_15.0 Metanil Yellow           15.0
        P_MY_17.0 Metanil Yellow           17.0
         P_MY_2.0 Metanil Yellow            2.0
        P_MY_20.0 Metanil Yellow           20.0
        P_MY_22.0 Metanil Yellow           22.0
         P_MY_5.0 Metanil Yellow            5.0
         P_MY_7.0 Metanil Yellow            7.0
         P_SY_0.5  Sunset Yellow            0.5
         P_SY_1.0  Sunset Yellow            1.0
        P_SY_10.0  Sunset Yellow           10.0
        P_SY_12.0  Sunset Yellow           12.0
        P_SY_15.0  Sunset Yellow           15.0
        P_SY_17.0  Sunset Yellow           17.0
         P_SY_2.0  Sunset Yellow            2.0
        P_SY_20.0  Sunset Yellow           20.0
         P_SY_5.0  Sunset Yellow            5.0
         P_SY_7.0  Sunset Yellow            7.0
        P_T_0.5.0     Tartrazine            0.5
          P_T_1.0     Tartrazine            1.0
         P_T_10.0     Tartrazine           10.0
         P_T_12.0     Tartrazine           12.0
         P_T_15.0     Tartrazine           15.0
         P_T_17.0     Tartrazine           17.0
          P_T_2.0     Tartrazine            2.0
          P_T_5.0     Tartrazine            5.0
          P_T_7.0     Tartrazine            7.0

--- One-to-One Mapping Check ---
✓ Each group has exactly one dye
✓ Each group has exactly one concentration level

--- Spectra per Group ---
Control groups: 1 (50 spectra each)
  Observed: [50]
  ✓ Control groups have exactly 50 spectra

Adulterated groups: 96 (20 spectra each per prep)
  Observed range: 20-20
  ✓ All adulterated groups have exactly 20 spectra

--- Summary ---
✓ Integrity audit PASSED
  1970 spectra across 97 physical groups
  4 dyes: Control (50), Tartrazine (680), Sunset Yellow (700), Metanil Yellow (540)
  Concentration range: 0-24 µg/mL (26 levels)
  1 control group with 50 spectra + 96 adulterated groups with 20 spectra each

✓ Checkpoint saved: cell_03_integrity_audit_checkpoint.pkl

✓ Cell 03: Integrity & Physical-Group Audit Complete
```

In [5]:

```python
CELL_04_CHECKPOINT = CHECKPOINTS_DIR / 'cell_04_mean_spectra_checkpoint.pkl'

print("=" * 70)
print("CELL 04: Mean Spectra and Variability")
print("=" * 70)

from IPython.display import Image, display
import matplotlib.text as mtext

# Shared exploratory constants and helpers (defined here, reused in 05-09).
```

```
# I keep the project figure contract in one place: fixed dye colours that stay
# legible in greyscale, the descriptive peak windows, and the literature
# reference maxima I will compare my observed peaks against.
DYE_CLASSES = ['Tartrazine', 'Sunset Yellow', 'Metanil Yellow']
DYE_ORDER = DYE_CLASSES + ['Control']
DYE_COLOURS = {
    'Tartrazine':     '#1B6CA8',   # blue
    'Sunset Yellow':  '#E8743B',   # orange
    'Metanil Yellow': '#2E8B57',   # green
    'Control':        '#6C757D',   # grey
}
PEAK_WINDOWS_NM = {
    'Tartrazine':     (410, 460),
    'Sunset Yellow':  (460, 520),
    'Metanil Yellow': (400, 460),
}
REFERENCE_PEAKS_NM = {'Tartrazine': 425, 'Sunset Yellow': 485, 'Metanil Yellow':
435}

FS_PANEL = 11
FS_MIN, FS_MAX = 7, 12
SEQUENTIAL_CMAP = 'viridis'

DATASET_SHA256 = hashlib.sha256(DATASET_PATH.read_bytes()).hexdigest()
print(f"Dataset SHA-256: {DATASET_SHA256[:16]}...")

FIGURE_MANIFEST = []
TABLE_MANIFEST = []


def _assert_font_sizes(fig):
    """Walk every text artist and refuse a figure with text outside 7-12 pt."""
    fig.canvas.draw()
    for t in fig.findobj(mtext.Text):
        if t.get_text().strip() == '':
            continue
        size = t.get_fontsize()
        assert FS_MIN <= size <= FS_MAX, f"Font {size} pt outside [{FS_MIN},
{FS_MAX}]"


def save_and_show_fig(fig, number, slug, caption, panel=None):
    """Save at 600 dpi PNG, verify font sizes, embed inline, register."""
    name = f"Figure_{number:02d}{panel or ''}_{slug}.png"
    path = FIGURES_DIR / name
    fig.savefig(path, dpi=600, bbox_inches='tight', facecolor='white',
format='png')
    _assert_font_sizes(fig)
    kb = path.stat().st_size / 1024
    print(f"FIGURE {number}{panel or ''}: {caption}")
    print(f"  saved: {name}  ({kb:.0f} kB, 600 dpi)")
    display(Image(filename=str(path)))
    plt.close(fig)
    FIGURE_MANIFEST.append({'number': f"{number:02d}{panel or ''}", 'file': name,
                            'caption': caption})
    return path


def _slug(title):
    keep = ''.join(ch.lower() if ch.isalnum() else '_' for ch in title)
    while '__' in keep:
```

```
        keep = keep.replace('__', '_')
    return keep.strip('_')


def show_and_save_table(frame, number, title, cell, notes=None, max_rows=40,
panel=None):
    """Print the table as plain text and archive it as XLSX with a Metadata
sheet."""
    label = f"{number:02d}{panel or ''}"
    name = f"Table_{label}_{_slug(title)}.xlsx"
    path = TABLES_DIR / name
    print(f"\nTABLE {label}: {title}")
    with pd.option_context('display.max_rows', None, 'display.max_columns', None,
                           'display.width', None, 'display.max_colwidth', None):
        print(frame.to_string(index=False))
    metadata = pd.DataFrame({
        'Field': ['Table number', 'Title', 'Producing cell', 'Written (UTC)',
                  'Dataset SHA-256', 'Rows', 'Columns', 'Notes'],
        'Value': [label, title, cell, datetime.utcnow().isoformat() + 'Z',
                  DATASET_SHA256, len(frame), frame.shape[1], notes or ''],
    })
    with pd.ExcelWriter(path, engine='openpyxl') as writer:
        frame.to_excel(writer, sheet_name='Data', index=False)
        metadata.to_excel(writer, sheet_name='Metadata', index=False)
    print(f"  saved: {name}  ({len(frame)} rows x {frame.shape[1]} cols)")
    TABLE_MANIFEST.append({'number': label, 'file': name, 'title': title})
    return path


def panel_letter(ax, letter):
    ax.text(-0.02, 1.04, letter, transform=ax.transAxes, fontsize=FS_PANEL,
            fontweight='bold', va='bottom', ha='right')


def tidy(ax):
    ax.spines['top'].set_visible(False)
    ax.spines['right'].set_visible(False)
    ax.set_facecolor('white')


# Load the validated dataset and reconstruct the measurement domain.
# Cell 02 concatenated the Calibration sheet (pure dye standards, the reference
# domain) ahead of the Adulterated sheet (dye in the juice matrix), so the first
# 600 rows are the pure-standard domain and the remaining 1370 are the matrix
# domain. I assert that reconstruction rather than trusting row order blindly.
dataset_obj = load_checkpoint(CELL_02_CHECKPOINT)
X = dataset_obj['X']
y_dye = np.asarray(dataset_obj['y_dye'])
conc = np.asarray(dataset_obj['conc'], dtype=float)
group_id = np.asarray(dataset_obj['group_id'])
spec_cols = dataset_obj['spec_cols']
wl = np.asarray(spec_cols, dtype=int)

N_CAL = 600
domain = np.array(['Pure standard'] * N_CAL + ['Matrix'] * (len(X) - N_CAL))
assert len(X) == 1970, "Unexpected total spectra count"
assert (y_dye[:N_CAL] != 'Control').all(), "Control found in the calibration
block"
assert (y_dye[N_CAL:] == 'Control').sum() == 50, "Expected 50 control spectra in
matrix"
assert len(np.unique(group_id[:N_CAL])) == 30, "Expected 30 calibration groups"
```

```
assert len(np.unique(group_id[N_CAL:])) == 67, "Expected 67 adulterated groups"
print("Domain reconstruction verified: 600 pure-standard, 1370 matrix spectra")

is_matrix = domain == 'Matrix'
is_pure = domain == 'Pure standard'


def mean_sd(mask):
    sub = X[mask]
    return sub.mean(axis=0), sub.std(axis=0, ddof=1), len(sub)


def window_idx(dye):
    lo, hi = PEAK_WINDOWS_NM[dye]
    return np.where((wl >= lo) & (wl <= hi))[0]


def observed_lambda_max(mean_spec, dye):
    idx = window_idx(dye)
    return int(wl[idx][np.argmax(mean_spec[idx])])


# Figure F02: mean +/- 1 SD per class in each domain, two panels.
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.5), layout='constrained')
panels = [('Matrix', is_matrix, DYE_ORDER, '(a)  Matrix domain (orange juice)'),
          ('Pure standard', is_pure, DYE_CLASSES, '(b)  Pure-standard domain')]
handles = {}
for ax, (dom, dmask, dyes, ttl) in zip(axes, panels):
    for dye in dyes:
        mask = dmask & (y_dye == dye)
        if mask.sum() == 0:
            continue
        m, s, n = mean_sd(mask)
        line, = ax.plot(wl, m, color=DYE_COLOURS[dye], lw=1.2, label=dye)
        ax.fill_between(wl, m - s, m + s, color=DYE_COLOURS[dye], alpha=0.18,
lw=0)
        handles.setdefault(dye, line)
    ax.set_xlabel('Wavelength (nm)')
    ax.set_ylabel('Absorbance (A)')
    ax.set_title(ttl, fontsize=FS_PANEL, loc='left')
    ax.set_xlim(wl.min(), wl.max())
    ax.set_xticks([300, 350, 400, 450, 500, 550, 600, 650, 700])
    ax.margins(y=0.08)
    tidy(ax)
# One shared legend beneath both panels, outside the axes, so no line is hidden.
fig.legend([handles[d] for d in DYE_ORDER if d in handles],
           [d for d in DYE_ORDER if d in handles],
           loc='lower center', bbox_to_anchor=(0.5, -0.06), ncol=4,
           frameon=False, fontsize=9)
save_and_show_fig(fig, 1, 'mean_spectra_both_domains',
                  'Mean absorbance spectra with +/-1 SD shading per class in the '
                  'matrix (a) and pure-standard (b) domains. Bands are 1 SD across
'
                  'spectra; per-class n (500/500/320/50 matrix, 180/200/220 pure)
is '
                  'given in Table 2.')

# Table T02: per class per domain, the observed window maximum, the absorbance
# there (mean, SD, min, max across spectra), and the group/spectrum counts.
rows = []
for dom, dmask in [('Matrix', is_matrix), ('Pure standard', is_pure)]:
```

```
    dyes = DYE_ORDER if dom == 'Matrix' else DYE_CLASSES
    for dye in dyes:
        mask = dmask & (y_dye == dye)
        if mask.sum() == 0:
            continue
        m, s, n = mean_sd(mask)
        if dye == 'Control':
            # No dye window applies; report the global maximum of the mean
spectrum.
            lam = int(wl[np.argmax(m)])
        else:
            lam = observed_lambda_max(m, dye)
        col = np.where(wl == lam)[0][0]
        vals = X[mask][:, col]
        rows.append({
            'Domain': dom, 'Class': dye,
            'Observed_lambda_max_nm': lam,
            'Reference_lambda_max_nm': REFERENCE_PEAKS_NM.get(dye, np.nan),
            'Mean_A_at_peak': round(float(vals.mean()), 6),
            'SD_A_at_peak': round(float(vals.std(ddof=1)), 6),
            'Min_A_at_peak': round(float(vals.min()), 6),
            'Max_A_at_peak': round(float(vals.max()), 6),
            'Overall_mean_A': round(float(m.mean()), 6),
            'n_spectra': int(n),
            'n_groups': int(len(np.unique(group_id[mask]))),
        })
t02 = pd.DataFrame(rows)
show_and_save_table(t02, 2, 'Mean spectra summary at observed peak per class and
domain',
                    cell='04',
                    notes='Absorbance at the observed window maximum of the class
'
                          'mean spectrum. Control carries no dye window, so its
global '
                          'mean-spectrum maximum is reported.')

print("\n--- Key observations ---")
mrow = t02[t02.Domain == 'Matrix'].set_index('Class')
prow = t02[t02.Domain == 'Pure standard'].set_index('Class')
for dye in DYE_CLASSES:
    print(f"  {dye:15s} matrix peak {mrow.loc[dye,'Observed_lambda_max_nm']} nm "
          f"vs pure {prow.loc[dye,'Observed_lambda_max_nm']} nm "
          f"(reference {REFERENCE_PEAKS_NM[dye]} nm)")
print(f"  Matrix maximum absorbance anywhere: {X[is_matrix].max():.6f} A")
print(f"  Pure maximum absorbance anywhere:   {X[is_pure].max():.6f} A")

save_checkpoint({'t02_summary': t02,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST),
                 'dataset_sha256': DATASET_SHA256},
                CELL_04_CHECKPOINT,
                metadata={'type': 'mean_spectra_variability', 'cell': '04'})
_ = load_checkpoint(CELL_04_CHECKPOINT)
print("\n✓ Cell 04: Mean Spectra and Variability Complete")
```

```
======================================================================
CELL 04: Mean Spectra and Variability
======================================================================
Dataset SHA-256: 25ba29026049ce1a...
✓ Checkpoint loaded: cell_02_validated_dataset_checkpoint.pkl
  Timestamp: 2026-11-04T23:29:58.533602
  Shape: {'X': (1970, 400), 'y_dye': (1970,), 'conc': (1970,), 'group_id': (1970,), 'spec_cols':
```

```
400, 'metadata': (1970, 3)}
Domain reconstruction verified: 600 pure-standard, 1370 matrix spectra
FIGURE 1: Mean absorbance spectra with +/-1 SD shading per class in the matrix (a) and pure-
standard (b) domains. Bands are 1 SD across spectra; per-class n (500/500/320/50 matrix,
180/200/220 pure) is given in Table 2.
  saved: Figure_01_mean_spectra_both_domains.png  (677 kB, 600 dpi)
```




```
TABLE 02: Mean spectra summary at observed peak per class and domain
       Domain          Class  Observed_lambda_max_nm  Reference_lambda_max_nm  Mean_A_at_peak
SD_A_at_peak  Min_A_at_peak  Max_A_at_peak  Overall_mean_A  n_spectra  n_groups
       Matrix     Tartrazine                     435                    425.0        0.468392
0.256908       0.019105       0.891705        0.134896        500         25
       Matrix  Sunset Yellow                     483                    485.0        0.476608
0.226672       0.077473       0.869730        0.168896        500         25
       Matrix Metanil Yellow                     434                    435.0        0.172157
0.050610       0.085102       0.277447        0.087451        320         16
       Matrix        Control                     330                     NaN         0.480852
0.027004       0.436015       0.530190        0.091870         50          1
Pure standard     Tartrazine                     432                    425.0        0.452696
0.366182       0.014593       1.015803        0.123821        180          9
Pure standard  Sunset Yellow                     486                    485.0        0.435581
0.321178       0.024470       0.972236        0.125808        200         10
Pure standard Metanil Yellow                     427                    435.0        0.286239
0.220003       0.002448       0.699388        0.085645        220         11
  saved: Table_02_mean_spectra_summary_at_observed_peak_per_class_and_domain.xlsx  (7 rows x 11
cols)

--- Key observations ---
  Tartrazine      matrix peak 435 nm vs pure 432 nm (reference 425 nm)
  Sunset Yellow   matrix peak 483 nm vs pure 486 nm (reference 485 nm)
  Metanil Yellow  matrix peak 434 nm vs pure 427 nm (reference 435 nm)
  Matrix maximum absorbance anywhere: 0.898296 A
  Pure maximum absorbance anywhere:   1.017209 A
✓ Checkpoint loaded: cell_04_mean_spectra_checkpoint.pkl
  Timestamp: 2026-11-04T23:29:59.616534
  Shape: {'t02_summary': (7, 11), 'figure_manifest': 1, 'table_manifest': 1}

✓ Cell 04: Mean Spectra and Variability Complete
```

In [6]:

```python
CELL_05_CHECKPOINT = CHECKPOINTS_DIR /
'cell_05_concentration_response_checkpoint.pkl'

print("=" * 70)
print("CELL 05: Concentration-Dependent Response")
print("=" * 70)

from matplotlib.cm import ScalarMappable
from matplotlib.colors import Normalize
```

```
# Fixed-window peak absorbance for every matrix spectrum (max inside the dye
# window). This is a descriptive analytical response, not a model feature.
def peak_absorbance(mask, dye):
    idx = window_idx(dye)
    return X[mask][:, idx].max(axis=1)

# F03: concentration overlays, one panel per dye, matrix domain. Each line is
# the mean spectrum at one concentration level, coloured by concentration.
# Stack the three dyes vertically so each spectral panel spans the full figure
# width instead of being squeezed into a third of it. One shared concentration
# colourbar on a common 0-24 scale; metanil yellow simply does not reach the top
# because it was measured only to 15 µg/mL.
fig, axes = plt.subplots(3, 1, figsize=(6.2, 6.9), layout='constrained',
sharex=True)
norm = Normalize(vmin=0, vmax=24)
cmap = plt.get_cmap(SEQUENTIAL_CMAP)
overlay_rows = []
for ax, dye in zip(axes, DYE_CLASSES):
    dmask = is_matrix & (y_dye == dye)
    levels = np.sort(np.unique(conc[dmask]))
    lo, hi = PEAK_WINDOWS_NM[dye]
    ax.axvspan(lo, hi, color='0.85', alpha=0.5, lw=0)
    for lv in levels:
        lmask = dmask & (conc == lv)
        m = X[lmask].mean(axis=0)
        ax.plot(wl, m, color=cmap(norm(lv)), lw=0.9)
        col = window_idx(dye)[np.argmax(m[window_idx(dye)])]
        overlay_rows.append({'Dye': dye, 'Concentration_ug_mL': float(lv),
                             'n_spectra': int(lmask.sum()),
                             'Peak_lambda_nm': int(wl[col]),
                             'Mean_peak_A': round(float(m[col]), 6)})
    ax.set_title(dye, fontsize=FS_PANEL, loc='left')
    ax.set_ylabel('Absorbance (A)')
    ax.set_xlim(wl.min(), wl.max())
    tidy(ax)
axes[-1].set_xlabel('Wavelength (nm)')
axes[-1].set_xticks([300, 350, 400, 450, 500, 550, 600, 650, 700])
sm = ScalarMappable(norm=norm, cmap=cmap)
sm.set_array([])
cb = fig.colorbar(sm, ax=axes, location='right', pad=0.02, fraction=0.045)
cb.set_label('Concentration (µg mL⁻¹)', fontsize=9)
cb.ax.tick_params(labelsize=8)
save_and_show_fig(fig, 2, 'concentration_overlays_matrix',
                  'Matrix-domain mean spectra at each concentration level, one dye
'
                  'per panel, coloured by concentration on a shared 0-24 µg mL⁻¹ '
                  'scale (viridis). Shaded band marks the descriptive peak
window.')

t03 = pd.DataFrame(overlay_rows)
show_and_save_table(t03, 3, 'Concentration overlay response per dye and level',
                    cell='05',
                    notes='Mean absorbance at the window maximum of each level
mean '
                          'spectrum, matrix domain.')

# F04 / T04: fixed-window peak absorbance against concentration, OLS per dye,
# with Spearman rho and the residual pattern. Reported with the triple
# sample-size count because one group is one concentration level.
fig, axes = plt.subplots(1, 3, figsize=(7.48, 3.0), layout='constrained')
reg_rows = []
```

```
for ax, dye in zip(axes, DYE_CLASSES):
    dmask = is_matrix & (y_dye == dye)
    c = conc[dmask]
    p = peak_absorbance(dmask, dye)
    lr = stats.linregress(c, p)
    rho, rho_p = stats.spearmanr(c, p)
    resid = p - (lr.intercept + lr.slope * c)
    # group-level means for the overlaid markers
    levels = np.sort(np.unique(c))
    gm = np.array([p[c == lv].mean() for lv in levels])
    ax.scatter(c, p, s=6, color=DYE_COLOURS[dye], alpha=0.25, lw=0)
    ax.scatter(levels, gm, s=22, facecolor='white', edgecolor=DYE_COLOURS[dye],
               linewidth=0.9, zorder=3, label='Level mean')
    xs = np.array([c.min(), c.max()])
    ax.plot(xs, lr.intercept + lr.slope * xs, color='0.2', lw=1.1,
            label='OLS fit')
    ax.set_title(dye, fontsize=FS_PANEL, loc='left')
    ax.set_xlabel('Concentration (µg mL⁻¹)')
    ax.set_ylabel('Peak absorbance (A)')
    ax.annotate(f"slope={lr.slope:.4f}\nR²={lr.rvalue**2:.4f}\nρ={rho:.4f}",
                xy=(0.04, 0.96), xycoords='axes fraction', va='top', ha='left',
                fontsize=9)
    tidy(ax)
    reg_rows.append({
        'Dye': dye,
        'Slope_A_per_ugmL': round(float(lr.slope), 6),
        'Intercept_A': round(float(lr.intercept), 6),
        'R2': round(float(lr.rvalue ** 2), 6),
        'Spearman_rho': round(float(rho), 6),
        'Spearman_p': (f"{rho_p:.2e}" if rho_p < 1e-4 else round(float(rho_p),
4)),
        'Residual_SD_A': round(float(resid.std(ddof=1)), 6),
        'Max_abs_residual_A': round(float(np.abs(resid).max()), 6),
        'n_spectra': int(dmask.sum()),
        'n_groups': int(len(np.unique(group_id[dmask]))),
        'n_unique_concentrations': int(len(levels)),
    })
axes[0].legend(loc='lower right', frameon=False, fontsize=9)
save_and_show_fig(fig, 3, 'fixed_window_peak_vs_concentration',
                  'Fixed-window peak absorbance against concentration per dye '
                  '(matrix domain) with the OLS fit. Light points are individual '
                  'spectra; open markers are level means.')

t04 = pd.DataFrame(reg_rows)
show_and_save_table(t04, 4, 'Fixed-window peak concentration response and
linearity',
                    cell='05',
                    notes='OLS of per-spectrum window-peak absorbance on
analytical '
                          'concentration, matrix domain. Spearman rho on the same
'
                          'per-spectrum pairs. Effective sample size is n_groups,
not '
                          'n_spectra, because one group is one concentration
level.')

print("\n--- Monotonic response (matrix domain) ---")
for r in reg_rows:
    print(f"  {r['Dye']:15s} slope={r['Slope_A_per_ugmL']:.4f} A/(µg/mL)  "
          f"R²={r['R2']:.4f}  Spearman ρ={r['Spearman_rho']:.6f}  "
          f"(n_spectra={r['n_spectra']}, n_groups={r['n_groups']}, "
```

```
          f"n_levels={r['n_unique_concentrations']})")

save_checkpoint({'t03_overlays': t03, 't04_regression': t04,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_05_CHECKPOINT,
                metadata={'type': 'concentration_response', 'cell': '05'})
_ = load_checkpoint(CELL_05_CHECKPOINT)
print("\n✓ Cell 05: Concentration-Dependent Response Complete")
```

```
======================================================================
CELL 05: Concentration-Dependent Response
======================================================================
FIGURE 2: Matrix-domain mean spectra at each concentration level, one dye per panel, coloured by concentration on a shared 0-24 µg mL⁻¹ scale (viridis). Shaded band marks the descriptive peak window.
  saved: Figure_02_concentration_overlays_matrix.png  (1907 kB, 600 dpi)
```




TABLE 03: Concentration overlay response per dye and level

| Dye | Concentration_ug_mL | n_spectra | Peak_lambda_nm | Mean_peak_A |
|---|---|---|---|---|
| Tartrazine | 0.5 | 20 | 453 | 0.053526 |
| Tartrazine | 1.0 | 20 | 436 | 0.075283 |
| Tartrazine | 2.0 | 20 | 437 | 0.133978 |
| Tartrazine | 3.0 | 20 | 433 | 0.146327 |

| | | | | |
|---|---|---|---|---|
| Tartrazine | 4.0 | 20 | 434 | 0.184550 |
| Tartrazine | 5.0 | 20 | 434 | 0.186449 |
| Tartrazine | 6.0 | 20 | 439 | 0.259016 |
| Tartrazine | 7.0 | 20 | 434 | 0.278313 |
| Tartrazine | 8.0 | 20 | 434 | 0.325246 |
| Tartrazine | 9.0 | 20 | 429 | 0.370418 |
| Tartrazine | 10.0 | 20 | 434 | 0.391104 |
| Tartrazine | 11.0 | 20 | 433 | 0.445578 |
| Tartrazine | 12.0 | 20 | 434 | 0.490263 |
| Tartrazine | 13.0 | 20 | 434 | 0.515485 |
| Tartrazine | 14.0 | 20 | 435 | 0.549080 |
| Tartrazine | 15.0 | 20 | 434 | 0.587851 |
| Tartrazine | 16.0 | 20 | 438 | 0.620760 |
| Tartrazine | 17.0 | 20 | 435 | 0.683146 |
| Tartrazine | 18.0 | 20 | 434 | 0.684577 |
| Tartrazine | 19.0 | 20 | 434 | 0.723997 |
| Tartrazine | 20.0 | 20 | 436 | 0.752529 |
| Tartrazine | 21.0 | 20 | 435 | 0.797544 |
| Tartrazine | 22.0 | 20 | 436 | 0.797807 |
| Tartrazine | 23.0 | 20 | 434 | 0.851941 |
| Tartrazine | 24.0 | 20 | 436 | 0.879705 |
| Sunset Yellow | 0.5 | 20 | 476 | 0.118204 |
| Sunset Yellow | 1.0 | 20 | 476 | 0.136023 |
| Sunset Yellow | 2.0 | 20 | 478 | 0.149402 |
| Sunset Yellow | 3.0 | 20 | 476 | 0.193661 |
| Sunset Yellow | 4.0 | 20 | 483 | 0.228167 |
| Sunset Yellow | 5.0 | 20 | 482 | 0.250141 |
| Sunset Yellow | 6.0 | 20 | 480 | 0.292470 |
| Sunset Yellow | 7.0 | 20 | 483 | 0.341065 |
| Sunset Yellow | 8.0 | 20 | 482 | 0.374187 |
| Sunset Yellow | 9.0 | 20 | 483 | 0.390912 |
| Sunset Yellow | 10.0 | 20 | 482 | 0.395345 |
| Sunset Yellow | 11.0 | 20 | 480 | 0.453232 |
| Sunset Yellow | 12.0 | 20 | 483 | 0.460023 |
| Sunset Yellow | 13.0 | 20 | 481 | 0.514604 |
| Sunset Yellow | 14.0 | 20 | 486 | 0.546607 |
| Sunset Yellow | 15.0 | 20 | 483 | 0.593784 |
| Sunset Yellow | 16.0 | 20 | 480 | 0.607208 |
| Sunset Yellow | 17.0 | 20 | 483 | 0.647737 |
| Sunset Yellow | 18.0 | 20 | 485 | 0.669977 |
| Sunset Yellow | 19.0 | 20 | 486 | 0.702498 |
| Sunset Yellow | 20.0 | 20 | 484 | 0.699850 |
| Sunset Yellow | 21.0 | 20 | 485 | 0.761464 |
| Sunset Yellow | 22.0 | 20 | 483 | 0.775313 |
| Sunset Yellow | 23.0 | 20 | 484 | 0.825228 |
| Sunset Yellow | 24.0 | 20 | 483 | 0.864929 |
| Metanil Yellow | 0.5 | 20 | 451 | 0.109169 |
| Metanil Yellow | 1.0 | 20 | 451 | 0.110263 |
| Metanil Yellow | 2.0 | 20 | 438 | 0.118652 |
| Metanil Yellow | 3.0 | 20 | 433 | 0.123322 |
| Metanil Yellow | 4.0 | 20 | 433 | 0.132762 |
| Metanil Yellow | 5.0 | 20 | 433 | 0.136367 |
| Metanil Yellow | 6.0 | 20 | 432 | 0.151894 |
| Metanil Yellow | 7.0 | 20 | 432 | 0.164394 |
| Metanil Yellow | 8.0 | 20 | 434 | 0.173593 |
| Metanil Yellow | 9.0 | 20 | 434 | 0.185055 |
| Metanil Yellow | 10.0 | 20 | 428 | 0.197910 |
| Metanil Yellow | 11.0 | 20 | 430 | 0.212887 |
| Metanil Yellow | 12.0 | 20 | 430 | 0.223059 |
| Metanil Yellow | 13.0 | 20 | 430 | 0.230807 |
| Metanil Yellow | 14.0 | 20 | 428 | 0.250207 |
| Metanil Yellow | 15.0 | 20 | 433 | 0.267038 |

  saved: Table_03_concentration_overlay_response_per_dye_and_level.xlsx  (66 rows x 5 cols)
FIGURE 3: Fixed-window peak absorbance against concentration per dye (matrix domain) with the OLS fit. Light points are individual spectra; open markers are level means.
  saved: Figure_03_fixed_window_peak_vs_concentration.png  (479 kB, 600 dpi)




```
TABLE 04: Fixed-window peak concentration response and linearity
           Dye  Slope_A_per_ugmL  Intercept_A       R2  Spearman_rho Spearman_p  Residual_SD_A
Max_abs_residual_A  n_spectra  n_groups  n_unique_concentrations
    Tartrazine          0.035247     0.064833 0.992139      0.995704   0.00e+00       0.022545
0.063860        500        25                       25
 Sunset Yellow          0.031078     0.121816 0.991956      0.994238   0.00e+00       0.020109
0.044474        500        25                       25
Metanil Yellow          0.010834     0.100960 0.959512      0.980371  2.58e-226       0.010165
0.034109        320        16                       16
  saved: Table_04_fixed_window_peak_concentration_response_and_linearity.xlsx  (3 rows x 11
cols)

--- Monotonic response (matrix domain) ---
  Tartrazine      slope=0.0352 A/(µg/mL)  R²=0.9921  Spearman ρ=0.995704  (n_spectra=500,
n_groups=25, n_levels=25)
  Sunset Yellow   slope=0.0311 A/(µg/mL)  R²=0.9920  Spearman ρ=0.994238  (n_spectra=500,
n_groups=25, n_levels=25)
  Metanil Yellow  slope=0.0108 A/(µg/mL)  R²=0.9595  Spearman ρ=0.980371  (n_spectra=320,
n_groups=16, n_levels=16)
✓ Checkpoint loaded: cell_05_concentration_response_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:01.617282
  Shape: {'t03_overlays': (66, 5), 't04_regression': (3, 11), 'figure_manifest': 3,
'table_manifest': 3}

✓ Cell 05: Concentration-Dependent Response Complete
```

In [7]:

```python
CELL_06_CHECKPOINT = CHECKPOINTS_DIR / 'cell_06_peak_shift_checkpoint.pkl'

print("=" * 70)
print("CELL 06: Fixed-Window Peak Analysis and Matrix-Induced Shift")
print("=" * 70)

from scipy.signal import savgol_filter

# Pure-domain mean-spectrum maxima, the reference I measure the matrix shift
# against. Using the class mean spectrum makes the summary peak robust to a
# single noisy spectrum picking a wavelength at the window edge.
pure_peak = {}
for dye in DYE_CLASSES:
    m = X[is_pure & (y_dye == dye)].mean(axis=0)
    pure_peak[dye] = observed_lambda_max(m, dye)

# Anomaly A-06: at low metanil-yellow concentration the per-spectrum maximum
# inside the window can land on the window boundary rather than on a real peak.
# I detect every edge hit, and for a flagged spectrum re-pick the maximum from a
# Savitzky-Golay-smoothed profile. The summary peak positions use the robust
# mean-spectrum maximum; the edge count is reported so the artefact is visible.
def per_spectrum_peaks(mask, dye):
    idx = window_idx(dye)
```

```
    sub = X[mask][:, idx]
    am = sub.argmax(axis=1)
    edge = (am == 0) | (am == len(idx) - 1)
    lam = wl[idx][am].astype(float)
    if edge.any():
        sm = savgol_filter(X[mask][edge], 11, 2, axis=1)
        lam[edge] = wl[idx][sm[:, idx].argmax(axis=1)]
    return lam, edge

shift_rows = []
edge_report = []
for dye in DYE_CLASSES:
    mmask = is_matrix & (y_dye == dye)
    lam, edge = per_spectrum_peaks(mmask, dye)
    shift = lam - pure_peak[dye]
    shift_rows.append({'Dye': dye, 'per_spec_shift': shift})
    # where do the edge artefacts sit in concentration?
    c = conc[mmask]
    lo_edge_conc = sorted(np.unique(c[edge]).tolist()) if edge.any() else []
    edge_report.append({'Dye': dye, 'n_edge_artefacts': int(edge.sum()),
                        'edge_conc_levels': lo_edge_conc})
    print(f"  {dye:15s} edge-of-window maxima: {int(edge.sum())} spectra"
          + (f" at concentrations {lo_edge_conc} µg/mL" if edge.any() else ""))

# T05: observed peak, reference, deviation, matrix-induced shift, peak absorbance.
rows = []
for dye in DYE_CLASSES:
    for dom, dmask in [('Pure standard', is_pure), ('Matrix', is_matrix)]:
        mask = dmask & (y_dye == dye)
        m = X[mask].mean(axis=0)
        lam = observed_lambda_max(m, dye)
        col = np.where(wl == lam)[0][0]
        row = {
            'Dye': dye, 'Domain': dom,
            'Observed_lambda_max_nm': lam,
            'Reference_lambda_max_nm': REFERENCE_PEAKS_NM[dye],
            'Deviation_from_reference_nm': lam - REFERENCE_PEAKS_NM[dye],
            'Mean_peak_A': round(float(m[col]), 6),
            'n_spectra': int(mask.sum()),
        }
        rows.append(row)
t05 = pd.DataFrame(rows)

# matrix-induced shift: matrix mean-spectrum peak minus pure mean-spectrum peak,
# plus the per-spectrum shift distribution.
shift_summary = []
for sr in shift_rows:
    dye = sr['Dye']
    mean_shift = observed_lambda_max(X[is_matrix & (y_dye == dye)].mean(0), dye) -
pure_peak[dye]
    ps = sr['per_spec_shift']
    er = next(e for e in edge_report if e['Dye'] == dye)
    shift_summary.append({
        'Dye': dye,
        'Pure_peak_nm': pure_peak[dye],
        'Matrix_peak_nm': pure_peak[dye] + mean_shift,
        'Matrix_shift_nm': mean_shift,
        'Per_spectrum_shift_mean_nm': round(float(ps.mean()), 3),
        'Per_spectrum_shift_SD_nm': round(float(ps.std(ddof=1)), 3),
        'n_edge_artefacts': er['n_edge_artefacts'],
        'Peak_picking_rule': 'mean-spectrum window maximum; SG re-pick for edge
```

```
hits',
    })
t05b = pd.DataFrame(shift_summary)

show_and_save_table(t05, 5, 'Observed peaks and deviation from reference per dye
and domain',
                    cell='06',
                    notes='Observed window maximum of the class mean spectrum.')
show_and_save_table(t05b, 6, 'Matrix-induced peak shift per dye', cell='06',
                    notes='Matrix shift is the matrix mean-spectrum peak minus the
'
                          'pure mean-spectrum peak. Per-spectrum shift uses the
window '
                          'maximum with Savitzky-Golay re-pick for window-edge
hits '
                          '(anomaly A-06).')

# F05: (a) observed peaks vs reference per dye/domain; (b) matrix-induced shift.
from matplotlib.lines import Line2D

fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.5), layout='constrained')
xpos = np.arange(len(DYE_CLASSES))

# Panel (a): a dumbbell per dye. Colour encodes the dye; marker shape encodes the
# domain (circle = pure, square = matrix); the grey dash marks the literature
# reference. A shape-only legend sits outside the axes so nothing is hidden.
ax = axes[0]
for i, dye in enumerate(DYE_CLASSES):
    pr = t05[(t05.Dye == dye) & (t05.Domain == 'Pure
standard')].iloc[0].Observed_lambda_max_nm
    mr = t05[(t05.Dye == dye) & (t05.Domain ==
'Matrix')].iloc[0].Observed_lambda_max_nm
    ref = REFERENCE_PEAKS_NM[dye]
    ax.plot([i, i], [pr, mr], color=DYE_COLOURS[dye], lw=1.4, alpha=0.6, zorder=1)
    ax.hlines(ref, i - 0.22, i + 0.22, color='0.4', lw=1.4, linestyle=(0, (4, 2)),
              zorder=1)
    ax.scatter(i, pr, s=85, marker='o', color=DYE_COLOURS[dye],
               edgecolor='white', linewidth=1.0, zorder=3)
    ax.scatter(i, mr, s=85, marker='s', color=DYE_COLOURS[dye],
               edgecolor='white', linewidth=1.0, zorder=3)
ax.set_xlim(-0.5, len(DYE_CLASSES) - 0.5)
ax.set_ylim(420, 497)
ax.set_xticks(xpos)
ax.set_xticklabels([d.replace(' ', '\n') for d in DYE_CLASSES])
ax.set_ylabel('Observed λmax (nm)')
ax.set_title('(a)  Peak position vs reference', fontsize=FS_PANEL, loc='left')
ax.grid(axis='y', alpha=0.2)
tidy(ax)
# Shape-only legend placed INSIDE panel (a)'s empty upper-left corner, so it
# never collides with the two-line x-axis tick labels beneath the axes.
legend_items = [
    Line2D([0], [0], marker='o', color='none', markerfacecolor='0.4',
           markeredgecolor='white', markersize=8, label='Pure standard'),
    Line2D([0], [0], marker='s', color='none', markerfacecolor='0.4',
           markeredgecolor='white', markersize=8, label='Matrix'),
    Line2D([0], [0], color='0.4', lw=1.4, linestyle=(0, (4, 2)), label='Reference
λmax'),
]
ax.legend(handles=legend_items, loc='upper left', bbox_to_anchor=(0.01, 0.99),
          frameon=False, fontsize=8, handlelength=1.5, labelspacing=0.3,
          borderaxespad=0.2)
```

```python
# Panel (b): the matrix-induced shift, with value labels given clear headroom so
# the negative label cannot collide with the axis or the tick labels.
ax = axes[1]
shifts = t05b.Matrix_shift_nm.values.astype(int)
colors = [DYE_COLOURS[d] for d in t05b.Dye]
ax.bar(xpos, shifts, color=colors, width=0.62, zorder=2)
ax.axhline(0, color='0.3', lw=0.9, zorder=1)
pad = 2.6
ax.set_ylim(min(shifts.min(), 0) - pad, max(shifts.max(), 0) + pad)
ax.set_xticks(xpos)
ax.set_xticklabels([d.replace(' ', '\n') for d in t05b.Dye])
ax.set_ylabel('Matrix-induced shift (nm)')
ax.set_title('(b)  Matrix minus pure peak', fontsize=FS_PANEL, loc='left')
ax.grid(axis='y', alpha=0.2)
for i, s in enumerate(shifts):
    above = s >= 0
    ax.annotate(f"{s:+d}", xy=(i, s),
                xytext=(0, 4 if above else -4), textcoords='offset points',
                ha='center', va='bottom' if above else 'top', fontsize=9,
                fontweight='bold')
tidy(ax)
save_and_show_fig(fig, 4, 'observed_peaks_and_matrix_shift',
                  'Observed window maxima against the literature reference per dye
'
                  '(a; circle = pure standard, square = matrix, dash = reference)
and '
                  'the matrix-induced peak shift (b).')

save_checkpoint({'t05_peaks': t05, 't05b_shift': t05b,
                 'edge_report': edge_report,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_06_CHECKPOINT,
                metadata={'type': 'peak_shift', 'cell': '06'})
_ = load_checkpoint(CELL_06_CHECKPOINT)
print("\n✓ Cell 06: Fixed-Window Peak Analysis and Matrix-Induced Shift
Complete")
```

```
======================================================================
CELL 06: Fixed-Window Peak Analysis and Matrix-Induced Shift
======================================================================
  Tartrazine      edge-of-window maxima: 2 spectra at concentrations [0.5, 3.0] µg/mL
  Sunset Yellow   edge-of-window maxima: 0 spectra
  Metanil Yellow  edge-of-window maxima: 2 spectra at concentrations [0.5] µg/mL

TABLE 05: Observed peaks and deviation from reference per dye and domain
           Dye        Domain  Observed_lambda_max_nm  Reference_lambda_max_nm
Deviation_from_reference_nm  Mean_peak_A  n_spectra
    Tartrazine Pure standard                     432                      425
7     0.452696        180
    Tartrazine        Matrix                     435                      425
10     0.468392        500
 Sunset Yellow Pure standard                     486                      485
1     0.435581        200
 Sunset Yellow        Matrix                     483                      485
-2     0.476608        500
Metanil Yellow Pure standard                     427                      435
-8     0.286239        220
Metanil Yellow        Matrix                     434                      435
-1     0.172157        320
  saved: Table_05_observed_peaks_and_deviation_from_reference_per_dye_and_domain.xlsx  (6 rows x
7 cols)

TABLE 06: Matrix-induced peak shift per dye
```

```
          Dye  Pure_peak_nm  Matrix_peak_nm  Matrix_shift_nm  Per_spectrum_shift_mean_nm
Per_spectrum_shift_SD_nm  n_edge_artefacts
Peak_picking_rule
    Tartrazine           432             435                3                       3.070
4.594                 2 mean-spectrum window maximum; SG re-pick for edge hits
 Sunset Yellow           486             483               -3                      -2.082
6.122                 0 mean-spectrum window maximum; SG re-pick for edge hits
Metanil Yellow           427             434                7                       5.106
7.898                 2 mean-spectrum window maximum; SG re-pick for edge hits
  saved: Table_06_matrix_induced_peak_shift_per_dye.xlsx  (3 rows x 8 cols)
FIGURE 4: Observed window maxima against the literature reference per dye (a; circle = pure
standard, square = matrix, dash = reference) and the matrix-induced peak shift (b).
  saved: Figure_04_observed_peaks_and_matrix_shift.png  (251 kB, 600 dpi)
```




```
✓ Checkpoint loaded: cell_06_peak_shift_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:02.310939
  Shape: {'t05_peaks': (6, 7), 't05b_shift': (3, 8), 'edge_report': 3, 'figure_manifest': 4,
'table_manifest': 5}

✓ Cell 06: Fixed-Window Peak Analysis and Matrix-Induced Shift Complete
```

In [8]:

```python
CELL_07_CHECKPOINT = CHECKPOINTS_DIR /
'cell_07_replicate_variability_checkpoint.pkl'

print("=" * 70)
print("CELL 07: Within-Group Replicate Variability (Instrument Repeatability)")
print("=" * 70)

# The 20 frames in a group are repeated instrument reads of one physical
# preparation, so their dispersion is instrument repeatability. It is NOT
# between-preparation precision: there are no independent duplicate preparations
# at any concentration, so that quantity cannot be estimated from this design.
MATRIX_PEAK_NM = {dye: observed_lambda_max(X[is_matrix & (y_dye == dye)].mean(0),
dye)
                  for dye in DYE_CLASSES}
RSD_FLOOR_A = 0.05   # ignore wavelengths whose group mean is near baseline

rows = []
for dye in DYE_CLASSES:
    col = np.where(wl == MATRIX_PEAK_NM[dye])[0][0]
    for g in np.unique(group_id[is_matrix & (y_dye == dye)]):
        frames = X[group_id == g]
        peak_vals = frames[:, col]
        rsd_peak = 100.0 * peak_vals.std(ddof=1) / peak_vals.mean()
        mean_spec = frames.mean(axis=0)
        sd_spec = frames.std(axis=0, ddof=1)
        keep = mean_spec > RSD_FLOOR_A
```

```
        rsd_full = np.median(100.0 * sd_spec[keep] / mean_spec[keep])
        rows.append({'Dye': dye, 'Group_ID': g, 'Concentration': conc[group_id ==
g][0],
                     'n_frames': len(frames),
                     'RSD_at_peak_pct': rsd_peak,
                     'RSD_fullspectrum_median_pct': rsd_full})
per_group = pd.DataFrame(rows)

# Per-dye summary of the per-group RSDs.
summary_rows = []
for dye in DYE_CLASSES:
    sub = per_group[per_group.Dye == dye]
    summary_rows.append({
        'Dye': dye, 'n_groups': len(sub),
        'Median_RSD_peak_pct': round(float(sub.RSD_at_peak_pct.median()), 4),
        'IQR_RSD_peak_pct': round(float(sub.RSD_at_peak_pct.quantile(0.75)
                                        - sub.RSD_at_peak_pct.quantile(0.25)), 4),
        'Max_RSD_peak_pct': round(float(sub.RSD_at_peak_pct.max()), 4),
        'Median_RSD_fullspec_pct':
round(float(sub.RSD_fullspectrum_median_pct.median()), 4),
        'Max_RSD_fullspec_pct':
round(float(sub.RSD_fullspectrum_median_pct.max()), 4),
    })
t07 = pd.DataFrame(summary_rows)
show_and_save_table(t07, 7, 'Within-group replicate variability per dye',
cell='07',
                    notes='RSD across the repeated frames within each preparation,
'
                          'summarised over groups. RSD at the matrix peak
wavelength '
                          'and the median full-spectrum RSD (wavelengths with
group '
                          f'mean > {RSD_FLOOR_A} A). Instrument repeatability, not
'
                          'between-preparation precision.')

overall_peak = per_group.RSD_at_peak_pct.median()
overall_full = per_group.RSD_fullspectrum_median_pct.median()
print(f"\nInstrument repeatability (median across {len(per_group)} groups):")
print(f"  RSD at peak wavelength      : {overall_peak:.3f} %")
print(f"  RSD across the spectrum      : {overall_full:.3f} %")
print("  Interpretation: repeatability of repeated reads of one preparation. "
      "Between-preparation precision is NOT estimable from this design.")

# F06: per-group RSD distributions by dye, two panels.
fig, axes = plt.subplots(1, 2, figsize=(7.0, 3.2), layout='constrained')
for ax, (col_name, ttl) in zip(
        axes, [('RSD_at_peak_pct', '(a)  RSD at matrix peak'),
               ('RSD_fullspectrum_median_pct', '(b)  Median full-spectrum
RSD')]):
    data = [per_group[per_group.Dye == dye][col_name].values for dye in
DYE_CLASSES]
    bp = ax.boxplot(data, patch_artist=True, widths=0.6,
                    medianprops=dict(color='0.15', lw=1.1),
                    flierprops=dict(marker='o', markersize=2.5, alpha=0.5))
    for patch, dye in zip(bp['boxes'], DYE_CLASSES):
        patch.set_facecolor(DYE_COLOURS[dye])
        patch.set_alpha(0.55)
    ax.set_xticks(range(1, len(DYE_CLASSES) + 1))
    ax.set_xticklabels([d.replace(' ', '\n') for d in DYE_CLASSES])
    ax.set_ylabel('RSD (%)')
```

```
    ax.set_title(ttl, fontsize=FS_PANEL, loc='left')
    tidy(ax)
save_and_show_fig(fig, 5, 'within_group_replicate_rsd',
                  'Per-preparation replicate RSD by dye: at the matrix peak
wavelength '
                  '(a) and the median across the spectrum (b). Each box is the '
                  'distribution over preparations (n = 25, 25, 16). This is
instrument '
                  'repeatability, not between-preparation precision.')

save_checkpoint({'t07_summary': t07, 'per_group_rsd': per_group,
                 'overall_rsd_peak_pct': float(overall_peak),
                 'overall_rsd_full_pct': float(overall_full),
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_07_CHECKPOINT,
                metadata={'type': 'replicate_variability', 'cell': '07'})
_ = load_checkpoint(CELL_07_CHECKPOINT)
print("\n✓ Cell 07: Within-Group Replicate Variability Complete")
```

```
======================================================================
CELL 07: Within-Group Replicate Variability (Instrument Repeatability)
======================================================================

TABLE 07: Within-group replicate variability per dye
          Dye  n_groups  Median_RSD_peak_pct  IQR_RSD_peak_pct  Max_RSD_peak_pct
Median_RSD_fullspec_pct  Max_RSD_fullspec_pct
    Tartrazine        25               2.9273            2.5237           35.0549
8.1511               13.5321
 Sunset Yellow        25               2.4859            2.9944           17.7260
6.1285               12.3130
Metanil Yellow        16               5.7303            2.6319            9.3258
5.5222                6.7184
  saved: Table_07_within_group_replicate_variability_per_dye.xlsx  (3 rows x 7 cols)

Instrument repeatability (median across 66 groups):
  RSD at peak wavelength      : 3.154 %
  RSD across the spectrum      : 6.389 %
  Interpretation: repeatability of repeated reads of one preparation. Between-preparation
precision is NOT estimable from this design.
FIGURE 5: Per-preparation replicate RSD by dye: at the matrix peak wavelength (a) and the median
across the spectrum (b). Each box is the distribution over preparations (n = 25, 25, 16). This
is instrument repeatability, not between-preparation precision.
  saved: Figure_05_within_group_replicate_rsd.png  (144 kB, 600 dpi)
```




```
✓ Checkpoint loaded: cell_07_replicate_variability_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:02.855271
  Shape: {'t07_summary': (3, 7), 'per_group_rsd': (66, 6), 'figure_manifest': 5,
'table_manifest': 6}
```

✓ Cell 07: Within-Group Replicate Variability Complete

In [9]:
```
CELL_08_CHECKPOINT = CHECKPOINTS_DIR / 'cell_08_pca_checkpoint.pkl'

print("=" * 70)
print("CELL 08: PCA and Multivariate Structure (visualisation only)")
print("=" * 70)
print("I describe the whole matrix set, unsupervised. It is not a "
      "model, it touches no train/test split, and nothing computed here enters the
"
      "modelling pipeline. The decomposition is over all matrix spectra for "
      "visualisation only.")

# Matrix domain, all adulterated spectra including the control preparation.
Xm = X[is_matrix]
ym = y_dye[is_matrix]
cm = conc[is_matrix]

# Correlation PCA by SVD on the standardised matrix. I standardise and decompose
# with numpy directly so there is no scikit-learn estimator state to carry: this
# block is descriptive and is never reused for prediction.
mu = Xm.mean(axis=0)
sd = Xm.std(axis=0, ddof=0)
sd[sd == 0] = 1.0
Xs = (Xm - mu) / sd
U, S, Vt = np.linalg.svd(Xs, full_matrices=False)
evr = (S ** 2) / (S ** 2).sum() * 100.0
scores = U * S                      # equals Xs @ Vt.T
components = Vt                      # rows are the loadings
evr = evr[:10]

print(f"\nExplained variance: PC1 {evr[0]:.2f} %, PC2 {evr[1]:.2f} %, "
      f"PC3 {evr[2]:.2f} %, cumulative(3) {evr[:3].sum():.2f} %")

# T08: explained variance + per-class score centroids (the numbers behind F07).
var_tbl = pd.DataFrame({
    'PC': [f"PC{i+1}" for i in range(10)],
    'Explained_variance_pct': np.round(evr, 4),
    'Cumulative_pct': np.round(np.cumsum(evr), 4),
})
cent_rows = []
for dye in DYE_ORDER:
    mask = ym == dye
    if mask.sum() == 0:
        continue
    cent_rows.append({'Class': dye, 'n_spectra': int(mask.sum()),
                      'Mean_PC1': round(float(scores[mask, 0].mean()), 4),
                      'Mean_PC2': round(float(scores[mask, 1].mean()), 4),
                      'Mean_PC3': round(float(scores[mask, 2].mean()), 4)})
centroids = pd.DataFrame(cent_rows)
show_and_save_table(var_tbl, 8, 'PCA explained variance and class score
centroids',
                    cell='08',
                    notes='Correlation PCA on standardised matrix spectra '
                          '(n_spectra=1370, n_groups=67). Class centroids printed
'
                          'below the variance table.')
print("\nClass score centroids:")
print(centroids.to_string(index=False))
```

```
# F07: score plots, coloured by class and by concentration.
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.4), layout='constrained')
ax = axes[0]
for dye in DYE_ORDER:
    mask = ym == dye
    if mask.sum() == 0:
        continue
    ax.scatter(scores[mask, 0], scores[mask, 1], s=7, alpha=0.5, lw=0,
               color=DYE_COLOURS[dye], label=dye)
ax.set_xlabel(f'PC1 ({evr[0]:.1f} %)')
ax.set_ylabel(f'PC2 ({evr[1]:.1f} %)')
ax.set_title('(a)  Scores by class', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper left', bbox_to_anchor=(1.02, 1.0), borderaxespad=0.0,
          frameon=False, fontsize=9)
tidy(ax)

ax = axes[1]
sc = ax.scatter(scores[:, 0], scores[:, 1], c=cm, s=7, alpha=0.6, lw=0,
                cmap=SEQUENTIAL_CMAP)
ax.set_xlabel(f'PC1 ({evr[0]:.1f} %)')
ax.set_ylabel(f'PC2 ({evr[1]:.1f} %)')
ax.set_title('(b)  Scores by concentration', fontsize=FS_PANEL, loc='left')
cb = fig.colorbar(sc, ax=ax, pad=0.02)
cb.set_label('Conc. (µg mL⁻¹)', fontsize=9)
cb.ax.tick_params(labelsize=8)
tidy(ax)
save_and_show_fig(fig, 6, 'pca_scores',
                  'PCA score plot of standardised matrix spectra, coloured by
class '
                  '(a) and by concentration (b). Visualisation only;
n_spectra=1370 '
                  'in 67 groups.')

# F08 / T09: loadings for PC1-PC3 and the wavelength cross-correlation summary.
corr = np.corrcoef(Xm.T)
iu = np.triu_indices_from(corr, k=1)
r = corr[iu]
ar = np.abs(r)
corr_summary = {
    'n_pairs': int(r.size),
    'mean_abs_r': round(float(ar.mean()), 6),
    'median_abs_r': round(float(np.median(ar)), 6),
    'pct_pairs_abs_gt_0.90': round(float(100.0 * (ar > 0.90).mean()), 4),
    'min_r': round(float(r.min()), 6),
    'max_r': round(float(r.max()), 6),
}
print(f"\nWavelength cross-correlation over {corr_summary['n_pairs']} pairs: "
      f"mean|r|={corr_summary['mean_abs_r']}, median|r|=
{corr_summary['median_abs_r']}, "
      f"{corr_summary['pct_pairs_abs_gt_0.90']} % above 0.90, "
      f"range {corr_summary['min_r']} to {corr_summary['max_r']}")

load_rows = []
for pc in range(3):
    L = components[pc]
    top = np.argsort(np.abs(L))[::-1][:5]
    load_rows.append({'PC': f"PC{pc+1}",
                      'Top_wavelengths_nm': ', '.join(str(int(wl[t])) for t in
top),
                      'Top_abs_loadings': ', '.join(f"{abs(L[t]):.3f}" for t in
top)})
```

```
t09 = pd.DataFrame(
    [{'Quantity': k, 'Value': v} for k, v in corr_summary.items()]
    + [{'Quantity': f"{row['PC']}_top_wavelengths_nm", 'Value':
row['Top_wavelengths_nm']}
       for row in load_rows]
    + [{'Quantity': f"{row['PC']}_top_abs_loadings", 'Value':
row['Top_abs_loadings']}
       for row in load_rows])
show_and_save_table(t09, 9, 'PCA loadings summary and wavelength cross-
correlation',
                    cell='08',
                    notes='Cross-correlation over all unique wavelength pairs of
the '
                          'matrix spectra, and the five highest absolute loadings
per '
                          'component.')

fig, ax = plt.subplots(figsize=(7.0, 3.3), layout='constrained')
pc_colours = ['#2B2B2B', '#8E44AD', '#16A085']
for pc in range(3):
    ax.plot(wl, components[pc], color=pc_colours[pc], lw=1.1,
            label=f"PC{pc+1} ({evr[pc]:.1f} %)")
# No dye-peak guide lines: the tartrazine and metanil-yellow matrix maxima sit
# 1 nm apart (435 vs 434 nm) and their markers overlap illegibly. The loadings
# are read directly; the top loading wavelengths per PC are tabulated in T09.
ax.axhline(0, color='0.6', lw=0.6)
ax.set_xlabel('Wavelength (nm)')
ax.set_ylabel('Loading')
ax.set_xlim(wl.min(), wl.max())
ax.legend(loc='upper left', bbox_to_anchor=(1.02, 1.0), borderaxespad=0.0,
          frameon=False, fontsize=9)
tidy(ax)
save_and_show_fig(fig, 7, 'pca_loadings',
                  'PCA loadings for the first three components against wavelength
'
                  '(visualisation only). Wavelength cross-correlation is
summarised in the '
                  'paired table.')

save_checkpoint({'explained_variance_pct': evr, 'var_table': var_tbl,
                 'centroids': centroids, 'corr_summary': corr_summary,
                 't09_loadings': t09,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_08_CHECKPOINT,
                metadata={'type': 'pca_structure', 'cell': '08'})
_ = load_checkpoint(CELL_08_CHECKPOINT)
print("\n✓ Cell 08: PCA and Multivariate Structure Complete")
```

```
======================================================================
CELL 08: PCA and Multivariate Structure (visualisation only)
======================================================================
I describe the whole matrix set, unsupervised. It is not a model, it touches no train/test
split, and nothing computed here enters the modelling pipeline. The decomposition is over all
matrix spectra for visualisation only.

Explained variance: PC1 50.30 %, PC2 35.17 %, PC3 5.91 %, cumulative(3) 91.37 %

TABLE 08: PCA explained variance and class score centroids
  PC  Explained_variance_pct  Cumulative_pct
 PC1                 50.2998         50.2998
 PC2                 35.1681         85.4679
 PC3                  5.9060         91.3739
```

| | | |
|---|---|---|
| PC4 | 2.4171 | 93.7911 |
| PC5 | 0.8194 | 94.6105 |
| PC6 | 0.6144 | 95.2249 |
| PC7 | 0.2945 | 95.5194 |
| PC8 | 0.1006 | 95.6201 |
| PC9 | 0.0879 | 95.7080 |
| PC10 | 0.0818 | 95.7897 |

saved: Table_08_pca_explained_variance_and_class_score_centroids.xlsx (10 rows x 3 cols)

Class score centroids:

| Class | n_spectra | Mean_PC1 | Mean_PC2 | Mean_PC3 |
|---|---|---|---|---|
| Tartrazine | 500 | 13.0491 | -4.8154 | 0.3760 |
| Sunset Yellow | 500 | -8.6118 | 10.8271 | 1.9688 |
| Metanil Yellow | 320 | -5.7703 | -8.5231 | -5.7761 |
| Control | 50 | -7.4432 | -5.5684 | 13.5190 |

FIGURE 6: PCA score plot of standardised matrix spectra, coloured by class (a) and by concentration (b). Visualisation only; n_spectra=1370 in 67 groups.
saved: Figure_06_pca_scores.png (704 kB, 600 dpi)




Wavelength cross-correlation over 79800 pairs: mean|r|=0.541988, median|r|=0.565973, 12.3233 % above 0.90, range -0.867163 to 0.998724

TABLE 09: PCA loadings summary and wavelength cross-correlation

| Quantity | Value |
|---|---|
| n_pairs | 79800 |
| mean_abs_r | 0.541988 |
| median_abs_r | 0.565973 |
| pct_pairs_abs_gt_0.90 | 12.3233 |
| min_r | -0.867163 |
| max_r | 0.998724 |
| PC1_top_wavelengths_nm | 435, 433, 434, 436, 432 |
| PC2_top_wavelengths_nm | 475, 474, 476, 477, 473 |
| PC3_top_wavelengths_nm | 360, 361, 359, 358, 357 |
| PC1_top_abs_loadings | 0.070, 0.070, 0.070, 0.070, 0.070 |
| PC2_top_abs_loadings | 0.082, 0.082, 0.082, 0.082, 0.082 |
| PC3_top_abs_loadings | 0.186, 0.182, 0.181, 0.177, 0.171 |

saved: Table_09_pca_loadings_summary_and_wavelength_cross_correlation.xlsx (12 rows x 2 cols)
FIGURE 7: PCA loadings for the first three components against wavelength (visualisation only). Wavelength cross-correlation is summarised in the paired table.
saved: Figure_07_pca_loadings.png (347 kB, 600 dpi)




```
✓ Checkpoint loaded: cell_08_pca_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:04.221180
  Shape: {'explained_variance_pct': (10,), 'var_table': (10, 3), 'centroids': (4, 5),
't09_loadings': (12, 2), 'figure_manifest': 7, 'table_manifest': 8}

✓ Cell 08: PCA and Multivariate Structure Complete
```

In [10]:

```
CELL_09_CHECKPOINT = CHECKPOINTS_DIR / 'cell_09_qc_fitness_checkpoint.pkl'

print("=" * 70)
print("CELL 09: Spectral QC Diagnostics and Fitness Decision")
print("=" * 70)

SAT_SCREEN_A = 1.15      # screening boundary
DETECTOR_CEILING_A = 1.20
UV_WL = 301
BASELINE_IDX = np.where(wl >= 690)[0]   # flat tail used for the noise estimate

# T10: per domain and class QC block.
rows = []
for dom, dmask in [('Pure standard', is_pure), ('Matrix', is_matrix)]:
    dyes = DYE_CLASSES if dom == 'Pure standard' else DYE_ORDER
    for dye in dyes:
        mask = dmask & (y_dye == dye)
        if mask.sum() == 0:
            continue
        sub = X[mask]
        rowmax = sub.max(axis=1)
        noise = np.median(sub[:, BASELINE_IDX].std(axis=1, ddof=1))
        rows.append({
            'Domain': dom, 'Class': dye, 'n_spectra': int(mask.sum()),
            'Max_A': round(float(sub.max()), 6),
            'Median_max_A': round(float(np.median(rowmax)), 6),
            'Pct_ge_1.15A': round(float(100.0 * (rowmax >= SAT_SCREEN_A).mean()),
4),
            'Pct_ge_1.20A': round(float(100.0 * (rowmax >=
DETECTOR_CEILING_A).mean()), 4),
            'Mean_A_at_301nm': round(float(sub[:, wl == UV_WL].mean()), 6),
            'Mean_A_at_700nm': round(float(sub[:, wl == 700].mean()), 6),
            'Noise_mA_at_tail': round(float(noise * 1000), 4),
        })
t10 = pd.DataFrame(rows)
show_and_save_table(t10, 10, 'Spectral QC diagnostics per class and domain',
cell='09',
```

```
                    notes='Max_A is the single highest absorbance in the block; '
                          'Median_max_A is the median per-spectrum maximum. Noise
is '
                          'the median per-spectrum SD over the 690-700 nm tail, in
'
                          'milli-absorbance. UV background quantified at 301 nm '
                          '(anomaly A-07).')

n_sat_115 = int((X.max(axis=1) >= SAT_SCREEN_A).sum())
n_sat_120 = int((X.max(axis=1) >= DETECTOR_CEILING_A).sum())
uv_matrix = float(X[is_matrix][:, wl == UV_WL].mean())
uv_pure = float(X[is_pure][:, wl == UV_WL].mean())
print(f"\nSaturation screen: {n_sat_115} spectra >= {SAT_SCREEN_A} A, "
      f"{n_sat_120} spectra >= {DETECTOR_CEILING_A} A (whole dataset of
{len(X)})")
print(f"Matrix UV background at 301 nm: {uv_matrix:.6f} A  vs  pure {uv_pure:.6f}
A "
      f"(ratio {uv_matrix/uv_pure:.2f}x)  -- anomaly A-07")

# F09: four QC panels.
fig, axes = plt.subplots(2, 2, figsize=(7.48, 5.6), layout='constrained')

# (a) per-spectrum maximum absorbance by class, matrix domain
ax = axes[0, 0]
data = [X[is_matrix & (y_dye == d)].max(axis=1) for d in DYE_ORDER]
bp = ax.boxplot(data, patch_artist=True, widths=0.6,
                medianprops=dict(color='0.15', lw=1.1),
                flierprops=dict(marker='o', markersize=2.5, alpha=0.4))
for patch, dye in zip(bp['boxes'], DYE_ORDER):
    patch.set_facecolor(DYE_COLOURS[dye]); patch.set_alpha(0.55)
ax.axhline(SAT_SCREEN_A, color='#B23A48', lw=1.0, ls='--', label='1.15 A screen')
ax.set_xticks(range(1, len(DYE_ORDER) + 1))
ax.set_xticklabels([d.split()[0] for d in DYE_ORDER])
ax.set_ylabel('Per-spectrum max A')
ax.set_title('(a)  Maximum absorbance, matrix', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper right', frameon=False, fontsize=9)
tidy(ax)

# (b) matrix absorbance percentile envelope
ax = axes[0, 1]
Xmat = X[is_matrix]
p5, p50, p95 = np.percentile(Xmat, [5, 50, 95], axis=0)
ax.fill_between(wl, p5, p95, color='#1B6CA8', alpha=0.2, lw=0, label='5-95 pctl')
ax.plot(wl, p50, color='#1B6CA8', lw=1.0, label='Median')
ax.set_xlim(wl.min(), wl.max())
ax.set_xlabel('Wavelength (nm)')
ax.set_ylabel('Absorbance (A)')
ax.set_title('(b)  Matrix absorbance envelope', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper right', frameon=False, fontsize=9)
tidy(ax)

# (c) UV background at 301 nm by domain
ax = axes[1, 0]
ax.bar([0, 1], [uv_pure, uv_matrix], color=['#6C757D', '#1B6CA8'], width=0.6)
ax.set_xticks([0, 1]); ax.set_xticklabels(['Pure\nstandard', 'Matrix'])
ax.set_ylabel('Mean A at 301 nm')
ax.set_title('(c)  UV background (A-07)', fontsize=FS_PANEL, loc='left')
for i, v in enumerate([uv_pure, uv_matrix]):
    ax.annotate(f"{v:.3f}", xy=(i, v), xytext=(0, 3), textcoords='offset points',
                ha='center', fontsize=9)
tidy(ax)
```

```
# (d) per-spectrum tail-noise distribution by domain
ax = axes[1, 1]
noise_pure = X[is_pure][:, BASELINE_IDX].std(axis=1, ddof=1) * 1000
noise_mat = X[is_matrix][:, BASELINE_IDX].std(axis=1, ddof=1) * 1000
bp = ax.boxplot([noise_pure, noise_mat], patch_artist=True, widths=0.6,
                medianprops=dict(color='0.15', lw=1.1),
                flierprops=dict(marker='o', markersize=2.5, alpha=0.4))
for patch, c in zip(bp['boxes'], ['#6C757D', '#1B6CA8']):
    patch.set_facecolor(c); patch.set_alpha(0.55)
ax.set_xticks([1, 2]); ax.set_xticklabels(['Pure\nstandard', 'Matrix'])
ax.set_ylabel('Tail noise (mA)')
ax.set_title('(d)  Noise, 690-700 nm', fontsize=FS_PANEL, loc='left')
tidy(ax)

save_and_show_fig(fig, 8, 'spectral_qc_diagnostics',
                  'Spectral QC. (a) per-spectrum maximum absorbance by class in
the '
                  'matrix with the 1.15 A screen; (b) matrix absorbance median
with '
                  'the 5-95 percentile envelope; (c) mean UV background at 301 nm
by '
                  'domain; (d) per-spectrum tail noise, 690-700 nm.')

# Written fitness decision.
print("\n" + "-" * 70)
print("FITNESS DECISION (end of Phase 1)")
print("-" * 70)
decision = [
    f"1. Dynamic range: 0 spectra reach the 1.15 A screen and 0 reach the 1.20 A "
    f"detector ceiling. Highest absorbance is {X[is_pure].max():.4f} A (pure) and
"
    f"{X[is_matrix].max():.4f} A (matrix). No clipping, no saturation exclusion.",
    "2. Integrity: 788000/788000 cells finite (Cell 03); no missing, negative, or
"
    "all-zero spectra. No observation is excluded; no exclusion criterion
exists.",
    "3. Response: window-peak absorbance rises monotonically with concentration
for "
    "all three dyes (Spearman rho 0.98-0.996, Cell 05). The assay carries
quantitative "
    "signal.",
    "4. Repeatability: median within-preparation RSD is ~3% at the peak (Cell 07);
"
    "this is instrument repeatability only, not between-preparation precision.",
    f"5. Matrix background: mean absorbance at 301 nm is {uv_matrix:.3f} A in the
"
    f"matrix against {uv_pure:.3f} A in pure standards ({uv_matrix/uv_pure:.1f}x,
"
    "anomaly A-07). Any wavelength importance below ~400 nm must be read as
possible "
    "juice-matrix signal, not dye absorption, and will be annotated as such
downstream.",
    "6. Structure: three dyes separate in PC1-PC2 and concentration runs along the
"
    "score gradient (Cell 08); wavelengths are highly collinear (12.3% of pairs "
    "|r|>0.90), which is why the modelling uses collinearity-aware chemometrics.",
    "VERDICT: the spectra are fit for modelling. Proceed to Phase 2
(preprocessing). "
    "Predictors remain exactly the 400 wavelength columns 301-700 nm.",
]
```

```python
for line in decision:
    print("  " + line)

save_checkpoint({'t10_qc': t10, 'n_ge_1.15A': n_sat_115, 'n_ge_1.20A': n_sat_120,
                 'uv_background_matrix_A': uv_matrix, 'uv_background_pure_A':
uv_pure,
                 'fitness_verdict': 'FIT — proceed to preprocessing; no
exclusions',
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_09_CHECKPOINT,
                metadata={'type': 'qc_fitness', 'cell': '09'})
_ = load_checkpoint(CELL_09_CHECKPOINT)

print("\n--- Phase 1 artefact manifest ---")
print(f"  Figures this phase: {[f['number'] for f in FIGURE_MANIFEST]}")
print(f"  Tables this phase : {[t['number'] for t in TABLE_MANIFEST]}")
print("\n✓ Cell 09: Spectral QC Diagnostics and Fitness Decision Complete")
print("✓ Phase 1 (Exploratory Spectroscopy) complete — ready for Gate G0/G1
review")
```

```
======================================================================
CELL 09: Spectral QC Diagnostics and Fitness Decision
======================================================================

TABLE 10: Spectral QC diagnostics per class and domain
       Domain          Class  n_spectra    Max_A  Median_max_A  Pct_ge_1.15A  Pct_ge_1.20A
Mean_A_at_301nm  Mean_A_at_700nm  Noise_mA_at_tail
Pure standard     Tartrazine        180 1.017209      0.364514           0.0           0.0
0.027126         0.041156            4.7346
Pure standard  Sunset Yellow        200 0.976802      0.419428           0.0           0.0
0.125986         0.060816            5.2860
Pure standard Metanil Yellow        220 0.700760      0.266159           0.0           0.0
0.075939         0.038502            4.9441
       Matrix     Tartrazine        500 0.898296      0.542310           0.0           0.0
0.150067         0.014369            8.3628
       Matrix  Sunset Yellow        500 0.885854      0.631221           0.0           0.0
0.514979         0.046220           11.6131
       Matrix Metanil Yellow        320 0.595284      0.539342           0.0           0.0
0.469332         0.046796           17.7682
       Matrix        Control         50 0.530190      0.486906           0.0           0.0
0.387053         0.017424            3.8909
  saved: Table_10_spectral_qc_diagnostics_per_class_and_domain.xlsx  (7 rows x 10 cols)

Saturation screen: 0 spectra >= 1.15 A, 0 spectra >= 1.2 A (whole dataset of 1970)
Matrix UV background at 301 nm: 0.366468 A  vs  pure 0.077977 A (ratio 4.70x)  -- anomaly A-07
FIGURE 8: Spectral QC. (a) per-spectrum maximum absorbance by class in the matrix with the 1.15
A screen; (b) matrix absorbance median with the 5-95 percentile envelope; (c) mean UV background
at 301 nm by domain; (d) per-spectrum tail noise, 690-700 nm.
  saved: Figure_08_spectral_qc_diagnostics.png  (492 kB, 600 dpi)
```




```
------------------------------------------------------------------------
FITNESS DECISION (end of Phase 1)
------------------------------------------------------------------------
  1. Dynamic range: 0 spectra reach the 1.15 A screen and 0 reach the 1.20 A detector ceiling.
Highest absorbance is 1.0172 A (pure) and 0.8983 A (matrix). No clipping, no saturation
exclusion.
  2. Integrity: 788000/788000 cells finite (Cell 03); no missing, negative, or all-zero spectra.
No observation is excluded; no exclusion criterion exists.
  3. Response: window-peak absorbance rises monotonically with concentration for all three dyes
(Spearman rho 0.98-0.996, Cell 05). The assay carries quantitative signal.
  4. Repeatability: median within-preparation RSD is ~3% at the peak (Cell 07); this is
instrument repeatability only, not between-preparation precision.
  5. Matrix background: mean absorbance at 301 nm is 0.366 A in the matrix against 0.078 A in
pure standards (4.7x, anomaly A-07). Any wavelength importance below ~400 nm must be read as
possible juice-matrix signal, not dye absorption, and will be annotated as such downstream.
  6. Structure: three dyes separate in PC1-PC2 and concentration runs along the score gradient
(Cell 08); wavelengths are highly collinear (12.3% of pairs |r|>0.90), which is why the
modelling uses collinearity-aware chemometrics.
  VERDICT: the spectra are fit for modelling. Proceed to Phase 2 (preprocessing). Predictors
remain exactly the 400 wavelength columns 301-700 nm.
✓ Checkpoint loaded: cell_09_qc_fitness_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:05.260765
  Shape: {'t10_qc': (7, 10), 'figure_manifest': 8, 'table_manifest': 9}

--- Phase 1 artefact manifest ---
  Figures this phase: ['01', '02', '03', '04', '05', '06', '07', '08']
  Tables this phase : ['02', '03', '04', '05', '06', '07', '08', '09', '10']

✓ Cell 09: Spectral QC Diagnostics and Fitness Decision Complete
✓ Phase 1 (Exploratory Spectroscopy) complete — ready for Gate G0/G1 review
```

In [11]:

```
CELL_10_CHECKPOINT = CHECKPOINTS_DIR /
'cell_10_preprocessing_transformers_checkpoint.pkl'

print("=" * 70)
print("CELL 10: Preprocessing Transformers")
print("=" * 70)
print("Seven representations enter the benchmark (Raw, SG1, SNV+SG1, MSC, L2, "
```

```
      "EMSC, PQN); edge-anchored detrend is defined too, only so Cell 12 can "
      "reproduce its recorded exclusion. 'Raw' is the supplied AirPLS-corrected "
      "spectrum. The scatter methods (MSC, EMSC, PQN) learn a reference INSIDE fit
"
      "so a Pipeline re-estimates them per training fold and no held-out spectrum
"
      "informs its own correction.")

from scipy.signal import savgol_filter
from sklearn.base import BaseEstimator, TransformerMixin
from sklearn.utils.validation import check_is_fitted
from sklearn.exceptions import NotFittedError

SG_WINDOW, SG_POLY, SG_DERIV = 11, 2, 1
_EPS = 1e-8

# Wavelength axis scaled to [-1, 1] for the polynomial terms of EMSC.
_w = (wl.astype(float) - wl.min()) / (wl.max() - wl.min())
_w = 2.0 * _w - 1.0


class SNV(BaseEstimator, TransformerMixin):
    """Standard normal variate: centre and scale each spectrum by its own
    mean and SD. Per-spectrum, so it learns nothing from the training fold."""
    def fit(self, X, y=None):
        return self
    def transform(self, X):
        X = np.asarray(X, dtype=float)
        mu = X.mean(axis=1, keepdims=True)
        sd = X.std(axis=1, ddof=1, keepdims=True)
        return (X - mu) / np.where(sd < _EPS, _EPS, sd)


class SG1(BaseEstimator, TransformerMixin):
    """Savitzky-Golay first derivative, 11-point window, order 2. Per-spectrum."""
    def fit(self, X, y=None):
        return self
    def transform(self, X):
        X = np.asarray(X, dtype=float)
        return savgol_filter(X, SG_WINDOW, SG_POLY, deriv=SG_DERIV, axis=1)


class SNVSG1(BaseEstimator, TransformerMixin):
    """SNV followed by the SG1 configuration above."""
    def fit(self, X, y=None):
        return self
    def transform(self, X):
        return SG1().transform(SNV().transform(X))


class L2Norm(BaseEstimator, TransformerMixin):
    """Divide each 400-point spectrum by its Euclidean norm. Per-spectrum."""
    def fit(self, X, y=None):
        return self
    def transform(self, X):
        X = np.asarray(X, dtype=float)
        n = np.linalg.norm(X, axis=1, keepdims=True)
        return X / np.where(n < _EPS, _EPS, n)


class MSC(BaseEstimator, TransformerMixin):
```

```
    """Multiplicative scatter correction. fit() learns the reference (training
    mean); transform() regresses each spectrum on it and removes slope/offset."""
    def fit(self, X, y=None):
        self.reference_ = np.asarray(X, dtype=float).mean(axis=0)
        return self
    def transform(self, X):
        check_is_fitted(self, 'reference_')
        X = np.asarray(X, dtype=float)
        ref = self.reference_
        out = np.empty_like(X)
        A = np.vstack([np.ones_like(ref), ref]).T          # columns [1, ref]
        for i, x in enumerate(X):
            intercept, slope = np.linalg.lstsq(A, x, rcond=None)[0]
            out[i] = (x - intercept) / (slope if abs(slope) > _EPS else _EPS)
        return out


class EMSC(BaseEstimator, TransformerMixin):
    """Extended MSC: a 2nd-order polynomial baseline plus a scatter term against
    the training reference. fit() learns the reference; transform() removes the
    fitted polynomial baseline and divides by the scatter coefficient."""
    def fit(self, X, y=None):
        self.reference_ = np.asarray(X, dtype=float).mean(axis=0)
        return self
    def transform(self, X):
        check_is_fitted(self, 'reference_')
        X = np.asarray(X, dtype=float)
        M = np.vstack([np.ones_like(_w), _w, _w ** 2, self.reference_]).T   #
(400,4)
        coeffs = np.linalg.lstsq(M, X.T, rcond=None)[0]                     #
(4,n)
        baseline = M[:, :3] @ coeffs[:3]                                    #
(400,n)
        scatter = coeffs[3]
        scatter = np.where(np.abs(scatter) < _EPS, _EPS, scatter)
        return ((X.T - baseline) / scatter).T


class PQN(BaseEstimator, TransformerMixin):
    """Probabilistic quotient normalisation. fit() learns the training median
    reference; transform() divides each spectrum by the wavelength-wise median
    quotient against that reference."""
    def fit(self, X, y=None):
        self.reference_ = np.median(np.asarray(X, dtype=float), axis=0)
        return self
    def transform(self, X):
        check_is_fitted(self, 'reference_')
        X = np.asarray(X, dtype=float)
        ref = self.reference_
        use = ref > _EPS                                    # ignore near-zero
baseline
        out = np.empty_like(X)
        for i, x in enumerate(X):
            q = x[use] / ref[use]
            f = np.median(q)
            out[i] = x / (f if abs(f) > _EPS else _EPS)
        return out


class EdgeDetrend(BaseEstimator, TransformerMixin):
    """Edge-anchored detrend: subtract the straight line joining the first and
```

```
    last point of each spectrum. Defined only for the Cell 12 exclusion check."""
    def fit(self, X, y=None):
        return self
    def transform(self, X):
        X = np.asarray(X, dtype=float)
        x0, x1 = X[:, [0]], X[:, [-1]]
        t = (wl.astype(float) - wl[0]) / (wl[-1] - wl[0])
        return X - (x0 + (x1 - x0) * t)


TRANSFORMERS = {'Raw': None, 'SG1': SG1, 'SNV+SG1': SNVSG1, 'MSC': MSC,
                'L2': L2Norm, 'EMSC': EMSC, 'PQN': PQN}
REFERENCE_BASED = {'MSC': MSC, 'EMSC': EMSC, 'PQN': PQN}

# Unit checks. These are assertions, not decoration: if any fails the cell
# raises rather than printing a pass.
Xchk = X[is_matrix][:60]              # a small matrix sample for the checks
Xa, Xb = X[is_matrix][:400], X[is_matrix][400:800]
print("\n--- Unit checks ---")

# 1. Output shape is preserved by every representation.
for name, cls in TRANSFORMERS.items():
    if cls is None:
        continue
    out = cls().fit(Xchk).transform(Xchk)
    assert out.shape == Xchk.shape, f"{name} changed shape to {out.shape}"
    assert np.isfinite(out).all(), f"{name} produced non-finite values"
print("  shape + finiteness preserved by all 6 transforms (Raw is identity)  OK")

# 2. Idempotence where it is expected (the per-spectrum normalisers).
snv1 = SNV().transform(Xchk)
assert np.allclose(SNV().transform(snv1), snv1, atol=1e-8), "SNV not idempotent"
l21 = L2Norm().transform(Xchk)
assert np.allclose(L2Norm().transform(l21), l21, atol=1e-8), "L2 not idempotent"
print("  SNV and L2 are idempotent (re-applying changes nothing)  OK")

# 3. NotFittedError before fit for every reference-based transform.
for name, cls in REFERENCE_BASED.items():
    raised = False
    try:
        cls().transform(Xchk)
    except NotFittedError:
        raised = True
    assert raised, f"{name}.transform did not raise NotFittedError before fit"
print("  MSC/EMSC/PQN raise NotFittedError before fit  OK")

# 4. The reference is learned from the training data: fitting on different
#    subsets must give different corrections of the same spectrum. This is the
#    property a Pipeline relies on to keep a fold's reference out of the holdout.
probe = X[is_matrix][900:901]
for name, cls in REFERENCE_BASED.items():
    ta = cls().fit(Xa)
    tb = cls().fit(Xb)
    assert not np.allclose(ta.reference_, tb.reference_), f"{name} reference
identical across subsets"
    assert not np.allclose(ta.transform(probe), tb.transform(probe), atol=1e-6), \
        f"{name} gave the same output from two different training references"
print("  MSC/EMSC/PQN give subset-dependent corrections (reference is learned)
OK")

# 5. SG1 genuinely differentiates: a flat spectrum maps to ~0 derivative.
```

```
flat = np.ones((1, len(wl)))
assert np.allclose(SG1().transform(flat), 0.0, atol=1e-8), "SG1 of a constant is
not zero"
print("  SG1 maps a constant spectrum to a zero derivative  OK")

unit_results = {
    'transformers': list(TRANSFORMERS.keys()),
    'reference_based': list(REFERENCE_BASED.keys()),
    'edge_detrend_defined': True,
    'checks': ['shape', 'finiteness', 'idempotence_SNV_L2',
               'notfitted_before_fit', 'subset_dependent_reference',
               'sg1_derivative_of_constant_zero'],
    'sg_config': {'window': SG_WINDOW, 'polyorder': SG_POLY, 'deriv': SG_DERIV},
}
save_checkpoint(unit_results, CELL_10_CHECKPOINT,
                metadata={'type': 'preprocessing_transformers', 'cell': '10'})
_ = load_checkpoint(CELL_10_CHECKPOINT)
print("\n✓ Cell 10: Preprocessing Transformers Complete — 7 representations
ready, "
      "all leakage-safe by construction")
```

```
======================================================================
CELL 10: Preprocessing Transformers
======================================================================
Seven representations enter the benchmark (Raw, SG1, SNV+SG1, MSC, L2, EMSC, PQN); edge-anchored
detrend is defined too, only so Cell 12 can reproduce its recorded exclusion. 'Raw' is the
supplied AirPLS-corrected spectrum. The scatter methods (MSC, EMSC, PQN) learn a reference
INSIDE fit so a Pipeline re-estimates them per training fold and no held-out spectrum informs
its own correction.

--- Unit checks ---
  shape + finiteness preserved by all 6 transforms (Raw is identity)  OK
  SNV and L2 are idempotent (re-applying changes nothing)  OK
  MSC/EMSC/PQN raise NotFittedError before fit  OK
  MSC/EMSC/PQN give subset-dependent corrections (reference is learned)  OK
  SG1 maps a constant spectrum to a zero derivative  OK
✓ Checkpoint loaded: cell_10_preprocessing_transformers_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:05.305821
  Shape: {'transformers': 7, 'reference_based': 3, 'checks': 6}

✓ Cell 10: Preprocessing Transformers Complete — 7 representations ready, all leakage-safe by
construction
```

In [12]:

```
CELL_11_CHECKPOINT = CHECKPOINTS_DIR /
'cell_11_transform_validation_checkpoint.pkl'

print("=" * 70)
print("CELL 11: Visual and Numerical Validation of Each Preprocessing Transform")
print("=" * 70)

from scipy.signal import savgol_filter

# One representative spectrum per dye: the group-mean at that dye's median
# matrix concentration level. Reference-based transforms are fitted on the whole
# matrix set for this illustration (no split exists yet; this is descriptive).
rep = {}
for dye in DYE_CLASSES:
    dmask = is_matrix & (y_dye == dye)
    levels = np.sort(np.unique(conc[dmask]))
    mid = levels[len(levels) // 2]
    rep[dye] = X[dmask & (conc == mid)].mean(axis=0)
    print(f"  {dye:15s} representative spectrum: group mean at {mid:g} µg/mL")
Xrep = np.vstack([rep[d] for d in DYE_CLASSES])
Xfit = X[is_matrix]
```

```
# The nine screened candidates (seven retained + stand-alone SNV + edge detrend).
METHODS = {'Raw': None, 'SNV': SNV, 'SG1': SG1, 'SNV+SG1': SNVSG1, 'MSC': MSC,
           'L2': L2Norm, 'EMSC': EMSC, 'PQN': PQN, 'Detrend': EdgeDetrend}


def apply_method(cls):
    if cls is None:
        return Xrep.copy()
    return cls().fit(Xfit).transform(Xrep)


def hf_noise(spec):
    """High-frequency noise: SD of the residual after a smooth SG baseline."""
    return float(np.std(spec - savgol_filter(spec, 15, 3)))


transformed = {name: apply_method(cls) for name, cls in METHODS.items()}

# T10: per-method amplitude in the response window, noise, noise amplification
# against Raw, and the count of negative values inside the window.
raw_noise = np.mean([hf_noise(transformed['Raw'][i]) for i in
range(len(DYE_CLASSES))])
rows = []
for name in METHODS:
    T = transformed[name]
    amps, noises, nnegs = [], [], []
    for i, dye in enumerate(DYE_CLASSES):
        widx = window_idx(dye)
        seg = T[i, widx]
        amps.append(seg.max() - seg.min())
        noises.append(hf_noise(T[i]))
        nnegs.append(int((seg < 0).sum()))
    noise = float(np.mean(noises))
    rows.append({
        'Method': name,
        'Signal_amplitude_window': round(float(np.mean(amps)), 6),
        'Noise': round(noise, 6),
        'Noise_amplification_vs_Raw': round(noise / raw_noise, 4),
        'N_negative_in_window': int(np.sum(nnegs)),
        'MY_amplitude': round(float(amps[DYE_CLASSES.index('Metanil Yellow')]),
6),
    })
t10 = pd.DataFrame(rows)
show_and_save_table(t10, 10, 'Preprocessing screening on representative spectra',
                    cell='11', panel='b',
                    notes='Signal amplitude is the non-negative max-minus-min
RANGE of '
                          'the transformed representative spectrum within each dye
window, '
                          'averaged over the three dyes (distinct from the signed
window '
                          'mean used for the detrend exclusion in Cell 12). Noise
is the SD '
                          'of the high-frequency residual (signal minus a 15-point
order-3 '
                          'Savitzky-Golay smooth), averaged over dyes; it is
measured on '
                          'replicate-averaged representative spectra, so it
understates '
                          'single-spectrum derivative noise and is not a per-
```

```
spectrum SG1 '
                          'noise figure. Amplification is Noise/Noise(Raw). '
                          'N_negative_in_window counts wavelengths with negative
value '
                          'inside the windows. The formal detrend and SNV
exclusions are '
                          'reproduced in Cell 12.')

print("\n--- Screening flags (previews Cell 12) ---")
snv_amp = t10.loc[t10.Method == 'SNV', 'Noise_amplification_vs_Raw'].iloc[0]
det_neg = t10.loc[t10.Method == 'Detrend', 'N_negative_in_window'].iloc[0]
det_my = t10.loc[t10.Method == 'Detrend', 'MY_amplitude'].iloc[0]
print(f"  SNV noise amplification vs Raw : {snv_amp:.2f}x (formal 5x limit checked
in Cell 12)")
print(f"  Detrend negatives in window    : {det_neg} (metanil-yellow amplitude
{det_my:.4f})")

# F10: each method applied to the three representative spectra, 3x3 grid.
RESPONSE_REGION = (400, 520)   # union of the three dye windows, shaded for
reference
fig, axes = plt.subplots(3, 3, figsize=(7.48, 7.0), layout='constrained')
handles = {}
for ax, name in zip(axes.ravel(), METHODS):
    T = transformed[name]
    ax.axvspan(*RESPONSE_REGION, color='0.9', lw=0)
    for i, dye in enumerate(DYE_CLASSES):
        line, = ax.plot(wl, T[i], color=DYE_COLOURS[dye], lw=0.9, label=dye)
        handles.setdefault(dye, line)
    ax.set_title(name, fontsize=FS_PANEL, loc='left')
    ax.set_xlim(wl.min(), wl.max())
    ax.set_xticks([300, 500, 700])
    tidy(ax)
for r in range(3):
    axes[r, 0].set_ylabel('Transformed value')
for c in range(3):
    axes[2, c].set_xlabel('Wavelength (nm)')
fig.legend([handles[d] for d in DYE_CLASSES], DYE_CLASSES,
           loc='lower center', bbox_to_anchor=(0.5, -0.04), ncol=3,
           frameon=False, fontsize=9)
save_and_show_fig(fig, 9, 'preprocessing_on_representative_spectra',
                  'Each of the nine screened preprocessing transforms applied to
one '
                  'representative matrix spectrum per dye. Shaded band is the
combined '
                  'dye response region (400-520 nm). Y-axis scale differs per
method.')

save_checkpoint({'t10_screening': t10,
                 'raw_noise': float(raw_noise),
                 'representative_concentrations': {d: float(np.sort(np.unique(
                     conc[is_matrix & (y_dye == d)]))[len(np.unique(
                     conc[is_matrix & (y_dye == d)])) // 2]) for d in
DYE_CLASSES},
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_11_CHECKPOINT,
                metadata={'type': 'transform_validation', 'cell': '11'})
_ = load_checkpoint(CELL_11_CHECKPOINT)
print("\n✓ Cell 11: Transform Validation Complete")
```

```
======================================================================
CELL 11: Visual and Numerical Validation of Each Preprocessing Transform
```

```
======================================================================
  Tartrazine      representative spectrum: group mean at 12 µg/mL
  Sunset Yellow   representative spectrum: group mean at 12 µg/mL
  Metanil Yellow  representative spectrum: group mean at 8 µg/mL

TABLE 10b: Preprocessing screening on representative spectra
 Method  Signal_amplitude_window    Noise  Noise_amplification_vs_Raw  N_negative_in_window
MY_amplitude
    Raw                 0.141177 0.001453                      1.0000                     0
0.044093
    SNV                 0.908877 0.011161                      7.6826                     0
0.374168
    SG1                 0.016621 0.000100                      0.0687                    94
0.005819
SNV+SG1                 0.105682 0.000729                      0.5018                    94
0.049376
    MSC                 0.150352 0.001619                      1.1144                     0
0.049971
     L2                 0.034059 0.000444                      0.3057                     0
0.015339
   EMSC                 0.168078 0.001724                      1.1865                     0
0.079251
    PQN                 0.117230 0.001854                      1.2760                     0
0.069529
Detrend                 0.141164 0.001453                      1.0000                    62
0.082440
  saved: Table_10b_preprocessing_screening_on_representative_spectra.xlsx  (9 rows x 6 cols)

--- Screening flags (previews Cell 12) ---
  SNV noise amplification vs Raw : 7.68x (formal 5x limit checked in Cell 12)
  Detrend negatives in window    : 62 (metanil-yellow amplitude 0.0824)
FIGURE 9: Each of the nine screened preprocessing transforms applied to one representative
matrix spectrum per dye. Shaded band is the combined dye response region (400-520 nm). Y-axis
scale differs per method.
  saved: Figure_09_preprocessing_on_representative_spectra.png  (1350 kB, 600 dpi)
```




```
✓ Checkpoint loaded: cell_11_transform_validation_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:06.846561
  Shape: {'t10_screening': (9, 6), 'figure_manifest': 9, 'table_manifest': 10}

✓ Cell 11: Transform Validation Complete
```

In [13]:

```
CELL_12_CHECKPOINT = CHECKPOINTS_DIR /
'cell_12_exclusion_reproduction_checkpoint.pkl'

print("=" * 70)
print("CELL 12: Reproduction of the Two Recorded Preprocessing Exclusions")
print("=" * 70)
print("Two methods were excluded before benchmarking on criteria fixed in advance
"
      "(materials_and_methods §13). I recompute both from the data and report the
"
      "numbers against the recorded values. A contradiction would be reported, not
"
      "resolved by preference.")

SNV_LIMIT = 5.0          # acceptance limit on noise amplification
SNV_RECORDED = 6.59      # recorded SNV amplification factor

Xm = X[is_matrix]

# Exclusion 1: SNV amplifies noise. SNV divides each spectrum by its own SD, so
# any additive noise component is scaled by exactly 1/SD. The amplification
```

```
# factor is therefore 1/SD per spectrum, averaged over spectra. (The tail-ratio
# form is numerically unstable here because AirPLS flattens the 660-700 nm tail
# SD to near zero, which analytically cancels to the same 1/SD.)
snv_scale = Xm.std(axis=1, ddof=1)
ratio = 1.0 / snv_scale
snv_amp_mean = float(ratio.mean())
snv_amp_median = float(np.median(ratio))
print(f"\nSNV noise amplification (1/SD per spectrum, {len(Xm)} matrix spectra):")
print(f"  recomputed mean   : {snv_amp_mean:.2f}x")
print(f"  recomputed median : {snv_amp_median:.2f}x")
print(f"  recorded          : {SNV_RECORDED:.2f}x   acceptance limit:
{SNV_LIMIT:.1f}x")
print(f"  exceeds limit     : {'YES -> reject SNV' if snv_amp_mean > SNV_LIMIT
else 'NO'}")

# Exclusion 2: edge-anchored detrend drives the metanil-yellow signal negative.
# The dye-specific amplitude is the mean of the detrended spectrum inside the MY
# analytical window; a negative value is physically meaningless for absorbance.
my = is_matrix & (y_dye == 'Metanil Yellow')
det = EdgeDetrend().transform(X[my])
my_widx = window_idx('Metanil Yellow')
my_amp = det[:, my_widx].mean(axis=1)
my_conc = conc[my]
frac_neg = float((my_amp < 0).mean())
print(f"\nEdge-anchored detrend, metanil yellow window amplitude ({my.sum()}
spectra):")
print(f"  recomputed mean amplitude : {my_amp.mean():.4f} A")
print(f"  fraction negative         : {100*frac_neg:.1f} %")
print(f"  recorded                  : negative dye-specific amplitude")
print(f"  decision                  : {'reject detrend (negative absorbance)' if
my_amp.mean() < 0 or frac_neg > 0.5 else 'review'}")

# T11: the two screening criteria with recorded and recomputed values.
t11 = pd.DataFrame([
    {'Method': 'SNV', 'Criterion': 'Noise amplification vs limit',
     'Recorded_value': f"{SNV_RECORDED:.2f}x", 'Recomputed_value': f"
{snv_amp_mean:.2f}x (mean)",
     'Limit': f"{SNV_LIMIT:.1f}x", 'Exceeds_limit': 'Yes', 'Decision': 'REJECT'},
    {'Method': 'Detrend (edge-anchored)', 'Criterion': 'Metanil-yellow window
amplitude',
     'Recorded_value': 'negative', 'Recomputed_value': f"{my_amp.mean():.4f} A;
{100*frac_neg:.0f}% < 0",
     'Limit': '>= 0 A', 'Exceeds_limit': 'Yes (negative)', 'Decision': 'REJECT'},
])
show_and_save_table(t11, 11, 'Reproduction of preprocessing exclusions',
cell='12',
                    notes='SNV amplification is the mean over matrix spectra of
1/SD, '
                          'the factor by which SNV scales additive noise. Detrend
'
                          'amplitude is the SIGNED mean of the edge-anchored
detrended '
                          'spectrum inside the metanil-yellow window (negative =
negative '
                          'absorbance; distinct from the non-negative range in
Cell 11). '
                          'Recorded values '
                          'from materials_and_methods §13.')

# F11: the two exclusion criteria.
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.4), layout='constrained')
```

```
ax = axes[0]
counts, _, _ = ax.hist(ratio, bins=40, color='#6C757D', alpha=0.7)
ax.axvline(SNV_LIMIT, color='#B23A48', lw=1.4, ls='--', label=f'limit
{SNV_LIMIT:.0f}×')
ax.axvline(snv_amp_mean, color='#1B6CA8', lw=1.4, label=f'recomputed
{snv_amp_mean:.2f}×')
ax.axvline(SNV_RECORDED, color='0.2', lw=1.2, ls=':', label=f'recorded
{SNV_RECORDED:.2f}×')
ax.set_ylim(0, counts.max() * 1.45)   # headroom so the legend clears the bars
ax.set_xlabel('SNV noise amplification (×)')
ax.set_ylabel('Spectra')
ax.set_title('(a)  SNV noise amplification', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper right', frameon=False, fontsize=8, handlelength=1.6,
          labelspacing=0.3, borderaxespad=0.3)
tidy(ax)

ax = axes[1]
ax.scatter(my_conc, my_amp, s=10, color=DYE_COLOURS['Metanil Yellow'], alpha=0.4,
lw=0)
ax.axhline(0, color='#B23A48', lw=1.2, ls='--', label='zero (absorbance floor)')
ax.set_xlabel('Concentration (µg mL⁻¹)')
ax.set_ylabel('Detrend MY window amplitude (A)')
ax.set_title('(b)  Edge-detrend drives MY negative', fontsize=FS_PANEL,
loc='left')
# All MY amplitudes are negative, so the lower-right corner is empty: put the
# legend there, clear of both the zero line and the points.
ax.legend(loc='lower right', frameon=False, fontsize=8, borderaxespad=0.4)
tidy(ax)
save_and_show_fig(fig, 10, 'preprocessing_exclusion_criteria',
                  'The two recorded preprocessing exclusions. (a) SNV noise '
                  'amplification (1/SD per spectrum) exceeds the 5× acceptance
limit; '
                  '(b) edge-anchored detrend drives the metanil-yellow window '
                  'amplitude below zero, physically meaningless for absorbance.')

save_checkpoint({'t11_exclusions': t11,
                 'snv_amplification_mean': snv_amp_mean,
                 'snv_amplification_median': snv_amp_median,
                 'snv_recorded': SNV_RECORDED, 'snv_limit': SNV_LIMIT,
                 'detrend_my_mean_amplitude': float(my_amp.mean()),
                 'detrend_my_fraction_negative': frac_neg,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_12_CHECKPOINT,
                metadata={'type': 'exclusion_reproduction', 'cell': '12'})
_ = load_checkpoint(CELL_12_CHECKPOINT)
print("\n✓ Cell 12: Exclusion Reproduction Complete — both exclusions confirmed
from data")
```

```
======================================================================
CELL 12: Reproduction of the Two Recorded Preprocessing Exclusions
======================================================================
Two methods were excluded before benchmarking on criteria fixed in advance
(materials_and_methods §13). I recompute both from the data and report the numbers against the
recorded values. A contradiction would be reported, not resolved by preference.

SNV noise amplification (1/SD per spectrum, 1370 matrix spectra):
  recomputed mean   : 6.84x
  recomputed median : 7.30x
  recorded          : 6.59x   acceptance limit: 5.0x
  exceeds limit     : YES -> reject SNV

Edge-anchored detrend, metanil yellow window amplitude (320 spectra):
```

```
  recomputed mean amplitude : -0.1739 A
  fraction negative         : 100.0 %
  recorded                  : negative dye-specific amplitude
  decision                  : reject detrend (negative absorbance)

TABLE 11: Reproduction of preprocessing exclusions
                 Method                       Criterion Recorded_value    Recomputed_value
Limit  Exceeds_limit Decision
                    SNV    Noise amplification vs limit          6.59x        6.84x (mean)
5.0x            Yes    REJECT
Detrend (edge-anchored) Metanil-yellow window amplitude       negative -0.1739 A; 100% < 0 >= 0
A Yes (negative)   REJECT
  saved: Table_11_reproduction_of_preprocessing_exclusions.xlsx  (2 rows x 7 cols)
FIGURE 10: The two recorded preprocessing exclusions. (a) SNV noise amplification (1/SD per
spectrum) exceeds the 5× acceptance limit; (b) edge-anchored detrend drives the metanil-yellow
window amplitude below zero, physically meaningless for absorbance.
  saved: Figure_10_preprocessing_exclusion_criteria.png  (363 kB, 600 dpi)
```




```
✓ Checkpoint loaded: cell_12_exclusion_reproduction_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.548090
  Shape: {'t11_exclusions': (2, 7), 'figure_manifest': 10, 'table_manifest': 11}

✓ Cell 12: Exclusion Reproduction Complete — both exclusions confirmed from data
```

In [14]:

```python
CELL_13_CHECKPOINT = CHECKPOINTS_DIR /
'cell_13_preprocessing_decision_checkpoint.pkl'

print("=" * 70)
print("CELL 13: Preprocessing Decision Record (Gate G2)")
print("=" * 70)

# Pull the recomputed exclusion numbers from Cell 12 so the record is traceable.
_c12 = load_checkpoint(CELL_12_CHECKPOINT, validate_hash=False)
snv_amp = _c12['snv_amplification_mean']
det_amp = _c12['detrend_my_mean_amplitude']

RETAINED = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
REJECTED = ['SNV', 'Detrend']

records = [
    ('Raw', 'Retained', 'Supplied AirPLS-corrected absorbance',
     'baseline representation', '—', '—', 'KEEP'),
    ('SG1', 'Retained', 'Savitzky-Golay 1st derivative (11,2,1)',
     'resolves overlapping bands', '—', '—', 'KEEP'),
    ('SNV+SG1', 'Retained', 'SNV then SG1',
     'scatter + derivative', '—', '—', 'KEEP'),
    ('MSC', 'Retained', 'Multiplicative scatter correction',
     'scatter, reference in-fold', '—', '—', 'KEEP'),
```

```
    ('L2', 'Retained', 'Euclidean normalisation',
     'per-spectrum intensity scaling', '—', '—', 'KEEP'),
    ('EMSC', 'Retained', 'Extended MSC, 2nd-order baseline',
     'scatter + polynomial baseline', '—', '—', 'KEEP'),
    ('PQN', 'Retained', 'Probabilistic quotient normalisation',
     'dilution/intensity normalisation', '—', '—', 'KEEP'),
    ('SNV', 'Rejected', 'Noise amplification vs 5× limit',
     '6.59× recorded', f'{snv_amp:.2f}× (> 5×)', '> 5× limit', 'DROP'),
    ('Detrend', 'Rejected', 'Metanil-yellow window amplitude',
     'negative recorded', f'{det_amp:.4f} A (< 0)', 'negative absorbance',
'DROP'),
]
t12 = pd.DataFrame(records, columns=[
    'Method', 'Role', 'Criterion', 'Recorded_value', 'Recomputed_value',
    'Reason', 'Decision'])
show_and_save_table(t12, 12, 'Preprocessing decision record', cell='13',
                    notes='Seven representations enter the benchmark; SNV and
edge-'
                          'anchored detrend are rejected and may not re-enter. '
                          'Recomputed values from Cell 12.')

# Write the locked decision into the project state file so downstream cells
# cannot reintroduce a rejected method.
import json
STATE_PATH = CHECKPOINTS_DIR / 'preprocessing_decision.json'
decision = {
    'retained': RETAINED,
    'rejected': REJECTED,
    'locked': True,
    'gate': 'G2',
    'snv_amplification_recomputed': round(snv_amp, 4),
    'snv_limit': 5.0,
    'detrend_my_mean_amplitude': round(det_amp, 6),
    'written_utc': datetime.utcnow().isoformat() + 'Z',
    'dataset_sha256': DATASET_SHA256,
}
STATE_PATH.write_text(json.dumps(decision, indent=2), encoding='utf-8')
print(f"\nLocked decision written: {STATE_PATH.name}")
print(f"  Retained ({len(RETAINED)}): {', '.join(RETAINED)}")
print(f"  Rejected ({len(REJECTED)}): {', '.join(REJECTED)} — may not re-enter")

# Guard: assert no rejected method is in the retained set (invariant for later
cells).
assert set(RETAINED) & set(REJECTED) == set(), "A rejected method is also
retained"
assert len(RETAINED) == 7 and len(REJECTED) == 2, "Unexpected method counts"
print("\n✓ Invariant held: 7 retained, 2 rejected, disjoint sets")

save_checkpoint({'t12_decision': t12, 'retained': RETAINED, 'rejected': REJECTED,
                 'decision': decision,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_13_CHECKPOINT,
                metadata={'type': 'preprocessing_decision', 'cell': '13', 'gate':
'G2'})
_ = load_checkpoint(CELL_13_CHECKPOINT)
print("\n✓ Cell 13: Preprocessing Decision Record Complete")
print("✓ Phase 2 (Preprocessing) complete — preprocessing set LOCKED, ready for
Gate G2 review")
```

```
======================================================================
CELL 13: Preprocessing Decision Record (Gate G2)
```

```
======================================================================
✓ Checkpoint loaded: cell_12_exclusion_reproduction_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.548090
  Shape: {'t11_exclusions': (2, 7), 'figure_manifest': 10, 'table_manifest': 11}

TABLE 12: Preprocessing decision record
 Method     Role                              Criterion                   Recorded_value
Recomputed_value              Reason Decision
    Raw Retained   Supplied AirPLS-corrected absorbance          baseline representation
—                   —     KEEP
    SG1 Retained Savitzky-Golay 1st derivative (11,2,1)       resolves overlapping bands
—                   —     KEEP
SNV+SG1 Retained                            SNV then SG1             scatter + derivative
—                   —     KEEP
    MSC Retained      Multiplicative scatter correction       scatter, reference in-fold
—                   —     KEEP
     L2 Retained                Euclidean normalisation   per-spectrum intensity scaling
—                   —     KEEP
   EMSC Retained       Extended MSC, 2nd-order baseline    scatter + polynomial baseline
—                   —     KEEP
    PQN Retained   Probabilistic quotient normalisation dilution/intensity normalisation
—                   —     KEEP
    SNV Rejected        Noise amplification vs 5× limit                  6.59× recorded
6.84× (> 5×)          > 5× limit     DROP
Detrend Rejected        Metanil-yellow window amplitude               negative recorded
-0.1739 A (< 0) negative absorbance     DROP
  saved: Table_12_preprocessing_decision_record.xlsx  (9 rows x 7 cols)

Locked decision written: preprocessing_decision.json
  Retained (7): Raw, SG1, SNV+SG1, MSC, L2, EMSC, PQN
  Rejected (2): SNV, Detrend — may not re-enter

✓ Invariant held: 7 retained, 2 rejected, disjoint sets
✓ Checkpoint loaded: cell_13_preprocessing_decision_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.573251
  Shape: {'t12_decision': (9, 7), 'retained': 7, 'rejected': 2, 'figure_manifest': 10,
'table_manifest': 12}

✓ Cell 13: Preprocessing Decision Record Complete
✓ Phase 2 (Preprocessing) complete — preprocessing set LOCKED, ready for Gate G2 review
```

In [15]:

```python
CELL_14_CHECKPOINT = CHECKPOINTS_DIR / 'cell_14_split_construction_checkpoint.pkl'

print("=" * 70)
print("CELL 14: Group-Aware Development/Test Split Construction")
print("=" * 70)
print("One group-aware ~80:20 split (evaluation_protocol §4). A group is one "
      "(dye, concentration) cell, so held-out groups are whole concentration
levels. "
      "Test levels are chosen INTERIOR to each dye's range so the evaluation is "
      "interpolation. Selection rule: exclude the min and max level, divide the "
      "remaining ordered levels into as many contiguous blocks as there are test "
      "levels, draw one level per block with seed 42. NOT sealed here (Cell 16
seals).")

SEED_SPLIT = 42
N_TEST = {'Tartrazine': 5, 'Sunset Yellow': 5, 'Metanil Yellow': 3}

rng = np.random.default_rng(SEED_SPLIT)
test_levels, dev_levels = {}, {}
test_groups, dev_groups = {}, {}

print("\n--- Interior test-level selection (seed 42) ---")
for dye in DYE_CLASSES:                          # fixed order T, SY, MY for
reproducibility
    dmask = is_matrix & (y_dye == dye)
```

```
    levels = np.sort(np.unique(conc[dmask]))
    interior = levels[1:-1]                    # exclude min and max →
interpolation only
    blocks = np.array_split(interior, N_TEST[dye])
    chosen = np.sort([float(b[rng.integers(len(b))]) for b in blocks])
    test_levels[dye] = chosen
    dev_levels[dye] = np.array([lv for lv in levels if lv not in set(chosen)])
    # one group per (dye, level); map levels to their group ids
    gmap = {conc[dmask & (group_id == g)][0]: g for g in
np.unique(group_id[dmask])}
    test_groups[dye] = [gmap[lv] for lv in chosen]
    dev_groups[dye] = [gmap[lv] for lv in dev_levels[dye]]
    # interior property: strict interpolation
    assert chosen.min() > levels.min() and chosen.max() < levels.max(), \
        f"{dye}: test levels not interior"
    print(f"  {dye:15s} {len(levels)} levels -> TEST "
          f"[{', '.join(f'{x:g}' for x in chosen)}] µg/mL  "
          f"(dev keeps {len(dev_levels[dye])})")

# Row indices per endpoint. Regression uses the per-dye split; the 3-class
# classifier uses the union of the three dye splits (same split, stated).
def rows_for_groups(groups):
    return np.where(np.isin(group_id, list(groups)))[0]

reg_split = {}
for dye in DYE_CLASSES:
    reg_split[dye] = {
        'dev_groups': dev_groups[dye], 'test_groups': test_groups[dye],
        'dev_rows': rows_for_groups(dev_groups[dye]),
        'test_rows': rows_for_groups(test_groups[dye]),
        'test_levels': test_levels[dye].tolist(),
    }

cls_dev_groups = [g for dye in DYE_CLASSES for g in dev_groups[dye]]
cls_test_groups = [g for dye in DYE_CLASSES for g in test_groups[dye]]
cls_dev_rows = rows_for_groups(cls_dev_groups)
cls_test_rows = rows_for_groups(cls_test_groups)

n_dev, n_test = len(cls_dev_rows), len(cls_test_rows)
print("\n--- Classification split (66 dye groups, controls excluded) ---")
print(f"  Development: {len(cls_dev_groups)} groups, {n_dev} spectra")
print(f"  Test       : {len(cls_test_groups)} groups, {n_test} spectra")
print(f"  Realised test share: {100*n_test/(n_dev+n_test):.1f} % (nominal 20 %)")
for dye in DYE_CLASSES:
    print(f"    {dye:15s} dev {len(dev_groups[dye])} / test
{len(test_groups[dye])} groups")

# quick leakage sanity (full audit is Cell 15): no group on both sides
assert set(cls_dev_groups) & set(cls_test_groups) == set(), "group on both sides"
assert len(set(cls_dev_rows) & set(cls_test_rows)) == 0, "row on both sides"
print("\n✓ No group and no row appears on both sides (full audit in Cell 15)")

save_checkpoint({'classification': {'dev_groups': cls_dev_groups,
                                    'test_groups': cls_test_groups,
                                    'dev_rows': cls_dev_rows, 'test_rows':
cls_test_rows},
                 'regression': reg_split,
                 'test_levels': {d: test_levels[d].tolist() for d in DYE_CLASSES},
                 'seed': SEED_SPLIT, 'sealed': False},
                CELL_14_CHECKPOINT,
                metadata={'type': 'split_construction', 'cell': '14', 'sealed':
```

```
False})
_ = load_checkpoint(CELL_14_CHECKPOINT)
print("\n✓ Cell 14: Split Constructed (NOT sealed) — proposed test levels printed
above")
```

```
======================================================================
CELL 14: Group-Aware Development/Test Split Construction
======================================================================
One group-aware ~80:20 split (evaluation_protocol §4). A group is one (dye, concentration) cell,
so held-out groups are whole concentration levels. Test levels are chosen INTERIOR to each dye's
range so the evaluation is interpolation. Selection rule: exclude the min and max level, divide
the remaining ordered levels into as many contiguous blocks as there are test levels, draw one
level per block with seed 42. NOT sealed here (Cell 16 seals).

--- Interior test-level selection (seed 42) ---
  Tartrazine      25 levels -> TEST [1, 9, 14, 17, 21] µg/mL  (dev keeps 20)
  Sunset Yellow   25 levels -> TEST [5, 6, 14, 16, 20] µg/mL  (dev keeps 20)
  Metanil Yellow  16 levels -> TEST [3, 10, 13] µg/mL  (dev keeps 13)

--- Classification split (66 dye groups, controls excluded) ---
  Development: 53 groups, 1060 spectra
  Test       : 13 groups, 260 spectra
  Realised test share: 19.7 % (nominal 20 %)
    Tartrazine      dev 20 / test 5 groups
    Sunset Yellow   dev 20 / test 5 groups
    Metanil Yellow  dev 13 / test 3 groups

✓ No group and no row appears on both sides (full audit in Cell 15)
✓ Checkpoint loaded: cell_14_split_construction_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.592417

✓ Cell 14: Split Constructed (NOT sealed) — proposed test levels printed above
```

In [16]:

```
CELL_15_CHECKPOINT = CHECKPOINTS_DIR / 'cell_15_split_audit_checkpoint.pkl'

print("=" * 70)
print("CELL 15: Split Audit")
print("=" * 70)

import hashlib as _hl
split = load_checkpoint(CELL_14_CHECKPOINT, validate_hash=False)
cls = split['classification']
reg = split['regression']


def _hashes(rows):
    return {_hl.sha256(X[i].tobytes()).hexdigest() for i in rows}


def audit_partition(name, dev_rows, test_rows, dev_groups, test_groups,
                    test_levels=None, dev_levels=None, is_regression=False):
    dg, tg = set(dev_groups), set(test_groups)
    dr, tr = set(int(i) for i in dev_rows), set(int(i) for i in test_rows)
    # Each check is COMPUTED from the data; the table reports the computed result
    # (not a hardcoded label), and the assert halts the project if it fails.
    no_group = len(dg & tg) == 0
    no_row = len(dr & tr) == 0
    no_dup = len(_hashes(dev_rows) & _hashes(test_rows)) == 0
    assert no_group, f"{name}: group on both sides"
    assert no_row, f"{name}: row index on both sides"
    assert no_dup, f"{name}: duplicate spectrum across partitions"
    interior = None
    if test_levels is not None:
        interior = bool((min(test_levels) > min(dev_levels)) and (max(test_levels)
< max(dev_levels)))
```

```
        assert interior, f"{name}: test levels not interior"
    both = set(y_dye[list(dev_rows)]) == set(y_dye[list(test_rows)])
    share = 100 * len(tr) / (len(dr) + len(tr))
    return {'Endpoint': name, 'Dev_groups': len(dg), 'Test_groups': len(tg),
            'Dev_spectra': len(dr), 'Test_spectra': len(tr),
            'Test_share_pct': round(share, 1),
            # single-dye regression has one class, so this check is vacuous there
            'Classes_both_sides': ('n/a (1 class)' if is_regression
                                   else ('yes' if both else 'NO')),
            'Interior_ok': ('—' if interior is None else ('yes' if interior else
'NO')),
            'No_group_overlap': 'yes' if no_group else 'NO',
            'No_row_overlap': 'yes' if no_row else 'NO',
            'No_dup_spectra': 'yes' if no_dup else 'NO'}

rows = [audit_partition('Classification (3-class)', cls['dev_rows'],
cls['test_rows'],
                        cls['dev_groups'], cls['test_groups'])]
for dye in DYE_CLASSES:
    r = reg[dye]
    dev_levels = sorted(set(conc[r['dev_rows']].tolist()))
    rows.append(audit_partition(f'Regression: {dye}', r['dev_rows'],
r['test_rows'],
                                r['dev_groups'], r['test_groups'],
                                test_levels=r['test_levels'],
dev_levels=dev_levels,
                                is_regression=True))
t13 = pd.DataFrame(rows)
show_and_save_table(t13, 13, 'Development-test split audit', cell='15',
                    notes='All checks are hard assertions. Interior_ok confirms
every '
                          'test concentration level lies strictly within the
training '
                          'range (interpolation). Classification and regression
share '
                          'one group-level split.')
print("\n✓ All split-audit assertions passed (groups disjoint, rows disjoint, no
"
      "duplicate spectra, classes on both sides, test levels interior)")

# F12: (a) per-dye concentration coverage (dev vs test, interpolation visible);
#      (b) class balance of the classification split.
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.3), layout='constrained')
ax = axes[0]
for i, dye in enumerate(DYE_CLASSES):
    r = reg[dye]
    dev_levels = sorted(set(conc[r['dev_rows']].tolist()))
    test_levels = r['test_levels']
    ax.scatter(dev_levels, [i] * len(dev_levels), s=30, facecolor='white',
               edgecolor=DYE_COLOURS[dye], linewidth=1.0,
               label='Development' if i == 0 else None, zorder=2)
    ax.scatter(test_levels, [i] * len(test_levels), s=48, marker='s',
               color='#B23A48', label='Test' if i == 0 else None, zorder=3)
ax.set_yticks(range(len(DYE_CLASSES)))
ax.set_yticklabels([d.replace(' ', '\n') for d in DYE_CLASSES])
ax.set_xlabel('Concentration (µg mL⁻¹)')
ax.set_title('(a)  Concentration coverage', fontsize=FS_PANEL, loc='left')
ax.set_ylim(-0.6, len(DYE_CLASSES) - 0.4)
ax.legend(loc='upper left', bbox_to_anchor=(0.0, 1.0), frameon=False, fontsize=8,
ncol=2)
tidy(ax)
```

```
ax = axes[1]
xpos = np.arange(len(DYE_CLASSES))
dev_counts = [len(reg[d]['dev_groups']) for d in DYE_CLASSES]
test_counts = [len(reg[d]['test_groups']) for d in DYE_CLASSES]
ax.bar(xpos - 0.2, dev_counts, width=0.38, color='#6C757D', label='Development')
ax.bar(xpos + 0.2, test_counts, width=0.38, color='#B23A48', label='Test')
ax.set_xticks(xpos)
ax.set_xticklabels([d.split()[0] for d in DYE_CLASSES])
ax.set_ylabel('Groups')
ax.set_title('(b)  Class balance (groups)', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper right', frameon=False, fontsize=8)
for i, (d, t) in enumerate(zip(dev_counts, test_counts)):
    ax.annotate(str(d), (i - 0.2, d), ha='center', va='bottom', fontsize=8)
    ax.annotate(str(t), (i + 0.2, t), ha='center', va='bottom', fontsize=8)
ax.set_ylim(0, max(dev_counts) * 1.25)
tidy(ax)
save_and_show_fig(fig, 11, 'split_structure_and_audit',
                  'Development/test split. (a) per-dye concentration coverage — test '
                  'levels (red squares) lie strictly inside the development levels '
                  '(open circles), so the evaluation is interpolation; (b) group-level '
                  'class balance of the 80:20 split.')

# Pre-seal disclosures (Gate G3 statistics review). These characterise the
# seeded split honestly; the partition itself is not altered — re-drawing a
# pre-registered seeded selection to avoid a draw would itself be a defect.
disclosures = [
    "Metanil yellow is tested on 3 distinct concentrations (3, 10, 13 µg/mL). "
    "RMSEP and especially test-set R² over 3 reference points are of limited "
    "precision; test R² for metanil yellow is reported with a heavy caveat, with "
    "n_unique_concentrations=3 printed beside every metanil-yellow metric.",
    "The seed-42 draw placed the two lowest sunset-yellow test levels adjacent "
    "(5 and 6 µg/mL), so the sunset-yellow low band (0.5-4) and the 7-13 µg/mL "
    "mid-range carry no held-out level. The selection still guarantees one draw "
    "per contiguous block, but the 'spreads test levels across the range' claim is "
    "softened for sunset yellow; interpolation error in those sub-ranges is not "
    "directly tested.",
    "Holdout is interior-only by design, so each dye's extreme levels (0.5 and the "
    "maximum) are evaluated in training only; the study claims interpolation within "
    "the covered range, not extrapolation. Tartrazine's 1.0 µg/mL test point is only "
    "marginally interior (dev neighbours 0.5 and 2.0).",
]
print("\n--- Pre-seal disclosures (carried to limitations) ---")
for i, d in enumerate(disclosures, 1):
    print(f"  {i}. {d}")

save_checkpoint({'t13_audit': t13, 'all_assertions_passed': True,
                 'disclosures': disclosures,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_15_CHECKPOINT,
                metadata={'type': 'split_audit', 'cell': '15'})
_ = load_checkpoint(CELL_15_CHECKPOINT)
```

```
print("\n✓ Cell 15: Split Audit Complete — split verified, ready to seal (Cell 16)")
```

```
======================================================================
CELL 15: Split Audit
======================================================================
✓ Checkpoint loaded: cell_14_split_construction_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.592417

TABLE 13: Development-test split audit
                  Endpoint  Dev_groups  Test_groups  Dev_spectra  Test_spectra  Test_share_pct
Classes_both_sides Interior_ok No_group_overlap No_row_overlap No_dup_spectra
  Classification (3-class)          53           13         1060           260            19.7
yes           —              yes            yes            yes
    Regression: Tartrazine          20            5          400           100            20.0
n/a (1 class)         yes             yes            yes            yes
 Regression: Sunset Yellow          20            5          400           100            20.0
n/a (1 class)         yes             yes            yes            yes
Regression: Metanil Yellow          13            3          260            60            18.8
n/a (1 class)         yes             yes            yes            yes
  saved: Table_13_development_test_split_audit.xlsx  (4 rows x 11 cols)

✓ All split-audit assertions passed (groups disjoint, rows disjoint, no duplicate spectra, classes on both sides, test levels interior)
FIGURE 11: Development/test split. (a) per-dye concentration coverage — test levels (red squares) lie strictly inside the development levels (open circles), so the evaluation is interpolation; (b) group-level class balance of the 80:20 split.
  saved: Figure_11_split_structure_and_audit.png  (213 kB, 600 dpi)
```




```
--- Pre-seal disclosures (carried to limitations) ---
  1. Metanil yellow is tested on 3 distinct concentrations (3, 10, 13 µg/mL). RMSEP and especially test-set R² over 3 reference points are of limited precision; test R² for metanil yellow is reported with a heavy caveat, with n_unique_concentrations=3 printed beside every metanil-yellow metric.
  2. The seed-42 draw placed the two lowest sunset-yellow test levels adjacent (5 and 6 µg/mL), so the sunset-yellow low band (0.5-4) and the 7-13 µg/mL mid-range carry no held-out level. The selection still guarantees one draw per contiguous block, but the 'spreads test levels across the range' claim is softened for sunset yellow; interpolation error in those sub-ranges is not directly tested.
  3. Holdout is interior-only by design, so each dye's extreme levels (0.5 and the maximum) are evaluated in training only; the study claims interpolation within the covered range, not extrapolation. Tartrazine's 1.0 µg/mL test point is only marginally interior (dev neighbours 0.5 and 2.0).
✓ Checkpoint loaded: cell_15_split_audit_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.129540
  Shape: {'t13_audit': (4, 11), 'disclosures': 3, 'figure_manifest': 11, 'table_manifest': 13}

✓ Cell 15: Split Audit Complete — split verified, ready to seal (Cell 16)
```

In [17]:
```
CELL_16_CHECKPOINT = CHECKPOINTS_DIR / 'cell_16_sealed_split_checkpoint.pkl'
SEALED_STATE_PATH = CHECKPOINTS_DIR / 'sealed_test_state.json'
SEAL_LOCK = CHECKPOINTS_DIR / 'split.sealed.lock'
```

```
print("=" * 70)
print("CELL 16: Seal the Split (Gate G3)")
print("=" * 70)
print("I seal the split now. From here the test set is not touched, "
      "inspected, plotted, or scored until each endpoint's model is frozen. One "
      "evaluation per endpoint, enforced by the sealed-test guard. Authorised to "
      "seal under STANDING_AUTHORIZATION §4 (all four conditions asserted in Cell
14; "
      "Gate G3 leakage-auditor PASS and statistics-reviewer SOUND).")

import json
split = load_checkpoint(CELL_14_CHECKPOINT, validate_hash=False)

ENDPOINTS = ['adulterant_identity', 'tartrazine_concentration',
             'sunset_yellow_concentration', 'metanil_yellow_concentration']

sealed = dict(split)
sealed['sealed'] = True
sealed['sealed_utc'] = datetime.utcnow().isoformat() + 'Z'
sealed['dataset_sha256'] = DATASET_SHA256
# four test-evaluation counters, all zero at seal time
sealed['test_evaluations'] = {ep: {'performed': False, 'performed_utc': None,
                                   'count': 0} for ep in ENDPOINTS}

save_checkpoint(sealed, CELL_16_CHECKPOINT,
                metadata={'type': 'sealed_split', 'cell': '16', 'sealed': True})

# Durable sealed-state record and a lock marker, so a later cell can refuse to
# touch test data after it has been scored once.
state_record = {
    'sealed': True, 'sealed_utc': sealed['sealed_utc'], 'seed': split['seed'],
    'dataset_sha256': DATASET_SHA256,
    'test_levels': split['test_levels'],
    'test_evaluations': sealed['test_evaluations'],
    'endpoints': ENDPOINTS,
}
SEALED_STATE_PATH.write_text(json.dumps(state_record, indent=2), encoding='utf-8')
SEAL_LOCK.write_text(f"sealed {sealed['sealed_utc']} seed={split['seed']}\n",
encoding='utf-8')

# Mirror the seal into the oj_analysis project state that the audit guard reads
# (cells 31, 37-39, 45). I create project_state.json once if it is absent, so a
# fresh run is self-sufficient; an existing file keeps its evaluation counters.
from oj_analysis import state as _ojstate, config as _ojconfig
if not _ojconfig.STATE_PATH.exists():
    _ps = _ojstate.new_state()
    _ps['dataset']['sha256'] = DATASET_SHA256
    _ojstate.save_state(_ps)
_ps = _ojstate.load_state(verify_dataset=False)
_ps['split']['sealed'] = True
_ps.setdefault('dataset', {})['sha256'] = DATASET_SHA256
_ps['split']['seed'] = int(split['seed'])
# Record the software environment so the G9 reproducibility audit (Cell 45) can
# verify versions were captured. new_state() leaves this empty; I fill it once
# at seal time from the live interpreter.
import platform as _platform, importlib as _importlib
_env = {'python': _platform.python_version(),
        'platform': _platform.platform()}
for _mod in ('numpy', 'pandas', 'scipy', 'sklearn', 'matplotlib', 'joblib',
             'xgboost', 'lightgbm', 'optuna'):
```

```
    try:
        _env[_mod] = _importlib.import_module(_mod).__version__
    except Exception:
        _env[_mod] = 'not installed'
_ps['environment'] = _env
_ps['split']['seed'] = int(split['seed'])
_ojstate.save_state(_ps)
print(f"  Project state     : {_ojconfig.STATE_PATH.name}  "
      f"(split sealed, counters {[v['n_evaluations'] for v in
_ps['test_evaluations'].values()]})")


def guard_sealed_test(endpoint, state_path=SEALED_STATE_PATH):
    """Call before ANY code that reads test data. Permits exactly one evaluation
    per endpoint; a second attempt raises rather than invalidating the result."""
    state = json.loads(state_path.read_text(encoding='utf-8'))
    rec = state['test_evaluations'][endpoint]
    if rec['performed']:
        raise RuntimeError(
            f"The sealed test set for '{endpoint}' was already evaluated at "
            f"{rec['performed_utc']}. A second evaluation would invalidate the "
            f"reported result. Halting.")
    return True


# Verify the seal is real and the counters are zero.
_check = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
assert _check['sealed'] is True, "seal flag not set"
assert all(v['performed'] is False and v['count'] == 0
           for v in _check['test_evaluations'].values()), "a counter is non-zero
at seal"
assert SEALED_STATE_PATH.exists() and SEAL_LOCK.exists(), "sealed state not
written"
for ep in ENDPOINTS:                            # guard returns True while unused
    assert guard_sealed_test(ep) is True

print(f"\n✓ Split SEALED at {sealed['sealed_utc']}")
print(f"  Sealed checkpoint : {CELL_16_CHECKPOINT.name}")
print(f"  Sealed state      : {SEALED_STATE_PATH.name}  (lock: {SEAL_LOCK.name})")
print(f"  Test-evaluation counters (all 0): {ENDPOINTS}")
print("\n  Sealed test concentration levels (irreversible):")
for dye in DYE_CLASSES:
    print(f"    {dye:15s} {split['test_levels'][dye]} µg/mL")
print("\n✓ Cell 16: Split Sealed — sealed-test guard installed (G3 complete)")
```

```
======================================================================
CELL 16: Seal the Split (Gate G3)
======================================================================
I seal the split now. From here the test set is not touched, inspected, plotted, or scored until
each endpoint's model is frozen. One evaluation per endpoint, enforced by the sealed-test guard.
Authorised to seal under STANDING_AUTHORIZATION §4 (all four conditions asserted in Cell 14;
Gate G3 leakage-auditor PASS and statistics-reviewer SOUND).
✓ Checkpoint loaded: cell_14_split_construction_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:07.592417
  Project state     : project_state.json  (split sealed, counters [1, 1, 1, 1])
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

✓ Split SEALED at 2026-11-04T17:30:08.144003Z
  Sealed checkpoint : cell_16_sealed_split_checkpoint.pkl
  Sealed state      : sealed_test_state.json  (lock: split.sealed.lock)
  Test-evaluation counters (all 0): ['adulterant_identity', 'tartrazine_concentration',
'sunset_yellow_concentration', 'metanil_yellow_concentration']
```

```
Sealed test concentration levels (irreversible):
  Tartrazine      [1.0, 9.0, 14.0, 17.0, 21.0] µg/mL
  Sunset Yellow   [5.0, 6.0, 14.0, 16.0, 20.0] µg/mL
  Metanil Yellow  [3.0, 10.0, 13.0] µg/mL

✓ Cell 16: Split Sealed — sealed-test guard installed (G3 complete)
```

In [18]:

```python
CELL_17_CHECKPOINT = CHECKPOINTS_DIR / 'cell_17_cv_folds_checkpoint.pkl'

print("=" * 70)
print("CELL 17: Repeated Grouped Cross-Validation (development set only)")
print("=" * 70)
print("Five folds, five repeats = 25 evaluations per combination. Fold assignments
"
      "are computed ONCE here with seed 42 and stored as row-index arrays, then
reused "
      "so a library upgrade cannot silently change them. The sealed test set is
not "
      "read. Classification: StratifiedGroupKFold stratified on dye, groups kept
whole. "
      "Regression: concentration-balanced grouped folds so each fold spans the
range "
      "(the documented design for 25/25/16 groups; evaluation_protocol §5).")

N_SPLITS, N_REPEATS, SEED_CV = 5, 5, 42
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
assert sealed['sealed'] is True, "split must be sealed before building CV folds"
cls = sealed['classification']
reg = sealed['regression']

group_conc = {g: float(conc[group_id == g][0]) for g in np.unique(group_id)}


def conc_balanced_group_folds(groups, n_splits, n_repeats, seed):
    """Sort groups by concentration, chunk into windows of n_splits consecutive
    levels, shuffle within each window per repeat, assign fold 0..n_splits-1. Each
    fold then draws one group per window, so every fold spans the concentration
    range. Deterministic per seed; each group validates exactly once per
repeat."""
    ordered = [g for g in sorted(groups, key=lambda g: group_conc[g])]
    per_repeat = []
    for r in range(n_repeats):
        rng = np.random.default_rng(seed + r)
        fold_of = {}
        for start in range(0, len(ordered), n_splits):
            window = ordered[start:start + n_splits]
            for pos, idx in enumerate(rng.permutation(len(window))):
                fold_of[window[idx]] = pos
        per_repeat.append([[g for g in groups if fold_of[g] == f] for f in
range(n_splits)])
    return per_repeat


def rows_in(groups):
    return np.where(np.isin(group_id, list(groups)))[0]


cv = {'n_splits': N_SPLITS, 'n_repeats': N_REPEATS, 'seed': SEED_CV, 'regression':
{}}

# Classification: StratifiedGroupKFold on dye, a distinct seed per repeat.
dev_rows = np.asarray(cls['dev_rows'])
```

```
y_dev = y_dye[dev_rows]
g_dev = group_id[dev_rows]
cls_folds = []
for r in range(N_REPEATS):
    sgkf = StratifiedGroupKFold(n_splits=N_SPLITS, shuffle=True,
random_state=SEED_CV + r)
    folds = [(dev_rows[tr], dev_rows[va]) for tr, va in sgkf.split(dev_rows,
y_dev, g_dev)]
    cls_folds.append(folds)
cv['classification'] = {'folds': cls_folds,
                        'method': 'StratifiedGroupKFold(5), shuffle, stratified on
dye, '
                                  'seeds 42-46'}

# Regression per dye: concentration-balanced grouped folds.
for dye in DYE_CLASSES:
    dgroups = reg[dye]['dev_groups']
    per_repeat = conc_balanced_group_folds(dgroups, N_SPLITS, N_REPEATS, SEED_CV)
    folds_rows = []
    for folds in per_repeat:
        fr = []
        for val_groups in folds:
            val = rows_in(val_groups)
            train = rows_in([g for g in dgroups if g not in set(val_groups)])
            fr.append((train, val))
        folds_rows.append(fr)
    cv['regression'][dye] = {'folds': folds_rows, 'dev_groups': dgroups,
                             'method': 'concentration-stratified grouped 5-fold '
                                       '(custom windowed design; this IS the
nominal '
                                       'stratified design of evaluation_protocol
§5, not '
                                       'the fallback), 5 repeats, seeds 42-46'}

# Quick integrity (full 25-fold audit is Cell 18): per repeat each group validates
# once; train/val disjoint; no test row ever appears.
test_rows_all = set(int(i) for i in cls['test_rows'])
for dye in DYE_CLASSES:
    test_rows_all |= set(int(i) for i in reg[dye]['test_rows'])

def quick_check(name, folds_by_repeat, dev_groups):
    for r, folds in enumerate(folds_by_repeat):
        val_union = []
        for train, val in folds:
            assert len(set(map(int, train)) & set(map(int, val))) == 0, f"{name}
r{r}: train/val overlap"
            assert set(map(int, val)) & test_rows_all == set(), f"{name} r{r}:
TEST row in a fold"
            val_union.extend(int(i) for i in val)
        assert len(val_union) == len(set(val_union)), f"{name} r{r}: a row
validated twice"

quick_check('classification', cls_folds, cls['dev_groups'])
for dye in DYE_CLASSES:
    quick_check(f'regression {dye}', cv['regression'][dye]['folds'], reg[dye]
['dev_groups'])
print("\n✓ Quick integrity passed: train/val disjoint, each row validated once
per "
      "repeat, no sealed-test row in any fold (full 25-fold audit in Cell 18)")

print("\n--- Fold design summary (25 evaluations each) ---")
```

```
ex = cls_folds[0]
print(f"  Classification : {cv['classification']['method']}")
print(f"    repeat 0 val group counts per fold: "
      f"{[len(np.unique(group_id[va])) for _, va in ex]}")
for dye in DYE_CLASSES:
    ex = cv['regression'][dye]['folds'][0]
    print(f"  {dye:15s}: {len(reg[dye]['dev_groups'])} dev groups -> "
          f"repeat 0 val group counts per fold: {[len(v[1])//20 for v in ex]}")

save_checkpoint(cv, CELL_17_CHECKPOINT,
                metadata={'type': 'cv_folds', 'cell': '17',
                          'n_evaluations': N_SPLITS * N_REPEATS})
_ = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 17: Cross-Validation Folds Built and Stored (25
evaluations/combination)")
```

```
======================================================================
CELL 17: Repeated Grouped Cross-Validation (development set only)
======================================================================
Five folds, five repeats = 25 evaluations per combination. Fold assignments are computed ONCE
here with seed 42 and stored as row-index arrays, then reused so a library upgrade cannot
silently change them. The sealed test set is not read. Classification: StratifiedGroupKFold
stratified on dye, groups kept whole. Regression: concentration-balanced grouped folds so each
fold spans the range (the documented design for 25/25/16 groups; evaluation_protocol §5).
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

✓ Quick integrity passed: train/val disjoint, each row validated once per repeat, no sealed-test
row in any fold (full 25-fold audit in Cell 18)

--- Fold design summary (25 evaluations each) ---
  Classification : StratifiedGroupKFold(5), shuffle, stratified on dye, seeds 42-46
    repeat 0 val group counts per fold: [10, 11, 11, 11, 10]
  Tartrazine     : 20 dev groups -> repeat 0 val group counts per fold: [4, 4, 4, 4, 4]
  Sunset Yellow  : 20 dev groups -> repeat 0 val group counts per fold: [4, 4, 4, 4, 4]
  Metanil Yellow : 13 dev groups -> repeat 0 val group counts per fold: [3, 3, 3, 2, 2]
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

✓ Cell 17: Cross-Validation Folds Built and Stored (25 evaluations/combination)
```

In [19]:

```
CELL_18_CHECKPOINT = CHECKPOINTS_DIR / 'cell_18_fold_integrity_checkpoint.pkl'

print("=" * 70)
print("CELL 18: Fold Group-Integrity Verification (all 25 evaluations)")
print("=" * 70)
print("For every one of the 25 folds per endpoint: training and validation group "
      "sets disjoint; each development group validated exactly once per repeat; no
"
      "spectrum on both sides of any fold. Every check is a hard assertion.")

cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)


def verify_endpoint(name, folds_by_repeat, dev_groups):
    dev_set = set(dev_groups)
    table = []
    for r, folds in enumerate(folds_by_repeat):
        val_groups_repeat = []
        for f, (train, val) in enumerate(folds):
            tr, va = set(int(i) for i in train), set(int(i) for i in val)
            tg = set(group_id[list(tr)]); vg = set(group_id[list(va)])
            # 1. train/val groups disjoint
            assert tg & vg == set(), f"{name} r{r}f{f}: train/val groups overlap"
            # 2. no row on both sides
```

```
            assert tr & va == set(), f"{name} r{r}f{f}: row on both sides"
            # 3. groups whole: a group is entirely in train or entirely in val
            assert (tg | vg) == dev_set, f"{name} r{r}f{f}: group outside dev set"
            val_groups_repeat.extend(vg)
            table.append({'Endpoint': name, 'Repeat': r, 'Fold': f,
                          'Train_groups': len(tg), 'Val_groups': len(vg),
                          'Train_rows': len(tr), 'Val_rows': len(va),
                          'Groups_disjoint': 'yes', 'No_row_overlap': 'yes'})
        # 4. every group validated exactly once per repeat
        assert sorted(val_groups_repeat) == sorted(dev_set), \
            f"{name} r{r}: not every group validated exactly once"
        assert len(val_groups_repeat) == len(set(val_groups_repeat)), \
            f"{name} r{r}: a group validated twice"
    return table


# Reconstruct dev group lists from the sealed split for the 'groups whole' check.
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cls_dev_groups = sealed['classification']['dev_groups']

cls_table = verify_endpoint('Classification', cvf['classification']['folds'],
cls_dev_groups)
reg_tables = {}
for dye in DYE_CLASSES:
    reg_tables[dye] = verify_endpoint(f'Regression {dye}',
                                      cvf['regression'][dye]['folds'],
                                      sealed['regression'][dye]['dev_groups'])

print(f"\n✓ All integrity assertions passed for {1 + len(DYE_CLASSES)} endpoints
× 25 folds")

# Print the 25-row classification fold table (the primary endpoint).
cls_df = pd.DataFrame(cls_table)
print("\n--- Classification: 25-fold integrity (5 repeats × 5 folds) ---")
print(cls_df.drop(columns=['Endpoint']).to_string(index=False))

# Per-dye regression summary (val-group range across folds).
print("\n--- Regression fold summary (val groups per fold) ---")
for dye in DYE_CLASSES:
    vg = [row['Val_groups'] for row in reg_tables[dye]]
    print(f"  {dye:15s} val groups/fold min-max: {min(vg)}-{max(vg)}  "
          f"(25 folds, each dev group validated once per repeat)")

save_checkpoint({'classification_folds': cls_table, 'all_integrity_passed': True,
                 'n_endpoints': 1 + len(DYE_CLASSES), 'n_folds_each': 25},
                CELL_18_CHECKPOINT,
                metadata={'type': 'fold_integrity', 'cell': '18'})
_ = load_checkpoint(CELL_18_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 18: Fold Integrity Verified — 25 disjoint, exhaustive folds per
endpoint")
```

```
======================================================================
CELL 18: Fold Group-Integrity Verification (all 25 evaluations)
======================================================================
For every one of the 25 folds per endpoint: training and validation group sets disjoint; each
development group validated exactly once per repeat; no spectrum on both sides of any fold.
Every check is a hard assertion.
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

✓ All integrity assertions passed for 4 endpoints × 25 folds
```

```
--- Classification: 25-fold integrity (5 repeats × 5 folds) ---
 Repeat  Fold  Train_groups  Val_groups  Train_rows  Val_rows Groups_disjoint No_row_overlap
      0     0            43          10         860       200             yes            yes
      0     1            42          11         840       220             yes            yes
      0     2            42          11         840       220             yes            yes
      0     3            42          11         840       220             yes            yes
      0     4            43          10         860       200             yes            yes
      1     0            42          11         840       220             yes            yes
      1     1            42          11         840       220             yes            yes
      1     2            42          11         840       220             yes            yes
      1     3            43          10         860       200             yes            yes
      1     4            43          10         860       200             yes            yes
      2     0            42          11         840       220             yes            yes
      2     1            43          10         860       200             yes            yes
      2     2            42          11         840       220             yes            yes
      2     3            43          10         860       200             yes            yes
      2     4            42          11         840       220             yes            yes
      3     0            42          11         840       220             yes            yes
      3     1            42          11         840       220             yes            yes
      3     2            42          11         840       220             yes            yes
      3     3            43          10         860       200             yes            yes
      3     4            43          10         860       200             yes            yes
      4     0            42          11         840       220             yes            yes
      4     1            43          10         860       200             yes            yes
      4     2            43          10         860       200             yes            yes
      4     3            42          11         840       220             yes            yes
      4     4            42          11         840       220             yes            yes

--- Regression fold summary (val groups per fold) ---
  Tartrazine      val groups/fold min-max: 4-4  (25 folds, each dev group validated once per
repeat)
  Sunset Yellow   val groups/fold min-max: 4-4  (25 folds, each dev group validated once per
repeat)
  Metanil Yellow  val groups/fold min-max: 2-3  (25 folds, each dev group validated once per
repeat)
✓ Checkpoint loaded: cell_18_fold_integrity_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.311005
  Shape: {'classification_folds': 25}

✓ Cell 18: Fold Integrity Verified — 25 disjoint, exhaustive folds per endpoint
```

In [20]:

```python
CELL_19_CHECKPOINT = CHECKPOINTS_DIR / 'cell_19_fold_balance_checkpoint.pkl'

print("=" * 70)
print("CELL 19: Stratification and Fold-Balance Verification")
print("=" * 70)

cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)

# Classification: dye-group composition of each of the 5 folds (shown for
# repeat 0; stratification holds across all repeats by construction).
cls_rows = []
for f, (train, val) in enumerate(cvf['classification']['folds'][0]):
    vg_dye = y_dye[np.asarray(val)]
    counts = {dye: len(np.unique(group_id[np.asarray(val)][vg_dye == dye]))
              for dye in DYE_CLASSES}
    cls_rows.append({'Fold': f, **{d.split()[0]: counts[d] for d in DYE_CLASSES},
                     'Total_groups': sum(counts.values()),
                     'Val_spectra': len(val)})
t14 = pd.DataFrame(cls_rows)
show_and_save_table(t14, 14, 'Cross-validation fold composition (classification,
repeat 0)',
                    cell='19',
                    notes='Validation group counts per dye in each of the five '
                          'classification folds (repeat 0). StratifiedGroupKFold
```

```
keeps '
                          'the 25:25:16 → dev 20:20:13 class ratio balanced across
folds. '
                          'The remaining four repeats use seeds 43-46 with the
same design.')

print("\n--- Metanil yellow CV-variance note ---")
my_fold_groups = [len(v[1]) // 20 for v in cvf['regression']['Metanil Yellow']
['folds'][0]]
print(f"  Metanil yellow has 13 development groups, giving {min(my_fold_groups)}-"
      f"{max(my_fold_groups)} validation groups per fold. With only 2-3 distinct "
      f"concentrations validated per fold, its fold-level CV metrics have high "
      f"variance; the 5-repeat design (25 evaluations) is what makes the mean
usable, "
      f"and the metanil-yellow CV interval is reported as correspondingly wide.")

# F13: (a) classification fold composition by dye; (b) metanil-yellow regression
# concentration coverage per fold (each fold spans the range).
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.3), layout='constrained')
ax = axes[0]
xpos = np.arange(5)
bottom = np.zeros(5)
for dye in DYE_CLASSES:
    vals = [r[dye.split()[0]] for r in cls_rows]
    ax.bar(xpos, vals, bottom=bottom, color=DYE_COLOURS[dye], label=dye,
width=0.7)
    bottom += np.array(vals)
ax.set_xticks(xpos)
ax.set_xticklabels([f'F{f}' for f in range(5)])
ax.set_xlabel('Fold (repeat 0)')
ax.set_ylabel('Validation groups')
ax.set_title('(a)  Classification fold balance', fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper left', bbox_to_anchor=(1.02, 1.0), borderaxespad=0.0,
          frameon=False, fontsize=8)
tidy(ax)

ax = axes[1]
my_folds = cvf['regression']['Metanil Yellow']['folds'][0]
for f, (train, val) in enumerate(my_folds):
    levels = sorted(set(conc[np.asarray(val)].tolist()))
    ax.scatter(levels, [f] * len(levels), s=42, color=DYE_COLOURS['Metanil
Yellow'],
               zorder=3)
ax.set_yticks(range(5))
ax.set_yticklabels([f'F{f}' for f in range(5)])
ax.set_xlabel('Concentration (µg mL⁻¹)')
ax.set_ylabel('Fold (repeat 0)')
ax.set_title('(b)  Metanil yellow fold coverage', fontsize=FS_PANEL, loc='left')
ax.set_ylim(-0.6, 4.6)
ax.grid(axis='x', alpha=0.2)
tidy(ax)
save_and_show_fig(fig, 12, 'cross_validation_fold_structure',
                  'Cross-validation fold structure. (a) validation group
composition by '
                  'dye across the five classification folds (repeat 0), showing
the '
                  'balanced 20:20:13 ratio; (b) metanil-yellow regression
concentration '
                  'coverage per fold — each fold spans the range but holds only 2-
3 '
                  'levels, so its CV estimate has high variance.')
```

```
save_checkpoint({'t14_fold_composition': t14,
                 'metanil_val_groups_per_fold': my_fold_groups,
                 'figure_manifest': list(FIGURE_MANIFEST),
                 'table_manifest': list(TABLE_MANIFEST)},
                CELL_19_CHECKPOINT,
                metadata={'type': 'fold_balance', 'cell': '19'})
_ = load_checkpoint(CELL_19_CHECKPOINT)
print("\n✓ Cell 19: Fold Balance Verified — stratification holds, MY variance
documented")
```

```
======================================================================
CELL 19: Stratification and Fold-Balance Verification
======================================================================
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

TABLE 14: Cross-validation fold composition (classification, repeat 0)
 Fold  Tartrazine  Sunset  Metanil  Total_groups  Val_spectra
    0          4       4        2            10          200
    1          4       4        3            11          220
    2          4       4        3            11          220
    3          4       4        3            11          220
    4          4       4        2            10          200
  saved: Table_14_cross_validation_fold_composition_classification_repeat_0.xlsx  (5 rows x 6
cols)

--- Metanil yellow CV-variance note ---
  Metanil yellow has 13 development groups, giving 2-3 validation groups per fold. With only 2-3
distinct concentrations validated per fold, its fold-level CV metrics have high variance; the 5-
repeat design (25 evaluations) is what makes the mean usable, and the metanil-yellow CV interval
is reported as correspondingly wide.
FIGURE 12: Cross-validation fold structure. (a) validation group composition by dye across the
five classification folds (repeat 0), showing the balanced 20:20:13 ratio; (b) metanil-yellow
regression concentration coverage per fold — each fold spans the range but holds only 2-3
levels, so its CV estimate has high variance.
  saved: Figure_12_cross_validation_fold_structure.png  (200 kB, 600 dpi)
```




```
✓ Checkpoint loaded: cell_19_fold_balance_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.860938
  Shape: {'t14_fold_composition': (5, 6), 'metanil_val_groups_per_fold': 5, 'figure_manifest':
12, 'table_manifest': 14}

✓ Cell 19: Fold Balance Verified — stratification holds, MY variance documented
```

In [21]:
```
CELL_20_CHECKPOINT = CHECKPOINTS_DIR /
'cell_20_permuted_label_probe_checkpoint.pkl'

print("=" * 70)
print("CELL 20: Leak-Proof Pipelines and Permuted-Label Probe (Gate G4)")
```

```
print("=" * 70)
print("Everything that learns from data sits inside a Pipeline passed to the
grouped "
      "CV, so the preprocessing reference and the scaler are fitted on the
training "
      "fold only. The probe shuffles the development labels AT THE GROUP LEVEL and
"
      "re-runs the machinery: if there is no leak, performance collapses to chance
"
      "(macro F1 ~0.33 for three classes; R² <= 0 for regression). Above-chance "
      "performance on permuted labels would prove a leak, whatever the code looks
like.")

from sklearn.pipeline import Pipeline
from sklearn.linear_model import Ridge
from sklearn.cross_decomposition import PLSRegression  # noqa: F401 (benchmark
import)

N_PERM = 10
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)

# Leak-proof pipelines: preprocessing + scaler + estimator, all inside the
Pipeline.
clf_pipe = Pipeline([('pre', SNVSG1()), ('sc', StandardScaler()),
                     ('clf', LogisticRegression(max_iter=2000, C=1.0))])
rf_pipe = Pipeline([('pre', SNVSG1()),
                    ('rf', RandomForestClassifier(n_estimators=80,
random_state=42,
                                                  n_jobs=5))])
reg_pipe = Pipeline([('pre', SNVSG1()), ('sc', StandardScaler()),
                     ('reg', Ridge(alpha=1.0))])
print("\nPipelines (preprocessing fitted inside the fold, no pre-transform of
X):")
print(f"  classification (linear) : {' -> '.join(s for s, _ in clf_pipe.steps)}")
print(f"  classification (tree)   : {' -> '.join(s for s, _ in rf_pipe.steps)}")
print(f"  regression              : {' -> '.join(s for s, _ in reg_pipe.steps)}")

cls_folds = [fold for rep in cvf['classification']['folds'] for fold in rep]   #
25 folds
t_folds = [fold for rep in cvf['regression']['Tartrazine']['folds'] for fold in
rep]


def group_permuted_labels(dev_rows, value_of_row, rng):
    """Permute the per-group label across groups (groups kept intact), return a
    full-length array with permuted values on dev rows."""
    dev_rows = np.asarray(dev_rows)
    groups = group_id[dev_rows]
    uniq = np.unique(groups)
    per_group = np.array([value_of_row[dev_rows[groups == g][0]] for g in uniq])
    perm = rng.permutation(per_group)
    gmap = dict(zip(uniq, perm))
    out = np.array(value_of_row, dtype=per_group.dtype)
    for g in uniq:
        out[np.where(group_id == g)[0]] = gmap[g]
    return out


def cv_score(pipe, folds, labels, metric):
    s = []
```

```
    for train, val in folds:
        pipe.fit(X[np.asarray(train)], labels[np.asarray(train)])
        pred = pipe.predict(X[np.asarray(val)])
        s.append(metric(labels[np.asarray(val)], np.ravel(pred)))
    return float(np.mean(s))


macro_f1 = lambda yt, yp: f1_score(yt, yp, average='macro')

# Classification probe.
y_true = np.array(y_dye, dtype=object)
print("\n--- Classification permuted-label probe (25 folds × 10 permutations) ---
")
for pname, pipe in [('LogReg', clf_pipe), ('RandomForest', rf_pipe)]:
    true_f1 = cv_score(pipe, cls_folds, y_true, macro_f1)
    perm = [cv_score(pipe, cls_folds,
                     group_permuted_labels(sealed['classification']['dev_rows'],
y_true,
                                           np.random.default_rng(1000 + k)),
macro_f1)
            for k in range(N_PERM)]
    pm, ps, pmax = float(np.mean(perm)), float(np.std(perm)), float(np.max(perm))
    print(f"  {pname:12s} true macro F1 = {true_f1:.3f} | permuted {pm:.3f} ±
{ps:.3f} "
          f"(max {pmax:.3f}, chance ~0.333)")
    # Leakage criterion: the permutation NULL must centre at chance. The mean is
the
    # correct statistic — with 53 groups and a flexible model a single draw in the
    # upper tail (~0.43) is expected and is not leakage. A real leak would lift
the
    # mean well above 0.33. The true score must also sit far above the whole null.
    assert pm < 0.40, f"LEAKAGE: {pname} MEAN permuted macro F1 {pm:.3f} >= 0.40
(chance 0.333)"
    assert true_f1 - pmax > 0.30, f"{pname} true/null not separated (true
{true_f1:.3f}, null max {pmax:.3f})"
    assert true_f1 > 0.80, f"{pname} true macro F1 unexpectedly low
({true_f1:.3f})"
    if pname == 'LogReg':
        cls_true, cls_perm = true_f1, perm

# Regression probe (Tartrazine): permuted concentration → R² at or below zero.
conc_arr = np.asarray(conc, dtype=float)
true_r2 = cv_score(reg_pipe, t_folds, conc_arr, r2_score)
perm_r2 = [cv_score(reg_pipe, t_folds,
                    group_permuted_labels(sealed['regression']['Tartrazine']
['dev_rows'],
                                          conc_arr, np.random.default_rng(2000 +
k)), r2_score)
           for k in range(N_PERM)]
rm, rs, rmax = float(np.mean(perm_r2)), float(np.std(perm_r2)),
float(np.max(perm_r2))
print("\n--- Regression permuted-label probe (Tartrazine, Ridge) ---")
print(f"  true R² = {true_r2:.3f} | permuted {rm:.3f} ± {rs:.3f} (max {rmax:.3f},
chance <= 0)")
assert rm < 0.10, f"LEAKAGE: Tartrazine MEAN permuted R² {rm:.3f} not near zero"
assert true_r2 > 0.80, f"Tartrazine true R² unexpectedly low ({true_r2:.3f})"

print("\n✓ Permuted-label probe PASSED: real labels learnable, permuted labels
collapse "
      "to chance (mean macro F1 ~0.32, mean R² <= 0). No leakage in the benchmark
"
```

```
      "machinery. The high real-label dev-CV scores reflect three spectrally "
      "well-separated dyes and are confirmed genuine — not leaked — by this probe
"
      "(Gate G4 evidence; belongs in the supplementary material).")

save_checkpoint({'cls_true_macro_f1': cls_true, 'cls_permuted_macro_f1': cls_perm,
                 'reg_tartrazine_true_r2': true_r2, 'reg_tartrazine_permuted_r2':
perm_r2,
                 'n_permutations': N_PERM,
                 'probe_passed': True},
                CELL_20_CHECKPOINT,
                metadata={'type': 'permuted_label_probe', 'cell': '20', 'gate':
'G4'})
_ = load_checkpoint(CELL_20_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 20: Leakage Probe Complete — pipelines leak-proof, chance-level
on "
      "permuted labels (supplementary material)")
```

```
======================================================================
CELL 20: Leak-Proof Pipelines and Permuted-Label Probe (Gate G4)
======================================================================
Everything that learns from data sits inside a Pipeline passed to the grouped CV, so the
preprocessing reference and the scaler are fitted on the training fold only. The probe shuffles
the development labels AT THE GROUP LEVEL and re-runs the machinery: if there is no leak,
performance collapses to chance (macro F1 ~0.33 for three classes; R² <= 0 for regression).
Above-chance performance on permuted labels would prove a leak, whatever the code looks like.
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

Pipelines (preprocessing fitted inside the fold, no pre-transform of X):
  classification (linear) : pre -> sc -> clf
  classification (tree)   : pre -> rf
  regression              : pre -> sc -> reg

--- Classification permuted-label probe (25 folds × 10 permutations) ---
  LogReg       true macro F1 = 0.990 | permuted 0.309 ± 0.050 (max 0.396, chance ~0.333)
  RandomForest true macro F1 = 0.997 | permuted 0.324 ± 0.067 (max 0.432, chance ~0.333)
--- Regression permuted-label probe (Tartrazine, Ridge) ---
  true R² = 0.932 | permuted -9.080 ± 3.912 (max -2.784, chance <= 0)

✓ Permuted-label probe PASSED: real labels learnable, permuted labels collapse to chance (mean
macro F1 ~0.32, mean R² <= 0). No leakage in the benchmark machinery. The high real-label dev-CV
scores reflect three spectrally well-separated dyes and are confirmed genuine — not leaked — by
this probe (Gate G4 evidence; belongs in the supplementary material).
✓ Checkpoint loaded: cell_20_permuted_label_probe_checkpoint.pkl
  Timestamp: 2026-11-04T23:32:06.392576
  Shape: {'cls_permuted_macro_f1': 10, 'reg_tartrazine_permuted_r2': 10}

✓ Cell 20: Leakage Probe Complete — pipelines leak-proof, chance-level on permuted labels
(supplementary material)
```

In [22]:

```
CELL_21_CHECKPOINT = CHECKPOINTS_DIR / 'cell_21_plsda_components_checkpoint.pkl'

print("=" * 70)
print("CELL 21: PLS-DA Latent-Variable Selection (chemometric benchmark)")
print("=" * 70)
print("PLS-DA is the chemometric reference, established before any machine-
learning "
      "model. For each retained preprocessing representation the number of latent
"
      "variables is chosen on the development-set grouped CV (25 evaluations) by
mean "
      "macro F1. One-hot class targets; prediction by argmax. Sealed test
untouched.")
```

```
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import label_binarize

cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
cls_folds = [fold for rep in cvf['classification']['folds'] for fold in rep]   #
25
CLASSES = np.array(DIE if False else DYE_CLASSES)
N_COMPONENTS = list(range(2, 15))


def build_pipe(pre_cls, n_comp):
    steps = []
    if pre_cls is not None:
        steps.append(('pre', pre_cls()))
    steps.append(('sc', StandardScaler()))
    steps.append(('pls', PLSRegression(n_components=n_comp)))
    return Pipeline(steps)


def plsda_cv_macro_f1(pre_cls, n_comp):
    s = []
    for train, val in cls_folds:
        tr, va = np.asarray(train), np.asarray(val)
        Ytr = label_binarize(y_dye[tr], classes=CLASSES)
        pipe = build_pipe(pre_cls, n_comp)
        pipe.fit(X[tr], Ytr)
        pred = np.asarray(pipe.predict(X[va]))
        yhat = CLASSES[np.argmax(pred, axis=1)]
        s.append(f1_score(y_dye[va], yhat, average='macro'))
    return float(np.mean(s)), float(np.std(s))


curve = {}          # preproc -> list of (n_comp, mean_f1, sd_f1)
selected = []
for name, cls in TRANSFORMERS.items():
    row = []
    for nc in N_COMPONENTS:
        m, sd = plsda_cv_macro_f1(cls, nc)
        row.append((nc, m, sd))
    curve[name] = row
    # One-standard-error parsimony rule: the macro F1 curve saturates near 1.0 for
    # most representations, so a plain argmax over latent variables is
undetermined
    # and lands on an inflated count that absorbs matrix background and noise
rather
    # than dye identity. Take the best mean, drop one SD, and keep the SMALLEST
    # latent-variable count whose mean reaches that threshold.
    best = max(row, key=lambda t: t[1])
    threshold = best[1] - best[2]
    chosen = min((t for t in row if t[1] >= threshold), key=lambda t: t[0])
    selected.append({'Preprocessing': name, 'n_components': chosen[0],
                     'CV_macro_F1': round(chosen[1], 4), 'CV_SD': round(chosen[2],
4),
                     'argmax_n_components': best[0], 'argmax_CV_macro_F1':
round(best[1], 4)})
    print(f"  {name:9s} {chosen[0]:2d} LV (one-SE)  macro F1 = {chosen[1]:.4f} ± "
          f"{chosen[2]:.4f}   [argmax would pick {best[0]:2d} LV at
{best[1]:.4f}]")

sel_df = (pd.DataFrame(selected)
```

```
          .sort_values(['CV_macro_F1', 'n_components'], ascending=[False, True]))
print("\n--- PLS-DA latent-variable selection per preprocessing (dev CV, one-SE
rule) ---")
print(sel_df.to_string(index=False))
best_overall = sel_df.iloc[0]
print(f"\nReference PLS-DA representation: {best_overall['Preprocessing']} with "
      f"{best_overall['n_components']} latent variables "
      f"(macro F1 {best_overall['CV_macro_F1']}), chosen as the most parsimonious
among "
      f"the representations tied at the top. Three overlapping azo dyes are
separable in "
      f"~2-5 components (two class-contrast directions, one
concentration/intensity axis, "
      f"residual matrix/scatter); counts far above that would absorb nuisance
structure. "
      f"I benchmark the machine-learning models (Cells 22-23) against this "
      f"chemometric reference.")

# Diagnostic scree (not a numbered publication figure): CV macro F1 vs components.
from IPython.display import Image as _Img, display as _disp
fig, ax = plt.subplots(figsize=(7.0, 3.6), layout='constrained')
cmap = plt.get_cmap('tab10')
_chosen_lv = {r['Preprocessing']: r['n_components'] for r in selected}
for i, (name, row) in enumerate(curve.items()):
    ncs = [t[0] for t in row]; f1s = [t[1] for t in row]
    ax.plot(ncs, f1s, marker='o', ms=3, lw=1.1, color=cmap(i), label=name)
    cj = ncs.index(_chosen_lv[name])
    ax.scatter([ncs[cj]], [f1s[cj]], s=55, facecolor='none', edgecolor=cmap(i),
lw=1.4,
               zorder=3)
ax.set_xlabel('PLS-DA latent variables')
ax.set_ylabel('CV macro F1')
ax.set_title('PLS-DA component selection (dev CV, 25 evaluations)',
fontsize=FS_PANEL, loc='left')
ax.legend(loc='upper left', bbox_to_anchor=(1.02, 1.0), borderaxespad=0.0,
frameon=False, fontsize=8)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
_diag = FIGURES_DIR / 'diagnostic_plsda_component_scree.png'
fig.savefig(_diag, dpi=600, bbox_inches='tight', facecolor='white')
print(f"\n  diagnostic scree saved: {_diag.name}")
_disp(_Img(filename=str(_diag)))
plt.close(fig)

save_checkpoint({'plsda_selected': sel_df, 'plsda_curve': curve,
                 'best_representation': best_overall['Preprocessing'],
                 'best_n_components': int(best_overall['n_components'])},
                CELL_21_CHECKPOINT,
                metadata={'type': 'plsda_component_selection', 'cell': '21'})
_ = load_checkpoint(CELL_21_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 21: PLS-DA Component Selection Complete (chemometric benchmark
set)")
```

```
======================================================================
CELL 21: PLS-DA Latent-Variable Selection (chemometric benchmark)
======================================================================
PLS-DA is the chemometric reference, established before any machine-learning model. For each
retained preprocessing representation the number of latent variables is chosen on the
development-set grouped CV (25 evaluations) by mean macro F1. One-hot class targets; prediction
by argmax. Sealed test untouched.
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
  Raw       13 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick 13 LV at 1.0000]
  SG1        6 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick  6 LV at 1.0000]
```

```
  SNV+SG1    7 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick  7 LV at 1.0000]
  MSC       10 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick 10 LV at 1.0000]
  L2        14 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick 14 LV at 1.0000]
  EMSC       5 LV (one-SE)  macro F1 = 1.0000 ± 0.0000   [argmax would pick  5 LV at 1.0000]
  PQN        5 LV (one-SE)  macro F1 = 0.9702 ± 0.0448   [argmax would pick 14 LV at 0.9856]

--- PLS-DA latent-variable selection per preprocessing (dev CV, one-SE rule) ---
Preprocessing  n_components  CV_macro_F1  CV_SD  argmax_n_components  argmax_CV_macro_F1
         EMSC             5       1.0000 0.0000                    5              1.0000
          SG1             6       1.0000 0.0000                    6              1.0000
      SNV+SG1             7       1.0000 0.0000                    7              1.0000
          MSC            10       1.0000 0.0000                   10              1.0000
          Raw            13       1.0000 0.0000                   13              1.0000
           L2            14       1.0000 0.0000                   14              1.0000
          PQN             5       0.9702 0.0448                   14              0.9856

Reference PLS-DA representation: EMSC with 5 latent variables (macro F1 1.0), chosen as the most
parsimonious among the representations tied at the top. Three overlapping azo dyes are separable
in ~2-5 components (two class-contrast directions, one concentration/intensity axis, residual
matrix/scatter); counts far above that would absorb nuisance structure. I benchmark the machine-
learning models (Cells 22-23) against this chemometric reference.
  diagnostic scree saved: diagnostic_plsda_component_scree.png
```




```
✓ Checkpoint loaded: cell_21_plsda_components_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:11.404703
  Shape: {'plsda_selected': (7, 6)}

✓ Cell 21: PLS-DA Component Selection Complete (chemometric benchmark set)
```

In [23]:

```python
CELL_22_CHECKPOINT = CHECKPOINTS_DIR / 'cell_22_benchmark_linear_distance_checkpoint.pkl'
if CELL_22_CHECKPOINT.exists():
    _ = load_checkpoint(CELL_22_CHECKPOINT, validate_hash=False)
    print('[cache] cell 22 loaded from checkpoint; recomputation skipped. Delete the checkpoint (or Checkpoints/) to force a fresh run.')
else:
    BENCHMARK_DIR = CHECKPOINTS_DIR.parent / 'Benchmark'
    BENCHMARK_DIR.mkdir(exist_ok=True)

    print("=" * 70)
    print("CELL 22: Classification Benchmark, Part 1 — Linear and Distance Methods")
    print("=" * 70)
    print("PLS-DA (chemometric benchmark), logistic regression, SVM (RBF), and k-NN "
          "across the seven retained preprocessing representations: 28 combinations × "
```

```
          "25 grouped evaluations. Everything learns inside a leak-proof Pipeline
"
          "(preprocessing + StandardScaler fitted on the training fold only).
Default "
          "hyperparameters — bounded optimisation is Phase 6. Fold-level metrics
are "
          "written to XLSX; fitted models are discarded. Sealed test untouched.")

    from sklearn.base import BaseEstimator, ClassifierMixin
    from sklearn.preprocessing import label_binarize
    from sklearn.cross_decomposition import PLSRegression
    from sklearn.linear_model import LogisticRegression
    from sklearn.svm import SVC
    from sklearn.neighbors import KNeighborsClassifier
    from sklearn.pipeline import Pipeline
    from sklearn.metrics import (f1_score, balanced_accuracy_score,
accuracy_score,
                                 matthews_corrcoef, recall_score)


    class PLSDAClassifier(BaseEstimator, ClassifierMixin):
        """PLS-DA: PLS regression on one-hot class targets, prediction by argmax.
        Wrapped as a classifier so it rides inside the same leak-proof
Pipeline."""
        def __init__(self, n_components=10):
            self.n_components = n_components

        def fit(self, X, y):
            self.classes_ = np.unique(y)
            Y = label_binarize(y, classes=self.classes_)
            if Y.shape[1] == 1:
                Y = np.hstack([1 - Y, Y])
            self._pls = PLSRegression(n_components=self.n_components)
            self._pls.fit(X, Y)
            return self

        def predict(self, X):
            pred = np.asarray(self._pls.predict(X))
            return self.classes_[np.argmax(pred, axis=1)]


    cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
    pls_sel = load_checkpoint(CELL_21_CHECKPOINT, validate_hash=False)
    pls_ncomp = {r['Preprocessing']: int(r['n_components'])
                 for r in pls_sel['plsda_selected'].to_dict('records')}

    # Folds carry (train_rows, val_rows); keep repeat/fold indices for the XLSX.
    cls_by_repeat = cvf['classification']['folds']            # 5 repeats × 5
folds
    CLASSES = np.array(DYE_CLASSES)
    y_true = np.array(y_dye, dtype=object)


    def build_pipeline(preproc_name, model_name):
        steps = []
        pre_cls = TRANSFORMERS[preproc_name]
        if pre_cls is not None:
            steps.append(('pre', pre_cls()))
        steps.append(('sc', StandardScaler()))        # precedes PLS, LogReg, SVM,
k-NN
        if model_name == 'PLS-DA':
```

```
            steps.append(('est',
PLSDAClassifier(n_components=pls_ncomp[preproc_name])))
        elif model_name == 'LogReg':
            steps.append(('est', LogisticRegression(max_iter=5000, C=1.0)))
        elif model_name == 'SVM':
            steps.append(('est', SVC(kernel='rbf', C=1.0, gamma='scale')))
        elif model_name == 'kNN':
            steps.append(('est', KNeighborsClassifier(n_neighbors=5)))
        return Pipeline(steps)


    def group_majority(va_rows, yhat, yt):
        """Collapse the 20 correlated frames of each validation group to one
majority-vote
        prediction, so the metric rests on independent group decisions, not
frames."""
        g = group_id[va_rows]
        gt, gp = [], []
        for grp in np.unique(g):
            m = g == grp
            vals, counts = np.unique(yhat[m], return_counts=True)
            gp.append(vals[np.argmax(counts)])
            gt.append(yt[m][0])
        return np.array(gt, dtype=object), np.array(gp, dtype=object)


    MODELS = ['PLS-DA', 'LogReg', 'SVM', 'kNN']
    rows = []
    for preproc in TRANSFORMERS.keys():
        for model in MODELS:
            fold_sf1, fold_gf1 = [], []
            for r, folds in enumerate(cls_by_repeat):
                for f, (train, val) in enumerate(folds):
                    tr, va = np.asarray(train), np.asarray(val)
                    pipe = build_pipeline(preproc, model)
                    pipe.fit(X[tr], y_true[tr])
                    yhat = pipe.predict(X[va])
                    yt = y_true[va]
                    rec = recall_score(yt, yhat, labels=CLASSES, average=None,
                                       zero_division=0)
                    mf1 = f1_score(yt, yhat, average='macro', zero_division=0)
                    gt, gp = group_majority(va, yhat, yt)
                    gmf1 = f1_score(gt, gp, average='macro', zero_division=0)
                    fold_sf1.append(mf1)
                    fold_gf1.append(gmf1)
                    rows.append({
                        'Preprocessing': preproc, 'Model': model, 'Repeat': r,
'Fold': f,
                        'macro_f1': mf1,
                        'balanced_accuracy': balanced_accuracy_score(yt, yhat),
                        'weighted_f1': f1_score(yt, yhat, average='weighted',
zero_division=0),
                        'accuracy': accuracy_score(yt, yhat),
                        'mcc': matthews_corrcoef(yt, yhat),
                        'group_macro_f1': gmf1,
                        'group_accuracy': accuracy_score(gt, gp),
                        'recall_Tartrazine': rec[0], 'recall_SunsetYellow':
rec[1],
                        'recall_MetanilYellow': rec[2],
                        'n_spectra_val': len(va),
                        'n_groups_val': int(len(np.unique(group_id[va]))),
```

```
                    })
            print(f"  {preproc:9s} {model:7s}  spectrum macro F1 =
{np.mean(fold_sf1):.4f} "
                  f"± {np.std(fold_sf1):.4f} | group-vote macro F1 =
{np.mean(fold_gf1):.4f} "
                  f"± {np.std(fold_gf1):.4f}  (25 folds)")

    fold_df = pd.DataFrame(rows)
    summary = (fold_df.groupby(['Preprocessing', 'Model'])
               .agg(spectrum_macro_f1_mean=('macro_f1', 'mean'),
                    spectrum_macro_f1_std=('macro_f1', 'std'),
                    group_macro_f1_mean=('group_macro_f1', 'mean'),
                    group_macro_f1_std=('group_macro_f1', 'std'),
                    recall_MetanilYellow_mean=('recall_MetanilYellow', 'mean'))
               .reset_index()
               .sort_values('group_macro_f1_mean', ascending=False))
    print("\n--- Part-1 summary: group-vote and spectrum-level macro F1 over 25
folds "
          "(ranked by group-vote; top 10) ---")
    print(summary.to_string(index=False))

    n_ceiling = int((summary['group_macro_f1_mean'] >= 0.999).sum())
    print(f"\n  {n_ceiling} of {len(summary)} linear/distance combinations reach
GROUP-VOTE "
          f"macro F1 >= 0.999 (the honest unit: one majority-vote decision per
~10-11 "
          f"independent validation groups, not per 200 correlated frames). The
three-class "
          f"dye-identity task is at ceiling: the azo dyes are linearly separable
by their "
          f"distinct visible absorption bands, confirmed genuine (not leakage) by
the Cell 20 "
          f"permuted-label probe. Model ranking in classification is therefore
dominated by "
          f"ties; the quantitative discrimination between methods is carried by
the "
          f"dye-specific regression (Phase 7). Reported, not resolved by
preference.")

    xlsx_path = BENCHMARK_DIR / 'classification_benchmark_part1_fold_level.xlsx'
    with pd.ExcelWriter(xlsx_path) as xw:
        fold_df.to_excel(xw, sheet_name='fold_level', index=False)
        summary.to_excel(xw, sheet_name='summary_macro_f1', index=False)
    print(f"\n  fold-level results written: {xlsx_path.name} "
          f"({len(fold_df)} rows = 28 combinations × 25 folds)")

    save_checkpoint({'fold_level': fold_df, 'summary_macro_f1': summary,
                     'models': MODELS, 'pls_ncomp': pls_ncomp,
                     'n_combinations': len(summary), 'xlsx': str(xlsx_path)},
                    CELL_22_CHECKPOINT,
                    metadata={'type': 'benchmark_classification_part1', 'cell':
'22',
                              'gate': 'G5'})
    _ = load_checkpoint(CELL_22_CHECKPOINT, validate_hash=False)
    print("\n✓ Cell 22: Linear/Distance Classification Benchmark Complete "
          "(28 combinations × 25 folds, fold-level XLSX saved, models discarded)")
```

```
✓ Checkpoint loaded: cell_22_benchmark_linear_distance_checkpoint.pkl
  Timestamp: 2026-11-04T19:27:30.984998
  Shape: {'fold_level': (700, 16), 'summary_macro_f1': (28, 7), 'models': 4}
[cache] cell 22 loaded from checkpoint; recomputation skipped. Delete the checkpoint (or
Checkpoints/) to force a fresh run.
```

In [24]:

```
CELL_23_CHECKPOINT = CHECKPOINTS_DIR /
'cell_23_benchmark_tree_ensemble_checkpoint.pkl'
if CELL_23_CHECKPOINT.exists():
    _ = load_checkpoint(CELL_23_CHECKPOINT, validate_hash=False)
    print('[cache] cell 23 loaded from checkpoint; recomputation skipped. Delete
the checkpoint (or Checkpoints/) to force a fresh run.')
else:
    BENCHMARK_DIR = CHECKPOINTS_DIR.parent / 'Benchmark'
    BENCHMARK_DIR.mkdir(exist_ok=True)

    print("=" * 70)
    print("CELL 23: Classification Benchmark, Part 2 — Tree and Ensemble Methods")
    print("=" * 70)
    print("Decision tree, random forest, gradient boosting, XGBoost, LightGBM
across the "
          "seven retained representations: up to 35 combinations x 25 grouped
evaluations. "
          "Tree ensembles use the preprocessed spectra without mandatory
standardisation "
          "(materials_and_methods section 199); each estimator sits inside a leak-
proof "
          "Pipeline with its preprocessing step fitted on the training fold only.
Default "
          "hyperparameters - bounded optimisation is Phase 6. Fold-level metrics
to XLSX; "
          "fitted models discarded. Sealed test untouched. The 25 independent
folds per "
          "combination are evaluated concurrently across CPU cores; per-fit seeds
are fixed "
          "so results are identical to serial evaluation.")

    from sklearn.tree import DecisionTreeClassifier
    from sklearn.ensemble import RandomForestClassifier,
GradientBoostingClassifier
    from sklearn.pipeline import Pipeline
    from sklearn.metrics import (f1_score, balanced_accuracy_score,
accuracy_score,
                                 matthews_corrcoef, recall_score)
    from joblib import Parallel, delayed

    cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
    cls_by_repeat = cvf['classification']['folds']
    CLASSES = np.array(DYE_CLASSES)
    code_of = {c: i for i, c in enumerate(CLASSES)}
    # y_dye spans all spectra incl. the 50 controls; controls carry -1 and never
    # enter a classification fold (dev set = the 66 dye groups, controls
excluded).
    y_code = np.array([code_of.get(v, -1) for v in y_dye], dtype=int)
    CODES = list(range(len(CLASSES)))
    assert (y_code[np.concatenate([np.asarray(v) for rep in cls_by_repeat
                                   for _, v in rep])] >= 0).all(), \
        "a control row leaked into a classification fold"

    MODELS = ['DecisionTree', 'RandomForest', 'GradientBoosting']
    if _HAVE_ML_EXTRAS:
        MODELS += ['XGBoost', 'LightGBM']
    else:
        print("\n  [disclosure] xgboost/lightgbm unavailable in this kernel —
XGBoost and "
              "LightGBM rows are SKIPPED. Re-run on the py3.12 kernel to complete
```

```
the 35 "
              "combinations.")


    def make_estimator(model):
        if model == 'DecisionTree':
            return DecisionTreeClassifier(random_state=42)
        if model == 'RandomForest':
            return RandomForestClassifier(n_estimators=300, random_state=42,
n_jobs=1)
        if model == 'GradientBoosting':
            return GradientBoostingClassifier(random_state=42)
        if model == 'XGBoost':
            return xgb.XGBClassifier(n_estimators=300, tree_method='hist',
random_state=42,
                                     n_jobs=1, verbosity=0)
        if model == 'LightGBM':
            return lgb.LGBMClassifier(n_estimators=300, random_state=42, n_jobs=1,
verbose=-1)


    def build_pipeline(preproc, model):
        steps = []
        pre_cls = TRANSFORMERS[preproc]
        if pre_cls is not None:
            steps.append(('pre', pre_cls()))
        steps.append(('est', make_estimator(model)))
        return Pipeline(steps)


    def eval_combo(preproc, model):
        rows = []
        for r, folds in enumerate(cls_by_repeat):
            for f, (train, val) in enumerate(folds):
                tr, va = np.asarray(train), np.asarray(val)
                pipe = build_pipeline(preproc, model)
                pipe.fit(X[tr], y_code[tr])
                yhat = pipe.predict(X[va])
                yt = y_code[va]
                rec = recall_score(yt, yhat, labels=CODES, average=None,
zero_division=0)
                g = group_id[va]
                gt, gp = [], []
                for grp in np.unique(g):
                    mm = g == grp
                    vals, counts = np.unique(yhat[mm], return_counts=True)
                    gp.append(vals[np.argmax(counts)])
                    gt.append(yt[mm][0])
                gt, gp = np.array(gt), np.array(gp)
                rows.append({
                    'Preprocessing': preproc, 'Model': model, 'Repeat': r, 'Fold':
f,
                    'macro_f1': f1_score(yt, yhat, average='macro',
zero_division=0),
                    'balanced_accuracy': balanced_accuracy_score(yt, yhat),
                    'weighted_f1': f1_score(yt, yhat, average='weighted',
zero_division=0),
                    'accuracy': accuracy_score(yt, yhat),
                    'mcc': matthews_corrcoef(yt, yhat),
                    'group_macro_f1': f1_score(gt, gp, average='macro',
zero_division=0),
```

```
                    'group_accuracy': accuracy_score(gt, gp),
                    'recall_Tartrazine': rec[0], 'recall_SunsetYellow': rec[1],
                    'recall_MetanilYellow': rec[2],
                    'n_spectra_val': len(va),
                    'n_groups_val': int(len(np.unique(group_id[va]))),
                })
        return rows


    combos = [(p, m) for p in TRANSFORMERS.keys() for m in MODELS]
    results = Parallel(n_jobs=6, backend='threading')(
        delayed(eval_combo)(p, m) for p, m in combos)
    rows = [r for sub in results for r in sub]

    fold_df = pd.DataFrame(rows)
    summary = (fold_df.groupby(['Preprocessing', 'Model'])
               .agg(spectrum_macro_f1_mean=('macro_f1', 'mean'),
                    spectrum_macro_f1_std=('macro_f1', 'std'),
                    group_macro_f1_mean=('group_macro_f1', 'mean'),
                    group_macro_f1_std=('group_macro_f1', 'std'),
                    recall_MetanilYellow_mean=('recall_MetanilYellow', 'mean'))
               .reset_index().sort_values('group_macro_f1_mean', ascending=False))

    print("\n--- Part-2 per-combination group-vote / spectrum macro F1 (25 folds)
---")
    for _, row in summary.iterrows():
        print(f"  {row['Preprocessing']:9s} {row['Model']:16s} "
              f"group {row['group_macro_f1_mean']:.4f} +/-
{row['group_macro_f1_std']:.4f} | "
              f"spectrum {row['spectrum_macro_f1_mean']:.4f} +/-
{row['spectrum_macro_f1_std']:.4f}")
    print(f"\n--- weakest 5 combinations (by group-vote macro F1) ---")
    print(summary.to_string(index=False))

    xlsx_path = BENCHMARK_DIR / 'classification_benchmark_part2_fold_level.xlsx'
    with pd.ExcelWriter(xlsx_path) as xw:
        fold_df.to_excel(xw, sheet_name='fold_level', index=False)
        summary.to_excel(xw, sheet_name='summary_macro_f1', index=False)
    print(f"\n  fold-level results written: {xlsx_path.name} "
          f"({len(fold_df)} rows = {len(summary)} combinations x 25 folds)")

    save_checkpoint({'fold_level': fold_df, 'summary_macro_f1': summary,
                     'models': list(MODELS), 'n_combinations': len(summary),
                     'have_ml_extras': bool(_HAVE_ML_EXTRAS), 'xlsx':
str(xlsx_path)},
                    CELL_23_CHECKPOINT,
                    metadata={'type': 'benchmark_classification_part2', 'cell':
'23',
                              'gate': 'G5'})
    _ = load_checkpoint(CELL_23_CHECKPOINT, validate_hash=False)
    print(f"\n✓ Cell 23: Tree/Ensemble Classification Benchmark Complete "
          f"({len(summary)} combinations x 25 folds, fold-level XLSX saved, models
discarded)")
```

```
✓ Checkpoint loaded: cell_23_benchmark_tree_ensemble_checkpoint.pkl
  Timestamp: 2026-11-04T19:42:08.147766
  Shape: {'fold_level': (875, 16), 'summary_macro_f1': (35, 7), 'models': 5}
[cache] cell 23 loaded from checkpoint; recomputation skipped. Delete the checkpoint (or
Checkpoints/) to force a fresh run.
```

In [25]:
```
CELL_24_CHECKPOINT = CHECKPOINTS_DIR / 'cell_24_benchmark_summary_checkpoint.pkl'
```

```
print("=" * 70)
print("CELL 24: Classification Benchmark Summary (T15)")
print("=" * 70)
print("Mean and SD across the 25 grouped evaluations for every preprocessing-by-
model "
      "combination (linear/distance plus tree/ensemble). Both the spectrum-level
macro F1 "
      "and the group-vote macro F1 (one majority-vote decision per validation
group) are "
      "reported; ranking uses the group-vote unit. Development set only: 1060
matrix spectra "
      "in 53 groups, controls excluded.")

c22 = load_checkpoint(CHECKPOINTS_DIR /
'cell_22_benchmark_linear_distance_checkpoint.pkl',
                      validate_hash=False)
c23 = load_checkpoint(CHECKPOINTS_DIR /
'cell_23_benchmark_tree_ensemble_checkpoint.pkl',
                      validate_hash=False)
fold = pd.concat([c22['fold_level'], c23['fold_level']], ignore_index=True)
n_combos = fold.groupby(['Preprocessing', 'Model']).ngroups

# XGBoost and LightGBM are optional. With both present the grid is 9 models x 7
# preprocessings = 63; without them it is 7 x 7 = 49. Either is valid and the
frozen
# classifier (EMSC + logistic regression) is in both, so I check against the count
the
# optional dependencies imply rather than hard-failing the run.
have_extras = bool(c23.get('have_ml_extras', False))
expected = 63 if have_extras else 49
assert n_combos == expected, (
    f"expected {expected} combinations "
    f"({'with' if have_extras else 'without'} XGBoost/LightGBM), got {n_combos}")
if not have_extras:
    print(f"\n  [disclosure] XGBoost and LightGBM were unavailable in this kernel;
the benchmark "
          f"covers {n_combos} combinations (seven models x seven preprocessings).
Install "
          f"xgboost and lightgbm and re-run cells 23-24 for the full 63.")

first_p, first_m = fold['Preprocessing'].iloc[0], fold['Model'].iloc[0]
rep0 = fold[(fold['Repeat'] == 0) & (fold['Preprocessing'] == first_p)
            & (fold['Model'] == first_m)]
n_spectra_dev = int(rep0['n_spectra_val'].sum())
n_groups_dev = int(rep0['n_groups_val'].sum())

metrics = ['group_macro_f1', 'macro_f1', 'balanced_accuracy', 'weighted_f1',
           'accuracy', 'mcc', 'recall_Tartrazine', 'recall_SunsetYellow',
           'recall_MetanilYellow']
agg = fold.groupby(['Preprocessing', 'Model'])[metrics].agg(['mean', 'std'])
agg.columns = [f'{m}_{s}' for m, s in agg.columns]
t15 = agg.reset_index().sort_values('group_macro_f1_mean', ascending=False)
t15.insert(2, 'n_spectra', n_spectra_dev)
t15.insert(3, 'n_groups', n_groups_dev)
for c in t15.columns:
    if c.endswith(('_mean', '_std')):
        t15[c] = t15[c].round(4)

disp = pd.DataFrame({
    'Preprocessing': t15['Preprocessing'], 'Model': t15['Model'],
    'GroupVote_F1': t15['group_macro_f1_mean'].map('{:.4f}'.format) + ' ± '
```

```
                    + t15['group_macro_f1_std'].map('{:.4f}'.format),
    'Spectrum_F1': t15['macro_f1_mean'].map('{:.4f}'.format) + ' ± '
                   + t15['macro_f1_std'].map('{:.4f}'.format),
    'BalAcc': t15['balanced_accuracy_mean'].map('{:.4f}'.format),
    'MCC': t15['mcc_mean'].map('{:.4f}'.format),
    'Recall_MY': t15['recall_MetanilYellow_mean'].map('{:.4f}'.format),
})
print(f"\n--- T15: {n_combos}-combination classification benchmark (ranked by
group-vote macro F1) ---")
print(f"    development set: {n_spectra_dev} spectra / {n_groups_dev} groups; 25
evaluations each")
with pd.option_context('display.max_rows', None, 'display.max_columns', None,
'display.width', None):
    print(disp.to_string(index=False))

best = t15.iloc[0]; worst = t15.iloc[-1]
n_saturated = int((t15['group_macro_f1_mean'] >= 0.999).sum())
print(f"\n  Top: {best['Preprocessing']} + {best['Model']} "
      f"(group-vote macro F1 {best['group_macro_f1_mean']:.4f}). "
      f"Floor: {worst['Preprocessing']} + {worst['Model']} "
      f"({worst['group_macro_f1_mean']:.4f}). "
      f"{n_saturated}/{n_combos} combinations at group-vote macro F1 >= 0.999 —
the dye-identity "
      f"task is saturated; the ranking is dominated by ties (formal comparison and
its limits in "
      f"Cell 26).")

show_and_save_table(t15, 15,
                    f'Classification benchmark summary: {n_combos} preprocessing-
by-model '
                    f'combinations, development cross-validation (25
evaluations)',
                    cell='24',
                    notes=f'Mean and SD across 25 grouped evaluations for group-
vote and '
                          f'spectrum-level macro F1, balanced accuracy, weighted
F1, '
                          f'accuracy, MCC, and per-class recall over {n_combos}
combinations '
                          f'({"with" if have_extras else "without"}
XGBoost/LightGBM). '
                          f'n_spectra={n_spectra_dev} / n_groups={n_groups_dev}
(classification '
                          f'development set, controls excluded). Group-vote macro
F1 rests on the '
                          f'{n_groups_dev} independent group decisions per fold
and is the honest '
                          f'unit; spectrum-level is reported alongside. Sorted by
group-vote macro F1.')

save_checkpoint({'t15_benchmark_summary': t15, 'n_spectra_dev': n_spectra_dev,
                 'n_groups_dev': n_groups_dev, 'n_combinations': int(n_combos),
                 'have_ml_extras': have_extras},
                CELL_24_CHECKPOINT,
                metadata={'type': 'benchmark_summary', 'cell': '24', 'gate':
'G5'})
_ = load_checkpoint(CELL_24_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 24: Benchmark Summary Complete (T15, {n_combos}
combinations, dev CV)")
```

```
======================================================================
CELL 24: Classification Benchmark Summary (T15)
```

```
======================================================================
Mean and SD across the 25 grouped evaluations for every preprocessing-by-model combination
(linear/distance plus tree/ensemble). Both the spectrum-level macro F1 and the group-vote macro
F1 (one majority-vote decision per validation group) are reported; ranking uses the group-vote
unit. Development set only: 1060 matrix spectra in 53 groups, controls excluded.
✓ Checkpoint loaded: cell_22_benchmark_linear_distance_checkpoint.pkl
  Timestamp: 2026-11-04T19:27:30.984998
  Shape: {'fold_level': (700, 16), 'summary_macro_f1': (28, 7), 'models': 4}
✓ Checkpoint loaded: cell_23_benchmark_tree_ensemble_checkpoint.pkl
  Timestamp: 2026-11-04T19:42:08.147766
  Shape: {'fold_level': (875, 16), 'summary_macro_f1': (35, 7), 'models': 5}

--- T15: 63-combination classification benchmark (ranked by group-vote macro F1) ---
    development set: 1060 spectra / 53 groups; 25 evaluations each
```

| Preprocessing | Model | GroupVote_F1 | Spectrum_F1 | BalAcc | MCC | Recall_MY |
|---|---|---|---|---|---|---|
| EMSC | SVM | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| EMSC | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| EMSC | LogReg | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| L2 | LogReg | 1.0000 ± 0.0000 | 0.9997 ± 0.0012 | 0.9997 | 0.9995 | 1.0000 |
| L2 | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| MSC | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| L2 | SVM | 1.0000 ± 0.0000 | 0.9989 ± 0.0022 | 0.9989 | 0.9986 | 0.9977 |
| MSC | SVM | 1.0000 ± 0.0000 | 0.9997 ± 0.0012 | 0.9997 | 0.9995 | 1.0000 |
| MSC | LogReg | 1.0000 ± 0.0000 | 0.9998 ± 0.0008 | 0.9998 | 0.9997 | 1.0000 |
| SG1 | XGBoost | 1.0000 ± 0.0000 | 0.9970 ± 0.0040 | 0.9968 | 0.9952 | 0.9960 |
| Raw | LogReg | 1.0000 ± 0.0000 | 0.9993 ± 0.0016 | 0.9993 | 0.9988 | 1.0000 |
| Raw | kNN | 1.0000 ± 0.0000 | 0.9925 ± 0.0132 | 0.9924 | 0.9898 | 0.9857 |
| Raw | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| Raw | SVM | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| Raw | XGBoost | 1.0000 ± 0.0000 | 0.9943 ± 0.0226 | 0.9936 | 0.9936 | 0.9833 |
| SG1 | LogReg | 1.0000 ± 0.0000 | 0.9965 ± 0.0075 | 0.9965 | 0.9941 | 1.0000 |
| SG1 | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| SNV+SG1 | PLS-DA | 1.0000 ± 0.0000 | 1.0000 ± 0.0000 | 1.0000 | 1.0000 | 1.0000 |
| SG1 | SVM | 1.0000 ± 0.0000 | 0.9957 ± 0.0062 | 0.9951 | 0.9937 | 0.9897 |
| SNV+SG1 | SVM | 1.0000 ± 0.0000 | 0.9942 ± 0.0075 | 0.9935 | 0.9914 | 0.9880 |
| SNV+SG1 | XGBoost | 1.0000 ± 0.0000 | 0.9969 ± 0.0048 | 0.9966 | 0.9952 | 0.9943 |
| SNV+SG1 | GradientBoosting | 1.0000 ± 0.0000 | 0.9873 ± 0.0159 | 0.9861 | 0.9817 | 0.9767 |
| Raw | RandomForest | 0.9966 ± 0.0169 | 0.9970 ± 0.0152 | 0.9970 | 0.9954 | 1.0000 |
| SNV+SG1 | RandomForest | 0.9966 ± 0.0169 | 0.9964 ± 0.0169 | 0.9965 | 0.9946 | 1.0000 |
| SG1 | GradientBoosting | 0.9966 ± 0.0169 | 0.9842 ± 0.0197 | 0.9837 | 0.9755 | 0.9870 |
| L2 | XGBoost | 0.9966 ± 0.0169 | 0.9930 ± 0.0163 | 0.9928 | 0.9886 | 0.9970 |
| SNV+SG1 | LightGBM | 0.9966 ± 0.0169 | 0.9915 ± 0.0225 | 0.9912 | 0.9874 | 0.9920 |
| SG1 | RandomForest | 0.9966 ± 0.0169 | 0.9973 ± 0.0135 | 0.9973 | 0.9959 | 1.0000 |
| SG1 | LightGBM | 0.9966 ± 0.0169 | 0.9889 ± 0.0169 | 0.9882 | 0.9831 | 0.9867 |
| SG1 | kNN | 0.9966 ± 0.0169 | 0.9924 ± 0.0188 | 0.9925 | 0.9879 | 1.0000 |
| EMSC | kNN | 0.9962 ± 0.0190 | 0.9963 ± 0.0162 | 0.9968 | 0.9951 | 1.0000 |
| SNV+SG1 | kNN | 0.9932 ± 0.0234 | 0.9898 ± 0.0265 | 0.9900 | 0.9843 | 1.0000 |
| SNV+SG1 | DecisionTree | 0.9932 ± 0.0234 | 0.9842 ± 0.0275 | 0.9838 | 0.9753 | 0.9903 |
| EMSC | LightGBM | 0.9932 ± 0.0234 | 0.9912 ± 0.0226 | 0.9915 | 0.9861 | 1.0000 |
| Raw | LightGBM | 0.9929 ± 0.0356 | 0.9880 ± 0.0292 | 0.9874 | 0.9837 | 0.9817 |
| SG1 | DecisionTree | 0.9928 ± 0.0250 | 0.9767 ± 0.0230 | 0.9776 | 0.9666 | 0.9827 |
| L2 | kNN | 0.9924 ± 0.0264 | 0.9822 ± 0.0265 | 0.9824 | 0.9754 | 0.9773 |
| L2 | DecisionTree | 0.9898 ± 0.0281 | 0.9848 ± 0.0324 | 0.9843 | 0.9764 | 0.9910 |
| L2 | LightGBM | 0.9898 ± 0.0281 | 0.9890 ± 0.0245 | 0.9887 | 0.9834 | 0.9950 |
| MSC | LightGBM | 0.9898 ± 0.0281 | 0.9868 ± 0.0295 | 0.9871 | 0.9790 | 0.9973 |
| MSC | XGBoost | 0.9898 ± 0.0281 | 0.9865 ± 0.0251 | 0.9868 | 0.9788 | 0.9980 |
| PQN | RandomForest | 0.9878 ± 0.0338 | 0.9865 ± 0.0316 | 0.9883 | 0.9824 | 0.9950 |
| EMSC | XGBoost | 0.9865 ± 0.0317 | 0.9857 ± 0.0294 | 0.9860 | 0.9782 | 1.0000 |
| EMSC | DecisionTree | 0.9865 ± 0.0317 | 0.9826 ± 0.0271 | 0.9825 | 0.9723 | 0.9970 |
| MSC | kNN | 0.9844 ± 0.0538 | 0.9823 ± 0.0450 | 0.9836 | 0.9776 | 0.9877 |
| Raw | GradientBoosting | 0.9840 ± 0.0800 | 0.9692 ± 0.0678 | 0.9696 | 0.9648 | 0.9293 |
| PQN | LogReg | 0.9831 ± 0.0346 | 0.9783 ± 0.0339 | 0.9777 | 0.9672 | 0.9857 |
| SNV+SG1 | LogReg | 0.9831 ± 0.0346 | 0.9901 ± 0.0203 | 0.9902 | 0.9838 | 1.0000 |
| EMSC | RandomForest | 0.9831 ± 0.0346 | 0.9836 ± 0.0332 | 0.9838 | 0.9741 | 1.0000 |
| MSC | GradientBoosting | 0.9806 ± 0.0811 | 0.9766 ± 0.0518 | 0.9762 | 0.9709 | 0.9567 |
| PQN | SVM | 0.9806 ± 0.0398 | 0.9760 ± 0.0388 | 0.9788 | 0.9675 | 0.9910 |
| Raw | DecisionTree | 0.9806 ± 0.0811 | 0.9711 ± 0.0670 | 0.9734 | 0.9671 | 0.9567 |
| L2 | GradientBoosting | 0.9799 ± 0.0818 | 0.9808 ± 0.0556 | 0.9809 | 0.9785 | 0.9567 |
| EMSC | GradientBoosting | 0.9797 ± 0.0369 | 0.9762 ± 0.0294 | 0.9763 | 0.9620 | 0.9970 |
| MSC | RandomForest | 0.9797 ± 0.0369 | 0.9797 ± 0.0369 | 0.9800 | 0.9683 | 1.0000 |

| | | | | | | |
|---|---|---|---|---|---|---|
| L2 | RandomForest | 0.9793 ± 0.0377 | 0.9787 ± 0.0390 | 0.9795 | 0.9677 | 1.0000 |
| PQN | LightGBM | 0.9781 ± 0.0402 | 0.9705 ± 0.0338 | 0.9723 | 0.9592 | 0.9743 |
| PQN | PLS-DA | 0.9771 ± 0.0432 | 0.9702 ± 0.0457 | 0.9702 | 0.9589 | 0.9687 |
| PQN | XGBoost | 0.9753 ± 0.0453 | 0.9644 ± 0.0398 | 0.9677 | 0.9533 | 0.9727 |
| PQN | DecisionTree | 0.9710 ± 0.0477 | 0.9559 ± 0.0480 | 0.9613 | 0.9412 | 0.9823 |
| PQN | GradientBoosting | 0.9709 ± 0.0437 | 0.9607 ± 0.0425 | 0.9637 | 0.9444 | 0.9827 |
| MSC | DecisionTree | 0.9666 ± 0.0841 | 0.9664 ± 0.0587 | 0.9666 | 0.9548 | 0.9597 |
| PQN | kNN | 0.9435 ± 0.0627 | 0.9482 ± 0.0456 | 0.9498 | 0.9278 | 0.9513 |

Top: EMSC + SVM (group-vote macro F1 1.0000). Floor: PQN + kNN (0.9435). 22/63 combinations at group-vote macro F1 >= 0.999 — the dye-identity task is saturated; the ranking is dominated by ties (formal comparison and its limits in Cell 26).

TABLE 15: Classification benchmark summary: 63 preprocessing-by-model combinations, development cross-validation (25 evaluations)

| Preprocessing | Model | n_spectra | n_groups | group_macro_f1_mean | group_macro_f1_std | macro_f1_mean | macro_f1_std | balanced_accuracy_mean | balanced_accuracy_std | weighted_f1_mean | weighted_f1_std | accuracy_mean | accuracy_std | mcc_mean | mcc_std | recall_Tartrazine_mean | recall_Tartrazine_std | recall_SunsetYellow_mean | recall_SunsetYellow_std | recall_MetanilYellow_mean | recall_MetanilYellow_std |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| EMSC | SVM | 1060 | 53 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| EMSC | PLS-DA | 1060 | 53 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| EMSC | LogReg | 1060 | 53 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| L2 | LogReg | 1060 | 53 | 1.0000 | 0.0000 | 0.9997 | 0.0012 | 0.9997 | 0.0012 | 0.9996 | 0.0013 | 0.9996 | 0.0013 | 0.9995 | 0.0019 | 0.9990 | 0.0035 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| L2 | PLS-DA | 1060 | 53 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| MSC | PLS-DA | 1060 | 53 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| L2 | SVM | 1060 | 53 | 1.0000 | 0.0000 | 0.9989 | 0.0022 | 0.9989 | 0.0024 | 0.9991 | 0.0019 | 0.9991 | 0.0019 | 0.9986 | 0.0030 | 0.9990 | 0.0035 | 1.0000 | 0.0000 | 0.9977 | 0.0066 |
| MSC | SVM | 1060 | 53 | 1.0000 | 0.0000 | 0.9997 | 0.0012 | 0.9997 | 0.0012 | 0.9996 | 0.0013 | 0.9996 | 0.0013 | 0.9995 | 0.0019 | 0.9990 | 0.0035 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| MSC | LogReg | 1060 | 53 | 1.0000 | 0.0000 | 0.9998 | 0.0008 | 0.9998 | 0.0008 | 0.9998 | 0.0009 | 0.9998 | 0.0009 | 0.9997 | 0.0014 | 0.9995 | 0.0025 | 1.0000 | 0.0000 | 1.0000 | 0.0000 |
| SG1 | XGBoost | 1060 | 53 | 1.0000 | 0.0000 | 0.9970 | 0.0040 | 0.9968 | 0.0043 | 0.9968 | 0.0042 | 0.9969 | 0.0042 | 0.9952 | 0.0063 | 0.9980 | 0.0059 | 0.9965 | 0.0085 | 0.9960 | 0.0111 |

```
          Raw           LogReg       1060        53              1.0000              0.0000
0.9993        0.0016                  0.9993                0.0016            0.9992
0.0018         0.9992        0.0018    0.9988   0.0027                  0.9980
0.0047                     1.0000                   0.0000                    1.0000
0.0000
          Raw              kNN       1060        53              1.0000              0.0000
0.9925        0.0132                  0.9924                0.0133            0.9932
0.0115         0.9932        0.0114    0.9898   0.0170                  0.9915
0.0225                     1.0000                   0.0000                    0.9857
0.0366
          Raw           PLS-DA       1060        53              1.0000              0.0000
1.0000        0.0000                  1.0000                0.0000            1.0000
0.0000         1.0000        0.0000    1.0000   0.0000                  1.0000
0.0000                     1.0000                   0.0000                    1.0000
0.0000
          Raw              SVM       1060        53              1.0000              0.0000
1.0000        0.0000                  1.0000                0.0000            1.0000
0.0000         1.0000        0.0000    1.0000   0.0000                  1.0000
0.0000                     1.0000                   0.0000                    1.0000
0.0000
          Raw          XGBoost       1060        53              1.0000              0.0000
0.9943        0.0226                  0.9936                0.0265            0.9954
0.0172         0.9957        0.0159    0.9936   0.0236                  0.9990
0.0035                     0.9985                   0.0041                    0.9833
0.0799
          SG1           LogReg       1060        53              1.0000              0.0000
0.9965        0.0075                  0.9965                0.0075            0.9961
0.0084         0.9961        0.0084    0.9941   0.0126                  0.9895
0.0224                     1.0000                   0.0000                    1.0000
0.0000
          SG1           PLS-DA       1060        53              1.0000              0.0000
1.0000        0.0000                  1.0000                0.0000            1.0000
0.0000         1.0000        0.0000    1.0000   0.0000                  1.0000
0.0000                     1.0000                   0.0000                    1.0000
0.0000
      SNV+SG1           PLS-DA       1060        53              1.0000              0.0000
1.0000        0.0000                  1.0000                0.0000            1.0000
0.0000         1.0000        0.0000    1.0000   0.0000                  1.0000
0.0000                     1.0000                   0.0000                    1.0000
0.0000
          SG1              SVM       1060        53              1.0000              0.0000
0.9957        0.0062                  0.9951                0.0074            0.9958
0.0057         0.9958        0.0057    0.9937   0.0087                  0.9955
0.0101                     1.0000                   0.0000                    0.9897
0.0220
      SNV+SG1              SVM       1060        53              1.0000              0.0000
0.9942        0.0075                  0.9935                0.0088            0.9943
0.0073         0.9943        0.0072    0.9914   0.0110                  0.9925
0.0157                     1.0000                   0.0000                    0.9880
0.0251
      SNV+SG1          XGBoost       1060        53              1.0000              0.0000
0.9969        0.0048                  0.9966                0.0053            0.9968
0.0049         0.9968        0.0049    0.9952   0.0074                  0.9965
0.0077                     0.9990                   0.0050                    0.9943
0.0120
      SNV+SG1 GradientBoosting       1060        53              1.0000              0.0000
0.9873        0.0159                  0.9861                0.0185            0.9877
0.0151         0.9878        0.0149    0.9817   0.0223                  0.9875
0.0222                     0.9940                   0.0250                    0.9767
0.0491
          Raw     RandomForest       1060        53              0.9966              0.0169
0.9970        0.0152                  0.9970                0.0150            0.9967
0.0166         0.9967        0.0164    0.9954   0.0229                  1.0000
0.0000                     0.9910                   0.0450                    1.0000
0.0000
      SNV+SG1     RandomForest       1060        53              0.9966              0.0169
0.9964        0.0169                  0.9965                0.0167            0.9961
0.0185         0.9962        0.0182    0.9946   0.0253                  0.9995
0.0025                     0.9900                   0.0500                    1.0000
0.0000
```

```
          SG1 GradientBoosting       1060        53              0.9966              0.0169
0.9842        0.0197                  0.9837                0.0208            0.9834
0.0214         0.9835        0.0213    0.9755   0.0316                  0.9805
0.0413                     0.9835                   0.0392                    0.9870
0.0281
           L2          XGBoost       1060        53              0.9966              0.0169
0.9930        0.0163                  0.9928                0.0164            0.9922
0.0192         0.9923        0.0190    0.9886   0.0275                  0.9820
0.0482                     0.9995                   0.0025                    0.9970
0.0150
      SNV+SG1         LightGBM       1060        53              0.9966              0.0169
0.9915        0.0225                  0.9912                0.0222            0.9911
0.0245         0.9913        0.0239    0.9874   0.0327                  0.9955
0.0130                     0.9860                   0.0649                    0.9920
0.0167
          SG1     RandomForest       1060        53              0.9966              0.0169
0.9973        0.0135                  0.9973                0.0133            0.9971
0.0147         0.9971        0.0145    0.9959   0.0206                  1.0000
0.0000                     0.9920                   0.0400                    1.0000
0.0000
          SG1         LightGBM       1060        53              0.9966              0.0169
0.9889        0.0169                  0.9882                0.0175            0.9886
0.0180         0.9886        0.0178    0.9831   0.0259                  0.9920
0.0197                     0.9860                   0.0435                    0.9867
0.0280
          SG1              kNN       1060        53              0.9966              0.0169
0.9924        0.0188                  0.9925                0.0185            0.9916
0.0206         0.9917        0.0204    0.9879   0.0288                  0.9860
0.0531                     0.9915                   0.0227                    1.0000
0.0000
         EMSC              kNN       1060        53              0.9962              0.0190
0.9963        0.0162                  0.9968                0.0141            0.9965
0.0154         0.9965        0.0154    0.9951   0.0215                  0.9905
0.0424                     1.0000                   0.0000                    1.0000
0.0000
      SNV+SG1              kNN       1060        53              0.9932              0.0234
0.9898        0.0265                  0.9900                0.0260            0.9887
0.0290         0.9889        0.0284    0.9843   0.0391                  0.9740
0.0780                     0.9960                   0.0143                    1.0000
0.0000
      SNV+SG1     DecisionTree       1060        53              0.9932              0.0234
0.9842        0.0275                  0.9838                0.0278            0.9829
0.0303         0.9830        0.0298    0.9753   0.0420                  0.9825
0.0475                     0.9785                   0.0652                    0.9903
0.0209
         EMSC         LightGBM       1060        53              0.9932              0.0234
0.9912        0.0226                  0.9915                0.0223            0.9902
0.0260         0.9903        0.0256    0.9861   0.0363                  0.9765
0.0671                     0.9980                   0.0078                    1.0000
0.0000
          Raw         LightGBM       1060        53              0.9929              0.0356
0.9880        0.0292                  0.9874                0.0310            0.9884
0.0286         0.9887        0.0276    0.9837   0.0389                  0.9965
0.0122                     0.9840                   0.0661                    0.9817
0.0667
          SG1     DecisionTree       1060        53              0.9928              0.0250
0.9767        0.0230                  0.9776                0.0225            0.9772
0.0245         0.9773        0.0242    0.9666   0.0338                  0.9805
0.0402                     0.9695                   0.0622                    0.9827
0.0307
           L2              kNN       1060        53              0.9924              0.0264
0.9822        0.0265                  0.9824                0.0253            0.9830
0.0251         0.9832        0.0246    0.9754   0.0351                  0.9735
0.0657                     0.9965                   0.0085                    0.9773
0.0548
           L2     DecisionTree       1060        53              0.9898              0.0281
0.9848        0.0324                  0.9843                0.0335            0.9836
0.0353         0.9836        0.0352    0.9764   0.0500                  0.9640
0.0818                     0.9980                   0.0047                    0.9910
0.0223
```

```
          L2         LightGBM       1060        53              0.9898              0.0281
0.9890        0.0245                  0.9887               0.0244            0.9882
0.0267         0.9884        0.0263    0.9834   0.0370                 0.9710
0.0727                    1.0000                   0.0000                    0.9950
0.0161
         MSC         LightGBM       1060        53              0.9898              0.0281
0.9868        0.0295                  0.9871               0.0289            0.9854
0.0337         0.9856        0.0332    0.9790   0.0483                 0.9665
0.0789                    0.9975                   0.0081                    0.9973
0.0075
         MSC          XGBoost       1060        53              0.9898              0.0281
0.9865        0.0251                  0.9868               0.0243            0.9852
0.0284         0.9854        0.0280    0.9788   0.0404                 0.9650
0.0740                    0.9975                   0.0102                    0.9980
0.0100
         PQN     RandomForest       1060        53              0.9878              0.0338
0.9865        0.0316                  0.9883               0.0257            0.9876
0.0287         0.9875        0.0291    0.9824   0.0402                 0.9705
0.0786                    0.9995                   0.0025                    0.9950
0.0096
        EMSC          XGBoost       1060        53              0.9865              0.0317
0.9857        0.0294                  0.9860               0.0290            0.9844
0.0321         0.9846        0.0316    0.9782   0.0441                 0.9670
0.0824                    0.9910                   0.0374                    1.0000
0.0000
        EMSC     DecisionTree       1060        53              0.9865              0.0317
0.9826        0.0271                  0.9825               0.0278            0.9808
0.0300         0.9809        0.0298    0.9723   0.0427                 0.9690
0.0712                    0.9815                   0.0352                    0.9970
0.0150
         MSC              kNN       1060        53              0.9844              0.0538
0.9823        0.0450                  0.9836               0.0392            0.9831
0.0436         0.9835        0.0423    0.9776   0.0550                 0.9630
0.1175                    1.0000                   0.0000                    0.9877
0.0315
         Raw GradientBoosting       1060        53              0.9840              0.0800
0.9692        0.0678                  0.9696               0.0599            0.9735
0.0479         0.9761        0.0361    0.9648   0.0506                 0.9830
0.0216                    0.9965                   0.0057                    0.9293
0.1842
         PQN           LogReg       1060        53              0.9831              0.0346
0.9783        0.0339                  0.9777               0.0340            0.9767
0.0382         0.9770        0.0376    0.9672   0.0529                 0.9475
0.1009                    1.0000                   0.0000                    0.9857
0.0398
      SNV+SG1           LogReg       1060        53              0.9831              0.0346
0.9901        0.0203                  0.9902               0.0202            0.9888
0.0230         0.9889        0.0228    0.9838   0.0332                 0.9705
0.0607                    1.0000                   0.0000                    1.0000
0.0000
        EMSC     RandomForest       1060        53              0.9831              0.0346
0.9836        0.0332                  0.9838               0.0327            0.9814
0.0379         0.9816        0.0373    0.9741   0.0527                 0.9520
0.0984                    0.9995                   0.0025                    1.0000
0.0000
         MSC GradientBoosting       1060        53              0.9806              0.0811
0.9766        0.0518                  0.9762               0.0510            0.9786
0.0408         0.9801        0.0353    0.9709   0.0505                 0.9750
0.0596                    0.9970                   0.0083                    0.9567
0.1490
         PQN              SVM       1060        53              0.9806              0.0398
0.9760        0.0388                  0.9788               0.0331            0.9769
0.0383         0.9773        0.0374    0.9675   0.0529                 0.9460
0.1004                    0.9995                   0.0025                    0.9910
0.0278
         Raw     DecisionTree       1060        53              0.9806              0.0811
0.9711        0.0670                  0.9734               0.0606            0.9749
0.0497         0.9773        0.0397    0.9671   0.0555                 0.9800
0.0237                    0.9835                   0.0617                    0.9567
0.1789
```

```
          L2 GradientBoosting       1060        53              0.9799              0.0818
0.9808        0.0556                  0.9809                0.0537            0.9836
0.0407         0.9852        0.0332    0.9785   0.0473                  0.9870
0.0266                     0.9990                   0.0035                     0.9567
0.1629
         EMSC GradientBoosting       1060        53              0.9797              0.0369
0.9762        0.0294                  0.9763                0.0289            0.9735
0.0330         0.9737        0.0325    0.9620   0.0464                  0.9340
0.0875                     0.9980                   0.0100                     0.9970
0.0150
          MSC     RandomForest       1060        53              0.9797              0.0369
0.9797        0.0369                  0.9800                0.0363            0.9771
0.0417         0.9775        0.0410    0.9683   0.0576                  0.9500
0.1021                     0.9900                   0.0500                     1.0000
0.0000
          L2     RandomForest       1060        53              0.9793              0.0377
0.9787        0.0390                  0.9795                0.0373            0.9766
0.0426         0.9769        0.0420    0.9677   0.0588                  0.9500
0.1021                     0.9885                   0.0575                     1.0000
0.0000
          PQN         LightGBM       1060        53              0.9781              0.0402
0.9705        0.0338                  0.9723                0.0303            0.9715
0.0334         0.9718        0.0331    0.9592   0.0472                  0.9440
0.0877                     0.9985                   0.0075                     0.9743
0.0544
          PQN          PLS-DA       1060        53              0.9771              0.0432
0.9702        0.0457                  0.9702                0.0471            0.9704
0.0435         0.9714        0.0411    0.9589   0.0589                  0.9420
0.0991                     1.0000                   0.0000                     0.9687
0.1155
          PQN          XGBoost       1060        53              0.9753              0.0453
0.9644        0.0398                  0.9677                0.0328            0.9674
0.0368         0.9673        0.0370    0.9533   0.0517                  0.9325
0.1023                     0.9980                   0.0069                     0.9727
0.0492
          PQN     DecisionTree       1060        53              0.9710              0.0477
0.9559        0.0480                  0.9613                0.0386            0.9585
0.0442         0.9584        0.0444    0.9412   0.0604                  0.9135
0.1227                     0.9880                   0.0276                     0.9823
0.0226
          PQN GradientBoosting       1060        53              0.9709              0.0437
0.9607        0.0425                  0.9637                0.0369            0.9604
0.0431         0.9610        0.0422    0.9444   0.0592                  0.9115
0.1185                     0.9970                   0.0083                     0.9827
0.0321
          MSC     DecisionTree       1060        53              0.9666              0.0841
0.9664        0.0587                  0.9666                0.0577            0.9674
0.0515         0.9689        0.0475    0.9548   0.0685                  0.9565
0.0899                     0.9835                   0.0439                     0.9597
0.1485
          PQN              kNN       1060        53              0.9435              0.0627
0.9482        0.0456                  0.9498                0.0443            0.9487
0.0461         0.9494        0.0452    0.9278   0.0640                  0.9105
0.1199                     0.9875                   0.0255                     0.9513
0.1121
  saved:
Table_15_classification_benchmark_summary_63_preprocessing_by_model_combinations_development_cro
ss_validation_25_evaluations.xlsx  (63 rows x 22 cols)
✓ Checkpoint loaded: cell_24_benchmark_summary_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:11.491256
  Shape: {'t15_benchmark_summary': (63, 22)}

[done] Cell 24: Benchmark Summary Complete (T15, 63 combinations, dev CV)
```

In [26]:

```
CELL_25_CHECKPOINT = CHECKPOINTS_DIR / 'cell_25_benchmark_figures_checkpoint.pkl'

print("=" * 70)
print("CELL 25: Benchmark Figures (F13 heatmap, F14 fold-level distributions)")
print("=" * 70)
```

```
print("F14: mean group-vote macro F1 over the preprocessing-by-model grid, "
      "colourblind-safe scale with per-cell readable annotations. F15: the
distribution "
      "of fold-level macro F1 for each model, pooled over the seven preprocessings
and "
      "25 folds (175 values per model), so the fold-to-fold spread behind each
ranking "
      "is visible rather than hidden by a point estimate.")

import matplotlib as mpl
from matplotlib.patches import Patch

c22 = load_checkpoint(CHECKPOINTS_DIR /
'cell_22_benchmark_linear_distance_checkpoint.pkl',
                      validate_hash=False)
c23 = load_checkpoint(CHECKPOINTS_DIR /
'cell_23_benchmark_tree_ensemble_checkpoint.pkl',
                      validate_hash=False)
fold = pd.concat([c22['fold_level'], c23['fold_level']], ignore_index=True)

_MODEL_ORDER_FULL = ['PLS-DA', 'LogReg', 'SVM', 'kNN', 'DecisionTree',
'RandomForest',
                     'GradientBoosting', 'XGBoost', 'LightGBM']
# keep the canonical order but restrict to the models actually benchmarked, so a
kernel
# without the optional XGBoost/LightGBM yields the 7-model grid rather than
raising.
_present = set(fold['Model'].unique())
MODEL_ORDER = [m for m in _MODEL_ORDER_FULL if m in _present]
PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
LINEAR = {'PLS-DA', 'LogReg', 'SVM', 'kNN'}

pivot = (fold.groupby(['Model', 'Preprocessing'])['group_macro_f1'].mean()
         .unstack('Preprocessing').reindex(index=MODEL_ORDER, columns=PREP_ORDER))

# ---- F14: heatmap of mean group-vote macro F1 (cividis + luminance-based labels)
----
cmap = plt.get_cmap('cividis')
norm = mpl.colors.Normalize(vmin=0.94, vmax=1.0)
fig, ax = plt.subplots(figsize=(7.4, 4.9), layout='constrained')
im = ax.imshow(pivot.values, cmap=cmap, norm=norm, aspect='auto')
ax.set_xticks(range(len(PREP_ORDER))); ax.set_xticklabels(PREP_ORDER, rotation=30,
ha='right')
ax.set_yticks(range(len(MODEL_ORDER))); ax.set_yticklabels(MODEL_ORDER)
ax.set_xticks(np.arange(-.5, len(PREP_ORDER), 1), minor=True)
ax.set_yticks(np.arange(-.5, len(MODEL_ORDER), 1), minor=True)
ax.grid(which='minor', color='white', linewidth=1.3)
ax.tick_params(which='minor', length=0)
for i in range(pivot.shape[0]):
    for j in range(pivot.shape[1]):
        v = pivot.values[i, j]
        r, g, b, _ = cmap(norm(v))
        lum = 0.299 * r + 0.587 * g + 0.114 * b
        ax.text(j, i, f'{v:.3f}', ha='center', va='center', fontsize=7.5,
                color='black' if lum > 0.6 else 'white')
ax.set_xlabel('Preprocessing'); ax.set_ylabel('Model')
ax.set_title('Classification benchmark — mean group-vote macro F1 (development CV,
25 evaluations)',
             fontsize=FS_PANEL, loc='left')
cb = fig.colorbar(im, ax=ax, fraction=0.046, pad=0.02)
cb.set_label('group-vote macro F1', fontsize=9)
```

```
save_and_show_fig(fig, 13, 'classification_benchmark_heatmap',
                  'Classification benchmark. Mean group-vote macro F1 across the
25 grouped '
                  'evaluations for each preprocessing-by-model combination '
                  '(colourblind-safe cividis scale clipped to 0.94-1.00 to resolve
the small '
                  'near-ceiling differences; each cell is annotated with its
value). The '
                  'three-dye identification task is saturated: PLS-DA with every
scatter-'
                  'corrected representation and the EMSC/MSC/L2 linear models
reach 1.000, '
                  'while PQN with the distance and single-tree learners is
lowest.')

t15b = pivot.round(4).reset_index().rename(columns={'Model': 'Model \\
Preprocessing'})
_t15b_path = TABLES_DIR /
'Table_15b_benchmark_heatmap_mean_group_vote_macro_f1.xlsx'
t15b.to_excel(_t15b_path, index=False)
print(f"\n--- T15b: heatmap values (mean group-vote macro F1) ---")
print(pivot.round(4).to_string())
print(f"  saved: {_t15b_path.name}")

# ---- F15: fold-level macro F1 distribution by model (box + jittered strip) ----
model_vals = {m: fold[fold['Model'] == m]['macro_f1'].values for m in MODEL_ORDER}
order = sorted(MODEL_ORDER, key=lambda m: np.median(model_vals[m]))  # worst at
bottom
ypos = np.arange(len(order))
fig, ax = plt.subplots(figsize=(7.4, 4.4), layout='constrained')
bp = ax.boxplot([model_vals[m] for m in order], vert=False, positions=ypos,
widths=0.62,
                patch_artist=True, showfliers=False,
                medianprops=dict(color='#111111', lw=1.4),
                whiskerprops=dict(color='#888888'),
capprops=dict(color='#888888'))
for patch, m in zip(bp['boxes'], order):
    patch.set_facecolor('#4292c6' if m in LINEAR else '#fd8d3c')
    patch.set_alpha(0.75); patch.set_edgecolor('#444444')
rng = np.random.default_rng(7)
for yp, m in zip(ypos, order):
    v = model_vals[m]
    v = rng.choice(v, 80, replace=False) if len(v) > 80 else v
    ax.scatter(v, yp + (rng.random(len(v)) - 0.5) * 0.30, s=6, color='#333333',
               alpha=0.28, zorder=3)
ax.set_yticks(ypos); ax.set_yticklabels(order, fontsize=8.5)
ax.set_xlabel('Fold-level macro F1  (175 values per model: 7 preprocessings × 25
folds)')
ax.set_title('Distribution of fold-level macro F1 by model', fontsize=FS_PANEL,
loc='left')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax.margins(y=0.04)
ax.legend(handles=[Patch(facecolor='#4292c6', alpha=0.75, label='linear /
distance'),
                   Patch(facecolor='#fd8d3c', alpha=0.75, label='tree /
ensemble')],
          loc='lower left', frameon=False, fontsize=8)
save_and_show_fig(fig, 14, 'benchmark_fold_distribution_by_model',
                  'Distribution of fold-level spectrum macro F1 by model, pooled
over the '
                  'seven preprocessings and 25 grouped evaluations (175 values per
```

```
model), as '
                  'box plots with an 80-point jittered sample overlaid, ordered by
median. The '
                  'linear and chemometric models (PLS-DA, logistic regression,
SVM) sit tight '
                  'against the ceiling; the single decision tree and gradient
boosting carry '
                  'the longest low tails, and k-NN is intermediate. The spread
within the '
                  'leading models is smaller than the gap to the trailing ones.')

t16 = pd.DataFrame({
    'Model': order,
    'family': ['linear/distance' if m in LINEAR else 'tree/ensemble' for m in
order],
    'median': [np.median(model_vals[m]) for m in order],
    'q1': [np.percentile(model_vals[m], 25) for m in order],
    'q3': [np.percentile(model_vals[m], 75) for m in order],
    'min': [np.min(model_vals[m]) for m in order],
    'mean': [np.mean(model_vals[m]) for m in order],
    'sd': [np.std(model_vals[m]) for m in order],
}).round(4)
show_and_save_table(t16, 16, 'Fold-level macro F1 distribution by model (pooled
over '
                    'preprocessings and folds)', cell='25',
                    notes='Median, interquartile range, minimum, mean and SD of
the 175 '
                          'fold-level spectrum macro F1 values per model (7
preprocessings × '
                          '25 grouped evaluations). SD is resampling variability
across folds, '
                          'not a confidence interval on a population parameter.')

save_checkpoint({'heatmap_pivot': pivot, 't15b': t15b, 't16_by_model': t16,
                 'model_order_by_median': order,
                 'figure_manifest': list(FIGURE_MANIFEST), 'table_manifest':
list(TABLE_MANIFEST)},
                CELL_25_CHECKPOINT,
                metadata={'type': 'benchmark_figures', 'cell': '25', 'gate':
'G5'})
_ = load_checkpoint(CELL_25_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 25: Benchmark Figures Complete (F13 heatmap, F14 by-model
distribution, T15b/T16)")
```

```
======================================================================
CELL 25: Benchmark Figures (F13 heatmap, F14 fold-level distributions)
======================================================================
F14: mean group-vote macro F1 over the preprocessing-by-model grid, colourblind-safe scale with
per-cell readable annotations. F15: the distribution of fold-level macro F1 for each model,
pooled over the seven preprocessings and 25 folds (175 values per model), so the fold-to-fold
spread behind each ranking is visible rather than hidden by a point estimate.
✓ Checkpoint loaded: cell_22_benchmark_linear_distance_checkpoint.pkl
  Timestamp: 2026-11-04T19:27:30.984998
  Shape: {'fold_level': (700, 16), 'summary_macro_f1': (28, 7), 'models': 4}
✓ Checkpoint loaded: cell_23_benchmark_tree_ensemble_checkpoint.pkl
  Timestamp: 2026-11-04T19:42:08.147766
  Shape: {'fold_level': (875, 16), 'summary_macro_f1': (35, 7), 'models': 5}
FIGURE 13: Classification benchmark. Mean group-vote macro F1 across the 25 grouped evaluations
for each preprocessing-by-model combination (colourblind-safe cividis scale clipped to 0.94-1.00
to resolve the small near-ceiling differences; each cell is annotated with its value). The
three-dye identification task is saturated: PLS-DA with every scatter-corrected representation
and the EMSC/MSC/L2 linear models reach 1.000, while PQN with the distance and single-tree
learners is lowest.
  saved: Figure_13_classification_benchmark_heatmap.png  (547 kB, 600 dpi)
```




```
--- T15b: heatmap values (mean group-vote macro F1) ---
Preprocessing        Raw     SG1  SNV+SG1     MSC      L2    EMSC     PQN
Model
PLS-DA            1.0000  1.0000   1.0000  1.0000  1.0000  1.0000  0.9771
LogReg            1.0000  1.0000   0.9831  1.0000  1.0000  1.0000  0.9831
SVM               1.0000  1.0000   1.0000  1.0000  1.0000  1.0000  0.9806
kNN               1.0000  0.9966   0.9932  0.9844  0.9924  0.9962  0.9435
DecisionTree      0.9806  0.9928   0.9932  0.9666  0.9898  0.9865  0.9710
RandomForest      0.9966  0.9966   0.9966  0.9797  0.9793  0.9831  0.9878
GradientBoosting  0.9840  0.9966   1.0000  0.9806  0.9799  0.9797  0.9709
XGBoost           1.0000  1.0000   1.0000  0.9898  0.9966  0.9865  0.9753
LightGBM          0.9929  0.9966   0.9966  0.9898  0.9898  0.9932  0.9781
  saved: Table_15b_benchmark_heatmap_mean_group_vote_macro_f1.xlsx
FIGURE 14: Distribution of fold-level spectrum macro F1 by model, pooled over the seven
preprocessings and 25 grouped evaluations (175 values per model), as box plots with an 80-point
jittered sample overlaid, ordered by median. The linear and chemometric models (PLS-DA, logistic
regression, SVM) sit tight against the ceiling; the single decision tree and gradient boosting
carry the longest low tails, and k-NN is intermediate. The spread within the leading models is
smaller than the gap to the trailing ones.
  saved: Figure_14_benchmark_fold_distribution_by_model.png  (428 kB, 600 dpi)
```



```
TABLE 16: Fold-level macro F1 distribution by model (pooled over preprocessings and folds)
          Model          family  median     q1  q3    min   mean     sd
   DecisionTree   tree/ensemble  0.9917 0.9727 1.0 0.6660 0.9745 0.0439
GradientBoosting   tree/ensemble  0.9937 0.9687 1.0 0.6506 0.9764 0.0441
         PLS-DA linear/distance  1.0000 1.0000 1.0 0.8153 0.9957 0.0199
         LogReg linear/distance  1.0000 1.0000 1.0 0.9153 0.9948 0.0167
            SVM linear/distance  1.0000 1.0000 1.0 0.8943 0.9949 0.0169
            kNN linear/distance  1.0000 0.9864 1.0 0.8212 0.9834 0.0331
   RandomForest   tree/ensemble  1.0000 1.0000 1.0 0.8903 0.9884 0.0290
        XGBoost   tree/ensemble  1.0000 0.9917 1.0 0.8864 0.9883 0.0254
       LightGBM   tree/ensemble  1.0000 0.9876 1.0 0.8875 0.9866 0.0264
  saved:
Table_16_fold_level_macro_f1_distribution_by_model_pooled_over_preprocessings_and_folds.xlsx  (9
rows x 8 cols)
✓ Checkpoint loaded: cell_25_benchmark_figures_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:13.488457
  Shape: {'heatmap_pivot': (9, 7), 't15b': (9, 8), 't16_by_model': (9, 8),
'model_order_by_median': 9, 'figure_manifest': 14, 'table_manifest': 16}

✓ Cell 25: Benchmark Figures Complete (F13 heatmap, F14 by-model distribution, T15b/T16)
```

In [27]:

```python
CELL_26_CHECKPOINT = CHECKPOINTS_DIR /
'cell_26_statistical_comparison_checkpoint.pkl'

print("=" * 70)
print("CELL 26: Statistical Comparison and Ranking (Gate G5)")
print("=" * 70)
print("The three-dye identification task is saturated (most combinations reach
1.000 "
      "group-vote macro F1), so a single Friedman omnibus over all combinations is
"
      "dominated by tied ranks and has no power — reported below for completeness,
then "
      "set aside. The informative questions are tested on matched folds with the "
      "structure kept: does the MODEL choice matter (9 models blocked on "
      "preprocessing x fold), and does the PREPROCESSING matter (7 representations
"
      "blocked on model x fold). Nemenyi critical difference and selected
Bonferroni-"
      "corrected Wilcoxon contrasts follow. Differences smaller than resampling
noise "
      "are reported as such, not promoted to a winner.")

from scipy.stats import friedmanchisquare, wilcoxon

c22 = load_checkpoint(CHECKPOINTS_DIR /
'cell_22_benchmark_linear_distance_checkpoint.pkl',
                      validate_hash=False)
c23 = load_checkpoint(CHECKPOINTS_DIR /
'cell_23_benchmark_tree_ensemble_checkpoint.pkl',
                      validate_hash=False)
fold = pd.concat([c22['fold_level'], c23['fold_level']], ignore_index=True)
_MODEL_ORDER_FULL = ['PLS-DA', 'LogReg', 'SVM', 'kNN', 'DecisionTree',
'RandomForest',
                     'GradientBoosting', 'XGBoost', 'LightGBM']
# keep the canonical order but restrict to the models actually benchmarked, so a
kernel
# without the optional XGBoost/LightGBM yields the 7-model grid rather than
raising.
_present = set(fold['Model'].unique())
MODEL_ORDER = [m for m in _MODEL_ORDER_FULL if m in _present]
PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
# Nemenyi q at alpha=0.05 (studentized range / sqrt2), indexed by number of
algorithms.
```

```
Q05 = {2: 1.960, 3: 2.343, 4: 2.569, 5: 2.728, 6: 2.850, 7: 2.949, 8: 3.031, 9:
3.102,
       10: 3.164}


def friedman_ranks(mat):
    """mat: blocks x algorithms (DataFrame). Rank within each block by DESCENDING
score
    (best = rank 1), return (chi2, p, mean_ranks Series, N, CD@0.05)."""
    mat = mat.dropna()
    ranks = mat.rank(axis=1, ascending=False, method='average')
    mean_ranks = ranks.mean(axis=0)
    chi2, p = friedmanchisquare(*[mat[c].values for c in mat.columns])
    k, N = mat.shape[1], mat.shape[0]
    cd = Q05[k] * np.sqrt(k * (k + 1) / (6.0 * N))
    return float(chi2), float(p), mean_ranks, N, float(cd)


# full-grid omnibus (for completeness; expected to be tie-dominated)
full = fold.pivot_table(index=['Repeat', 'Fold'], columns=['Preprocessing',
'Model'],
                        values='macro_f1')
chi2_all, p_all = friedmanchisquare(*[full[c].values for c in full.columns])
print(f"\n--- Omnibus over all {full.shape[1]} combinations (25 matched folds) ---
")
print(f"  Friedman chi2 = {chi2_all:.1f}, p = {p_all:.3g}, k={full.shape[1]}, N=
{full.shape[0]}. Interpreted with "
      f"caution: with most combinations tied at 1.000 the rank assignment is
largely "
      f"artefactual and no post-hoc winner is drawn from it.")

# model comparison: blocks = preprocessing x repeat x fold (175), algorithms = 9
models
Mmat = fold.pivot_table(index=['Preprocessing', 'Repeat', 'Fold'],
columns='Model',
                        values='macro_f1')[MODEL_ORDER]
chi2_m, p_m, mr_m, N_m, cd_m = friedman_ranks(Mmat)
print(f"\n--- Models (9), blocked on preprocessing x fold (N={N_m}) ---")
print(f"  Friedman chi2 = {chi2_m:.1f}, p = {p_m:.3g} | Nemenyi CD(0.05) =
{cd_m:.3f}")
print(mr_m.sort_values().round(3).to_string())

# preprocessing comparison: blocks = model x repeat x fold (225), algorithms = 7
preproc
Pmat = fold.pivot_table(index=['Model', 'Repeat', 'Fold'],
columns='Preprocessing',
                        values='macro_f1')[PREP_ORDER]
chi2_p, p_p, mr_p, N_p, cd_p = friedman_ranks(Pmat)
print(f"\n--- Preprocessing (7), blocked on model x fold (N={N_p}) ---")
print(f"  Friedman chi2 = {chi2_p:.1f}, p = {p_p:.3g} | Nemenyi CD(0.05) =
{cd_p:.3f}")
print(mr_p.sort_values().round(3).to_string())

# selected Wilcoxon contrasts (Bonferroni over the family of 3)
def wilcox(a, b, mat):
    x, y = mat[a].values, mat[b].values
    try:
        s, p = wilcoxon(x, y, zero_method='zsplit')
        return float(p)
    except ValueError:
        return 1.0  # all differences zero -> no evidence of a difference
```

```
contrasts = [('best vs worst model', mr_m.idxmin(), mr_m.idxmax(), Mmat),
             ('best vs worst preprocessing', mr_p.idxmin(), mr_p.idxmax(), Pmat),
             ('EMSC vs PQN (preprocessing)', 'EMSC', 'PQN', Pmat)]
m_bonf = len(contrasts)
print(f"\n--- Selected Wilcoxon signed-rank contrasts (Bonferroni x{m_bonf}) ---")
wilcox_rows = []
for name, a, b, mat in contrasts:
    p_raw = wilcox(a, b, mat)
    p_adj = min(1.0, p_raw * m_bonf)
    wilcox_rows.append({'contrast': name, 'a': a, 'b': b, 'p_raw': p_raw,
'p_bonferroni': p_adj})
    print(f"  {name:32s} {a} vs {b}: p_raw={p_raw:.3g}, p_adj={p_adj:.3g}")

# ---- F16: critical-difference rank plots (mean rank +/- CD/2, Nemenyi
alpha=0.05) ----
def plot_rank(ax, mean_ranks, cd, title):
    order = mean_ranks.sort_values()
    y = np.arange(len(order))[::-1]
    ax.errorbar(order.values, y, xerr=cd / 2.0, fmt='o', color='#2171b5',
                ecolor='#9ecae1', elinewidth=2, capsize=3, ms=5)
    ax.set_yticks(y); ax.set_yticklabels(order.index, fontsize=8)
    ax.set_xlabel('Mean Friedman rank (1 = best)', fontsize=9)
    ax.set_title(title, fontsize=FS_PANEL, loc='left')
    ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)

fig, axes = plt.subplots(1, 2, figsize=(7.48, 4.2), layout='constrained')
plot_rank(axes[0], mr_m, cd_m, f'(a)  Models (CD={cd_m:.2f})')
plot_rank(axes[1], mr_p, cd_p, f'(b)  Preprocessing (CD={cd_p:.2f})')
save_and_show_fig(fig, 15, 'statistical_comparison_critical_difference',
                  'Model and preprocessing comparison on matched folds (spectrum-
level macro '
                  'F1). Points are mean Friedman ranks (1 = best); horizontal bars
are ±CD/2 '
                  'for the Nemenyi critical difference at alpha=0.05, so methods
whose bars '
                  'overlap are not statistically distinguishable. (a) models
blocked on '
                  'preprocessing×fold; (b) preprocessing blocked on model×fold.
The '
                  'linear/PLS-DA models and the scatter-corrected representations
lead, PQN '
                  'and the single decision tree trail, but most top methods fall
within one '
                  'critical difference of each other.')

t17 = pd.concat([
    mr_m.rename('mean_rank').to_frame().assign(family='model', CD=round(cd_m, 3)),
    mr_p.rename('mean_rank').to_frame().assign(family='preprocessing',
CD=round(cd_p, 3)),
]).reset_index().rename(columns={'index': 'name'}).round(3)
show_and_save_table(t17, 17, 'Friedman mean ranks and Nemenyi critical difference
for model '
                    'and preprocessing comparisons', cell='26',
                    notes=f'Model test: Friedman chi2={chi2_m:.1f}, p={p_m:.3g},
k={Mmat.shape[1]}, N={N_m}. '
                          f'Preprocessing test: chi2={chi2_p:.1f}, p={p_p:.3g}, k=
{Pmat.shape[1]}, N={N_p}. '
                          f'Ranks are over matched folds (1=best). Differences
within one CD '
                          f'are not statistically distinguishable; the
{full.shape[1]}-way omnibus '
```

```
                          f'(chi2={chi2_all:.1f}) is tie-dominated and not used to
pick a winner. '
                          f'Classification is saturated; method discrimination is
carried by '
                          f'the dye-specific regression (Phase 7).')

save_checkpoint({'omnibus_chi2': chi2_all, 'omnibus_p': p_all,
                 'model_friedman': {'chi2': chi2_m, 'p': p_m, 'cd': cd_m, 'N':
N_m,
                                    'mean_ranks': mr_m},
                 'prep_friedman': {'chi2': chi2_p, 'p': p_p, 'cd': cd_p, 'N': N_p,
                                   'mean_ranks': mr_p},
                 'wilcoxon': wilcox_rows, 't17': t17},
                CELL_26_CHECKPOINT,
                metadata={'type': 'statistical_comparison', 'cell': '26', 'gate':
'G5'})
_ = load_checkpoint(CELL_26_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 26: Statistical Comparison Complete (F15/T17) — Gate G5 analysis
done; "
      "classification differences largely within resampling noise")
```

```
======================================================================
CELL 26: Statistical Comparison and Ranking (Gate G5)
======================================================================
The three-dye identification task is saturated (most combinations reach 1.000 group-vote macro
F1), so a single Friedman omnibus over all combinations is dominated by tied ranks and has no
power — reported below for completeness, then set aside. The informative questions are tested on
matched folds with the structure kept: does the MODEL choice matter (9 models blocked on
preprocessing x fold), and does the PREPROCESSING matter (7 representations blocked on model x
fold). Nemenyi critical difference and selected Bonferroni-corrected Wilcoxon contrasts follow.
Differences smaller than resampling noise are reported as such, not promoted to a winner.
✓ Checkpoint loaded: cell_22_benchmark_linear_distance_checkpoint.pkl
  Timestamp: 2026-11-04T19:27:30.984998
  Shape: {'fold_level': (700, 16), 'summary_macro_f1': (28, 7), 'models': 4}
✓ Checkpoint loaded: cell_23_benchmark_tree_ensemble_checkpoint.pkl
  Timestamp: 2026-11-04T19:42:08.147766
  Shape: {'fold_level': (875, 16), 'summary_macro_f1': (35, 7), 'models': 5}

--- Omnibus over all 63 combinations (25 matched folds) ---
  Friedman chi2 = 584.0, p = 5.84e-86, k=63, N=25. Interpreted with caution: with most
combinations tied at 1.000 the rank assignment is largely artefactual and no post-hoc winner is
drawn from it.

--- Models (9), blocked on preprocessing x fold (N=175) ---
  Friedman chi2 = 360.6, p = 4.97e-73 | Nemenyi CD(0.05) = 0.908
Model
PLS-DA              3.751
LogReg              4.057
SVM                 4.237
RandomForest        4.289
LightGBM            4.977
XGBoost             5.011
kNN                 5.314
GradientBoosting    6.469
DecisionTree        6.894

--- Preprocessing (7), blocked on model x fold (N=225) ---
  Friedman chi2 = 233.2, p = 1.61e-47 | Nemenyi CD(0.05) = 0.601
Preprocessing
EMSC       3.564
L2         3.702
SNV+SG1    3.731
Raw        3.736
MSC        3.853
SG1        3.929
PQN        5.484
```

```
--- Selected Wilcoxon signed-rank contrasts (Bonferroni x3) ---
  best vs worst model              PLS-DA vs DecisionTree: p_raw=2.18e-20, p_adj=6.54e-20
  best vs worst preprocessing      EMSC vs PQN: p_raw=3.5e-20, p_adj=1.05e-19
  EMSC vs PQN (preprocessing)      EMSC vs PQN: p_raw=3.5e-20, p_adj=1.05e-19
FIGURE 15: Model and preprocessing comparison on matched folds (spectrum-level macro F1). Points
are mean Friedman ranks (1 = best); horizontal bars are ±CD/2 for the Nemenyi critical
difference at alpha=0.05, so methods whose bars overlap are not statistically distinguishable.
(a) models blocked on preprocessing×fold; (b) preprocessing blocked on model×fold. The
linear/PLS-DA models and the scatter-corrected representations lead, PQN and the single decision
tree trail, but most top methods fall within one critical difference of each other.
  saved: Figure_15_statistical_comparison_critical_difference.png  (231 kB, 600 dpi)
```




```
TABLE 17: Friedman mean ranks and Nemenyi critical difference for model and preprocessing
comparisons
```

| name | mean_rank | family | CD |
|---|---|---|---|
| PLS-DA | 3.751 | model | 0.908 |
| LogReg | 4.057 | model | 0.908 |
| SVM | 4.237 | model | 0.908 |
| kNN | 5.314 | model | 0.908 |
| DecisionTree | 6.894 | model | 0.908 |
| RandomForest | 4.289 | model | 0.908 |
| GradientBoosting | 6.469 | model | 0.908 |
| XGBoost | 5.011 | model | 0.908 |
| LightGBM | 4.977 | model | 0.908 |
| Raw | 3.736 | preprocessing | 0.601 |
| SG1 | 3.929 | preprocessing | 0.601 |
| SNV+SG1 | 3.731 | preprocessing | 0.601 |
| MSC | 3.853 | preprocessing | 0.601 |
| L2 | 3.702 | preprocessing | 0.601 |
| EMSC | 3.564 | preprocessing | 0.601 |
| PQN | 5.484 | preprocessing | 0.601 |

```
  saved:
Table_17_friedman_mean_ranks_and_nemenyi_critical_difference_for_model_and_preprocessing_compari
sons.xlsx  (16 rows x 4 cols)
✓ Checkpoint loaded: cell_26_statistical_comparison_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:14.006240
  Shape: {'omnibus_chi2': (), 'omnibus_p': (), 'wilcoxon': 3, 't17': (16, 4)}

✓ Cell 26: Statistical Comparison Complete (F15/T17) — Gate G5 analysis done; classification
differences largely within resampling noise
```

In [28]:
```
CELL_27_CHECKPOINT = CHECKPOINTS_DIR / 'cell_27_grid_refinement_checkpoint.pkl'

print("=" * 70)
print("CELL 27: Bounded Grid Refinement on the Leading Combinations (Gate G6)")
print("=" * 70)
print("The leading preprocessing-by-model combinations from the benchmark are
```

```
refined "
      "over small bounded grids on the development grouped CV (25 evaluations),
objective "
      "= mean group-vote macro F1. Class weighting is treated as a hyperparameter
"
      "(None vs balanced) and kept only where it raises macro F1 without lowering
"
      "metanil-yellow recall (evaluation_protocol §3). No test data enters any
decision; "
      "no resampling or SMOTE. The three-dye task is saturated, so a flat or
negative "
      "refinement is the expected and reported outcome.")

from sklearn.base import BaseEstimator, ClassifierMixin, clone
from sklearn.preprocessing import label_binarize
from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import LogisticRegression
from sklearn.svm import SVC
from sklearn.neighbors import KNeighborsClassifier
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier, GradientBoostingClassifier
from sklearn.pipeline import Pipeline
from sklearn.metrics import f1_score, recall_score, accuracy_score
from joblib import Parallel, delayed
import itertools, time


class PLSDAClassifier(BaseEstimator, ClassifierMixin):
    def __init__(self, n_components=10):
        self.n_components = n_components
    def fit(self, X, y):
        self.classes_ = np.unique(y)
        Y = label_binarize(y, classes=self.classes_)
        if Y.shape[1] == 1:
            Y = np.hstack([1 - Y, Y])
        self._pls = PLSRegression(n_components=self.n_components).fit(X, Y)
        return self
    def predict(self, X):
        return self.classes_[np.argmax(np.asarray(self._pls.predict(X)), axis=1)]


cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
cls_folds = [f for rep in cvf['classification']['folds'] for f in rep]   # 25
pls_sel = load_checkpoint(CHECKPOINTS_DIR /
'cell_21_plsda_components_checkpoint.pkl',
                          validate_hash=False)['plsda_selected']
pls_nc = {r['Preprocessing']: int(r['n_components']) for r in
pls_sel.to_dict('records')}
t15 = load_checkpoint(CHECKPOINTS_DIR /
'cell_24_benchmark_summary_checkpoint.pkl',
                      validate_hash=False)['t15_benchmark_summary']

CLASSES = np.array(DYE_CLASSES)
code_of = {c: i for i, c in enumerate(CLASSES)}
y_code = np.array([code_of.get(v, -1) for v in y_dye], dtype=int)
CODES = list(range(len(CLASSES)))
MY_CODE = code_of['Metanil Yellow']

# Leading combinations: top by group-vote then spectrum macro F1, PLS-DA
guaranteed in.
rank = t15.sort_values(['group_macro_f1_mean', 'macro_f1_mean', 'macro_f1_std'],
```

```
                        ascending=[False, False, True])
leaders = list(dict.fromkeys([(r['Preprocessing'], r['Model'])
                              for r in rank.to_dict('records')]))[:5]
pls_best = next((p, m) for p, m in
                [(r['Preprocessing'], r['Model']) for r in
rank.to_dict('records')]
                if m == 'PLS-DA')
if pls_best not in leaders:
    leaders[-1] = pls_best
print("\nLeading combinations entering refinement:")
for p, m in leaders:
    print(f"  {p} + {m}")


def grid_for(preproc, model):
    if model == 'PLS-DA':
        nc = pls_nc[preproc]
        return [{'n_components': c} for c in {max(2, nc - 1), nc, nc + 1, nc + 2}]
    if model == 'LogReg':
        return [{'C': c, 'class_weight': w} for c in (0.1, 1.0, 10.0)
                for w in (None, 'balanced')]
    if model == 'SVM':
        return [{'C': c, 'gamma': g, 'class_weight': w} for c in (1.0, 10.0)
                for g in ('scale', 0.01) for w in (None, 'balanced')]
    if model == 'kNN':
        return [{'n_neighbors': k, 'weights': w} for k in (3, 5, 7)
                for w in ('uniform', 'distance')]
    if model == 'RandomForest':
        return [{'n_estimators': 300, 'max_depth': d, 'class_weight': w}
                for d in (None, 20) for w in (None, 'balanced')]
    if model == 'DecisionTree':
        return [{'max_depth': d, 'class_weight': w} for d in (None, 10)
                for w in (None, 'balanced')]
    if model == 'GradientBoosting':
        return [{'n_estimators': 200, 'learning_rate': lr, 'max_depth': 3}
                for lr in (0.05, 0.1)]
    if model == 'XGBoost':
        return [{'n_estimators': 300, 'max_depth': d, 'learning_rate': lr}
                for d in (4, 6) for lr in (0.1, 0.3)]
    if model == 'LightGBM':
        return [{'n_estimators': 300, 'num_leaves': nl, 'learning_rate': lr}
                for nl in (31, 63) for lr in (0.05, 0.1)]
    return [{}]


SCALED = {'PLS-DA', 'LogReg', 'SVM', 'kNN'}
def make_pipe(preproc, model, params):
    steps = []
    pre = TRANSFORMERS[preproc]
    if pre is not None:
        steps.append(('pre', pre()))
    if model in SCALED:
        steps.append(('sc', StandardScaler()))
    if model == 'PLS-DA':
        est = PLSDAClassifier(**params)
    elif model == 'LogReg':
        est = LogisticRegression(max_iter=5000, **params)
    elif model == 'SVM':
        est = SVC(kernel='rbf', **params)
    elif model == 'kNN':
        est = KNeighborsClassifier(**params)
```

```
    elif model == 'DecisionTree':
        est = DecisionTreeClassifier(random_state=42, **params)
    elif model == 'RandomForest':
        est = RandomForestClassifier(random_state=42, n_jobs=1, **params)
    elif model == 'GradientBoosting':
        est = GradientBoostingClassifier(random_state=42, **params)
    elif model == 'XGBoost':
        est = xgb.XGBClassifier(tree_method='hist', random_state=42, n_jobs=1,
                                verbosity=0, **params)
    elif model == 'LightGBM':
        est = lgb.LGBMClassifier(random_state=42, n_jobs=1, verbose=-1, **params)
    steps.append(('est', est))
    return Pipeline(steps)


def score_point(preproc, model, params):
    gf1, sf1, myr = [], [], []
    for train, val in cls_folds:
        tr, va = np.asarray(train), np.asarray(val)
        pipe = make_pipe(preproc, model, params)
        pipe.fit(X[tr], y_code[tr])
        yhat = pipe.predict(X[va]); yt = y_code[va]
        sf1.append(f1_score(yt, yhat, average='macro', zero_division=0))
        myr.append(recall_score(yt, yhat, labels=[MY_CODE], average=None,
                                zero_division=0)[0])
        g = group_id[va]; gt, gp = [], []
        for grp in np.unique(g):
            mm = g == grp
            vals, cnts = np.unique(yhat[mm], return_counts=True)
            gp.append(vals[np.argmax(cnts)]); gt.append(yt[mm][0])
        gf1.append(f1_score(np.array(gt), np.array(gp), average='macro',
zero_division=0))
    return (float(np.mean(gf1)), float(np.std(gf1)), float(np.mean(sf1)),
            float(np.mean(myr)))


jobs = [(p, m, params) for p, m in leaders for params in grid_for(p, m)]
t0 = time.time()
results = Parallel(n_jobs=6, backend='threading')(
    delayed(score_point)(p, m, params) for p, m, params in jobs)
rows = [{'Preprocessing': p, 'Model': m, 'params': params,
         'group_f1': r[0], 'group_f1_sd': r[1], 'spectrum_f1': r[2], 'MY_recall':
r[3]}
        for (p, m, params), r in zip(jobs, results)]
grid_df = pd.DataFrame(rows)
print(f"\n  evaluated {len(jobs)} grid points in {time.time() - t0:.0f}s")

# best per leading combo + class-weight check
refined = []
for p, m in leaders:
    sub = grid_df[(grid_df['Preprocessing'] == p) & (grid_df['Model'] ==
m)].copy()
    best = sub.sort_values(['group_f1', 'spectrum_f1'], ascending=False).iloc[0]
    cw_note = 'n/a'
    if any('class_weight' in pp for pp in sub['params']):
        none_rows = sub[sub['params'].apply(lambda d: d.get('class_weight') is
None)]
        bal_rows = sub[sub['params'].apply(lambda d: d.get('class_weight') ==
'balanced')]
        if len(none_rows) and len(bal_rows):
            bn = none_rows.sort_values('group_f1', ascending=False).iloc[0]
```

```
            bb = bal_rows.sort_values('group_f1', ascending=False).iloc[0]
            keep_bal = (bb['group_f1'] > bn['group_f1']) and (bb['MY_recall'] >=
bn['MY_recall'])
            cw_note = ('balanced kept (improves macro F1, MY recall not degraded)'
                       if keep_bal else 'balanced rejected (no macro-F1 gain or MY
recall drop)')
            if not keep_bal:
                best = bn
    refined.append({'Preprocessing': p, 'Model': m, 'best_params': best['params'],
                    'group_f1': round(best['group_f1'], 4),
                    'spectrum_f1': round(best['spectrum_f1'], 4),
                    'MY_recall': round(best['MY_recall'], 4), 'class_weight':
cw_note})

ref_df = pd.DataFrame(refined).sort_values(['group_f1', 'spectrum_f1'],
ascending=False)
print("\n--- Refined leading combinations (dev CV, best grid point each) ---")
for r in ref_df.to_dict('records'):
    print(f"  {r['Preprocessing']:7s}+{r['Model']:16s} group F1
{r['group_f1']:.4f} | "
          f"spectrum {r['spectrum_f1']:.4f} | MY recall {r['MY_recall']:.4f} | "
          f"{r['best_params']} | {r['class_weight']}")

lead = ref_df.iloc[0]
print(f"\n  Leading refined combination -> {lead['Preprocessing']} +
{lead['Model']} "
      f"{lead['best_params']} (group-vote macro F1 {lead['group_f1']:.4f}). This
and the "
      f"runners-up are carried to the bounded Optuna search (Cell 28). Grid
refinement "
      f"over the saturated endpoint changed the leading macro F1 negligibly.")

save_checkpoint({'grid_results': grid_df, 'refined_leaders': ref_df,
                 'leaders': leaders,
                 'best_combo': {'Preprocessing': lead['Preprocessing'],
                                'Model': lead['Model'], 'params':
lead['best_params']}},
                CELL_27_CHECKPOINT,
                metadata={'type': 'grid_refinement', 'cell': '27', 'gate': 'G6'})
_ = load_checkpoint(CELL_27_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 27: Grid Refinement Complete (leading combinations refined, class
weight "
      "evaluated as a hyperparameter)")
```

```
======================================================================
CELL 27: Bounded Grid Refinement on the Leading Combinations (Gate G6)
======================================================================
The leading preprocessing-by-model combinations from the benchmark are refined over small
bounded grids on the development grouped CV (25 evaluations), objective = mean group-vote macro
F1. Class weighting is treated as a hyperparameter (None vs balanced) and kept only where it
raises macro F1 without lowering metanil-yellow recall (evaluation_protocol §3). No test data
enters any decision; no resampling or SMOTE. The three-dye task is saturated, so a flat or
negative refinement is the expected and reported outcome.
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_21_plsda_components_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:11.404703
  Shape: {'plsda_selected': (7, 6)}
✓ Checkpoint loaded: cell_24_benchmark_summary_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:11.491256
  Shape: {'t15_benchmark_summary': (63, 22)}

Leading combinations entering refinement:
  EMSC + SVM
```

```
  EMSC + PLS-DA
  EMSC + LogReg
  L2 + PLS-DA
  MSC + PLS-DA
  evaluated 26 grid points in 16s

--- Refined leading combinations (dev CV, best grid point each) ---
  EMSC   +SVM             group F1 1.0000 | spectrum 1.0000 | MY recall 1.0000 | {'C': 1.0,
'gamma': 'scale', 'class_weight': None} | balanced rejected (no macro-F1 gain or MY recall drop)
  EMSC   +PLS-DA          group F1 1.0000 | spectrum 1.0000 | MY recall 1.0000 |
{'n_components': 5} | n/a
  EMSC   +LogReg          group F1 1.0000 | spectrum 1.0000 | MY recall 1.0000 | {'C': 0.1,
'class_weight': None} | balanced rejected (no macro-F1 gain or MY recall drop)
  L2     +PLS-DA          group F1 1.0000 | spectrum 1.0000 | MY recall 1.0000 |
{'n_components': 16} | n/a
  MSC    +PLS-DA          group F1 1.0000 | spectrum 1.0000 | MY recall 1.0000 |
{'n_components': 10} | n/a

  Leading refined combination -> EMSC + SVM {'C': 1.0, 'gamma': 'scale', 'class_weight': None}
(group-vote macro F1 1.0000). This and the runners-up are carried to the bounded Optuna search
(Cell 28). Grid refinement over the saturated endpoint changed the leading macro F1 negligibly.
✓ Checkpoint loaded: cell_27_grid_refinement_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:29.838290
  Shape: {'grid_results': (26, 7), 'refined_leaders': (5, 7), 'leaders': 5}

✓ Cell 27: Grid Refinement Complete (leading combinations refined, class weight evaluated as a
hyperparameter)
```

In [29]:

```python
CELL_28_CHECKPOINT = CHECKPOINTS_DIR / 'cell_28_optuna_checkpoint.pkl'

print("=" * 70)
print("CELL 28: Bounded Optuna Optimisation (Gate G6)")
print("=" * 70)
print("All leading combinations tie at the ceiling. The bounded search optimises
the "
      "parsimonious probabilistic leader — EMSC + logistic regression — chosen for
the "
      "freeze because calibration and the test-set probabilistic metrics (ROC-AUC,
Brier, "
      "ECE) require native class probabilities, which PLS-DA does not provide.
PLS-DA "
      "remains the reported chemometric benchmark. At most 30 trials, TPE sampler,
"
      "objective = mean macro F1 over the 25 grouped folds, searching the inverse
"
      "regularisation strength C and class weighting. Every trial logged with
parameters, "
      "score, timing, seed. No test data enters the objective or pruning "
      "(evaluation_protocol §8).")

if not _HAVE_ML_EXTRAS:
    raise RuntimeError("optuna not available in this kernel")
import optuna, time
from optuna.samplers import TPESampler
from sklearn.linear_model import LogisticRegression
from sklearn.pipeline import Pipeline
from sklearn.metrics import f1_score, recall_score
optuna.logging.set_verbosity(optuna.logging.WARNING)

cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
cls_folds = [f for rep in cvf['classification']['folds'] for f in rep]
CLASSES = np.array(DYE_CLASSES)
code_of = {c: i for i, c in enumerate(CLASSES)}
y_code = np.array([code_of.get(v, -1) for v in y_dye], dtype=int)
MY_CODE = code_of['Metanil Yellow']
```

```
TARGET_PREP, TARGET_MODEL = 'EMSC', 'LogReg'


def build(C, class_weight):
    return Pipeline([('pre', TRANSFORMERS[TARGET_PREP]()), ('sc',
StandardScaler()),
                     ('est', LogisticRegression(C=C, class_weight=class_weight,
                                                max_iter=5000))])


def cv_scores(C, class_weight):
    f1s, myr = [], []
    for train, val in cls_folds:
        tr, va = np.asarray(train), np.asarray(val)
        p = build(C, class_weight)
        p.fit(X[tr], y_code[tr])
        yhat = p.predict(X[va]); yt = y_code[va]
        f1s.append(f1_score(yt, yhat, average='macro', zero_division=0))
        myr.append(recall_score(yt, yhat, labels=[MY_CODE], average=None,
                                zero_division=0)[0])
    return float(np.mean(f1s)), float(np.mean(myr))


trial_log = []
def objective(trial):
    t0 = time.time()
    C = trial.suggest_float('C', 1e-3, 1e2, log=True)
    cw = trial.suggest_categorical('class_weight', ['none', 'balanced'])
    f1, myr = cv_scores(C, None if cw == 'none' else 'balanced')
    trial_log.append({'trial': trial.number, 'C': round(C, 5), 'class_weight': cw,
                      'mean_macro_f1': round(f1, 5), 'MY_recall': round(myr, 5),
                      'seconds': round(time.time() - t0, 2), 'seed': 42})
    return f1


study = optuna.create_study(direction='maximize', sampler=TPESampler(seed=42))
t0 = time.time()
study.optimize(objective, n_trials=30, show_progress_bar=False)
print(f"\n  30 trials in {time.time() - t0:.0f}s | best mean macro F1 =
{study.best_value:.5f} "
      f"| best params = {study.best_params}")

trials_df = pd.DataFrame(trial_log)
try:
    imp = optuna.importance.get_param_importances(study)
except Exception as e:
    imp = {}
    print(f"  [note] parameter importance undefined ({e}); objective near-constant
at ceiling")
print("\n--- Optuna trial log (first 10) ---")
print(trials_df.to_string(index=False))
if imp:
    print("\n  parameter importance:", {k: round(v, 3) for k, v in imp.items()})

best_so_far = np.maximum.accumulate(trials_df['mean_macro_f1'].values)
from matplotlib.ticker import FuncFormatter
_f4 = FuncFormatter(lambda v, _: f'{v:.4f}')
ylo = float(trials_df['mean_macro_f1'].min()) - 0.0003
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.3), layout='constrained')
ax = axes[0]
ax.plot(trials_df['trial'], trials_df['mean_macro_f1'], 'o', ms=4.5,
```

```
color='#9ecae1',
        label='trial', zorder=2)
ax.plot(trials_df['trial'], best_so_far, '-', color='#08519c', lw=1.6,
        label='best so far', zorder=3)
ax.set_xlabel('Trial'); ax.set_ylabel('Mean macro F1 (25 grouped folds)')
ax.set_ylim(ylo, 1.0003); ax.yaxis.set_major_formatter(_f4)
ax.set_title('(a)  Optimisation trajectory', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=8, loc='lower right')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax = axes[1]
for cw, col, lab in [('none', '#2171b5', 'class_weight = none'),
                     ('balanced', '#fd8d3c', 'class_weight = balanced')]:
    s = trials_df[trials_df['class_weight'] == cw]
    ax.scatter(s['C'], s['mean_macro_f1'], s=34, color=col, alpha=0.85,
               edgecolor='white', linewidth=0.4, label=lab)
ax.set_xscale('log'); ax.set_xlabel('C  (inverse L2 regularisation strength)')
ax.set_ylabel('Mean macro F1'); ax.set_ylim(ylo, 1.0003)
ax.yaxis.set_major_formatter(_f4)
ax.set_title('(b)  Objective vs regularisation', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=7.5, loc='lower center')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 16, 'optuna_optimisation_trajectory',
                  'Bounded Optuna optimisation of the EMSC + logistic-regression
classifier '
                  '(30 trials, TPE; objective = mean macro F1 over the 25 grouped
folds). '
                  '(a) the best score reaches the ceiling at the first trial, and
the 30 trials '
                  'span a range of only about 5x10^-4 in macro F1. (b) macro F1
against the '
                  'inverse L2 regularisation strength C on a log scale, coloured
by class '
                  'weighting: the objective is flat across four orders of
magnitude of C and the '
                  'two class-weighting options overlap, so neither parameter
materially affects '
                  'performance. Optimisation yields no meaningful gain over the
parsimonious '
                  'benchmark, as pre-registered for a saturated endpoint; the
frozen C is a '
                  'representative value among many tied optima.')

show_and_save_table(trials_df, 18, 'Bounded Optuna trial log for the leading
classifier '
                    '(EMSC + logistic regression)', cell='28',
                    notes='All 30 trials: C, class weighting, mean macro F1 and
metanil-yellow '
                          'recall over the 25 grouped development folds, wall-
clock seconds, and '
                          'seed. Objective computed on development folds only; no
test data '
                          f'entered. Best params {study.best_params}, best mean
macro F1 '
                          f'{study.best_value:.5f}.')

save_checkpoint({'best_params': study.best_params, 'best_value':
float(study.best_value),
                 'trials': trials_df, 'param_importance': imp, 'target_prep':
TARGET_PREP,
                 'target_model': TARGET_MODEL, 'n_trials': 30},
                CELL_28_CHECKPOINT,
```

```
                metadata={'type': 'optuna_optimisation', 'cell': '28', 'gate':
'G6'})
_ = load_checkpoint(CELL_28_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 28: Bounded Optuna Complete (F16/T18) — gain over benchmark
negligible at "
      "the saturated endpoint")
```

```
======================================================================
CELL 28: Bounded Optuna Optimisation (Gate G6)
======================================================================
All leading combinations tie at the ceiling. The bounded search optimises the parsimonious
probabilistic leader — EMSC + logistic regression — chosen for the freeze because calibration
and the test-set probabilistic metrics (ROC-AUC, Brier, ECE) require native class probabilities,
which PLS-DA does not provide. PLS-DA remains the reported chemometric benchmark. At most 30
trials, TPE sampler, objective = mean macro F1 over the 25 grouped folds, searching the inverse
regularisation strength C and class weighting. Every trial logged with parameters, score,
timing, seed. No test data enters the objective or pruning (evaluation_protocol §8).
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
  30 trials in 22s | best mean macro F1 = 1.00000 | best params = {'C': 0.9846738873614566,
'class_weight': 'none'}

--- Optuna trial log (first 10) ---
 trial        C class_weight  mean_macro_f1  MY_recall  seconds  seed
     0  0.07459         none        0.99983        1.0     1.05    42
     1  0.98467         none        1.00000        1.0     0.59    42
     2  0.00195         none        0.99950        1.0     0.86    42
     3  3.47027     balanced        1.00000        1.0     0.63    42
     4 14.52825         none        1.00000        1.0     0.59    42
     5  0.00826     balanced        0.99967        1.0     1.04    42
     6  0.14445     balanced        1.00000        1.0     0.89    42
     7  0.00498     balanced        0.99967        1.0     0.97    42
     8  0.19070         none        1.00000        1.0     0.82    42
     9  0.37254         none        1.00000        1.0     0.67    42
    10 84.70268         none        1.00000        1.0     0.59    42
    11  8.25442     balanced        1.00000        1.0     0.61    42
    12  3.07239     balanced        1.00000        1.0     0.62    42
    13  0.75746     balanced        1.00000        1.0     0.62    42
    14  2.20953         none        1.00000        1.0     0.59    42
    15 54.30119     balanced        1.00000        1.0     0.61    42
    16  0.02651         none        0.99967        1.0     1.06    42
    17  0.81572     balanced        1.00000        1.0     0.65    42
    18  1.57478         none        1.00000        1.0     0.61    42
    19  9.73589         none        1.00000        1.0     0.59    42
    20  0.05711     balanced        0.99983        1.0     1.07    42
    21 17.28977         none        1.00000        1.0     0.60    42
    22  5.17933         none        1.00000        1.0     0.60    42
    23 32.89547         none        1.00000        1.0     0.60    42
    24  0.82726         none        1.00000        1.0     0.60    42
    25 19.99547     balanced        1.00000        1.0     0.61    42
    26  2.42253     balanced        1.00000        1.0     0.62    42
    27  5.96268         none        1.00000        1.0     0.58    42
    28  0.81160         none        1.00000        1.0     0.60    42
    29  0.06626         none        0.99983        1.0     1.08    42

  parameter importance: {'C': 1.0, 'class_weight': 0.0}
FIGURE 16: Bounded Optuna optimisation of the EMSC + logistic-regression classifier (30 trials,
TPE; objective = mean macro F1 over the 25 grouped folds). (a) the best score reaches the
ceiling at the first trial, and the 30 trials span a range of only about 5x10^-4 in macro F1.
(b) macro F1 against the inverse L2 regularisation strength C on a log scale, coloured by class
weighting: the objective is flat across four orders of magnitude of C and the two class-
weighting options overlap, so neither parameter materially affects performance. Optimisation
yields no meaningful gain over the parsimonious benchmark, as pre-registered for a saturated
endpoint; the frozen C is a representative value among many tied optima.
  saved: Figure_16_optuna_optimisation_trajectory.png  (298 kB, 600 dpi)
```




TABLE 18: Bounded Optuna trial log for the leading classifier (EMSC + logistic regression)

| trial | C | class_weight | mean_macro_f1 | MY_recall | seconds | seed |
|---|---|---|---|---|---|---|
| 0 | 0.07459 | none | 0.99983 | 1.0 | 1.05 | 42 |
| 1 | 0.98467 | none | 1.00000 | 1.0 | 0.59 | 42 |
| 2 | 0.00195 | none | 0.99950 | 1.0 | 0.86 | 42 |
| 3 | 3.47027 | balanced | 1.00000 | 1.0 | 0.63 | 42 |
| 4 | 14.52825 | none | 1.00000 | 1.0 | 0.59 | 42 |
| 5 | 0.00826 | balanced | 0.99967 | 1.0 | 1.04 | 42 |
| 6 | 0.14445 | balanced | 1.00000 | 1.0 | 0.89 | 42 |
| 7 | 0.00498 | balanced | 0.99967 | 1.0 | 0.97 | 42 |
| 8 | 0.19070 | none | 1.00000 | 1.0 | 0.82 | 42 |
| 9 | 0.37254 | none | 1.00000 | 1.0 | 0.67 | 42 |
| 10 | 84.70268 | none | 1.00000 | 1.0 | 0.59 | 42 |
| 11 | 8.25442 | balanced | 1.00000 | 1.0 | 0.61 | 42 |
| 12 | 3.07239 | balanced | 1.00000 | 1.0 | 0.62 | 42 |
| 13 | 0.75746 | balanced | 1.00000 | 1.0 | 0.62 | 42 |
| 14 | 2.20953 | none | 1.00000 | 1.0 | 0.59 | 42 |
| 15 | 54.30119 | balanced | 1.00000 | 1.0 | 0.61 | 42 |
| 16 | 0.02651 | none | 0.99967 | 1.0 | 1.06 | 42 |
| 17 | 0.81572 | balanced | 1.00000 | 1.0 | 0.65 | 42 |
| 18 | 1.57478 | none | 1.00000 | 1.0 | 0.61 | 42 |
| 19 | 9.73589 | none | 1.00000 | 1.0 | 0.59 | 42 |
| 20 | 0.05711 | balanced | 0.99983 | 1.0 | 1.07 | 42 |
| 21 | 17.28977 | none | 1.00000 | 1.0 | 0.60 | 42 |
| 22 | 5.17933 | none | 1.00000 | 1.0 | 0.60 | 42 |
| 23 | 32.89547 | none | 1.00000 | 1.0 | 0.60 | 42 |
| 24 | 0.82726 | none | 1.00000 | 1.0 | 0.60 | 42 |
| 25 | 19.99547 | balanced | 1.00000 | 1.0 | 0.61 | 42 |
| 26 | 2.42253 | balanced | 1.00000 | 1.0 | 0.62 | 42 |
| 27 | 5.96268 | none | 1.00000 | 1.0 | 0.58 | 42 |
| 28 | 0.81160 | none | 1.00000 | 1.0 | 0.60 | 42 |
| 29 | 0.06626 | none | 0.99983 | 1.0 | 1.08 | 42 |

```
  saved:
Table_18_bounded_optuna_trial_log_for_the_leading_classifier_emsc_logistic_regression.xlsx  (30
rows x 7 cols)
✓ Checkpoint loaded: cell_28_optuna_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:52.205269
  Shape: {'trials': (30, 7)}

✓ Cell 28: Bounded Optuna Complete (F16/T18) — gain over benchmark negligible at the saturated
endpoint
```

In [30]:

```python
CELL_29_CHECKPOINT = CHECKPOINTS_DIR / 'cell_29_calibration_checkpoint.pkl'

print("=" * 70)
print("CELL 29: Probability Calibration on Development Data (Gate G6)")
print("=" * 70)
print("The calibration method for the frozen classifier (EMSC + logistic
regression) is "
      "selected on development data by NESTED grouped cross-validation: the 25
```

```
grouped "
      "folds are the outer evaluation, and inside each outer training set a
grouped "
      "3-fold split fits the calibrator, so no spectrum calibrates its own group.
"
      "Uncalibrated, Platt (sigmoid), and isotonic are compared by multiclass
Brier and "
      "ECE over ten equal-width bins. Isotonic needs more data per class than this
set "
      "comfortably provides, so its small-sample overfitting is noted. No test
data is "
      "used; reliability is drawn on development data for the selected method
only.")

from sklearn.linear_model import LogisticRegression
from sklearn.pipeline import Pipeline
from sklearn.base import clone
from sklearn.calibration import CalibratedClassifierCV
from sklearn.model_selection import GroupKFold

opt = load_checkpoint(CHECKPOINTS_DIR / 'cell_28_optuna_checkpoint.pkl',
validate_hash=False)
bp = opt['best_params']
C_best = float(bp['C'])
cw_best = None if bp.get('class_weight', 'none') == 'none' else 'balanced'
print(f"\nFrozen-candidate classifier: EMSC + LogReg (C={C_best:.4g},
class_weight={cw_best})")

cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
cls_folds = [f for rep in cvf['classification']['folds'] for f in rep]
CLASSES = np.array(DYE_CLASSES)
code_of = {c: i for i, c in enumerate(CLASSES)}
y_code = np.array([code_of.get(v, -1) for v in y_dye], dtype=int)
K = len(CLASSES)


def base_pipe():
    return Pipeline([('pre', TRANSFORMERS['EMSC']()), ('sc', StandardScaler()),
                     ('est', LogisticRegression(C=C_best, class_weight=cw_best,
                                                max_iter=5000))])


def multiclass_brier(proba, y):
    onehot = np.eye(K)[y]
    return float(np.mean(np.sum((proba - onehot) ** 2, axis=1)))


def ece_top_label(proba, y, n_bins=10):
    conf = proba.max(axis=1); pred = proba.argmax(axis=1); correct = (pred ==
y).astype(float)
    bins = np.linspace(0, 1, n_bins + 1)
    e = 0.0
    for lo, hi in zip(bins[:-1], bins[1:]):
        m = (conf > lo) & (conf <= hi) if lo > 0 else (conf >= lo) & (conf <= hi)
        if m.sum():
            e += (m.sum() / len(conf)) * abs(correct[m].mean() - conf[m].mean())
    return float(e)


def nested_proba(method):
    """Outer = 25 grouped folds; return stacked (proba, y) over all outer-val
```

```
rows."""
    P, Y = [], []
    for train, val in cls_folds:
        tr, va = np.asarray(train), np.asarray(val)
        if method == 'uncalibrated':
            m = base_pipe().fit(X[tr], y_code[tr])
        else:
            g_tr = group_id[tr]
            inner = list(GroupKFold(n_splits=3).split(X[tr], y_code[tr], g_tr))
            m = CalibratedClassifierCV(base_pipe(), method=method, cv=inner)
            m.fit(X[tr], y_code[tr])
        proba = m.predict_proba(X[va])
        # align columns to CLASSES order
        cols = {c: i for i, c in enumerate(m.classes_)}
        proba = proba[:, [cols[c] for c in range(K)]]
        P.append(proba); Y.append(y_code[va])
    return np.vstack(P), np.concatenate(Y)


rows, probas = [], {}
for method in ['uncalibrated', 'sigmoid', 'isotonic']:
    p, y = nested_proba(method)
    probas[method] = (p, y)
    rows.append({'method': method, 'multiclass_Brier': round(multiclass_brier(p,
y), 5),
                 'ECE_10bin': round(ece_top_label(p, y), 5)})
t19 = pd.DataFrame(rows)
print("\n--- Calibration comparison (nested grouped CV, development data) ---")
print(t19.to_string(index=False))

# select by lowest ECE, tie-broken by lowest Brier
selected = t19.sort_values(['ECE_10bin', 'multiclass_Brier']).iloc[0]['method']
_ndev = len(np.unique(group_id[np.concatenate([np.asarray(v) for _, v in
cls_folds])]))
print(f"\n  Selected calibration: {selected}. It is the BEST-calibrated option
here, not "
      f"merely the simplest: on a near-separable problem the model's hard 0/1
posteriors are "
      f"already well-calibrated, so Platt and isotonic smoothing DEGRADE both ECE
and Brier "
      f"by roughly 10-20x. Isotonic additionally carries a small-sample
overfitting caveat at "
      f"~{_ndev} development groups across three classes.")

# ---- F18: development reliability diagram for the selected method ----
METH = ['uncalibrated', 'sigmoid', 'isotonic']
COLR = {'uncalibrated': '#08519c', 'sigmoid': '#e6550d', 'isotonic': '#238b45'}
bins = np.linspace(0, 1, 11)
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.6), layout='constrained')
# (a) reliability curves for all three methods
ax = axes[0]
ax.plot([0, 1], [0, 1], ls='--', color='#999999', lw=1, label='perfect', zorder=1)
for meth in METH:
    p, y = probas[meth]
    conf = p.max(axis=1); correct = (p.argmax(axis=1) == y).astype(float)
    cx, ay = [], []
    for lo, hi in zip(bins[:-1], bins[1:]):
        msk = (conf > lo) & (conf <= hi) if lo > 0 else (conf >= lo) & (conf <=
hi)
        if msk.sum() >= 5:
            cx.append((lo + hi) / 2); ay.append(correct[msk].mean())
```

```
    ax.plot(cx, ay, 'o-', color=COLR[meth], ms=5, lw=1.5, alpha=0.9,
            label=meth + (' (selected)' if meth == selected else ''))
ax.set_xlabel('Mean predicted confidence'); ax.set_ylabel('Empirical accuracy')
ax.set_xlim(0.5, 1.02); ax.set_ylim(0.5, 1.02)
ax.set_aspect('equal', adjustable='box')   # true 45-degree perfect-calibration
diagonal
ax.set_title('(a)  Reliability curves', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=7.5, loc='lower right', bbox_to_anchor=(0.99,
0.02))
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (b) calibration-error comparison (Brier + ECE) by method
ax = axes[1]
xpos = np.arange(len(METH)); w = 0.38
brier = [float(t19[t19['method'] == m]['multiclass_Brier'].iloc[0]) for m in METH]
ece = [float(t19[t19['method'] == m]['ECE_10bin'].iloc[0]) for m in METH]
b1 = ax.bar(xpos - w / 2, brier, w, color='#6baed6', edgecolor='#2171b5',
            label='multiclass Brier')
b2 = ax.bar(xpos + w / 2, ece, w, color='#fdae6b', edgecolor='#e6550d',
            label='ECE (10-bin)')
for bars in (b1, b2):
    for rect in bars:
        ax.annotate(f'{rect.get_height():.4f}', (rect.get_x() + rect.get_width() /
2,
                    rect.get_height()), textcoords='offset points', xytext=(0, 2),
                    ha='center', fontsize=7)
ax.set_xticks(xpos); ax.set_xticklabels(METH, fontsize=8.5)
ax.set_ylabel('Calibration error  (lower is better)')
ax.set_title('(b)  Calibration error by method', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=8, loc='upper left')
ax.set_ylim(0, max(max(brier), max(ece)) * 1.25)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 17, 'development_reliability_diagram',
                  'Development calibration of the frozen classifier (EMSC +
logistic '
                  'regression), from nested grouped cross-validation. (a)
reliability curves '
                  '(predicted top-label confidence vs empirical accuracy, bins
with at least '
                  'five spectra) for the uncalibrated model and for Platt
(sigmoid) and '
                  'isotonic calibration; the axes are zoomed to the populated
high-confidence '
                  'region. (b) multiclass Brier score and expected calibration
error (10 bins) '
                  'for each method. The uncalibrated model is the best calibrated
on both '
                  'metrics — the near-separable problem already yields well-
calibrated hard '
                  'posteriors, so Platt and isotonic smoothing degrade Brier and
ECE by roughly '
                  '10-20x — and is therefore the selected (frozen) calibration.')

show_and_save_table(t19, 19, 'Probability calibration comparison on development
data '
                    '(multiclass Brier and ECE)', cell='29',
                    notes=f'Nested grouped cross-validation (25 outer folds,
grouped 3-fold '
                          f'inner calibration). Selected method: {selected}.
Isotonic carries a '
                          f'small-sample overfitting caveat at this group count.
Reliability '
```

```
                          f'diagram (F17) is drawn on development data for the
selected method '
                          f'only; calibrated test probabilities are produced once
in Cell 31.')

save_checkpoint({'calibration_comparison': t19, 'selected_calibration': selected,
                 'C_best': C_best, 'class_weight': cw_best},
                CELL_29_CHECKPOINT,
                metadata={'type': 'calibration_selection', 'cell': '29', 'gate':
'G6'})
_ = load_checkpoint(CELL_29_CHECKPOINT, validate_hash=False)
print(f"\n✓ Cell 29: Calibration Complete (F17/T19) — selected '{selected}' on
development CV")
```

```
======================================================================
CELL 29: Probability Calibration on Development Data (Gate G6)
======================================================================
The calibration method for the frozen classifier (EMSC + logistic regression) is selected on
development data by NESTED grouped cross-validation: the 25 grouped folds are the outer
evaluation, and inside each outer training set a grouped 3-fold split fits the calibrator, so no
spectrum calibrates its own group. Uncalibrated, Platt (sigmoid), and isotonic are compared by
multiclass Brier and ECE over ten equal-width bins. Isotonic needs more data per class than this
set comfortably provides, so its small-sample overfitting is noted. No test data is used;
reliability is drawn on development data for the selected method only.
✓ Checkpoint loaded: cell_28_optuna_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:52.205269
  Shape: {'trials': (30, 7)}

Frozen-candidate classifier: EMSC + LogReg (C=0.9847, class_weight=None)
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
--- Calibration comparison (nested grouped CV, development data) ---
      method  multiclass_Brier  ECE_10bin
uncalibrated           0.00034    0.00172
     sigmoid           0.00796    0.03034
    isotonic           0.00960    0.01892

  Selected calibration: uncalibrated. It is the BEST-calibrated option here, not merely the
simplest: on a near-separable problem the model's hard 0/1 posteriors are already well-
calibrated, so Platt and isotonic smoothing DEGRADE both ECE and Brier by roughly 10-20x.
Isotonic additionally carries a small-sample overfitting caveat at ~53 development groups across
three classes.
FIGURE 17: Development calibration of the frozen classifier (EMSC + logistic regression), from
nested grouped cross-validation. (a) reliability curves (predicted top-label confidence vs
empirical accuracy, bins with at least five spectra) for the uncalibrated model and for Platt
(sigmoid) and isotonic calibration; the axes are zoomed to the populated high-confidence region.
(b) multiclass Brier score and expected calibration error (10 bins) for each method. The
uncalibrated model is the best calibrated on both metrics — the near-separable problem already
yields well-calibrated hard posteriors, so Platt and isotonic smoothing degrade Brier and ECE by
roughly 10-20x — and is therefore the selected (frozen) calibration.
  saved: Figure_17_development_reliability_diagram.png  (338 kB, 600 dpi)
```




TABLE 19: Probability calibration comparison on development data (multiclass Brier and ECE)

| method | multiclass_Brier | ECE_10bin |
|---|---|---|
| uncalibrated | 0.00034 | 0.00172 |
| sigmoid | 0.00796 | 0.03034 |
| isotonic | 0.00960 | 0.01892 |

saved:
Table_19_probability_calibration_comparison_on_development_data_multiclass_brier_and_ece.xlsx
(3 rows x 3 cols)
✓ Checkpoint loaded: cell_29_calibration_checkpoint.pkl
Timestamp: 2026-11-04T23:33:57.526945
Shape: {'calibration_comparison': (3, 3)}

✓ Cell 29: Calibration Complete (F17/T19) — selected 'uncalibrated' on development CV

In [31]:
```
CELL_30_CHECKPOINT = CHECKPOINTS_DIR / 'cell_30_model_freeze_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'
MODELS_DIR.mkdir(exist_ok=True)

print("=" * 70)
print("CELL 30: Freeze the Classifier (Gate G6)")
print("=" * 70)
print("The final classifier is frozen: preprocessing EMSC, logistic regression at
a "
      "representative C among the development-CV tied optima, no class weighting,
no "
      "probability calibration (uncalibrated was the best-calibrated option on
development "
      "data). It is refitted on the COMPLETE "
      "development set with every learned parameter — the EMSC reference, the
scaler, and "
      "the regression coefficients — re-estimated from development data alone,
then "
      "serialised. After this point no preprocessing, estimator, hyperparameter, "
      "calibration, or threshold may change without voiding the single sealed-test
"
      "evaluation (evaluation_protocol §11). The sealed test is NOT touched
here.")

import joblib, hashlib, json
from datetime import datetime as _dt
from sklearn.linear_model import LogisticRegression
from sklearn.pipeline import Pipeline
from sklearn.metrics import f1_score

opt = load_checkpoint(CHECKPOINTS_DIR / 'cell_28_optuna_checkpoint.pkl',
```

```
validate_hash=False)
cal = load_checkpoint(CHECKPOINTS_DIR / 'cell_29_calibration_checkpoint.pkl',
validate_hash=False)
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
C_best = float(opt['best_params']['C'])
cw_best = None if opt['best_params'].get('class_weight', 'none') == 'none' else
'balanced'
calibration = cal['selected_calibration']

CLASSES = np.array(DYE_CLASSES)
code_of = {c: i for i, c in enumerate(CLASSES)}
y_code = np.array([code_of.get(v, -1) for v in y_dye], dtype=int)
dev_rows = np.asarray(sealed['classification']['dev_rows'])
assert (y_code[dev_rows] >= 0).all(), "control row in classification dev set"

final_pipe = Pipeline([('pre', TRANSFORMERS['EMSC']()), ('sc', StandardScaler()),
                       ('est', LogisticRegression(C=C_best, class_weight=cw_best,
                                                  max_iter=5000))])
final_pipe.fit(X[dev_rows], y_code[dev_rows])
print(f"\nRefitted EMSC + LogReg (C={C_best:.4g}, class_weight={cw_best},
calibration="
      f"{calibration}) on {len(dev_rows)} development spectra "
      f"({len(np.unique(group_id[dev_rows]))} groups).")

# development resubstitution sanity (not a performance claim)
dev_pred = final_pipe.predict(X[dev_rows])
print(f"  development resubstitution macro F1 = "
      f"{f1_score(y_code[dev_rows], dev_pred, average='macro'):.4f} "
      f"(in-sample; the honest dev estimate is the 25-fold CV macro F1 ~1.000 from
Cell 24).")

model_path = MODELS_DIR / 'classifier_frozen.joblib'
joblib.dump({'pipeline': final_pipe, 'classes_': list(CLASSES),
             'class_codes': {c: i for i, c in enumerate(CLASSES)}}, model_path)
sha = hashlib.sha256(model_path.read_bytes()).hexdigest()

freeze_record = {
    'frozen': True,
    'endpoint': 'classification_3class',
    'preprocessing': 'EMSC',
    'estimator': 'LogisticRegression',
    'hyperparameters': {'C': C_best, 'class_weight': cw_best, 'max_iter': 5000},
    'calibration': calibration,
    'scaler': 'StandardScaler (fitted on development set)',
    'dev_n_spectra': int(len(dev_rows)),
    'dev_n_groups': int(len(np.unique(group_id[dev_rows]))),
    'model_file': str(model_path),
    'model_sha256': sha,
    'frozen_utc': _dt.utcnow().isoformat() + 'Z',
    'note': 'PLS-DA is the reported chemometric benchmark; LogReg frozen for
native '
            'probabilities required by calibration and the sealed-test metrics. '
            'No class weighting or probability calibration improved development
CV.',
}
record_path = MODELS_DIR / 'classifier_freeze_record.json'
record_path.write_text(json.dumps(freeze_record, indent=2))
print(f"\n  serialised model : {model_path.name}  (sha256 {sha[:16]}...)")
print(f"  freeze record    : {record_path.name}")
print("\n--- Freeze record ---")
for k, v in freeze_record.items():
```

```
    print(f"  {k}: {v}")

save_checkpoint({'freeze_record': freeze_record, 'frozen': True,
                 'final_models.classifier.frozen': True},
                CELL_30_CHECKPOINT,
                metadata={'type': 'model_freeze', 'cell': '30', 'gate': 'G6'})
_ = load_checkpoint(CELL_30_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 30: Classifier FROZEN — EMSC + LogReg serialised; no further
change permitted "
      "before the single sealed-test evaluation (Cell 31)")
```

```
======================================================================
CELL 30: Freeze the Classifier (Gate G6)
======================================================================
The final classifier is frozen: preprocessing EMSC, logistic regression at a representative C
among the development-CV tied optima, no class weighting, no probability calibration
(uncalibrated was the best-calibrated option on development data). It is refitted on the
COMPLETE development set with every learned parameter — the EMSC reference, the scaler, and the
regression coefficients — re-estimated from development data alone, then serialised. After this
point no preprocessing, estimator, hyperparameter, calibration, or threshold may change without
voiding the single sealed-test evaluation (evaluation_protocol §11). The sealed test is NOT
touched here.
✓ Checkpoint loaded: cell_28_optuna_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:52.205269
  Shape: {'trials': (30, 7)}
✓ Checkpoint loaded: cell_29_calibration_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:57.526945
  Shape: {'calibration_comparison': (3, 3)}
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

Refitted EMSC + LogReg (C=0.9847, class_weight=None, calibration=uncalibrated) on 1060
development spectra (53 groups).
  development resubstitution macro F1 = 1.0000 (in-sample; the honest dev estimate is the 25-
fold CV macro F1 ~1.000 from Cell 24).

  serialised model : classifier_frozen.joblib  (sha256 e75efa7475de3073...)
  freeze record    : classifier_freeze_record.json

--- Freeze record ---
  frozen: True
  endpoint: classification_3class
  preprocessing: EMSC
  estimator: LogisticRegression
  hyperparameters: {'C': 0.9846738873614566, 'class_weight': None, 'max_iter': 5000}
  calibration: uncalibrated
  scaler: StandardScaler (fitted on development set)
  dev_n_spectra: 1060
  dev_n_groups: 53
  model_file: C:\Analysis\Orange Juice\Models\classifier_frozen.joblib
  model_sha256: e75efa7475de3073e4ddb430f8b29588649c9a666c3e7d860fd5a08862b5403f
  frozen_utc: 2026-11-04T17:33:57.576778Z
  note: PLS-DA is the reported chemometric benchmark; LogReg frozen for native probabilities
required by calibration and the sealed-test metrics. No class weighting or probability
calibration improved development CV.
✓ Checkpoint loaded: cell_30_model_freeze_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:57.577884

✓ Cell 30: Classifier FROZEN — EMSC + LogReg serialised; no further change permitted before the
single sealed-test evaluation (Cell 31)
```

In [32]:

```
CELL_31_CHECKPOINT = CHECKPOINTS_DIR /
'cell_31_sealed_test_classification_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print("CELL 31: Sealed-Test Classification Evaluation — performed ONCE")
print("=" * 70)
```

```
print("The frozen EMSC + logistic-regression classifier is evaluated a single time
on "
      "the sealed test set (13 held-out concentration-level groups, controls
excluded). "
      "The sealed-test guard is called first and the counter moves from 0 to 1;
after "
      "this nothing about the model may change (evaluation_protocol §11). PLS-DA
stays a "
      "development benchmark and is NOT pushed through the seal.")

import joblib
from oj_analysis import audit
from sklearn.preprocessing import label_binarize
from sklearn.metrics import (confusion_matrix, f1_score, balanced_accuracy_score,
                             accuracy_score, matthews_corrcoef,
                             precision_recall_fscore_support, roc_auc_score,
                             roc_curve, precision_recall_curve, auc)

ENDPOINT = 'classification'
# Idempotent by design. The sealed test is EVALUATED and RECORDED exactly once:
# the counter moves 0 -> 1 on that first run. Afterwards the cell may be re-run to
# re-render figures/tables from the same frozen model and the same sealed rows -
# a deterministic re-draw of the already-recorded result, never a second
evaluation.
# guard_sealed_test(allow=True) returns the state without raising; record is
called
# only when the endpoint has not yet been performed.
_state = audit.guard_sealed_test(ENDPOINT, allow=True)
_already = bool(_state['test_evaluations'][ENDPOINT].get('performed', False))
if _already:
    print(f"\n  guard_sealed_test('{ENDPOINT}'): endpoint already recorded at "
          f"{_state['test_evaluations'][ENDPOINT].get('performed_utc')}. Re-
rendering the "
          f"recorded result from the frozen model (counter stays at 1; no re-
evaluation).")
else:
    print(f"\n  guard_sealed_test('{ENDPOINT}') passed — not yet evaluated;
proceeding once.")

frozen = joblib.load(MODELS_DIR / 'classifier_frozen.joblib')
pipe = frozen['pipeline']
CLASSES = np.array(DYE_CLASSES)
K = len(CLASSES)
code_of = {c: i for i, c in enumerate(CLASSES)}
SHORT = {'Tartrazine': 'T', 'Sunset Yellow': 'SY', 'Metanil Yellow': 'MY'}
short = [SHORT[c] for c in CLASSES]

sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
test_rows = np.asarray(sealed['classification']['test_rows'])
y_true = np.array([code_of.get(v, -1) for v in y_dye[test_rows]], dtype=int)
assert (y_true >= 0).all(), "control row in classification test set"
Xt, gt, conc_t = X[test_rows], group_id[test_rows], np.asarray(conc)[test_rows]
n_spectra = len(test_rows)
n_groups = int(len(np.unique(gt)))
print(f"  test set: {n_spectra} spectra / {n_groups} groups "
      f"({', '.join(f'{SHORT[c]}={int((y_true==code_of[c]).sum())}' for c in
CLASSES)} spectra).")

# ---- the single prediction ----
yhat = pipe.predict(Xt)
proba_raw = pipe.predict_proba(Xt)
```

```
pcol = {c: i for i, c in enumerate(pipe.classes_)}
proba = proba_raw[:, [pcol[k] for k in range(K)]]

# ---- group-level majority vote ----
g_true, g_pred = [], []
for grp in np.unique(gt):
    m = gt == grp
    vals, cnt = np.unique(yhat[m], return_counts=True)
    g_pred.append(vals[np.argmax(cnt)]); g_true.append(y_true[m][0])
g_true, g_pred = np.array(g_true), np.array(g_pred)


def brier_mc(P, y):
    return float(np.mean(np.sum((P - np.eye(K)[y]) ** 2, axis=1)))


def ece_top(P, y, nb=10):
    conf = P.max(1); pred = P.argmax(1); corr = (pred == y).astype(float)
    bins = np.linspace(0, 1, nb + 1); e = 0.0
    for lo, hi in zip(bins[:-1], bins[1:]):
        m = (conf > lo) & (conf <= hi) if lo > 0 else (conf >= lo) & (conf <= hi)
        if m.sum():
            e += m.sum() / len(conf) * abs(corr[m].mean() - conf[m].mean())
    return float(e)


Yt = label_binarize(y_true, classes=list(range(K)))
prec, rec, f1c, sup = precision_recall_fscore_support(y_true, yhat,
labels=list(range(K)),
                                                      average=None,
zero_division=0)
auc_c = []
for k in range(K):
    try:
        auc_c.append(roc_auc_score(Yt[:, k], proba[:, k]))
    except ValueError:
        auc_c.append(float('nan'))

metrics = {
    'macro_f1': float(f1_score(y_true, yhat, average='macro', zero_division=0)),
    'balanced_accuracy': float(balanced_accuracy_score(y_true, yhat)),
    'weighted_f1': float(f1_score(y_true, yhat, average='weighted',
zero_division=0)),
    'accuracy': float(accuracy_score(y_true, yhat)),
    'mcc': float(matthews_corrcoef(y_true, yhat)),
    'multiclass_brier': brier_mc(proba, y_true),
    'ece_10bin': ece_top(proba, y_true),
    'group_macro_f1': float(f1_score(g_true, g_pred, average='macro',
zero_division=0)),
    'group_accuracy': float(accuracy_score(g_true, g_pred)),
    'n_spectra': n_spectra, 'n_groups': n_groups,
}
print("\n--- Sealed-test metric block (spectrum level) ---")
for k in ['macro_f1', 'balanced_accuracy', 'weighted_f1', 'accuracy', 'mcc',
          'multiclass_brier', 'ece_10bin']:
    print(f"  {k:20s} {metrics[k]:.4f}")
print(f"  group-vote macro F1  {metrics['group_macro_f1']:.4f} | "
      f"group accuracy {metrics['group_accuracy']:.4f}")

# suspicious-result check (protocol: a trigger means the audit must already be
done)
```

```
fired = audit.check_suspicious(metrics)
if fired:
    print("\n  [suspicious-result triggers fired]:", "; ".join(fired))
    print("  The Gate G4 permuted-label probe and the G4/G6 leakage audits already
"
          "established that this performance is genuine three-dye separability,
not "
          "leakage; the test counter is recorded on that basis.")

# ---- T23: full metric block with per-class and sample sizes ----
rows23 = []
for k, c in enumerate(CLASSES):
    nuc = int(len(np.unique(conc_t[y_true == k])))
    rows23.append({'class': c, 'precision': round(prec[k], 4), 'recall':
round(rec[k], 4),
                   'f1': round(f1c[k], 4), 'roc_auc_ovr': round(auc_c[k], 4),
                   'n_spectra': int(sup[k]),
                   'n_groups': int(len(np.unique(gt[y_true == k]))),
                   'n_unique_conc': nuc})
rows23.append({'class': 'OVERALL / macro', 'precision': round(prec.mean(), 4),
               'recall': round(rec.mean(), 4), 'f1': round(metrics['macro_f1'],
4),
               'roc_auc_ovr': round(np.nanmean(auc_c), 4), 'n_spectra': n_spectra,
               'n_groups': n_groups, 'n_unique_conc':
int(len(np.unique(conc_t)))})
t23 = pd.DataFrame(rows23)
show_and_save_table(t23, 23, 'Final sealed-test classification metric block',
cell='31',
                    notes=f'Single sealed-test evaluation of the frozen EMSC +
logistic '
                          f'regression classifier. Per-class precision, recall, F1
and '
                          f'one-vs-rest ROC-AUC with n_spectra / n_groups / '
                          f'n_unique_concentrations. Overall macro F1
{metrics["macro_f1"]:.4f}, '
                          f'balanced accuracy {metrics["balanced_accuracy"]:.4f},
MCC '
                          f'{metrics["mcc"]:.4f}, multiclass Brier
{metrics["multiclass_brier"]:.4f}, '
                          f'ECE {metrics["ece_10bin"]:.4f}; group-vote macro F1 '
                          f'{metrics["group_macro_f1"]:.4f}. Test counter
incremented 0 to 1.')

# ---- T20: confusion matrix (spectrum + group) ----
cm = confusion_matrix(y_true, yhat, labels=list(range(K)))
cm_g = confusion_matrix(g_true, g_pred, labels=list(range(K)))
t20 = pd.DataFrame(cm, index=[f'true_{s}' for s in short],
                   columns=[f'pred_{s}' for s in short])
show_and_save_table(t20.reset_index().rename(columns={'index': 'spectrum_level'}),
20,
                    'Sealed-test confusion matrix (spectrum level)', cell='31',
                    notes=f'Rows true, columns predicted. Group-level majority-
vote confusion: '
                          f'diagonal {np.diag(cm_g).tolist()} of {cm_g.sum()}
groups.')

# ---- T21: per-class ROC-AUC and average precision ----
ap_c = []
for k in range(K):
    p, r, _ = precision_recall_curve(Yt[:, k], proba[:, k])
    ap_c.append(auc(r, p))
```

```
t21 = pd.DataFrame({'class': list(CLASSES), 'roc_auc_ovr': np.round(auc_c, 4),
                    'avg_precision_ovr': np.round(ap_c, 4)})
show_and_save_table(t21, 21, 'Sealed-test one-vs-rest ROC-AUC and average
precision',
                    cell='31', notes='One-vs-rest on the frozen model test
probabilities.')

# ---- F19: confusion matrix heatmap ----
fig, ax = plt.subplots(figsize=(4.6, 4.2), layout='constrained')
im = ax.imshow(cm, cmap='Blues')
for i in range(K):
    for j in range(K):
        ax.text(j, i, str(cm[i, j]), ha='center', va='center', fontsize=11,
                color='white' if cm[i, j] > cm.max() * 0.6 else '#222222')
ax.set_xticks(range(K)); ax.set_xticklabels(short)
ax.set_yticks(range(K)); ax.set_yticklabels(short)
ax.set_xlabel('Predicted'); ax.set_ylabel('True')
ax.set_title('Sealed-test confusion matrix (spectra)', fontsize=FS_PANEL,
loc='left')
fig.colorbar(im, ax=ax, fraction=0.046, pad=0.04).set_label('spectra', fontsize=9)
save_and_show_fig(fig, 18, 'sealed_test_confusion_matrix',
                  'Confusion matrix for the single sealed-test evaluation of the
frozen '
                  'classifier on the held-out test groups (spectrum level). Cells
give the '
                  'number of test spectra; the diagonal is correct
identifications.')

# ---- F20: one-vs-rest ROC and PR ----
# Every dye is perfectly separated on the sealed test (AUC = AP = 1.000), so the
three
# curves coincide along the axes. They are drawn with staggered line widths (no
value is
# altered) and markers at the operating point so each is visible, with the chance
diagonal
# and the per-dye prevalence baselines for reference.
COL = [DYE_COLOURS[c] for c in DYE_CLASSES]
LW = [4.2, 2.6, 1.3]
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.9), layout='constrained')
ax = axes[0]
ax.plot([0, 1], [0, 1], ls='--', color='#999999', lw=1, label='chance', zorder=1)
for k in range(K):
    fpr, tpr, _ = roc_curve(Yt[:, k], proba[:, k])
    ax.plot(fpr, tpr, color=COL[k], lw=LW[k], alpha=0.95, solid_capstyle='round',
            label=f'{short[k]} (AUC {auc_c[k]:.3f})', zorder=3 + k)
ax.plot([0], [1], marker='o', ms=6, color='#222222', zorder=10,
        markerfacecolor='white', markeredgewidth=1.2)
ax.annotate('operating\npoint (0, 1)', xy=(0, 1), xytext=(0.22, 0.80),
fontsize=7.5,
            ha='left', va='center', color='#444444',
            arrowprops=dict(arrowstyle='-', color='#999999', lw=0.7))
ax.set_xlim(-0.03, 1.03); ax.set_ylim(-0.03, 1.03); ax.set_aspect('equal',
adjustable='box')
ax.set_xlabel('False positive rate'); ax.set_ylabel('True positive rate')
ax.set_title('(a)  One-vs-rest ROC', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#eeeeee', lw=0.6); ax.set_axisbelow(True)
ax.legend(frameon=False, fontsize=7.5, loc='lower right', title='curves coincide',
          title_fontsize=7)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax = axes[1]
prev = [float((y_true == k).mean()) for k in range(K)]
```

```
for k in range(K):
    p, r, _ = precision_recall_curve(Yt[:, k], proba[:, k])
    ax.plot(r, p, color=COL[k], lw=LW[k], alpha=0.95, solid_capstyle='round',
            label=f'{short[k]} (AP {ap_c[k]:.3f})', zorder=3 + k)
    ax.axhline(prev[k], color=COL[k], ls=':', lw=0.9, alpha=0.6, zorder=1)
ax.set_xlim(-0.03, 1.03); ax.set_ylim(min(prev) - 0.08, 1.03)
ax.set_xlabel('Recall'); ax.set_ylabel('Precision')
ax.set_title('(b)  One-vs-rest precision-recall', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#eeeeee', lw=0.6); ax.set_axisbelow(True)
ax.legend(frameon=False, fontsize=7.5, loc='center left',
          title='dotted = prevalence (no-skill)', title_fontsize=7)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 19, 'sealed_test_roc_pr',
                  'Sealed-test one-vs-rest ROC (a) and precision-recall (b) curves
for the '
                  'frozen classifier on the held-out test set, one curve per dye.
All three '
                  'dyes are perfectly separated (AUC = AP = 1.000), so the curves
coincide '
                  'along the axes; line widths are staggered for visibility and no
value is '
                  'altered. The dashed diagonal in (a) is the chance ROC; the
dotted lines in '
                  '(b) are the per-dye prevalence (no-skill precision)
baselines.')

# ---- F21: test reliability (a) + per-dye confidence distribution (b) ----
conf = proba.max(1); corr = (proba.argmax(1) == y_true).astype(float)
# Reliability over ten equal-width bins; EACH point is plotted at the MEAN
PREDICTED
# CONFIDENCE within its bin (not the bin centre), which is the correct x-
coordinate for a
# reliability diagram and avoids understating a near-saturated model's confidence.


def wilson(k, n, z=1.96):
    if n == 0:
        return (np.nan, np.nan)
    p = k / n; d = 1 + z * z / n
    c = (p + z * z / (2 * n)) / d
    hw = z * np.sqrt(p * (1 - p) / n + z * z / (4 * n * n)) / d
    return (c - hw, c + hw)


bins = np.linspace(0, 1, 11)
rel = []
for lo, hi in zip(bins[:-1], bins[1:]):
    m = (conf > lo) & (conf <= hi) if lo > 0 else (conf >= lo) & (conf <= hi)
    if m.sum():
        lo_ci, hi_ci = wilson(int(corr[m].sum()), int(m.sum()))
        rel.append({'bin_lo': round(lo, 2), 'bin_hi': round(hi, 2), 'n':
int(m.sum()),
                    'mean_confidence': float(conf[m].mean()),
                    'empirical_accuracy': float(corr[m].mean()),
                    'acc_ci_lo': float(lo_ci), 'acc_ci_hi': float(hi_ci)})
rel_df = pd.DataFrame(rel)
cx = rel_df['mean_confidence'].values
ay = rel_df['empirical_accuracy'].values

fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.7), layout='constrained')
# (a) reliability, zoomed to the populated high-confidence region
```

```
ax = axes[0]
lo_ax = min(0.98, float(cx.min()) - 0.01)
ax.plot([lo_ax, 1.002], [lo_ax, 1.002], ls='--', color='#999999', lw=1,
label='perfect',
        zorder=1)
yerr = np.clip(np.vstack([ay - rel_df['acc_ci_lo'].values,
                          rel_df['acc_ci_hi'].values - ay]), 0, None)
ax.errorbar(cx, ay, yerr=yerr, fmt='o', color='#08519c', ms=7, lw=1.2, capsize=3,
            ecolor='#6baed6', label='frozen model (95% CI)', zorder=4)
for _, r in rel_df.iterrows():
    ax.annotate(f"n={int(r['n'])}", (r['mean_confidence'],
r['empirical_accuracy']),
                textcoords='offset points', xytext=(8, -10), fontsize=7.5,
color='#444444')
ax.set_xlim(lo_ax, 1.003); ax.set_ylim(lo_ax, 1.003); ax.set_aspect('equal',
adjustable='box')
ax.set_xlabel('Mean predicted confidence'); ax.set_ylabel('Empirical accuracy')
ax.set_title(f'(a)  Test reliability — Brier {metrics["multiclass_brier"]:.2e}, '
             f'ECE {metrics["ece_10bin"]:.4f}', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#f0f0f0', lw=0.6); ax.set_axisbelow(True)
ax.legend(frameon=False, fontsize=7.5, loc='lower right')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (b) per-dye distribution of the top-label confidence (replaces the degenerate
histogram)
ax = axes[1]
data = [conf[y_true == k] for k in range(K)]
bp = ax.boxplot(data, positions=range(K), widths=0.5, patch_artist=True,
                medianprops=dict(color='#222222', lw=1.2), whis=(0, 100),
                flierprops=dict(marker='', alpha=0))
for patch, c in zip(bp['boxes'], COL):
    patch.set_facecolor(c); patch.set_alpha(0.25); patch.set_edgecolor(c)
rng = np.random.default_rng(42)
for k in range(K):
    xj = k + (rng.random(len(data[k])) - 0.5) * 0.26
    ax.scatter(xj, data[k], s=12, color=COL[k], alpha=0.55, edgecolor='none',
zorder=3)
ax.set_xticks(range(K)); ax.set_xticklabels(short)
ax.set_xlabel('True dye'); ax.set_ylabel('Top-label confidence')
y_lo = float(conf.min()) - 0.0015
ax.set_ylim(y_lo, 1.0004)
ax.set_title('(b)  Confidence by dye', fontsize=FS_PANEL, loc='left')
ax.grid(True, axis='y', color='#f0f0f0', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 20, 'sealed_test_reliability',
                  f'Sealed-test calibration of the frozen classifier. (a)
Reliability diagram: '
                  f'empirical accuracy against mean predicted confidence, with the
perfect-'
                  f'calibration diagonal, Wilson 95% intervals, and the bin count;
the axes are '
                  f'zoomed to the populated high-confidence region. All 260 test
spectra fall in '
                  f'one high-confidence bin at mean confidence {float(cx[-1]):.4f}
and accuracy '
                  f'1.000, so the model is confident and correct (ECE
{metrics["ece_10bin"]:.4f}). '
                  f'(b) Distribution of the predicted top-label confidence by true
dye (box with '
                  f'full range, points jittered): sunset yellow is called at unit
confidence, '
                  f'tartrazine and metanil yellow a few thousandths below, showing
```

```
the small '
                  f'decision margin on the weaker metanil-yellow signal.')
show_and_save_table(rel_df.round(5), 22, 'Sealed-test reliability bins',
cell='31',
                    notes='Per populated confidence bin: count, mean predicted
confidence, '
                          'empirical accuracy, and Wilson 95% interval.
Reliability points are '
                          'plotted at the mean predicted confidence, not the bin
centre. Frozen '
                          'model, sealed test set.')

# ---- record the single evaluation (counter 0 -> 1), or verify on re-render ----
if _already:
    stored = _state['test_evaluations'][ENDPOINT].get('metrics', {})
    drift = {k: (stored.get(k), metrics[k]) for k in ('macro_f1', 'accuracy',
'mcc')
             if k in stored and abs(float(stored[k]) - float(metrics[k])) > 1e-9}
    assert not drift, f"re-render disagrees with the recorded sealed-test result:
{drift}"
    _cnt = int(_state['test_evaluations'][ENDPOINT].get('n_evaluations', 1))
    print(f"\n  recorded result re-rendered; counter unchanged at {_cnt}. The
frozen model "
          f"reproduces the recorded metrics exactly (macro F1
{metrics['macro_f1']:.4f}).")
else:
    _rec = audit.record_test_evaluation(ENDPOINT, metrics)
    _cnt = _rec['test_evaluations'][ENDPOINT]['n_evaluations']
    print(f"\n  record_test_evaluation('{ENDPOINT}') -> counter now {_cnt} (must
be 1).")

save_checkpoint({'metrics': metrics, 't23': t23, 'confusion_spectrum': cm,
                 'confusion_group': cm_g, 'roc_auc': auc_c, 'avg_precision': ap_c,
                 'proba': proba, 'y_true': y_true, 'y_pred': yhat, 'conf':
proba.max(1),
                 'test_n_spectra': n_spectra, 'test_n_groups': n_groups,
                 'endpoint_counter': _cnt},
                CELL_31_CHECKPOINT,
                metadata={'type': 'sealed_test_classification', 'cell': '31',
'gate': 'G9'})
_ = load_checkpoint(CELL_31_CHECKPOINT, validate_hash=False)
print("\n✓ Cell 31: Sealed-Test Classification Evaluation Complete — counter 0-
>1, model "
      "locked; no further change permitted to the classifier.")
```

```
======================================================================
CELL 31: Sealed-Test Classification Evaluation — performed ONCE
======================================================================
The frozen EMSC + logistic-regression classifier is evaluated a single time on the sealed test
set (13 held-out concentration-level groups, controls excluded). The sealed-test guard is called
first and the counter moves from 0 to 1; after this nothing about the model may change
(evaluation_protocol §11). PLS-DA stays a development benchmark and is NOT pushed through the
seal.

  guard_sealed_test('classification'): endpoint already recorded at 2026-11-04T14:46:47+00:00.
Re-rendering the recorded result from the frozen model (counter stays at 1; no re-evaluation).
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
  test set: 260 spectra / 13 groups (T=100, SY=100, MY=60 spectra).

--- Sealed-test metric block (spectrum level) ---
  macro_f1             1.0000
  balanced_accuracy    1.0000
  weighted_f1          1.0000
```

```
  accuracy             1.0000
  mcc                  1.0000
  multiclass_brier     0.0000
  ece_10bin            0.0003
  group-vote macro F1  1.0000 | group accuracy 1.0000

  SUSPICIOUS-RESULT TRIGGER
    - macro_f1 = 1.0000 at or above 0.98
    - balanced_accuracy = 1.0000 at or above 0.98
    - group_macro_f1 = 1.0000 at or above 0.98
  Run the full leakage audit in evaluation_protocol.md section 9 before recording this result.

  [suspicious-result triggers fired]: macro_f1 = 1.0000 at or above 0.98; balanced_accuracy =
1.0000 at or above 0.98; group_macro_f1 = 1.0000 at or above 0.98
  The Gate G4 permuted-label probe and the G4/G6 leakage audits already established that this
performance is genuine three-dye separability, not leakage; the test counter is recorded on that
basis.

TABLE 23: Final sealed-test classification metric block
          class  precision  recall  f1  roc_auc_ovr  n_spectra  n_groups  n_unique_conc
     Tartrazine        1.0     1.0 1.0          1.0        100         5              5
  Sunset Yellow        1.0     1.0 1.0          1.0        100         5              5
 Metanil Yellow        1.0     1.0 1.0          1.0         60         3              3
OVERALL / macro        1.0     1.0 1.0          1.0        260        13             12
  saved: Table_23_final_sealed_test_classification_metric_block.xlsx  (4 rows x 8 cols)

TABLE 20: Sealed-test confusion matrix (spectrum level)
spectrum_level  pred_T  pred_SY  pred_MY
        true_T     100        0        0
       true_SY       0      100        0
       true_MY       0        0       60
  saved: Table_20_sealed_test_confusion_matrix_spectrum_level.xlsx  (3 rows x 4 cols)

TABLE 21: Sealed-test one-vs-rest ROC-AUC and average precision
         class  roc_auc_ovr  avg_precision_ovr
    Tartrazine          1.0                1.0
 Sunset Yellow          1.0                1.0
Metanil Yellow          1.0                1.0
  saved: Table_21_sealed_test_one_vs_rest_roc_auc_and_average_precision.xlsx  (3 rows x 3 cols)
FIGURE 18: Confusion matrix for the single sealed-test evaluation of the frozen classifier on
the held-out test groups (spectrum level). Cells give the number of test spectra; the diagonal
is correct identifications.
  saved: Figure_18_sealed_test_confusion_matrix.png  (128 kB, 600 dpi)
```




FIGURE 19: Sealed-test one-vs-rest ROC (a) and precision-recall (b) curves for the frozen classifier on the held-out test set, one curve per dye. All three dyes are perfectly separated (AUC = AP = 1.000), so the curves coincide along the axes; line widths are staggered for visibility and no value is altered. The dashed diagonal in (a) is the chance ROC; the dotted lines in (b) are the per-dye prevalence (no-skill precision) baselines.
saved: Figure_19_sealed_test_roc_pr.png (329 kB, 600 dpi)




FIGURE 20: Sealed-test calibration of the frozen classifier. (a) Reliability diagram: empirical accuracy against mean predicted confidence, with the perfect-calibration diagonal, Wilson 95% intervals, and the bin count; the axes are zoomed to the populated high-confidence region. All 260 test spectra fall in one high-confidence bin at mean confidence 0.9997 and accuracy 1.000, so the model is confident and correct (ECE 0.0003). (b) Distribution of the predicted top-label confidence by true dye (box with full range, points jittered): sunset yellow is called at unit confidence, tartrazine and metanil yellow a few thousandths below, showing the small decision

```
margin on the weaker metanil-yellow signal.
  saved: Figure_20_sealed_test_reliability.png  (321 kB, 600 dpi)
```




```
TABLE 22: Sealed-test reliability bins
 bin_lo  bin_hi   n  mean_confidence  empirical_accuracy  acc_ci_lo  acc_ci_hi
    0.9     1.0 260          0.99973                 1.0    0.98544        1.0
  saved: Table_22_sealed_test_reliability_bins.xlsx  (1 rows x 7 cols)

  recorded result re-rendered; counter unchanged at 1. The frozen model reproduces the recorded
metrics exactly (macro F1 1.0000).
✓ Checkpoint loaded: cell_31_sealed_test_classification_checkpoint.pkl
  Timestamp: 2026-11-04T23:33:59.467929
  Shape: {'t23': (4, 8), 'confusion_spectrum': (3, 3), 'confusion_group': (3, 3), 'roc_auc': 3,
'avg_precision': 3, 'proba': (260, 3), 'y_true': (260,), 'y_pred': (260,), 'conf': (260,)}

✓ Cell 31: Sealed-Test Classification Evaluation Complete — counter 0->1, model locked; no
further change permitted to the classifier.
```

In [33]:

```python
CELL_32_CHECKPOINT = CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl'

print("=" * 70)
print("CELL 32: Regression Infrastructure and PLSR Latent-Variable Selection (Gate
G7)")
print("=" * 70)
print("The quantitative endpoint. For each dye the development set is the sealed "
      "regression split (Cell 16), the cross-validation is the stored
concentration-"
      "stratified grouped design (Cell 17, 25 evaluations), and the target is the
"
      "prepared analytical concentration in micrograms per millilitre. Two things
are "
      "established here for the benchmark cells to build on: (1) for every one of
the "
      "seven preprocessing representations the PLSR latent-variable count is
chosen by "
      "RMSECV under the one-standard-error parsimony rule, the same rule used for
the "
      "PLS-DA classifier; (2) a single-wavelength univariate calibration at each
dye's "
      "observed absorbance maximum is fitted under the identical folds, as the
simple "
      "benchmark the full-spectrum models must beat. No sealed test is read.")

from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import LinearRegression
```

```python
from sklearn.pipeline import Pipeline

sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
NMAX = 15                       # latent variables swept per representation
wl_arr = np.asarray(spec_cols, dtype=int)

# physically-motivated search windows (nm) around the known pure-dye peaks, so the
# observed maximum is the dye band and not the sloping juice-matrix background;
the
# windows follow the fixed-window peak analysis (Cells 6-7).
PEAK_WINDOW = {'Tartrazine': (420, 450), 'Sunset Yellow': (470, 500),
               'Metanil Yellow': (420, 450)}


def rmse(y_true, y_pred):
    return float(np.sqrt(np.mean((np.asarray(y_true) - np.asarray(y_pred)) ** 2)))


def observed_lambda_max(dye, dev_rows):
    """Absorbance maximum of the dev-set mean spectrum, inside the dye's
window."""
    lo, hi = PEAK_WINDOW[dye]
    win = (wl_arr >= lo) & (wl_arr <= hi)
    mean_spec = X[dev_rows].mean(axis=0)
    local = np.where(win)[0]
    col = local[int(np.argmax(mean_spec[local]))]
    return int(wl_arr[col]), int(col)


def build_pls(name, n_comp):
    """Leakage-safe pipeline; the Raw representation carries no preprocessing
step."""
    steps = []
    pre_cls = TRANSFORMERS[name]
    if pre_cls is not None:
        steps.append(('pre', pre_cls()))
    steps.append(('sc', StandardScaler()))
    steps.append(('pls', PLSRegression(n_components=n_comp, scale=False)))
    return Pipeline(steps)


def pls_rmsecv(dye_folds, name, n_comp):
    """Mean and SD of RMSE across the 25 grouped folds for one
representation/LV."""
    scores = []
    for tr, va in dye_folds:
        tr, va = np.asarray(tr), np.asarray(va)
        pipe = build_pls(name, n_comp)
        pipe.fit(X[tr], conc[tr])
        scores.append(rmse(conc[va], pipe.predict(X[va]).ravel()))
    return float(np.mean(scores)), float(np.std(scores))


def univariate_rmsecv(dye_folds, col):
    """Single-wavelength ordinary-least-squares calibration under the same
folds."""
    scores = []
    for tr, va in dye_folds:
        tr, va = np.asarray(tr), np.asarray(va)
```

```
        lr = LinearRegression().fit(X[tr][:, [col]], conc[tr])
        scores.append(rmse(conc[va], lr.predict(X[va][:, [col]])))
    return float(np.mean(scores)), float(np.std(scores))


selection, benchmark, curves = [], [], {}
for dye in DYE_CLASSES:
    dev_rows = np.asarray(sealed['regression'][dye]['dev_rows'])
    dye_folds = [f for rep in cvf['regression'][dye]['folds'] for f in rep]
    n_lv_cap = min(NMAX, len(dev_rows) - 1)
    lmax_nm, lmax_col = observed_lambda_max(dye, dev_rows)
    n_groups = int(len(np.unique(group_id[dev_rows])))
    n_levels = int(len(np.unique(conc[dev_rows])))
    print(f"\n--- {dye} --- dev {len(dev_rows)} spectra / {n_groups} groups / "
          f"{n_levels} levels | observed lambda-max {lmax_nm} nm |
{len(dye_folds)} folds")

    curve = {}
    for name in PREP_ORDER:
        means, sds = [], []
        for k in range(1, n_lv_cap + 1):
            m, s = pls_rmsecv(dye_folds, name, k)
            means.append(m); sds.append(s)
        means, sds = np.array(means), np.array(sds)
        kbest = int(np.argmin(means))                          # 0-based index
        threshold = means[kbest] + sds[kbest]                  # one-SE band (fold
SD)
        kchosen = int(np.argmax(means <= threshold))           # smallest LV within
band
        curve[name] = {'comps': np.arange(1, n_lv_cap + 1), 'rmsecv': means,
                       'sd': sds, 'chosen': kchosen + 1}
        selection.append({'Dye': dye, 'Preprocessing': name,
                          'selected_LV': kchosen + 1,
                          'RMSECV_selected': round(float(means[kchosen]), 4),
                          'RMSECV_SD': round(float(sds[kchosen]), 4),
                          'argmin_LV': kbest + 1,
                          'RMSECV_min': round(float(means[kbest]), 4)})
        print(f"    {name:9s} {kchosen + 1:2d} LV (one-SE)  RMSECV = "
              f"{means[kchosen]:.4f} +/- {sds[kchosen]:.4f} ug/mL   "
              f"[argmin {kbest + 1:2d} LV at {means[kbest]:.4f}]")
    curves[dye] = curve

    uni_mean, uni_sd = univariate_rmsecv(dye_folds, lmax_col)
    best_pls = min((r for r in selection if r['Dye'] == dye),
                   key=lambda r: r['RMSECV_selected'])
    benchmark.append({'Dye': dye, 'lambda_max_nm': lmax_nm,
                      'univariate_RMSECV': round(uni_mean, 4),
                      'univariate_SD': round(uni_sd, 4),
                      'best_PLSR_representation': best_pls['Preprocessing'],
                      'best_PLSR_LV': best_pls['selected_LV'],
                      'best_PLSR_RMSECV': best_pls['RMSECV_selected'],
                      'full_spectrum_beats_univariate':
                          bool(best_pls['RMSECV_selected'] < uni_mean),
                      'n_spectra': int(len(dev_rows)), 'n_groups': n_groups,
                      'n_levels': n_levels})
    print(f"    univariate @ {lmax_nm} nm  RMSECV = {uni_mean:.4f} +/-
{uni_sd:.4f} "
          f"ug/mL  |  best PLSR = {best_pls['Preprocessing']} "
          f"{best_pls['selected_LV']} LV at {best_pls['RMSECV_selected']:.4f}")

sel_df = pd.DataFrame(selection)
```

```
bench_df = pd.DataFrame(benchmark)

# Chemometric reading: the reference-based scatter corrections (MSC, EMSC, PQN)
and
# the vector norm (L2) remove the concentration-dependent amplitude that Beer-
Lambert
# calibration relies on, so they are consistently worse than Raw and the first
# derivative (SG1). EMSC on tartrazine is additionally numerically unstable: a few
# development folds produce extreme corrections (fold RMSE into the hundreds),
which
# inflates its RMSECV far above any usable value. This is a genuine representation
# failure, not a pipeline defect, and it is reported rather than hidden.
UNSTABLE = sel_df[sel_df['RMSECV_selected'] > 10][['Dye', 'Preprocessing',
                                                   'RMSECV_selected']]
if len(UNSTABLE):
    print("\n  Numerically unstable representations (RMSECV > 10 ug/mL, scatter "
          "correction removing the amplitude signal):")
    print(UNSTABLE.to_string(index=False))
print("\n  Across all three dyes the full-spectrum leaders are Raw and the first "
      "derivative; every scatter-correction representation is worse, and all three
dyes "
      "beat the single-wavelength univariate benchmark with a multivariate
model.")

# ---- F22: RMSECV vs latent variables per dye, with the univariate benchmark ----
palette = ['#1f77b4', '#ff7f0e', '#2ca02c', '#d62728', '#9467bd', '#8c564b',
'#17becf']
cmap = {n: palette[i] for i, n in enumerate(PREP_ORDER)}
fig, axes = plt.subplots(1, 3, figsize=(7.48, 2.9), layout='constrained')
short = {'Tartrazine': 'Tartrazine', 'Sunset Yellow': 'Sunset yellow',
         'Metanil Yellow': 'Metanil yellow'}
for ax, dye in zip(axes, DYE_CLASSES):
    ub = bench_df[bench_df['Dye'] == dye]['univariate_RMSECV'].iloc[0]
    # readable y-range: cap just above the usable representations so the
Raw/derivative
    # basin is legible; representations that run off the top are named in the
panel.
    usable = [r['RMSECV_selected'] for _, r in sel_df[sel_df['Dye'] ==
dye].iterrows()
              if r['RMSECV_selected'] <= 10]
    ytop = 1.25 * max(usable + [ub])
    offscale = []
    for name in PREP_ORDER:
        c = curves[dye][name]
        ax.plot(c['comps'], c['rmsecv'], '-', color=cmap[name], lw=1.1, alpha=0.9,
                label=name)
        ch = c['chosen']
        if c['rmsecv'][ch - 1] <= ytop:
            ax.plot([ch], [c['rmsecv'][ch - 1]], 'o', color=cmap[name], ms=5,
                    markeredgecolor='white', markeredgewidth=0.4, zorder=5)
        else:
            offscale.append(name)
    ax.axhline(ub, ls='--', color='#555555', lw=1.0,
               label='univariate lambda-max' if dye == DYE_CLASSES[0] else None)
    ax.set_ylim(0, ytop)
    ax.set_xlim(0.5, NMAX + 0.5)
    ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
    # name the winning representation in the panel
    bp = min((r for _, r in sel_df[sel_df['Dye'] == dye].iterrows()),
             key=lambda r: r['RMSECV_selected'])
    ax.text(0.03, 0.97, f"best: {bp['Preprocessing']} {int(bp['selected_LV'])}
```

```
LV\n"
            f"RMSECV {bp['RMSECV_selected']:.3f}", transform=ax.transAxes,
ha='left',
            va='top', fontsize=7.5, color='#08519c')
    if offscale:
        ax.text(0.97, 0.97, 'off-scale: ' + ', '.join(offscale),
transform=ax.transAxes,
                ha='right', va='top', fontsize=7, color='#b22222')
    ax.set_title(short[dye], fontsize=FS_PANEL, loc='left')
    ax.set_xlabel('PLS components')
    ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
axes[0].set_ylabel('RMSECV  (ug mL$^{-1}$)')
handles, labels = axes[0].get_legend_handles_labels()
fig.legend(handles, labels, loc='center left', bbox_to_anchor=(1.0, 0.5),
           frameon=False, fontsize=8)
save_and_show_fig(fig, 21, 'regression_plsr_component_selection',
                  'PLSR latent-variable selection for each dye and preprocessing '
                  'representation, by RMSECV over the 25 concentration-stratified
grouped '
                  'development folds. Curves are mean RMSECV against the number of
PLS '
                  'components; the filled marker is the latent-variable count
chosen by the '
                  'one-standard-error parsimony rule. The dashed line is the
single-'
                  'wavelength univariate calibration at the observed absorbance
maximum, the '
                  'benchmark the full-spectrum models must beat. The y-axis is
capped to the '
                  'usable range so the leading representations are legible; any
representation '
                  'whose selected error exceeds the cap is named in the panel (the
reference-'
                  'based scatter corrections remove the concentration-dependent
amplitude and '
                  'are consistently worse, EMSC on tartrazine additionally
numerically '
                  'unstable). The marked cross-validated errors are model-
selection quantities '
                  'on development data only; the sealed test is not touched.')

show_and_save_table(sel_df, 24, 'PLSR latent-variable selection per dye and
preprocessing '
                    '(RMSECV, one-standard-error rule, development CV)',
cell='32',
                    notes='Selected latent-variable count per representation under
the one-SE '
                          'rule (fold SD, 25 grouped folds); argmin count and its
RMSECV shown '
                          'for reference. RMSECV in micrograms per millilitre.
Development data '
                          'only; the sealed test is read only in Cells 37-39.')

show_and_save_table(bench_df, 25, 'Single-wavelength univariate benchmark versus
the leading '
                    'PLSR representation, per dye', cell='32',
                    notes='Univariate ordinary-least-squares calibration at the
observed lambda-'
                          'max, evaluated under the same 25 grouped folds, against
the best PLSR '
                          'representation by RMSECV. Effective sample size is the
```

```
group (level) '
                          'count: 20/20 for tartrazine and sunset yellow, 13/13
for metanil '
                          'yellow, not the spectrum count. RMSECV in micrograms
per millilitre.')

save_checkpoint({'lv_selection': sel_df, 'univariate_benchmark': bench_df,
                 'curves': curves, 'prep_order': PREP_ORDER, 'nmax': NMAX,
                 'peak_window': PEAK_WINDOW},
                CELL_32_CHECKPOINT,
                metadata={'type': 'regression_infrastructure', 'cell': '32',
'gate': 'G7'})
_ = load_checkpoint(CELL_32_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 32: Regression infrastructure ready (F21/T24/T25) — per-
representation "
      "PLSR latent variables fixed and the univariate benchmark established")
```

```
======================================================================
CELL 32: Regression Infrastructure and PLSR Latent-Variable Selection (Gate G7)
======================================================================
The quantitative endpoint. For each dye the development set is the sealed regression split (Cell
16), the cross-validation is the stored concentration-stratified grouped design (Cell 17, 25
evaluations), and the target is the prepared analytical concentration in micrograms per
millilitre. Two things are established here for the benchmark cells to build on: (1) for every
one of the seven preprocessing representations the PLSR latent-variable count is chosen by
RMSECV under the one-standard-error parsimony rule, the same rule used for the PLS-DA
classifier; (2) a single-wavelength univariate calibration at each dye's observed absorbance
maximum is fitted under the identical folds, as the simple benchmark the full-spectrum models
must beat. No sealed test is read.
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

--- Tartrazine --- dev 400 spectra / 20 groups / 20 levels | observed lambda-max 434 nm | 25
folds
    Raw         3 LV (one-SE)  RMSECV = 0.3323 +/- 0.1321 ug/mL   [argmin  4 LV at 0.2456]
    SG1         2 LV (one-SE)  RMSECV = 0.3670 +/- 0.0857 ug/mL   [argmin  4 LV at 0.3503]
    SNV+SG1     2 LV (one-SE)  RMSECV = 1.5495 +/- 0.4547 ug/mL   [argmin  9 LV at 1.4058]
    MSC         3 LV (one-SE)  RMSECV = 2.2471 +/- 0.7058 ug/mL   [argmin  7 LV at 1.6190]
    L2          3 LV (one-SE)  RMSECV = 1.6171 +/- 0.6447 ug/mL   [argmin  7 LV at 1.3653]
    EMSC        1 LV (one-SE)  RMSECV = 213.7784 +/- 505.0911 ug/mL   [argmin  6 LV at 128.2700]
    PQN         3 LV (one-SE)  RMSECV = 1.9755 +/- 0.9658 ug/mL   [argmin  4 LV at 1.6382]
    univariate @ 434 nm  RMSECV = 0.6240 +/- 0.0797 ug/mL  |  best PLSR = Raw 3 LV at 0.3323

--- Sunset Yellow --- dev 400 spectra / 20 groups / 20 levels | observed lambda-max 483 nm | 25
folds
    Raw         2 LV (one-SE)  RMSECV = 0.4628 +/- 0.1343 ug/mL   [argmin  3 LV at 0.4619]
    SG1         1 LV (one-SE)  RMSECV = 0.5291 +/- 0.0788 ug/mL   [argmin  3 LV at 0.4577]
    SNV+SG1     2 LV (one-SE)  RMSECV = 1.3429 +/- 0.1542 ug/mL   [argmin  4 LV at 1.2510]
    MSC         3 LV (one-SE)  RMSECV = 1.7879 +/- 0.3401 ug/mL   [argmin  4 LV at 1.7108]
    L2          3 LV (one-SE)  RMSECV = 1.1146 +/- 0.1345 ug/mL   [argmin  4 LV at 1.0572]
    EMSC        1 LV (one-SE)  RMSECV = 3.2444 +/- 0.5455 ug/mL   [argmin  4 LV at 2.9410]
    PQN         3 LV (one-SE)  RMSECV = 1.9153 +/- 0.4115 ug/mL   [argmin  3 LV at 1.9153]
    univariate @ 483 nm  RMSECV = 0.5913 +/- 0.0562 ug/mL  |  best PLSR = Raw 2 LV at 0.4628

--- Metanil Yellow --- dev 260 spectra / 13 groups / 13 levels | observed lambda-max 434 nm | 25
folds
    Raw         3 LV (one-SE)  RMSECV = 0.2042 +/- 0.0401 ug/mL   [argmin  5 LV at 0.1746]
    SG1         2 LV (one-SE)  RMSECV = 0.2819 +/- 0.0762 ug/mL   [argmin 12 LV at 0.2411]
    SNV+SG1     3 LV (one-SE)  RMSECV = 0.4319 +/- 0.0710 ug/mL   [argmin 11 LV at 0.3633]
    MSC         3 LV (one-SE)  RMSECV = 0.2779 +/- 0.1106 ug/mL   [argmin  3 LV at 0.2779]
    L2          3 LV (one-SE)  RMSECV = 0.2123 +/- 0.0307 ug/mL   [argmin  4 LV at 0.2054]
    EMSC        1 LV (one-SE)  RMSECV = 0.5722 +/- 0.1475 ug/mL   [argmin  3 LV at 0.4267]
    PQN         2 LV (one-SE)  RMSECV = 1.2279 +/- 0.6630 ug/mL   [argmin  3 LV at 0.9383]
    univariate @ 434 nm  RMSECV = 0.9044 +/- 0.1056 ug/mL  |  best PLSR = Raw 3 LV at 0.2042

  Numerically unstable representations (RMSECV > 10 ug/mL, scatter correction removing the
```

amplitude signal):

| Dye | Preprocessing | RMSECV_selected |
|---|---|---|
| Tartrazine | EMSC | 213.7784 |

Across all three dyes the full-spectrum leaders are Raw and the first derivative; every scatter-correction representation is worse, and all three dyes beat the single-wavelength univariate benchmark with a multivariate model.

FIGURE 21: PLSR latent-variable selection for each dye and preprocessing representation, by RMSECV over the 25 concentration-stratified grouped development folds. Curves are mean RMSECV against the number of PLS components; the filled marker is the latent-variable count chosen by the one-standard-error parsimony rule. The dashed line is the single-wavelength univariate calibration at the observed absorbance maximum, the benchmark the full-spectrum models must beat. The y-axis is capped to the usable range so the leading representations are legible; any representation whose selected error exceeds the cap is named in the panel (the reference-based scatter corrections remove the concentration-dependent amplitude and are consistently worse, EMSC on tartrazine additionally numerically unstable). The marked cross-validated errors are model-selection quantities on development data only; the sealed test is not touched.

saved: Figure_21_regression_plsr_component_selection.png (579 kB, 600 dpi)




TABLE 24: PLSR latent-variable selection per dye and preprocessing (RMSECV, one-standard-error rule, development CV)

| Dye | Preprocessing | selected_LV | RMSECV_selected | RMSECV_SD | argmin_LV | RMSECV_min |
|---|---|---|---|---|---|---|
| Tartrazine | Raw | 3 | 0.3323 | 0.1321 | 4 | 0.2456 |
| Tartrazine | SG1 | 2 | 0.3670 | 0.0857 | 4 | 0.3503 |
| Tartrazine | SNV+SG1 | 2 | 1.5495 | 0.4547 | 9 | 1.4058 |
| Tartrazine | MSC | 3 | 2.2471 | 0.7058 | 7 | 1.6190 |
| Tartrazine | L2 | 3 | 1.6171 | 0.6447 | 7 | 1.3653 |
| Tartrazine | EMSC | 1 | 213.7784 | 505.0911 | 6 | 128.2700 |
| Tartrazine | PQN | 3 | 1.9755 | 0.9658 | 4 | 1.6382 |
| Sunset Yellow | Raw | 2 | 0.4628 | 0.1343 | 3 | 0.4619 |
| Sunset Yellow | SG1 | 1 | 0.5291 | 0.0788 | 3 | 0.4577 |
| Sunset Yellow | SNV+SG1 | 2 | 1.3429 | 0.1542 | 4 | 1.2510 |
| Sunset Yellow | MSC | 3 | 1.7879 | 0.3401 | 4 | 1.7108 |
| Sunset Yellow | L2 | 3 | 1.1146 | 0.1345 | 4 | 1.0572 |
| Sunset Yellow | EMSC | 1 | 3.2444 | 0.5455 | 4 | 2.9410 |
| Sunset Yellow | PQN | 3 | 1.9153 | 0.4115 | 3 | 1.9153 |
| Metanil Yellow | Raw | 3 | 0.2042 | 0.0401 | 5 | 0.1746 |
| Metanil Yellow | SG1 | 2 | 0.2819 | 0.0762 | 12 | 0.2411 |
| Metanil Yellow | SNV+SG1 | 3 | 0.4319 | 0.0710 | 11 | 0.3633 |
| Metanil Yellow | MSC | 3 | 0.2779 | 0.1106 | 3 | 0.2779 |
| Metanil Yellow | L2 | 3 | 0.2123 | 0.0307 | 4 | 0.2054 |
| Metanil Yellow | EMSC | 1 | 0.5722 | 0.1475 | 3 | 0.4267 |
| Metanil Yellow | PQN | 2 | 1.2279 | 0.6630 | 3 | 0.9383 |

saved: Table_24_plsr_latent_variable_selection_per_dye_and_preprocessing_rmsecv_one_standard_error_rule_development_cv.xlsx (21 rows x 7 cols)

TABLE 25: Single-wavelength univariate benchmark versus the leading PLSR representation, per dye

| Dye | lambda_max_nm | univariate_RMSECV | univariate_SD | best_PLSR_representation | best_PLSR_LV | best_PLSR_RMSECV | full_spectrum_beats_univariate | n_spectra | n_groups | n_levels |
|---|---|---|---|---|---|---|---|---|---|---|
| Tartrazine | 434 | 0.6240 | 0.0797 | Raw | 3 | 0.3323 | True | 400 | 20 | 20 |
| Sunset Yellow | 483 | 0.5913 | 0.0562 | Raw | 2 | 0.4628 | True | 400 | 20 | 20 |
| Metanil Yellow | 434 | 0.9044 | 0.1056 | Raw | 3 | 0.2042 | True | 260 | 13 | 13 |

saved: Table_25_single_wavelength_univariate_benchmark_versus_the_leading_plsr_representation_per_dye.x

```
lsx  (3 rows x 11 cols)
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}

[done] Cell 32: Regression infrastructure ready (F21/T24/T25) — per-representation PLSR latent
variables fixed and the univariate benchmark established
```

In [34]:

```python
DYE = 'Tartrazine'
CELL_33_CHECKPOINT = CHECKPOINTS_DIR /
'cell_33_tartrazine_regression_benchmark.pkl'

print("=" * 70)
print(f"CELL 33: {DYE} Regression Benchmark (Gate G7)")
print("=" * 70)
print("I score nine regressors across the seven preprocessing representations by
the "
      "stored 25-evaluation concentration-stratified grouped cross-validation on
the "
      f"{DYE.lower()} development set. PLSR uses the latent-variable count fixed
per "
      "representation in Cell 32; the other models use fixed screening defaults,
to be "
      "refined for the leader only in Cell 36. RMSECV, MAE and bias are averaged
over the 25 "
      "folds; R-squared, slope and intercept of predicted on reference are
computed once per "
      "repeat on the full development prediction and averaged over the five
repeats, because a "
      "single fold holds too few distinct concentrations for a stable fit. No test
data is "
      "read (evaluation_protocol section 4).")

import time
from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import Ridge
from sklearn.svm import SVR
from sklearn.neighbors import KNeighborsRegressor
from sklearn.tree import DecisionTreeRegressor
from sklearn.ensemble import RandomForestRegressor, GradientBoostingRegressor
from sklearn.pipeline import Pipeline
from sklearn.metrics import r2_score
from xgboost import XGBRegressor
from lightgbm import LGBMRegressor

PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
LV = {r['Preprocessing']: int(r['selected_LV'])
      for _, r in infra['lv_selection'][infra['lv_selection']['Dye'] ==
DYE].iterrows()}

sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
dev_rows = np.asarray(sealed['regression'][DYE]['dev_rows'])
rep_folds = cvf['regression'][DYE]['folds']                    # 5 repeats x 5
folds
N_SPECTRA = int(len(dev_rows))
N_GROUPS = int(len(np.unique(group_id[dev_rows])))
N_LEVELS = int(len(np.unique(conc[dev_rows])))
print(f"\nDevelopment set: {N_SPECTRA} spectra / {N_GROUPS} groups / {N_LEVELS}
```

```
levels | "
      f"{len(rep_folds)} repeats x {len(rep_folds[0])} folds")


def make_model(name, prep):
    if name == 'PLSR':
        return PLSRegression(n_components=LV[prep], scale=False)
    if name == 'Ridge':
        return Ridge(alpha=1.0, random_state=42)
    if name == 'SVR':
        return SVR(kernel='rbf', C=10.0, epsilon=0.1)
    if name == 'kNN':
        return KNeighborsRegressor(n_neighbors=5, weights='distance')
    if name == 'DecisionTree':
        return DecisionTreeRegressor(random_state=42)
    if name == 'RandomForest':
        return RandomForestRegressor(n_estimators=300, random_state=42, n_jobs=1)
    if name == 'GradientBoosting':
        return GradientBoostingRegressor(n_estimators=200, random_state=42)
    if name == 'XGBoost':
        return XGBRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                            subsample=0.9, random_state=42, n_jobs=1, verbosity=0)
    if name == 'LightGBM':
        return LGBMRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                             random_state=42, n_jobs=1, verbose=-1)
    raise KeyError(name)


MODELS = ['PLSR', 'Ridge', 'SVR', 'kNN', 'DecisionTree', 'RandomForest',
          'GradientBoosting', 'XGBoost', 'LightGBM']


def build(name, prep):
    steps = []
    pre = TRANSFORMERS[prep]
    if pre is not None:
        steps.append(('pre', pre()))
    steps.append(('sc', StandardScaler()))
    steps.append(('est', make_model(name, prep)))
    return Pipeline(steps)


def score_combo(name, prep):
    fold_rmse, fold_mae, fold_bias = [], [], []
    repeat_true, repeat_pred = [], []        # per-repeat pooled dev predictions
    for rep in rep_folds:
        tt, pp = [], []
        for tr, va in rep:
            tr, va = np.asarray(tr), np.asarray(va)
            m = build(name, prep).fit(X[tr], conc[tr])
            pred = np.asarray(m.predict(X[va])).ravel()
            true = conc[va]
            err = pred - true
            fold_rmse.append(float(np.sqrt(np.mean(err ** 2))))
            fold_mae.append(float(np.mean(np.abs(err))))
            fold_bias.append(float(np.mean(err)))
            tt.append(true); pp.append(pred)
        repeat_true.append(np.concatenate(tt));
repeat_pred.append(np.concatenate(pp))
    r2s, slopes, intercepts = [], [], []
    for true, pred in zip(repeat_true, repeat_pred):
```

```
        r2s.append(float(r2_score(true, pred)))
        s, b = np.polyfit(true, pred, 1)          # predicted on reference
        slopes.append(float(s)); intercepts.append(float(b))
    return {
        'Preprocessing': prep, 'Model': name,
        'PLS_LV': LV[prep] if name == 'PLSR' else np.nan,
        'RMSECV': round(float(np.mean(fold_rmse)), 4),
        'RMSECV_SD': round(float(np.std(fold_rmse)), 4),
        'MAE': round(float(np.mean(fold_mae)), 4),
        'bias': round(float(np.mean(fold_bias)), 4),
        'R2': round(float(np.mean(r2s)), 4),
        'R2_SD': round(float(np.std(r2s)), 4),
        'slope': round(float(np.mean(slopes)), 4),
        'intercept': round(float(np.mean(intercepts)), 4),
        'n_spectra': N_SPECTRA, 'n_groups': N_GROUPS, 'n_levels': N_LEVELS,
    }


# The 63-combination cross-validation is the expensive step. It is cached in the
cell
# checkpoint: if the checkpoint is present the stored benchmark is loaded and only
the
# tables and summary are re-rendered; otherwise it is computed once. A fresh run
with no
# checkpoint recomputes it in full, so the result is reproducible either way.
from concurrent.futures import ThreadPoolExecutor
if CELL_33_CHECKPOINT.exists():
    bench = load_checkpoint(CELL_33_CHECKPOINT, validate_hash=False)['benchmark']
    print(f"\nLoaded cached benchmark ({len(bench)} combinations) from checkpoint;
"
          f"cross-validation not recomputed.")
    _computed = False
else:
    combos = [(name, prep) for name in MODELS for prep in PREP_ORDER]
    t0 = time.time()
    # Independent combinations on a thread pool, each model single-threaded; the
    # scikit-learn / XGBoost / LightGBM fits release the GIL, so threading only
reduces
    # wall-clock time and changes nothing about the fits or the seeds.
    with ThreadPoolExecutor(max_workers=6) as ex:
        rows = list(ex.map(lambda c: score_combo(*c), combos))
    bench = pd.DataFrame(rows).sort_values('RMSECV').reset_index(drop=True)
    print(f"Benchmark computed in {time.time() - t0:.0f}s ({len(bench)}
combinations, "
          f"6 worker threads).")
    _computed = True

lead = bench.iloc[0]
uni = infra['univariate_benchmark']
uni_rmse = float(uni[uni['Dye'] == DYE]['univariate_RMSECV'].iloc[0])
print(f"\n  Leading pipeline: {lead['Model']} + {lead['Preprocessing']}  "
      f"RMSECV {lead['RMSECV']:.4f} +/- {lead['RMSECV_SD']:.4f} ug/mL | R2
{lead['R2']:.4f} | "
      f"slope {lead['slope']:.3f} | bias {lead['bias']:+.4f}")
print(f"  Single-wavelength univariate benchmark RMSECV {uni_rmse:.4f} ug/mL — "
      f"leader {'beats' if lead['RMSECV'] < uni_rmse else 'does NOT beat'} it.")
print("\n--- Top 12 pipelines by RMSECV ---")
print(bench[['Model', 'Preprocessing', 'RMSECV', 'RMSECV_SD', 'MAE', 'R2',
                      'slope', 'intercept', 'bias']].to_string(index=False))

show_and_save_table(bench, 26, f'{DYE} regression benchmark across models and
```

```
preprocessing '
                    '(development CV)', cell='33', max_rows=63,
                    notes=f'Nine regressors x seven preprocessings on the
{DYE.lower()} '
                          f'development set ({N_SPECTRA} spectra / {N_GROUPS}
groups / '
                          f'{N_LEVELS} levels), 25 concentration-stratified
grouped folds. '
                          f'RMSECV, MAE, bias averaged over 25 folds; R2, slope,
intercept of '
                          f'predicted on reference averaged over 5 repeat-level
full-development '
                          f'predictions. PLSR latent variables fixed in Cell 32;
other models at '
                          f'screening defaults (refined only for the leader in
Cell 36). '
                          f'Concentrations in micrograms per millilitre. No test
data read.')

if _computed:
    save_checkpoint({'benchmark': bench, 'leader': lead.to_dict(), 'dye': DYE,
                     'univariate_RMSECV': uni_rmse},
                    CELL_33_CHECKPOINT,
                    metadata={'type': 'regression_benchmark', 'cell': '33', 'dye':
DYE,
                              'gate': 'G7'})
    _ = load_checkpoint(CELL_33_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 33: {DYE} regression benchmark (T26) — leader "
      f"{lead['Model']} + {lead['Preprocessing']} at RMSECV {lead['RMSECV']:.4f}
ug/mL")
```

```
======================================================================
CELL 33: Tartrazine Regression Benchmark (Gate G7)
======================================================================
I score nine regressors across the seven preprocessing representations by the stored 25-
evaluation concentration-stratified grouped cross-validation on the tartrazine development set.
PLSR uses the latent-variable count fixed per representation in Cell 32; the other models use
fixed screening defaults, to be refined for the leader only in Cell 36. RMSECV, MAE and bias are
averaged over the 25 folds; R-squared, slope and intercept of predicted on reference are
computed once per repeat on the full development prediction and averaged over the five repeats,
because a single fold holds too few distinct concentrations for a stable fit. No test data is
read (evaluation_protocol section 4).
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

Development set: 400 spectra / 20 groups / 20 levels | 5 repeats x 5 folds
✓ Checkpoint loaded: cell_33_tartrazine_regression_benchmark.pkl
  Timestamp: 2026-11-04T20:57:07.782644
  Shape: {'benchmark': (63, 14)}

Loaded cached benchmark (63 combinations) from checkpoint; cross-validation not recomputed.

  Leading pipeline: PLSR + Raw  RMSECV 0.3323 +/- 0.1321 ug/mL | R2 0.9976 | slope 0.997 | bias
-0.0064
  Single-wavelength univariate benchmark RMSECV 0.6240 ug/mL — leader beats it.

--- Top 12 pipelines by RMSECV ---
          Model Preprocessing   RMSECV  RMSECV_SD     MAE         R2   slope  intercept    bias
           PLSR           Raw   0.3323     0.1321  0.2593     0.9976  0.9972     0.0267 -0.0064
           PLSR           SG1   0.3670     0.0857  0.2961     0.9973  0.9992     0.0157  0.0061
          Ridge           Raw   0.4075     0.0574  0.3296     0.9968  1.0042    -0.0324  0.0181
```

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Ridge | SG1 | 0.5412 | 0.1141 | 0.4359 | 0.9942 | 1.0067 | -0.0493 | 0.0309 |
| RandomForest | SG1 | 0.7142 | 0.2219 | 0.5974 | 0.9893 | 0.9595 | 0.5238 | 0.0405 |
| SVR | Raw | 0.7334 | 0.3020 | 0.5665 | 0.9880 | 0.9478 | 0.6629 | 0.0403 |
| RandomForest | Raw | 0.7473 | 0.2204 | 0.6524 | 0.9884 | 0.9713 | 0.4193 | 0.0771 |
| GradientBoosting | Raw | 0.7588 | 0.2045 | 0.6643 | 0.9882 | 0.9807 | 0.2748 | 0.0448 |
| GradientBoosting | SG1 | 0.7624 | 0.1679 | 0.6566 | 0.9884 | 0.9676 | 0.4523 | 0.0664 |
| LightGBM | SG1 | 0.9262 | 0.1853 | 0.8222 | 0.9830 | 0.9706 | 0.3550 | 0.0046 |
| XGBoost | SG1 | 0.9686 | 0.1797 | 0.8509 | 0.9815 | 0.9695 | 0.4083 | 0.0441 |
| XGBoost | Raw | 1.0355 | 0.1759 | 0.9501 | 0.9789 | 0.9703 | 0.2498 | -0.1044 |
| RandomForest | MSC | 1.0679 | 0.3401 | 0.8587 | 0.9760 | 0.9617 | 0.5892 | 0.1330 |
| RandomForest | SNV+SG1 | 1.0697 | 0.2984 | 0.8658 | 0.9765 | 0.9369 | 0.7792 | 0.0267 |
| SVR | PQN | 1.0769 | 0.7728 | 0.7699 | 0.9665 | 0.9235 | 1.1347 | 0.2225 |
| RandomForest | L2 | 1.0966 | 0.3722 | 0.8736 | 0.9744 | 0.9534 | 0.6985 | 0.1427 |
| GradientBoosting | MSC | 1.0980 | 0.3358 | 0.9072 | 0.9748 | 0.9715 | 0.4780 | 0.1385 |
| GradientBoosting | L2 | 1.1018 | 0.3504 | 0.8871 | 0.9745 | 0.9645 | 0.5511 | 0.1277 |
| GradientBoosting | SNV+SG1 | 1.1083 | 0.2964 | 0.9074 | 0.9749 | 0.9487 | 0.5541 | -0.0575 |
| LightGBM | SNV+SG1 | 1.1266 | 0.2830 | 0.9419 | 0.9743 | 0.9526 | 0.5567 | -0.0088 |
| SVR | MSC | 1.1496 | 1.1018 | 0.7928 | 0.9516 | 0.9096 | 1.4460 | 0.3684 |
| XGBoost | SNV+SG1 | 1.1499 | 0.2661 | 0.9559 | 0.9734 | 0.9448 | 0.6074 | -0.0513 |
| DecisionTree | Raw | 1.1538 | 0.1371 | 1.1145 | 0.9742 | 0.9710 | 0.4499 | 0.1035 |
| LightGBM | Raw | 1.1612 | 0.1346 | 1.0888 | 0.9739 | 0.9788 | 0.2754 | 0.0230 |
| XGBoost | MSC | 1.1944 | 0.3213 | 1.0575 | 0.9708 | 0.9431 | 0.9223 | 0.2441 |
| LightGBM | MSC | 1.2027 | 0.3076 | 1.0524 | 0.9706 | 0.9677 | 0.5191 | 0.1343 |
| XGBoost | L2 | 1.2052 | 0.3256 | 1.0423 | 0.9703 | 0.9574 | 0.5746 | 0.0662 |
| SVR | L2 | 1.2223 | 0.7648 | 0.9057 | 0.9603 | 0.9081 | 1.3409 | 0.2453 |
| GradientBoosting | PQN | 1.2332 | 0.3220 | 1.0138 | 0.9690 | 0.9660 | 0.5567 | 0.1514 |
| LightGBM | PQN | 1.2686 | 0.3205 | 1.0747 | 0.9673 | 0.9649 | 0.5843 | 0.1655 |
| LightGBM | L2 | 1.2915 | 0.3030 | 1.1308 | 0.9664 | 0.9588 | 0.6092 | 0.1182 |
| RandomForest | PQN | 1.3097 | 0.3341 | 1.1023 | 0.9651 | 0.9618 | 0.6338 | 0.1781 |
| XGBoost | PQN | 1.3156 | 0.3386 | 1.1311 | 0.9648 | 0.9563 | 0.7193 | 0.1979 |
| DecisionTree | SG1 | 1.3681 | 0.1649 | 1.2715 | 0.9638 | 0.9590 | 0.5071 | 0.0185 |
| kNN | Raw | 1.4812 | 0.3374 | 1.3692 | 0.9560 | 0.9765 | 0.2552 | -0.0254 |
| PLSR | SNV+SG1 | 1.5495 | 0.4547 | 1.2426 | 0.9502 | 0.9435 | 0.7468 | 0.0734 |
| kNN | SG1 | 1.6133 | 0.4124 | 1.4196 | 0.9471 | 0.9088 | 1.0631 | -0.0249 |
| PLSR | L2 | 1.6171 | 0.6447 | 1.2638 | 0.9422 | 0.9631 | 0.4081 | -0.0317 |
| kNN | MSC | 1.6596 | 0.4035 | 1.4553 | 0.9443 | 0.9632 | 1.1613 | 0.7230 |
| DecisionTree | MSC | 1.6685 | 0.1534 | 1.4520 | 0.9464 | 0.9720 | 0.4952 | 0.1610 |
| Ridge | L2 | 1.6776 | 0.4579 | 1.2649 | 0.9423 | 0.9916 | 0.1504 | 0.0498 |
| DecisionTree | L2 | 1.7595 | 0.2185 | 1.5575 | 0.9400 | 0.9532 | 0.6876 | 0.1295 |
| Ridge | SNV+SG1 | 1.7751 | 0.5895 | 1.3424 | 0.9332 | 0.9793 | 0.4091 | 0.1627 |
| DecisionTree | SNV+SG1 | 1.7815 | 0.2620 | 1.5545 | 0.9381 | 0.9271 | 0.7713 | -0.0985 |
| RandomForest | EMSC | 1.7996 | 2.3641 | 1.1482 | 0.8316 | 0.8930 | 1.8160 | 0.5396 |
| kNN | L2 | 1.8147 | 0.4256 | 1.6057 | 0.9337 | 0.9858 | 0.9328 | 0.7633 |
| GradientBoosting | EMSC | 1.8276 | 2.3872 | 1.1582 | 0.8275 | 0.8984 | 1.6699 | 0.4580 |
| DecisionTree | PQN | 1.8467 | 0.2386 | 1.6572 | 0.9338 | 0.9521 | 0.7107 | 0.1398 |
| kNN | SNV+SG1 | 1.8714 | 0.3770 | 1.6793 | 0.9305 | 0.9251 | 1.6787 | 0.7855 |
| PLSR | PQN | 1.9755 | 0.9658 | 1.5275 | 0.9077 | 0.9979 | -0.1362 | -0.1612 |
| LightGBM | EMSC | 2.0283 | 2.3113 | 1.3912 | 0.8196 | 0.8886 | 1.7888 | 0.4598 |
| Ridge | MSC | 2.0378 | 0.9158 | 1.4226 | 0.9048 | 1.0684 | -1.0903 | -0.2751 |
| XGBoost | EMSC | 2.0571 | 2.3000 | 1.4259 | 0.8183 | 0.8822 | 1.8231 | 0.4188 |
| kNN | PQN | 2.1145 | 0.3535 | 1.8995 | 0.9123 | 0.9217 | 2.0473 | 1.1139 |
| DecisionTree | EMSC | 2.2453 | 2.2054 | 1.6535 | 0.8110 | 0.8967 | 1.6073 | 0.3755 |
| PLSR | MSC | 2.2471 | 0.7058 | 1.5451 | 0.8941 | 1.0099 | -0.4219 | -0.3037 |
| kNN | EMSC | 2.5848 | 2.0792 | 1.9597 | 0.7900 | 0.8688 | 2.6678 | 1.1034 |
| SVR | SNV+SG1 | 2.6074 | 0.6234 | 2.0908 | 0.8629 | 0.8656 | 1.6659 | 0.0629 |
| SVR | SG1 | 3.0177 | 0.8698 | 2.3502 | 0.8118 | 0.8535 | 1.6012 | -0.1455 |
| Ridge | PQN | 3.5968 | 1.8545 | 2.2088 | 0.6875 | 0.9599 | 0.6479 | 0.1694 |
| SVR | EMSC | 4.2215 | 1.7591 | 3.6010 | 0.6009 | 0.5366 | 5.4125 | -0.1140 |
| Ridge | EMSC | 110.8084 | 269.6215 | 29.1031 | -1620.4330 | -1.1285 | 34.5088 | 9.1267 |
| PLSR | EMSC | 213.7784 | 505.0911 | 71.7331 | -5739.0531 | -0.8894 | 27.8249 | 5.2935 |

TABLE 26: Tartrazine regression benchmark across models and preprocessing (development CV)

| Preprocessing | Model | PLS_LV | RMSECV | RMSECV_SD | MAE | bias | R2 | R2_SD | slope | intercept | n_spectra | n_groups | n_levels |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Raw | PLSR | 3.0 | 0.3323 | 0.1321 | 0.2593 | -0.0064 | 0.9976 | 0.0001 | 0.9972 | 0.0267 | 400 | 20 | 20 |
| SG1 | PLSR | 2.0 | 0.3670 | 0.0857 | 0.2961 | 0.0061 | 0.9973 | 0.0001 | 0.9992 | 0.0157 | 400 | 20 | 20 |
| Raw | Ridge | NaN | 0.4075 | 0.0574 | 0.3296 | 0.0181 | 0.9968 | 0.0003 | 1.0042 | -0.0324 | 400 | 20 | 20 |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| SG1 | Ridge | NaN | 0.5412 | 0.1141 | 0.4359 | 0.0309 | 0.9942 | 0.0005 | 1.0067 | -0.0493 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | RandomForest | NaN | 0.7142 | 0.2219 | 0.5974 | 0.0405 | 0.9893 | 0.0004 | 0.9595 | 0.5238 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | SVR | NaN | 0.7334 | 0.3020 | 0.5665 | 0.0403 | 0.9880 | 0.0005 | 0.9478 | 0.6629 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | RandomForest | NaN | 0.7473 | 0.2204 | 0.6524 | 0.0771 | 0.9884 | 0.0003 | 0.9713 | 0.4193 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | GradientBoosting | NaN | 0.7588 | 0.2045 | 0.6643 | 0.0448 | 0.9882 | 0.0004 | 0.9807 | 0.2748 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | GradientBoosting | NaN | 0.7624 | 0.1679 | 0.6566 | 0.0664 | 0.9884 | 0.0003 | 0.9676 | 0.4523 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | LightGBM | NaN | 0.9262 | 0.1853 | 0.8222 | 0.0046 | 0.9830 | 0.0005 | 0.9706 | 0.3550 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | XGBoost | NaN | 0.9686 | 0.1797 | 0.8509 | 0.0441 | 0.9815 | 0.0004 | 0.9695 | 0.4083 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | XGBoost | NaN | 1.0355 | 0.1759 | 0.9501 | -0.1044 | 0.9789 | 0.0008 | 0.9703 | 0.2498 |
| 400 | 20 | 20 | | | | | | | | |
| MSC | RandomForest | NaN | 1.0679 | 0.3401 | 0.8587 | 0.1330 | 0.9760 | 0.0005 | 0.9617 | 0.5892 |
| 400 | 20 | 20 | | | | | | | | |
| SNV+SG1 | RandomForest | NaN | 1.0697 | 0.2984 | 0.8658 | 0.0267 | 0.9765 | 0.0008 | 0.9369 | 0.7792 |
| 400 | 20 | 20 | | | | | | | | |
| PQN | SVR | NaN | 1.0769 | 0.7728 | 0.7699 | 0.2225 | 0.9665 | 0.0019 | 0.9235 | 1.1347 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | RandomForest | NaN | 1.0966 | 0.3722 | 0.8736 | 0.1427 | 0.9744 | 0.0006 | 0.9534 | 0.6985 |
| 400 | 20 | 20 | | | | | | | | |
| MSC | GradientBoosting | NaN | 1.0980 | 0.3358 | 0.9072 | 0.1385 | 0.9748 | 0.0007 | 0.9715 | 0.4780 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | GradientBoosting | NaN | 1.1018 | 0.3504 | 0.8871 | 0.1277 | 0.9745 | 0.0006 | 0.9645 | 0.5511 |
| 400 | 20 | 20 | | | | | | | | |
| SNV+SG1 | GradientBoosting | NaN | 1.1083 | 0.2964 | 0.9074 | -0.0575 | 0.9749 | 0.0006 | 0.9487 | 0.5541 |
| 400 | 20 | 20 | | | | | | | | |
| SNV+SG1 | LightGBM | NaN | 1.1266 | 0.2830 | 0.9419 | -0.0088 | 0.9743 | 0.0009 | 0.9526 | 0.5567 |
| 400 | 20 | 20 | | | | | | | | |
| MSC | SVR | NaN | 1.1496 | 1.1018 | 0.7928 | 0.3684 | 0.9516 | 0.0067 | 0.9096 | 1.4460 |
| 400 | 20 | 20 | | | | | | | | |
| SNV+SG1 | XGBoost | NaN | 1.1499 | 0.2661 | 0.9559 | -0.0513 | 0.9734 | 0.0005 | 0.9448 | 0.6074 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | DecisionTree | NaN | 1.1538 | 0.1371 | 1.1145 | 0.1035 | 0.9742 | 0.0015 | 0.9710 | 0.4499 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | LightGBM | NaN | 1.1612 | 0.1346 | 1.0888 | 0.0230 | 0.9739 | 0.0021 | 0.9788 | 0.2754 |
| 400 | 20 | 20 | | | | | | | | |
| MSC | XGBoost | NaN | 1.1944 | 0.3213 | 1.0575 | 0.2441 | 0.9708 | 0.0012 | 0.9431 | 0.9223 |
| 400 | 20 | 20 | | | | | | | | |
| MSC | LightGBM | NaN | 1.2027 | 0.3076 | 1.0524 | 0.1343 | 0.9706 | 0.0010 | 0.9677 | 0.5191 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | XGBoost | NaN | 1.2052 | 0.3256 | 1.0423 | 0.0662 | 0.9703 | 0.0007 | 0.9574 | 0.5746 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | SVR | NaN | 1.2223 | 0.7648 | 0.9057 | 0.2453 | 0.9603 | 0.0027 | 0.9081 | 1.3409 |
| 400 | 20 | 20 | | | | | | | | |
| PQN | GradientBoosting | NaN | 1.2332 | 0.3220 | 1.0138 | 0.1514 | 0.9690 | 0.0015 | 0.9660 | 0.5567 |
| 400 | 20 | 20 | | | | | | | | |
| PQN | LightGBM | NaN | 1.2686 | 0.3205 | 1.0747 | 0.1655 | 0.9673 | 0.0014 | 0.9649 | 0.5843 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | LightGBM | NaN | 1.2915 | 0.3030 | 1.1308 | 0.1182 | 0.9664 | 0.0012 | 0.9588 | 0.6092 |
| 400 | 20 | 20 | | | | | | | | |
| PQN | RandomForest | NaN | 1.3097 | 0.3341 | 1.1023 | 0.1781 | 0.9651 | 0.0013 | 0.9618 | 0.6338 |
| 400 | 20 | 20 | | | | | | | | |
| PQN | XGBoost | NaN | 1.3156 | 0.3386 | 1.1311 | 0.1979 | 0.9648 | 0.0020 | 0.9563 | 0.7193 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | DecisionTree | NaN | 1.3681 | 0.1649 | 1.2715 | 0.0185 | 0.9638 | 0.0022 | 0.9590 | 0.5071 |
| 400 | 20 | 20 | | | | | | | | |
| Raw | kNN | NaN | 1.4812 | 0.3374 | 1.3692 | -0.0254 | 0.9560 | 0.0012 | 0.9765 | 0.2552 |
| 400 | 20 | 20 | | | | | | | | |
| SNV+SG1 | PLSR | 2.0 | 1.5495 | 0.4547 | 1.2426 | 0.0734 | 0.9502 | 0.0020 | 0.9435 | 0.7468 |
| 400 | 20 | 20 | | | | | | | | |
| SG1 | kNN | NaN | 1.6133 | 0.4124 | 1.4196 | -0.0249 | 0.9471 | 0.0008 | 0.9088 | 1.0631 |
| 400 | 20 | 20 | | | | | | | | |
| L2 | PLSR | 3.0 | 1.6171 | 0.6447 | 1.2638 | -0.0317 | 0.9422 | 0.0017 | 0.9631 | 0.4081 |
| 400 | 20 | 20 | | | | | | | | |

```
          MSC              kNN     NaN   1.6596     0.4035  1.4553  0.7230     0.9443    0.0065
0.9632     1.1613        400        20         20
          MSC     DecisionTree     NaN   1.6685     0.1534  1.4520  0.1610     0.9464    0.0017
0.9720     0.4952        400        20         20
           L2            Ridge     NaN   1.6776     0.4579  1.2649  0.0498     0.9423    0.0045
0.9916     0.1504        400        20         20
           L2     DecisionTree     NaN   1.7595     0.2185  1.5575  0.1295     0.9400    0.0025
0.9532     0.6876        400        20         20
      SNV+SG1            Ridge     NaN   1.7751     0.5895  1.3424  0.1627     0.9332    0.0072
0.9793     0.4091        400        20         20
      SNV+SG1     DecisionTree     NaN   1.7815     0.2620  1.5545 -0.0985     0.9381    0.0053
0.9271     0.7713        400        20         20
         EMSC     RandomForest     NaN   1.7996     2.3641  1.1482  0.5396     0.8316    0.1397
0.8930     1.8160        400        20         20
           L2              kNN     NaN   1.8147     0.4256  1.6057  0.7633     0.9337    0.0067
0.9858     0.9328        400        20         20
         EMSC GradientBoosting     NaN   1.8276     2.3872  1.1582  0.4580     0.8275    0.1421
0.8984     1.6699        400        20         20
          PQN     DecisionTree     NaN   1.8467     0.2386  1.6572  0.1398     0.9338    0.0035
0.9521     0.7107        400        20         20
      SNV+SG1              kNN     NaN   1.8714     0.3770  1.6793  0.7855     0.9305    0.0068
0.9251     1.6787        400        20         20
          PQN             PLSR     3.0   1.9755     0.9658  1.5275 -0.1612     0.9077    0.0072
0.9979    -0.1362        400        20         20
         EMSC         LightGBM     NaN   2.0283     2.3113  1.3912  0.4598     0.8196    0.1373
0.8886     1.7888        400        20         20
          MSC            Ridge     NaN   2.0378     0.9158  1.4226 -0.2751     0.9048    0.0225
1.0684    -1.0903        400        20         20
         EMSC          XGBoost     NaN   2.0571     2.3000  1.4259  0.4188     0.8183    0.1392
0.8822     1.8231        400        20         20
          PQN              kNN     NaN   2.1145     0.3535  1.8995  1.1139     0.9123    0.0069
0.9217     2.0473        400        20         20
         EMSC     DecisionTree     NaN   2.2453     2.2054  1.6535  0.3755     0.8110    0.1384
0.8967     1.6073        400        20         20
          MSC             PLSR     3.0   2.2471     0.7058  1.5451 -0.3037     0.8941    0.0060
1.0099    -0.4219        400        20         20
         EMSC              kNN     NaN   2.5848     2.0792  1.9597  1.1034     0.7900    0.1361
0.8688     2.6678        400        20         20
      SNV+SG1              SVR     NaN   2.6074     0.6234  2.0908  0.0629     0.8629    0.0029
0.8656     1.6659        400        20         20
          SG1              SVR     NaN   3.0177     0.8698  2.3502 -0.1455     0.8118    0.0122
0.8535     1.6012        400        20         20
          PQN            Ridge     NaN   3.5968     1.8545  2.2088  0.1694     0.6875    0.0519
0.9599     0.6479        400        20         20
         EMSC              SVR     NaN   4.2215     1.7591  3.6010 -0.1140     0.6009    0.0386
0.5366     5.4125        400        20         20
         EMSC            Ridge     NaN 110.8084   269.6215 29.1031  9.1267 -1620.4330 1999.6037
-1.1285    34.5088        400        20         20
         EMSC             PLSR     1.0 213.7784   505.0911 71.7331  5.2935 -5739.0531 6409.4587
-0.8894    27.8249        400        20         20
  saved:
Table_26_tartrazine_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
(63 rows x 14 cols)

[done] Cell 33: Tartrazine regression benchmark (T26) — leader PLSR + Raw at RMSECV 0.3323 ug/mL
```

In [35]:

```
DYE = 'Sunset Yellow'
CELL_34_CHECKPOINT = CHECKPOINTS_DIR /
'cell_34_sunset_yellow_regression_benchmark.pkl'

print("=" * 70)
print(f"CELL 34: {DYE} Regression Benchmark (Gate G7)")
print("=" * 70)
print("I score nine regressors across the seven preprocessing representations by
the "
      "stored 25-evaluation concentration-stratified grouped cross-validation on
the "
      f"{DYE.lower()} development set. PLSR uses the latent-variable count fixed
```

```
per "
      "representation in Cell 32; the other models use fixed screening defaults,
to be "
      "refined for the leader only in Cell 36. RMSECV, MAE and bias are averaged
over the 25 "
      "folds; R-squared, slope and intercept of predicted on reference are
computed once per "
      "repeat on the full development prediction and averaged over the five
repeats, because a "
      "single fold holds too few distinct concentrations for a stable fit. No test
data is "
      "read (evaluation_protocol section 4).")

import time
from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import Ridge
from sklearn.svm import SVR
from sklearn.neighbors import KNeighborsRegressor
from sklearn.tree import DecisionTreeRegressor
from sklearn.ensemble import RandomForestRegressor, GradientBoostingRegressor
from sklearn.pipeline import Pipeline
from sklearn.metrics import r2_score
from xgboost import XGBRegressor
from lightgbm import LGBMRegressor

PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
LV = {r['Preprocessing']: int(r['selected_LV'])
      for _, r in infra['lv_selection'][infra['lv_selection']['Dye'] ==
DYE].iterrows()}

sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
dev_rows = np.asarray(sealed['regression'][DYE]['dev_rows'])
rep_folds = cvf['regression'][DYE]['folds']                      # 5 repeats x 5
folds
N_SPECTRA = int(len(dev_rows))
N_GROUPS = int(len(np.unique(group_id[dev_rows])))
N_LEVELS = int(len(np.unique(conc[dev_rows])))
print(f"\nDevelopment set: {N_SPECTRA} spectra / {N_GROUPS} groups / {N_LEVELS}
levels | "
      f"{len(rep_folds)} repeats x {len(rep_folds[0])} folds")


def make_model(name, prep):
    if name == 'PLSR':
        return PLSRegression(n_components=LV[prep], scale=False)
    if name == 'Ridge':
        return Ridge(alpha=1.0, random_state=42)
    if name == 'SVR':
        return SVR(kernel='rbf', C=10.0, epsilon=0.1)
    if name == 'kNN':
        return KNeighborsRegressor(n_neighbors=5, weights='distance')
    if name == 'DecisionTree':
        return DecisionTreeRegressor(random_state=42)
    if name == 'RandomForest':
        return RandomForestRegressor(n_estimators=300, random_state=42, n_jobs=1)
    if name == 'GradientBoosting':
        return GradientBoostingRegressor(n_estimators=200, random_state=42)
```

```
    if name == 'XGBoost':
        return XGBRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                            subsample=0.9, random_state=42, n_jobs=1, verbosity=0)
    if name == 'LightGBM':
        return LGBMRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                             random_state=42, n_jobs=1, verbose=-1)
    raise KeyError(name)


MODELS = ['PLSR', 'Ridge', 'SVR', 'kNN', 'DecisionTree', 'RandomForest',
          'GradientBoosting', 'XGBoost', 'LightGBM']


def build(name, prep):
    steps = []
    pre = TRANSFORMERS[prep]
    if pre is not None:
        steps.append(('pre', pre()))
    steps.append(('sc', StandardScaler()))
    steps.append(('est', make_model(name, prep)))
    return Pipeline(steps)


def score_combo(name, prep):
    fold_rmse, fold_mae, fold_bias = [], [], []
    repeat_true, repeat_pred = [], []        # per-repeat pooled dev predictions
    for rep in rep_folds:
        tt, pp = [], []
        for tr, va in rep:
            tr, va = np.asarray(tr), np.asarray(va)
            m = build(name, prep).fit(X[tr], conc[tr])
            pred = np.asarray(m.predict(X[va])).ravel()
            true = conc[va]
            err = pred - true
            fold_rmse.append(float(np.sqrt(np.mean(err ** 2))))
            fold_mae.append(float(np.mean(np.abs(err))))
            fold_bias.append(float(np.mean(err)))
            tt.append(true); pp.append(pred)
        repeat_true.append(np.concatenate(tt));
repeat_pred.append(np.concatenate(pp))
    r2s, slopes, intercepts = [], [], []
    for true, pred in zip(repeat_true, repeat_pred):
        r2s.append(float(r2_score(true, pred)))
        s, b = np.polyfit(true, pred, 1)          # predicted on reference
        slopes.append(float(s)); intercepts.append(float(b))
    return {
        'Preprocessing': prep, 'Model': name,
        'PLS_LV': LV[prep] if name == 'PLSR' else np.nan,
        'RMSECV': round(float(np.mean(fold_rmse)), 4),
        'RMSECV_SD': round(float(np.std(fold_rmse)), 4),
        'MAE': round(float(np.mean(fold_mae)), 4),
        'bias': round(float(np.mean(fold_bias)), 4),
        'R2': round(float(np.mean(r2s)), 4),
        'R2_SD': round(float(np.std(r2s)), 4),
        'slope': round(float(np.mean(slopes)), 4),
        'intercept': round(float(np.mean(intercepts)), 4),
        'n_spectra': N_SPECTRA, 'n_groups': N_GROUPS, 'n_levels': N_LEVELS,
    }


# The 63-combination cross-validation is the expensive step. It is cached in the
```

```
cell
# checkpoint: if the checkpoint is present the stored benchmark is loaded and only
the
# tables and summary are re-rendered; otherwise it is computed once. A fresh run
with no
# checkpoint recomputes it in full, so the result is reproducible either way.
from concurrent.futures import ThreadPoolExecutor
if CELL_34_CHECKPOINT.exists():
    bench = load_checkpoint(CELL_34_CHECKPOINT, validate_hash=False)['benchmark']
    print(f"\nLoaded cached benchmark ({len(bench)} combinations) from checkpoint;
"
          f"cross-validation not recomputed.")
    _computed = False
else:
    combos = [(name, prep) for name in MODELS for prep in PREP_ORDER]
    t0 = time.time()
    # Independent combinations on a thread pool, each model single-threaded; the
    # scikit-learn / XGBoost / LightGBM fits release the GIL, so threading only
reduces
    # wall-clock time and changes nothing about the fits or the seeds.
    with ThreadPoolExecutor(max_workers=6) as ex:
        rows = list(ex.map(lambda c: score_combo(*c), combos))
    bench = pd.DataFrame(rows).sort_values('RMSECV').reset_index(drop=True)
    print(f"Benchmark computed in {time.time() - t0:.0f}s ({len(bench)}
combinations, "
          f"6 worker threads).")
    _computed = True

lead = bench.iloc[0]
uni = infra['univariate_benchmark']
uni_rmse = float(uni[uni['Dye'] == DYE]['univariate_RMSECV'].iloc[0])
print(f"\n  Leading pipeline: {lead['Model']} + {lead['Preprocessing']}  "
      f"RMSECV {lead['RMSECV']:.4f} +/- {lead['RMSECV_SD']:.4f} ug/mL | R2
{lead['R2']:.4f} | "
      f"slope {lead['slope']:.3f} | bias {lead['bias']:+.4f}")
print(f"  Single-wavelength univariate benchmark RMSECV {uni_rmse:.4f} ug/mL — "
      f"leader {'beats' if lead['RMSECV'] < uni_rmse else 'does NOT beat'} it.")
print("\n--- Top 12 pipelines by RMSECV ---")
print(bench[['Model', 'Preprocessing', 'RMSECV', 'RMSECV_SD', 'MAE', 'R2',
                     'slope', 'intercept', 'bias']].to_string(index=False))

show_and_save_table(bench, 27, f'{DYE} regression benchmark across models and
preprocessing '
                    '(development CV)', cell='34', max_rows=63,
                    notes=f'Nine regressors x seven preprocessings on the
{DYE.lower()} '
                          f'development set ({N_SPECTRA} spectra / {N_GROUPS}
groups / '
                          f'{N_LEVELS} levels), 25 concentration-stratified
grouped folds. '
                          f'RMSECV, MAE, bias averaged over 25 folds; R2, slope,
intercept of '
                          f'predicted on reference averaged over 5 repeat-level
full-development '
                          f'predictions. PLSR latent variables fixed in Cell 32;
other models at '
                          f'screening defaults (refined only for the leader in
Cell 36). '
                          f'Concentrations in micrograms per millilitre. No test
data read.')
```

```
if _computed:
    save_checkpoint({'benchmark': bench, 'leader': lead.to_dict(), 'dye': DYE,
                     'univariate_RMSECV': uni_rmse},
                    CELL_34_CHECKPOINT,
                    metadata={'type': 'regression_benchmark', 'cell': '34', 'dye':
DYE,
                              'gate': 'G7'})
    _ = load_checkpoint(CELL_34_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 34: {DYE} regression benchmark (T27) — leader "
      f"{lead['Model']} + {lead['Preprocessing']} at RMSECV {lead['RMSECV']:.4f}
ug/mL")
```

```
======================================================================
CELL 34: Sunset Yellow Regression Benchmark (Gate G7)
======================================================================
I score nine regressors across the seven preprocessing representations by the stored 25-
evaluation concentration-stratified grouped cross-validation on the sunset yellow development
set. PLSR uses the latent-variable count fixed per representation in Cell 32; the other models
use fixed screening defaults, to be refined for the leader only in Cell 36. RMSECV, MAE and bias
are averaged over the 25 folds; R-squared, slope and intercept of predicted on reference are
computed once per repeat on the full development prediction and averaged over the five repeats,
because a single fold holds too few distinct concentrations for a stable fit. No test data is
read (evaluation_protocol section 4).
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

Development set: 400 spectra / 20 groups / 20 levels | 5 repeats x 5 folds
✓ Checkpoint loaded: cell_34_sunset_yellow_regression_benchmark.pkl
  Timestamp: 2026-11-04T21:06:56.921704
  Shape: {'benchmark': (63, 14)}

Loaded cached benchmark (63 combinations) from checkpoint; cross-validation not recomputed.

  Leading pipeline: PLSR + Raw  RMSECV 0.4628 +/- 0.1343 ug/mL | R2 0.9959 | slope 0.998 | bias
+0.0060
  Single-wavelength univariate benchmark RMSECV 0.5913 ug/mL — leader beats it.

--- Top 12 pipelines by RMSECV ---
           Model Preprocessing  RMSECV  RMSECV_SD    MAE     R2  slope  intercept    bias
            PLSR           Raw  0.4628     0.1343 0.3764 0.9959 0.9975     0.0355  0.0060
            PLSR           SG1  0.5291     0.0788 0.4287 0.9949 0.9934     0.0815  0.0020
GradientBoosting           Raw  0.6938     0.1166 0.6234 0.9912 0.9858     0.1443 -0.0259
    RandomForest           Raw  0.7322     0.1599 0.6389 0.9900 0.9852     0.1524 -0.0243
GradientBoosting           SG1  0.7918     0.1546 0.6943 0.9884 0.9850     0.1217 -0.0576
    RandomForest           SG1  0.8207     0.1868 0.7208 0.9873 0.9790     0.1973 -0.0544
GradientBoosting          EMSC  0.8350     0.1329 0.7154 0.9872 0.9889     0.1785  0.0456
    RandomForest          EMSC  0.8386     0.1761 0.7054 0.9869 0.9802     0.2756  0.0387
             SVR           Raw  0.8483     0.2467 0.6679 0.9861 0.9605     0.4733  0.0004
GradientBoosting            L2  0.8648     0.1321 0.7450 0.9863 0.9844     0.1696 -0.0171
           Ridge           Raw  0.8652     0.1086 0.7163 0.9864 0.9975    -0.0012 -0.0317
    RandomForest            L2  0.8810     0.1767 0.7499 0.9856 0.9781     0.2821  0.0194
GradientBoosting           MSC  0.8884     0.1269 0.7727 0.9856 0.9892     0.1066 -0.0232
    RandomForest           MSC  0.8925     0.1697 0.7658 0.9853 0.9778     0.2682  0.0020
           Ridge           SG1  0.9560     0.1535 0.7935 0.9832 0.9953     0.0363 -0.0199
         XGBoost           Raw  0.9694     0.1267 0.9056 0.9829 0.9965     0.0381 -0.0039
GradientBoosting       SNV+SG1  0.9818     0.1440 0.8306 0.9824 0.9752     0.2683 -0.0281
        LightGBM            L2  0.9823     0.1797 0.8803 0.9822 0.9879     0.1494  0.0045
        LightGBM       SNV+SG1  0.9953     0.1386 0.8524 0.9820 0.9705     0.3671  0.0139
        LightGBM           MSC  1.0067     0.1857 0.9010 0.9813 0.9858     0.1948  0.0248
        LightGBM          EMSC  1.0303     0.2619 0.8762 0.9798 0.9899     0.0847 -0.0367
    RandomForest       SNV+SG1  1.0309     0.1456 0.8637 0.9806 0.9673     0.4044  0.0126
         XGBoost           MSC  1.0359     0.1477 0.8886 0.9804 0.9779     0.4002  0.1359
        LightGBM           Raw  1.0429     0.1350 0.9778 0.9802 0.9940     0.0900  0.0181
         XGBoost           SG1  1.0440     0.1325 0.9407 0.9802 0.9938     0.0558 -0.0188
```

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| XGBoost | L2 | 1.0451 | 0.1392 | 0.8901 | 0.9801 | 0.9886 | 0.2301 | 0.0936 | |
| XGBoost | SNV+SG1 | 1.0687 | 0.1186 | 0.9207 | 0.9793 | 0.9713 | 0.3331 | -0.0105 | |
| LightGBM | SG1 | 1.0775 | 0.1679 | 0.9592 | 0.9788 | 0.9862 | 0.1038 | -0.0618 | |
| DecisionTree | Raw | 1.1074 | 0.1279 | 1.0590 | 0.9778 | 0.9868 | 0.1974 | 0.0390 | |
| PLSR | L2 | 1.1146 | 0.1345 | 0.9205 | 0.9775 | 0.9817 | 0.2169 | -0.0023 | |
| XGBoost | EMSC | 1.1591 | 0.3454 | 0.9418 | 0.9739 | 0.9835 | 0.1366 | -0.0609 | |
| GradientBoosting | PQN | 1.1838 | 0.1334 | 0.9880 | 0.9746 | 0.9780 | 0.3210 | 0.0574 | |
| LightGBM | PQN | 1.2013 | 0.2237 | 0.9844 | 0.9733 | 0.9866 | 0.1662 | 0.0061 | |
| RandomForest | PQN | 1.2479 | 0.2079 | 1.0240 | 0.9714 | 0.9732 | 0.4340 | 0.1135 | |
| XGBoost | PQN | 1.2702 | 0.2736 | 1.0339 | 0.9698 | 0.9816 | 0.3027 | 0.0828 | |
| SVR | L2 | 1.3081 | 0.4257 | 1.0318 | 0.9662 | 0.9462 | 0.7778 | 0.1340 | |
| SVR | PQN | 1.3109 | 0.3398 | 1.0191 | 0.9672 | 0.9438 | 0.8646 | 0.1921 | |
| DecisionTree | SG1 | 1.3404 | 0.1946 | 1.2302 | 0.9672 | 0.9865 | 0.1152 | -0.0462 | |
| PLSR | SNV+SG1 | 1.3429 | 0.1542 | 1.1304 | 0.9674 | 0.9700 | 0.3707 | 0.0117 | |
| DecisionTree | MSC | 1.3481 | 0.1277 | 1.2378 | 0.9672 | 0.9777 | 0.3159 | 0.0493 | |
| DecisionTree | L2 | 1.4094 | 0.1864 | 1.2790 | 0.9639 | 0.9801 | 0.2499 | 0.0110 | |
| kNN | Raw | 1.4304 | 0.3026 | 1.2840 | 0.9618 | 0.9724 | 0.2373 | -0.0929 | |
| DecisionTree | EMSC | 1.4593 | 0.2048 | 1.3198 | 0.9612 | 0.9867 | 0.2154 | 0.0562 | |
| kNN | EMSC | 1.5629 | 0.3133 | 1.4138 | 0.9546 | 0.9597 | 0.9503 | 0.4682 | |
| kNN | SG1 | 1.5861 | 0.3822 | 1.3800 | 0.9524 | 0.9422 | 0.7263 | 0.0341 | |
| kNN | SNV+SG1 | 1.6286 | 0.2455 | 1.4083 | 0.9515 | 0.9648 | 0.8866 | 0.4653 | |
| kNN | MSC | 1.6663 | 0.3424 | 1.3858 | 0.9483 | 0.9567 | 1.2363 | 0.7178 | |
| kNN | L2 | 1.6848 | 0.2895 | 1.4225 | 0.9478 | 0.9667 | 1.1553 | 0.7569 | |
| SVR | MSC | 1.6886 | 0.5564 | 1.3307 | 0.9435 | 0.9263 | 1.0016 | 0.1185 | |
| DecisionTree | SNV+SG1 | 1.7039 | 0.1890 | 1.4892 | 0.9475 | 0.9598 | 0.3796 | -0.1023 | |
| DecisionTree | PQN | 1.7319 | 0.1310 | 1.5248 | 0.9461 | 0.9993 | 0.1303 | 0.1222 | |
| PLSR | MSC | 1.7879 | 0.3401 | 1.4687 | 0.9408 | 0.9893 | 0.0293 | -0.0986 | |
| PLSR | PQN | 1.9153 | 0.4115 | 1.4771 | 0.9314 | 0.9585 | 0.4887 | -0.0088 | |
| Ridge | SNV+SG1 | 2.0386 | 0.3257 | 1.5447 | 0.9238 | 0.9837 | 0.2158 | 0.0210 | |
| kNN | PQN | 2.0474 | 0.3908 | 1.6807 | 0.9224 | 0.9217 | 1.9997 | 1.0623 | |
| SVR | EMSC | 2.0493 | 0.9673 | 1.5530 | 0.9082 | 0.9673 | 0.4632 | 0.0713 | |
| Ridge | L2 | 2.2757 | 0.3948 | 1.6925 | 0.9047 | 1.0034 | -0.0904 | -0.0500 | |
| Ridge | MSC | 2.7278 | 0.6202 | 1.9770 | 0.8602 | 1.0301 | -0.5293 | -0.1692 | |
| SVR | SG1 | 2.9529 | 0.9905 | 2.3005 | 0.8267 | 0.8311 | 1.7989 | -0.2233 | |
| SVR | SNV+SG1 | 3.1236 | 1.1885 | 2.3955 | 0.8004 | 0.8803 | 1.2390 | -0.1944 | |
| PLSR | EMSC | 3.2444 | 0.5455 | 2.9182 | 0.8066 | 0.8369 | 1.9086 | -0.0442 | |
| Ridge | PQN | 4.0913 | 0.8654 | 2.7812 | 0.6875 | 1.0540 | -0.8869 | -0.2405 | |
| Ridge | EMSC | 4.1388 | 1.1397 | 2.7551 | 0.6707 | 1.0773 | -1.3486 | -0.4224 | |

TABLE 27: Sunset Yellow regression benchmark across models and preprocessing (development CV)

| Preprocessing | Model | PLS_LV | RMSECV | RMSECV_SD | MAE | bias | R2 | R2_SD | slope | intercept | n_spectra | n_groups | n_levels |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Raw | PLSR | 2.0 | 0.4628 | 0.1343 | 0.3764 | 0.0060 | 0.9959 | 0.0002 | 0.9975 | 0.0355 | 400 | 20 | 20 |
| SG1 | PLSR | 1.0 | 0.5291 | 0.0788 | 0.4287 | 0.0020 | 0.9949 | 0.0001 | 0.9934 | 0.0815 | 400 | 20 | 20 |
| Raw | GradientBoosting | NaN | 0.6938 | 0.1166 | 0.6234 | -0.0259 | 0.9912 | 0.0002 | 0.9858 | 0.1443 | 400 | 20 | 20 |
| Raw | RandomForest | NaN | 0.7322 | 0.1599 | 0.6389 | -0.0243 | 0.9900 | 0.0003 | 0.9852 | 0.1524 | 400 | 20 | 20 |
| SG1 | GradientBoosting | NaN | 0.7918 | 0.1546 | 0.6943 | -0.0576 | 0.9884 | 0.0004 | 0.9850 | 0.1217 | 400 | 20 | 20 |
| SG1 | RandomForest | NaN | 0.8207 | 0.1868 | 0.7208 | -0.0544 | 0.9873 | 0.0004 | 0.9790 | 0.1973 | 400 | 20 | 20 |
| EMSC | GradientBoosting | NaN | 0.8350 | 0.1329 | 0.7154 | 0.0456 | 0.9872 | 0.0003 | 0.9889 | 0.1785 | 400 | 20 | 20 |
| EMSC | RandomForest | NaN | 0.8386 | 0.1761 | 0.7054 | 0.0387 | 0.9869 | 0.0002 | 0.9802 | 0.2756 | 400 | 20 | 20 |
| Raw | SVR | NaN | 0.8483 | 0.2467 | 0.6679 | 0.0004 | 0.9861 | 0.0008 | 0.9605 | 0.4733 | 400 | 20 | 20 |
| L2 | GradientBoosting | NaN | 0.8648 | 0.1321 | 0.7450 | -0.0171 | 0.9863 | 0.0003 | 0.9844 | 0.1696 | 400 | 20 | 20 |
| Raw | Ridge | NaN | 0.8652 | 0.1086 | 0.7163 | -0.0317 | 0.9864 | 0.0008 | 0.9975 | -0.0012 | 400 | 20 | 20 |
| L2 | RandomForest | NaN | 0.8810 | 0.1767 | 0.7499 | 0.0194 | 0.9856 | 0.0003 | 0.9781 | 0.2821 | 400 | 20 | 20 |
| MSC | GradientBoosting | NaN | 0.8884 | 0.1269 | 0.7727 | -0.0232 | 0.9856 | 0.0005 | 0.9892 | 0.1066 | 400 | 20 | 20 |
| MSC | RandomForest | NaN | 0.8925 | 0.1697 | 0.7658 | 0.0020 | 0.9853 | 0.0004 | 0.9778 | 0.2682 | 400 | 20 | 20 |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| SG1 | Ridge | NaN | 0.9560 | 0.1535 | 0.7935 | -0.0199 | 0.9832 | 0.0010 | 0.9953 | 0.0363 | 400 | 20 | 20 |
| Raw | XGBoost | NaN | 0.9694 | 0.1267 | 0.9056 | -0.0039 | 0.9829 | 0.0001 | 0.9965 | 0.0381 | 400 | 20 | 20 |
| SNV+SG1 | GradientBoosting | NaN | 0.9818 | 0.1440 | 0.8306 | -0.0281 | 0.9824 | 0.0016 | 0.9752 | 0.2683 | 400 | 20 | 20 |
| L2 | LightGBM | NaN | 0.9823 | 0.1797 | 0.8803 | 0.0045 | 0.9822 | 0.0014 | 0.9879 | 0.1494 | 400 | 20 | 20 |
| SNV+SG1 | LightGBM | NaN | 0.9953 | 0.1386 | 0.8524 | 0.0139 | 0.9820 | 0.0012 | 0.9705 | 0.3671 | 400 | 20 | 20 |
| MSC | LightGBM | NaN | 1.0067 | 0.1857 | 0.9010 | 0.0248 | 0.9813 | 0.0015 | 0.9858 | 0.1948 | 400 | 20 | 20 |
| EMSC | LightGBM | NaN | 1.0303 | 0.2619 | 0.8762 | -0.0367 | 0.9798 | 0.0046 | 0.9899 | 0.0847 | 400 | 20 | 20 |
| SNV+SG1 | RandomForest | NaN | 1.0309 | 0.1456 | 0.8637 | 0.0126 | 0.9806 | 0.0004 | 0.9673 | 0.4044 | 400 | 20 | 20 |
| MSC | XGBoost | NaN | 1.0359 | 0.1477 | 0.8886 | 0.1359 | 0.9804 | 0.0004 | 0.9779 | 0.4002 | 400 | 20 | 20 |
| Raw | LightGBM | NaN | 1.0429 | 0.1350 | 0.9778 | 0.0181 | 0.9802 | 0.0014 | 0.9940 | 0.0900 | 400 | 20 | 20 |
| SG1 | XGBoost | NaN | 1.0440 | 0.1325 | 0.9407 | -0.0188 | 0.9802 | 0.0018 | 0.9938 | 0.0558 | 400 | 20 | 20 |
| L2 | XGBoost | NaN | 1.0451 | 0.1392 | 0.8901 | 0.0936 | 0.9801 | 0.0011 | 0.9886 | 0.2301 | 400 | 20 | 20 |
| SNV+SG1 | XGBoost | NaN | 1.0687 | 0.1186 | 0.9207 | -0.0105 | 0.9793 | 0.0008 | 0.9713 | 0.3331 | 400 | 20 | 20 |
| SG1 | LightGBM | NaN | 1.0775 | 0.1679 | 0.9592 | -0.0618 | 0.9788 | 0.0022 | 0.9862 | 0.1038 | 400 | 20 | 20 |
| Raw | DecisionTree | NaN | 1.1074 | 0.1279 | 1.0590 | 0.0390 | 0.9778 | 0.0009 | 0.9868 | 0.1974 | 400 | 20 | 20 |
| L2 | PLSR | 3.0 | 1.1146 | 0.1345 | 0.9205 | -0.0023 | 0.9775 | 0.0005 | 0.9817 | 0.2169 | 400 | 20 | 20 |
| EMSC | XGBoost | NaN | 1.1591 | 0.3454 | 0.9418 | -0.0609 | 0.9739 | 0.0028 | 0.9835 | 0.1366 | 400 | 20 | 20 |
| PQN | GradientBoosting | NaN | 1.1838 | 0.1334 | 0.9880 | 0.0574 | 0.9746 | 0.0011 | 0.9780 | 0.3210 | 400 | 20 | 20 |
| PQN | LightGBM | NaN | 1.2013 | 0.2237 | 0.9844 | 0.0061 | 0.9733 | 0.0015 | 0.9866 | 0.1662 | 400 | 20 | 20 |
| PQN | RandomForest | NaN | 1.2479 | 0.2079 | 1.0240 | 0.1135 | 0.9714 | 0.0010 | 0.9732 | 0.4340 | 400 | 20 | 20 |
| PQN | XGBoost | NaN | 1.2702 | 0.2736 | 1.0339 | 0.0828 | 0.9698 | 0.0018 | 0.9816 | 0.3027 | 400 | 20 | 20 |
| L2 | SVR | NaN | 1.3081 | 0.4257 | 1.0318 | 0.1340 | 0.9662 | 0.0018 | 0.9462 | 0.7778 | 400 | 20 | 20 |
| PQN | SVR | NaN | 1.3109 | 0.3398 | 1.0191 | 0.1921 | 0.9672 | 0.0012 | 0.9438 | 0.8646 | 400 | 20 | 20 |
| SG1 | DecisionTree | NaN | 1.3404 | 0.1946 | 1.2302 | -0.0462 | 0.9672 | 0.0017 | 0.9865 | 0.1152 | 400 | 20 | 20 |
| SNV+SG1 | PLSR | 2.0 | 1.3429 | 0.1542 | 1.1304 | 0.0117 | 0.9674 | 0.0009 | 0.9700 | 0.3707 | 400 | 20 | 20 |
| MSC | DecisionTree | NaN | 1.3481 | 0.1277 | 1.2378 | 0.0493 | 0.9672 | 0.0016 | 0.9777 | 0.3159 | 400 | 20 | 20 |
| L2 | DecisionTree | NaN | 1.4094 | 0.1864 | 1.2790 | 0.0110 | 0.9639 | 0.0033 | 0.9801 | 0.2499 | 400 | 20 | 20 |
| Raw | kNN | NaN | 1.4304 | 0.3026 | 1.2840 | -0.0929 | 0.9618 | 0.0011 | 0.9724 | 0.2373 | 400 | 20 | 20 |
| EMSC | DecisionTree | NaN | 1.4593 | 0.2048 | 1.3198 | 0.0562 | 0.9612 | 0.0027 | 0.9867 | 0.2154 | 400 | 20 | 20 |
| EMSC | kNN | NaN | 1.5629 | 0.3133 | 1.4138 | 0.4682 | 0.9546 | 0.0029 | 0.9597 | 0.9503 | 400 | 20 | 20 |
| SG1 | kNN | NaN | 1.5861 | 0.3822 | 1.3800 | 0.0341 | 0.9524 | 0.0103 | 0.9422 | 0.7263 | 400 | 20 | 20 |
| SNV+SG1 | kNN | NaN | 1.6286 | 0.2455 | 1.4083 | 0.4653 | 0.9515 | 0.0059 | 0.9648 | 0.8866 | 400 | 20 | 20 |
| MSC | kNN | NaN | 1.6663 | 0.3424 | 1.3858 | 0.7178 | 0.9483 | 0.0035 | 0.9567 | 1.2363 | 400 | 20 | 20 |
| L2 | kNN | NaN | 1.6848 | 0.2895 | 1.4225 | 0.7569 | 0.9478 | 0.0036 | 0.9667 | 1.1553 | 400 | 20 | 20 |
| MSC | SVR | NaN | 1.6886 | 0.5564 | 1.3307 | 0.1185 | 0.9435 | 0.0012 | 0.9263 | 1.0016 | 400 | 20 | 20 |

```
      SNV+SG1     DecisionTree      NaN  1.7039     0.1890 1.4892 -0.1023 0.9475 0.0046 0.9598
0.3796        400         20         20
          PQN     DecisionTree      NaN  1.7319     0.1310 1.5248  0.1222 0.9461 0.0033 0.9993
0.1303        400         20         20
          MSC              PLSR      3.0  1.7879     0.3401 1.4687 -0.0986 0.9408 0.0013 0.9893
0.0293        400         20         20
          PQN              PLSR      3.0  1.9153     0.4115 1.4771 -0.0088 0.9314 0.0042 0.9585
0.4887        400         20         20
      SNV+SG1             Ridge      NaN  2.0386     0.3257 1.5447  0.0210 0.9238 0.0023 0.9837
0.2158        400         20         20
          PQN               kNN      NaN  2.0474     0.3908 1.6807  1.0623 0.9224 0.0025 0.9217
1.9997        400         20         20
         EMSC               SVR      NaN  2.0493     0.9673 1.5530  0.0713 0.9082 0.0121 0.9673
0.4632        400         20         20
           L2             Ridge      NaN  2.2757     0.3948 1.6925 -0.0500 0.9047 0.0048 1.0034
-0.0904        400         20         20
          MSC             Ridge      NaN  2.7278     0.6202 1.9770 -0.1692 0.8602 0.0084 1.0301
-0.5293        400         20         20
          SG1               SVR      NaN  2.9529     0.9905 2.3005 -0.2233 0.8267 0.0056 0.8311
1.7989        400         20         20
      SNV+SG1               SVR      NaN  3.1236     1.1885 2.3955 -0.1944 0.8004 0.0058 0.8803
1.2390        400         20         20
         EMSC              PLSR      1.0  3.2444     0.5455 2.9182 -0.0442 0.8066 0.0025 0.8369
1.9086        400         20         20
          PQN             Ridge      NaN  4.0913     0.8654 2.7812 -0.2405 0.6875 0.0084 1.0540
-0.8869        400         20         20
         EMSC             Ridge      NaN  4.1388     1.1397 2.7551 -0.4224 0.6707 0.0221 1.0773
-1.3486        400         20         20
  saved:
Table_27_sunset_yellow_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
(63 rows x 14 cols)

[done] Cell 34: Sunset Yellow regression benchmark (T27) — leader PLSR + Raw at RMSECV 0.4628
ug/mL
```

In [36]:

```
DYE = 'Metanil Yellow'
CELL_35_CHECKPOINT = CHECKPOINTS_DIR /
'cell_35_metanil_yellow_regression_benchmark.pkl'

print("=" * 70)
print(f"CELL 35: {DYE} Regression Benchmark (Gate G7)")
print("=" * 70)
print("I score nine regressors across the seven preprocessing representations by
the "
      "stored 25-evaluation concentration-stratified grouped cross-validation on
the "
      f"{DYE.lower()} development set. PLSR uses the latent-variable count fixed
per "
      "representation in Cell 32; the other models use fixed screening defaults,
to be "
      "refined for the leader only in Cell 36. RMSECV, MAE and bias are averaged
over the 25 "
      "folds; R-squared, slope and intercept of predicted on reference are
computed once per "
      "repeat on the full development prediction and averaged over the five
repeats, because a "
      "single fold holds too few distinct concentrations for a stable fit. No test
data is "
      "read (evaluation_protocol section 4).")
print("Metanil yellow is the harder target: its mean fixed-window peak is 0.172 A
against "
      "0.468 and 0.477 A for the other two dyes, and only 16 groups exist (13
development, 3 "
      "test), so each fold spans fewer concentration levels and the errors carry
wider "
      "fold-to-fold spread. I read these numbers in that light.")
```

```
import time
from sklearn.cross_decomposition import PLSRegression
from sklearn.linear_model import Ridge
from sklearn.svm import SVR
from sklearn.neighbors import KNeighborsRegressor
from sklearn.tree import DecisionTreeRegressor
from sklearn.ensemble import RandomForestRegressor, GradientBoostingRegressor
from sklearn.pipeline import Pipeline
from sklearn.metrics import r2_score
from xgboost import XGBRegressor
from lightgbm import LGBMRegressor

PREP_ORDER = ['Raw', 'SG1', 'SNV+SG1', 'MSC', 'L2', 'EMSC', 'PQN']
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
LV = {r['Preprocessing']: int(r['selected_LV'])
      for _, r in infra['lv_selection'][infra['lv_selection']['Dye'] ==
DYE].iterrows()}

sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
dev_rows = np.asarray(sealed['regression'][DYE]['dev_rows'])
rep_folds = cvf['regression'][DYE]['folds']                    # 5 repeats x 5
folds
N_SPECTRA = int(len(dev_rows))
N_GROUPS = int(len(np.unique(group_id[dev_rows])))
N_LEVELS = int(len(np.unique(conc[dev_rows])))
print(f"\nDevelopment set: {N_SPECTRA} spectra / {N_GROUPS} groups / {N_LEVELS}
levels | "
      f"{len(rep_folds)} repeats x {len(rep_folds[0])} folds")


def make_model(name, prep):
    if name == 'PLSR':
        return PLSRegression(n_components=LV[prep], scale=False)
    if name == 'Ridge':
        return Ridge(alpha=1.0, random_state=42)
    if name == 'SVR':
        return SVR(kernel='rbf', C=10.0, epsilon=0.1)
    if name == 'kNN':
        return KNeighborsRegressor(n_neighbors=5, weights='distance')
    if name == 'DecisionTree':
        return DecisionTreeRegressor(random_state=42)
    if name == 'RandomForest':
        return RandomForestRegressor(n_estimators=300, random_state=42, n_jobs=1)
    if name == 'GradientBoosting':
        return GradientBoostingRegressor(n_estimators=200, random_state=42)
    if name == 'XGBoost':
        return XGBRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                            subsample=0.9, random_state=42, n_jobs=1, verbosity=0)
    if name == 'LightGBM':
        return LGBMRegressor(n_estimators=300, max_depth=4, learning_rate=0.08,
                             random_state=42, n_jobs=1, verbose=-1)
    raise KeyError(name)


MODELS = ['PLSR', 'Ridge', 'SVR', 'kNN', 'DecisionTree', 'RandomForest',
          'GradientBoosting', 'XGBoost', 'LightGBM']
```

```
def build(name, prep):
    steps = []
    pre = TRANSFORMERS[prep]
    if pre is not None:
        steps.append(('pre', pre()))
    steps.append(('sc', StandardScaler()))
    steps.append(('est', make_model(name, prep)))
    return Pipeline(steps)


def score_combo(name, prep):
    fold_rmse, fold_mae, fold_bias = [], [], []
    repeat_true, repeat_pred = [], []        # per-repeat pooled dev predictions
    for rep in rep_folds:
        tt, pp = [], []
        for tr, va in rep:
            tr, va = np.asarray(tr), np.asarray(va)
            m = build(name, prep).fit(X[tr], conc[tr])
            pred = np.asarray(m.predict(X[va])).ravel()
            true = conc[va]
            err = pred - true
            fold_rmse.append(float(np.sqrt(np.mean(err ** 2))))
            fold_mae.append(float(np.mean(np.abs(err))))
            fold_bias.append(float(np.mean(err)))
            tt.append(true); pp.append(pred)
        repeat_true.append(np.concatenate(tt));
repeat_pred.append(np.concatenate(pp))
    r2s, slopes, intercepts = [], [], []
    for true, pred in zip(repeat_true, repeat_pred):
        r2s.append(float(r2_score(true, pred)))
        s, b = np.polyfit(true, pred, 1)          # predicted on reference
        slopes.append(float(s)); intercepts.append(float(b))
    return {
        'Preprocessing': prep, 'Model': name,
        'PLS_LV': LV[prep] if name == 'PLSR' else np.nan,
        'RMSECV': round(float(np.mean(fold_rmse)), 4),
        'RMSECV_SD': round(float(np.std(fold_rmse)), 4),
        'MAE': round(float(np.mean(fold_mae)), 4),
        'bias': round(float(np.mean(fold_bias)), 4),
        'R2': round(float(np.mean(r2s)), 4),
        'R2_SD': round(float(np.std(r2s)), 4),
        'slope': round(float(np.mean(slopes)), 4),
        'intercept': round(float(np.mean(intercepts)), 4),
        'n_spectra': N_SPECTRA, 'n_groups': N_GROUPS, 'n_levels': N_LEVELS,
    }


# The 63-combination cross-validation is the expensive step. It is cached in the
cell
# checkpoint: if the checkpoint is present the stored benchmark is loaded and only
the
# tables and summary are re-rendered; otherwise it is computed once. A fresh run
with no
# checkpoint recomputes it in full, so the result is reproducible either way.
from concurrent.futures import ThreadPoolExecutor
if CELL_35_CHECKPOINT.exists():
    bench = load_checkpoint(CELL_35_CHECKPOINT, validate_hash=False)['benchmark']
    print(f"\nLoaded cached benchmark ({len(bench)} combinations) from checkpoint;
"
          f"cross-validation not recomputed.")
```

```
    _computed = False
else:
    combos = [(name, prep) for name in MODELS for prep in PREP_ORDER]
    t0 = time.time()
    # Independent combinations on a thread pool, each model single-threaded; the
    # scikit-learn / XGBoost / LightGBM fits release the GIL, so threading only
reduces
    # wall-clock time and changes nothing about the fits or the seeds.
    with ThreadPoolExecutor(max_workers=6) as ex:
        rows = list(ex.map(lambda c: score_combo(*c), combos))
    bench = pd.DataFrame(rows).sort_values('RMSECV').reset_index(drop=True)
    print(f"Benchmark computed in {time.time() - t0:.0f}s ({len(bench)}
combinations, "
          f"6 worker threads).")
    _computed = True

lead = bench.iloc[0]
uni = infra['univariate_benchmark']
uni_rmse = float(uni[uni['Dye'] == DYE]['univariate_RMSECV'].iloc[0])
print(f"\n  Leading pipeline: {lead['Model']} + {lead['Preprocessing']}  "
      f"RMSECV {lead['RMSECV']:.4f} +/- {lead['RMSECV_SD']:.4f} ug/mL | R2
{lead['R2']:.4f} | "
      f"slope {lead['slope']:.3f} | bias {lead['bias']:+.4f}")
print(f"  Single-wavelength univariate benchmark RMSECV {uni_rmse:.4f} ug/mL — "
      f"leader {'beats' if lead['RMSECV'] < uni_rmse else 'does NOT beat'} it.")
print("\n--- Top 12 pipelines by RMSECV ---")
print(bench[['Model', 'Preprocessing', 'RMSECV', 'RMSECV_SD', 'MAE', 'R2',
                      'slope', 'intercept', 'bias']].to_string(index=False))

show_and_save_table(bench, 28, f'{DYE} regression benchmark across models and
preprocessing '
                    '(development CV)', cell='35', max_rows=63,
                    notes=f'Nine regressors x seven preprocessings on the
{DYE.lower()} '
                          f'development set ({N_SPECTRA} spectra / {N_GROUPS}
groups / '
                          f'{N_LEVELS} levels), 25 concentration-stratified
grouped folds. '
                          f'RMSECV, MAE, bias averaged over 25 folds; R2, slope,
intercept of '
                          f'predicted on reference averaged over 5 repeat-level
full-development '
                          f'predictions. PLSR latent variables fixed in Cell 32;
other models at '
                          f'screening defaults (refined only for the leader in
Cell 36). '
                          f'Concentrations in micrograms per millilitre. No test
data read.')

if _computed:
    save_checkpoint({'benchmark': bench, 'leader': lead.to_dict(), 'dye': DYE,
                     'univariate_RMSECV': uni_rmse},
                    CELL_35_CHECKPOINT,
                    metadata={'type': 'regression_benchmark', 'cell': '35', 'dye':
DYE,
                              'gate': 'G7'})
    _ = load_checkpoint(CELL_35_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 35: {DYE} regression benchmark (T28) — leader "
      f"{lead['Model']} + {lead['Preprocessing']} at RMSECV {lead['RMSECV']:.4f}
ug/mL")
```

```
======================================================================
CELL 35: Metanil Yellow Regression Benchmark (Gate G7)
======================================================================
I score nine regressors across the seven preprocessing representations by the stored 25-
evaluation concentration-stratified grouped cross-validation on the metanil yellow development
set. PLSR uses the latent-variable count fixed per representation in Cell 32; the other models
use fixed screening defaults, to be refined for the leader only in Cell 36. RMSECV, MAE and bias
are averaged over the 25 folds; R-squared, slope and intercept of predicted on reference are
computed once per repeat on the full development prediction and averaged over the five repeats,
because a single fold holds too few distinct concentrations for a stable fit. No test data is
read (evaluation_protocol section 4).
Metanil yellow is the harder target: its mean fixed-window peak is 0.172 A against 0.468 and
0.477 A for the other two dyes, and only 16 groups exist (13 development, 3 test), so each fold
spans fewer concentration levels and the errors carry wider fold-to-fold spread. I read these
numbers in that light.
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891

Development set: 260 spectra / 13 groups / 13 levels | 5 repeats x 5 folds
✓ Checkpoint loaded: cell_35_metanil_yellow_regression_benchmark.pkl
  Timestamp: 2026-11-04T21:13:10.817641
  Shape: {'benchmark': (63, 14)}

Loaded cached benchmark (63 combinations) from checkpoint; cross-validation not recomputed.

  Leading pipeline: PLSR + Raw  RMSECV 0.2042 +/- 0.0401 ug/mL | R2 0.9980 | slope 0.998 | bias
+0.0083
  Single-wavelength univariate benchmark RMSECV 0.9044 ug/mL — leader beats it.

--- Top 12 pipelines by RMSECV ---
           Model Preprocessing  RMSECV  RMSECV_SD    MAE     R2  slope  intercept    bias
            PLSR           Raw  0.2042     0.0401 0.1547 0.9980 0.9984     0.0225  0.0083
            PLSR            L2  0.2123     0.0307 0.1639 0.9978 0.9954     0.0303  0.0003
           Ridge           SG1  0.2552     0.0658 0.1950 0.9966 1.0069    -0.0617 -0.0127
           Ridge           Raw  0.2580     0.0391 0.2089 0.9967 1.0034    -0.0121  0.0130
            PLSR           MSC  0.2779     0.1106 0.2174 0.9958 0.9986     0.0069 -0.0019
            PLSR           SG1  0.2819     0.0762 0.2318 0.9959 0.9914     0.0476 -0.0067
           Ridge            L2  0.3300     0.0738 0.2574 0.9945 1.0011    -0.0414 -0.0292
           Ridge       SNV+SG1  0.4203     0.0889 0.3211 0.9911 1.0090    -0.0573  0.0058
            PLSR       SNV+SG1  0.4319     0.0710 0.3421 0.9908 0.9894     0.0671  0.0014
           Ridge           MSC  0.4429     0.0878 0.3488 0.9902 1.0073    -0.0522  0.0023
    RandomForest          EMSC  0.4860     0.1410 0.4237 0.9876 0.9660     0.2661  0.0485
    RandomForest           MSC  0.5156     0.1494 0.4548 0.9863 0.9576     0.2872  0.0155
    RandomForest            L2  0.5460     0.1951 0.4787 0.9843 0.9541     0.3201  0.0290
            PLSR          EMSC  0.5722     0.1475 0.4853 0.9836 0.9883     0.0613 -0.0026
GradientBoosting            L2  0.6078     0.1618 0.5353 0.9816 0.9524     0.3589  0.0560
    RandomForest           Raw  0.6172     0.1864 0.5177 0.9807 0.9469     0.3551  0.0075
GradientBoosting           MSC  0.6180     0.1045 0.5417 0.9814 0.9585     0.3071  0.0312
           Ridge          EMSC  0.6279     0.1641 0.4878 0.9797 1.0038    -0.0768 -0.0424
GradientBoosting          EMSC  0.6482     0.0919 0.5578 0.9794 0.9590     0.3970  0.1310
GradientBoosting           Raw  0.7168     0.1342 0.6381 0.9753 0.9500     0.4194  0.0955
        LightGBM           SG1  0.7187     0.1164 0.6049 0.9747 0.9530     0.3700  0.0536
        LightGBM       SNV+SG1  0.7691     0.0948 0.6205 0.9711 0.9558     0.3523  0.0581
GradientBoosting           SG1  0.8032     0.1345 0.6816 0.9686 0.9338     0.4658  0.0172
         XGBoost           SG1  0.8419     0.1696 0.7358 0.9651 0.9283     0.5844  0.0940
GradientBoosting       SNV+SG1  0.8458     0.0878 0.7018 0.9655 0.9346     0.4774  0.0292
         XGBoost            L2  0.8632     0.1492 0.7764 0.9633 0.9416     0.3824 -0.0227
         XGBoost       SNV+SG1  0.8666     0.0960 0.7156 0.9639 0.9297     0.5447  0.0593
         XGBoost           MSC  0.8771     0.0917 0.7925 0.9633 0.9383     0.3828 -0.0446
    RandomForest           SG1  0.8933     0.1921 0.7717 0.9597 0.9015     0.7583  0.0838
    RandomForest       SNV+SG1  0.9258     0.1735 0.7727 0.9566 0.8967     0.7436  0.0342
         XGBoost           Raw  0.9277     0.1823 0.8215 0.9591 0.9512     0.1649 -0.1779
        LightGBM           MSC  0.9473     0.1645 0.8570 0.9552 0.9518     0.3110 -0.0052
         XGBoost          EMSC  0.9500     0.2174 0.8403 0.9540 0.9523     0.3390  0.0187
        LightGBM            L2  0.9901     0.2075 0.8958 0.9513 0.9647     0.2841  0.0637
```

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| LightGBM | EMSC | 0.9916 | 0.1988 | 0.8710 | 0.9510 | 0.9759 | 0.1821 | 0.0334 | |
| LightGBM | Raw | 0.9931 | 0.1940 | 0.9027 | 0.9529 | 0.9368 | 0.4955 | 0.0598 | |
| SVR | L2 | 1.0503 | 0.5462 | 0.7598 | 0.9335 | 0.8599 | 1.1377 | 0.1798 | |
| GradientBoosting | PQN | 1.1428 | 0.3251 | 0.9150 | 0.9310 | 0.9154 | 0.5851 | 0.0276 | |
| DecisionTree | MSC | 1.1632 | 0.1929 | 1.1003 | 0.9327 | 0.9583 | 0.3185 | 0.0537 | |
| RandomForest | PQN | 1.1667 | 0.3263 | 0.9411 | 0.9291 | 0.8907 | 0.7885 | 0.0679 | |
| DecisionTree | L2 | 1.1709 | 0.1995 | 1.1110 | 0.9321 | 0.9490 | 0.3545 | 0.0310 | |
| DecisionTree | Raw | 1.1714 | 0.2132 | 1.0953 | 0.9322 | 0.9392 | 0.4600 | 0.0580 | |
| DecisionTree | EMSC | 1.2132 | 0.1689 | 1.1397 | 0.9296 | 0.9596 | 0.3830 | 0.1037 | |
| kNN | Raw | 1.2255 | 0.4653 | 1.0926 | 0.9225 | 0.8994 | 0.7563 | 0.0403 | |
| PLSR | PQN | 1.2279 | 0.6630 | 0.9919 | 0.9069 | 0.9191 | 0.5619 | 0.0230 | |
| SVR | Raw | 1.2497 | 0.6121 | 0.9183 | 0.9077 | 0.8232 | 1.4501 | 0.2379 | |
| kNN | L2 | 1.2528 | 0.5153 | 1.1224 | 0.9153 | 0.8950 | 0.7272 | -0.0129 | |
| XGBoost | PQN | 1.2736 | 0.2618 | 1.0557 | 0.9196 | 0.9108 | 0.5873 | -0.0043 | |
| SVR | MSC | 1.2751 | 0.5124 | 0.9569 | 0.9096 | 0.8653 | 1.0832 | 0.1625 | |
| LightGBM | PQN | 1.2767 | 0.3528 | 1.0251 | 0.9153 | 0.9200 | 0.5290 | -0.0111 | |
| kNN | MSC | 1.3101 | 0.5431 | 1.1457 | 0.9059 | 0.8747 | 0.7742 | -0.1079 | |
| SVR | PQN | 1.3290 | 0.8758 | 0.9422 | 0.8814 | 0.7740 | 1.8488 | 0.2869 | |
| kNN | EMSC | 1.3527 | 0.6388 | 1.2157 | 0.8930 | 0.8494 | 0.8006 | -0.2498 | |
| kNN | PQN | 1.5122 | 0.6366 | 1.2941 | 0.8718 | 0.8655 | 1.1318 | 0.1900 | |
| DecisionTree | SG1 | 1.5815 | 0.2593 | 1.4387 | 0.8771 | 0.8969 | 0.8335 | 0.1160 | |
| Ridge | PQN | 1.6001 | 0.4071 | 1.2104 | 0.8712 | 1.0121 | -0.2508 | -0.1517 | |
| SVR | EMSC | 1.6203 | 0.6235 | 1.2545 | 0.8559 | 0.9031 | 0.8401 | 0.1869 | |
| DecisionTree | SNV+SG1 | 1.6337 | 0.1887 | 1.4760 | 0.8700 | 0.8948 | 0.8168 | 0.0847 | |
| kNN | SNV+SG1 | 1.7347 | 0.7538 | 1.5104 | 0.8308 | 0.7548 | 2.0372 | 0.3053 | |
| kNN | SG1 | 1.7570 | 0.7353 | 1.5266 | 0.8285 | 0.7367 | 2.0122 | 0.1560 | |
| DecisionTree | PQN | 1.7584 | 0.3831 | 1.5467 | 0.8487 | 0.8962 | 0.6519 | -0.0553 | |
| SVR | SNV+SG1 | 2.0870 | 0.8554 | 1.6534 | 0.7503 | 0.7768 | 1.4741 | -0.0706 | |
| SVR | SG1 | 2.2255 | 0.8913 | 1.7571 | 0.7183 | 0.7739 | 1.4447 | -0.1227 | |

TABLE 28: Metanil Yellow regression benchmark across models and preprocessing (development CV)

| Preprocessing | Model | PLS_LV | RMSECV | RMSECV_SD | MAE | bias | R2 | R2_SD | slope | intercept | n_spectra | n_groups | n_levels |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Raw | PLSR | 3.0 | 0.2042 | 0.0401 | 0.1547 | 0.0083 | 0.9980 | 0.0000 | 0.9984 | 0.0225 | 260 | 13 | 13 |
| L2 | PLSR | 3.0 | 0.2123 | 0.0307 | 0.1639 | 0.0003 | 0.9978 | 0.0001 | 0.9954 | 0.0303 | 260 | 13 | 13 |
| SG1 | Ridge | NaN | 0.2552 | 0.0658 | 0.1950 | -0.0127 | 0.9966 | 0.0003 | 1.0069 | -0.0617 | 260 | 13 | 13 |
| Raw | Ridge | NaN | 0.2580 | 0.0391 | 0.2089 | 0.0130 | 0.9967 | 0.0003 | 1.0034 | -0.0121 | 260 | 13 | 13 |
| MSC | PLSR | 3.0 | 0.2779 | 0.1106 | 0.2174 | -0.0019 | 0.9958 | 0.0004 | 0.9986 | 0.0069 | 260 | 13 | 13 |
| SG1 | PLSR | 2.0 | 0.2819 | 0.0762 | 0.2318 | -0.0067 | 0.9959 | 0.0002 | 0.9914 | 0.0476 | 260 | 13 | 13 |
| L2 | Ridge | NaN | 0.3300 | 0.0738 | 0.2574 | -0.0292 | 0.9945 | 0.0002 | 1.0011 | -0.0414 | 260 | 13 | 13 |
| SNV+SG1 | Ridge | NaN | 0.4203 | 0.0889 | 0.3211 | 0.0058 | 0.9911 | 0.0006 | 1.0090 | -0.0573 | 260 | 13 | 13 |
| SNV+SG1 | PLSR | 3.0 | 0.4319 | 0.0710 | 0.3421 | 0.0014 | 0.9908 | 0.0007 | 0.9894 | 0.0671 | 260 | 13 | 13 |
| MSC | Ridge | NaN | 0.4429 | 0.0878 | 0.3488 | 0.0023 | 0.9902 | 0.0008 | 1.0073 | -0.0522 | 260 | 13 | 13 |
| EMSC | RandomForest | NaN | 0.4860 | 0.1410 | 0.4237 | 0.0485 | 0.9876 | 0.0002 | 0.9660 | 0.2661 | 260 | 13 | 13 |
| MSC | RandomForest | NaN | 0.5156 | 0.1494 | 0.4548 | 0.0155 | 0.9863 | 0.0003 | 0.9576 | 0.2872 | 260 | 13 | 13 |
| L2 | RandomForest | NaN | 0.5460 | 0.1951 | 0.4787 | 0.0290 | 0.9843 | 0.0004 | 0.9541 | 0.3201 | 260 | 13 | 13 |
| EMSC | PLSR | 1.0 | 0.5722 | 0.1475 | 0.4853 | -0.0026 | 0.9836 | 0.0005 | 0.9883 | 0.0613 | 260 | 13 | 13 |
| L2 | GradientBoosting | NaN | 0.6078 | 0.1618 | 0.5353 | 0.0560 | 0.9816 | 0.0004 | 0.9524 | 0.3589 | 260 | 13 | 13 |
| Raw | RandomForest | NaN | 0.6172 | 0.1864 | 0.5177 | 0.0075 | 0.9807 | 0.0001 | 0.9469 | 0.3551 | 260 | 13 | 13 |
| MSC | GradientBoosting | NaN | 0.6180 | 0.1045 | 0.5417 | 0.0312 | 0.9814 | 0.0009 | 0.9585 | 0.3071 | 260 | 13 | 13 |
| EMSC | Ridge | NaN | 0.6279 | 0.1641 | 0.4878 | -0.0424 | 0.9797 | 0.0012 | 1.0038 | -0.0768 | 260 | 13 | 13 |
| EMSC | GradientBoosting | NaN | 0.6482 | 0.0919 | 0.5578 | 0.1310 | 0.9794 | 0.0015 | 0.9590 | | | | |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 0.3970 | 260 | 13 | 13 | | | | | | | |
| Raw | GradientBoosting | NaN | 0.7168 | 0.1342 | 0.6381 | 0.0955 | 0.9753 | 0.0011 | 0.9500 | |
| 0.4194 | 260 | 13 | 13 | | | | | | | |
| SG1 | LightGBM | NaN | 0.7187 | 0.1164 | 0.6049 | 0.0536 | 0.9747 | 0.0008 | 0.9530 | |
| 0.3700 | 260 | 13 | 13 | | | | | | | |
| SNV+SG1 | LightGBM | NaN | 0.7691 | 0.0948 | 0.6205 | 0.0581 | 0.9711 | 0.0009 | 0.9558 | |
| 0.3523 | 260 | 13 | 13 | | | | | | | |
| SG1 | GradientBoosting | NaN | 0.8032 | 0.1345 | 0.6816 | 0.0172 | 0.9686 | 0.0014 | 0.9338 | |
| 0.4658 | 260 | 13 | 13 | | | | | | | |
| SG1 | XGBoost | NaN | 0.8419 | 0.1696 | 0.7358 | 0.0940 | 0.9651 | 0.0011 | 0.9283 | |
| 0.5844 | 260 | 13 | 13 | | | | | | | |
| SNV+SG1 | GradientBoosting | NaN | 0.8458 | 0.0878 | 0.7018 | 0.0292 | 0.9655 | 0.0008 | 0.9346 | |
| 0.4774 | 260 | 13 | 13 | | | | | | | |
| L2 | XGBoost | NaN | 0.8632 | 0.1492 | 0.7764 | -0.0227 | 0.9633 | 0.0024 | 0.9416 | |
| 0.3824 | 260 | 13 | 13 | | | | | | | |
| SNV+SG1 | XGBoost | NaN | 0.8666 | 0.0960 | 0.7156 | 0.0593 | 0.9639 | 0.0024 | 0.9297 | |
| 0.5447 | 260 | 13 | 13 | | | | | | | |
| MSC | XGBoost | NaN | 0.8771 | 0.0917 | 0.7925 | -0.0446 | 0.9633 | 0.0004 | 0.9383 | |
| 0.3828 | 260 | 13 | 13 | | | | | | | |
| SG1 | RandomForest | NaN | 0.8933 | 0.1921 | 0.7717 | 0.0838 | 0.9597 | 0.0017 | 0.9015 | |
| 0.7583 | 260 | 13 | 13 | | | | | | | |
| SNV+SG1 | RandomForest | NaN | 0.9258 | 0.1735 | 0.7727 | 0.0342 | 0.9566 | 0.0012 | 0.8967 | |
| 0.7436 | 260 | 13 | 13 | | | | | | | |
| Raw | XGBoost | NaN | 0.9277 | 0.1823 | 0.8215 | -0.1779 | 0.9591 | 0.0014 | 0.9512 | |
| 0.1649 | 260 | 13 | 13 | | | | | | | |
| MSC | LightGBM | NaN | 0.9473 | 0.1645 | 0.8570 | -0.0052 | 0.9552 | 0.0009 | 0.9518 | |
| 0.3110 | 260 | 13 | 13 | | | | | | | |
| EMSC | XGBoost | NaN | 0.9500 | 0.2174 | 0.8403 | 0.0187 | 0.9540 | 0.0028 | 0.9523 | |
| 0.3390 | 260 | 13 | 13 | | | | | | | |
| L2 | LightGBM | NaN | 0.9901 | 0.2075 | 0.8958 | 0.0637 | 0.9513 | 0.0035 | 0.9647 | |
| 0.2841 | 260 | 13 | 13 | | | | | | | |
| EMSC | LightGBM | NaN | 0.9916 | 0.1988 | 0.8710 | 0.0334 | 0.9510 | 0.0056 | 0.9759 | |
| 0.1821 | 260 | 13 | 13 | | | | | | | |
| Raw | LightGBM | NaN | 0.9931 | 0.1940 | 0.9027 | 0.0598 | 0.9529 | 0.0019 | 0.9368 | |
| 0.4955 | 260 | 13 | 13 | | | | | | | |
| L2 | SVR | NaN | 1.0503 | 0.5462 | 0.7598 | 0.1798 | 0.9335 | 0.0038 | 0.8599 | |
| 1.1377 | 260 | 13 | 13 | | | | | | | |
| PQN | GradientBoosting | NaN | 1.1428 | 0.3251 | 0.9150 | 0.0276 | 0.9310 | 0.0078 | 0.9154 | |
| 0.5851 | 260 | 13 | 13 | | | | | | | |
| MSC | DecisionTree | NaN | 1.1632 | 0.1929 | 1.1003 | 0.0537 | 0.9327 | 0.0035 | 0.9583 | |
| 0.3185 | 260 | 13 | 13 | | | | | | | |
| PQN | RandomForest | NaN | 1.1667 | 0.3263 | 0.9411 | 0.0679 | 0.9291 | 0.0096 | 0.8907 | |
| 0.7885 | 260 | 13 | 13 | | | | | | | |
| L2 | DecisionTree | NaN | 1.1709 | 0.1995 | 1.1110 | 0.0310 | 0.9321 | 0.0029 | 0.9490 | |
| 0.3545 | 260 | 13 | 13 | | | | | | | |
| Raw | DecisionTree | NaN | 1.1714 | 0.2132 | 1.0953 | 0.0580 | 0.9322 | 0.0032 | 0.9392 | |
| 0.4600 | 260 | 13 | 13 | | | | | | | |
| EMSC | DecisionTree | NaN | 1.2132 | 0.1689 | 1.1397 | 0.1037 | 0.9296 | 0.0037 | 0.9596 | |
| 0.3830 | 260 | 13 | 13 | | | | | | | |
| Raw | kNN | NaN | 1.2255 | 0.4653 | 1.0926 | 0.0403 | 0.9225 | 0.0035 | 0.8994 | |
| 0.7563 | 260 | 13 | 13 | | | | | | | |
| PQN | PLSR | 2.0 | 1.2279 | 0.6630 | 0.9919 | 0.0230 | 0.9069 | 0.0089 | 0.9191 | |
| 0.5619 | 260 | 13 | 13 | | | | | | | |
| Raw | SVR | NaN | 1.2497 | 0.6121 | 0.9183 | 0.2379 | 0.9077 | 0.0059 | 0.8232 | |
| 1.4501 | 260 | 13 | 13 | | | | | | | |
| L2 | kNN | NaN | 1.2528 | 0.5153 | 1.1224 | -0.0129 | 0.9153 | 0.0015 | 0.8950 | |
| 0.7272 | 260 | 13 | 13 | | | | | | | |
| PQN | XGBoost | NaN | 1.2736 | 0.2618 | 1.0557 | -0.0043 | 0.9196 | 0.0041 | 0.9108 | |
| 0.5873 | 260 | 13 | 13 | | | | | | | |
| MSC | SVR | NaN | 1.2751 | 0.5124 | 0.9569 | 0.1625 | 0.9096 | 0.0035 | 0.8653 | |
| 1.0832 | 260 | 13 | 13 | | | | | | | |
| PQN | LightGBM | NaN | 1.2767 | 0.3528 | 1.0251 | -0.0111 | 0.9153 | 0.0056 | 0.9200 | |
| 0.5290 | 260 | 13 | 13 | | | | | | | |
| MSC | kNN | NaN | 1.3101 | 0.5431 | 1.1457 | -0.1079 | 0.9059 | 0.0031 | 0.8747 | |
| 0.7742 | 260 | 13 | 13 | | | | | | | |
| PQN | SVR | NaN | 1.3290 | 0.8758 | 0.9422 | 0.2869 | 0.8814 | 0.0110 | 0.7740 | |
| 1.8488 | 260 | 13 | 13 | | | | | | | |
| EMSC | kNN | NaN | 1.3527 | 0.6388 | 1.2157 | -0.2498 | 0.8930 | 0.0056 | 0.8494 | |
| 0.8006 | 260 | 13 | 13 | | | | | | | |
| PQN | kNN | NaN | 1.5122 | 0.6366 | 1.2941 | 0.1900 | 0.8718 | 0.0061 | 0.8655 | |

```
1.1318        260        13        13
          SG1     DecisionTree     NaN  1.5815     0.2593 1.4387  0.1160 0.8771 0.0161 0.8969
0.8335        260        13        13
          PQN            Ridge     NaN  1.6001     0.4071 1.2104 -0.1517 0.8712 0.0134 1.0121
-0.2508        260        13        13
         EMSC              SVR     NaN  1.6203     0.6235 1.2545  0.1869 0.8559 0.0043 0.9031
0.8401        260        13        13
      SNV+SG1     DecisionTree     NaN  1.6337     0.1887 1.4760  0.0847 0.8700 0.0061 0.8948
0.8168        260        13        13
      SNV+SG1              kNN     NaN  1.7347     0.7538 1.5104  0.3053 0.8308 0.0011 0.7548
2.0372        260        13        13
          SG1              kNN     NaN  1.7570     0.7353 1.5266  0.1560 0.8285 0.0005 0.7367
2.0122        260        13        13
          PQN     DecisionTree     NaN  1.7584     0.3831 1.5467 -0.0553 0.8487 0.0184 0.8962
0.6519        260        13        13
      SNV+SG1              SVR     NaN  2.0870     0.8554 1.6534 -0.0706 0.7503 0.0036 0.7768
1.4741        260        13        13
          SG1              SVR     NaN  2.2255     0.8913 1.7571 -0.1227 0.7183 0.0060 0.7739
1.4447        260        13        13
  saved:
Table_28_metanil_yellow_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
(63 rows x 14 cols)

[done] Cell 35: Metanil Yellow regression benchmark (T28) — leader PLSR + Raw at RMSECV 0.2042
ug/mL
```

In [37]:

```python
CELL_36_CHECKPOINT = CHECKPOINTS_DIR / 'cell_36_regression_freeze_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'
MODELS_DIR.mkdir(exist_ok=True)

print("=" * 70)
print("CELL 36: Regression Comparison, Bounded Optimisation, and Freeze (Gate
G7)")
print("=" * 70)
print("I compare the three development benchmarks, optimise the leading pipeline
per dye "
      "within bounds, and freeze the final regressors. Across all three dyes the "
      "leader is PLS regression on the raw (AirPLS-corrected) spectra: the latent-
variable "
      "models capture the Beer-Lambert amplitude that the scatter-correction
representations "
      "remove, and they beat the single-wavelength univariate benchmark.
Optimisation follows "
      "the pre-registered scheme (materials_and_methods section 201): a bounded
latent-variable "
      "grid refinement under the one-standard-error rule, then a bounded Optuna
search (<=30 "
      "trials, TPE, objective = mean RMSECV over the 25 grouped folds) over the
PLS latent-"
      "variable count and the unit-variance-scaling flag. The model is frozen at
the parsimonious "
      "one-SE latent-variable count; Optuna is reported as confirmation that no
materially lower "
      "RMSECV is available. The sealed test is NOT read (evaluation_protocol
section 11).")

import joblib, hashlib, json, time, optuna
from datetime import datetime as _dt
from sklearn.cross_decomposition import PLSRegression
from sklearn.pipeline import Pipeline
from optuna.samplers import TPESampler
from oj_analysis import state as state_mod
optuna.logging.set_verbosity(optuna.logging.WARNING)
```

```
DYES = list(DYE_CLASSES)
SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
uni = infra['univariate_benchmark']
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
BENCH = {
    'Tartrazine': load_checkpoint(CHECKPOINTS_DIR /
'cell_33_tartrazine_regression_benchmark.pkl',
                                  validate_hash=False)['benchmark'],
    'Sunset Yellow': load_checkpoint(CHECKPOINTS_DIR /
'cell_34_sunset_yellow_regression_benchmark.pkl',
                                     validate_hash=False)['benchmark'],
    'Metanil Yellow': load_checkpoint(CHECKPOINTS_DIR /
'cell_35_metanil_yellow_regression_benchmark.pkl',
                                      validate_hash=False)['benchmark'],
}
NMAX = 15


def rmse(a, b):
    return float(np.sqrt(np.mean((np.asarray(a) - np.asarray(b)) ** 2)))


def folds_of(dye):
    return [f for rep in cvf['regression'][dye]['folds'] for f in rep]


def plsr_raw_cv(dye, n_comp, scale=False):
    """Mean and SD of per-fold RMSE for PLSR on raw spectra (25 grouped folds)."""
    s = []
    for tr, va in folds_of(dye):
        tr, va = np.asarray(tr), np.asarray(va)
        p = Pipeline([('sc', StandardScaler()),
                      ('pls', PLSRegression(n_components=n_comp,
scale=scale))]).fit(X[tr], conc[tr])
        s.append(rmse(conc[va], p.predict(X[va]).ravel()))
    return float(np.mean(s)), float(np.std(s))


# ---- comparison + bounded grid (one-SE) + bounded Optuna + freeze, per dye ----
summary, freeze_records, optuna_rows = [], {}, []
for dye in DYES:
    dev = np.asarray(sealed['regression'][dye]['dev_rows'])
    assert conc[dev].min() >= 0, "negative concentration in dev set"
    ncap = min(NMAX, len(dev) - 1)

    # (1) bounded latent-variable grid refinement, one-SE rule (fold SD)
    means = np.array([plsr_raw_cv(dye, k)[0] for k in range(1, ncap + 1)])
    sds = np.array([plsr_raw_cv(dye, k)[1] for k in range(1, ncap + 1)])
    kbest = int(np.argmin(means))
    kopt = int(np.argmax(means <= means[kbest] + sds[kbest])) + 1      # one-SE
parsimony
    opt_rmsecv, opt_sd = float(means[kopt - 1]), float(sds[kopt - 1])

    # (2) bounded Optuna (materials_and_methods section 201)
    log = []

    def objective(trial):
```

```
        k = trial.suggest_int('n_components', 1, ncap)
        sc = trial.suggest_categorical('scale', [False, True])
        m, s = plsr_raw_cv(dye, k, sc)
        log.append({'dye': dye, 'trial': trial.number, 'n_components': k, 'scale':
sc,
                    'mean_RMSECV': round(m, 5)})
        return m

    study = optuna.create_study(direction='minimize', sampler=TPESampler(seed=42))
    t_opt = time.time()
    study.optimize(objective, n_trials=30, show_progress_bar=False)
    opt_best_lv = int(study.best_params['n_components'])
    opt_best_scale = bool(study.best_params['scale'])
    opt_best_rmsecv = float(study.best_value)
    optuna_rows.extend(log)

    # (3) freeze at the parsimonious one-SE latent-variable count, scale=False
    final_pipe = Pipeline([('sc', StandardScaler()),
                           ('pls', PLSRegression(n_components=kopt,
scale=False))])
    final_pipe.fit(X[dev], conc[dev])
    resub = final_pipe.predict(X[dev]).ravel()
    path = MODELS_DIR / f"regressor_{SHORT[dye]}_frozen.joblib"
    joblib.dump({'pipeline': final_pipe, 'dye': dye, 'preprocessing': 'Raw',
                 'estimator': 'PLSRegression', 'n_components': kopt}, path)
    sha = hashlib.sha256(path.read_bytes()).hexdigest()
    uni_rmse = float(uni[uni['Dye'] == dye]['univariate_RMSECV'].iloc[0])
    lead = BENCH[dye].iloc[0]
    best_nonpls = BENCH[dye][BENCH[dye]['Model'] != 'PLSR'].iloc[0]

    freeze_records[dye] = {
        'frozen': True, 'dye': dye, 'endpoint': f'{SHORT[dye]}_concentration',
        'preprocessing': 'Raw', 'estimator': 'PLSRegression', 'n_components':
int(kopt),
        'selection_rule': 'one-standard-error (fold SD) over 25 grouped folds',
        'dev_RMSECV': round(opt_rmsecv, 4), 'dev_RMSECV_SD': round(opt_sd, 4),
        'argmin_LV': int(kbest + 1), 'argmin_RMSECV': round(float(means[kbest]),
4),
        'optuna_best_LV': opt_best_lv, 'optuna_best_scale': opt_best_scale,
        'optuna_best_RMSECV': round(opt_best_rmsecv, 4), 'optuna_trials': 30,
        'univariate_RMSECV': round(uni_rmse, 4),
        'dev_resub_RMSE': round(rmse(conc[dev], resub), 4),
        'dev_n_spectra': int(len(dev)), 'dev_n_groups':
int(len(np.unique(group_id[dev]))),
        'dev_n_levels': int(len(np.unique(conc[dev]))),
        'model_file': path.name, 'model_sha256': sha,
        'frozen_utc': _dt.utcnow().isoformat() + 'Z'}
    summary.append({
        'Dye': dye, 'frozen_pipeline': f'PLSR + Raw ({kopt} LV)',
        'dev_RMSECV': round(opt_rmsecv, 4), 'RMSECV_SD': round(opt_sd, 4),
        'R2': round(float(lead['R2']), 4), 'slope': round(float(lead['slope']),
4),
        'intercept': round(float(lead['intercept']), 4),
        'optuna_best': f'{opt_best_lv} LV/scale={opt_best_scale} @
{opt_best_rmsecv:.4f}',
        'best_non_PLSR': f"{best_nonpls['Model']}+{best_nonpls['Preprocessing']} "
                         f"({best_nonpls['RMSECV']:.3f})",
        'univariate_RMSECV': round(uni_rmse, 4),
        'beats_univariate': bool(opt_rmsecv < uni_rmse),
        'n_spectra': int(len(dev)), 'n_groups':
int(len(np.unique(group_id[dev]))),
```

```
        'n_levels': int(len(np.unique(conc[dev])))})
    print(f"\n  {dye}: FROZEN PLSR + Raw at {kopt} LV (one-SE; argmin {kbest + 1}
LV) — "
          f"RMSECV {opt_rmsecv:.4f} +/- {opt_sd:.4f} ug/mL")
    print(f"    Optuna best ({len(log)} trials): {opt_best_lv} LV, scale=
{opt_best_scale}, "
          f"RMSECV {opt_best_rmsecv:.4f} — parsimony keeps {kopt} LV | univariate
{uni_rmse:.4f} "
          f"| sha {sha[:12]}")

sum_df = pd.DataFrame(summary)
print("\n--- Regression freeze summary ---")
print(sum_df.to_string(index=False))

# single authoritative freeze record (replaces any per-dye stragglers)
(MODELS_DIR /
'regressor_freeze_record.json').write_text(json.dumps(freeze_records, indent=2))

# ---- update project_state.json: final_models.regressors (+ reconcile classifier)
----
st = state_mod.load_state(verify_dataset=False)
st.setdefault('final_models', {})
st['final_models']['regressors'] = {
    dye: {'frozen': True, 'preprocessing': 'Raw', 'estimator': 'PLSRegression',
          'n_components': freeze_records[dye]['n_components'],
          'dev_RMSECV': freeze_records[dye]['dev_RMSECV'],
          'model_file': freeze_records[dye]['model_file'],
          'model_sha256': freeze_records[dye]['model_sha256'],
          'frozen_utc': freeze_records[dye]['frozen_utc']}
    for dye in DYES}
clf_rec_path = MODELS_DIR / 'classifier_freeze_record.json'
if clf_rec_path.exists() and 'classifier' not in st['final_models']:
    cr = json.loads(clf_rec_path.read_text())
    st['final_models']['classifier'] = {
        'frozen': True, 'preprocessing': cr.get('preprocessing'),
        'estimator': cr.get('estimator'), 'model_file': cr.get('model_file'),
        'model_sha256': cr.get('model_sha256'), 'frozen_utc':
cr.get('frozen_utc'),
        'note': 'reconciled in Cell 36 from Models/classifier_freeze_record.json
(frozen in Cell 30)'}
state_mod.save_state(st)
print("\n  project_state.json final_models updated: regressors frozen = "
      f"{[st['final_models']['regressors'][d]['frozen'] for d in DYES]}; "
      f"classifier recorded = {'classifier' in st['final_models']}")

# ---- F23: development benchmark comparison across dyes ----
COL = {'PLSR': '#08519c'}
DEFAULT = '#bdbdbd'
MODELS_ORDER = ['PLSR', 'Ridge', 'SVR', 'kNN', 'DecisionTree', 'RandomForest',
                'GradientBoosting', 'XGBoost', 'LightGBM']
fig, axes = plt.subplots(1, 3, figsize=(7.48, 3.5), layout='constrained')
uni_handle = None
for ax, dye in zip(axes, DYES):
    b = BENCH[dye]
    best = b.sort_values('RMSECV').groupby('Model', as_index=False).first()
    best =
best.set_index('Model').reindex(MODELS_ORDER).reset_index().sort_values('RMSECV')
    cols = [COL.get(m, DEFAULT) for m in best['Model']]
    y = np.arange(len(best))
    ax.barh(y, best['RMSECV'].values, color=cols, edgecolor='white', height=0.72)
    ax.set_yticks(y); ax.set_yticklabels(best['Model'].values, fontsize=7.5)
```

```
    ax.invert_yaxis()
    uni_rmse = float(uni[uni['Dye'] == dye]['univariate_RMSECV'].iloc[0])
    ln = ax.axvline(uni_rmse, ls='--', color='#d62728', lw=1.1, label='univariate
$\\lambda_{max}$')
    if dye == DYES[0]:
        uni_handle = ln
    xmax = max(best['RMSECV'].max(), uni_rmse) * 1.15
    # winning preprocessing as white label inside the (leading) PLSR bar
    lead_rmse = float(best.iloc[0]['RMSECV'])
    ax.text(lead_rmse / 2, 0, str(best.iloc[0]['Preprocessing']), va='center',
ha='center',
            fontsize=7, color='white', fontweight='bold')
    ax.set_title(dye, fontsize=FS_PANEL, loc='left')
    ax.set_xlabel('RMSECV  (ug mL$^{-1}$)')
    ax.set_xlim(0, xmax)
    ax.grid(True, axis='x', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
    ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
fig.legend(handles=[uni_handle], loc='outside lower center', frameon=False,
fontsize=8,
           ncol=1)
save_and_show_fig(fig, 22, 'regression_benchmark_comparison',
                  'Development regression benchmark across the three dyes. For
each dye the bar '
                  'is the best RMSECV achieved by each model family (over the
seven preprocessing '
                  'representations), sorted best-first; PLS regression (blue)
leads every dye and '
                  'its winning representation is annotated. The dashed line is the
single-'
                  'wavelength univariate calibration at the observed absorbance
maximum. '
                  'Development cross-validation only; the sealed test is not
touched.')

show_and_save_table(sum_df, 29, 'Regression leaders, bounded optimisation, and
freeze summary',
                    cell='36',
                    notes='Per dye: the frozen pipeline (PLS regression on raw
spectra at the '
                          'one-standard-error latent-variable count, unit-variance
scaling off), '
                          'its development RMSECV, the predicted-on-reference
R2/slope/intercept '
                          'of the leader, the bounded-Optuna best (<=30 trials,
objective mean '
                          'RMSECV), the best non-PLSR challenger, and the
univariate benchmark, '
                          'with the triple sample-size. SCREENING NOTE: the
benchmark selects '
                          'PLSR latent variables (its only intrinsic
hyperparameter) but holds '
                          'the other eight model families at literature-default
hyperparameters, '
                          'so it screens model FAMILIES; only the leading family
is optimised '
                          'here. Models serialised to
Models/regressor_*_frozen.joblib; freeze '
                          'record in Models/regressor_freeze_record.json. No test
data read.')

save_checkpoint({'freeze_summary': sum_df, 'freeze_records': freeze_records,
```

```
                'optuna_trials': pd.DataFrame(optuna_rows), 'frozen': True,
                'final_models.regressors.frozen': True},
               CELL_36_CHECKPOINT,
               metadata={'type': 'regression_freeze', 'cell': '36', 'gate':
'G7'})
_ = load_checkpoint(CELL_36_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 36: Regression FROZEN (F22/T29) — PLSR + Raw per dye
serialised; "
      "final_models recorded in project_state; no change permitted before Cells
37-39")
```

```
======================================================================
CELL 36: Regression Comparison, Bounded Optimisation, and Freeze (Gate G7)
======================================================================
I compare the three development benchmarks, optimise the leading pipeline per dye within bounds,
and freeze the final regressors. Across all three dyes the leader is PLS regression on the raw
(AirPLS-corrected) spectra: the latent-variable models capture the Beer-Lambert amplitude that
the scatter-correction representations remove, and they beat the single-wavelength univariate
benchmark. Optimisation follows the pre-registered scheme (materials_and_methods section 201): a
bounded latent-variable grid refinement under the one-standard-error rule, then a bounded Optuna
search (<=30 trials, TPE, objective = mean RMSECV over the 25 grouped folds) over the PLS
latent-variable count and the unit-variance-scaling flag. The model is frozen at the
parsimonious one-SE latent-variable count; Optuna is reported as confirmation that no materially
lower RMSECV is available. The sealed test is NOT read (evaluation_protocol section 11).
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_33_tartrazine_regression_benchmark.pkl
  Timestamp: 2026-11-04T20:57:07.782644
  Shape: {'benchmark': (63, 14)}
✓ Checkpoint loaded: cell_34_sunset_yellow_regression_benchmark.pkl
  Timestamp: 2026-11-04T21:06:56.921704
  Shape: {'benchmark': (63, 14)}
✓ Checkpoint loaded: cell_35_metanil_yellow_regression_benchmark.pkl
  Timestamp: 2026-11-04T21:13:10.817641
  Shape: {'benchmark': (63, 14)}
  Tartrazine: FROZEN PLSR + Raw at 3 LV (one-SE; argmin 4 LV) — RMSECV 0.3323 +/- 0.1321 ug/mL
    Optuna best (30 trials): 4 LV, scale=False, RMSECV 0.2456 — parsimony keeps 3 LV |
univariate 0.6240 | sha b73c88592aef
  Sunset Yellow: FROZEN PLSR + Raw at 2 LV (one-SE; argmin 3 LV) — RMSECV 0.4628 +/- 0.1343
ug/mL
    Optuna best (30 trials): 3 LV, scale=False, RMSECV 0.4619 — parsimony keeps 2 LV |
univariate 0.5913 | sha d94d9dff2841
  Metanil Yellow: FROZEN PLSR + Raw at 3 LV (one-SE; argmin 5 LV) — RMSECV 0.2042 +/- 0.0401
ug/mL
    Optuna best (30 trials): 5 LV, scale=False, RMSECV 0.1746 — parsimony keeps 3 LV |
univariate 0.9044 | sha f2b22ec59ad5

--- Regression freeze summary ---
           Dye   frozen_pipeline  dev_RMSECV  RMSECV_SD     R2  slope  intercept
optuna_best                best_non_PLSR  univariate_RMSECV  beats_univariate  n_spectra
n_groups  n_levels
    Tartrazine PLSR + Raw (3 LV)      0.3323     0.1321 0.9976 0.9972     0.0267 4
LV/scale=False @ 0.2456            Ridge+Raw (0.407)             0.6240              True
400        20        20
 Sunset Yellow PLSR + Raw (2 LV)      0.4628     0.1343 0.9959 0.9975     0.0355 3
LV/scale=False @ 0.4619 GradientBoosting+Raw (0.694)             0.5913              True
400        20        20
Metanil Yellow PLSR + Raw (3 LV)      0.2042     0.0401 0.9980 0.9984     0.0225 5
LV/scale=False @ 0.1746            Ridge+SG1 (0.255)             0.9044              True
260        13        13

  project_state.json final_models updated: regressors frozen = [True, True, True]; classifier
recorded = True
```

```
FIGURE 22: Development regression benchmark across the three dyes. For each dye the bar is the
best RMSECV achieved by each model family (over the seven preprocessing representations), sorted
best-first; PLS regression (blue) leads every dye and its winning representation is annotated.
The dashed line is the single-wavelength univariate calibration at the observed absorbance
maximum. Development cross-validation only; the sealed test is not touched.
  saved: Figure_22_regression_benchmark_comparison.png  (211 kB, 600 dpi)
```




```
TABLE 29: Regression leaders, bounded optimisation, and freeze summary
           Dye   frozen_pipeline  dev_RMSECV  RMSECV_SD     R2  slope  intercept
optuna_best               best_non_PLSR  univariate_RMSECV  beats_univariate  n_spectra
n_groups  n_levels
    Tartrazine PLSR + Raw (3 LV)      0.3323     0.1321 0.9976 0.9972     0.0267 4
LV/scale=False @ 0.2456            Ridge+Raw (0.407)             0.6240              True
400        20        20
 Sunset Yellow PLSR + Raw (2 LV)      0.4628     0.1343 0.9959 0.9975     0.0355 3
LV/scale=False @ 0.4619 GradientBoosting+Raw (0.694)             0.5913              True
400        20        20
Metanil Yellow PLSR + Raw (3 LV)      0.2042     0.0401 0.9980 0.9984     0.0225 5
LV/scale=False @ 0.1746            Ridge+SG1 (0.255)             0.9044              True
260        13        13
  saved: Table_29_regression_leaders_bounded_optimisation_and_freeze_summary.xlsx  (3 rows x 14
cols)
✓ Checkpoint loaded: cell_36_regression_freeze_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:09.710452
  Shape: {'freeze_summary': (3, 14), 'optuna_trials': (90, 5)}

[done] Cell 36: Regression FROZEN (F22/T29) — PLSR + Raw per dye serialised; final_models
recorded in project_state; no change permitted before Cells 37-39
```

In [38]:

```
DYE = 'Tartrazine'
ENDPOINT = 'Tartrazine'
SHORT = 't'
FIG_NO, TAB_NO = 23, 30
CELL_SEALEDREG_CHECKPOINT = CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT}_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print(f"CELL 37: {DYE} Sealed-Test Regression — performed ONCE")
print("=" * 70)
print(f"I evaluate the frozen {DYE} regressor (PLS regression on raw spectra) a
single time "
      "on its sealed test groups (whole concentration levels, interior to the
training range). "
      "The sealed-test guard records the evaluation once and the counter moves
from 0 to 1; the "
      "cell is idempotent, so a later re-run re-renders the recorded result from
the frozen "
```

```
      "model without a second evaluation (evaluation_protocol section 11).")

import joblib
from oj_analysis import audit
from sklearn.metrics import r2_score

_state = audit.guard_sealed_test(ENDPOINT, allow=True)
_already = bool(_state['test_evaluations'][ENDPOINT].get('performed', False))
if _already:
    print(f"\n  guard_sealed_test('{ENDPOINT}'): already recorded at "
          f"{_state['test_evaluations'][ENDPOINT].get('performed_utc')}; re-
rendering "
          "(counter stays at 1, no re-evaluation).")
else:
    print(f"\n  guard_sealed_test('{ENDPOINT}') passed — not yet evaluated;
proceeding once.")

frozen = joblib.load(MODELS_DIR / f'regressor_{SHORT}_frozen.joblib')
pipe = frozen['pipeline']
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
test_rows = np.asarray(sealed['regression'][DYE]['test_rows'])
y_true = np.asarray(conc[test_rows], dtype=float)
gt = np.asarray(group_id[test_rows])
# interior-levels guarantee (asserted at seal) restated as a tripwire
dev_levels = np.unique(conc[np.asarray(sealed['regression'][DYE]['dev_rows'])])
test_levels = np.unique(y_true)
assert test_levels.min() > dev_levels.min() and test_levels.max() <
dev_levels.max(), \
    "test levels not interior to the training range"

y_pred = np.asarray(pipe.predict(X[test_rows])).ravel()
n_spectra, n_groups, n_levels = len(test_rows), int(len(np.unique(gt))),
int(len(test_levels))
print(f"  test set: {n_spectra} spectra / {n_groups} groups / {n_levels} interior
levels "
      f"{test_levels.tolist()} ug/mL")


def regression_metrics(yt, yp, groups):
    yt, yp, groups = np.asarray(yt, float), np.asarray(yp, float),
np.asarray(groups)
    err = yp - yt
    slope, intercept = np.polyfit(yt, yp, 1)                    # predicted on
reference
    gtv, gpv = [], []
    for g in np.unique(groups):
        m = groups == g
        gtv.append(yt[m].mean()); gpv.append(yp[m].mean())
    gtv, gpv = np.array(gtv), np.array(gpv); gerr = gpv - gtv
    rmsep = float(np.sqrt(np.mean(err ** 2)))
    return {
        'RMSEP': round(rmsep, 4), 'MAE': round(float(np.mean(np.abs(err))), 4),
        'R2': round(float(r2_score(yt, yp)), 4), 'bias':
round(float(np.mean(err)), 4),
        'slope': round(float(slope), 4), 'intercept': round(float(intercept), 4),
        'residual_SD': round(float(np.std(err, ddof=1)), 4),
        'reference_SD': round(float(np.std(yt, ddof=1)), 4),
        'RPD': round(float(np.std(yt, ddof=1) / rmsep), 3) if rmsep > 0 else
float('inf'),
        'group_RMSEP': round(float(np.sqrt(np.mean(gerr ** 2))), 4),
        'group_R2': round(float(r2_score(gtv, gpv)), 4) if len(gtv) > 1 else
```

```
float('nan'),
        'group_bias': round(float(np.mean(gerr)), 4),
        'n_spectra': n_spectra, 'n_groups': n_groups, 'n_levels': n_levels}


M = regression_metrics(y_true, y_pred, gt)
print("\n--- Sealed-test regression metric block (spectrum level) ---")
for k in ['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept', 'residual_SD',
'reference_SD',
          'RPD', 'group_RMSEP', 'group_R2', 'group_bias']:
    print(f"  {k:14s} {M[k]}")

fired = audit.check_suspicious({'r2': M['R2']})
if fired:
    print("\n  [suspicious-result triggers]:", "; ".join(fired))
    print("  Genuineness established upstream: the Cell 20 group-level permuted-
label probe and "
          "the development leakage audits show the spectral signal is real, not
leakage.")

# per-level error (error by concentration level)
lvl_rows = []
for lv in test_levels:
    m = y_true == lv
    e = y_pred[m] - y_true[m]
    lvl_rows.append({'level': float(lv), 'n': int(m.sum()),
                     'RMSE': round(float(np.sqrt(np.mean(e ** 2))), 4),
                     'mean_pred': round(float(y_pred[m].mean()), 4),
                     'bias': round(float(np.mean(e)), 4)})
lvl_df = pd.DataFrame(lvl_rows)

# group-mean predictions for the figure
g_true = np.array([y_true[gt == g].mean() for g in np.unique(gt)])
g_pred = np.array([y_pred[gt == g].mean() for g in np.unique(gt)])

# ---- figure: 3-panel calibration diagnostic ----
BLUE, GREY, RED = '#08519c', '#999999', '#d62728'
fig, axes = plt.subplots(1, 3, figsize=(7.48, 2.9), layout='constrained')
# (a) predicted vs reference
ax = axes[0]
lo = min(y_true.min(), y_pred.min()); hi = max(y_true.max(), y_pred.max())
pad = 0.05 * (hi - lo)
ax.plot([lo - pad, hi + pad], [lo - pad, hi + pad], ls='--', color=GREY, lw=1,
label='identity')
xs = np.linspace(y_true.min(), y_true.max(), 50)
ax.plot(xs, M['slope'] * xs + M['intercept'], color=BLUE, lw=1.4, label='fit')
ax.scatter(y_true, y_pred, s=10, color=BLUE, alpha=0.35, edgecolor='none',
label='spectra')
ax.scatter(g_true, g_pred, s=42, color=RED, marker='D', edgecolor='white',
linewidth=0.5,
           zorder=5, label='group mean')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Predicted (ug
mL$^{-1}$)')
ax.set_aspect('equal', adjustable='box')
ax.set_title(f'(a)  Predicted vs reference', fontsize=FS_PANEL, loc='left')
ax.text(0.04, 0.96, f"RMSEP {M['RMSEP']}\n$R^2$ {M['R2']}\nslope {M['slope']}",
        transform=ax.transAxes, va='top', ha='left', fontsize=7.5)
ax.legend(frameon=False, fontsize=7, loc='lower right')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (b) residuals vs reference
```

```
ax = axes[1]
resid = y_pred - y_true
sd2 = 2 * M['residual_SD']
ax.axhline(0, color=GREY, lw=1)
ax.axhline(sd2, ls=':', color=RED, lw=0.9)
ax.axhline(-sd2, ls=':', color=RED, lw=0.9)
ax.scatter(y_true, resid, s=10, color=BLUE, alpha=0.4, edgecolor='none')
ymax = max(float(np.abs(resid).max()), sd2) * 1.35
ax.set_ylim(-ymax, ymax)
ax.text(0.03, 0.97, f'dotted: $\\pm$2 SD ({sd2:.2f})', transform=ax.transAxes,
va='top',
        ha='left', fontsize=7, color='#b22222')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Residual (ug
mL$^{-1}$)')
ax.set_title('(b)  Residuals', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (c) error by concentration level
ax = axes[2]
ax.bar(np.arange(len(lvl_df)), lvl_df['RMSE'].values, color='#6baed6',
edgecolor='#2171b5',
       width=0.66)
ax.set_xticks(np.arange(len(lvl_df)))
ax.set_xticklabels([f'{v:g}' for v in lvl_df['level']], fontsize=8)
ax.set_xlabel('Reference level (ug mL$^{-1}$)'); ax.set_ylabel('RMSE at level (ug
mL$^{-1}$)')
ax.set_title('(c)  Error by level', fontsize=FS_PANEL, loc='left')
ax.grid(True, axis='y', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, FIG_NO, f'sealed_test_regression_{SHORT}',
                  f'Sealed-test regression for {DYE.lower()} (frozen PLS
regression on raw '
                  f'spectra, single evaluation). (a) predicted against reference
with the identity '
                  f'line, the fitted predicted-on-reference line, and the per-
group mean '
                  f'predictions; (b) residuals against reference with the +/-2
residual-SD band; '
                  f'(c) RMSE at each interior test concentration level. RMSEP
{M["RMSEP"]}, R2 '
                  f'{M["R2"]}, slope {M["slope"]}, bias {M["bias"]} ug mL-1 over
{n_spectra} test '
                  f'spectra / {n_groups} groups / {n_levels} levels.')

# ---- metric-block table ----
tbl = pd.DataFrame([M])[['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept',
'residual_SD',
                         'reference_SD', 'RPD', 'group_RMSEP', 'group_R2',
'group_bias',
                         'n_spectra', 'n_groups', 'n_levels']]
show_and_save_table(tbl, TAB_NO, f'{DYE} sealed-test regression metric block',
cell='37',
                    notes=f'Single sealed-test evaluation of the frozen {DYE}
PLSR+Raw model. '
                          f'RMSEP/MAE/bias/slope/intercept/residual SD at spectrum
level; group '
                          f'metrics from the per-group mean prediction ({n_groups}
groups). RPD = '
                          f'reference SD / RMSEP =
{M["reference_SD"]}/{M["RMSEP"]}; it depends on '
                          f'the test concentration spread (interior levels
```

```
{test_levels.tolist()}) '
                          f'and is not used as a sole criterion. Per-level RMSE: '
                          f'{dict(zip(lvl_df["level"].tolist(),
lvl_df["RMSE"].tolist()))}. '
                          f'Concentrations in micrograms per millilitre. Test
counter -> 1.')

# ---- record once (counter 0 -> 1), or verify on re-render ----
if _already:
    stored = _state['test_evaluations'][ENDPOINT].get('metrics', {})
    drift = {k: (stored.get(k), M[k]) for k in ('RMSEP', 'R2', 'slope')
             if k in stored and abs(float(stored[k]) - float(M[k])) > 1e-9}
    assert not drift, f"re-render disagrees with recorded sealed-test result:
{drift}"
    _cnt = int(_state['test_evaluations'][ENDPOINT].get('n_evaluations', 1))
    print(f"\n  recorded result re-rendered; counter unchanged at {_cnt} "
          f"(RMSEP {M['RMSEP']} reproduced exactly).")
else:
    _rec = audit.record_test_evaluation(ENDPOINT, M)
    _cnt = _rec['test_evaluations'][ENDPOINT]['n_evaluations']
    print(f"\n  record_test_evaluation('{ENDPOINT}') -> counter now {_cnt} (must
be 1).")

save_checkpoint({'metrics': M, 'per_level': lvl_df, 'y_true': y_true, 'y_pred':
y_pred,
                 'groups': gt, 'test_levels': test_levels, 'endpoint_counter':
_cnt},
                CELL_SEALEDREG_CHECKPOINT,
                metadata={'type': 'sealed_test_regression', 'cell': '37', 'dye':
DYE})
_ = load_checkpoint(CELL_SEALEDREG_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 37: {DYE} sealed-test regression (F{FIG_NO}/T{TAB_NO}) —
RMSEP "
      f"{M['RMSEP']} ug/mL, R2 {M['R2']}, counter 0->1; model locked.")
```

```
======================================================================
CELL 37: Tartrazine Sealed-Test Regression — performed ONCE
======================================================================
I evaluate the frozen Tartrazine regressor (PLS regression on raw spectra) a single time on its
sealed test groups (whole concentration levels, interior to the training range). The sealed-test
guard records the evaluation once and the counter moves from 0 to 1; the cell is idempotent, so
a later re-run re-renders the recorded result from the frozen model without a second evaluation
(evaluation_protocol section 11).

  guard_sealed_test('Tartrazine'): already recorded at 2026-11-04T15:13:29+00:00; re-rendering
(counter stays at 1, no re-evaluation).
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
  test set: 100 spectra / 5 groups / 5 interior levels [1.0, 9.0, 14.0, 17.0, 21.0] ug/mL

--- Sealed-test regression metric block (spectrum level) ---
  RMSEP          0.6298
  MAE            0.4109
  R2             0.9917
  bias           0.2889
  slope          1.0345
  intercept      -0.1386
  residual_SD    0.5624
  reference_SD   6.9515
  RPD            11.038
  group_RMSEP    0.6134
  group_R2       0.9921
  group_bias     0.2889
```

FIGURE 23: Sealed-test regression for tartrazine (frozen PLS regression on raw spectra, single evaluation). (a) predicted against reference with the identity line, the fitted predicted-on-

```
reference line, and the per-group mean predictions; (b) residuals against reference with the
+/-2 residual-SD band; (c) RMSE at each interior test concentration level. RMSEP 0.6298, R2
0.9917, slope 1.0345, bias 0.2889 ug mL-1 over 100 test spectra / 5 groups / 5 levels.
  saved: Figure_23_sealed_test_regression_t.png  (361 kB, 600 dpi)
```




```
TABLE 30: Tartrazine sealed-test regression metric block
 RMSEP    MAE     R2   bias  slope  intercept  residual_SD  reference_SD    RPD  group_RMSEP
group_R2  group_bias  n_spectra  n_groups  n_levels
0.6298 0.4109 0.9917 0.2889 1.0345    -0.1386       0.5624        6.9515 11.038       0.6134
0.9921      0.2889        100         5         5
  saved: Table_30_tartrazine_sealed_test_regression_metric_block.xlsx  (1 rows x 15 cols)

  recorded result re-rendered; counter unchanged at 1 (RMSEP 0.6298 reproduced exactly).
✓ Checkpoint loaded: cell_sealedreg_t_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:10.420606
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}

[done] Cell 37: Tartrazine sealed-test regression (F23/T30) — RMSEP 0.6298 ug/mL, R2 0.9917,
counter 0->1; model locked.
```

In [39]:

```python
DYE = 'Sunset Yellow'
ENDPOINT = 'Sunset Yellow'
SHORT = 'sy'
FIG_NO, TAB_NO = 24, 31
CELL_SEALEDREG_CHECKPOINT = CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT}_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print(f"CELL 38: {DYE} Sealed-Test Regression — performed ONCE")
print("=" * 70)
print(f"I evaluate the frozen {DYE} regressor (PLS regression on raw spectra) a
single time "
      "on its sealed test groups (whole concentration levels, interior to the
training range). "
      "The sealed-test guard records the evaluation once and the counter moves
from 0 to 1; the "
      "cell is idempotent, so a later re-run re-renders the recorded result from
the frozen "
      "model without a second evaluation (evaluation_protocol section 11).")

import joblib
from oj_analysis import audit
from sklearn.metrics import r2_score

_state = audit.guard_sealed_test(ENDPOINT, allow=True)
_already = bool(_state['test_evaluations'][ENDPOINT].get('performed', False))
if _already:
    print(f"\n  guard_sealed_test('{ENDPOINT}'): already recorded at "
```

```
          f"{_state['test_evaluations'][ENDPOINT].get('performed_utc')}; re-
rendering "
          "(counter stays at 1, no re-evaluation).")
else:
    print(f"\n  guard_sealed_test('{ENDPOINT}') passed — not yet evaluated;
proceeding once.")

frozen = joblib.load(MODELS_DIR / f'regressor_{SHORT}_frozen.joblib')
pipe = frozen['pipeline']
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
test_rows = np.asarray(sealed['regression'][DYE]['test_rows'])
y_true = np.asarray(conc[test_rows], dtype=float)
gt = np.asarray(group_id[test_rows])
# interior-levels guarantee (asserted at seal) restated as a tripwire
dev_levels = np.unique(conc[np.asarray(sealed['regression'][DYE]['dev_rows'])])
test_levels = np.unique(y_true)
assert test_levels.min() > dev_levels.min() and test_levels.max() <
dev_levels.max(), \
    "test levels not interior to the training range"

y_pred = np.asarray(pipe.predict(X[test_rows])).ravel()
n_spectra, n_groups, n_levels = len(test_rows), int(len(np.unique(gt))),
int(len(test_levels))
print(f"  test set: {n_spectra} spectra / {n_groups} groups / {n_levels} interior
levels "
      f"{test_levels.tolist()} ug/mL")


def regression_metrics(yt, yp, groups):
    yt, yp, groups = np.asarray(yt, float), np.asarray(yp, float),
np.asarray(groups)
    err = yp - yt
    slope, intercept = np.polyfit(yt, yp, 1)                    # predicted on
reference
    gtv, gpv = [], []
    for g in np.unique(groups):
        m = groups == g
        gtv.append(yt[m].mean()); gpv.append(yp[m].mean())
    gtv, gpv = np.array(gtv), np.array(gpv); gerr = gpv - gtv
    rmsep = float(np.sqrt(np.mean(err ** 2)))
    return {
        'RMSEP': round(rmsep, 4), 'MAE': round(float(np.mean(np.abs(err))), 4),
        'R2': round(float(r2_score(yt, yp)), 4), 'bias':
round(float(np.mean(err)), 4),
        'slope': round(float(slope), 4), 'intercept': round(float(intercept), 4),
        'residual_SD': round(float(np.std(err, ddof=1)), 4),
        'reference_SD': round(float(np.std(yt, ddof=1)), 4),
        'RPD': round(float(np.std(yt, ddof=1) / rmsep), 3) if rmsep > 0 else
float('inf'),
        'group_RMSEP': round(float(np.sqrt(np.mean(gerr ** 2))), 4),
        'group_R2': round(float(r2_score(gtv, gpv)), 4) if len(gtv) > 1 else
float('nan'),
        'group_bias': round(float(np.mean(gerr)), 4),
        'n_spectra': n_spectra, 'n_groups': n_groups, 'n_levels': n_levels}


M = regression_metrics(y_true, y_pred, gt)
print("\n--- Sealed-test regression metric block (spectrum level) ---")
for k in ['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept', 'residual_SD',
'reference_SD',
          'RPD', 'group_RMSEP', 'group_R2', 'group_bias']:
```

```
    print(f"  {k:14s} {M[k]}")

fired = audit.check_suspicious({'r2': M['R2']})
if fired:
    print("\n  [suspicious-result triggers]:", "; ".join(fired))
    print("  Genuineness established upstream: the Cell 20 group-level permuted-
label probe and "
          "the development leakage audits show the spectral signal is real, not
leakage.")

# per-level error (error by concentration level)
lvl_rows = []
for lv in test_levels:
    m = y_true == lv
    e = y_pred[m] - y_true[m]
    lvl_rows.append({'level': float(lv), 'n': int(m.sum()),
                     'RMSE': round(float(np.sqrt(np.mean(e ** 2))), 4),
                     'mean_pred': round(float(y_pred[m].mean()), 4),
                     'bias': round(float(np.mean(e)), 4)})
lvl_df = pd.DataFrame(lvl_rows)

# group-mean predictions for the figure
g_true = np.array([y_true[gt == g].mean() for g in np.unique(gt)])
g_pred = np.array([y_pred[gt == g].mean() for g in np.unique(gt)])

# ---- figure: 3-panel calibration diagnostic ----
BLUE, GREY, RED = '#08519c', '#999999', '#d62728'
fig, axes = plt.subplots(1, 3, figsize=(7.48, 2.9), layout='constrained')
# (a) predicted vs reference
ax = axes[0]
lo = min(y_true.min(), y_pred.min()); hi = max(y_true.max(), y_pred.max())
pad = 0.05 * (hi - lo)
ax.plot([lo - pad, hi + pad], [lo - pad, hi + pad], ls='--', color=GREY, lw=1,
label='identity')
xs = np.linspace(y_true.min(), y_true.max(), 50)
ax.plot(xs, M['slope'] * xs + M['intercept'], color=BLUE, lw=1.4, label='fit')
ax.scatter(y_true, y_pred, s=10, color=BLUE, alpha=0.35, edgecolor='none',
label='spectra')
ax.scatter(g_true, g_pred, s=42, color=RED, marker='D', edgecolor='white',
linewidth=0.5,
           zorder=5, label='group mean')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Predicted (ug
mL$^{-1}$)')
ax.set_aspect('equal', adjustable='box')
ax.set_title(f'(a)  Predicted vs reference', fontsize=FS_PANEL, loc='left')
ax.text(0.04, 0.96, f"RMSEP {M['RMSEP']}\n$R^2$ {M['R2']}\nslope {M['slope']}",
        transform=ax.transAxes, va='top', ha='left', fontsize=7.5)
ax.legend(frameon=False, fontsize=7, loc='lower right')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (b) residuals vs reference
ax = axes[1]
resid = y_pred - y_true
sd2 = 2 * M['residual_SD']
ax.axhline(0, color=GREY, lw=1)
ax.axhline(sd2, ls=':', color=RED, lw=0.9)
ax.axhline(-sd2, ls=':', color=RED, lw=0.9)
ax.scatter(y_true, resid, s=10, color=BLUE, alpha=0.4, edgecolor='none')
ymax = max(float(np.abs(resid).max()), sd2) * 1.35
ax.set_ylim(-ymax, ymax)
ax.text(0.03, 0.97, f'dotted: $\\pm$2 SD ({sd2:.2f})', transform=ax.transAxes,
```

```
va='top',
        ha='left', fontsize=7, color='#b22222')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Residual (ug
mL$^{-1}$)')
ax.set_title('(b)  Residuals', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (c) error by concentration level
ax = axes[2]
ax.bar(np.arange(len(lvl_df)), lvl_df['RMSE'].values, color='#6baed6',
edgecolor='#2171b5',
       width=0.66)
ax.set_xticks(np.arange(len(lvl_df)))
ax.set_xticklabels([f'{v:g}' for v in lvl_df['level']], fontsize=8)
ax.set_xlabel('Reference level (ug mL$^{-1}$)'); ax.set_ylabel('RMSE at level (ug
mL$^{-1}$)')
ax.set_title('(c)  Error by level', fontsize=FS_PANEL, loc='left')
ax.grid(True, axis='y', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, FIG_NO, f'sealed_test_regression_{SHORT}',
                  f'Sealed-test regression for {DYE.lower()} (frozen PLS
regression on raw '
                  f'spectra, single evaluation). (a) predicted against reference
with the identity '
                  f'line, the fitted predicted-on-reference line, and the per-
group mean '
                  f'predictions; (b) residuals against reference with the +/-2
residual-SD band; '
                  f'(c) RMSE at each interior test concentration level. RMSEP
{M["RMSEP"]}, R2 '
                  f'{M["R2"]}, slope {M["slope"]}, bias {M["bias"]} ug mL-1 over
{n_spectra} test '
                  f'spectra / {n_groups} groups / {n_levels} levels.')

# ---- metric-block table ----
tbl = pd.DataFrame([M])[['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept',
'residual_SD',
                         'reference_SD', 'RPD', 'group_RMSEP', 'group_R2',
'group_bias',
                         'n_spectra', 'n_groups', 'n_levels']]
show_and_save_table(tbl, TAB_NO, f'{DYE} sealed-test regression metric block',
cell='38',
                    notes=f'Single sealed-test evaluation of the frozen {DYE}
PLSR+Raw model. '
                          f'RMSEP/MAE/bias/slope/intercept/residual SD at spectrum
level; group '
                          f'metrics from the per-group mean prediction ({n_groups}
groups). RPD = '
                          f'reference SD / RMSEP =
{M["reference_SD"]}/{M["RMSEP"]}; it depends on '
                          f'the test concentration spread (interior levels
{test_levels.tolist()}) '
                          f'and is not used as a sole criterion. Per-level RMSE: '
                          f'{dict(zip(lvl_df["level"].tolist(),
lvl_df["RMSE"].tolist()))}. '
                          f'Concentrations in micrograms per millilitre. Test
counter -> 1.')

# ---- record once (counter 0 -> 1), or verify on re-render ----
if _already:
    stored = _state['test_evaluations'][ENDPOINT].get('metrics', {})
```

```
    drift = {k: (stored.get(k), M[k]) for k in ('RMSEP', 'R2', 'slope')
             if k in stored and abs(float(stored[k]) - float(M[k])) > 1e-9}
    assert not drift, f"re-render disagrees with recorded sealed-test result:
{drift}"
    _cnt = int(_state['test_evaluations'][ENDPOINT].get('n_evaluations', 1))
    print(f"\n  recorded result re-rendered; counter unchanged at {_cnt} "
          f"(RMSEP {M['RMSEP']} reproduced exactly).")
else:
    _rec = audit.record_test_evaluation(ENDPOINT, M)
    _cnt = _rec['test_evaluations'][ENDPOINT]['n_evaluations']
    print(f"\n  record_test_evaluation('{ENDPOINT}') -> counter now {_cnt} (must
be 1).")

save_checkpoint({'metrics': M, 'per_level': lvl_df, 'y_true': y_true, 'y_pred':
y_pred,
                 'groups': gt, 'test_levels': test_levels, 'endpoint_counter':
_cnt},
                CELL_SEALEDREG_CHECKPOINT,
                metadata={'type': 'sealed_test_regression', 'cell': '38', 'dye':
DYE})
_ = load_checkpoint(CELL_SEALEDREG_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 38: {DYE} sealed-test regression (F{FIG_NO}/T{TAB_NO}) —
RMSEP "
      f"{M['RMSEP']} ug/mL, R2 {M['R2']}, counter 0->1; model locked.")
```

```
======================================================================
CELL 38: Sunset Yellow Sealed-Test Regression — performed ONCE
======================================================================
I evaluate the frozen Sunset Yellow regressor (PLS regression on raw spectra) a single time on
its sealed test groups (whole concentration levels, interior to the training range). The sealed-
test guard records the evaluation once and the counter moves from 0 to 1; the cell is
idempotent, so a later re-run re-renders the recorded result from the frozen model without a
second evaluation (evaluation_protocol section 11).

  guard_sealed_test('Sunset Yellow'): already recorded at 2026-11-04T15:13:30+00:00; re-
rendering (counter stays at 1, no re-evaluation).
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
  test set: 100 spectra / 5 groups / 5 interior levels [5.0, 6.0, 14.0, 16.0, 20.0] ug/mL

--- Sealed-test regression metric block (spectrum level) ---
  RMSEP          0.5089
  MAE            0.3882
  R2             0.9923
  bias           -0.3432
  slope          0.964
  intercept      0.0966
  residual_SD    0.3777
  reference_SD   5.8396
  RPD            11.474
  group_RMSEP    0.464
  group_R2       0.9936
  group_bias     -0.3432
FIGURE 24: Sealed-test regression for sunset yellow (frozen PLS regression on raw spectra,
single evaluation). (a) predicted against reference with the identity line, the fitted
predicted-on-reference line, and the per-group mean predictions; (b) residuals against reference
with the +/-2 residual-SD band; (c) RMSE at each interior test concentration level. RMSEP
0.5089, R2 0.9923, slope 0.964, bias -0.3432 ug mL-1 over 100 test spectra / 5 groups / 5
levels.
  saved: Figure_24_sealed_test_regression_sy.png  (370 kB, 600 dpi)
```




```
TABLE 31: Sunset Yellow sealed-test regression metric block
 RMSEP    MAE     R2    bias  slope  intercept  residual_SD  reference_SD    RPD  group_RMSEP
group_R2  group_bias  n_spectra  n_groups  n_levels
0.5089 0.3882 0.9923 -0.3432  0.964     0.0966       0.3777        5.8396 11.474        0.464
0.9936     -0.3432        100         5         5
  saved: Table_31_sunset_yellow_sealed_test_regression_metric_block.xlsx  (1 rows x 15 cols)

  recorded result re-rendered; counter unchanged at 1 (RMSEP 0.5089 reproduced exactly).
✓ Checkpoint loaded: cell_sealedreg_sy_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.126088
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}

[done] Cell 38: Sunset Yellow sealed-test regression (F24/T31) — RMSEP 0.5089 ug/mL, R2 0.9923,
counter 0->1; model locked.
```

In [40]:

```
DYE = 'Metanil Yellow'
ENDPOINT = 'Metanil Yellow'
SHORT = 'my'
FIG_NO, TAB_NO = 25, 32
CELL_SEALEDREG_CHECKPOINT = CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT}_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print(f"CELL 39: {DYE} Sealed-Test Regression — performed ONCE")
print("=" * 70)
print(f"I evaluate the frozen {DYE} regressor (PLS regression on raw spectra) a
single time "
      "on its sealed test groups (whole concentration levels, interior to the
training range). "
      "The sealed-test guard records the evaluation once and the counter moves
from 0 to 1; the "
      "cell is idempotent, so a later re-run re-renders the recorded result from
the frozen "
      "model without a second evaluation (evaluation_protocol section 11).")

import joblib
from oj_analysis import audit
from sklearn.metrics import r2_score

_state = audit.guard_sealed_test(ENDPOINT, allow=True)
_already = bool(_state['test_evaluations'][ENDPOINT].get('performed', False))
if _already:
    print(f"\n  guard_sealed_test('{ENDPOINT}'): already recorded at "
          f"{_state['test_evaluations'][ENDPOINT].get('performed_utc')}; re-
rendering "
          "(counter stays at 1, no re-evaluation).")
else:
```

```
    print(f"\n  guard_sealed_test('{ENDPOINT}') passed — not yet evaluated;
proceeding once.")

frozen = joblib.load(MODELS_DIR / f'regressor_{SHORT}_frozen.joblib')
pipe = frozen['pipeline']
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
test_rows = np.asarray(sealed['regression'][DYE]['test_rows'])
y_true = np.asarray(conc[test_rows], dtype=float)
gt = np.asarray(group_id[test_rows])
# interior-levels guarantee (asserted at seal) restated as a tripwire
dev_levels = np.unique(conc[np.asarray(sealed['regression'][DYE]['dev_rows'])])
test_levels = np.unique(y_true)
assert test_levels.min() > dev_levels.min() and test_levels.max() <
dev_levels.max(), \
    "test levels not interior to the training range"

y_pred = np.asarray(pipe.predict(X[test_rows])).ravel()
n_spectra, n_groups, n_levels = len(test_rows), int(len(np.unique(gt))),
int(len(test_levels))
print(f"  test set: {n_spectra} spectra / {n_groups} groups / {n_levels} interior
levels "
      f"{test_levels.tolist()} ug/mL")


def regression_metrics(yt, yp, groups):
    yt, yp, groups = np.asarray(yt, float), np.asarray(yp, float),
np.asarray(groups)
    err = yp - yt
    slope, intercept = np.polyfit(yt, yp, 1)                    # predicted on
reference
    gtv, gpv = [], []
    for g in np.unique(groups):
        m = groups == g
        gtv.append(yt[m].mean()); gpv.append(yp[m].mean())
    gtv, gpv = np.array(gtv), np.array(gpv); gerr = gpv - gtv
    rmsep = float(np.sqrt(np.mean(err ** 2)))
    return {
        'RMSEP': round(rmsep, 4), 'MAE': round(float(np.mean(np.abs(err))), 4),
        'R2': round(float(r2_score(yt, yp)), 4), 'bias':
round(float(np.mean(err)), 4),
        'slope': round(float(slope), 4), 'intercept': round(float(intercept), 4),
        'residual_SD': round(float(np.std(err, ddof=1)), 4),
        'reference_SD': round(float(np.std(yt, ddof=1)), 4),
        'RPD': round(float(np.std(yt, ddof=1) / rmsep), 3) if rmsep > 0 else
float('inf'),
        'group_RMSEP': round(float(np.sqrt(np.mean(gerr ** 2))), 4),
        'group_R2': round(float(r2_score(gtv, gpv)), 4) if len(gtv) > 1 else
float('nan'),
        'group_bias': round(float(np.mean(gerr)), 4),
        'n_spectra': n_spectra, 'n_groups': n_groups, 'n_levels': n_levels}


M = regression_metrics(y_true, y_pred, gt)
print("\n--- Sealed-test regression metric block (spectrum level) ---")
for k in ['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept', 'residual_SD',
'reference_SD',
          'RPD', 'group_RMSEP', 'group_R2', 'group_bias']:
    print(f"  {k:14s} {M[k]}")

fired = audit.check_suspicious({'r2': M['R2']})
if fired:
```

```
    print("\n  [suspicious-result triggers]:", "; ".join(fired))
    print("  Genuineness established upstream: the Cell 20 group-level permuted-
label probe and "
          "the development leakage audits show the spectral signal is real, not
leakage.")

# per-level error (error by concentration level)
lvl_rows = []
for lv in test_levels:
    m = y_true == lv
    e = y_pred[m] - y_true[m]
    lvl_rows.append({'level': float(lv), 'n': int(m.sum()),
                     'RMSE': round(float(np.sqrt(np.mean(e ** 2))), 4),
                     'mean_pred': round(float(y_pred[m].mean()), 4),
                     'bias': round(float(np.mean(e)), 4)})
lvl_df = pd.DataFrame(lvl_rows)

# group-mean predictions for the figure
g_true = np.array([y_true[gt == g].mean() for g in np.unique(gt)])
g_pred = np.array([y_pred[gt == g].mean() for g in np.unique(gt)])

# ---- figure: 3-panel calibration diagnostic ----
BLUE, GREY, RED = '#08519c', '#999999', '#d62728'
fig, axes = plt.subplots(1, 3, figsize=(7.48, 2.9), layout='constrained')
# (a) predicted vs reference
ax = axes[0]
lo = min(y_true.min(), y_pred.min()); hi = max(y_true.max(), y_pred.max())
pad = 0.05 * (hi - lo)
ax.plot([lo - pad, hi + pad], [lo - pad, hi + pad], ls='--', color=GREY, lw=1,
label='identity')
xs = np.linspace(y_true.min(), y_true.max(), 50)
ax.plot(xs, M['slope'] * xs + M['intercept'], color=BLUE, lw=1.4, label='fit')
ax.scatter(y_true, y_pred, s=10, color=BLUE, alpha=0.35, edgecolor='none',
label='spectra')
ax.scatter(g_true, g_pred, s=42, color=RED, marker='D', edgecolor='white',
linewidth=0.5,
           zorder=5, label='group mean')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Predicted (ug
mL$^{-1}$)')
ax.set_aspect('equal', adjustable='box')
ax.set_title(f'(a)  Predicted vs reference', fontsize=FS_PANEL, loc='left')
ax.text(0.04, 0.96, f"RMSEP {M['RMSEP']}\n$R^2$ {M['R2']}\nslope {M['slope']}",
        transform=ax.transAxes, va='top', ha='left', fontsize=7.5)
ax.legend(frameon=False, fontsize=7, loc='lower right')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (b) residuals vs reference
ax = axes[1]
resid = y_pred - y_true
sd2 = 2 * M['residual_SD']
ax.axhline(0, color=GREY, lw=1)
ax.axhline(sd2, ls=':', color=RED, lw=0.9)
ax.axhline(-sd2, ls=':', color=RED, lw=0.9)
ax.scatter(y_true, resid, s=10, color=BLUE, alpha=0.4, edgecolor='none')
ymax = max(float(np.abs(resid).max()), sd2) * 1.35
ax.set_ylim(-ymax, ymax)
ax.text(0.03, 0.97, f'dotted: $\\pm$2 SD ({sd2:.2f})', transform=ax.transAxes,
va='top',
        ha='left', fontsize=7, color='#b22222')
ax.set_xlabel('Reference (ug mL$^{-1}$)'); ax.set_ylabel('Residual (ug
mL$^{-1}$)')
```

```
ax.set_title('(b)  Residuals', fontsize=FS_PANEL, loc='left')
ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
# (c) error by concentration level
ax = axes[2]
ax.bar(np.arange(len(lvl_df)), lvl_df['RMSE'].values, color='#6baed6',
edgecolor='#2171b5',
       width=0.66)
ax.set_xticks(np.arange(len(lvl_df)))
ax.set_xticklabels([f'{v:g}' for v in lvl_df['level']], fontsize=8)
ax.set_xlabel('Reference level (ug mL$^{-1}$)'); ax.set_ylabel('RMSE at level (ug
mL$^{-1}$)')
ax.set_title('(c)  Error by level', fontsize=FS_PANEL, loc='left')
ax.grid(True, axis='y', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, FIG_NO, f'sealed_test_regression_{SHORT}',
                  f'Sealed-test regression for {DYE.lower()} (frozen PLS
regression on raw '
                  f'spectra, single evaluation). (a) predicted against reference
with the identity '
                  f'line, the fitted predicted-on-reference line, and the per-
group mean '
                  f'predictions; (b) residuals against reference with the +/-2
residual-SD band; '
                  f'(c) RMSE at each interior test concentration level. RMSEP
{M["RMSEP"]}, R2 '
                  f'{M["R2"]}, slope {M["slope"]}, bias {M["bias"]} ug mL-1 over
{n_spectra} test '
                  f'spectra / {n_groups} groups / {n_levels} levels.')

# ---- metric-block table ----
tbl = pd.DataFrame([M])[['RMSEP', 'MAE', 'R2', 'bias', 'slope', 'intercept',
'residual_SD',
                         'reference_SD', 'RPD', 'group_RMSEP', 'group_R2',
'group_bias',
                         'n_spectra', 'n_groups', 'n_levels']]
show_and_save_table(tbl, TAB_NO, f'{DYE} sealed-test regression metric block',
cell='39',
                    notes=f'Single sealed-test evaluation of the frozen {DYE}
PLSR+Raw model. '
                          f'RMSEP/MAE/bias/slope/intercept/residual SD at spectrum
level; group '
                          f'metrics from the per-group mean prediction ({n_groups}
groups). RPD = '
                          f'reference SD / RMSEP =
{M["reference_SD"]}/{M["RMSEP"]}; it depends on '
                          f'the test concentration spread (interior levels
{test_levels.tolist()}) '
                          f'and is not used as a sole criterion. Per-level RMSE: '
                          f'{dict(zip(lvl_df["level"].tolist(),
lvl_df["RMSE"].tolist()))}. '
                          f'Concentrations in micrograms per millilitre. Test
counter -> 1.')

# ---- record once (counter 0 -> 1), or verify on re-render ----
if _already:
    stored = _state['test_evaluations'][ENDPOINT].get('metrics', {})
    drift = {k: (stored.get(k), M[k]) for k in ('RMSEP', 'R2', 'slope')
             if k in stored and abs(float(stored[k]) - float(M[k])) > 1e-9}
    assert not drift, f"re-render disagrees with recorded sealed-test result:
{drift}"
```

```
    _cnt = int(_state['test_evaluations'][ENDPOINT].get('n_evaluations', 1))
    print(f"\n  recorded result re-rendered; counter unchanged at {_cnt} "
          f"(RMSEP {M['RMSEP']} reproduced exactly).")
else:
    _rec = audit.record_test_evaluation(ENDPOINT, M)
    _cnt = _rec['test_evaluations'][ENDPOINT]['n_evaluations']
    print(f"\n  record_test_evaluation('{ENDPOINT}') -> counter now {_cnt} (must
be 1).")

save_checkpoint({'metrics': M, 'per_level': lvl_df, 'y_true': y_true, 'y_pred':
y_pred,
                 'groups': gt, 'test_levels': test_levels, 'endpoint_counter':
_cnt},
                CELL_SEALEDREG_CHECKPOINT,
                metadata={'type': 'sealed_test_regression', 'cell': '39', 'dye':
DYE})
_ = load_checkpoint(CELL_SEALEDREG_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 39: {DYE} sealed-test regression (F{FIG_NO}/T{TAB_NO}) —
RMSEP "
      f"{M['RMSEP']} ug/mL, R2 {M['R2']}, counter 0->1; model locked.")
```

```
======================================================================
CELL 39: Metanil Yellow Sealed-Test Regression — performed ONCE
======================================================================
I evaluate the frozen Metanil Yellow regressor (PLS regression on raw spectra) a single time on
its sealed test groups (whole concentration levels, interior to the training range). The sealed-
test guard records the evaluation once and the counter moves from 0 to 1; the cell is
idempotent, so a later re-run re-renders the recorded result from the frozen model without a
second evaluation (evaluation_protocol section 11).

  guard_sealed_test('Metanil Yellow'): already recorded at 2026-11-04T15:13:31+00:00; re-
rendering (counter stays at 1, no re-evaluation).
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
  test set: 60 spectra / 3 groups / 3 interior levels [3.0, 10.0, 13.0] ug/mL

--- Sealed-test regression metric block (spectrum level) ---
  RMSEP          0.3069
  MAE            0.2627
  R2             0.9946
  bias           -0.2427
  slope          0.9829
  intercept      -0.0943
  residual_SD    0.1895
  reference_SD   4.2253
  RPD            13.768
  group_RMSEP    0.2784
  group_R2       0.9956
  group_bias     -0.2427
FIGURE 25: Sealed-test regression for metanil yellow (frozen PLS regression on raw spectra,
single evaluation). (a) predicted against reference with the identity line, the fitted
predicted-on-reference line, and the per-group mean predictions; (b) residuals against reference
with the +/-2 residual-SD band; (c) RMSE at each interior test concentration level. RMSEP
0.3069, R2 0.9946, slope 0.9829, bias -0.2427 ug mL-1 over 60 test spectra / 3 groups / 3
levels.
  saved: Figure_25_sealed_test_regression_my.png  (356 kB, 600 dpi)
```




```
TABLE 32: Metanil Yellow sealed-test regression metric block
 RMSEP    MAE     R2    bias  slope  intercept  residual_SD  reference_SD    RPD  group_RMSEP
group_R2  group_bias  n_spectra  n_groups  n_levels
0.3069 0.2627 0.9946 -0.2427 0.9829    -0.0943       0.1895        4.2253 13.768       0.2784
0.9956     -0.2427         60         3         3
  saved: Table_32_metanil_yellow_sealed_test_regression_metric_block.xlsx  (1 rows x 15 cols)

  recorded result re-rendered; counter unchanged at 1 (RMSEP 0.3069 reproduced exactly).
✓ Checkpoint loaded: cell_sealedreg_my_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.842716
  Shape: {'per_level': (3, 5), 'y_true': (60,), 'y_pred': (60,), 'groups': (60,), 'test_levels':
(3,)}

[done] Cell 39: Metanil Yellow sealed-test regression (F25/T32) — RMSEP 0.3069 ug/mL, R2 0.9946,
counter 0->1; model locked.
```

In [41]:

```python
CELL_40_CHECKPOINT = CHECKPOINTS_DIR / 'cell_40_attribution_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print("CELL 40: Spectral Attribution (Gate G8)")
print("=" * 70)
print("Which wavelengths the frozen models rely on. The frozen estimators are
linear / latent-"
      "variable (logistic regression for identity, PLS regression for
concentration), so their "
      "exact feature attributions are available directly and a tree-SHAP
approximation is "
      "neither applicable nor needed (the SHAP package is also absent here):
concentration "
      "attribution uses PLS Variable Importance in Projection (VIP) per dye, and
identity "
      "attribution uses model-agnostic permutation importance (macro-F1 drop)
through the full "
      "frozen classification pipeline. Spearman rank agreement between the two
views is reported. "
      "Importance below roughly 400 nm is flagged as possibly matrix (juice)
background rather "
      "than dye signal, and no importance value is read as chemical causality.")

import joblib
from sklearn.inspection import permutation_importance
from scipy.stats import spearmanr

wl = np.asarray(spec_cols, dtype=int)
P = len(wl)
LAMBDA_MAX = {'Tartrazine': 435, 'Sunset Yellow': 483, 'Metanil Yellow': 434}
COLR = {d: DYE_COLOURS[d] for d in DYE_CLASSES}
SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}
```

```
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)


def pls_vip(pls):
    """Variable Importance in Projection from a fitted PLSRegression (single
target)."""
    W = pls.x_weights_                       # (P, A)
    T = pls.x_scores_                        # (n, A)
    q = np.asarray(pls.y_loadings_).ravel() # (A,)
    ss = (q ** 2) * np.sum(T ** 2, axis=0)  # SSY explained per component
    wnorm2 = np.sum(W ** 2, axis=0)
    vip = np.sqrt(P * ((W ** 2 / wnorm2) @ ss) / np.sum(ss))
    return vip


# ---- regression VIP per dye ----
vip = {}
for dye in DYE_CLASSES:
    reg = joblib.load(MODELS_DIR / f"regressor_{SHORT[dye]}_frozen.joblib")
    vip[dye] = pls_vip(reg['pipeline'].named_steps['pls'])
    top = wl[np.argsort(vip[dye])[::-1][:5]]
    print(f"  {dye:15s} PLS VIP top-5 wavelengths: {top.tolist()} nm "
          f"(lambda-max {LAMBDA_MAX[dye]} nm)")

# ---- classification permutation importance (macro-F1 drop) ----
clf_obj = joblib.load(MODELS_DIR / 'classifier_frozen.joblib')
clf = clf_obj['pipeline']
code_of = clf_obj['class_codes']            # {dye: integer code} the model was
trained on
cls_dev = np.asarray(sealed['classification']['dev_rows'])
y_dev = np.array([code_of[v] for v in y_dye[cls_dev]], dtype=int)
print(f"\n  Permutation importance on {len(cls_dev)} development spectra "
      f"(frozen EMSC+LogReg, macro-F1, 5 repeats)...")
pi = permutation_importance(clf, X[cls_dev], y_dev, scoring='f1_macro',
                            n_repeats=5, random_state=42, n_jobs=1)
perm_imp = pi.importances_mean.copy()
perm_imp[perm_imp < 0] = 0.0
perm_max = float(perm_imp.max())
print(f"  Permutation importance: max single-wavelength macro-F1 drop =
{perm_max:.4f}. "
      "Because the classifier is saturated and the 400 wavelengths are highly
collinear, "
      "removing any single wavelength leaves enough redundant signal to classify
perfectly, so "
      "permutation importance is ~0 everywhere and is uninformative at the single-
wavelength "
      "level. I therefore base identity attribution on the exact logistic-
regression coefficient "
      "magnitude (mean |coef| over the three one-vs-rest weight vectors), the "
      "appropriate attribution for a linear model.")
# exact linear-model identity attribution: mean |coef| per wavelength (EMSC+scaled
space,
# wavelength identity preserved by the per-wavelength preprocessing)
cls_imp = np.mean(np.abs(clf.named_steps['est'].coef_), axis=0)

# ---- rank agreement: mean VIP vs classifier coefficient magnitude ----
mean_vip = np.mean([vip[d] for d in DYE_CLASSES], axis=0)
rho, pval = spearmanr(mean_vip, cls_imp)
print(f"  Spearman rank agreement (mean PLS VIP vs classifier |coefficient|): "
      f"rho = {rho:.3f} (p = {pval:.1e})")
```

```
uv_mask = wl < 400

# Tartrazine (435 nm) and metanil yellow (434 nm) absorbance maxima coincide to
# within 1 nm, so their guide lines are spread by a small symmetric offset and
# given distinct dash styles to keep both visible; sunset yellow (483 nm) stands
# apart. The exact maxima are stated in the caption and T33.
def guide_positions(lmax, min_sep=6.0, spread=6.0):
    vx = {}
    for i, (d, v) in enumerate(sorted(lmax.items(), key=lambda kv: kv[1])):
        vx[d] = v
    items = sorted(lmax.items(), key=lambda kv: kv[1])
    k = 0
    while k < len(items):
        j = k
        while j + 1 < len(items) and items[j + 1][1] - items[k][1] < min_sep:
            j += 1
        grp = items[k:j + 1]
        if len(grp) > 1:
            centre = np.mean([v for _, v in grp])
            offs = np.linspace(-spread / 2, spread / 2, len(grp))
            for (d, _), o in zip(grp, offs):
                vx[d] = centre + o
        k = j + 1
    return vx

VX = guide_positions(LAMBDA_MAX)
GUIDE_LS = {'Tartrazine': ':', 'Sunset Yellow': ':', 'Metanil Yellow': (0, (4,
2))}

# ---- F27: attribution profiles ----
fig, axes = plt.subplots(2, 1, figsize=(7.48, 5.0), layout='constrained',
sharex=True)
ax = axes[0]
for dye in DYE_CLASSES:
    ax.plot(wl, vip[dye], color=COLR[dye], lw=1.3, label=dye)
    ax.axvline(VX[dye], color=COLR[dye], ls=GUIDE_LS[dye], lw=1.1, alpha=0.9)
ax.axhline(1.0, color='#999999', ls='--', lw=1, label='VIP = 1')
ax.axvspan(wl.min(), 400, color='#f0e9d8', alpha=0.6, zorder=0)
ax.text(401, ax.get_ylim()[1] * 0.92, 'UV < 400 nm:\npossible matrix', fontsize=7,
        color='#8a6d3b', va='top')
ax.set_ylabel('PLS VIP (concentration)')
ax.set_title('(a)  Regression attribution — PLS VIP per dye', fontsize=FS_PANEL,
loc='left')
ax.legend(frameon=False, fontsize=7.5, loc='upper right', ncol=2)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax = axes[1]
ax.plot(wl, cls_imp, color='#6a51a3', lw=1.2)
ax.axvspan(wl.min(), 400, color='#f0e9d8', alpha=0.6, zorder=0)
for dye in DYE_CLASSES:
    ax.axvline(VX[dye], color=COLR[dye], ls=GUIDE_LS[dye], lw=1.1, alpha=0.9)
ax.set_xlabel('Wavelength (nm)')
ax.set_ylabel('mean |LogReg coef| (identity)')
ax.set_title(f'(b)  Classification attribution — coefficient magnitude  '
             f'(Spearman rho vs VIP = {rho:.2f})', fontsize=FS_PANEL, loc='left')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 26, 'spectral_attribution',
                  'Spectral attribution for the frozen models. (a) PLS Variable
Importance in '
                  'Projection for each dye concentration model against wavelength,
with the VIP=1 '
                  'reference and each dye observed absorbance maximum as a
```

```
vertical guide. The '
                  'tartrazine (435 nm) and metanil yellow (434 nm) maxima coincide
to within 1 nm, '
                  'so their guides carry a small horizontal offset and distinct
dashes for '
                  'legibility; sunset yellow is at 483 nm. (b) Mean absolute '
                  'logistic-regression coefficient of the frozen identity
classifier against '
                  'wavelength (the exact linear-model attribution; single-
wavelength permutation '
                  f'importance is ~0 everywhere, max macro-F1 drop {perm_max:.3f},
because the '
                  'saturated classifier has redundant collinear inputs). The
shaded band below '
                  '400 nm is the ultraviolet region where the juice matrix absorbs
strongly, so '
                  'importance there is flagged as possible matrix background
rather than dye '
                  f'signal. Spearman rank agreement between the two views is rho =
{rho:.2f}. '
                  'Importance is not interpreted as chemical causality.')


def region(w):
    if w < 400:
        return 'UV <400 nm (possible matrix)'
    if w <= 500:
        return 'visible 400-500 nm (dye band)'
    return 'visible >500 nm (tail)'


# ---- T33: top-30 wavelengths by combined importance ----
vip_rank = (-mean_vip).argsort().argsort()
cls_rank = (-cls_imp).argsort().argsort()
combined = vip_rank + cls_rank                  # Lower = more important in both
order = np.argsort(combined)[:30]
rows = []
for i in order:
    rows.append({'rank_combined': int(combined[i]), 'wavelength_nm': int(wl[i]),
                 'VIP_T': round(float(vip['Tartrazine'][i]), 3),
                 'VIP_SY': round(float(vip['Sunset Yellow'][i]), 3),
                 'VIP_MY': round(float(vip['Metanil Yellow'][i]), 3),
                 'VIP_mean': round(float(mean_vip[i]), 3),
                 'cls_importance': round(float(cls_imp[i]), 5),
                 'UV_Vis_region': region(int(wl[i]))})
top_df = pd.DataFrame(rows).sort_values('VIP_mean',
ascending=False).reset_index(drop=True)
n_uv = int((top_df['wavelength_nm'] < 400).sum())
show_and_save_table(top_df, 33, 'Top-30 wavelengths by combined attribution rank',
cell='40',
                    notes=f'Combined rank = PLS-VIP rank (mean over dyes) +
classifier '
                          f'coefficient-magnitude rank; lower is more important in
both views. '
                          f'Per-dye VIP, mean VIP, classifier mean |LogReg
coefficient|, and UV-Vis '
                          f'region annotation. {n_uv}/30 of the leading
wavelengths lie below 400 '
                          f'nm and are flagged as possible matrix (juice)
background. Spearman rho '
                          f'(mean VIP vs classifier |coef|) = {rho:.3f}, p =
```

```
{pval:.1e}. Single-'
                          f'wavelength permutation importance was ~0 (max macro-F1
drop {perm_max:.3f}) '
                          f'owing to spectral redundancy. Attribution is
descriptive, not a claim '
                          f'of chemical causality.')

save_checkpoint({'vip': vip, 'mean_vip': mean_vip, 'cls_importance': cls_imp,
                 'perm_importance': perm_imp, 'perm_max': perm_max,
                 'wavelengths': wl, 'spearman_rho': float(rho), 'spearman_p':
float(pval),
                 'top30': top_df, 'lambda_max': LAMBDA_MAX},
                CELL_40_CHECKPOINT,
                metadata={'type': 'spectral_attribution', 'cell': '40', 'gate':
'G8'})
_ = load_checkpoint(CELL_40_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 40: Spectral attribution (F26/T33) — PLS VIP + permutation
importance; "
      f"rank agreement rho {rho:.2f}; {n_uv}/30 leading wavelengths flagged
UV/matrix.")
```

```
======================================================================
CELL 40: Spectral Attribution (Gate G8)
======================================================================
Which wavelengths the frozen models rely on. The frozen estimators are linear / latent-variable
(logistic regression for identity, PLS regression for concentration), so their exact feature
attributions are available directly and a tree-SHAP approximation is neither applicable nor
needed (the SHAP package is also absent here): concentration attribution uses PLS Variable
Importance in Projection (VIP) per dye, and identity attribution uses model-agnostic permutation
importance (macro-F1 drop) through the full frozen classification pipeline. Spearman rank
agreement between the two views is reported. Importance below roughly 400 nm is flagged as
possibly matrix (juice) background rather than dye signal, and no importance value is read as
chemical causality.
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
  Tartrazine      PLS VIP top-5 wavelengths: [449, 444, 442, 448, 443] nm (lambda-max 435 nm)
  Sunset Yellow   PLS VIP top-5 wavelengths: [489, 494, 481, 483, 490] nm (lambda-max 483 nm)
  Metanil Yellow  PLS VIP top-5 wavelengths: [435, 416, 430, 427, 434] nm (lambda-max 434 nm)

  Permutation importance on 1060 development spectra (frozen EMSC+LogReg, macro-F1, 5
repeats)...
  Permutation importance: max single-wavelength macro-F1 drop = 0.0000. Because the classifier
is saturated and the 400 wavelengths are highly collinear, removing any single wavelength leaves
enough redundant signal to classify perfectly, so permutation importance is ~0 everywhere and is
uninformative at the single-wavelength level. I therefore base identity attribution on the exact
logistic-regression coefficient magnitude (mean |coef| over the three one-vs-rest weight
vectors), the appropriate attribution for a linear model.
  Spearman rank agreement (mean PLS VIP vs classifier |coefficient|): rho = 0.118 (p = 1.8e-02)
FIGURE 26: Spectral attribution for the frozen models. (a) PLS Variable Importance in Projection
for each dye concentration model against wavelength, with the VIP=1 reference and each dye
observed absorbance maximum as a vertical guide. The tartrazine (435 nm) and metanil yellow (434
nm) maxima coincide to within 1 nm, so their guides carry a small horizontal offset and distinct
dashes for legibility; sunset yellow is at 483 nm. (b) Mean absolute logistic-regression
coefficient of the frozen identity classifier against wavelength (the exact linear-model
attribution; single-wavelength permutation importance is ~0 everywhere, max macro-F1 drop 0.000,
because the saturated classifier has redundant collinear inputs). The shaded band below 400 nm
is the ultraviolet region where the juice matrix absorbs strongly, so importance there is
flagged as possible matrix background rather than dye signal. Spearman rank agreement between
the two views is rho = 0.12. Importance is not interpreted as chemical causality.
  saved: Figure_26_spectral_attribution.png  (780 kB, 600 dpi)
```




TABLE 33: Top-30 wavelengths by combined attribution rank

| rank_combined | wavelength_nm | VIP_T | VIP_SY | VIP_MY | VIP_mean | cls_importance | UV_Vis_region |
|---|---|---|---|---|---|---|---|
| 152 | 442 | 1.136 | 1.138 | 1.551 | 1.275 | 0.03456 | visible 400-500 nm (dye band) |
| 149 | 440 | 1.135 | 1.136 | 1.548 | 1.273 | 0.03542 | visible 400-500 nm (dye band) |
| 168 | 439 | 1.135 | 1.132 | 1.551 | 1.273 | 0.03401 | visible 400-500 nm (dye band) |
| 175 | 443 | 1.136 | 1.139 | 1.546 | 1.273 | 0.03255 | visible 400-500 nm (dye band) |
| 178 | 435 | 1.135 | 1.122 | 1.554 | 1.271 | 0.03357 | visible 400-500 nm (dye band) |
| 147 | 466 | 1.133 | 1.143 | 1.457 | 1.244 | 0.04223 | visible 400-500 nm (dye band) |
| 156 | 467 | 1.133 | 1.143 | 1.446 | 1.241 | 0.04190 | visible 400-500 nm (dye band) |
| 114 | 468 | 1.132 | 1.142 | 1.444 | 1.239 | 0.05359 | visible 400-500 nm (dye band) |
| 113 | 469 | 1.132 | 1.143 | 1.421 | 1.232 | 0.05764 | visible 400-500 nm (dye band) |
| 127 | 470 | 1.131 | 1.143 | 1.400 | 1.225 | 0.05394 | visible 400-500 nm (dye band) |
| 143 | 471 | 1.130 | 1.143 | 1.361 | 1.211 | 0.04874 | visible 400-500 nm (dye band) |
| 149 | 472 | 1.129 | 1.143 | 1.334 | 1.202 | 0.04756 | visible 400-500 nm (dye band) |
| 150 | 473 | 1.128 | 1.143 | 1.273 | 1.181 | 0.04778 | visible 400-500 nm (dye band) |
| 169 | 474 | 1.128 | 1.143 | 1.233 | 1.168 | 0.04618 | visible 400-500 nm (dye band) |
| 166 | 476 | 1.125 | 1.143 | 1.147 | 1.138 | 0.05029 | visible 400-500 nm (dye band) |
| 122 | 301 | 1.069 | 1.122 | 0.915 | 1.036 | 0.12535 | UV <400 nm (possible matrix) |
| 161 | 326 | 1.047 | 1.001 | 1.018 | 1.022 | 0.07200 | UV <400 nm (possible matrix) |
| 155 | 345 | 1.021 | 0.965 | 1.077 | 1.021 | 0.08156 | UV <400 nm (possible matrix) |
| 126 | 302 | 1.068 | 1.127 | 0.868 | 1.021 | 0.12683 | UV <400 nm (possible matrix) |
| 154 | 342 | 1.041 | 0.923 | 1.076 | 1.013 | 0.08936 | UV <400 nm |

```
(possible matrix)
          173           325  1.043   1.024   0.964     1.010         0.06897  UV <400 nm
(possible matrix)
          137           303  1.066   1.127   0.834     1.009         0.12559  UV <400 nm
(possible matrix)
          161           343  1.039   0.934   1.049     1.007         0.08768  UV <400 nm
(possible matrix)
          171           346  1.010   0.982   1.019     1.004         0.07583  UV <400 nm
(possible matrix)
          167           344  1.027   0.945   1.029     1.000         0.08660  UV <400 nm
(possible matrix)
          161           341  1.045   0.886   1.066     0.999         0.09251  UV <400 nm
(possible matrix)
          163           340  1.038   0.831   1.099     0.989         0.09590  UV <400 nm
(possible matrix)
          159           304  1.067   1.126   0.731     0.975         0.12302  UV <400 nm
(possible matrix)
          172           339  1.046   0.774   1.085     0.969         0.09730  UV <400 nm
(possible matrix)
          174           305  1.061   1.127   0.665     0.951         0.12045  UV <400 nm
(possible matrix)
  saved: Table_33_top_30_wavelengths_by_combined_attribution_rank.xlsx  (30 rows x 8 cols)
✓ Checkpoint loaded: cell_40_attribution_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:31.910884
  Shape: {'mean_vip': (400,), 'cls_importance': (400,), 'perm_importance': (400,),
'wavelengths': (400,), 'top30': (30, 8)}

[done] Cell 40: Spectral attribution (F26/T33) — PLS VIP + permutation importance; rank
agreement rho 0.12; 15/30 leading wavelengths flagged UV/matrix.
```

In [42]:

```python
CELL_41_CHECKPOINT = CHECKPOINTS_DIR / 'cell_41_bands_checkpoint.pkl'

print("=" * 70)
print("CELL 41: Severity Bands and Decision-Boundary Behaviour (Gate G8)")
print("=" * 70)
print("Predicted concentrations are mapped to the descriptive analytical-
concentration strata "
      "defined over the experimentally covered range: A-E for tartrazine and
sunset yellow, "
      "M1-M4 for metanil yellow. These bands are a REPORTING LAYER applied after
prediction, not "
      "model targets, and carry NO legal, toxicological, or permissible-intake
meaning. The "
      "100 mg/kg anchor of Revision 1 (-> 8.0 ug/mL in the analytical solution) is
"
      "[VERIFY-REQUIRED] and is NOT asserted as a legal limit here.\n"
      "To characterise band assignment across EVERY stratum, I build the confusion
matrix from "
      "POOLED OUT-OF-SAMPLE predictions: the development-set grouped cross-
validation out-of-fold "
      "predictions (each spectrum predicted only by folds that never saw its
concentration group) "
      "together with the sealed-test predictions. The sealed test alone covers
only a subset of "
      "levels per dye (metanil yellow at 3, 10, 13 ug/mL maps to M1/M3/M4 and
never to M2); the "
      "development levels fill the remaining bands, so no stratum is left
unevaluated. Both "
      "prediction sources are out-of-sample, so the pooled matrix does not
understate "
      "error. Reported: the band confusion matrix, prediction error in the 5-8
ug/mL region, and "
      "sensitivity/specificity across each adjacent-band boundary, as analytical
behaviour near a "
      "decision boundary rather than compliance testing.")
```

```
print("\n  [VERIFY-REQUIRED] Regulatory anchor (100 mg/kg product -> 8.0 ug/mL
analytical) is "
      "unverified; bands below are descriptive strata only.")

from sklearn.cross_decomposition import PLSRegression
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import StandardScaler

# band definitions (M&M section 15): boundaries placed between the integer levels
AE_EDGES = [4.5, 8.5, 13.5, 18.5]; AE_LABELS = ['A', 'B', 'C', 'D', 'E']
M_EDGES = [3.5, 7.5, 11.5]; M_LABELS = ['M1', 'M2', 'M3', 'M4']
AE_RANGES = {'A': '0-4', 'B': '5-8', 'C': '9-13', 'D': '14-18', 'E': '19-24'}
M_RANGES = {'M1': '0-3', 'M2': '4-7', 'M3': '8-11', 'M4': '12-15'}
SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}


def to_band(x, edges, labels):
    return [labels[int(np.searchsorted(edges, v))] for v in np.atleast_1d(x)]


# frozen preprocessing/LV design (read from disk; no test data touched)
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
LVsel = {d: {r['Preprocessing']: int(r['selected_LV'])
             for _, r in infra['lv_selection'][infra['lv_selection']['Dye'] ==
d].iterrows()}
         for d in DYE_CLASSES}


def fit_pls(tr, lv):
    return Pipeline([('sc', StandardScaler()),
                     ('pls', PLSRegression(n_components=lv,
scale=False))]).fit(X[tr], conc[tr])


def dev_oof_predictions(dye):
    """Out-of-fold development predictions from the frozen PLSR+Raw design: each
development
    spectrum is predicted only by cross-validation folds whose training set
excluded its
    concentration group, then averaged over the cross-validation repeats."""
    lv = LVsel[dye]['Raw']
    folds = [f for rep in cvf['regression'][dye]['folds'] for f in rep]
    acc = {}
    for tr, va in folds:
        tr = np.asarray(tr); va = np.asarray(va)
        pv = fit_pls(tr, lv).predict(X[va]).ravel()
        for r, p in zip(va, pv):
            acc.setdefault(int(r), []).append(float(p))
    rows = np.array(sorted(acc))
    yp = np.array([np.mean(acc[r]) for r in rows])
    return conc[rows], yp


# pooled out-of-sample predictions per dye: development out-of-fold + sealed test
PRED = {}; SRC = {}; PRED_TEST = {}; PRED_DEV = {}
for dye in DYE_CLASSES:
```

```
    t = load_checkpoint(CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT[dye]}_checkpoint.pkl',
                        validate_hash=False)
    yt_test = np.asarray(t['y_true'], float); yp_test = np.asarray(t['y_pred'],
float)
    yt_dev, yp_dev = dev_oof_predictions(dye)
    PRED_TEST[dye] = (yt_test, yp_test); PRED_DEV[dye] = (yt_dev, yp_dev)
    PRED[dye] = (np.concatenate([yt_dev, yt_test]), np.concatenate([yp_dev,
yp_test]))
    SRC[dye] = np.array(['dev-CV'] * len(yt_dev) + ['sealed-test'] * len(yt_test))
    print(f"  {dye:15s} pooled n = {len(yt_dev)} dev-CV + {len(yt_test)} sealed-
test "
          f"= {len(PRED[dye][0])}")


def confusion(dyes, edges, labels):
    yt_band, yp_band = [], []
    for dye in dyes:
        yt, yp = PRED[dye]
        yt_band += to_band(yt, edges, labels); yp_band += to_band(yp, edges,
labels)
    K = len(labels); idx = {b: i for i, b in enumerate(labels)}
    M = np.zeros((K, K), int)
    for a, b in zip(yt_band, yp_band):
        M[idx[a], idx[b]] += 1
    return M


def boundary_sens_spec(dyes, edges, labels):
    yt = np.concatenate([PRED[d][0] for d in dyes])
    yp = np.concatenate([PRED[d][1] for d in dyes])
    rows = []
    for e, lo, hi in zip(edges, labels[:-1], labels[1:]):
        true_pos = yt >= e; pred_pos = yp >= e
        tp = int(np.sum(true_pos & pred_pos)); fn = int(np.sum(true_pos &
~pred_pos))
        tn = int(np.sum(~true_pos & ~pred_pos)); fp = int(np.sum(~true_pos &
pred_pos))
        sens = tp / (tp + fn) if (tp + fn) else float('nan')
        spec = tn / (tn + fp) if (tn + fp) else float('nan')
        rows.append({'boundary': f'{lo}|{hi}', 'threshold_ugml': e,
                     'sensitivity': round(sens, 4), 'specificity': round(spec, 4),
                     'TP': tp, 'FN': fn, 'TN': tn, 'FP': fp})
    return pd.DataFrame(rows)


cm_ae = confusion(['Tartrazine', 'Sunset Yellow'], AE_EDGES, AE_LABELS)
cm_m = confusion(['Metanil Yellow'], M_EDGES, M_LABELS)
bnd_ae = boundary_sens_spec(['Tartrazine', 'Sunset Yellow'], AE_EDGES, AE_LABELS)
bnd_m = boundary_sens_spec(['Metanil Yellow'], M_EDGES, M_LABELS)

# 5-8 ug/mL region error (band B / M2 analogue)
reg_rows = []
for sysname, dyes in [('A-E (T+SY)', ['Tartrazine', 'Sunset Yellow']),
                      ('M1-M4 (MY)', ['Metanil Yellow'])]:
    yt = np.concatenate([PRED[d][0] for d in dyes]); yp = np.concatenate([PRED[d]
[1] for d in dyes])
    m = (yt >= 5) & (yt <= 8)
    if m.sum():
        e = yp[m] - yt[m]
        reg_rows.append({'system': sysname, 'n_spectra_5_8': int(m.sum()),
```

```
                        'RMSE_5_8': round(float(np.sqrt(np.mean(e ** 2))), 4),
                        'MAE_5_8': round(float(np.mean(np.abs(e))), 4),
                        'bias_5_8': round(float(np.mean(e)), 4)})
    else:
        reg_rows.append({'system': sysname, 'n_spectra_5_8': 0, 'RMSE_5_8':
float('nan'),
                        'MAE_5_8': float('nan'), 'bias_5_8': float('nan')})
reg58 = pd.DataFrame(reg_rows)

# per-band support (true-band counts) to confirm every stratum is populated
support_ae = {b: int(cm_ae[i].sum()) for i, b in enumerate(AE_LABELS)}
support_m = {b: int(cm_m[i].sum()) for i, b in enumerate(M_LABELS)}

print("\n--- Band confusion A-E (tartrazine + sunset yellow, rows=true, cols=pred)
---")
print(pd.DataFrame(cm_ae, index=AE_LABELS, columns=AE_LABELS).to_string())
print(f"  per-band support (true): {support_ae}")
print("\n--- Band confusion M1-M4 (metanil yellow) ---")
print(pd.DataFrame(cm_m, index=M_LABELS, columns=M_LABELS).to_string())
print(f"  per-band support (true): {support_m}")
print("\n--- 5-8 ug/mL region error (pooled) ---");
print(reg58.to_string(index=False))
print("\n--- Adjacent-boundary sensitivity/specificity (A-E) ---");
print(bnd_ae.to_string(index=False))
print("\n--- Adjacent-boundary sensitivity/specificity (M1-M4) ---");
print(bnd_m.to_string(index=False))
ae_acc = float(np.trace(cm_ae) / cm_ae.sum()); m_acc = float(np.trace(cm_m) /
cm_m.sum())
print(f"\n  Band accuracy (pooled out-of-sample): A-E {ae_acc:.3f} "
      f"({int(np.trace(cm_ae))}/{int(cm_ae.sum())}); M1-M4 {m_acc:.3f} "
      f"({int(np.trace(cm_m))}/{int(cm_m.sum())}).")
assert min(support_m.values()) > 0, "a metanil-yellow band is unpopulated"
assert min(support_ae.values()) > 0, "an A-E band is unpopulated"
print("  Every severity band is populated (no undetected stratum).")


def plot_cm(ax, M, labels, ranges, title):
    n = len(labels)
    im = ax.imshow(M, cmap='Blues', vmin=0)
    thr = M.max() * 0.5 if M.max() > 0 else 1
    for i in range(n):
        for j in range(n):
            ax.text(j, i, str(int(M[i, j])), ha='center', va='center', fontsize=9,
                    color='white' if M[i, j] > thr else '#333333')
    ax.set_xticks(range(n)); ax.set_xticklabels([f'{b}\n({ranges[b]})' for b in
labels], fontsize=8)
    ax.set_yticks(range(n)); ax.set_yticklabels([f'{b} ({ranges[b]})' for b in
labels], fontsize=8)
    ax.set_xticks(np.arange(-0.5, n, 1), minor=True)
    ax.set_yticks(np.arange(-0.5, n, 1), minor=True)
    ax.grid(which='minor', color='white', lw=1.6); ax.tick_params(which='minor',
length=0)
    ax.set_xlabel('Predicted band (ug mL$^{-1}$)'); ax.set_ylabel('True band (ug
mL$^{-1}$)')
    ax.set_title(title, fontsize=FS_PANEL, loc='left')
    return im


fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.5), layout='constrained')
plot_cm(axes[0], cm_ae, AE_LABELS, AE_RANGES,
        f'(a)  A-E bands (T+SY)  acc {ae_acc:.2f}')
```

```
plot_cm(axes[1], cm_m, M_LABELS, M_RANGES, f'(b)  M1-M4 bands (MY)  acc
{m_acc:.2f}')
save_and_show_fig(fig, 27, 'severity_band_confusion',
                  'Descriptive severity-band confusion matrices from pooled out-
of-sample '
                  'concentration predictions (development grouped cross-validation
out-of-fold '
                  'predictions combined with the sealed-test predictions). (a) A-E
strata for '
                  'tartrazine and sunset yellow; (b) M1-M4 strata for metanil
yellow. Rows are the '
                  'true band of the reference concentration, columns the band of
the predicted '
                  'concentration; off-diagonal cells are adjacent-band crossings
near a decision '
                  'boundary. Pooling the development out-of-fold predictions with
the sealed test '
                  'populates every stratum, including the metanil-yellow M2 (4-7
ug/mL) band that '
                  'the sealed-test levels (3, 10, 13 ug/mL) do not reach; both
sources are '
                  'out-of-sample. The bands are descriptive analytical-
concentration strata over '
                  'the experimentally covered range with NO legal or toxicological
meaning; the '
                  '8.0 ug/mL regulatory anchor is [VERIFY-REQUIRED] and is not
asserted as a limit.')

band_tbl = pd.concat([
    bnd_ae.assign(system='A-E (T+SY)'), bnd_m.assign(system='M1-M4 (MY)')
], ignore_index=True)[['system', 'boundary', 'threshold_ugml', 'sensitivity',
'specificity',
                       'TP', 'FN', 'TN', 'FP']]
# sealed-test-only accuracy, kept for traceability
cmt_ae = np.zeros_like(cm_ae); cmt_m = np.zeros_like(cm_m)
for dye, (cmt, lab, edg) in [('Tartrazine', (cmt_ae, AE_LABELS, AE_EDGES)),
                             ('Sunset Yellow', (cmt_ae, AE_LABELS, AE_EDGES)),
                             ('Metanil Yellow', (cmt_m, M_LABELS, M_EDGES))]:
    yt, yp = PRED_TEST[dye]; idx = {b: i for i, b in enumerate(lab)}
    for a, b in zip(to_band(yt, edg, lab), to_band(yp, edg, lab)):
        cmt[idx[a], idx[b]] += 1
test_ae_acc = float(np.trace(cmt_ae) / cmt_ae.sum()); test_m_acc =
float(np.trace(cmt_m) / cmt_m.sum())
show_and_save_table(band_tbl, 34, 'Adjacent-band boundary sensitivity and
specificity '
                    '(pooled out-of-sample predictions)', cell='41',
                    notes=f'Pooled out-of-sample predictions = development
grouped-CV out-of-fold + '
                          f'sealed test. Each row treats "concentration at or
above the boundary '
                          f'threshold" as positive. Band accuracy (pooled): A-E
{ae_acc:.3f}, '
                          f'M1-M4 {m_acc:.3f}; sealed-test only: A-E
{test_ae_acc:.3f}, '
                          f'M1-M4 {test_m_acc:.3f}. Per-band true support A-E
{support_ae}, '
                          f'M1-M4 {support_m} (every stratum populated, including
MY M2). 5-8 ug/mL '
                          f'region error: {reg58.to_dict("records")}. Bands are
DESCRIPTIVE strata '
                          f'(M&M section 15) over the covered range; the 100 mg/kg
```

```
-> 8.0 ug/mL '
                          f'anchor is [VERIFY-REQUIRED] and no legal/toxicological
interpretation is '
                          f'made. Reported as analytical behaviour near a decision
boundary, not '
                          f'compliance testing.')

save_checkpoint({'cm_ae': cm_ae, 'cm_m': cm_m, 'boundary_ae': bnd_ae,
'boundary_m': bnd_m,
                 'region_5_8': reg58, 'ae_accuracy': ae_acc, 'm_accuracy': m_acc,
                 'test_ae_accuracy': test_ae_acc, 'test_m_accuracy': test_m_acc,
                 'support_ae': support_ae, 'support_m': support_m,
                 'pooled_sources': {d: {'dev_CV': int(len(PRED_DEV[d][0])),
                                        'sealed_test': int(len(PRED_TEST[d][0]))}
                                    for d in DYE_CLASSES},
                 'verify_required': True},
                CELL_41_CHECKPOINT,
                metadata={'type': 'severity_bands', 'cell': '41', 'gate': 'G8'})
_ = load_checkpoint(CELL_41_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 41: Severity bands (F27/T34) — pooled out-of-sample; every
stratum populated; "
      f"A-E acc {ae_acc:.2f}, M1-M4 acc {m_acc:.2f}; regulatory anchor restated
[VERIFY-REQUIRED].")
```

```
======================================================================
CELL 41: Severity Bands and Decision-Boundary Behaviour (Gate G8)
======================================================================
Predicted concentrations are mapped to the descriptive analytical-concentration strata defined
over the experimentally covered range: A-E for tartrazine and sunset yellow, M1-M4 for metanil
yellow. These bands are a REPORTING LAYER applied after prediction, not model targets, and carry
NO legal, toxicological, or permissible-intake meaning. The 100 mg/kg anchor of Revision 1 (->
8.0 ug/mL in the analytical solution) is [VERIFY-REQUIRED] and is NOT asserted as a legal limit
here.
To characterise band assignment across EVERY stratum, I build the confusion matrix from POOLED
OUT-OF-SAMPLE predictions: the development-set grouped cross-validation out-of-fold predictions
(each spectrum predicted only by folds that never saw its concentration group) together with the
sealed-test predictions. The sealed test alone covers only a subset of levels per dye (metanil
yellow at 3, 10, 13 ug/mL maps to M1/M3/M4 and never to M2); the development levels fill the
remaining bands, so no stratum is left unevaluated. Both prediction sources are out-of-sample,
so the pooled matrix does not understate error. Reported: the band confusion matrix, prediction
error in the 5-8 ug/mL region, and sensitivity/specificity across each adjacent-band boundary,
as analytical behaviour near a decision boundary rather than compliance testing.

  [VERIFY-REQUIRED] Regulatory anchor (100 mg/kg product -> 8.0 ug/mL analytical) is unverified;
bands below are descriptive strata only.
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
✓ Checkpoint loaded: cell_sealedreg_t_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:10.420606
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}
  Tartrazine      pooled n = 400 dev-CV + 100 sealed-test = 500
✓ Checkpoint loaded: cell_sealedreg_sy_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.126088
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}
  Sunset Yellow   pooled n = 400 dev-CV + 100 sealed-test = 500
✓ Checkpoint loaded: cell_sealedreg_my_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.842716
  Shape: {'per_level': (3, 5), 'y_true': (60,), 'y_pred': (60,), 'groups': (60,), 'test_levels':
(3,)}
  Metanil Yellow  pooled n = 260 dev-CV + 60 sealed-test = 320
```

```
--- Band confusion A-E (tartrazine + sunset yellow, rows=true, cols=pred) ---
     A    B    C    D    E
A  200    0    0    0    0
B   22  125   13    0    0
C    0    1  199    0    0
D    0    0    1  198    1
E    0    0    0    0  240
  per-band support (true): {'A': 200, 'B': 160, 'C': 200, 'D': 200, 'E': 240}

--- Band confusion M1-M4 (metanil yellow) ---
    M1  M2  M3  M4
M1  80   0   0   0
M2   0  78   2   0
M3   0   0  80   0
M4   0   0   0  80
  per-band support (true): {'M1': 80, 'M2': 80, 'M3': 80, 'M4': 80}

--- 5-8 ug/mL region error (pooled) ---
    system  n_spectra_5_8  RMSE_5_8  MAE_5_8  bias_5_8
A-E (T+SY)            160    0.4338   0.3302     0.009
M1-M4 (MY)             80    0.2058   0.1452     0.053

--- Adjacent-boundary sensitivity/specificity (A-E) ---
boundary  threshold_ugml  sensitivity  specificity  TP  FN  TN  FP
     A|B            4.5       0.9725       1.0000 778  22 200   0
     B|C            8.5       0.9984       0.9639 639   1 347  13
     C|D           13.5       0.9977       1.0000 439   1 560   0
     D|E           18.5       1.0000       0.9987 240   0 759   1

--- Adjacent-boundary sensitivity/specificity (M1-M4) ---
boundary  threshold_ugml  sensitivity  specificity  TP  FN  TN  FP
   M1|M2            3.5          1.0       1.0000 240   0  80   0
   M2|M3            7.5          1.0       0.9875 160   0 158   2
   M3|M4           11.5          1.0       1.0000  80   0 240   0

  Band accuracy (pooled out-of-sample): A-E 0.962 (962/1000); M1-M4 0.994 (318/320).
  Every severity band is populated (no undetected stratum).
```

FIGURE 27: Descriptive severity-band confusion matrices from pooled out-of-sample concentration predictions (development grouped cross-validation out-of-fold predictions combined with the sealed-test predictions). (a) A-E strata for tartrazine and sunset yellow; (b) M1-M4 strata for metanil yellow. Rows are the true band of the reference concentration, columns the band of the predicted concentration; off-diagonal cells are adjacent-band crossings near a decision boundary. Pooling the development out-of-fold predictions with the sealed test populates every stratum, including the metanil-yellow M2 (4-7 ug/mL) band that the sealed-test levels (3, 10, 13 ug/mL) do not reach; both sources are out-of-sample. The bands are descriptive analytical-concentration strata over the experimentally covered range with NO legal or toxicological meaning; the 8.0 ug/mL regulatory anchor is [VERIFY-REQUIRED] and is not asserted as a limit.

  saved: Figure_27_severity_band_confusion.png  (334 kB, 600 dpi)



```
TABLE 34: Adjacent-band boundary sensitivity and specificity (pooled out-of-sample predictions)
    system boundary  threshold_ugml  sensitivity  specificity  TP  FN  TN  FP
A-E (T+SY)      A|B             4.5       0.9725       1.0000 778  22 200   0
A-E (T+SY)      B|C             8.5       0.9984       0.9639 639   1 347  13
A-E (T+SY)      C|D            13.5       0.9977       1.0000 439   1 560   0
A-E (T+SY)      D|E            18.5       1.0000       0.9987 240   0 759   1
M1-M4 (MY)    M1|M2             3.5       1.0000       1.0000 240   0  80   0
M1-M4 (MY)    M2|M3             7.5       1.0000       0.9875 160   0 158   2
M1-M4 (MY)    M3|M4            11.5       1.0000       1.0000  80   0 240   0
  saved:
Table_34_adjacent_band_boundary_sensitivity_and_specificity_pooled_out_of_sample_predictions.xls
x  (7 rows x 9 cols)
✓ Checkpoint loaded: cell_41_bands_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:33.251217
  Shape: {'cm_ae': (5, 5), 'cm_m': (4, 4), 'boundary_ae': (4, 8), 'boundary_m': (3, 8),
'region_5_8': (2, 5)}

[done] Cell 41: Severity bands (F27/T34) — pooled out-of-sample; every stratum populated; A-E
acc 0.96, M1-M4 acc 0.99; regulatory anchor restated [VERIFY-REQUIRED].
```

In [43]:

```
CELL_42_CHECKPOINT = CHECKPOINTS_DIR / 'cell_42_matrix_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print("CELL 42: Matrix Effect and Domain-Transfer Sensitivity (Gate G8)")
print("=" * 70)
print("Pure-standard (dye in solvent) and matrix (dye in orange juice) spectra are
compared at "
      "matching analytical concentrations to quantify the matrix-associated change
in peak "
      "position, amplitude, baseline, and shape. Then a labelled sensitivity
analysis: the "
      "frozen MATRIX concentration model is applied to PURE-standard spectra and
the error is "
      "reported strictly as a domain-transfer probe, never as validation (the
models are "
      "validated only on the sealed matrix test set, already consumed). Matrix
effects are read "
      "from the observed difference between domains, not against a borrowed
acceptance "
      "threshold.")

import joblib
wl = np.asarray(spec_cols, dtype=int)
PEAK_WINDOW = {'Tartrazine': (420, 450), 'Sunset Yellow': (470, 500), 'Metanil
Yellow': (420, 450)}
SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}
COLR = {d: DYE_COLOURS[d] for d in DYE_CLASSES}
BASE = (wl >= 650) & (wl <= 700)


def lmax(spec, dye):
    lo, hi = PEAK_WINDOW[dye]; w = (wl >= lo) & (wl <= hi)
    loc = np.where(w)[0]
    return int(wl[loc[int(np.argmax(spec[loc]))]])


def rmse(a, b):
    return float(np.sqrt(np.mean((np.asarray(a) - np.asarray(b)) ** 2)))


rows, spectra = [], {}
for dye in DYE_CLASSES:
    pm = is_pure & (y_dye == dye); mm = is_matrix & (y_dye == dye)
```

```
    cp, cm = set(np.round(conc[pm], 3)), set(np.round(conc[mm], 3))
    common = sorted(cp & cm)
    sel_p = pm & np.isin(np.round(conc, 3), list(common))
    sel_m = mm & np.isin(np.round(conc, 3), list(common))
    pure = X[sel_p].mean(0); matr = X[sel_m].mean(0)
    spectra[dye] = (pure, matr)
    lp, lmv = lmax(pure, dye), lmax(matr, dye)
    ip = int(np.where(wl == lmv)[0][0])
    amp_ratio = float(matr[ip] / pure[ip]) if pure[ip] != 0 else float('nan')
    baseline = float(matr[BASE].mean() - pure[BASE].mean())
    shape_r = float(np.corrcoef(pure, matr)[0, 1])
    # domain-transfer probe: frozen matrix model on pure-standard spectra of this
dye
    reg = joblib.load(MODELS_DIR / f'regressor_{SHORT[dye]}_frozen.joblib')
['pipeline']
    pred_pure = reg.predict(X[pm]).ravel()
    transfer_rmse = rmse(conc[pm], pred_pure)
    transfer_bias = float(np.mean(pred_pure - conc[pm]))
    rows.append({'Dye': dye, 'n_common_levels': len(common),
                 'pure_lambda_max_nm': lp, 'matrix_lambda_max_nm': lmv,
                 'peak_shift_nm': lmv - lp, 'amplitude_ratio_matrix_over_pure':
round(amp_ratio, 3),
                 'baseline_offset_650_700': round(baseline, 4),
'shape_correlation': round(shape_r, 4),
                 'domain_transfer_RMSE': round(transfer_rmse, 4),
                 'domain_transfer_bias': round(transfer_bias, 4),
                 'n_pure_spectra': int(pm.sum())})
    print(f"  {dye:15s} shift {lmv - lp:+d} nm | amp ratio {amp_ratio:.3f} |
baseline "
          f"{baseline:+.4f} | shape r {shape_r:.4f} | domain-transfer RMSE
{transfer_rmse:.3f} "
          f"ug/mL (probe only)")

mtx = pd.DataFrame(rows)

# in-domain (matrix) sealed-test RMSEP for the gap comparison
indom = {}
for dye in DYE_CLASSES:
    d = load_checkpoint(CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT[dye]}_checkpoint.pkl',
                        validate_hash=False)
    indom[dye] = float(d['metrics']['RMSEP'])

# ---- F29: (a) pure vs matrix mean spectra; (b) domain-transfer vs in-domain
error ----
fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.3), layout='constrained')
ax = axes[0]
for dye in DYE_CLASSES:
    pure, matr = spectra[dye]
    ax.plot(wl, pure, color=COLR[dye], lw=1.1, ls='--', alpha=0.9)
    ax.plot(wl, matr, color=COLR[dye], lw=1.4, label=dye)
ax.plot([], [], color='#555555', ls='--', label='pure standard')
ax.plot([], [], color='#555555', ls='-', label='matrix')
ax.set_xlabel('Wavelength (nm)'); ax.set_ylabel('Absorbance (AirPLS-corrected)')
ax.set_title('(a)  Pure vs matrix mean spectra', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=7, loc='upper right', ncol=1)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax = axes[1]
xp = np.arange(len(DYE_CLASSES)); w = 0.38
ind = [indom[d] for d in DYE_CLASSES]; tr = [mtx[mtx.Dye == d]
['domain_transfer_RMSE'].iloc[0]
```

```
                                          for d in DYE_CLASSES]
ax.bar(xp - w / 2, ind, w, color='#6baed6', edgecolor='#2171b5', label='in-domain
RMSEP (matrix test)')
ax.bar(xp + w / 2, tr, w, color='#fdae6b', edgecolor='#e6550d', label='domain-
transfer RMSE (pure, probe)')
ax.set_xticks(xp); ax.set_xticklabels([SHORT[d].upper() for d in DYE_CLASSES])
ax.set_ylabel('Error (ug mL$^{-1}$)'); ax.set_xlabel('Dye')
ax.set_title('(b)  Domain-transfer sensitivity', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=7, loc='upper left')
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 28, 'matrix_effect_domain_transfer',
                  'Matrix effect and domain-transfer sensitivity. (a) Mean pure-
standard (dashed) '
                  'and matrix (solid) spectra per dye at matching analytical
concentrations, '
                  'showing matrix-associated peak-position, amplitude and baseline
differences. '
                  '(b) Error of the frozen matrix concentration model in its own
domain (sealed '
                  'matrix test RMSEP) against the same model applied to pure-
standard spectra '
                  '(domain-transfer probe, NOT validation). A large transfer error
is expected '
                  'and quantifies how matrix-specific each calibration is.')

show_and_save_table(mtx, 35, 'Matrix effect and domain-transfer probe per dye',
cell='42',
                    notes='Pure vs matrix compared at matching analytical
concentrations: peak '
                          'position, amplitude ratio at the matrix peak, baseline
offset '
                          '(650-700 nm), and whole-spectrum shape correlation.
Domain-transfer '
                          'columns apply the frozen MATRIX model to pure-standard
spectra and are '
                          'a sensitivity PROBE, never validation; in-domain sealed
matrix-test '
                          f'RMSEP for comparison: { {d: round(indom[d],4) for d in
DYE_CLASSES} }. '
                          'Matrix effects are read from the between-domain
difference, not against '
                          'a borrowed acceptance threshold.')

save_checkpoint({'matrix_table': mtx, 'spectra': spectra, 'in_domain_rmsep':
indom},
                CELL_42_CHECKPOINT,
                metadata={'type': 'matrix_effect', 'cell': '42', 'gate': 'G8'})
_ = load_checkpoint(CELL_42_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 42: Matrix effect and domain-transfer (F28/T35) — between-
domain peak "
      "shift/amplitude/baseline quantified; domain-transfer reported as a probe
only.")
```

```
======================================================================
CELL 42: Matrix Effect and Domain-Transfer Sensitivity (Gate G8)
======================================================================
```

Pure-standard (dye in solvent) and matrix (dye in orange juice) spectra are compared at matching analytical concentrations to quantify the matrix-associated change in peak position, amplitude, baseline, and shape. Then a labelled sensitivity analysis: the frozen MATRIX concentration model is applied to PURE-standard spectra and the error is reported strictly as a domain-transfer probe, never as validation (the models are validated only on the sealed matrix test set, already consumed). Matrix effects are read from the observed difference between domains, not against a borrowed acceptance threshold.

```
  Tartrazine      shift +3 nm | amp ratio 0.704 | baseline -0.0176 | shape r 0.6263 | domain-transfer RMSE 4.365 ug/mL (probe only)
  Sunset Yellow   shift -4 nm | amp ratio 0.871 | baseline -0.0127 | shape r 0.5737 | domain-transfer RMSE 8.177 ug/mL (probe only)
  Metanil Yellow  shift +3 nm | amp ratio 0.949 | baseline +0.0037 | shape r 0.2776 | domain-transfer RMSE 11.018 ug/mL (probe only)
✓ Checkpoint loaded: cell_sealedreg_t_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:10.420606
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,), 'test_levels': (5,)}
✓ Checkpoint loaded: cell_sealedreg_sy_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.126088
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,), 'test_levels': (5,)}
✓ Checkpoint loaded: cell_sealedreg_my_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.842716
  Shape: {'per_level': (3, 5), 'y_true': (60,), 'y_pred': (60,), 'groups': (60,), 'test_levels': (3,)}
FIGURE 28: Matrix effect and domain-transfer sensitivity. (a) Mean pure-standard (dashed) and matrix (solid) spectra per dye at matching analytical concentrations, showing matrix-associated peak-position, amplitude and baseline differences. (b) Error of the frozen matrix concentration model in its own domain (sealed matrix test RMSEP) against the same model applied to pure-standard spectra (domain-transfer probe, NOT validation). A large transfer error is expected and quantifies how matrix-specific each calibration is.
  saved: Figure_28_matrix_effect_domain_transfer.png  (499 kB, 600 dpi)
```




```
TABLE 35: Matrix effect and domain-transfer probe per dye
          Dye  n_common_levels  pure_lambda_max_nm  matrix_lambda_max_nm  peak_shift_nm  amplitude_ratio_matrix_over_pure  baseline_offset_650_700  shape_correlation  domain_transfer_RMSE  domain_transfer_bias  n_pure_spectra
    Tartrazine                9                 432                   435              3                             0.704                  -0.0176             0.6263                4.3652                4.1764             180
 Sunset Yellow               10                 486                   482             -4                             0.871                  -0.0127             0.5737                8.1770                4.0641             200
Metanil Yellow                8                 427                   430              3                             0.949                   0.0037             0.2776               11.0179                8.3198             220
  saved: Table_35_matrix_effect_and_domain_transfer_probe_per_dye.xlsx  (3 rows x 11 cols)
✓ Checkpoint loaded: cell_42_matrix_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:33.861566
  Shape: {'matrix_table': (3, 11)}

[done] Cell 42: Matrix effect and domain-transfer (F28/T35) — between-domain peak shift/amplitude/baseline quantified; domain-transfer reported as a probe only.
```

In [44]:

```python
CELL_43_CHECKPOINT = CHECKPOINTS_DIR / 'cell_43_validation_checkpoint.pkl'

print("=" * 70)
print("CELL 43: Single-Wavelength Validation and Replicate Precision (M&M section 16)")
```

```
print("=" * 70)
print("Analytical-validation quantities that sit BESIDE the multivariate models,
not inside "
      "them. Single-wavelength limit of detection and limit of quantification are
computed by "
      "the slope method on the univariate absorbance-maximum calibration in the
matrix domain "
      "(LOD = 3.3 sigma/S, LOQ = 10 sigma/S, sigma = residual standard deviation
of the "
      "calibration, S = slope); these are reported separately and are NOT
transferred to the "
      "PLS models. Replicate precision from the 20 within-group instrument frames
estimates "
      "instrument REPEATABILITY only; it does not estimate between-preparation
reproducibility, "
      "because no independent duplicate preparations exist. Multivariate lower-
range validity is "
      "read from the sealed-test prediction error in the lowest concentration
band.")

PEAK_WINDOW = {'Tartrazine': (420, 450), 'Sunset Yellow': (470, 500), 'Metanil
Yellow': (420, 450)}
SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}
COLR = {d: DYE_COLOURS[d] for d in DYE_CLASSES}
wl = np.asarray(spec_cols, dtype=int)


def lmax_col(dye, mask):
    lo, hi = PEAK_WINDOW[dye]; w = (wl >= lo) & (wl <= hi)
    loc = np.where(w)[0]
    mean = X[mask].mean(0)
    return int(loc[int(np.argmax(mean[loc]))])


rows, cal = [], {}
for dye in DYE_CLASSES:
    mask = is_matrix & (y_dye == dye)
    col = lmax_col(dye, mask)
    A = X[mask][:, col].astype(float); c = conc[mask].astype(float)
    S, b = np.polyfit(c, A, 1)
    fit = S * c + b
    sigma = float(np.sqrt(np.sum((A - fit) ** 2) / (len(A) - 2)))     # residual
SD (Sy/x)
    r2cal = float(1 - np.sum((A - fit) ** 2) / np.sum((A - A.mean()) ** 2))
    LOD = 3.3 * sigma / abs(S); LOQ = 10 * sigma / abs(S)
    # instrument repeatability: within-group RSD of the peak absorbance, averaged
over groups
    rsd = []
    for g in np.unique(group_id[mask]):
        a = X[(group_id == g) & mask][:, col]
        if a.mean() != 0 and len(a) > 1:
            rsd.append(100.0 * a.std(ddof=1) / abs(a.mean()))
    repeat_rsd = float(np.mean(rsd)) if rsd else float('nan')
    # multivariate low-range validity: lowest-level sealed-test RMSE
    srd = load_checkpoint(CHECKPOINTS_DIR /
f'cell_sealedreg_{SHORT[dye]}_checkpoint.pkl',
                          validate_hash=False)
    pl = srd['per_level']
    low_rmse = float(pl.sort_values('level').iloc[0]['RMSE'])
    low_level = float(pl.sort_values('level').iloc[0]['level'])
    cal[dye] = (c, A, S, b, LOD, LOQ, int(wl[col]))
```

```
    rows.append({'Dye': dye, 'lambda_max_nm': int(wl[col]),
                 'slope_S_AU_per_ugml': round(float(S), 5),
                 'residual_sigma_AU': round(sigma, 5), 'calibration_R2':
round(r2cal, 4),
                 'LOD_ugml': round(LOD, 3), 'LOQ_ugml': round(LOQ, 3),
                 'instrument_repeatability_RSD_pct': round(repeat_rsd, 3),
                 'lowest_level_ugml': low_level,
                 'multivariate_low_range_RMSE': round(low_rmse, 4)})
    print(f"  {dye:15s} lambda-max {int(wl[col])} nm | S {S:.4g} AU/(ug/mL) |
sigma {sigma:.4g} | "
          f"LOD {LOD:.3f} | LOQ {LOQ:.3f} ug/mL | repeatability RSD
{repeat_rsd:.2f}% | "
          f"PLS low-range RMSE {low_rmse:.3f} @ {low_level:g}")

val = pd.DataFrame(rows)

# ---- F30: univariate calibration with LOD/LOQ per dye ----
fig, axes = plt.subplots(1, 3, figsize=(7.48, 2.9), layout='constrained')
for ax, dye in zip(axes, DYE_CLASSES):
    c, A, S, b, LOD, LOQ, lm = cal[dye]
    ax.scatter(c, A, s=10, color=COLR[dye], alpha=0.35, edgecolor='none')
    xs = np.linspace(0, c.max(), 50); ax.plot(xs, S * xs + b, color=COLR[dye],
lw=1.4)
    ax.axvline(LOD, color='#d62728', ls=':', lw=1.0)
    ax.axvline(LOQ, color='#555555', ls='--', lw=1.0)
    ytop = ax.get_ylim()[1]
    ax.text(LOD, ytop * 0.99, f'LOD {LOD:.2f}', fontsize=7, color='#d62728',
            rotation=90, va='top', ha='right')
    ax.text(LOQ, ytop * 0.99, f'LOQ {LOQ:.2f}', fontsize=7, color='#333333',
            rotation=90, va='top', ha='right')
    ax.set_title(f'{SHORT[dye].upper()} ({lm} nm)', fontsize=FS_PANEL, loc='left')
    ax.set_xlabel('Concentration (ug mL$^{-1}$)')
    ax.grid(True, color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
    ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
axes[0].set_ylabel('Absorbance at $\\lambda_{max}$')
save_and_show_fig(fig, 29, 'univariate_lod_loq',
                  'Single-wavelength calibration at each dye absorbance maximum
(matrix domain), '
                  'with the slope-method limit of detection (LOD, dotted) and
limit of '
                  'quantification (LOQ, dashed). These single-wavelength figures
of merit are '
                  'reported separately from the multivariate models and are NOT
transferred to '
                  'them; the PLS lower-range validity is assessed from the sealed-
test error in '
                  'the lowest concentration band (tabulated).')

show_and_save_table(val, 36, 'Single-wavelength LOD/LOQ (slope method) and
replicate precision',
                    cell='43',
                    notes='Univariate absorbance-maximum calibration in the matrix
domain: slope '
                          'S, residual standard deviation sigma (Sy/x),
calibration R-squared, '
                          'LOD = 3.3 sigma/S, LOQ = 10 sigma/S.
instrument_repeatability_RSD_pct '
                          'is the mean within-group relative SD of the peak
absorbance over the 20 '
                          'frames per group and estimates INSTRUMENT REPEATABILITY
ONLY, not '
```

```
                          'between-preparation reproducibility (no independent
duplicate '
                          'preparations exist). multivariate_low_range_RMSE is the
frozen PLS '
                          'sealed-test RMSE at the lowest test level. LOD/LOQ are
single-'
                          'wavelength and are not transferred to the multivariate
models.')

save_checkpoint({'validation': val, 'calibration': {d: cal[d] for d in
DYE_CLASSES}},
                CELL_43_CHECKPOINT,
                metadata={'type': 'analytical_validation', 'cell': '43'})
_ = load_checkpoint(CELL_43_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 43: Single-wavelength LOD/LOQ + replicate precision (F29/T36)
— reported "
      "separately from the multivariate models; repeatability stated as
instrument-only.")
```

```
======================================================================
CELL 43: Single-Wavelength Validation and Replicate Precision (M&M section 16)
======================================================================
Analytical-validation quantities that sit BESIDE the multivariate models, not inside them.
Single-wavelength limit of detection and limit of quantification are computed by the slope
method on the univariate absorbance-maximum calibration in the matrix domain (LOD = 3.3 sigma/S,
LOQ = 10 sigma/S, sigma = residual standard deviation of the calibration, S = slope); these are
reported separately and are NOT transferred to the PLS models. Replicate precision from the 20
within-group instrument frames estimates instrument REPEATABILITY only; it does not estimate
between-preparation reproducibility, because no independent duplicate preparations exist.
Multivariate lower-range validity is read from the sealed-test prediction error in the lowest
concentration band.
✓ Checkpoint loaded: cell_sealedreg_t_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:10.420606
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}
  Tartrazine      lambda-max 435 nm | S 0.03563 AU/(ug/mL) | sigma 0.02147 | LOD 1.989 | LOQ
6.026 ug/mL | repeatability RSD 5.90% | PLS low-range RMSE 0.262 @ 1
✓ Checkpoint loaded: cell_sealedreg_sy_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.126088
  Shape: {'per_level': (5, 5), 'y_true': (100,), 'y_pred': (100,), 'groups': (100,),
'test_levels': (5,)}
  Sunset Yellow   lambda-max 483 nm | S 0.03144 AU/(ug/mL) | sigma 0.01883 | LOD 1.977 | LOQ
5.990 ug/mL | repeatability RSD 3.86% | PLS low-range RMSE 0.476 @ 5
✓ Checkpoint loaded: cell_sealedreg_my_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:11.842716
  Shape: {'per_level': (3, 5), 'y_true': (60,), 'y_pred': (60,), 'groups': (60,), 'test_levels':
(3,)}
  Metanil Yellow  lambda-max 434 nm | S 0.01089 AU/(ug/mL) | sigma 0.009472 | LOD 2.871 | LOQ
8.701 ug/mL | repeatability RSD 5.21% | PLS low-range RMSE 0.245 @ 3
FIGURE 29: Single-wavelength calibration at each dye absorbance maximum (matrix domain), with
the slope-method limit of detection (LOD, dotted) and limit of quantification (LOQ, dashed).
These single-wavelength figures of merit are reported separately from the multivariate models
and are NOT transferred to them; the PLS lower-range validity is assessed from the sealed-test
error in the lowest concentration band (tabulated).
  saved: Figure_29_univariate_lod_loq.png  (568 kB, 600 dpi)
```




TABLE 36: Single-wavelength LOD/LOQ (slope method) and replicate precision

| Dye | lambda_max_nm | slope_S_AU_per_ugml | residual_sigma_AU | calibration_R2 | LOD_ugml | LOQ_ugml | instrument_repeatability_RSD_pct | lowest_level_ugml | multivariate_low_range_RMSE |
|---|---|---|---|---|---|---|---|---|---|
| Tartrazine | 435 | 0.03563 | 0.02147 | 0.9930 | 1.989 | 6.026 | 5.901 | 1.0 | 0.2621 |
| Sunset Yellow | 483 | 0.03144 | 0.01883 | 0.9931 | 1.977 | 5.990 | 3.856 | 5.0 | 0.4757 |
| Metanil Yellow | 434 | 0.01089 | 0.00947 | 0.9651 | 2.871 | 8.701 | 5.208 | 3.0 | 0.2450 |

saved: Table_36_single_wavelength_lod_loq_slope_method_and_replicate_precision.xlsx (3 rows x 10 cols)

✓ Checkpoint loaded: cell_43_validation_checkpoint.pkl
Timestamp: 2026-11-04T23:35:34.477399
Shape: {'validation': (3, 10)}

[done] Cell 43: Single-wavelength LOD/LOQ + replicate precision (F29/T36) — reported separately from the multivariate models; repeatability stated as instrument-only.

In [45]:

```
CELL_44_CHECKPOINT = CHECKPOINTS_DIR / 'cell_44_robustness_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'

print("=" * 70)
print("CELL 44: Robustness and Determinism")
print("=" * 70)
print("How sensitive the frozen quantitative result is to arbitrary choices.
Reported per dye: "
      "RMSECV of the frozen PLSR+Raw model under five alternative grouped-CV fold
seeds; "
      "RMSECV at the frozen latent-variable count plus or minus one; the stability
of the top-30 "
      "PLS-VIP wavelength set across the 25 development folds (Jaccard overlap
with the full-set "
      "ranking); and the measured prediction non-determinism of the frozen model
across repeat "
      "calls, which isolates residual threaded-library non-determinism.
Development data only.")

import joblib
from sklearn.cross_decomposition import PLSRegression
from sklearn.pipeline import Pipeline

SHORT = {'Tartrazine': 't', 'Sunset Yellow': 'sy', 'Metanil Yellow': 'my'}
COLR = {d: DYE_COLOURS[d] for d in DYE_CLASSES}
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)
cvf = load_checkpoint(CELL_17_CHECKPOINT, validate_hash=False)
infra = load_checkpoint(CHECKPOINTS_DIR /
'cell_32_regression_infrastructure_checkpoint.pkl',
                        validate_hash=False)
LVsel = {d: {r['Preprocessing']: int(r['selected_LV'])
```

```
            for _, r in infra['lv_selection'][infra['lv_selection']['Dye'] ==
d].iterrows()}
         for d in DYE_CLASSES}
wl = np.asarray(spec_cols, dtype=int)


def rmse(a, b):
    return float(np.sqrt(np.mean((np.asarray(a) - np.asarray(b)) ** 2)))


def fit_pls(tr, lv):
    return Pipeline([('sc', StandardScaler()),
                     ('pls', PLSRegression(n_components=lv,
scale=False))]).fit(X[tr], conc[tr])


def seed_rmsecv(dev, lv, seed, n_splits=5):
    groups = group_id[dev]; ug = np.unique(groups)
    rng = np.random.default_rng(seed); perm = rng.permutation(len(ug))
    fold_of = {g: int(perm[i] % n_splits) for i, g in enumerate(ug)}
    sc = []
    for f in range(n_splits):
        vmask = np.isin(groups, [g for g in ug if fold_of[g] == f])
        va, tr = dev[vmask], dev[~vmask]
        if len(np.unique(group_id[tr])) <= lv:
            continue
        p = fit_pls(tr, lv); sc.append(rmse(conc[va], p.predict(X[va]).ravel()))
    return float(np.mean(sc))


def pls_vip(pls):
    W = pls.x_weights_; T = pls.x_scores_; q = np.asarray(pls.y_loadings_).ravel()
    ss = (q ** 2) * np.sum(T ** 2, axis=0); wn = np.sum(W ** 2, axis=0)
    return np.sqrt(len(wl) * ((W ** 2 / wn) @ ss) / np.sum(ss))


rows, seed_scores = [], {}
for dye in DYE_CLASSES:
    dev = np.asarray(sealed['regression'][dye]['dev_rows'])
    lv = LVsel[dye]['Raw']
    folds = [f for rep in cvf['regression'][dye]['folds'] for f in rep]
    # seed sensitivity
    seeds = [43, 44, 45, 46, 47]
    ss = [seed_rmsecv(dev, lv, s) for s in seeds]
    seed_scores[dye] = ss
    # LV sensitivity (frozen folds)
    def lv_rmsecv(k):
        return float(np.mean([rmse(conc[np.asarray(va)], fit_pls(np.asarray(tr),
k)
                                   .predict(X[np.asarray(va)]).ravel()) for tr, va
in folds]))
    rm_lv = {k: lv_rmsecv(k) for k in (max(1, lv - 1), lv, lv + 1)}
    # top-30 VIP stability across the 25 folds
    full = fit_pls(dev, lv); top_full =
set(wl[np.argsort(pls_vip(full.named_steps['pls']))[::-1][:30]])
    jac = []
    for tr, _ in folds:
        v = pls_vip(fit_pls(np.asarray(tr), lv).named_steps['pls'])
        topf = set(wl[np.argsort(v)[::-1][:30]])
        jac.append(len(top_full & topf) / len(top_full | topf))
    # determinism
```

```
    reg = joblib.load(MODELS_DIR / f'regressor_{SHORT[dye]}_frozen.joblib')
['pipeline']
    p1 = reg.predict(X[dev]).ravel(); p2 = reg.predict(X[dev]).ravel()
    det = float(np.max(np.abs(p1 - p2)))
    rows.append({'Dye': dye, 'frozen_LV': lv, 'frozen_RMSECV': round(rm_lv[lv],
4),
                 'seed_RMSECV_mean': round(float(np.mean(ss)), 4),
                 'seed_RMSECV_SD': round(float(np.std(ss)), 4),
                 f'RMSECV_LV_minus1': round(rm_lv[max(1, lv - 1)], 4),
                 f'RMSECV_LV_plus1': round(rm_lv[lv + 1], 4),
                 'top30_VIP_Jaccard_mean': round(float(np.mean(jac)), 3),
                 'determinism_max_abs_diff': det})
    print(f"  {dye:15s} frozen RMSECV {rm_lv[lv]:.4f} | 5-seed
{np.mean(ss):.4f}+/-{np.std(ss):.4f} "
          f"| LV-1 {rm_lv[max(1,lv-1)]:.4f} LV+1 {rm_lv[lv+1]:.4f} | VIP Jaccard "
          f"{np.mean(jac):.3f} | determinism max|d| {det:.2e}")

rob = pd.DataFrame(rows)

fig, axes = plt.subplots(1, 2, figsize=(7.48, 3.5), layout='constrained')
ax = axes[0]
rng = np.random.default_rng(0)
for i, dye in enumerate(DYE_CLASSES):
    ys = np.asarray(seed_scores[dye]); fr = rob[rob.Dye == dye]
['frozen_RMSECV'].iloc[0]
    ax.errorbar(i - 0.12, ys.mean(), yerr=ys.std(), fmt='o', ms=6,
color=COLR[dye],
                capsize=3, lw=1.2, zorder=3)
    ax.scatter(i - 0.12 + (rng.random(len(ys)) - 0.5) * 0.14, ys, s=16,
color=COLR[dye],
               alpha=0.5, edgecolor='none', zorder=2)
    ax.scatter([i + 0.14], [fr], marker='D', s=42, color='#222222',
edgecolor='white',
               linewidth=0.5, zorder=4)
ax.set_xticks(range(3)); ax.set_xticklabels([SHORT[d].upper() for d in
DYE_CLASSES])
ax.set_xlim(-0.6, 2.6)
ax.set_ylabel('RMSECV (ug mL$^{-1}$)'); ax.set_xlabel('Dye')
ax.set_title('(a)  Alternative-seed fold sensitivity', fontsize=FS_PANEL,
loc='left')
ax.errorbar([], [], yerr=[], fmt='o', color='#777777', capsize=3, label='5 seeds
(mean $\\pm$ SD)')
ax.scatter([], [], marker='D', s=42, color='#222222', label='frozen design')
ax.legend(frameon=False, fontsize=7, loc='upper center', bbox_to_anchor=(0.5,
-0.26), ncol=2)
ax.grid(True, axis='y', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
ax = axes[1]
xp = np.arange(3); w = 0.26
for j, (lab, key) in enumerate([('LV-1', 'RMSECV_LV_minus1'), ('LV',
'frozen_RMSECV'),
                                ('LV+1', 'RMSECV_LV_plus1')]):
    vals = [rob[rob.Dye == d][key].iloc[0] for d in DYE_CLASSES]
    ax.bar(xp + (j - 1) * w, vals, w, label=lab,
           color=['#c6dbef', '#6baed6', '#2171b5'][j], edgecolor='white')
ax.set_xticks(xp); ax.set_xticklabels([SHORT[d].upper() for d in DYE_CLASSES])
ax.set_ylabel('RMSECV (ug mL$^{-1}$)'); ax.set_xlabel('Dye')
ax.set_title('(b)  Latent-variable sensitivity', fontsize=FS_PANEL, loc='left')
ax.legend(frameon=False, fontsize=7, loc='upper center', bbox_to_anchor=(0.5,
-0.26), ncol=3)
ax.grid(True, axis='y', color='#f2f2f2', lw=0.6); ax.set_axisbelow(True)
```

```
ax.spines['top'].set_visible(False); ax.spines['right'].set_visible(False)
save_and_show_fig(fig, 30, 'robustness_sensitivity',
                  'Robustness of the frozen regression. (a) RMSECV of each frozen
PLSR+Raw model '
                  'under five alternative grouped cross-validation fold seeds
(points) against '
                  'the frozen-design RMSECV (bar); (b) RMSECV at the frozen
latent-variable count '
                  'and at plus or minus one component. Small spreads indicate the
quantitative '
                  'result does not depend on the particular fold assignment or an
exact '
                  'latent-variable count. Development data only.')

show_and_save_table(rob, 37, 'Robustness and determinism summary', cell='44',
                    notes='Per dye: frozen latent-variable count and RMSECV; mean
and SD of '
                          'RMSECV over five alternative grouped-CV fold seeds (43-
47); RMSECV at '
                          'LV-1 and LV+1; mean Jaccard overlap of the top-30 PLS-
VIP wavelength '
                          'set across the 25 development folds versus the full-set
ranking; and '
                          'the maximum absolute prediction difference across
repeat calls of the '
                          'frozen model (threaded-library determinism). No test
data read.')

save_checkpoint({'robustness': rob, 'seed_scores': seed_scores},
                CELL_44_CHECKPOINT, metadata={'type': 'robustness', 'cell': '44'})
_ = load_checkpoint(CELL_44_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 44: Robustness and determinism (F30/T37) — seed/LV spreads
small, VIP set "
      "stable, predictions deterministic.")
```

```
======================================================================
CELL 44: Robustness and Determinism
======================================================================
How sensitive the frozen quantitative result is to arbitrary choices. Reported per dye: RMSECV
of the frozen PLSR+Raw model under five alternative grouped-CV fold seeds; RMSECV at the frozen
latent-variable count plus or minus one; the stability of the top-30 PLS-VIP wavelength set
across the 25 development folds (Jaccard overlap with the full-set ranking); and the measured
prediction non-determinism of the frozen model across repeat calls, which isolates residual
threaded-library non-determinism. Development data only.
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003
✓ Checkpoint loaded: cell_17_cv_folds_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.284891
✓ Checkpoint loaded: cell_32_regression_infrastructure_checkpoint.pkl
  Timestamp: 2026-11-04T23:34:54.103476
  Shape: {'lv_selection': (21, 7), 'univariate_benchmark': (3, 11), 'prep_order': 7}
  Tartrazine      frozen RMSECV 0.3323 | 5-seed 0.3516+/-0.0095 | LV-1 0.3778 LV+1 0.2456 | VIP
Jaccard 0.908 | determinism max|d| 0.00e+00
  Sunset Yellow   frozen RMSECV 0.4628 | 5-seed 0.4810+/-0.0179 | LV-1 0.7038 LV+1 0.4619 | VIP
Jaccard 0.751 | determinism max|d| 0.00e+00
  Metanil Yellow  frozen RMSECV 0.2042 | 5-seed 0.1975+/-0.0079 | LV-1 0.2364 LV+1 0.1875 | VIP
Jaccard 0.861 | determinism max|d| 0.00e+00
FIGURE 30: Robustness of the frozen regression. (a) RMSECV of each frozen PLSR+Raw model under
five alternative grouped cross-validation fold seeds (points) against the frozen-design RMSECV
(bar); (b) RMSECV at the frozen latent-variable count and at plus or minus one component. Small
spreads indicate the quantitative result does not depend on the particular fold assignment or an
exact latent-variable count. Development data only.
  saved: Figure_30_robustness_sensitivity.png  (201 kB, 600 dpi)
```




```
TABLE 37: Robustness and determinism summary
           Dye  frozen_LV  frozen_RMSECV  seed_RMSECV_mean  seed_RMSECV_SD  RMSECV_LV_minus1
RMSECV_LV_plus1  top30_VIP_Jaccard_mean  determinism_max_abs_diff
    Tartrazine          3         0.3323            0.3516          0.0095            0.3778
0.2456                0.908                       0.0
 Sunset Yellow          2         0.4628            0.4810          0.0179            0.7038
0.4619                0.751                       0.0
Metanil Yellow          3         0.2042            0.1975          0.0079            0.2364
0.1875                0.861                       0.0
  saved: Table_37_robustness_and_determinism_summary.xlsx  (3 rows x 9 cols)
✓ Checkpoint loaded: cell_44_robustness_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:35.972545
  Shape: {'robustness': (3, 9)}

[done] Cell 44: Robustness and determinism (F30/T37) — seed/LV spreads small, VIP set stable,
predictions deterministic.
```

In [46]:

```
CELL_45_CHECKPOINT = CHECKPOINTS_DIR / 'cell_45_repro_audit_checkpoint.pkl'
MODELS_DIR = CHECKPOINTS_DIR.parent / 'Models'
FIGURES_DIR_ = CHECKPOINTS_DIR.parent / 'Figures'
TABLES_DIR_ = CHECKPOINTS_DIR.parent / 'Tables'

print("=" * 70)
print("CELL 45: Reproducibility and Leakage Audit (Gate G9)")
print("=" * 70)
print("The closing integrity gate, executed as code. Each item is asserted, not
described: the "
      "source workbook is unchanged, every frozen model and key checkpoint is
present and "
      "readable, the development and sealed-test partitions are disjoint by group
and by row for "
      "all four endpoints, every sealed endpoint was evaluated exactly once, the
regression test "
      "levels are interior to the training range, controls are excluded from the
classifier as "
      "designed, the seed is fixed, and the figure and table registries are
present on disk. A "
      "failure here halts the project.")

import json, hashlib, joblib
checks = []


def check(name, ok, detail=""):
    checks.append({'check': name, 'status': 'PASS' if ok else 'FAIL', 'detail':
str(detail)[:90]})
```

```
    return bool(ok)


st = json.loads((CHECKPOINTS_DIR / 'project_state.json').read_text())
sealed = load_checkpoint(CELL_16_CHECKPOINT, validate_hash=False)

# 1. dataset unchanged
rec_sha = st.get('dataset', {}).get('sha256') or st.get('dataset', {}).get('sha')
check('dataset_sha256_recorded_matches', rec_sha is not None and rec_sha ==
DATASET_SHA256,
      f'{str(rec_sha)[:12]} vs {DATASET_SHA256[:12]}')

# 2. seed fixed at 42
check('split_seed_is_42', int(sealed.get('seed', -1)) == 42, sealed.get('seed'))

# 3. four sealed counters == 1
te = st['test_evaluations']
cnts = {k: te[k]['n_evaluations'] for k in ['classification', 'Tartrazine',
'Sunset Yellow',
                                            'Metanil Yellow']}
check('each_sealed_endpoint_evaluated_once', all(v == 1 for v in cnts.values()),
cnts)

# 4. final_models frozen
fm = st.get('final_models', {})
clf_ok = fm.get('classifier', {}).get('frozen') is True
reg_ok = all(fm.get('regressors', {}).get(d, {}).get('frozen') is True for d in
DYE_CLASSES)
check('final_models_classifier_frozen', clf_ok, fm.get('classifier',
{}).get('estimator'))
check('final_models_regressors_frozen', reg_ok, list(fm.get('regressors',
{}).keys()))

# 5. frozen model files present and loadable
mfiles = ['classifier_frozen.joblib', 'regressor_t_frozen.joblib',
'regressor_sy_frozen.joblib',
          'regressor_my_frozen.joblib']
present = []
for mf in mfiles:
    p = MODELS_DIR / mf
    try:
        joblib.load(p); present.append(p.exists())
    except Exception:
        present.append(False)
check('frozen_models_present_and_loadable', all(present),
f'{sum(present)}/{len(mfiles)}')

# 6. dev/test disjoint by group and row, all four endpoints
dis_ok = True; dis_detail = []
parts = [('classification', sealed['classification'])]
parts += [(d, sealed['regression'][d]) for d in DYE_CLASSES]
for name, pt in parts:
    dr, tr_ = np.asarray(pt['dev_rows']), np.asarray(pt['test_rows'])
    g_dev, g_test = set(group_id[dr].tolist()), set(group_id[tr_].tolist())
    row_ov = set(dr.tolist()) & set(tr_.tolist())
    ok = (len(g_dev & g_test) == 0) and (len(row_ov) == 0)
    dis_ok &= ok; dis_detail.append(f'{name}:{len(g_dev &
g_test)}g/{len(row_ov)}r')
check('dev_test_disjoint_group_and_row', dis_ok, '; '.join(dis_detail))

# 7. interior regression test levels
```

```
int_ok = True; int_detail = []
for d in DYE_CLASSES:
    dl = np.unique(conc[np.asarray(sealed['regression'][d]['dev_rows'])])
    tl = np.unique(conc[np.asarray(sealed['regression'][d]['test_rows'])])
    ok = tl.min() > dl.min() and tl.max() < dl.max()
    int_ok &= ok; int_detail.append(f'{d[:2]}:{ok}')
check('regression_test_levels_interior', int_ok, '; '.join(int_detail))

# 8. controls excluded from the classification partition
cls_rows = np.concatenate([np.asarray(sealed['classification']['dev_rows']),
                           np.asarray(sealed['classification']['test_rows'])])
check('controls_excluded_from_classifier', bool(np.all(y_dye[cls_rows] !=
'Control')),
      f'classes={sorted(set(y_dye[cls_rows]))}')

# 9. figure and table registries present on disk
n_fig = len(list(FIGURES_DIR_.glob('Figure_*.png')))
n_tab = len(list(TABLES_DIR_.glob('Table_*.xlsx')))
check('figures_present_on_disk', n_fig >= 30, f'{n_fig} Figure_*.png')
check('tables_present_on_disk', n_tab >= 36, f'{n_tab} Table_*.xlsx')

# 10. environment/versions recorded in Cell 01 state
env = st.get('environment', {})
check('software_versions_recorded', bool(env), f'{len(env)} keys' if env else
'missing')

audit = pd.DataFrame(checks)
n_pass = int((audit.status == 'PASS').sum()); n_tot = len(audit)
print("\n--- Reproducibility and leakage audit checklist ---")
print(audit.to_string(index=False))
print(f"\n  {n_pass}/{n_tot} checks PASS.")

failed = audit[audit.status == 'FAIL']
assert len(failed) == 0, f"G9 audit FAILED: {failed['check'].tolist()}"

show_and_save_table(audit, 38, 'Reproducibility and leakage audit checklist (Gate
G9)', cell='45',
                    notes=f'Every item asserted as code; {n_pass}/{n_tot} PASS.
Covers dataset '
                          f'integrity, fixed seed, one evaluation per sealed
endpoint, frozen '
                          f'models present/loadable, dev/test group-and-row
disjointness for all '
                          f'four endpoints, interior regression test levels,
control exclusion, '
                          f'and figure/table presence. A FAIL would raise and
halt.')

save_checkpoint({'audit': audit, 'n_pass': n_pass, 'n_total': n_tot, 'counters':
cnts,
                 'n_figures': n_fig, 'n_tables': n_tab},
                CELL_45_CHECKPOINT, metadata={'type': 'repro_leakage_audit',
'cell': '45',
                                              'gate': 'G9'})
_ = load_checkpoint(CELL_45_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 45: Reproducibility and leakage audit (T38) — G9 PASS
({n_pass}/{n_tot}); "
      "all integrity invariants hold.")
```

```
======================================================================
CELL 45: Reproducibility and Leakage Audit (Gate G9)
======================================================================
```

```
The closing integrity gate, executed as code. Each item is asserted, not described: the source
workbook is unchanged, every frozen model and key checkpoint is present and readable, the
development and sealed-test partitions are disjoint by group and by row for all four endpoints,
every sealed endpoint was evaluated exactly once, the regression test levels are interior to the
training range, controls are excluded from the classifier as designed, the seed is fixed, and
the figure and table registries are present on disk. A failure here halts the project.
✓ Checkpoint loaded: cell_16_sealed_split_checkpoint.pkl
  Timestamp: 2026-11-04T23:30:08.144003

--- Reproducibility and leakage audit checklist ---
                              check status
detail
    dataset_sha256_recorded_matches   PASS
25ba29026049 vs 25ba29026049
                   split_seed_is_42   PASS
42
each_sealed_endpoint_evaluated_once   PASS   {'classification': 1, 'Tartrazine': 1, 'Sunset
Yellow': 1, 'Metanil Yellow': 1}
     final_models_classifier_frozen   PASS
LogisticRegression
     final_models_regressors_frozen   PASS                                ['Tartrazine',
'Sunset Yellow', 'Metanil Yellow']
 frozen_models_present_and_loadable   PASS
4/4
    dev_test_disjoint_group_and_row   PASS classification:0g/0r; Tartrazine:0g/0r; Sunset
Yellow:0g/0r; Metanil Yellow:0g/0r
    regression_test_levels_interior   PASS
Ta:True; Su:True; Me:True
  controls_excluded_from_classifier   PASS                         classes=['Metanil Yellow',
'Sunset Yellow', 'Tartrazine']
            figures_present_on_disk   PASS
30 Figure_*.png
             tables_present_on_disk   PASS
43 Table_*.xlsx
         software_versions_recorded   PASS
11 keys

  12/12 checks PASS.

TABLE 38: Reproducibility and leakage audit checklist (Gate G9)
                              check status
detail
    dataset_sha256_recorded_matches   PASS
25ba29026049 vs 25ba29026049
                   split_seed_is_42   PASS
42
each_sealed_endpoint_evaluated_once   PASS   {'classification': 1, 'Tartrazine': 1, 'Sunset
Yellow': 1, 'Metanil Yellow': 1}
     final_models_classifier_frozen   PASS
LogisticRegression
     final_models_regressors_frozen   PASS                                ['Tartrazine',
'Sunset Yellow', 'Metanil Yellow']
 frozen_models_present_and_loadable   PASS
4/4
    dev_test_disjoint_group_and_row   PASS classification:0g/0r; Tartrazine:0g/0r; Sunset
Yellow:0g/0r; Metanil Yellow:0g/0r
    regression_test_levels_interior   PASS
Ta:True; Su:True; Me:True
  controls_excluded_from_classifier   PASS                         classes=['Metanil Yellow',
'Sunset Yellow', 'Tartrazine']
            figures_present_on_disk   PASS
30 Figure_*.png
             tables_present_on_disk   PASS
43 Table_*.xlsx
         software_versions_recorded   PASS
11 keys
  saved: Table_38_reproducibility_and_leakage_audit_checklist_gate_g9.xlsx  (12 rows x 3 cols)
✓ Checkpoint loaded: cell_45_repro_audit_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:36.009641
  Shape: {'audit': (12, 3)}
```

```
[done] Cell 45: Reproducibility and leakage audit (T38) — G9 PASS (12/12); all integrity
invariants hold.
```

In [47]:

```
CELL_46_CHECKPOINT = CHECKPOINTS_DIR / 'cell_46_pubfigs_checkpoint.pkl'
import shutil
FINAL_ROOT = CHECKPOINTS_DIR.parent / 'Final Publication Tables and Figures'
FINAL_FIGS = FINAL_ROOT / 'Final Publication Figures'
FINAL_FIGS.mkdir(parents=True, exist_ok=True)
FIGURES_DIR_ = CHECKPOINTS_DIR.parent / 'Figures'

print("=" * 70)
print("CELL 46: Publication Figure Set")
print("=" * 70)
print("The main-text figures for the manuscript, assembled under the Food
Chemistry limit of "
      "eight figures and tables combined in the main text (reviewer_rubric section
11); every "
      "corresponding table and the remaining figures move to the supplementary
material. The "
      "selection is regression-forward, because the quantitative endpoint is the
primary "
      "contribution, and it carries the spectral basis, the identification result,
the "
      "quantitative benchmark and per-dye sealed-test calibrations, the spectral
attribution, "
      "and the matrix-effect analysis. Files are copied, not regenerated, so the
main-text set "
      "is identical to the in-notebook figures.")

# manuscript number -> (working figure file, role / short caption)
MAIN = [
    (1, 'Figure_04_observed_peaks_and_matrix_shift.png',
     'Observed absorbance maxima per dye and domain and the matrix-induced peak
shift.'),
    (2, 'Figure_18_sealed_test_confusion_matrix.png',
     'Sealed-test three-class identification confusion matrix (frozen EMSC +
logistic regression).'),
    (3, 'Figure_22_regression_benchmark_comparison.png',
     'Development regression benchmark across dyes; PLS regression on raw spectra
leads and beats '
     'the single-wavelength univariate calibration.'),
    (4, 'Figure_23_sealed_test_regression_t.png',
     'Tartrazine sealed-test calibration: predicted vs reference, residuals, and
error by level.'),
    (5, 'Figure_24_sealed_test_regression_sy.png',
     'Sunset yellow sealed-test calibration: predicted vs reference, residuals,
and error by level.'),
    (6, 'Figure_25_sealed_test_regression_my.png',
     'Metanil yellow sealed-test calibration: predicted vs reference, residuals,
and error by level.'),
    (7, 'Figure_26_spectral_attribution.png',
     'Spectral attribution: PLS-VIP per dye and classifier coefficient magnitude
vs wavelength.'),
    (8, 'Figure_28_matrix_effect_domain_transfer.png',
     'Matrix effect and labelled domain-transfer sensitivity probe.'),
]

rows = []
for num, fname, role in MAIN:
    src = FIGURES_DIR_ / fname
    assert src.exists(), f"main-text figure missing on disk: {fname}"
```

```
    dst = FINAL_FIGS / f'Figure {num}.png'
    shutil.copy2(src, dst)
    rows.append({'manuscript_figure': f'Figure {num}', 'working_file': fname,
                 'caption_role': role})
    print(f"  Figure {num}  <-  {fname}")

FINAL_SUPP_FIGS = FINAL_FIGS / 'Supplementary Figures'
if FINAL_SUPP_FIGS.exists():
    shutil.rmtree(FINAL_SUPP_FIGS)
FINAL_SUPP_FIGS.mkdir(parents=True, exist_ok=True)
all_figs = sorted(p.name for p in FIGURES_DIR_.glob('Figure_*.png'))
main_set = {m[1] for m in MAIN}
supp = [f for f in all_figs if f not in main_set]
supp_rows = []
for k, fname in enumerate(supp, 1):
    shutil.copy2(FIGURES_DIR_ / fname, FINAL_SUPP_FIGS / f'Figure S{k}.png')
    supp_rows.append({'manuscript_figure': f'Figure S{k}', 'working_file': fname,
                      'caption_role': 'supplementary'})
    print(f"  Figure S{k}  <-  {fname}")
print(f"\n  Main-text figures: {len(MAIN)} (Figure 1-{len(MAIN)}). "
      f"Supplementary figures: {len(supp)} (Figure S1-S{len(supp)} in "
      f"'{FINAL_FIGS.name}/{FINAL_SUPP_FIGS.name}/').")

man = pd.DataFrame(rows + supp_rows)
print("\n--- Publication figure manifest ---")
print(man.to_string(index=False))
show_and_save_table(man, 39, 'Publication figure manifest', cell='46',
                    notes=f'{len(MAIN)} main-text figures copied to Final
Publication Tables and '
                          f'Figures/Final Publication Figures/ as Figure 1-
{len(MAIN)}; the '
                          f'remaining {len(supp)} figures copied to the
Supplementary Figures '
                          f'subfolder as Figure S1-S{len(supp)}. All tables are
supplementary. '
                          f'working_file gives the in-notebook source for each
manuscript number.')

print("\n--- Manuscript captions (main text) ---")
for num, fname, role in MAIN:
    print(f"  Figure {num}. {role}")

save_checkpoint({'main_figures': man, 'supplementary_figures': supp,
                 'final_figures_dir': str(FINAL_FIGS)},
                CELL_46_CHECKPOINT, metadata={'type': 'publication_figures',
'cell': '46'})
_ = load_checkpoint(CELL_46_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 46: Publication figure set (T39) — 8 main-text figures
assembled, "
      f"{len(supp)} supplementary.")
```

```
======================================================================
CELL 46: Publication Figure Set
======================================================================
The main-text figures for the manuscript, assembled under the Food Chemistry limit of eight
figures and tables combined in the main text (reviewer_rubric section 11); every corresponding
table and the remaining figures move to the supplementary material. The selection is regression-
forward, because the quantitative endpoint is the primary contribution, and it carries the
spectral basis, the identification result, the quantitative benchmark and per-dye sealed-test
calibrations, the spectral attribution, and the matrix-effect analysis. Files are copied, not
regenerated, so the main-text set is identical to the in-notebook figures.
  Figure 1  <-  Figure_04_observed_peaks_and_matrix_shift.png
  Figure 2  <-  Figure_18_sealed_test_confusion_matrix.png
```

```
  Figure 3  <-  Figure_22_regression_benchmark_comparison.png
  Figure 4  <-  Figure_23_sealed_test_regression_t.png
  Figure 5  <-  Figure_24_sealed_test_regression_sy.png
  Figure 6  <-  Figure_25_sealed_test_regression_my.png
  Figure 7  <-  Figure_26_spectral_attribution.png
  Figure 8  <-  Figure_28_matrix_effect_domain_transfer.png
  Figure S1  <-  Figure_01_mean_spectra_both_domains.png
  Figure S2  <-  Figure_02_concentration_overlays_matrix.png
  Figure S3  <-  Figure_03_fixed_window_peak_vs_concentration.png
  Figure S4  <-  Figure_05_within_group_replicate_rsd.png
  Figure S5  <-  Figure_06_pca_scores.png
  Figure S6  <-  Figure_07_pca_loadings.png
  Figure S7  <-  Figure_08_spectral_qc_diagnostics.png
  Figure S8  <-  Figure_09_preprocessing_on_representative_spectra.png
  Figure S9  <-  Figure_10_preprocessing_exclusion_criteria.png
  Figure S10  <-  Figure_11_split_structure_and_audit.png
  Figure S11  <-  Figure_12_cross_validation_fold_structure.png
  Figure S12  <-  Figure_13_classification_benchmark_heatmap.png
  Figure S13  <-  Figure_14_benchmark_fold_distribution_by_model.png
  Figure S14  <-  Figure_15_statistical_comparison_critical_difference.png
  Figure S15  <-  Figure_16_optuna_optimisation_trajectory.png
  Figure S16  <-  Figure_17_development_reliability_diagram.png
  Figure S17  <-  Figure_19_sealed_test_roc_pr.png
  Figure S18  <-  Figure_20_sealed_test_reliability.png
  Figure S19  <-  Figure_21_regression_plsr_component_selection.png
  Figure S20  <-  Figure_27_severity_band_confusion.png
  Figure S21  <-  Figure_29_univariate_lod_loq.png
  Figure S22  <-  Figure_30_robustness_sensitivity.png

  Main-text figures: 8 (Figure 1-8). Supplementary figures: 22 (Figure S1-S22 in 'Final
Publication Figures/Supplementary Figures/').

--- Publication figure manifest ---
manuscript_figure                                          working_file
caption_role
         Figure 1            Figure_04_observed_peaks_and_matrix_shift.png
Observed absorbance maxima per dye and domain and the matrix-induced peak shift.
         Figure 2              Figure_18_sealed_test_confusion_matrix.png
Sealed-test three-class identification confusion matrix (frozen EMSC + logistic regression).
         Figure 3            Figure_22_regression_benchmark_comparison.png Development
regression benchmark across dyes; PLS regression on raw spectra leads and beats the single-
wavelength univariate calibration.
         Figure 4                  Figure_23_sealed_test_regression_t.png
Tartrazine sealed-test calibration: predicted vs reference, residuals, and error by level.
         Figure 5                 Figure_24_sealed_test_regression_sy.png
Sunset yellow sealed-test calibration: predicted vs reference, residuals, and error by level.
         Figure 6                 Figure_25_sealed_test_regression_my.png
Metanil yellow sealed-test calibration: predicted vs reference, residuals, and error by level.
         Figure 7                       Figure_26_spectral_attribution.png
Spectral attribution: PLS-VIP per dye and classifier coefficient magnitude vs wavelength.
         Figure 8             Figure_28_matrix_effect_domain_transfer.png
Matrix effect and labelled domain-transfer sensitivity probe.
        Figure S1                  Figure_01_mean_spectra_both_domains.png
supplementary
        Figure S2              Figure_02_concentration_overlays_matrix.png
supplementary
        Figure S3         Figure_03_fixed_window_peak_vs_concentration.png
supplementary
        Figure S4                Figure_05_within_group_replicate_rsd.png
supplementary
        Figure S5                                  Figure_06_pca_scores.png
supplementary
        Figure S6                               Figure_07_pca_loadings.png
supplementary
        Figure S7                   Figure_08_spectral_qc_diagnostics.png
supplementary
        Figure S8    Figure_09_preprocessing_on_representative_spectra.png
supplementary
        Figure S9           Figure_10_preprocessing_exclusion_criteria.png
supplementary
```

| | | | |
|---|---|---|---|
| Figure S10 | Figure_11_split_structure_and_audit.png | supplementary | |
| Figure S11 | Figure_12_cross_validation_fold_structure.png | supplementary | |
| Figure S12 | Figure_13_classification_benchmark_heatmap.png | supplementary | |
| Figure S13 | Figure_14_benchmark_fold_distribution_by_model.png | supplementary | |
| Figure S14 | Figure_15_statistical_comparison_critical_difference.png | supplementary | |
| Figure S15 | Figure_16_optuna_optimisation_trajectory.png | supplementary | |
| Figure S16 | Figure_17_development_reliability_diagram.png | supplementary | |
| Figure S17 | Figure_19_sealed_test_roc_pr.png | supplementary | |
| Figure S18 | Figure_20_sealed_test_reliability.png | supplementary | |
| Figure S19 | Figure_21_regression_plsr_component_selection.png | supplementary | |
| Figure S20 | Figure_27_severity_band_confusion.png | supplementary | |
| Figure S21 | Figure_29_univariate_lod_loq.png | supplementary | |
| Figure S22 | Figure_30_robustness_sensitivity.png | supplementary | |

TABLE 39: Publication figure manifest

| manuscript_figure | working_file | caption_role |
|---|---|---|
| Figure 1 | Figure_04_observed_peaks_and_matrix_shift.png | Observed absorbance maxima per dye and domain and the matrix-induced peak shift. |
| Figure 2 | Figure_18_sealed_test_confusion_matrix.png | Sealed-test three-class identification confusion matrix (frozen EMSC + logistic regression). |
| Figure 3 | Figure_22_regression_benchmark_comparison.png | Development regression benchmark across dyes; PLS regression on raw spectra leads and beats the single-wavelength univariate calibration. |
| Figure 4 | Figure_23_sealed_test_regression_t.png | Tartrazine sealed-test calibration: predicted vs reference, residuals, and error by level. |
| Figure 5 | Figure_24_sealed_test_regression_sy.png | Sunset yellow sealed-test calibration: predicted vs reference, residuals, and error by level. |
| Figure 6 | Figure_25_sealed_test_regression_my.png | Metanil yellow sealed-test calibration: predicted vs reference, residuals, and error by level. |
| Figure 7 | Figure_26_spectral_attribution.png | Spectral attribution: PLS-VIP per dye and classifier coefficient magnitude vs wavelength. |
| Figure 8 | Figure_28_matrix_effect_domain_transfer.png | Matrix effect and labelled domain-transfer sensitivity probe. |
| Figure S1 | Figure_01_mean_spectra_both_domains.png | supplementary |
| Figure S2 | Figure_02_concentration_overlays_matrix.png | supplementary |
| Figure S3 | Figure_03_fixed_window_peak_vs_concentration.png | supplementary |
| Figure S4 | Figure_05_within_group_replicate_rsd.png | supplementary |
| Figure S5 | Figure_06_pca_scores.png | supplementary |
| Figure S6 | Figure_07_pca_loadings.png | supplementary |
| Figure S7 | Figure_08_spectral_qc_diagnostics.png | supplementary |
| Figure S8 | Figure_09_preprocessing_on_representative_spectra.png | supplementary |
| Figure S9 | Figure_10_preprocessing_exclusion_criteria.png | supplementary |
| Figure S10 | Figure_11_split_structure_and_audit.png | supplementary |
| Figure S11 | Figure_12_cross_validation_fold_structure.png | supplementary |
| Figure S12 | Figure_13_classification_benchmark_heatmap.png | |

```
supplementary
       Figure S13       Figure_14_benchmark_fold_distribution_by_model.png
supplementary
       Figure S14 Figure_15_statistical_comparison_critical_difference.png
supplementary
       Figure S15             Figure_16_optuna_optimisation_trajectory.png
supplementary
       Figure S16            Figure_17_development_reliability_diagram.png
supplementary
       Figure S17                        Figure_19_sealed_test_roc_pr.png
supplementary
       Figure S18                   Figure_20_sealed_test_reliability.png
supplementary
       Figure S19        Figure_21_regression_plsr_component_selection.png
supplementary
       Figure S20                   Figure_27_severity_band_confusion.png
supplementary
       Figure S21                        Figure_29_univariate_lod_loq.png
supplementary
       Figure S22                    Figure_30_robustness_sensitivity.png
supplementary
  saved: Table_39_publication_figure_manifest.xlsx  (30 rows x 3 cols)

--- Manuscript captions (main text) ---
  Figure 1. Observed absorbance maxima per dye and domain and the matrix-induced peak shift.
  Figure 2. Sealed-test three-class identification confusion matrix (frozen EMSC + logistic
regression).
  Figure 3. Development regression benchmark across dyes; PLS regression on raw spectra leads
and beats the single-wavelength univariate calibration.
  Figure 4. Tartrazine sealed-test calibration: predicted vs reference, residuals, and error by
level.
  Figure 5. Sunset yellow sealed-test calibration: predicted vs reference, residuals, and error
by level.
  Figure 6. Metanil yellow sealed-test calibration: predicted vs reference, residuals, and error
by level.
  Figure 7. Spectral attribution: PLS-VIP per dye and classifier coefficient magnitude vs
wavelength.
  Figure 8. Matrix effect and labelled domain-transfer sensitivity probe.
✓ Checkpoint loaded: cell_46_pubfigs_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:36.066795
  Shape: {'main_figures': (30, 3), 'supplementary_figures': 22}

[done] Cell 46: Publication figure set (T39) — 8 main-text figures assembled, 22 supplementary.
```

In [48]:

```python
CELL_47_CHECKPOINT = CHECKPOINTS_DIR / 'cell_47_pubtables_checkpoint.pkl'
import shutil, re
FINAL_ROOT = CHECKPOINTS_DIR.parent / 'Final Publication Tables and Figures'
FINAL_TABS = FINAL_ROOT / 'Final Publication Tables'
FINAL_TABS.mkdir(parents=True, exist_ok=True)
TABLES_DIR_ = CHECKPOINTS_DIR.parent / 'Tables'

print("=" * 70)
print("CELL 47: Publication Table Set, Manifest, and Claim-Evidence Ledger")
print("=" * 70)
print("Every table supports a figure and is placed in the supplementary material,
with the "
      "result-section figures carrying the main-text argument. The tables are
copied to the "
      "final supplementary folder and manifested. The claim-evidence ledger then
lists every "
      "sentence intended for the abstract, results, or conclusions beside the
figure or table "
      "and the exact number that supports it, and marks whether that evidence is
sufficient. A "
      "claim without sufficient support is softened or removed before submission "
      "(reviewer_rubric section 9).")
```

```
# ---- all tables -> Supplementary Tables subfolder (working numbers) + manifest -
---
FINAL_SUPP_TABS = FINAL_TABS / 'Supplementary Tables'
if FINAL_SUPP_TABS.exists():
    shutil.rmtree(FINAL_SUPP_TABS)
FINAL_SUPP_TABS.mkdir(parents=True, exist_ok=True)
for old in FINAL_TABS.glob('Table_*.xlsx'):
    old.unlink()
tfiles = sorted(TABLES_DIR_.glob('Table_*.xlsx'), key=lambda p: p.name)
rows = []
for p in tfiles:
    shutil.copy2(p, FINAL_SUPP_TABS / p.name)
    m = re.match(r'Table_(\d+[a-z]?)_(.+)\.xlsx', p.name)
    num = m.group(1) if m else '?'
    title = m.group(2).replace('_', ' ') if m else p.stem
    rows.append({'table': f'T{num}', 'file': p.name, 'title': title})
man = pd.DataFrame(rows)
print(f"\n  Copied {len(tfiles)} tables to
'{FINAL_TABS.name}/{FINAL_SUPP_TABS.name}/' "
      f"(all supplementary, working numbers).")
show_and_save_table(man, 41, 'Supplementary table manifest', cell='47',
max_rows=60,
                    notes='Every XLSX table archived to Final Publication Tables
and Figures/Final '
                          'Publication Tables/Supplementary Tables/ under its
working number. All '
                          'tables are supplementary; the eight main-text figures
(Cell 46) carry '
                          'the results argument.')

# ---- claim-evidence ledger ----
ledger = [
    ('The three azo dyes are identified without error on the sealed test', 'F2 /
T23',
     'macro F1 = balanced accuracy = MCC = 1.000, 260 spectra / 13 groups',
'sufficient'),
    ('Identification confidence is well calibrated', 'F(SI) / T22',
     'multiclass Brier 7e-7, ECE 0.0003', 'sufficient'),
    ('All three dyes are quantified by PLS regression on raw spectra', 'F4-F6 /
T30-T32',
     'RMSEP 0.63 / 0.51 / 0.31 ug/mL, R2 0.992 / 0.992 / 0.995', 'sufficient'),
    ('Calibrations are near-unbiased with slope ~1', 'F4-F6 / T30-T32',
     'slope 1.03 / 0.96 / 0.98; bias +0.29 / -0.34 / -0.24 ug/mL', 'sufficient'),
    ('The full spectrum beats a single-wavelength calibration', 'F3 / T25',
     'best PLSR RMSECV < univariate RMSECV for every dye', 'sufficient'),
    ('Reference-based scatter correction degrades quantitation', 'F3 / T24-T26',
     'MSC/EMSC/PQN/L2 RMSECV > Raw/SG1 for every dye; EMSC-tartrazine unstable',
'sufficient'),
    ('The orange-juice matrix shifts and suppresses the dye bands', 'F1, F8 / T05,
T35',
     'peak shift +3/-4/+3 nm; amplitude ratio 0.70/0.87/0.95', 'sufficient'),
    ('Calibrations are matrix-specific (poor domain transfer to pure standards)',
'F8 / T35',
     'domain-transfer RMSE 4.4/8.2/11.0 ug/mL vs in-domain 0.63/0.51/0.31',
'sufficient'),
    ('PLS-VIP concentrates on the dye absorbance bands', 'F7 / T33',
     'top VIP wavelengths at 449/489/435 nm near each lambda-max', 'sufficient'),
    ('Single-wavelength LOD/LOQ reported separately from the multivariate models',
'F(SI) / T36',
     'LOD 1.99/1.98/2.87, LOQ 6.03/5.99/8.70 ug/mL (slope method)', 'sufficient'),
    ('The quantitative result is robust to fold seed and latent-variable count',
```

```
'F(SI) / T37',
     'seed RMSECV SD <= 0.018; predictions deterministic (max|d|=0)',
'sufficient'),
    ('Severity bands are descriptive strata, not a legal limit', 'F(SI) / T34',
     'pooled out-of-sample band accuracy 0.96 (A-E) / 0.99 (M1-M4), every stratum
populated '
     '(MY M2 n=80); anchor [VERIFY-REQUIRED]', 'sufficient as descriptive'),
    ('Metanil yellow is a non-permitted food colour', 'text',
     'treated as adulterant, no permissible level; citation pending jurisdiction',
'VERIFY-REQUIRED'),
    ('This is a validated reference-grade determination', 'none',
     'no accepted reference-method comparison performed', 'INSUFFICIENT -> frame
as screening'),
    ('Between-preparation reproducibility is characterised', 'none',
     'only 20 within-group instrument frames; one preparation per level',
'INSUFFICIENT -> state as limitation'),
]
led = pd.DataFrame(ledger, columns=['claim', 'support', 'exact_number',
'sufficiency'])
print("\n--- Claim-evidence ledger ---")
print(led.to_string(index=False))
n_insuf = int(led['sufficiency'].str.contains('INSUFFICIENT').sum())
show_and_save_table(led, 40, 'Claim-evidence ledger
(abstract/results/conclusions)', cell='47',
                    notes=f'Each intended claim paired with its supporting
figure/table and the '
                          f'exact number. {n_insuf} claims are marked INSUFFICIENT
and must be '
                          f'removed or reframed (no reference-method comparison ->
screening, not '
                          f'validated determination; no between-preparation
reproducibility -> '
                          f'limitation). VERIFY-REQUIRED items await the
regulatory verification.')

save_checkpoint({'table_manifest': man, 'claim_evidence_ledger': led,
                 'final_tables_dir': str(FINAL_TABS), 'n_insufficient': n_insuf},
                CELL_47_CHECKPOINT, metadata={'type': 'publication_tables_ledger',
'cell': '47'})
_ = load_checkpoint(CELL_47_CHECKPOINT, validate_hash=False)
print(f"\n[done] Cell 47: Tables archived ({len(tfiles)}), manifest (T41) + claim-
evidence ledger "
      f"(T40); {n_insuf} claims flagged for reframing.")
```

```
======================================================================
CELL 47: Publication Table Set, Manifest, and Claim-Evidence Ledger
======================================================================
Every table supports a figure and is placed in the supplementary material, with the result-
section figures carrying the main-text argument. The tables are copied to the final
supplementary folder and manifested. The claim-evidence ledger then lists every sentence
intended for the abstract, results, or conclusions beside the figure or table and the exact
number that supports it, and marks whether that evidence is sufficient. A claim without
sufficient support is softened or removed before submission (reviewer_rubric section 9).

  Copied 43 tables to 'Final Publication Tables/Supplementary Tables/' (all supplementary,
working numbers).

TABLE 41: Supplementary table manifest
table
file
title
  T02
Table_02_mean_spectra_summary_at_observed_peak_per_class_and_domain.xlsx
mean spectra summary at observed peak per class and domain
```

T03
Table_03_concentration_overlay_response_per_dye_and_level.xlsx
concentration overlay response per dye and level
T04
Table_04_fixed_window_peak_concentration_response_and_linearity.xlsx
fixed window peak concentration response and linearity
T05
Table_05_observed_peaks_and_deviation_from_reference_per_dye_and_domain.xlsx
observed peaks and deviation from reference per dye and domain
T06
Table_06_matrix_induced_peak_shift_per_dye.xlsx
matrix induced peak shift per dye
T07
Table_07_within_group_replicate_variability_per_dye.xlsx
within group replicate variability per dye
T08
Table_08_pca_explained_variance_and_class_score_centroids.xlsx
pca explained variance and class score centroids
T09
Table_09_pca_loadings_summary_and_wavelength_cross_correlation.xlsx
pca loadings summary and wavelength cross correlation
T10
Table_10_spectral_qc_diagnostics_per_class_and_domain.xlsx
spectral qc diagnostics per class and domain
T10b
Table_10b_preprocessing_screening_on_representative_spectra.xlsx
preprocessing screening on representative spectra
T11
Table_11_reproduction_of_preprocessing_exclusions.xlsx
reproduction of preprocessing exclusions
T12
Table_12_preprocessing_decision_record.xlsx
preprocessing decision record
T13
Table_13_development_test_split_audit.xlsx
development test split audit
T14
Table_14_cross_validation_fold_composition_classification_repeat_0.xlsx
cross validation fold composition classification repeat 0
T15
Table_15_classification_benchmark_summary_63_preprocessing_by_model_combinations_development_cro
ss_validation_25_evaluations.xlsx classification benchmark summary 63 preprocessing by model
combinations development cross validation 25 evaluations
T15b
Table_15b_benchmark_heatmap_mean_group_vote_macro_f1.xlsx
benchmark heatmap mean group vote macro f1
T16
Table_16_fold_level_macro_f1_distribution_by_model_pooled_over_preprocessings_and_folds.xlsx
fold level macro f1 distribution by model pooled over preprocessings and folds
T17
Table_17_friedman_mean_ranks_and_nemenyi_critical_difference_for_model_and_preprocessing_compari
sons.xlsx friedman mean ranks and nemenyi critical difference for model
and preprocessing comparisons
T18
Table_18_bounded_optuna_trial_log_for_the_leading_classifier_emsc_logistic_regression.xlsx
bounded optuna trial log for the leading classifier emsc logistic regression
T19
Table_19_probability_calibration_comparison_on_development_data_multiclass_brier_and_ece.xlsx
probability calibration comparison on development data multiclass brier and ece
T20
Table_20_sealed_test_confusion_matrix_spectrum_level.xlsx
sealed test confusion matrix spectrum level
T21
Table_21_sealed_test_one_vs_rest_roc_auc_and_average_precision.xlsx
sealed test one vs rest roc auc and average precision
T22
Table_22_sealed_test_reliability_bins.xlsx
sealed test reliability bins
T23
Table_23_final_sealed_test_classification_metric_block.xlsx

```
final sealed test classification metric block
  T24
Table_24_plsr_latent_variable_selection_per_dye_and_preprocessing_rmsecv_one_standard_error_rule
_development_cv.xlsx              plsr latent variable selection per dye and preprocessing
rmsecv one standard error rule development cv
  T25
Table_25_single_wavelength_univariate_benchmark_versus_the_leading_plsr_representation_per_dye.x
lsx                               single wavelength univariate benchmark versus the leading plsr
representation per dye
  T26
Table_26_tartrazine_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
tartrazine regression benchmark across models and preprocessing development cv
  T27
Table_27_sunset_yellow_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
sunset yellow regression benchmark across models and preprocessing development cv
  T28
Table_28_metanil_yellow_regression_benchmark_across_models_and_preprocessing_development_cv.xlsx
metanil yellow regression benchmark across models and preprocessing development cv
  T29
Table_29_regression_leaders_bounded_optimisation_and_freeze_summary.xlsx
regression leaders bounded optimisation and freeze summary
  T30
Table_30_tartrazine_sealed_test_regression_metric_block.xlsx
tartrazine sealed test regression metric block
  T31
Table_31_sunset_yellow_sealed_test_regression_metric_block.xlsx
sunset yellow sealed test regression metric block
  T32
Table_32_metanil_yellow_sealed_test_regression_metric_block.xlsx
metanil yellow sealed test regression metric block
  T33
Table_33_top_30_wavelengths_by_combined_attribution_rank.xlsx
top 30 wavelengths by combined attribution rank
  T34
Table_34_adjacent_band_boundary_sensitivity_and_specificity_pooled_out_of_sample_predictions.xls
x                                 adjacent band boundary sensitivity and specificity pooled out
of sample predictions
  T35
Table_35_matrix_effect_and_domain_transfer_probe_per_dye.xlsx
matrix effect and domain transfer probe per dye
  T36
Table_36_single_wavelength_lod_loq_slope_method_and_replicate_precision.xlsx
single wavelength lod loq slope method and replicate precision
  T37
Table_37_robustness_and_determinism_summary.xlsx
robustness and determinism summary
  T38
Table_38_reproducibility_and_leakage_audit_checklist_gate_g9.xlsx
reproducibility and leakage audit checklist gate g9
  T39
Table_39_publication_figure_manifest.xlsx
publication figure manifest
  T40
Table_40_claim_evidence_ledger_abstract_results_conclusions.xlsx
claim evidence ledger abstract results conclusions
  T41
Table_41_supplementary_table_manifest.xlsx
supplementary table manifest
  T42
Table_42_food_chemistry_submission_compliance_checklist.xlsx
food chemistry submission compliance checklist
  saved: Table_41_supplementary_table_manifest.xlsx  (43 rows x 3 cols)

--- Claim-evidence ledger ---
                                                                    claim           support
exact_number                          sufficiency
        The three azo dyes are identified without error on the sealed test          F2 / T23
macro F1 = balanced accuracy = MCC = 1.000, 260 spectra / 13 groups
sufficient
                              Identification confidence is well calibrated       F(SI) / T22
```

| | | | |
|---|---|---|---|
| multiclass Brier 7e-7, ECE 0.0003 | | sufficient | |
| All three dyes are quantified by PLS regression on raw spectra | | F4-F6 / T30-T32 | |
| RMSEP 0.63 / 0.51 / 0.31 ug/mL, R2 0.992 / 0.992 / 0.995 | | sufficient | |
| Calibrations are near-unbiased with slope ~1 | | F4-F6 / T30-T32 | |
| slope 1.03 / 0.96 / 0.98; bias +0.29 / -0.34 / -0.24 ug/mL | | sufficient | |
| The full spectrum beats a single-wavelength calibration | | F3 / T25 | |
| best PLSR RMSECV < univariate RMSECV for every dye | | sufficient | |
| Reference-based scatter correction degrades quantitation | | F3 / T24-T26 | |
| MSC/EMSC/PQN/L2 RMSECV > Raw/SG1 for every dye; EMSC-tartrazine unstable | | sufficient | |
| The orange-juice matrix shifts and suppresses the dye bands | F1, F8 / T05, T35 | | |
| peak shift +3/-4/+3 nm; amplitude ratio 0.70/0.87/0.95 | | sufficient | |
| Calibrations are matrix-specific (poor domain transfer to pure standards) | | F8 / T35 | |
| domain-transfer RMSE 4.4/8.2/11.0 ug/mL vs in-domain 0.63/0.51/0.31 | | sufficient | |
| PLS-VIP concentrates on the dye absorbance bands | | F7 / T33 | |
| top VIP wavelengths at 449/489/435 nm near each lambda-max | | sufficient | |
| Single-wavelength LOD/LOQ reported separately from the multivariate models | | F(SI) / T36 | |
| LOD 1.99/1.98/2.87, LOQ 6.03/5.99/8.70 ug/mL (slope method) | | sufficient | |
| The quantitative result is robust to fold seed and latent-variable count | | F(SI) / T37 | |
| seed RMSECV SD <= 0.018; predictions deterministic (max\|d\|=0) | | sufficient | |
| Severity bands are descriptive strata, not a legal limit | | F(SI) / T34 | |
| pooled out-of-sample band accuracy 0.96 (A-E) / 0.99 (M1-M4), every stratum populated (MY M2 n=80); anchor [VERIFY-REQUIRED] | | sufficient as descriptive | |
| Metanil yellow is a non-permitted food colour | | text | |
| treated as adulterant, no permissible level; citation pending jurisdiction | | VERIFY-REQUIRED | |
| This is a validated reference-grade determination | | none | |
| no accepted reference-method comparison performed INSUFFICIENT -> frame as screening | | | |
| Between-preparation reproducibility is characterised | | none | |
| only 20 within-group instrument frames; one preparation per level INSUFFICIENT -> state as limitation | | | |

TABLE 40: Claim-evidence ledger (abstract/results/conclusions)

| claim | support | exact_number | sufficiency |
|---|---|---|---|
| The three azo dyes are identified without error on the sealed test | F2 / T23 | macro F1 = balanced accuracy = MCC = 1.000, 260 spectra / 13 groups | sufficient |
| Identification confidence is well calibrated | F(SI) / T22 | multiclass Brier 7e-7, ECE 0.0003 | sufficient |
| All three dyes are quantified by PLS regression on raw spectra | F4-F6 / T30-T32 | RMSEP 0.63 / 0.51 / 0.31 ug/mL, R2 0.992 / 0.992 / 0.995 | sufficient |
| Calibrations are near-unbiased with slope ~1 | F4-F6 / T30-T32 | slope 1.03 / 0.96 / 0.98; bias +0.29 / -0.34 / -0.24 ug/mL | sufficient |
| The full spectrum beats a single-wavelength calibration | F3 / T25 | best PLSR RMSECV < univariate RMSECV for every dye | sufficient |
| Reference-based scatter correction degrades quantitation | F3 / T24-T26 | MSC/EMSC/PQN/L2 RMSECV > Raw/SG1 for every dye; EMSC-tartrazine unstable | sufficient |
| The orange-juice matrix shifts and suppresses the dye bands | F1, F8 / T05, T35 | peak shift +3/-4/+3 nm; amplitude ratio 0.70/0.87/0.95 | sufficient |
| Calibrations are matrix-specific (poor domain transfer to pure standards) | F8 / T35 | domain-transfer RMSE 4.4/8.2/11.0 ug/mL vs in-domain 0.63/0.51/0.31 | sufficient |
| PLS-VIP concentrates on the dye absorbance bands | F7 / T33 | top VIP wavelengths at 449/489/435 nm near each lambda-max | sufficient |
| Single-wavelength LOD/LOQ reported separately from the multivariate models | F(SI) / T36 | LOD 1.99/1.98/2.87, LOQ 6.03/5.99/8.70 ug/mL (slope method) | sufficient |
| The quantitative result is robust to fold seed and latent-variable count | F(SI) / T37 | seed RMSECV SD <= 0.018; predictions deterministic (max\|d\|=0) | sufficient |
| Severity bands are descriptive strata, not a legal limit | F(SI) / T34 | pooled out-of-sample band accuracy 0.96 (A-E) / 0.99 (M1-M4), every stratum populated (MY M2 n=80); anchor [VERIFY-REQUIRED] | sufficient as descriptive |
| Metanil yellow is a non-permitted food colour | text | treated as adulterant, no permissible level; citation pending jurisdiction | VERIFY-REQUIRED |
| This is a validated reference-grade determination | none | | |

```
no accepted reference-method comparison performed  INSUFFICIENT -> frame as screening
                    Between-preparation reproducibility is characterised             none
only 20 within-group instrument frames; one preparation per level INSUFFICIENT -> state as
limitation
  saved: Table_40_claim_evidence_ledger_abstract_results_conclusions.xlsx  (15 rows x 4 cols)
✓ Checkpoint loaded: cell_47_pubtables_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:36.145291
  Shape: {'table_manifest': (43, 3), 'claim_evidence_ledger': (15, 4)}

[done] Cell 47: Tables archived (43), manifest (T41) + claim-evidence ledger (T40); 2 claims
flagged for reframing.
```

In [49]:

```python
CELL_48_CHECKPOINT = CHECKPOINTS_DIR / 'cell_48_hostile_review_checkpoint.pkl'

print("=" * 70)
print("CELL 48: Hostile Q1 Review and Food Chemistry Compliance")
print("=" * 70)
print("A Food Chemistry referee who works on spectroscopy and chemometrics, has
rejected papers "
      "for exactly these faults, and has no obligation to be generous. Written in
full; the "
      "publication-readiness verdict is allowed to be negative (reviewer_rubric
section 10).")


def block(title, lines):
    print(f"\n{title}")
    for ln in lines:
        print(f"  - {ln}")


block("STRENGTHS", [
    "The split is sealed before any model decision; each endpoint is evaluated
exactly once "
    "(counters 1/1/1/1), and the leakage audit passes 12/12 as executed code.",
    "Group-aware, concentration-level-out partitioning throughout; effective
sample size reported "
    "as 25/25/16, not spectrum counts.",
    "The quantitative models are honest: sealed-test RMSEP (0.63/0.51/0.31)
exceeds development "
    "RMSECV, and R2 stays below the suspicious-result trigger.",
    "A single-wavelength univariate benchmark is included and beaten; the full-
spectrum advantage "
    "is shown, not assumed.",
    "Interpretation is deferred to after the freeze; attribution uses exact
linear/PLS tools, not "
    "a mis-applied tree SHAP; UV-matrix regions are flagged."])

block("MAJOR CONCERNS (answered with a number or conceded)", [
    "One group per concentration means the regressions rest on 25/25/16
independent preparations: "
    "ANSWERED - every metric carries n_spectra/n_groups/n_levels and group-mean
metrics are "
    "reported beside spectrum-level; an R2 over 500 spectra is disclosed as
resting on 20 levels.",
    "The 20 within-group spectra are instrument frames from one preparation:
CONCEDED - reported "
    "as instrument repeatability (RSD 3.9-5.9%), NOT between-preparation
reproducibility, which "
    "this design cannot provide (stated as a limitation).",
    "The 50 controls are one preparation, so authentic-juice variability is not
characterised: "
    "CONCEDED - this is why the primary classifier is three-class (controls
```

```
excluded); no "
    "authentic-batch generalisation is claimed.",
    "One juice, one instrument, one laboratory: CONCEDED - no claim beyond this
dataset; framed "
    "as a screening method.",
    "Held-out groups are whole concentration levels: ANSWERED - interior-level
selection asserted, "
    "so the reported error is interpolation error and is stated as such.",
    "What does UV-Vis add over a separation-based determination: CONCEDED - no
reference-method "
    "(HPLC) comparison was performed; the contribution is reframed as rapid
screening, not a "
    "validated determination.",
    "Regulatory severity bands - legal basis, product category, jurisdiction:
CONCEDED - bands are "
    "descriptive strata only; the 8.0 ug/mL anchor is [VERIFY-REQUIRED] and no
limit is asserted.",
    "Is the full spectrum better than a single lambda-max: ANSWERED - yes, shown
per dye (T25).",
    "Metanil yellow's weaker response and fewest groups: ANSWERED - explained
(0.172 A vs "
    "0.468/0.477 A; weakest univariate slope 0.011, highest LOD 2.87); yet its
sealed-test RMSEP "
    "is the lowest (0.31) because its concentration range is narrowest.",
    "Attribution below 400 nm overlaps matrix background: ANSWERED - UV<400
regions explicitly "
    "flagged as possible matrix signal; importance not read as causality."])

block("MINOR CONCERNS", [
    "Abstract must be <=150 words with no uncommon abbreviations; 3-5 highlights
at <=85 chars; "
    "1-7 keywords; CRediT roles; data-availability under Option C; generative-AI
disclosure - all "
    "to prepare at submission.",
    "Unify the micrometre symbol (ug -> micro-g) across every axis label;
standardise captions."])

block("STATISTICAL WEAKNESSES", [
    "Dependence between folds and between the 20 frames within a group; interval
estimates avoid "
    "assuming independence the design lacks (fold SD reported, never divided by
sqrt n).",
    "Multiplicity across 63 benchmark combinations handled on matched folds with
correction; ties "
    "inside resampling noise described as ties.",
    "Effective degrees of freedom in every regression metric limited by 25/25/16
levels."])

block("SPECTROSCOPIC WEAKNESSES", [
    "Overlapping azo-dye bands and a strong UV matrix background; peak-shift
interpretation is "
    "descriptive. No reference-method comparison. Single-wavelength LOD/LOQ
reported separately "
    "and not transferred to the multivariate models."])

block("MACHINE-LEARNING WEAKNESSES", [
    "Small effective sample size against 400 collinear predictors favours latent-
variable and "
    "regularised models (as found); hyperparameter search bounded by compute,
acknowledged.",
    "Classification is saturated, so optimisation and single-wavelength
```

```
permutation importance are "
    "near-vacuous; this is stated rather than hidden."])

block("REPRODUCIBILITY WEAKNESSES", [
    "Residual threaded-library non-determinism measured at zero; seed sensitivity
small. The whole "
    "pipeline is in the notebook with seeds and versions recorded; G9 audit
passes."])

block("FIGURE AND TABLE WEAKNESSES", [
    "600 dpi meets the 300 dpi floor but is below the journal's 1000 dpi
preference for line art; "
    "consider raising the eight main-text figures. A few working-figure legends
sit inside empty "
    "corners; main-text figures use outside legends."])

block("UNSUPPORTED CLAIMS (from the claim-evidence ledger)", [
    "'Validated reference-grade determination' - REMOVE/REFRAME as screening (no
reference method).",
    "'Between-preparation reproducibility characterised' - REMOVE (only instrument
repeatability).",
    "Any legal/permissible-intake reading of the severity bands - REMOVE until
verification."])

block("ANALYSES STILL NEEDED", [
    "A reference-method (e.g. HPLC-DAD) comparison on a subset - would convert
screening into a "
    "validated determination; not feasible with the existing data alone.",
    "Independent duplicate preparations per level - would provide between-
preparation precision; "
    "requires new sample preparation.",
    "The regulatory-citation verification (Codex INS 102/110 in 14.1.2/14.1.3;
jurisdiction and "
    "product category) before the Discussion is written."])

verdict = ("READY AFTER THE LISTED REVISIONS, as a rapid screening method - NOT as
a validated "
           "reference-grade determination. The chemometrics, leakage control, and
sealed-test "
           "discipline are sound and the quantitative result is honest; acceptance
requires "
           "reframing the contribution as screening, stating the between-
preparation and "
           "reference-method gaps as limitations, and completing the regulatory
verification. "
           "Without a reference-method comparison the stronger 'validated
determination' claim is "
           "not supportable from this dataset.")
print("\nPUBLICATION READINESS")
print(f"  {verdict}")

# ---- Food Chemistry compliance checklist ----
comp = [
    ('Within scope (analytical method for food, real-sample data)', 'Yes',
'Adulterant screening in orange juice'),
    ('Article type, <8000 words', 'To confirm', 'Research Paper / Analytical
Methods'),
    ('<=8 figures+tables in main text', 'Yes', '8 main-text figures; all tables
supplementary'),
    ('Abstract <=150 words, standalone', 'To prepare', ''),
    ('Highlights 3-5 x <=85 chars', 'To prepare', ''),
```

```
    ('Keywords 1-7', 'To prepare', ''),
    ('SI units throughout', 'Partial', 'standardise micro-g symbol in figure
labels'),
    ('Figures separate files, logical names, captions', 'Yes', 'Final Publication
Figures/Figure 1-8'),
    ('Resolution at/above journal minimum', 'Yes (600 dpi)', 'consider 1000 dpi
for line art'),
    ('Tables editable, no vertical rules/shading', 'Yes', 'XLSX, supplementary'),
    ('References APA 7th, DOIs, all real', 'To prepare', 'citation pass pending'),
    ('Research data Option C (deposit + cite)', 'To prepare', ''),
    ('Generative-AI disclosure', 'To prepare', 'disclose AI assistance; not an
author'),
    ('CRediT, competing interests, funding', 'To prepare', ''),
    ('Validation + reference-method comparison', 'Gap', 'no reference method;
frame as screening, state in limitations'),
]
comp_df = pd.DataFrame(comp, columns=['requirement', 'status', 'note'])
print("\n--- Food Chemistry compliance checklist ---")
print(comp_df.to_string(index=False))
show_and_save_table(comp_df, 42, 'Food Chemistry submission compliance checklist',
cell='48',
                    notes='Reviewer_rubric section 11. The last row is decisive:
with no reference-'
                          'method comparison the paper is framed as screening and
the gap is stated '
                          'as a limitation. Manuscript-preparation items
(abstract, highlights, '
                          'CRediT, data statement, AI disclosure, references) are
prepared at '
                          'submission, outside the notebook.')

save_checkpoint({'verdict': verdict, 'compliance': comp_df},
                CELL_48_CHECKPOINT, metadata={'type': 'hostile_review', 'cell':
'48', 'gate': 'G9'})
_ = load_checkpoint(CELL_48_CHECKPOINT, validate_hash=False)
print("\n[done] Cell 48: Hostile Q1 review + compliance (T42) — verdict: ready
after revisions "
      "as a screening method; reference-method and reproducibility gaps stated as
limitations.")
```

```
======================================================================
CELL 48: Hostile Q1 Review and Food Chemistry Compliance
======================================================================
A Food Chemistry referee who works on spectroscopy and chemometrics, has rejected papers for
exactly these faults, and has no obligation to be generous. Written in full; the publication-
readiness verdict is allowed to be negative (reviewer_rubric section 10).

STRENGTHS
  - The split is sealed before any model decision; each endpoint is evaluated exactly once
(counters 1/1/1/1), and the leakage audit passes 12/12 as executed code.
  - Group-aware, concentration-level-out partitioning throughout; effective sample size reported
as 25/25/16, not spectrum counts.
  - The quantitative models are honest: sealed-test RMSEP (0.63/0.51/0.31) exceeds development
RMSECV, and R2 stays below the suspicious-result trigger.
  - A single-wavelength univariate benchmark is included and beaten; the full-spectrum advantage
is shown, not assumed.
  - Interpretation is deferred to after the freeze; attribution uses exact linear/PLS tools, not
a mis-applied tree SHAP; UV-matrix regions are flagged.

MAJOR CONCERNS (answered with a number or conceded)
  - One group per concentration means the regressions rest on 25/25/16 independent preparations:
ANSWERED - every metric carries n_spectra/n_groups/n_levels and group-mean metrics are reported
beside spectrum-level; an R2 over 500 spectra is disclosed as resting on 20 levels.
  - The 20 within-group spectra are instrument frames from one preparation: CONCEDED - reported
as instrument repeatability (RSD 3.9-5.9%), NOT between-preparation reproducibility, which this
```

design cannot provide (stated as a limitation).
  - The 50 controls are one preparation, so authentic-juice variability is not characterised: CONCEDED - this is why the primary classifier is three-class (controls excluded); no authentic-batch generalisation is claimed.
  - One juice, one instrument, one laboratory: CONCEDED - no claim beyond this dataset; framed as a screening method.
  - Held-out groups are whole concentration levels: ANSWERED - interior-level selection asserted, so the reported error is interpolation error and is stated as such.
  - What does UV-Vis add over a separation-based determination: CONCEDED - no reference-method (HPLC) comparison was performed; the contribution is reframed as rapid screening, not a validated determination.
  - Regulatory severity bands - legal basis, product category, jurisdiction: CONCEDED - bands are descriptive strata only; the 8.0 ug/mL anchor is [VERIFY-REQUIRED] and no limit is asserted.
  - Is the full spectrum better than a single lambda-max: ANSWERED - yes, shown per dye (T25).
  - Metanil yellow's weaker response and fewest groups: ANSWERED - explained (0.172 A vs 0.468/0.477 A; weakest univariate slope 0.011, highest LOD 2.87); yet its sealed-test RMSEP is the lowest (0.31) because its concentration range is narrowest.
  - Attribution below 400 nm overlaps matrix background: ANSWERED - UV<400 regions explicitly flagged as possible matrix signal; importance not read as causality.

MINOR CONCERNS
  - Abstract must be <=150 words with no uncommon abbreviations; 3-5 highlights at <=85 chars; 1-7 keywords; CRediT roles; data-availability under Option C; generative-AI disclosure - all to prepare at submission.
  - Unify the micrometre symbol (ug -> micro-g) across every axis label; standardise captions.

STATISTICAL WEAKNESSES
  - Dependence between folds and between the 20 frames within a group; interval estimates avoid assuming independence the design lacks (fold SD reported, never divided by sqrt n).
  - Multiplicity across 63 benchmark combinations handled on matched folds with correction; ties inside resampling noise described as ties.
  - Effective degrees of freedom in every regression metric limited by 25/25/16 levels.

SPECTROSCOPIC WEAKNESSES
  - Overlapping azo-dye bands and a strong UV matrix background; peak-shift interpretation is descriptive. No reference-method comparison. Single-wavelength LOD/LOQ reported separately and not transferred to the multivariate models.

MACHINE-LEARNING WEAKNESSES
  - Small effective sample size against 400 collinear predictors favours latent-variable and regularised models (as found); hyperparameter search bounded by compute, acknowledged.
  - Classification is saturated, so optimisation and single-wavelength permutation importance are near-vacuous; this is stated rather than hidden.

REPRODUCIBILITY WEAKNESSES
  - Residual threaded-library non-determinism measured at zero; seed sensitivity small. The whole pipeline is in the notebook with seeds and versions recorded; G9 audit passes.

FIGURE AND TABLE WEAKNESSES
  - 600 dpi meets the 300 dpi floor but is below the journal's 1000 dpi preference for line art; consider raising the eight main-text figures. A few working-figure legends sit inside empty corners; main-text figures use outside legends.

UNSUPPORTED CLAIMS (from the claim-evidence ledger)
  - 'Validated reference-grade determination' - REMOVE/REFRAME as screening (no reference method).
  - 'Between-preparation reproducibility characterised' - REMOVE (only instrument repeatability).
  - Any legal/permissible-intake reading of the severity bands - REMOVE until verification.

ANALYSES STILL NEEDED
  - A reference-method (e.g. HPLC-DAD) comparison on a subset - would convert screening into a validated determination; not feasible with the existing data alone.
  - Independent duplicate preparations per level - would provide between-preparation precision; requires new sample preparation.
  - The regulatory-citation verification (Codex INS 102/110 in 14.1.2/14.1.3; jurisdiction and product category) before the Discussion is written.

PUBLICATION READINESS
  READY AFTER THE LISTED REVISIONS, as a rapid screening method - NOT as a validated reference-

grade determination. The chemometrics, leakage control, and sealed-test discipline are sound and the quantitative result is honest; acceptance requires reframing the contribution as screening, stating the between-preparation and reference-method gaps as limitations, and completing the regulatory verification. Without a reference-method comparison the stronger 'validated determination' claim is not supportable from this dataset.

--- Food Chemistry compliance checklist ---

| | requirement | status | note |
|---|---|---|---|
| Within scope (analytical method for food, real-sample data) | | Yes | Adulterant screening in orange juice |
| Article type, <8000 words | | To confirm | Research Paper / Analytical Methods |
| <=8 figures+tables in main text | | Yes | 8 main-text figures; all tables supplementary |
| Abstract <=150 words, standalone | | To prepare | |
| Highlights 3-5 x <=85 chars | | To prepare | |
| Keywords 1-7 | | To prepare | |
| SI units throughout | | Partial | standardise micro-g symbol in figure labels |
| Figures separate files, logical names, captions | | Yes | Final Publication Figures/Figure 1-8 |
| Resolution at/above journal minimum | Yes (600 dpi) | | consider 1000 dpi for line art |
| Tables editable, no vertical rules/shading | | Yes | XLSX, supplementary |
| References APA 7th, DOIs, all real | | To prepare | citation pass pending |
| Research data Option C (deposit + cite) | | To prepare | |
| Generative-AI disclosure | | To prepare | disclose AI assistance; not an author |
| CRediT, competing interests, funding | | To prepare | |
| Validation + reference-method comparison | | Gap | no reference method; frame as screening, state in limitations |

TABLE 42: Food Chemistry submission compliance checklist

| | requirement | status | note |
|---|---|---|---|
| Within scope (analytical method for food, real-sample data) | | Yes | Adulterant screening in orange juice |
| Article type, <8000 words | | To confirm | Research Paper / Analytical Methods |
| <=8 figures+tables in main text | | Yes | 8 main-text figures; all tables supplementary |
| Abstract <=150 words, standalone | | To prepare | |
| Highlights 3-5 x <=85 chars | | To prepare | |
| Keywords 1-7 | | To prepare | |
| SI units throughout | | Partial | standardise micro-g symbol in figure labels |
| Figures separate files, logical names, captions | | Yes | Final Publication Figures/Figure 1-8 |
| Resolution at/above journal minimum | Yes (600 dpi) | | consider 1000 dpi for line art |
| Tables editable, no vertical rules/shading | | Yes | XLSX, supplementary |
| References APA 7th, DOIs, all real | | To prepare | citation pass pending |
| Research data Option C (deposit + cite) | | To prepare | |
| Generative-AI disclosure | | To prepare | disclose AI assistance; not an author |
| CRediT, competing interests, funding | | To prepare | |
| Validation + reference-method comparison | | Gap | no reference method; frame as screening, state in limitations |

  saved: Table_42_food_chemistry_submission_compliance_checklist.xlsx  (15 rows x 3 cols)
✓ Checkpoint loaded: cell_48_hostile_review_checkpoint.pkl
  Timestamp: 2026-11-04T23:35:36.168743
  Shape: {'compliance': (15, 3)}

[done] Cell 48: Hostile Q1 review + compliance (T42) — verdict: ready after revisions as a screening method; reference-method and reproducibility gaps stated as limitations.