Week 11 - Lab 9.

1 Threads:

```
class NewThread1 implements Runnable
{
  Thread t;
  NewThread1 ()
  {
  t= new Thread (this, "NThread1");
   System.out.println("CT :"+t);
     t.start();
  }
  public void run()
  {
  try
  {
     for (int n=3; n>0; n--)
  {
   System.out.println("BMS college of Engineering");
     Thread.sleep(10000);
    }
  } .
  catch (InterruptedException ie)
  {
   System.out.println("child Thread1 Enterrupted");
  }
  System.out.println("child Thread1 quitting");
}
}

class Newthread2 implements Runnable
{
  Thread t;
   NewThread2().
```

```
{
NewThread2()
{
t = new Thread(this, "NThread2");
System.out.println("CT:"+t);
t.start();
}
public void run()
{
try
{
for(int n=10; n>0; n--)
{
System.out.println("CSE");
Thread.sleep(2000);
}
}
catch(InterruptedException ie).
{
System.out.println("Child Thread2
Interrupted");
}
System.out.println("Child thread2 quitting");
}
}
class ThreadDemo
{
public static void main(String ss[])
{
NewThread n1 = new NewThread1();
NewThread n2 = new NewThread2();
}} System.out.println("Back in main");
```