STEP 3: TECHNICAL PROJECTS MASTERY & BRIDGING

Comprehensive First-Principles Breakdown & Evernorth Healthcare Mapping

Candidate: **Anshika Keshari** | B.Tech CSE (KIIT) | IIIT Naya Raipur Research Intern

Projects: (1) Smart Grid Physics-Informed Graph Digital Twin | (2) Anti-Money Laundering ML Pipeline

1 The Strategic Framing: How to Introduce Your Projects at Evernorth

Evernorth Strategic Bridge: The Dual-Project Power Pitch

"Both of my core technical projects address the exact challenges facing Evernorth Health Services:

1. **My Research Project (Graph Digital Twin)** addresses **Cyber-Physical Resilience in Life-Critical Infrastructure**. In smart grids, attacks manipulate electrical sensors; in healthcare, the exact same attacks target connected medical devices (IoMT) and hospital microgrids. My model detects stealthy sensor spoofing with a **96.8% F1-score** and triggers sub-15ms automated cyber mitigation.
2. **My Applied ML Project (Anti-Money Laundering)** addresses **Security Analytics & Threat Detection in Massive Skewed Datasets**. By engineering 15+ behavioral attributes and tuning XGBoost to achieve **98.2% Precision**, I solved the problem of 'analyst alert fatigue'—the exact challenge faced by Evernorth's Security Operations Center (SOC) managing millions of daily authentication and claim events."

2 Project 1: Physics-Informed Graph Digital Twin (IIIT Naya Raipur & Norway INTPART)

2.1 Intuition & Real-World Analogies (Explain Like I'm 5)

Everyday Intuition & Real-World Analogy: The ICU Hospital Patient Analogy

Imagine a critically ill patient in a hospital Intensive Care Unit (ICU):

- **Normal Hardware Glitch:** A sensor wire comes loose. The monitor beeps loudly and reads 0 BPM. The nurse plugs it back in. This is classical "Bad Data Detection."
- **Stealthy Cyber-Attack (FDIA):** A hacker infiltrates the hospital network. The patient is actually suffering sudden cardiac arrest, but the hacker's computer injects fake electrical signals so the monitor displays a peaceful 72 BPM with normal blood pressure. Doctors take no action, and the patient suffers severe harm.
- **The Solution (Graph Digital Twin):** Our AI doesn't look at one sensor in isolation. It understands the connected biology of the whole body: *"If the heart is beating at 72 BPM, the blood flow in the neck and oxygen saturation in the lungs must follow exact physical laws. Because they contradict each other, Bus 9 is lying!"*

2.2 The Engineering & Mathematical Reality

Engineering & Mathematical Core: Power Grid as an Attributed Graph

The power grid network is modeled as an undirected attributed graph:

$$\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{X}, \mathbf{E})$$

- **Nodes ($|\mathcal{V}| = 14$ Buses):** Power substations where lines intersect (IEEE 14-bus benchmark).
- **Edges ($|\mathcal{E}| = 20$ Branches):** Transmission lines and transformers.
- **Node Feature Matrix $\mathbf{X} \in \mathbb{R}^{14\times4}$:** Telemetry at bus i:

  $$\mathbf{x}_i = [V_i, \theta_i, P_i, Q_i]^T$$

  where V is Voltage Magnitude, θ is Phase Angle, P is Active Power (MW), and Q is Reactive Power (MVAr).
- **Edge Features $\mathbf{E} \in \mathbb{R}^{40\times2}$:** Resistance R and Reactance X in ohms.

Engineering & Mathematical Core: Why Classical State Estimation Fails: The FDIA Math

Classical power system state estimation checks measurement residuals:

$$r = \|z - H\hat{x}\|_2 \leq \tau$$

A sophisticated cyber-adversary designs an attack vector a lying in the column space of the Jacobian matrix H:

$$a = Hc$$

for an arbitrary false state shift $c \in \mathbb{R}^n$. The compromised measurement is $z_a = z + a$, and the estimated state becomes $\hat{x}_a = \hat{x} + c$.
The resulting residual is:

$$r_a = \|z_a - H\hat{x}_a\|_2 = \|(z + a) - H(\hat{x} + c)\|_2 = \|(z - H\hat{x}) + (a - Hc)\|_2 = \|z - H\hat{x}\|_2 = r \leq \tau$$

The Conclusion: The residual is mathematically identical to normal operation! The classical security estimator sees zero anomaly. This is why a Graph Neural Network is mandatory.

Engineering & Mathematical Core: GraphSAGE Architecture & Multi-Task Training

1. **3 SAGEConv Layers:**

   $$h_i^{(l+1)} = \text{ReLU}\left(\mathbf{W}^{(l)} \cdot \left[h_i^{(l)} \,\|\, \text{MEAN}_{j\in\mathcal{N}(i)}(h_j^{(l)})\right]\right)$$

   with hidden dimension 64 and Dropout ($p = 0.2$).
2. **Joint Multi-Task Loss:**

   $$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{graph}} + 1.5 \cdot \mathcal{L}_{\text{node}}$$

   Simultaneously performs **Graph Classification** (Is the grid under attack? $\rightarrow$ **96.8% F1**) and **Node Classification** (Which specific substation is compromised?).
3. **Sub-15ms Automated Mitigation:** Isolates compromised telemetry at Bus k and substitutes the nominal baseline forecast profile ($\pm2\%$ uncertainty), recovering state estimation accuracy by **95.2%** in **12.4 ms** without tripping circuit breakers!

3 Project 2: Anti-Money Laundering (AML) Detection System

3.1 Intuition & Real-World Analogies

Everyday Intuition & Real-World Analogy: The Airport Baggage Customs Analogy

Imagine customs screening at an airport with 10,000 travelers:

- **Normal Passengers (9,980):** Tourists carrying clothes and souvenirs.
- **Smugglers (20):** Criminals carrying contraband disguised as common items.
- **The Accuracy Paradox:** An inspector who approves everyone without looking is **99.8% accurate**, but lets every criminal through! In ML, raw accuracy is meaningless on imbalanced data.
- **The Smart Investigator (Feature Engineering):** The officer checks behavioral cues: *Did this traveler buy a cash ticket 10 minutes before boarding? Did they visit 4 countries in 24 hours with no luggage?* That is **Feature Engineering**!

3.2 The Machine Learning Reality

Engineering & Mathematical Core: 15+ Behavioral Attributes & The SMOTE Pipeline

1. **Velocity Features:** `tx_count_1h`, `tx_count_24h`, `tx_amount_sum_24h`.
2. **Financial Ratios:** $\frac{\text{Amount}}{\text{Balance}+\epsilon}$ (fraudsters drain 95–100% of balance immediately).
3. **Behavioral Flags:** `dormancy_reactivation` (accounts dormant for > 180 days suddenly moving large funds), `geo_velocity_flag` (impossible physical travel speed between login IPs).
4. **SMOTE (Synthetic Minority Over-sampling Technique):** Interpolates new synthetic minority instances along line segments connecting k-nearest neighbors:

$$x_{\text{new}} = x_i + \lambda \cdot (x_{zi} - x_i), \quad \lambda \sim \mathcal{U}(0,1)$$

   Data Leakage Prevention: SMOTE was embedded **exclusively inside the training fold** of 5-fold cross-validation using an `imblearn.pipeline.Pipeline`.
5. **Why XGBoost Won:** Handled non-linear feature interactions and minimized loss using second-order gradients (g_i, h_i), achieving **98.2% Precision** to stop compliance analyst alert fatigue!

4 Top 15 Technical Grilling Questions & Master Answers

Q1: Why did you choose Graph Neural Networks over Random Forest or CNNs?

Winning Interview Strategy: Answer Strategy

"Power grids and computer networks are non-Euclidean graphs. Flattening bus measurements into a 1D vector for Random Forest destroys topological adjacency—it treats two substations 500 miles apart the same as two connected by a high-voltage line. CNNs require rigid grid matrices (like pixels), whereas electrical networks have irregular degree connectivity. GNNs perform localized message-passing along transmission lines, directly reflecting physical flow laws."

Q2: How does your AML project apply to Evernorth's Security Operations Center?

Winning Interview Strategy: Answer Strategy

"Evernorth's SOC processes millions of security logs and authentication events daily. In security analytics, 99.9% of logs are benign, while true cyber intrusions are rare. If a SIEM rule has low precision, analysts are flooded with false alarms and suffer from alert fatigue. By engineering high-signal behavioral features and tuning XGBoost for **98.2% Precision**, I demonstrated how to build high-confidence alert mechanisms that allow security analysts to respond rapidly."

Q3: What was your hyperparameter optimization strategy for XGBoost?

Winning Interview Strategy: Answer Strategy

"We used 5-fold Stratified Cross-Validation with `RandomizedSearchCV` followed by `GridSearchCV`:

- `max_depth` (3–6): Kept shallow to avoid fitting noisy outlier fraud instances.
- `learning_rate` ($\eta = 0.05$): Low step size with `n_estimators` = 300 for smooth convergence.
- `subsample` (0.8) & `colsample_bytree` (0.8): Added feature and row randomization to prevent dominant features from biasing trees.

Q4: How did you avoid over-smoothing in your Graph Neural Network?

Winning Interview Strategy: Answer Strategy

"Over-smoothing causes node embeddings across the entire graph to converge to the same average vector as layers increase. We prevented this by restricting our depth to **3 SAGEConv layers** (matching the graph diameter of the IEEE 14-bus grid) and applying **Dropout ($p = 0.2$)** between convolutions."

Interview Trap & Pro-Tip: Pro-Tip for Project Explanations

Always transition from the **everyday analogy** $\rightarrow$ **the exact mathematical terms** $\rightarrow$ **how it helps Evernorth**. This shows both deep intuition and business maturity!