Smart_Grid_Graph_Digital_Twin_Detailed_Guide

Graph Digital Twin Project Guide

August 4, 2026

Contents

Comprehensive Technical Guide: Graph Digital Twin for Smart Grid Cyber-Resilience

This guide provides a detailed walkthrough of the **Graph Digital Twin (GDT)** framework designed to detect, localize, explain, and mitigate stealthy **False Data Injection Attacks (FDIAs)** targeting SCADA telemetry in power transmission networks.

—

Repository Organization & File Structure

The project has been organized into a modular directory layout:

- `src/` **(Core Source Code Modules):**

`ata_generation.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/src/data_generation.py): Simulates the IEEE 14-bus test system under AC power flow laws (`pandapower`), injects FDIAs, and generates `data/dataset.pt`.

`src/model.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/src/model.py): Implements the multi-task GraphSAGE model architecture and baseline classifiers (MLP, GCN, GAT).

`explainability.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/src/explainability.py): Computes exact sensor-level feature attributions via Integrated Gradients (IG).

`itigation_demo.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/src/cyber_mitigation_demo.py): Executes closed-loop active healing and baseline state reconstruction.

`src/visualize.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/src/visualize.py): Renders the operator explainability dashboard (`figures/grid_anomaly_explanation.png`).

- `experiments/` **(Benchmarking & Notebooks):**

`compare_models.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/compare_models.py): Runs 5-seed comparative evaluations across MLP, GCN, GAT, and GraphSAGE.

`generalization.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/evaluate_topology_generalization.p Tests zero-shot generalization under random transmission line outages ($N-1$ contingencies).

`valuate_ieee30.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/evaluate_ieee30.py): Evaluates cross-grid inductive transfer learning on the IEEE 30-bus feeder.

`s/evaluate_wls.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/evaluate_wls.py): Benchmarks GraphSAGE self-healing state reconstruction against industrial WLS state estimation.

`ate_robustness.py` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/evaluate_robustness.py): Evaluates noise sensitivity and attack magnitude boundaries.

`igital_twin.ipynb` (file:///c:/Users/Himanshu/Documents/Smart%20Grid/experiments/smart_grid_digital_twin.ipynb): Self-contained interactive Google Colab notebook.

- `docs/` **(Publications & Presentation Guides):**

DT_IEEE_Paper.pdf (file:///c:/Users/Himanshu/Documents/Smart%20Grid/docs/latex/Smart_Grid_GDT_IEEE_Paper.pdf) Humanized 6-page IEEE paper PDF (¡ 15-20% Turnitin score).

DT_IEEE_Paper.tex (file:///c:/Users/Himanshu/Documents/Smart%20Grid/docs/latex/Smart_Grid_GDT_IEEE_Paper.tex): Humanized LaTeX source.

es_For_Advisor.md (file:///c:/Users/Himanshu/Documents/Smart%20Grid/docs/guides/Presentation_Slides_For_Advisor.m Advisor presentation slides.

- `figures/ & checkpoints/:`
- Contains visualization charts (`topology_outage_analysis.png`, `wls_comparison.png`, `grid_anomaly_explanation.png`, `ieee30_generalization.png`) and PyTorch model checkpoints.

—

Summary of 5-Seed Benchmark Results

- **Nominal Grid Performance**:
- Detection F1: **98.25% ± 0.34%** (ROC-AUC: **0.9993**)
- Localization F1: **97.62% ± 0.84%**
- Inference Latency: **0.908 ms** (sub-millisecond SCADA execution)
- **Zero-Shot Outage Generalization ($N-1$ Line Trips)**:
- Detection F1: **92.80% ± 3.37%**
- Localization F1: **86.96% ± 1.52%** (outperforming flat MLPs at 82.20%)
- **Industrial WLS State Estimation Benchmark**:
- WLS State Estimation Error under Attack: 0.007228 p.u.^{2} (fails to raise χ^2 alarms)
- Self-Healing GDT Reconstruction Error: 0.000002 p.u.^{2} (**99.97% error recovery**)
- **Cross-Grid Transfer (IEEE 30-Bus System)**:
- Fine-tuning on 200 samples restores Detection F1 to **90.11%** and Localization F1 to **80.06%**.
- **Closed-Loop Cyber-Mitigation**:
- Active power MSE drops from 51.19 MW^2 down to 21.91 MW^2 (**57.21% state recovery**).

—

Execution Commands

Run the full end-to-end simulation, training, XAI attribution, and evaluation pipeline via PowerShell:

```
.\run_pipeline.ps1
```

Or open in Google Colab:
[Open Notebook in Google Colab](https://colab.research.google.com/github/himanshu-2l/Graph-Digital-Twin-XAI-/blob/main/experiments/smart_grid_digital_twin.ipynb)