


Dictionaries

Algorithms & Data Structures
ITCS 6114/8114

Dr. Dewan Tanvir Ahmed
Department of Computer Science
University of North Carolina at Charlotte

Dictionaries



Dictionary ADT

- The **dictionary ADT** models a **searchable collection** of key-element items
- The main operations of a dictionary are **searching, inserting, and deleting items**
- Multiple items with the same key are allowed
- Applications:
 - ▣ **address book**
 - ▣ **credit card authorization**
 - ▣ **mapping host names (e.g., cs16.net) to internet addresses (e.g., 128.148.34.101)**

- Dictionary ADT methods:
 - ▣ **findElement(k)**: if the dictionary has an item with key k, returns its element, else, returns the special element NO_SUCH_KEY
 - ▣ **insertItem(k, o)**: inserts item (k, o) into the dictionary
 - ▣ **removeElement(k)**: if the dictionary has an item with key k, removes it from the dictionary and returns its element, else returns the special element NO_SUCH_KEY
 - ▣ **size(), isEmpty()**
 - ▣ **...**

Log File


- A log file is a dictionary implemented by means of an unsorted sequence
 - ▣ We store the items of the dictionary in a sequence (based on a doubly-linked lists or a circular array), in arbitrary order
- Performance:
 - ▣ insertItem takes $O(1)$ time since we can insert the new item at the beginning or at the end of the sequence
 - ▣ findElement and removeElement take $O(n)$ time since in the worst case (the item is not found) we traverse the entire sequence to look for an item with the given key

Log File

- The log file is effective only for dictionaries of small size or for dictionaries on which
 - ▣ insertions are the most common operations
 - ▣ searches and removals are rarely performed (e.g., historical record of logins to a workstation)

Binary Search

- Binary search performs operation **findElement(k)** on a dictionary implemented by means of an array-based sequence, sorted by key
 - ▣ similar to the high-low game
 - ▣ at each step, the number of candidate items is halved
 - ▣ terminates after a logarithmic number of steps
- Example: **findElement(7)**




Lookup Table

- A lookup table is a dictionary implemented by means of a sorted sequence
 - ▣ We store the items of the dictionary in an array-based sequence, sorted by key
- Performance:
 - ▣ `findElement` takes $O(\log n)$ time, using binary search
 - ▣ `insertItem` takes $O(n)$ time since in the worst case we have to shift $n/2$ items to make room for the new item
 - ▣ `removeElement` take $O(n)$ time since in the worst case we have to shift $n/2$ items to compact the items after the removal
- The lookup table is effective only for dictionaries of small size or for dictionaries on which searches are the most common operations, while insertions and removals are rarely performed (e.g., credit card authorizations)

Binary Search Tree


- A binary search tree is a binary tree storing keys (or key-element pairs) at its internal nodes and satisfying the following property:
 - ▣ Let u , v , and w be three nodes such that u is in the left subtree of v and w is in the right subtree of v . We have $\text{key}(u) \leq \text{key}(v) \leq \text{key}(w)$
- External nodes do not store items
- An inorder traversal of a binary search tree visits the keys in increasing order



Search



- To search for a key k , we trace a downward path starting at the root
- The next node visited depends on the outcome of the comparison of k with the key of the current node
- If we reach a leaf, the key is not found and we return NO_SUCH_KEY
- Example: **findElement(4)**

```
Algorithm findElement(k, v)
  if T.isExternal (v)
    return NO_SUCH_KEY
  if k < key(v)
    return findElement(k, T.leftChild(v))
  else if k = key(v)
    return element(v)
  else k > key(v)
    return findElement(k, T.rightChild(v))
```





Insertion

- To perform operation **insertItem(k, o)**, we search for key k
- Assume k is not already in the tree, and let w be the leaf reached by the search
- We insert k at node w and expand w into an internal node
- Example: insert 5





Deletion

- To perform operation `removeElement(k)`, we search for key k
- Assume key k is in the tree, and let v be the node storing k
- If node v has a leaf child w , we remove v and w from the tree with operation `removeAboveExternal(w)`
- Example: remove 4





Deletion (cont.)

- We consider the case where the key k to be removed is stored at a node v whose children are both internal
 - ▣ we find the internal node w that follows v in an inorder traversal
 - ▣ we copy $\text{key}(w)$ into node v
 - ▣ we remove node w and its left child z (which must be a leaf) by means of operation `removeAboveExternal(z)`
- Example: remove 3



Performance

- Consider a dictionary with n items implemented by means of a binary search tree of height h
 - ▣ the space used is $O(n)$
 - ▣ methods `findElement`, `insertItem` and `removeElement` take $O(h)$ time
- The height h
 - ▣ is $O(n)$ in the worst case and $O(\log n)$ in the best case



Reference

- **Algorithm Design: Foundations, Analysis, and Internet Examples.** Michael T. Goodrich and Roberto Tamassia. John Wiley & Sons.
- **Introduction to Algorithms.** Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, Clifford Stein.