Nationwide House Energy Rating Scheme
NatHERS Certificate No. 0012293403

Generated on 13 Oct 2025 using BERS Pro v4.4.1.5 (3.21)

ARMIDALE Regional Council

Environmental Planning and Assessment Act 1979
this is the APPROVED plan referred to in
Development Consent No. DA-163-2023/A
dated 10/12/2025

This plan is to be read in conjunction with Council's written conent notice. Any subsequent changes to the plans, other than those required by conditions of the Development Consent, may require further consent ot be obtained.

Lucy Kelly
Development Planner

Lucy Kelly

6.4

The more stars the more energy efficient

NATIONWIDE HOUSE ENERGY RATING SCHEME ®

115.2 MJ/m²

Predicted annual energy load for heating and cooling based on standard occupancy assumptions.

For more information on your dwelling's rating see: www.nathers.gov.au

Property

Address	385 Castledoyle Road, Armidale , NSW , 2350
Lot/DP	1294198
NCC Class*	1A
Type	New Dwelling

Plans

Main plan	2023-022 - 9/09/25
Prepared by	Mitchell Ayre

Construction and environment

Assessed floor area (m^2)*

Conditioned*	204.0
Unconditioned*	86.0
Total	290.0
Garage	63.0

Exposure type

Open

NatHERS climate zone

14

Thermal performance

Heating	Cooling
111.8	3.4
MJ/m^2	MJ/m^2

Accredited assessor

Name	John Marchant
Business name	Partners Energy Management
Email	johnm@partnersenergy.com.au
Phone	0421381005
Accreditation No.	101526

Assessor Accrediting Organisation

ABSA

Declaration of interest	The Assessor has provided design advice to the Applicant

About the rating

NatHERS software models the expected thermal energy loads using information about the design and construction, climate and common patterns of household use. The software does not take into account appliances, apart from the airflow impacts from ceiling fans.

Verification

To verify this certificate, scan the QR code or visit hstar.com.au/QR/Generate?p=IyzaHkTzP.
When using either link, ensure you are visiting hstar.com.au

Reference: 240001/02
Date: 31/03/2026
Luke Powell
Registered Certifier
BDC2937
4U Certification Pty Ltd
4U CERTIFICATION
APPROVE - CONSTRUCT - CERTIFY
APPROVED

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to: insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

* Refer to glossary

Certificate check

Ensure the dwelling is designed and then built as per the NatHERS Certificate. While you need to check the accuracy of the whole Certificate, the following spot check covers some important items impacting the dwelling's rating.

Genuine certificate

Does this Certificate match the one available at the web address or QR code in the verification box on the front page? Does the set of NatHERS-stamped plans for the dwelling have a Certificate number on the stamp that matches this Certificate?

Ceiling penetrations*

Does the 'number' and 'type' of ceiling penetrations (e.g. downlights, exhaust fans, etc) shown on the stamped plans or installed, match what is shown in this Certificate?

Windows

Does the installed window meet the substitution tolerances (SHGC and U-value) and window type, of the window shown on this Certificate? Substituted values must be based on the Australian Fenestration Rating Council (AFRC) protocol.

Apartment entrance doors

Does the 'External Door Schedule' show apartment entrance doors? Please note that an "external door" between the modelled dwelling and a shared space, such as an enclosed corridor or foyer, should not be included in the assessment (because it overstates the possible ventilation) and would invalidate the Certificate.

Exposure*

Has the appropriate exposure level (terrain) been applied? For example, it is unlikely that a ground-floor apartment is "exposed" or a top floor high-rise apartment is "protected".

Provisional* values

Have provisional values been used in the assessment and, if so, noted in "additional notes" below?

Additional notes

For glazing only the U and SHGC values are to be used - NOT the product descriptions.
Also for all glazing the SHGC tolerances are +/-5% - regardless of the Certificate notations.
Downlights must not penetrate ceiling insulation.
I have modeled the shading in accordance with NatHERS principles

Window and glazed door *type and performance*

Default* windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges SHGC lower limit	SHGC upper limit
No Data Available					

Custom* windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges SHGC lower limit	SHGC upper limit
GJA-001-03 A	GJA-001-03 A Type 048 Series Awning Window SG 3E A	4.8	0.53	0.50	0.56

Reference: 240001/02
Date: 31/03/2026
Luke Powell
Registered Certifier
BDC2937
4U Certification Sydney
4U CERTIFICATION
APPROVE - CONSTRUCT - CERTIFY
APPROVED

Custom* windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
GJA-013-02 A	GJA-013-02 A Type 131 Aluminium Sliding Window SG 3EA	4.5	0.65	0.62	0.68

Window and glazed door *schedule*

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orientation	Window shading device*
Garage	GJA-001-03 A	n/a	1800	730	n/a	70	W	No
Garage	GJA-001-03 A	n/a	1800	730	n/a	70	W	No
Garage	GJA-001-03 A	n/a	1800	730	n/a	70	W	No
Laundry	GJA-013-02 A	n/a	900	730	n/a	45	N	No
Master Bed	GJA-013-02 A	n/a	1500	2400	n/a	45	N	No
Master Bed	GJA-013-02 A	n/a	2100	2410	n/a	45	E	No
Ensuite Master	GJA-013-02 A	n/a	1200	2110	n/a	45	E	No
Ensuite Master	GJA-001-03 A	n/a	1800	730	n/a	70	S	No
WIR Master	GJA-001-03 A	n/a	1800	730	n/a	70	S	No
Bathroom	GJA-001-03 A	n/a	1800	730	n/a	70	S	No
Bedroom 2	GJA-013-02 A	n/a	1500	2400	n/a	45	N	No
Bedroom 3	GJA-013-02 A	n/a	1500	2400	n/a	45	N	No
Butlers	GJA-001-03 A	n/a	1800	730	n/a	70	S	No
Kitchen/Lounge	GJA-013-02 A	n/a	2100	1200	n/a	00	N	No
Kitchen/Lounge	GJA-001-03 A	n/a	2100	5900	n/a	90	N	No
Kitchen/Lounge	GJA-013-02 A	n/a	600	2800	n/a	00	N	No
Kitchen/Lounge	GJA-013-02 A	n/a	600	2800	n/a	00	N	No
Kitchen/Lounge	GJA-013-02 A	n/a	1800	1800	n/a	00	N	No
Kitchen/Lounge	GJA-013-02 A	n/a	2100	1200	n/a	00	N	No
Kitchen/Lounge	GJA-001-03 A	n/a	900	900	n/a	90	S	No
Kitchen/Lounge	GJA-001-03 A	n/a	900	900	n/a	90	S	No
Kitchen/Lounge	GJA-013-02 A	n/a	900	858	n/a	00	S	No
Kitchen/Lounge	GJA-001-03 A	n/a	1050	1200	n/a	90	S	No
Kitchen/Lounge	GJA-001-03 A	n/a	900	900	n/a	90	S	No

Reference: 240001/02
Date: 31/03/2026
Luke Powell
Registered Certifier
BDC2937
4U Certification Pty Ltd
4U CERTIFICATION
APPROVE - CONSTRUCT - CERTIFY
APPROVED

* Refer to glossary.

Location	Window ID	Window no.	Height (mm)	Width (mm)	Window type	Opening %	Orientation	Window shading device*
Kitchen/Lounge	GJA-001-03 A	n/a	900	900	n/a	90	S	No
Kitchen/Lounge	GJA-013-02 A	n/a	900	858	n/a	00	S	No
WC	GJA-001-03 A	n/a	1800	730	n/a	70	S	No

Roof window *type and performance*

Default* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Custom* roof windows

Window ID	Window Description	Maximum U-value*	SHGC*	Substitution tolerance ranges	
				SHGC lower limit	SHGC upper limit
No Data Available					

Roof window *schedule*

Location	Window ID	Window no.	Opening %	Height (mm)	Width (mm)	Orientation	Outdoor shade	Indoor shade
No Data Available								

Skylight *type and performance*

Skylight ID	Skylight description
No Data Available	

Skylight *schedule*

Location	Skylight ID	Skylight No.	Skylight shaft length (mm)	Area (m^2)	Orientation	Outdoor shade	Diffuser	Skylight shaft reflectance
No Data Available								

Reference: 240001/02
Date: 31/03/2026
Luke Powell
Registered Certifier
BDC2937
4U Certification Pty Ltd
4U CERTIFICATION
APPROVE - CONSTRUCT - CERTIFY
APPROVED

* Refer to glossary.

External door *schedule*

Location	Height (mm)	Width (mm)	Opening %	Orientation
Garage	2100	3450	90	S
Garage	2100	3450	90	S
Garage	2100	820	90	W
Kitchen/Lounge	1050	1200	90	S

External wall *type*

Wall ID	Wall type	Solar absorptance	Wall shade (colour)	Bulk insulation (R-value)	Reflective wall wrap*
EW-1	Concrete block, lined	0.50	Medium	No insulation	No
EW-2	Concrete block, lined	0.50	Medium	Anti-glare foil with bulk no gap R2	No

External wall *schedule*

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* maximum projection (mm)	Vertical shading feature (yes/no)
Garage	EW-1	2700	5595	N	500	NO
Garage	EW-1	2700	7995	S	600	NO
Garage	EW-1	2700	8700	W	500	NO
Laundry	EW-2	2700	3790	N	500	NO
Master Bed	EW-2	2700	4195	N	500	NO
Master Bed	EW-2	2700	5495	E	600	NO
Ensuite Master	EW-2	2700	3195	E	600	NO
Ensuite Master	EW-2	2700	3195	S	600	NO
WIR Master	EW-2	2700	2390	S	600	NO
Bathroom	EW-2	2700	2490	S	600	NO
Study	EW-2	2700	2190	S	600	NO
Bedroom 2	EW-2	2700	3690	N	500	NO
Bedroom 3	EW-2	2700	3690	N	500	NO
Butlers	EW-2	2700	3090	S	600	NO
Larder	EW-2	2700	1990	N	500	NO

* Refer to glossary.

Location	Wall ID	Height (mm)	Width (mm)	Orientation	Horizontal shading feature* maximum projection (mm)	Vertical shading feature (yes/no)
Kitchen/Lounge	EW-2	4500	9490	N	5000	NO
Kitchen/Lounge	EW-2	2700	1200	E	12200	YES
Kitchen/Lounge	EW-2	3375	3600	S	3800	YES
Kitchen/Lounge	EW-2	2700	1200	E	4100	YES
Kitchen/Lounge	EW-2	4500	2300	S	2600	NO
Kitchen/Lounge	EW-2	2700	1200	W	4000	YES
Kitchen/Lounge	EW-2	3375	3500	S	3800	YES
Kitchen/Lounge	EW-2	2700	1200	W	500	YES
Kitchen/Lounge	EW-2	2700	395	S	5000	YES
WC	EW-2	2700	1290	S	600	YES

Internal wall *type*

Wall ID	Wall type	Area (m^2)	Bulk insulation
IW-1 - Cavity wall, direct fix plasterboard, single gap		30.00	Bulk Insulation, No Air Gap R2
IW-2 - Cavity wall, direct fix plasterboard, single gap		189.00	No insulation

Floor *type*

Location	Construction	Area (m^2)	Sub-floor ventilation	Added insulation (R-value)	Covering
Garage	Concrete Slab on Ground 100mm	63.10	None	No Insulation	Bare
Laundry	Concrete Slab on Ground 100mm	11.30	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Master Bed	Concrete Slab on Ground 100mm	24.40	None	Bulk Insulation in Contact with Floor R2	Carpet+Rubber Underlay 18mm
Ensuite Master	Concrete Slab on Ground 100mm	10.00	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
WIR Master	Concrete Slab on Ground 100mm	7.30	None	Bulk Insulation in Contact with Floor R2	Carpet+Rubber Underlay 18mm
Bathroom	Concrete Slab on Ground 100mm	7.60	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Study	Concrete Slab on Ground 100mm	6.70	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab on Ground 100mm	15.00	None	Bulk Insulation in Contact with Floor R2	Carpet+Rubber Underlay 18mm

* Refer to glossary.

Location	Construction	Area (m^2)	Sub-floor ventilation	Added insulation (R-value)	Covering
Bedroom 3	Concrete Slab on Ground 100mm	15.00	None	Bulk Insulation in Contact with Floor R2	Carpet+Rubber Underlay 18mm
Butlers	Concrete Slab on Ground 100mm	9.50	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Larder	Concrete Slab on Ground 100mm	7.90	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Hallway West	Concrete Slab on Ground 100mm	4.00	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Hallway East	Concrete Slab on Ground 100mm	7.10	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
Kitchen/Lounge	Concrete Slab on Ground 100mm	96.90	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm
WC	Concrete Slab on Ground 100mm	3.80	None	Bulk Insulation in Contact with Floor R2	Ceramic Tiles 8mm

Ceiling *type*

Location	Construction material/type	Bulk insulation R-value (may include edge batt values)	Reflective wrap*
Garage	Plasterboard	No insulation	No
Laundry	Plasterboard	Bulk Insulation R4	No
Master Bed	Plasterboard	Bulk Insulation R4	No
Ensuite Master	Plasterboard	Bulk Insulation R4	No
WIR Master	Plasterboard	Bulk Insulation R4	No
Bathroom	Plasterboard	Bulk Insulation R4	No
Study	Plasterboard	Bulk Insulation R4	No
Bedroom 2	Plasterboard	Bulk Insulation R4	No
Bedroom 3	Plasterboard	Bulk Insulation R4	No
Butlers	Plasterboard	Bulk Insulation R4	No
Larder	Plasterboard	Bulk Insulation R4	No
Hallway West	Plasterboard	Bulk Insulation R4	No
Hallway East	Plasterboard	Bulk Insulation R4	No
Kitchen/Lounge	Plasterboard	Bulk Insulation R3	No
WC	Plasterboard	Bulk Insulation R4	No

* Refer to glossary.

Ceiling penetrations*

Location	Quantity	Type	Diameter (mm)	Sealed/unsealed
Garage	12	Downlights - LED	0	Sealed
Laundry	2	Downlights - LED	0	Sealed
Master Bed	4	Downlights - LED	0	Sealed
Ensuite Master	2	Downlights - LED	0	Sealed
WIR Master	2	Downlights - LED	0	Sealed
Bathroom	2	Downlights - LED	0	Sealed
Study	2	Downlights - LED	0	Sealed
Bedroom 2	3	Downlights - LED	0	Sealed
Bedroom 3	3	Downlights - LED	0	Sealed
Butlers	2	Downlights - LED	0	Sealed
Larder	4	Downlights - LED	0	Sealed
Hallway West	2	Downlights - LED	0	Sealed
Hallway East	2	Downlights - LED	0	Sealed
Kitchen/Lounge	18	Downlights - LED	0	Sealed

Ceiling *fans*

Location	Quantity	Diameter (mm)
No Data Available		

Roof *type*

Construction	Added insulation (R-value)	Solar absorptance	Roof shade
Corrugated Iron	Bulk, Reflective Side Down, No Air Gap Above R1.4	0.85	Dark

Reference: 240001/02
Date: 31/03/2026

Luke Powell
Registered Certifier
BDC2937
4U Certification Pty Ltd

4U CERTIFICATION
APPROVE - CONSTRUCT - CERTIFY
APPROVED

* Refer to glossary.

Explanatory notes

About this report

A NatHERS rating is a comprehensive, dynamic computer modelling evaluation of a home, using the floorplans, elevations and specifications to estimate an energy load. It addresses the building layout, orientation and fabric (i.e. walls, windows, floors, roofs and ceilings), but does not cover the water or energy use of appliances or energy production of solar panels.

Ratings are based on a unique climate zone where the home is located and are generated using standard assumptions, including occupancy patterns and thermostat settings. The actual energy consumption of a home may vary significantly from the predicted energy load, as the assumptions used in the rating will not match actual usage patterns. For example, the number of occupants and personal heating or cooling preferences will vary.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparing different dwelling designs and to demonstrate that the design meets the energy efficiency requirements in the National Construction Code. Homes that are energy efficient use less energy, are warmer on cool days, cooler on hot days and cost less to run. The higher the star rating the more thermally efficient the dwelling is.

Accredited assessors

To ensure the NatHERS Certificate is of a high quality, always use an accredited or licenced assessor. NatHERS accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

Australian Capital Territory (ACT) licensed assessors may only produce assessments for regulatory purposes using software for which they have a licence endorsement. Licence endorsements can be confirmed on the ACT licensing register

AAOs have specific quality assurance processes in place, and continuing professional development requirements, to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any ongoing training requirements.

Any questions or concerns about this report should be directed to the assessor in the first instance. If the assessor is unable to address these questions or concerns, the AAO specified on the front of this certificate should be contacted.

Disclaimer

The format of the NatHERS Certificate was developed by the NatHERS Administrator. However the content of each individual certificate is entered and created by the assessor to create a NatHERS Certificate. It is the responsibility of the assessor who prepared this certificate to use NatHERS accredited software correctly and follow the NatHERS Technical Notes to produce a NatHERS Certificate.

The predicted annual energy load in this NatHERS Certificate is an estimate based on an assessment of the building by the assessor. It is not a prediction of actual energy use, but may be used to compare how other buildings are likely to perform when used in a similar way.

Information presented in this report relies on a range of standard assumptions (both embedded in NatHERS accredited software and made by the assessor who prepared this report), including assumptions about occupancy, indoor air temperature and local climate.

Not all assumptions that may have been made by the assessor while using the NatHERS accredited software tool are presented in this report and further details or data files may be available from the assessor.

Glossary

Annual energy load	the predicted amount of energy required for heating and cooling, based on standard occupancy assumptions.
Assessed floor area	the floor area modelled in the software for the purpose of the NatHERS assessment. Note, this may not be consistent with the floor area in the design documents.
Ceiling penetrations	features that require a penetration to the ceiling, including downlights, vents, exhaust fans, rangehoods, chimneys and flues. Excludes fixtures attached to the ceiling with small holes through the ceiling for wiring, e.g. ceiling fans; pendant lights, and heating and cooling ducts.
Conditioned	a zone within a dwelling that is expected to require heating and cooling based on standard occupancy assumptions. In some circumstances it will include garages.
Custom windows	windows listed in NatHERS software that are available on the market in Australia and have a WERS (Window Energy Rating Scheme) rating.
Default windows	windows that are representative of a specific type of window product and whose properties have been derived by statistical methods.
Entrance door	these signify ventilation benefits in the modelling software and must not be modelled as a door when opening to a minimally ventilated corridor in a Class 2 building.
Exposure category – exposed	terrain with no obstructions e.g. flat grazing land, ocean-frontage, desert, exposed high-rise unit (usually above 10 floors).
Exposure category – open	terrain with few obstructions at a similar height e.g. grasslands with few well scattered obstructions below 10m, farmland with scattered sheds, lightly vegetated bush blocks, elevated units (e.g. above 3 floors).
Exposure category – suburban	terrain with numerous, closely spaced obstructions below 10m e.g. suburban housing, heavily vegetated bushland areas.
Exposure category – protected	terrain with numerous, closely spaced obstructions over 10 m e.g. city and industrial areas.
Horizontal shading feature	provides shading to the building in the horizontal plane, e.g. eaves, verandahs, pergolas, carports, or overhangs or balconies from upper levels.
National Construction Code (NCC) Class	the NCC groups buildings by their function and use, and assigns a classification code. NatHERS software models NCC Class 1, 2 or 4 buildings and attached Class 10a buildings. Definitions can be found at www.abcb.gov.au.
Opening percentage	the openability percentage or operable (moveable) area of doors or windows that is used in ventilation calculations.
Provisional value	an assumed value that does not represent an actual value. For example, if the wall colour is unspecified in the documentation, a provisional value of 'medium' must be modelled. Acceptable provisional values are outlined in the NatHERS Technical Note and can be found at www.nathers.gov.au
Reflective wrap (also known as foil)	can be applied to walls, roofs and ceilings. When combined with an appropriate airgap and emissivity value, it provides insulative properties.
Roof window	for NatHERS this is typically an operable window (i.e. can be opened), will have a plaster or similar light well if there is an attic space, and generally does not have a diffuser.
Shading device	a device fixed to windows that provides shading e.g. window awnings or screens but excludes eaves.
Shading features	includes neighbouring buildings, fences, and wing walls, but excludes eaves.
Solar heat gain coefficient (SHGC)	the fraction of incident solar radiation admitted through a window, both directly transmitted as well as absorbed and subsequently released inward. SHGC is expressed as a number between 0 and 1. The lower a window's SHGC, the less solar heat it transmits.
Skylight (also known as roof lights)	for NatHERS this is typically a moulded unit with flexible reflective tubing (light well) and a diffuser at ceiling level.
U-value	the rate of heat transfer through a window. The lower the U-value, the better the insulating ability.
Unconditioned	a zone within a dwelling that is assumed to not require heating and cooling based on standard occupancy assumptions.
Vertical shading features	provides shading to the building in the vertical plane and can be parallel or perpendicular to the subject wall/window. Includes privacy screens, other walls in the building (wing walls), fences, other buildings, vegetation (protected or listed heritage trees).