

Dominos Sales Analysis SQL Project



Project Overview

Project Title: Dominos Pizza Sales

Level: Beginner

Database: Dominos_db

This project is designed to demonstrate SQL skills and techniques typically used by data analysts to explore, clean, and analyze Dominos Pizza sales data. project involves setting up a rdatabase, performing exploratory data analysis (EDA), and answering specific business questions through SQL queries.

OBJECTIVES

1. **Set up a Dominos sales database**: Create and populate a retail sales database with the provided sales data.
2. **Data Cleaning**: Identify and remove any records with missing or null values.
3. **Exploratory Data Analysis (EDA)**: Perform basic exploratory data analysis to understand the dataset.
4. **Business Analysis**: Use SQL to answer specific business questions and derive insights from the sales data.

1. Retrieve the total number of orders placed.

```sql
SELECT
    COUNT(order_id) Total_order
FROM
    orders;
```

Total_order
21350

2. Calculate the total revenue generated from pizza sales.

```sql
SELECT
    ROUND(SUM(o.quantity * p.price), 2) AS Total_sales
FROM
    order_details o
        JOIN
    pizzas p ON o.pizza_id = p.pizza_id;
```

Total_sales
817860.05

3. Identify the highest-priced pizza.

```sql
SELECT
    pt.name, p.price
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
ORDER BY p.price DESC
LIMIT 1;
```

name	price
The Greek Pizza	35.95

4. Identify the most common pizza size ordered.

```sql
SELECT
    p.size,
    COUNT(od.order_details_id) AS Order_count
FROM
    pizzas p
        JOIN
    order_details od ON p.pizza_id = od.pizza_id
GROUP BY p.size
ORDER BY Order_count DESC;
```

size	Order_count
L	18526
M	15385
S	14137
XL	544
XXL	28

5. List the top 5 most ordered pizza types along with their quantities.

```sql
SELECT
    pt.name,
    SUM(od.quantity) AS Quantity
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
        JOIN
    order_details od ON od.pizza_id = p.pizza_id
GROUP BY pt.name
ORDER BY Quantity DESC
LIMIT 5;
```

name	Quantity
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

6. Join the necessary tables to find the total quantity of each pizza category ordered.

```sql
SELECT
    pt.category, SUM(od.quantity) AS Total_quantity
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
        JOIN
    order_details od ON od.pizza_id = p.pizza_id
GROUP BY pt.category
ORDER BY Total_quantity DESC;
```

category	Total_quantity
Classic	14888
Supreme	11987
Veggie	11649
Chicken	11050

7. Group the orders by date and calculate the average number of pizzas ordered per day.

```sql
SELECT
    ROUND(AVG(total_order),0) AS avg_pizza_order_per_day
FROM
    (SELECT
        o.date, SUM(od.quantity) AS Total_Order
    FROM
        orders o
    JOIN order_details od ON o.order_id = od.order_id
    GROUP BY o.date) AS Order_quantity;
```

avg_pizza_order_per_day
138

8. Determine the top 3 most ordered pizza types based on revenue.

```sql
SELECT
    pt.name, ROUND(SUM(od.quantity * p.price), 1) AS Revenue
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
        JOIN
    order_details od ON od.pizza_id = p.pizza_id
GROUP BY pt.name
ORDER BY revenue DESC
LIMIT 3;
```

name	Revenue
The Thai Chicken Pizza	43434.2
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

9. Calculate the percentage contribution of each pizza type to total revenue.

```sql
SELECT
    pt.category,
    CONCAT(ROUND(SUM(od.quantity * p.price) * 100 / (SELECT
                            SUM(od2.quantity * p2.price)
                        FROM
                            pizzas p2
                                JOIN
                            order_details od2 ON od2.pizza_id = p2.pizza_id),
                    2),
            '%') AS revenue_percentage
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
        JOIN
    order_details od ON od.pizza_id = p.pizza_id
GROUP BY pt.category
ORDER BY revenue_percentage DESC;
```

category	revenue_percentage
Classic	26.91%
Supreme	25.46%
Chicken	23.96%
Veggie	23.68%

10. Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```sql
select name,revenue from
(select category,name,revenue,
rank() over(partition by category order by revenue desc )as rn
from
(select
pt.category,
pt.name,
sum(od.quantity * p.price) as revenue
from order_details od join pizzas p
on od.pizza_id = p.pizza_id
join pizza_types pt on pt.pizza_type_id = p.pizza_type_id
group by pt.category,pt.name) as sales) as b
where rn <=3;
```

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5
The Classic Deluxe Pizza	38180.5
The Hawaiian Pizza	32273.25
The Pepperoni Pizza	30161.75
The Spicy Italian Pizza	34831.25
The Italian Supreme Pizza	33476.75
The Sicilian Pizza	30940.5
The Four Cheese Pizza	32265.70000000065
The Mexicana Pizza	26780.75
The Five Cheese Pizza	26066.5

THANK YOU



