

DATABASE SYSTEMS ENGINEERING AND DISTRIBUTED BACKENDDEVELOPMENT

PRACTICAL WEEK 2

Assignments

Problem Statement 1: SkyTrack Airline Management System

Roll.no - 2520030429

```
Command Prompt - mysql -u x + v
Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Himavanth Sai Ganesh>cd "C:\Program Files\MySQL\MySQL Server 8.0\bin"

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql -u root -p
Enter password: ****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 9
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE skytrack_db;
Query OK, 1 row affected (0.01 sec)

mysql> USE skytrack_db;
Database changed
mysql> CREATE TABLE Flights (
  -> flight_id INT PRIMARY KEY,
  -> flight_number VARCHAR(10) UNIQUE,
  -> source VARCHAR(50) NOT NULL,
  -> destination VARCHAR(50) NOT NULL,
  -> departure_date DATE,
  -> ticket_price DECIMAL(10,2),
  -> CHECK (ticket_price > 0)
  -> );
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE Passengers (
  -> passenger_id INT PRIMARY KEY,
  -> passenger_name VARCHAR(100) NOT NULL,
  -> email VARCHAR(100) UNIQUE
  -> );
Query OK, 0 rows affected (0.03 sec)
```

```
Command Prompt - mysql -u x + v

mysql> CREATE TABLE Bookings (
-> booking_id INT PRIMARY KEY,
-> passenger_id INT,
-> flight_id INT,
-> booking_date DATE,
-> FOREIGN KEY (passenger_id) REFERENCES Passengers(passenger_id),
-> FOREIGN KEY (flight_id) REFERENCES Flights(flight_id)
-> );
Query OK, 0 rows affected (0.04 sec)

mysql> SHOW TABLES;DESCRIBE Flights;
+-----+
| Tables_in_skytrack_db |
+-----+
| bookings              |
| flights               |
| passengers             |
+-----+
3 rows in set (0.00 sec)

+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| flight_id      | int           | NO   | PRI | NULL    |       |
| flight_number  | varchar(10)   | YES  | UNI | NULL    |       |
| source         | varchar(50)   | NO   |     | NULL    |       |
| destination    | varchar(50)   | NO   |     | NULL    |       |
| departure_date | date          | YES  |     | NULL    |       |
| ticket_price   | decimal(10,2) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> DESCRIBE Passengers;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| passenger_id   | int           | NO   | PRI | NULL    |       |
| passenger_name | varchar(100)  | NO   |     | NULL    |       |
| email          | varchar(100)  | YES  | UNI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
Command Prompt - mysql -u x + v

mysql> DESCRIBE Bookings;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| booking_id | int | NO | PRI | NULL | |
| passenger_id | int | YES | MUL | NULL | |
| flight_id | int | YES | MUL | NULL | |
| booking_date | date | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> INSERT INTO Flights VALUES
-> (1,'AI101','Hyderabad','Delhi','2026-08-01',5500),
-> (2,'AI102','Delhi','Mumbai','2026-08-02',4500),
-> (3,'AI103','Mumbai','Chennai','2026-08-03',4000),
-> (4,'AI104','Chennai','Bangalore','2026-08-04',3000),
-> (5,'AI105','Bangalore','Hyderabad','2026-08-05',3500),
-> (6,'AI106','Hyderabad','Pune','2026-08-06',4200),
-> (7,'AI107','Pune','Kolkata','2026-08-07',6000),
-> (8,'AI108','Kolkata','Delhi','2026-08-08',5200),
-> (9,'AI109','Delhi','Goa','2026-08-09',4800),
-> (10,'AI110','Goa','Hyderabad','2026-08-10',5000);
Query OK, 10 rows affected (0.01 sec)
Records: 10 Duplicates: 0 Warnings: 0

mysql> INSERT INTO Passengers VALUES
-> (1,'Rahul','rahul@gmail.com'),
-> (2,'Sneha','sneha@gmail.com'),
-> (3,'Kiran','kiran@gmail.com'),
-> (4,'Anjali','anjali@gmail.com'),
-> (5,'Vikram','vikram@gmail.com'),
-> (6,'Priya','priya@gmail.com'),
-> (7,'Arjun','arjun@gmail.com'),
-> (8,'Meena','meena@gmail.com'),
-> (9,'Ravi','ravi@gmail.com'),
-> (10,'Sita','sita@gmail.com');
Query OK, 10 rows affected (0.03 sec)
Records: 10 Duplicates: 0 Warnings: 0
```

```
Command Prompt - mysql -u x + v

mysql> INSERT INTO Bookings VALUES
-> (101,1,1,'2026-07-20'),
-> (102,2,2,'2026-07-21'),
-> (103,3,3,'2026-07-22'),
-> (104,4,4,'2026-07-23'),
-> (105,5,5,'2026-07-24'),
-> (106,6,6,'2026-07-25'),
-> (107,7,7,'2026-07-26'),
-> (108,8,8,'2026-07-27'),
-> (109,9,9,'2026-07-28'),
-> (110,10,10,'2026-07-29');
Query OK, 10 rows affected (0.01 sec)
Records: 10 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM Flights;
+-----+-----+-----+-----+-----+-----+
| flight_id | flight_number | source | destination | departure_date | ticket_price |
+-----+-----+-----+-----+-----+-----+
| 1 | AI101 | Hyderabad | Delhi | 2026-08-01 | 5500.00 |
| 2 | AI102 | Delhi | Mumbai | 2026-08-02 | 4500.00 |
| 3 | AI103 | Mumbai | Chennai | 2026-08-03 | 4000.00 |
| 4 | AI104 | Chennai | Bangalore | 2026-08-04 | 3000.00 |
| 5 | AI105 | Bangalore | Hyderabad | 2026-08-05 | 3500.00 |
| 6 | AI106 | Hyderabad | Pune | 2026-08-06 | 4200.00 |
| 7 | AI107 | Pune | Kolkata | 2026-08-07 | 6000.00 |
| 8 | AI108 | Kolkata | Delhi | 2026-08-08 | 5200.00 |
| 9 | AI109 | Delhi | Goa | 2026-08-09 | 4800.00 |
| 10 | AI110 | Goa | Hyderabad | 2026-08-10 | 5000.00 |
+-----+-----+-----+-----+-----+-----+
10 rows in set (0.00 sec)
```

```
Command Prompt - mysql -u x + v

mysql> SELECT * FROM Passengers;
+-----+-----+-----+
| passenger_id | passenger_name | email |
+-----+-----+-----+
| 1 | Rahul | rahul@gmail.com |
| 2 | Sneha | sneha@gmail.com |
| 3 | Kiran | kiran@gmail.com |
| 4 | Anjali | anjali@gmail.com |
| 5 | Vikram | vikram@gmail.com |
| 6 | Priya | priya@gmail.com |
| 7 | Arjun | arjun@gmail.com |
| 8 | Meena | meena@gmail.com |
| 9 | Ravi | ravi@gmail.com |
| 10 | Sita | sita@gmail.com |
+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT * FROM Bookings;
+-----+-----+-----+-----+
| booking_id | passenger_id | flight_id | booking_date |
+-----+-----+-----+-----+
| 101 | 1 | 1 | 2026-07-20 |
| 102 | 2 | 2 | 2026-07-21 |
| 103 | 3 | 3 | 2026-07-22 |
| 104 | 4 | 4 | 2026-07-23 |
| 105 | 5 | 5 | 2026-07-24 |
| 106 | 6 | 6 | 2026-07-25 |
| 107 | 7 | 7 | 2026-07-26 |
| 108 | 8 | 8 | 2026-07-27 |
| 109 | 9 | 9 | 2026-07-28 |
| 110 | 10 | 10 | 2026-07-29 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT
-> Passengers.passenger_name,
-> Flights.flight_number,
-> Flights.source,
-> Flights.destination
-> FROM Bookings
```

```
mysql> SELECT
-> Passengers.passenger_name,
-> Flights.flight_number,
-> Flights.source,
-> Flights.destination
-> FROM Bookings
-> INNER JOIN Passengers
-> ON Bookings.passenger_id = Passengers.passenger_id
-> INNER JOIN Flights
-> ON Bookings.flight_id = Flights.flight_id;
```

passenger_name	flight_number	source	destination
Rahul	AI101	Hyderabad	Delhi
Sneha	AI102	Delhi	Mumbai
Kiran	AI103	Mumbai	Chennai
Anjali	AI104	Chennai	Bangalore
Vikram	AI105	Bangalore	Hyderabad
Priya	AI106	Hyderabad	Pune
Arjun	AI107	Pune	Kolkata
Meena	AI108	Kolkata	Delhi
Ravi	AI109	Delhi	Goa
Sita	AI110	Goa	Hyderabad

10 rows in set (0.00 sec)

```
mysql> SELECT
-> destination,
-> COUNT(*) AS total_flights
-> FROM Flights
-> GROUP BY destination;
```

destination	total_flights
Delhi	2
Mumbai	1
Chennai	1
Bangalore	1
Hyderabad	2
Pune	1
Kolkata	1
Goa	1

```
Command Prompt - mysql -u x + v
| destination | total_flights |
+-----+-----+
| Delhi       | 2             |
| Mumbai      | 1             |
| Chennai     | 1             |
| Bangalore   | 1             |
| Hyderabad   | 2             |
| Pune        | 1             |
| Kolkata     | 1             |
| Goa         | 1             |
+-----+-----+
8 rows in set (0.00 sec)

mysql> CREATE TABLE Flight_History(
  -> history_id INT PRIMARY KEY,
  -> flight_id INT,
  -> flight_number VARCHAR(10),
  -> action_date DATE
  -> );
Query OK, 0 rows affected (0.03 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO Flights
  -> VALUES
  -> (11,'AI111','Hyderabad','Jaipur','2026-08-11',6200);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO Flight_History
  -> VALUES
  -> (1,11,'AI111','2026-07-30');
Query OK, 1 row affected (0.00 sec)

mysql> COMMIT;
Query OK, 0 rows affected (0.01 sec)

mysql> ROLLBACK;
Query OK, 0 rows affected (0.00 sec)

mysql> CREATE INDEX idx_flight_number
```

```
mysql> CREATE INDEX idx_flight_number
  -> ON Flights(flight_number);
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM Flights
  -> WHERE flight_number='AI105';
+-----+-----+-----+-----+-----+-----+
| flight_id | flight_number | source   | destination | departure_date | ticket_price |
+-----+-----+-----+-----+-----+-----+
| 5         | AI105        | Bangalore | Hyderabad   | 2026-08-05     | 3500.00      |
+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql> SELECT * FROM Flights
  -> WHERE destination='Hyderabad';
+-----+-----+-----+-----+-----+-----+
| flight_id | flight_number | source   | destination | departure_date | ticket_price |
+-----+-----+-----+-----+-----+-----+
| 5         | AI105        | Bangalore | Hyderabad   | 2026-08-05     | 3500.00      |
| 10        | AI110        | Goa      | Hyderabad   | 2026-08-10     | 5000.00      |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> |
```

Problem Statement 2: MediCare Hospital Management System

```
Command Prompt - mysql -u × + ▾
Microsoft Windows [Version 10.0.26200.8875]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Himavanth Sai Ganesh>cd "C:\Program Files\MySQL\MySQL Server 8.0\bin"

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql -u root -p
Enter password: ****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 11
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE medicare_db;
Query OK, 1 row affected (0.01 sec)

mysql> USE medicare_db;
Database changed

mysql> CREATE TABLE Doctors (
    -> doctor_id INT PRIMARY KEY,
    -> doctor_name VARCHAR(100) NOT NULL,
    -> specialization VARCHAR(100),
    -> consultation_fee DECIMAL(10,2),
    -> CHECK (consultation_fee > 0)
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE Patients (
    -> patient_id INT PRIMARY KEY,
    -> patient_name VARCHAR(100) NOT NULL,
    -> email VARCHAR(100) UNIQUE
    -> );
Query OK, 0 rows affected (0.10 sec)

mysql> CREATE TABLE Appointments (
    -> appointment_id INT PRIMARY KEY,
    -> doctor_id INT,
    -> patient_id INT,
    -> appointment_date DATE,
    -> FOREIGN KEY (doctor_id) REFERENCES Doctors(doctor_id),
    -> FOREIGN KEY (patient_id) REFERENCES Patients(patient_id)
    -> );
Query OK, 0 rows affected (0.11 sec)

mysql> SHOW TABLES;
+-----+
| Tables_in_medicare_db |
+-----+
```

```
mysql> SHOW TABLES;
```

```
+-----+
| Tables_in_medicare_db |
+-----+
| appointments          |
| doctors               |
| patients              |
+-----+
3 rows in set (0.00 sec)
```

```
mysql> DESCRIBE Doctors;
```

```
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| doctor_id      | int           | NO   | PRI | NULL    |       |
| doctor_name    | varchar(100)  | NO   |     | NULL    |       |
| specialization | varchar(100)  | YES  |     | NULL    |       |
| consultation_fee | decimal(10,2) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> DESCRIBE Patients;
```

```
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| patient_id     | int           | NO   | PRI | NULL    |       |
| patient_name   | varchar(100)  | NO   |     | NULL    |       |
| email          | varchar(100)  | YES  | UNI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> DESCRIBE Appointments;
```

```
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| appointment_id | int           | NO   | PRI | NULL    |       |
| doctor_id      | int           | YES  | MUL | NULL    |       |
| patient_id     | int           | YES  | MUL | NULL    |       |
| appointment_date | date          | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
Command Prompt - mysql -u x + v
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> INSERT INTO Doctors VALUES
-> (1,'Dr. Ramesh','Cardiology',800),
-> (2,'Dr. Suresh','Neurology',900),
-> (3,'Dr. Kavitha','Orthopedics',700),
-> (4,'Dr. Anjali','Dermatology',600),
-> (5,'Dr. Rajesh','Pediatrics',500),
-> (6,'Dr. Mahesh','ENT',550),
-> (7,'Dr. Priya','Gynecology',750),
-> (8,'Dr. Arjun','Ophthalmology',650),
-> (9,'Dr. Kiran','Cardiology',850),
-> (10,'Dr. Meena','General Medicine',400);
Query OK, 10 rows affected (0.06 sec)
Records: 10 Duplicates: 0 Warnings: 0

mysql> INSERT INTO Patients VALUES
-> (1,'Rahul','rahul@gmail.com'),
-> (2,'Sneha','sneha@gmail.com'),
-> (3,'Kiran','kiran@gmail.com'),
-> (4,'Anjali','anjali@gmail.com'),
-> (5,'Vikram','vikram@gmail.com'),
-> (6,'Priya','priya@gmail.com'),
-> (7,'Arjun','arjun@gmail.com'),
-> (8,'Meena','meena@gmail.com'),
-> (9,'Ravi','ravi@gmail.com'),
-> (10,'Sita','sita@gmail.com');
Query OK, 10 rows affected (0.05 sec)
Records: 10 Duplicates: 0 Warnings: 0

mysql> INSERT INTO Appointments VALUES
-> (101,1,1,'2026-08-01'),
-> (102,2,2,'2026-08-02'),
-> (103,3,3,'2026-08-03'),
-> (104,4,4,'2026-08-04'),
-> (105,5,5,'2026-08-05'),
-> (106,6,6,'2026-08-06'),
-> (107,7,7,'2026-08-07'),
-> (108,8,8,'2026-08-08')
```

```
Command Prompt - mysql -u × + v
-> (109,9,9,'2026-08-09'),
-> (110,10,10,'2026-08-10');
Query OK, 10 rows affected (0.07 sec)
Records: 10 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM Doctors;
+-----+-----+-----+-----+
| doctor_id | doctor_name | specialization | consultation_fee |
+-----+-----+-----+-----+
| 1 | Dr. Ramesh | Cardiology | 800.00 |
| 2 | Dr. Suresh | Neurology | 900.00 |
| 3 | Dr. Kavitha | Orthopedics | 700.00 |
| 4 | Dr. Anjali | Dermatology | 600.00 |
| 5 | Dr. Rajesh | Pediatrics | 500.00 |
| 6 | Dr. Mahesh | ENT | 550.00 |
| 7 | Dr. Priya | Gynecology | 750.00 |
| 8 | Dr. Arjun | Ophthalmology | 650.00 |
| 9 | Dr. Kiran | Cardiology | 850.00 |
| 10 | Dr. Meena | General Medicine | 400.00 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT * FROM Patients;
+-----+-----+-----+
| patient_id | patient_name | email |
+-----+-----+-----+
| 1 | Rahul | rahul@gmail.com |
| 2 | Sneha | sneha@gmail.com |
| 3 | Kiran | kiran@gmail.com |
| 4 | Anjali | anjali@gmail.com |
| 5 | Vikram | vikram@gmail.com |
| 6 | Priya | priya@gmail.com |
| 7 | Arjun | arjun@gmail.com |
| 8 | Meena | meena@gmail.com |
| 9 | Ravi | ravi@gmail.com |
| 10 | Sita | sita@gmail.com |
+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT * FROM Appointments;
```

```
Command Prompt - mysql -u x + v

mysql> SELECT * FROM Appointments;
+-----+-----+-----+-----+
| appointment_id | doctor_id | patient_id | appointment_date |
+-----+-----+-----+-----+
| 101 | 1 | 1 | 2026-08-01 |
| 102 | 2 | 2 | 2026-08-02 |
| 103 | 3 | 3 | 2026-08-03 |
| 104 | 4 | 4 | 2026-08-04 |
| 105 | 5 | 5 | 2026-08-05 |
| 106 | 6 | 6 | 2026-08-06 |
| 107 | 7 | 7 | 2026-08-07 |
| 108 | 8 | 8 | 2026-08-08 |
| 109 | 9 | 9 | 2026-08-09 |
| 110 | 10 | 10 | 2026-08-10 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT
  -> Patients.patient_name,
  -> Doctors.doctor_name,
  -> Doctors.specialization,
  -> Appointments.appointment_date
  -> FROM Appointments
  -> INNER JOIN Patients
  -> ON Appointments.patient_id = Patients.patient_id
  -> INNER JOIN Doctors
  -> ON Appointments.doctor_id = Doctors.doctor_id;
+-----+-----+-----+-----+
| patient_name | doctor_name | specialization | appointment_date |
+-----+-----+-----+-----+
| Rahul | Dr. Ramesh | Cardiology | 2026-08-01 |
| Sneha | Dr. Suresh | Neurology | 2026-08-02 |
| Kiran | Dr. Kavitha | Orthopedics | 2026-08-03 |
| Anjali | Dr. Anjali | Dermatology | 2026-08-04 |
| Vikram | Dr. Rajesh | Pediatrics | 2026-08-05 |
| Priya | Dr. Mahesh | ENT | 2026-08-06 |
| Arjun | Dr. Priya | Gynecology | 2026-08-07 |
| Meena | Dr. Arjun | Ophthalmology | 2026-08-08 |
| Ravi | Dr. Kiran | Cardiology | 2026-08-09 |
| Sita | Dr. Meena | General Medicine | 2026-08-10 |
+-----+-----+-----+-----+
```

```
Command Prompt - mysql -u X + v
| Sita | Dr. Meena | General Medicine | 2026-08-10 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)

mysql> SELECT
-> specialization,
-> COUNT(*) AS total_doctors
-> FROM Doctors
-> GROUP BY specialization;
+-----+-----+
| specialization | total_doctors |
+-----+-----+
| Cardiology | 2 |
| Neurology | 1 |
| Orthopedics | 1 |
| Dermatology | 1 |
| Pediatrics | 1 |
| ENT | 1 |
| Gynecology | 1 |
| Ophthalmology | 1 |
| General Medicine | 1 |
+-----+-----+
9 rows in set (0.00 sec)

mysql> CREATE TABLE Doctor_History (
-> history_id INT PRIMARY KEY,
-> doctor_id INT,
-> doctor_name VARCHAR(100),
-> registration_date DATE
-> );
Query OK, 0 rows affected (0.18 sec)

mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO Doctors
-> VALUES
-> (11, 'Dr. Sanjay', 'Cardiology', 900);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO Doctor_History
```

```
Command Prompt - mysql -u X + v
mysql> INSERT INTO Doctors
      -> VALUES
      -> (11,'Dr. Sanjay','Cardiology',900);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Doctor_History
      -> VALUES
      -> (1,11,'Dr. Sanjay','2026-07-30');
Query OK, 1 row affected (0.00 sec)
```

```
mysql> COMMIT;
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> CREATE INDEX idx_specialization
      -> ON Doctors(specialization);
Query OK, 0 rows affected (0.10 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> SELECT * FROM Doctors
      -> WHERE specialization='Cardiology';
```

doctor_id	doctor_name	specialization	consultation_fee
1	Dr. Ramesh	Cardiology	800.00
9	Dr. Kiran	Cardiology	850.00
11	Dr. Sanjay	Cardiology	900.00

```
3 rows in set (0.00 sec)
```

```
mysql> |
```