RAJALAKSHMI ENGINEERING COLLEGE

Himaya Shree V 250701243-2025-CSE

H2

Started on	Friday, 28 August 2026, 4:01 PM
State	Finished
Completed on	Friday, 28 August 2026, 4:10 PM
Time taken	9 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>
int compareAsc(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}
int compareDesc(const void *a, const void *b) {
    return (*(int*)b - *(int*)a);
}
int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;
    int *array_One = (int*)malloc(n * sizeof(int));
    int *array_Two = (int*)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) scanf("%d", &array_One[i]);
    for (int i = 0; i < n; i++) scanf("%d", &array_Two[i]);
    qsort(array_One, n, sizeof(int), compareAsc);
    qsort(array_Two, n, sizeof(int), compareDesc);
    long long min_sum = 0;
    for (int i = 0; i < n; i++) {
        min_sum += (long long)array_One[i] * array_Two[i];
    }
    printf("%lld\n", min_sum);
    free(array_One);
    free(array_Two);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course