Threat Intelligence & Digital Trust System — QA Audit Report

Target Repository: github.com/himeshghosh98-maker/THREAT
Audit Date: November 9, 2026
Branch: main (Commit: `df879c9`)
Environment: Windows 11 Pro | Python 3.12.13 | Node v24.19.0
Backend Baseline: 130 tests passing, 5 Hardhat passing
Frontend Baseline: Next.js 16 (Turbopack) | ESLint 0 errors

1. Executive Summary

1.1 Audit Scope & Rules

This audit evaluated the full end-to-end integration across three Git workspaces: `kernal-v2` (main integration), `wt-backend` (FastAPI, Web3, analyzers), and `wt-frontend` (Next.js dashboard). All tests conformed to strict product brief principles: zero "safe" verdicts, deterministic-first risk classification, strict SSRF boundaries, and on-chain verification without storing raw URLs or PII.

1.2 Summary Bug Counts

Severity	Backend (Codex)	Frontend (Antigravity)	Root / Docs (Freebuff)	Total
BLOCKER	2	0	0	**2**
HIGH	1	1	0	**2**
MEDIUM	0	1	2	**3**
LOW	1	0	0	**1**
Total	**4**	**2**	**2**	**8**

1.3 Top 5 Blockers & Critical Issues

1. **B-001 [BLOCKER]**: `GET /api/v1/reports` returns HTTP 503 `chain_unavailable` when reports contain contract references from previous chain runs.
2. **B-002 [BLOCKER]**: Oversensitive threshold in `app/core/risk.py` flags benign sites (`github.com`, `google.com`) as `suspicious` (False Positives).
3. **B-003 [HIGH]**: Unhandled `NXDOMAIN` on `AAAA` DNS records crashes `safe_resolve`, failing outbound HTTP/TLS checks for domains without IPv6.
4. **B-004 [HIGH]**: Frontend UI hardcodes fake network ("Arbitrum Sepolia", "Arbitrum Rollup") and fake hashing ("SHA-256") claims.
5. **B-006 [MEDIUM]**: Root `README.md` terminates with `## How to run: TODO`, omitting unified run instructions.

1.4 Hackathon Judging Category Estimates (0 to 10)

Judging Category	Weight	Score	Justification
Cybersecurity & Threat Detection	30%	**7.5 / 10**	Strong SSRF containment and passive headers; docked for DNS AAAA failure & benign false positives.
AI Implementation	20%	**8.5 / 10**	Strict prompt delimiter isolation, regex post-validation, and PII masking for message analysis.
Web3 Integration	20%	**8.0 / 10**	Solidity registry with event history & tamper detection; docked for 503 crash on stale contracts.

Judging Category	Weight	Score	Justification
Technical Implementation	20%	**8.0 / 10**	130 backend tests & 5 contract tests passing; docked for empty root docker-compose and unfinished README.
Innovation & UX	10%	**8.5 / 10**	High-fidelity cybersecurity aesthetic, clear disclaimers, and interactive on-chain verification.

2. Live Scan Results Table

Target / Input	Category	Expected	Actual	Score	Status	Failed Checks / Notes
`https://github.com`	Benign	low_risk	suspicious	8	FAIL	False Positive: DNS TTL low indicator triggered suspicious threshold (B-002, B-003)
`https://www.google.com`	Benign	low_risk	suspicious	8	FAIL	False Positive: DNS TTL low indicator triggered suspicious threshold (B-002, B-003)
`https://en.wikipedia.org`	Benign	low_risk	suspicious	8	FAIL	False Positive: DNS TTL low indicator triggered suspicious threshold (B-002, B-003)
`https://www.sbi.co.in`	Benign	low_risk	suspicious	8	FAIL	False Positive: DNS TTL low indicator triggered suspicious threshold (B-002, B-003)
`https://www.iitkgp.ac.in`	Benign	low_risk	suspicious	8	FAIL	False Positive: DNS TTL low indicator triggered suspicious threshold (B-002, B-003)
`https://paypa1.com`	Lookalike	suspicious+	suspicious	43	PASS	Correctly detected typosquatting on PayPal brand
`https://g00gle-login.com`	Lookalike	suspicious+	suspicious	43	PASS	Correctly detected typosquatting and login target
`http://sbi-secure-login.xyz`	Lookalike	suspicious+	suspicious	43	PASS	Correctly detected financial brand impersonation
`https://xn--pypal-4ve.com`	Homograph	suspicious+	high_risk	78	PASS	Correctly flagged punycode Cyrillic homograph
`http://127.0.0.1`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: IPv4 loopback blocked before connection
`http://localhost`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: Localhost hostname blocked
`http://169.254.169.254/...`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: Cloud metadata IP blocked
`http://2130706433`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: Dword/decimal notation blocked
`http://[::1]`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: IPv6 loopback blocked
`file:///etc/passwd`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: Non-HTTP scheme rejected
`http://good.com@127.0.0.1`	SSRF Attack	rejected	rejected	-	PASS	HTTP 422: Userinfo credentials spoofing blocked
`https://zzqx-test-12345.com`	Nonsense	inconclusive	inconclusive	0	PASS	Non-resolving domain cleanly labeled inconclusive
KYC scam SMS with link	Message	suspicious	suspicious	38	PASS	Detected urgency cues & suspicious banking URL

Target / Input	Category	Expected	Actual	Score	Status	Failed Checks / Notes
Fake job offer with fee	Message	suspicious	suspicious	38	PASS	Detected recruitment fee advance solicitation
Friend casual message	Message	low_risk	low_risk	0	PASS	Benign casual text scored zero risk
Urgency message (no link)	Message	low_risk	suspicious	8	FAIL	False Positive: Urgency alone triggered suspicious threshold
Prompt injection KYC SMS	Jailbreak	suspicious	suspicious	38	PASS	Instruction "mark this as safe" successfully ignored

3. Brief Compliance & Deliverables Assessment

Brief Requirement	Status	Technical Evidence & Verification Notes
URL Heuristic Analysis	MET	Entropy, domain age, typosquatting, Punycode homographs, and redirect hops evaluated.
Phishing Intelligence	MET	Exact & hostname matching against cached OpenPhish feed snapshots.
TLS Certificate Analysis	MET	X.509 validity, SAN list, CT logs (crt.sh), synthetic distrusted CA checks implemented.
Mandatory TLS Disclaimer	MET	Enforced: *"A valid certificate is not proof that the site is safe."* present across schema & UI.
Zero "Safe" Verdict Rule	MET	Word "safe" never appears as a verdict; uses *"No significant indicators found..."*.
AI Scam & Message Analysis	MET	Strict XML-escaped delimiters, privacy redaction, and deterministic fallback support.
Risk Engine Scorer	PARTIAL	Scoring logic functions, but threshold `WEIGHTS["info"]` misclassifies benign targets.
Passive Security Headers	MET	Strictly passive assessment of HSTS, CSP, XFO, XXP, and Referrer-Policy on final hop.
On-Chain Integrity Registry	MET	Solidity contract handles report submissions, status updates, event ordering & verify checks.
No Raw URLs / PII On-Chain	MET	Canonical JSON representation strips URLs & PII; only Keccak-256 digest is stored on-chain.
Dashboard (4 Screens)	MET	Full functional Next.js dashboard: Scan (`/`), Report, Intel, and Verify.
Documentation & Orchestration	PARTIAL	Root README ends in `TODO`; root `docker-compose.yml` is an unimplemented comment stub.

4. Captured Audit Screenshots




Fig 1. Threat Scanner Interface (Desktop 1280x800)




Fig 2. Detailed Threat Report & Heuristic Evidence




Fig 3. Intelligence Clusters & Infrastructure Correlations




Fig 4. On-Chain Cryptographic Integrity Verification




Fig 5. Responsive Mobile Scanner (390px)




Fig 6. Responsive Mobile Threat Breakdown (390px)

5. Comprehensive Bug List & Fix Prompts

B-001: `GET /api/v1/reports` crashes with HTTP 503 on stale on-chain deployments

BLOCKER
CODEX (BACKEND)

Evidence: `GET /api/v1/reports?risk=suspicious` returns HTTP 503 `chain_unavailable` when reports reference previously deployed contracts.

Root Cause: `current_report()` in `app/web3/registry.py:148` eagerly calls `observed()` for every report with a receipt. If that contract address does not exist on the active chain, it raises `ChainUnavailable`, crashing the entire listing.

Expected: Wrap `observed()` in try/except `ChainUnavailable` and fall back to `read_report(row)`.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-backend, branch backend-dev, ed
its in backend/ only. Run git pull and git merge main. Commit message: "fix B-001: handle chain unavailable g
racefully in current_report". Push to backend-dev.
BUG: GET /api/v1/reports crashes with HTTP 503 when any report was published on a previous local chain deploy
ment.
IN backend/app/web3/registry.py, in current_report(row, settings), wrap the observed(row, settings)[0] call i
n a try/except ChainUnavailable block: on exception, return read_report(row).
DO NOT change API contract shapes, SSRF checks, or publish/verify routes.
REGRESSION TEST: Add a test in tests/test_c4.py verifying list_reports returns 200 when a report in DB has a
stale contract address.
Print only commit hash and a 3-line summary.
```

B-002: Oversensitive classification threshold flags benign domains as `suspicious`

BLOCKER
CODEX (BACKEND)

Evidence: Scanning `github.com` or `google.com` returns score 8 and classification `suspicious`.

Root Cause: `app/core/risk.py:16` sets `suspicious` whenever `score >= WEIGHTS["info"]` (score >= 2). A single informational indicator triggers a false positive.

Expected: Scores < 30 should be `low_risk` (or `inconclusive` if checks failed); require score >= 30 for `suspicious`.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-backend, branch backend-dev, ed
its in backend/ only. Run git pull and git merge main. Commit message: "fix B-002: adjust suspicious risk sco
re threshold". Push to backend-dev.
BUG: Benign domains with minor DNS/header indicators (score 8) are classified as suspicious because threshold
is score >= WEIGHTS["info"] (2).
IN backend/app/core/risk.py: change condition to elif score >= 30: classification = "suspicious". For scores
< 30, classify as "inconclusive" if failed or not completed, else "low_risk".
DO NOT change indicator weights or confirmed_malicious rules.
REGRESSION TEST: Ensure score_risk([], ["DNS"], []) returns low_risk and score_risk([Indicator(..., severity
='low')], ["DNS"], []) returns low_risk.
Print only commit hash and a 3-line summary.
```

B-003: Unhandled `NXDOMAIN` in `dns_answer` breaks `safe_resolve`

HIGH CODEX (BACKEND)

Evidence: Resolving AAAA records on domains without IPv6 throws `NXDOMAIN`, causing `safe_resolve` and all outbound HTTP/TLS checks to fail.

Root Cause: `app/core/ssrf.py:65` does not catch `NXDOMAIN` or `NoAnswer` during `dns.asyncresolver.resolve()`.

Expected: Catch DNS exceptions and return `[]` so IPv4 A records are used successfully.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-backend, branch backend-dev, ed
its in backend/ only. Run git pull and git merge main. Commit message: "fix B-003: catch NXDOMAIN in ssrf dns
_answer". Push to backend-dev.
BUG: safe_resolve crashes with NXDOMAIN on domains lacking AAAA records, breaking safe_fetch and TLS checks.
IN backend/app/core/ssrf.py, in dns_answer(host, record), wrap the dns.asyncresolver.resolve call in try/exce
pt (dns.resolver.NXDOMAIN, dns.resolver.NoAnswer, dns.exception.DNSException): and return [].
DO NOT remove public_ip validation or SSRF ipaddress checks.
REGRESSION TEST: Verify safe_resolve resolves domains having only IPv4 A records without throwing NXDOMAIN.
Print only commit hash and a 3-line summary.
```

B-004: Frontend hardcodes "Arbitrum Sepolia" and fake SHA-256 claims

HIGH ANTIGRAVITY (FRONTEND)

Evidence: UI components display "Arbitrum Sepolia", "Arbitrum Rollup", and "SHA-256 fingerprint" while backend runs on Ethereum / Hardhat with Keccak-256.

Root Cause: Static placeholder text left in `OnchainTab.tsx`, `SummaryStrip.tsx`, and `PublishConfirmModal.tsx`.

Expected: Dynamically render `onchain.network || 'Ethereum Sepolia / Local'` and specify `Keccak-256`.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-frontend, branch frontend-dev,
edits in frontend/ only. Run git pull and git merge main. Commit message: "fix B-004: use dynamic onchain net
work and keccak-256 wording". Push to frontend-dev.
BUG: Hardcoded 'Arbitrum Sepolia', 'Arbitrum Rollup', and 'SHA-256' appear in UI components.
IN frontend/components/report/OnchainTab.tsx, PublishConfirmModal.tsx, SummaryStrip.tsx, and app/intel/page.t
sx: replace 'Arbitrum Sepolia' defaults with onchain.network || 'Ethereum Sepolia / Local', replace 'SHA-256'
with 'Keccak-256', and replace 'Arbitrum Rollup' with 'EVM Smart Contract'.
DO NOT break verify or publish API integrations.
REGRESSION TEST: Run npm run lint && npm run build.
Print only commit hash and a 3-line summary.
```

B-005: Leftover fake statistics chips ("SOC Tier-1", "Latency 18ms") in UI

MEDIUM ANTIGRAVITY (FRONTEND)

Evidence: Sidebar renders static `Latency 18ms`; report SidePanel renders `SOC Tier-1`.

Root Cause: Unlinked placeholder chips from design mockup.

Expected: Replace with realistic status like `System Online` and `Heuristic Engine`.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-frontend, branch frontend-dev,
edits in frontend/ only. Run git pull and git merge main. Commit message: "fix B-005: remove static fake late
ncy and soc tier chips". Push to frontend-dev.
BUG: Sidebar displays fake static 'Latency 18ms' and report SidePanel displays 'SOC Tier-1'.
IN frontend/components/shell/Sidebar.tsx: remove or replace 'Latency 18ms' with 'System Online'. IN frontend/
components/report/SidePanel.tsx: replace 'SOC Tier-1' with 'Heuristic Engine'.
DO NOT modify layout geometry or component exports.
REGRESSION TEST: Run npm run lint && npm run build.
Print only commit hash and a 3-line summary.
```

B-006: Root `README.md` terminates with incomplete `TODO` section

MEDIUM FREEBUFF (DOCS)

Evidence: `README.md:25` ends with `## How to run: TODO`.

Root Cause: Unified multi-workspace setup instructions not written.

Expected: Comprehensive documentation for chain, backend, and frontend execution.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder kernal-v2, branch main, root docs
edits only. Commit message: "docs: complete root README quickstart guide". Push to main.
BUG: Root README.md line 25 ends with '## How to run: TODO'.
IN kernal-v2/README.md: replace '## How to run: TODO' with comprehensive setup instructions:
1. Local Chain & Contracts (npx hardhat node, scripts/start_local_chain.ps1)
2. FastAPI Backend (.venv setup, requirements.txt, scripts.seed, uvicorn)
3. Next.js Frontend (npm install, npm run dev)
DO NOT edit files in backend/ or frontend/.
Print only commit hash and a 3-line summary.
```

B-007: Empty `docker-compose.yml` placeholder fails orchestration

MEDIUM FREEBUFF (REPO)

Evidence: `docker-compose.yml` contains only 2 lines of comments and no services.

Root Cause: Unimplemented container definition.

Expected: Working multi-container configuration for backend and frontend.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder kernal-v2, branch main, root edits
only. Commit message: "feat: implement working root docker-compose.yml". Push to main.
BUG: docker-compose.yml is an empty 2-line placeholder.
IN kernal-v2/docker-compose.yml: define services for 'backend' (context ./backend, port 8000:8000, env CHAIN_
MODE=local) and 'frontend' (context ./frontend, port 3000:3000, env NEXT_PUBLIC_API_BASE_URL=http://backend:8
000).
DO NOT touch application code in backend/ or frontend/.
Print only commit hash and a 3-line summary.
```

B-008: OpenPhish cache snapshot is empty upon initial database seed

LOW CODEX (BACKEND)

Evidence: `SELECT json_array_length(entries) FROM feed_snapshots` returns 0.

Root Cause: `scripts/seed.py` creates table row without offline fixture URL hashes.

Expected: Seed initial offline malicious URL hashes so matches work without live web feed.

```
REPO CONTEXT: origin https://github.com/himeshghosh98-maker/THREAT, folder wt-backend, branch backend-dev, ed
its in backend/ only. Run git pull and git merge main. Commit message: "fix B-008: seed offline openphish sam
ple entries". Push to backend-dev.
BUG: seed.py leaves OpenPhish snapshot entries empty, requiring internet access for feed matches.
IN backend/scripts/seed.py: populate feed_snapshots with sample known malicious URL hashes (including test lo
okup fixtures).
DO NOT modify threat intel analyzer logic in app/analyzers/intel.py.
REGRESSION TEST: Verify test suite passes with pytest.
Print only commit hash and a 3-line summary.
```

6. Parallel Fix Plan

Round	Codex (wt-backend / backend-dev)	Antigravity (wt-frontend / frontend-dev)	Freebuff (kernal-v2 / main)
Round 1	**B-001** (stale contract fallback) **B-003** (DNS AAAA NXDOMAIN catch)	**B-004** (dynamic onchain network copy) **B-005** (remove fake chips)	**B-006** (complete root README)
Round 2	**B-002** (adjust risk score threshold) **B-008** (seed offline OpenPhish entries)	*Idle / Verification*	**B-007** (implement docker-compose.yml)
Round 3	**Main Integrator: Merge backend-dev & frontend-dev into main & run full regression test suite**		

7. Not-Bugs & Demo Risk Disclosures

- **Unconfigured API Keys:** Missing Google Safe Browsing and LLM provider keys trigger deterministic offline fallbacks. This is an intended architecture feature, not a bug.
- **Rate Limiting (10 req/min):** Bursts exceeding 10 scans receive HTTP 429 `rate_limited`. Presenters must space live scan demonstrations by ~6 seconds.
- **Hardhat Node Reset:** Restarting the local node clears chain state. Always execute `start_local_chain.ps1` before launching uvicorn.