Kubernetes Project using EKS:

Pre-Requirements:

```
Install the Aws-Cli, Eksctl, Kubectl in the os.
```

Aws-cli Installation:

or use below command:

```
curl "https://s3.amazonaws.com/aws-cli/awscli-bundle.zip" -o "awscli-bundle.zip"
  unzip awscli-bundle.zip
  ./awscli-bundle/install -b ~/bin/aws
```

Installation of eks:

```
* sudo apt update
  * curl --silent --location
"https://github.com/weaveworks/eksctl/releases/latest/download/eksctl_$(uname -
s)_amd64.tar.gz" | tar xz -C /tmp
     * sudo mv /tmp/eksctl /usr/local/bin
     * eksctl version
```

Installation of Kubectl on Ubuntu:

```
* curl -LO "https://dl.k8s.io/release/$(curl -L -s
https://dl.k8s.io/release/stable.txt)/bin/linux/amd64/kubectl"

* sudo install -o root -g root -m 0755 kubectl /usr/local/bin/kubectl

* chmod +x kubectl

* mkdir -p ~/.local/bin

* mv ./kubectl ~/.local/bin/kubectl
```

Create a Cluster in Aws

```
* go to aws console and create a cluster before that create a role anyone in the below mentioned.
```

^{* 1.} AWS Service: eks2.

Connect eks to kubectl:

```
* aws eks update-kubeconfig --name safexpay-new --region ap-south-1
* aws configure:
* AWS Access Key ID [None]: AKIAWRMAGMDWCO3JX3FK
* AWS Secret Access Key [None]: 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
* Default region name [None]: ap-south-1
* Default output format [None]:
```

Creating the ingress controller-nlb:

```
* kubectl create serviceaccount nginx-ingress-controller
* kubectl create clusterrolebinding nginx-ingress-controller --clusterrole=cluster-
admin --serviceaccount=default:nginx-ingress-controller
* kubectl create namespace ingress-nginx
* mkdir nginx-ingress-controller
* helm repo add ingress-nginx https://kubernetes.github.io/ingress-nginx
* helm repo update
* helm install nginx-ingress ingress-nginx/ingress-nginx --namespace ingress-nginx --set controller.service.annotations."service\.beta\.kubernetes\.io/aws-load-balancer-
type"=classic
```

Nginx-ingress-controller.yaml file

```
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
 name: backend-ingress
 namespace: ingress-nginx
 annotations:
    nginx.ingress.kubernetes.io/ssl-redirect: "false"
    kubernetes.io/ingress.class: 'nginx'
    nginx.ingress.kubernetes.io/use-regex: "true"
spec:
  rules:
    - http:
        paths:
          - path: /ms-auth-server-1-0
            pathType: Prefix
            backend:
              service:
                name: auth-service
                port:
                  number: 8201
          - path: /ms-otp-service-1-0
            pathType: Prefix
            backend:
              service:
                name: otp-service
                port:
                  number: 8102
          - path: /core-service-1-0
```

```
pathType: Prefix
 backend:
    service:
      name: core-service
      port:
        number: 9099
- path: /ms-portal-1-0
  pathType: Prefix
backend:
    service:
      name: portal-service
      port:
        number: 8008
- path: /dao-service-1-0
  pathType: Prefix
  backend:
    service:
      name: dao-service
      port:
        number: 8100
- path: /cache-service-1-0
  pathType: Prefix
  backend:
    service:
      name: cache-service
      port:
        number: 9098
- path: /kafka-service-1-0
  pathType: Prefix
  backend:
    service:
      name: kafka-service
      port:
        number: 8105
- path: /pg-cron-1-0
  pathType: Prefix
  backend:
    service:
      name: pg-cron
      port:
        number: 8104
- path: /kafka-service(/|$)(.*)
  pathType: ImplementationSpecific
  backend:
    service:
      name: kafka-service
      port:
         number: 9092
```

Then use backend and frontend deployment files where you can see in the name of

 $Backend_Deployment_files_yamls$

Frontend_deployment_files