

Class 10 Mini Project

AUTHOR

Jimmi Nguyen

Exploratory Analysis of Halloween Candy

Get the data from the FiveThirtyEight GitHub repo

```
candy_file <- "candy-data.csv"

candy = read.csv(candy_file, row.names=1)
head(candy)
```

	chocolate	fruity	caramel	peanutyalmondy	nougat	crispedricewafer
100 Grand	1	0	1	0	0	1
3 Musketeers	1	0	0	0	1	0
One dime	0	0	0	0	0	0
One quarter	0	0	0	0	0	0
Air Heads	0	1	0	0	0	0
Almond Joy	1	0	0	1	0	0

	hard	bar	pluribus	sugarpercent	pricepercent	winpercent
100 Grand	0	1	0	0.732	0.860	66.97173
3 Musketeers	0	1	0	0.604	0.511	67.60294
One dime	0	0	0	0.011	0.116	32.26109
One quarter	0	0	0	0.011	0.511	46.11650
Air Heads	0	0	0	0.906	0.511	52.34146
Almond Joy	0	1	0	0.465	0.767	50.34755

Q1. How many different candy types are in this dataset?

```
colnames(candy)
```

```
[1] "chocolate"      "fruity"          "caramel"         "peanutyalmondy"
[5] "nougat"          "crispedricewafer" "hard"            "bar"
[9] "pluribus"        "sugarpercent"    "pricepercent"    "winpercent"
```

```
ncol(candy[-1:-3])
```

```
[1] 9
```

Q2. How many fruity candy types are in the dataset?

```
sum(candy$fruity)
```

```
[1] 38
```

Q3. What is your favorite candy in the dataset and what is it's winpercent value?

```
candy["Whopper", ]$winpercent
```

```
[1] 49.52411
```

Q4. What is the winpercent value for "Kit Kat"?

```
candy["Kit Kat", ]$winpercent
```

```
[1] 76.7686
```

Q5. What is the winpercent value for "Tootsie Roll Snack Bars"?

```
candy["Tootsie Roll Snack Bars", ]$winpercent
```

```
[1] 49.6535
```

Let's install skimr package and try it on our candy data.

```
library("skimr")
skim(candy)
```

Data summary

Name	candy
Number of rows	85
Number of columns	12
Column type frequency:	
numeric	12
Group variables	
None	

Variable type: numeric

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
chocolate	0	1	0.44	0.50	0.00	0.00	0.00	1.00	1.00	
fruity	0	1	0.45	0.50	0.00	0.00	0.00	1.00	1.00	
caramel	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
peanutyalmondy	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
nougat	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
crispedricewafer	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
hard	0	1	0.18	0.38	0.00	0.00	0.00	0.00	1.00	
bar	0	1	0.25	0.43	0.00	0.00	0.00	0.00	1.00	
pluribus	0	1	0.52	0.50	0.00	0.00	1.00	1.00	1.00	
sugarpercent	0	1	0.48	0.28	0.01	0.22	0.47	0.73	0.99	
pricepercent	0	1	0.47	0.29	0.01	0.26	0.47	0.65	0.98	
winpercent	0	1	50.32	14.71	22.45	39.14	47.83	59.86	84.18	

Q6. Is there any variable/column that looks to be on a different scale to the majority of the other columns in the dataset?

From the `skim()` function, we find that only the winpercent variable appears to be on a different scale due to all of their values being above 1. All other variables have values between 0 and 1 within this function.

Q7. What do you think a zero and one represent for the `candy$chocolate` column?


A zero represent a false statement that the candy of the row *is not* of a chocolate type, while a one represent a true statement that the candy of the row *is* of the chocolate type.

Exploratory analysis with a histogram

Q8. Plot a histogram of winpercent values

```
hist(candy$winpercent)
```

Histogram of candy\$winpercent



Q9. Is the distribution of winpercent values symmetrical?

The distribution is not symmetrical. It appears to be slightly skewed left distribution.

Q10. Is the center of the distribution above or below 50%?

The center of distribution is below 50%.

Q11. On average is chocolate candy higher or lower ranked than fruit candy?

```
#average chocolate candy win percent
choco.win = candy$winpercent[as.logical(candy$chocolate)]
mean(choco.win)
```

```
[1] 60.92153
```

```
#average fruity candy win percent
fruit.win = candy$winpercent[as.logical(candy$fruity)]
mean(fruit.win)
```

```
[1] 44.11974
```

Comparing the two values, chocolate candy is ranked higher than fruit candy.

Q12. Is this difference statistically significant?

```
t.test(choco.win, fruit.win)
```

Welch Two Sample t-test

```
data: choco.win and fruit.win
t = 6.2582, df = 68.882, p-value = 2.871e-08
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
 11.44563 22.15795
sample estimates:
mean of x mean of y
 60.92153  44.11974
```

The difference is statically different because the t-test yielded a p-value of 2.871e-08

Overall candy rankings

Using the dplyr package, we can sort the candies by winpercent with the `arrange()` function.

Q13. What are the five least liked candy types in this set?

```
library(dplyr)
```

Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

`filter`, `lag`

The following objects are masked from 'package:base':

`intersect`, `setdiff`, `setequal`, `union`

```
candy %>% arrange(winpercent) %>% head(5)
```

	chocolate	fruity	caramel	peanut	almondy	nougat
Nik L Nip	0	1	0		0	0
Boston Baked Beans	0	0	0		1	0
Chiclets	0	1	0		0	0
Super Bubble	0	1	0		0	0
Jawbusters	0	1	0		0	0

	crisped	rice	wafer	hard	bar	pluribus	sugar	percent	price	percent
Nik L Nip				0	0	0	1	0.197		0.976
Boston Baked Beans				0	0	0	1	0.313		0.511
Chiclets				0	0	0	1	0.046		0.325
Super Bubble				0	0	0	0	0.162		0.116

Jawbusters		0	1	0	1	0.093	0.511
	winpercent						
Nik L Nip	22.44534						
Boston Baked Beans	23.41782						
Chiclets	24.52499						
Super Bubble	27.30386						
Jawbusters	28.12744						

Q14. What are the top 5 all time favorite candy types out of this set?

```
library(dplyr)

candy %>% arrange(desc(winpercent)) %>% head(5)
```


	chocolate	fruity	caramel	peanutyalmondy	nougat
Reese's Peanut Butter cup	1	0	0	1	0
Reese's Miniatures	1	0	0	1	0
Twix	1	0	1	0	0
Kit Kat	1	0	0	0	0
Snickers	1	0	1	1	1
	crispedricewafer	hard	bar	pluribus	sugarpercent
Reese's Peanut Butter cup	0	0	0	0	0.720
Reese's Miniatures	0	0	0	0	0.034
Twix	1	0	1	0	0.546
Kit Kat	1	0	1	0	0.313
Snickers	0	0	1	0	0.546
	pricepercent	winpercent			
Reese's Peanut Butter cup	0.651	84.18029			
Reese's Miniatures	0.279	81.86626			
Twix	0.906	81.64291			
Kit Kat	0.511	76.76860			
Snickers	0.651	76.67378			

Examine more of the data set in this vain we can make a barplot to visualize the overall rankings. Getting a rough starting plot and then refining and adding useful details

Q15. Make a first barplot of candy ranking based on winpercent values.


```
library(ggplot2)

ggplot(candy) +
  aes(winpercent, rownames(candy)) +
  geom_col()
```



Q16. This is quite ugly, use the `reorder()` function to get the bars sorted by winpercent

```
ggplot(candy) +
  aes(winpercent, reorder(rownames(candy),winpercent)) +
  geom_col()
```




setup a color vector (that signifies candy type) that we can then use for some future plots

```
my_cols=rep("black", nrow(candy))
my_cols[as.logical(candy$chocolate)] = "chocolate"
my_cols[as.logical(candy$bar)] = "brown"
my_cols[as.logical(candy$fruity)] = "pink"
```

try our barplot with these colors.

```
ggplot(candy) +
  aes(winpercent, reorder(rownames(candy),winpercent)) +
  geom_col(fill=my_cols)
```

Q17. What is the worst ranked chocolate candy?

The worst ranked chocolate candy is Sixlets.

Q18. What is the best ranked fruity candy?

The best ranked fruity candy is Starburst.


Taking a look at pricepercent

make a plot of winpercent vs the pricepercent variable

```
library(ggrepel)

# How about a plot of price vs win
ggplot(candy) +
  aes(winpercent, pricepercent, label=rownames(candy)) +
  geom_point(col=my_cols) +
  geom_text_repel(col=my_cols, size=3.3, max.overlaps = 5)
```

Warning: ggrepel: 53 unlabeled data points (too many overlaps). Consider increasing max.overlaps



Q19. Which candy type is the highest ranked in terms of winpercent for the least money - i.e. offers the most bang for your buck?

Chocolate candys are the highest ranked in terms of winpercent for the least money

Q20. What are the top 5 most expensive candy types in the dataset and of these which is the least popular?

```
ord <- order(candy$pricepercent, decreasing = TRUE)
head( candy[ord,c(11,12)], n=5 )
```


	pricepercent	winpercent
Nik L Nip	0.976	22.44534
Nestle Smarties	0.976	37.88719
Ring pop	0.965	35.29076
Hershey's Krackel	0.918	62.28448
Hershey's Milk Chocolate	0.918	56.49050

Top five are Nik L Nips, Nestle Smarties, Ring pop, Ring pop, Hershey's Krackel, and Hershey's Milk Chocolate. The least popular one was Nik L Nips.


Q21. Make a barplot again with `geom_col()` this time using `pricepercent` and then improve this step by step, first ordering the x-axis by value and finally making a so called "dot chat" or "lollipop" chart by swapping `geom_col()` for `geom_point()` + `geom_segment()`.

```
# Make a lollipop chart of pricepercent
ggplot(candy) +
  aes(pricepercent, reorder(rownames(candy), pricepercent)) +
  geom_col(aes(yend = reorder(rownames(candy), pricepercent),
    xend = 0), col="gray40")
```

Warning in geom_col(aes(yend = reorder(rownames(candy), pricepercent), xend = 0), : Ignoring unknown aesthetics: yend and xend



```
# Make a lollipop chart of pricepercent
ggplot(candy) +
  aes(pricepercent, reorder(rownames(candy), pricepercent)) +
  geom_segment(aes(yend = reorder(rownames(candy), pricepercent),
    xend = 0), col="gray40") +
  geom_point()
```




Now that we've explored the dataset a little, we'll see how the variables interact with one another. We'll use correlation and view the results with the `corrplot` package to plot a correlation matrix.

```
library(corrplot)
```

```
corrplot 0.92 loaded
```

```
cij <- cor(candy)
corrplot(cij)
```



Q22. Examining this plot what two variables are anti-correlated (i.e. have minus values)?

Chocolate and Fruity are the most anti-correlated.

```
cij["chocolate","fruity"]
```

```
[1] -0.7417211
```

Q23. Similarly, what two variables are most positively correlated?

Chocolate and winpercent would be the most positively correlated.

```
cij["chocolate","winpercent"]
```

```
[1] 0.6365167
```

```
cij["chocolate","bar"]
```

```
[1] 0.5974211
```

Let's apply PCA using the `prcomp()` function to our candy dataset remembering to set the `scale=TRUE` argument.


```
pca <- prcomp(candy, scale=T)
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	2.0788	1.1378	1.1092	1.07533	0.9518	0.81923	0.81530
Proportion of Variance	0.3601	0.1079	0.1025	0.09636	0.0755	0.05593	0.05539
Cumulative Proportion	0.3601	0.4680	0.5705	0.66688	0.7424	0.79830	0.85369
	PC8	PC9	PC10	PC11	PC12		
Standard deviation	0.74530	0.67824	0.62349	0.43974	0.39760		
Proportion of Variance	0.04629	0.03833	0.03239	0.01611	0.01317		
Cumulative Proportion	0.89998	0.93832	0.97071	0.98683	1.00000		


Now we can plot our main PCA score plot of PC1 vs PC2.

```
plot(pca$x[,1:2])
```



We can change the plotting character and add some color:


```
plot(pca$x[,1:2], col=my_cols, pch=16)
```



we make a new data.frame here that contains our PCA results with all the rest of our candy data. We will then use this for making plots below

```
# Make a new data-frame with our PCA results and candy data
my_data <- cbind(candy, pca$x[,1:3])
```

```
p <- ggplot(my_data) +
  aes(x=PC1, y=PC2,
      size=winpercent/100,
      text=rownames(my_data),
      label=rownames(my_data)) +
  geom_point(col=my_cols)
p
```




Again we can use the `ggrepel` package and the function `ggrepel::geom_text_repel()` to label up the plot with non overlapping candy names like. We will also add a title and subtitle like so:

```
library(ggrepel)


p + geom_text_repel(size=3.3, col=my_cols, max.overlaps = 7) +
  theme(legend.position = "none") +
  labs(title="Halloween Candy PCA Space",
        subtitle="Colored by type: chocolate bar (dark brown), chocolate other (light brown), fruity (red), o",
        caption="Data from 538")
```

Warning: `ggrepel`: 40 unlabeled data points (too many overlaps). Consider increasing `max.overlaps`



Let's finish by taking a quick look at PCA our loadings.

```
par(mar=c(8,4,2,2))
barplot(pca$rotation[,1], las=2, ylab="PC1 Contribution")
```



Q24. What original variables are picked up strongly by PC1 in the positive direction? Do these make sense to you?

Fruity, hard, and pluribus were the variables strongly picked up by Pc1 positively. These make sense because they may not be much variability within these variables.