Test Execution Report

EXEC-02182 — Status: FAIL

1. Execution Summary

Execution ID	EXEC-02182
Status	FAIL
Build Version	5.1.6
Timestamp	2024-02-04 17:07:44
Duration	84 seconds (84283 ms)
Executed By	eng022@synthetic-qa.dev
Test Run	RUN-005 — Regression Cycle 5 — Build 5.1.6
Release	REL-006 — 5.2.7
Environment	ENV-007 — Staging

2. Test Case Reference

Test Case ID	TC-0914
Title	Confirm that the system recovers gracefully after Data Mismatch during user auth...
Test Type	End-to-End
Priority	Critical
Automation	Automated
Requirement	REQ-0045 — Network Behavior — Biometric Verification

3. Environment Details

Environment ID	ENV-007
Name	Staging
Device Type	Mobile
OS Version	Android 13
Network Type	LTE
Location	Bangalore Lab
Configuration	4-core CPU, 8GB RAM, 82GB storage

4. Executed Steps

1	Observe the status indicator for up to 30 seconds.	A success toast message is displayed.	PASS
2	Re-connect the phone and confirm auto-recovery.	Server returns HTTP 200 with a valid JSON payload.	PASS
3	Check server logs for event code 'EVT-4402'.	The operation completes without error.	FAIL

SYNTHETIC DATA — No real Samsung confidential information

5. Failure Details

Failure ID	FAIL-0443
Failure Type	Network Failure
Severity	Critical
Component	Sync Engine
Error Message	SocketException: Connection reset by peer on interface eth0.
Observed	The system exhibited network failure when Bluetooth interference is present.
Expected	The system should complete device pairing within the defined SLA.
Resolution	Resolved

Error Log Excerpt:

```
com.samsung.browser.SearchIndexer.execute(line 682)
```

Linked Defect	BUG-0236 — Network Failure in Sync Engine: SocketException: Connection ...
Defect Status	REOPENED

6. Synthetic Data Notice

This document is entirely synthetic and intended for AI/RAG research only.