Failure Analysis Report

FAIL-0715 — Configuration Error

1. Failure Summary

Failure ID	FAIL-0715
Failure Type	Configuration Error
Severity	Major
Component	Voice Pipeline
Application	APP-001 — SmartHome
Build Version	5.1.3
Timestamp	2023-05-11 22:40:55
Environment	ENV-003 — Hub Lab
OS Version	Tizen 7.0
Network	WiFi-6
Resolution	Resolved

2. Test Case Reference

Test Case ID	TC-1344
Title	Ensure that health metric upload does not exceed the p99 latency (1s) threshold ...
Execution ID	EXEC-03733
Test Run	RUN-009 — Regression Cycle 9 — Build 6.1.8
Requirement	REQ-0441 — Battery — Payment Processing

3. Expected vs Observed Behaviour

Expected Behaviour	The system should complete NFC tap-to-pay within the defined SLA.
Observed Behaviour	The system exhibited configuration error when two concurrent requests are made simultaneously.

4. Error Details

Error Message:

```
ConfigError: missing required key 'API_ENDPOINT' in environment profile 'uat'.
```

Stack Trace / Log Excerpt:

```
com.samsung.browser.SyncEngine.execute(line 559)
```

Log Reference	LOG-35535

5. Executed Steps at Time of Failure

SYNTHETIC DATA — No real Samsung confidential information

1	Verify that the UI displays 'Error: retry'.	A confirmation notification appears on the paired device.
2	Observe the status indicator for up to 12 seconds.	A confirmation notification appears on the paired device.
3	Observe the status indicator for up to 3 seconds.	The UI transitions to the next screen within 3 seconds.
4	Record response time using the built-in performance monitor.	The performance counter logs a value below the SLA threshold.
5	Check server logs for event code 'EVT-3851'.	The device reconnects automatically within 10 seconds.

6. Root Cause Analysis

UI thread blocked by synchronous network call; ANR triggered after 5 seconds.

7. Linked Defect

Defect ID	BUG-0465
Title	Configuration Error in Voice Pipeline: ConfigError: missing required key 'API_EN...
Severity	Major
Priority	Critical
Status	CLOSED
Root Cause	UI thread blocked by synchronous network call; ANR triggered after 5 seconds.
Resolution	Added CRC32 checksum validation step before OTA flash; partial-write detection a...
Assigned To	ENG-037

8. Historical Similar Failures

HIST-0122	FAIL-0123	Configuration Error	4.3.5	2022-03-12	5	Resolved
HIST-0199	FAIL-0200	Configuration Error	6.4.1	2022-06-30	4	Resolved
HIST-0656	FAIL-0657	Configuration Error	3.2.1	2023-03-08	2	Wont Fix

9. Synthetic Data Notice

This document is entirely synthetic and intended for AI/RAG research only.

SYNTHETIC DATA — No real Samsung confidential information