Test Plan

TS-0032 — APP-006 — Integration Suite 32

1. Test Plan Overview

Suite ID	TS-0032
Suite Name	APP-006 — Integration Suite 32
Suite Type	Performance
Priority	Low
Status	Active
Application	APP-006 — XRPlatform
Release	REL-002 — Release 4.2.0
Release Version	4.2.8
Release Date	2023-03-01
Created Date	2022-11-20

2. Scope & Objectives

This test plan covers performance testing for the XRPlatform application. Suite covering Database scenarios for APP-006.

3. Test Strategy

Testing will follow a risk-based approach with priority on Low severity scenarios. Automated test cases will be executed first to detect regressions early, followed by manual exploratory testing for edge cases. Performance and security test cases will run in parallel in dedicated environments.

4. Requirements Under Test

REQ-0215	Functional — Firmware Over-The-Air Update	Performance	High	Draft
REQ-0398	Usability — Configuration Reload	Performance	Low	Draft
REQ-0122	Security — Offline Mode	Reliability	Low	Draft
REQ-0260	Functional — Device Pairing	Compatibility	Low	Approved
REQ-0014	Connectivity — Dark Mode	Error Handling	Medium	Deprecated

5. Test Cases Summary

TC-0073	Verify that NFC tap-to-pay completes successfully ...	Sanity	Manual	Critical
TC-0234	Validate that push notification delivery returns t...	System	Semi-Automated	High
TC-0238	Confirm that Bluetooth reconnection triggers the e...	Compatibility	Manual	Medium
TC-0326	Validate that payment processing returns the corre...	Smoke	Manual	Low
TC-0416	Verify that device pairing completes successfully ...	Compatibility	Automated	Medium

SYNTHETIC DATA — No real Samsung confidential information

TC-0431	Verify end-to-end flow of health metric upload fro...	Reliability	Semi-Automated	High
TC-0493	Verify end-to-end flow of firmware over-the-air up...	Recovery	Manual	Low
TC-0500	Confirm that voice command recognition triggers th...	Reliability	Automated	Low

6. Test Environments

Primary	Mobile Lab — Android 14 — WiFi-6 (ENV-001)
Secondary	Staging — Android 13 — LTE (ENV-007)
Extended	Low Network Env — Android 14 — Low-BW Sim (ENV-009)
Performance	High Load Env — Ubuntu 22.04 — Ethernet (ENV-010)

7. Entry & Exit Criteria

Entry — Build	Smoke suite must pass 100% before full regression begins.
Entry — Env	All required environments must be Available status.
Entry — Defects	No Critical-severity open defects from the previous cycle.
Exit — Pass Rate	Overall pass rate >= 95%.
Exit — Critical	Zero open Critical-severity defects.
Exit — Coverage	All Priority=High test cases executed.

8. Risks

Network instability in low-BW env	Medium	Reserve stable WiFi fallback
Device unavailability	Low	Reserve backup devices 48h ahead
Build quality regression	Medium	Execute smoke before full regression
Flaky automation scripts	Low	Quarantine flaky TCs, re-run 3x

9. Responsible Engineers

ENG-051	Victor Garcia	Test Architect	Security QA
ENG-018	Victor Ueda	Performance Engineer	XR QA
ENG-031	Laura Rossi	QA Engineer	Automation QA

10. Synthetic Data Notice

This document is entirely synthetic and intended for AI/RAG research only.

SYNTHETIC DATA — No real Samsung confidential information