

Submission Detail


258 / 258 test cases passed.

Runtime: 16 ms

Status: Accepted

Submitted: 23 minutes ago

Accepted Solutions Runtime Distribution



Submitted Code: 23 minutes ago

Language: c

Edit Code

```
1 int numDecodings(char* s) {
2
3     if (s[0] == '0') {
4         return 0;
5     }
6     int *F = (int *)malloc(sizeof(int) * strlen(s));
7     int *G = (int *)malloc(sizeof(int) * strlen(s));
8     F[0] = 1;
9     G[0] = 0;
10    for (int i = 1; i < strlen(s); i++) {
11        int can_alone = s[i] != '0';
12        char tmp[3] = {s[i - 1], s[i], '\0'};
13        int num = atoi(tmp);
14        int can_combine = 1 <= num && num <= 26 && tmp[0] != 0;
15        if (!can_alone && !can_combine) {
16            return 0;
17        }
18        if (can_alone)
19            F[i] = F[i - 1] + G[i - 1];
20        else
21            F[i] = 0;
22        if (can_combine) {
23            G[i] = F[i - 1];
24        } else {
25            G[i] = 0;
26        }
27    }
28    int answer = F[strlen(s) - 1] + G[strlen(s) - 1];
29    free(F);
30    free(G);
31    return answer;
32
33 }
34
```

[Back to problem \(/problems/decode-ways/\)](/problems/decode-ways/)

