



Select a definition

highscoresapi v1

# HighScores API <sup>v1</sup> OAS3

<http://localhost:8080/swagger/v1/swagger.json>

## HighScores

GET

/HighScores This endpoint returns semi-structured HighScores



Requires an API Header to determine if your app is authorized

### Parameters

Cancel

Name

Description

x-api-key  
String  
(header)

ExecuteClear

### Responses

#### Curl

```
curl -X 'GET' \  
  'http://localhost:8080/HighScores' \  
  -H 'accept: text/plain' \  
  -H 'x-api-key: asd'
```

#### Request URL

<http://localhost:8080/HighScores>

#### Server response

Code

Details

401

Undocumented

Error: Unauthorized

Response body

Api Key is not valid

Response headers

content-length: 20  
content-type: text/plain; charset=utf-8  
date: Thu,06 Jan 2022 04:02:52 GMT  
server: Kestrel

Responses

Code	Description	Links
200	Success	No links

Media type

text/plain

Controls Accept header.

Example Value

Schema

[  
  {  
    "id": "string",  
    "data": "string",  
    "userId": 0  
  }  
]

POST

/HighScores

This endpoint returns semi-structured HighScores

Requires an API Header to determine if your app is authorized

Parameters

Try it out

Name	Description
------	-------------

Name

Description

x-api-key

String

(header)

x-api-key

Request body

application/json

Example Value

Schema

```
{
  "data": "string",
  "userId": 0
}
```

Responses

Code	Description	Links
201	Success	No links

Media type

text/plain

Controls Accept header.

Example Value

Schema

3fa85f64-5717-4562-b3fc-2c963f66afa6

DELETE

/HighScores/{id}

This endpoint deletes a high score

Requires an API Header to determine if your app is authorized

Parameters

Try it out

Name	Description
------	-------------

id \* required

```
string($uuid)
(path)
```

id

x-api-key

String  
(header)

x-api-key

## Responses

Code	Description	Links
204	Success	No links
404	Not Found	No links

Media type

text/plain

Example Value	Schema
---------------	--------

string

## Users



**GET**

**/Users** This endpoint returns users for the provided application



Requires an API Header to determine if your app is authorized

Parameters

Try it out

Name	Description
x-api-key String (header)	<div>x-api-key</div>

Responses

Code	Description	Links
200	Success	No links

Media type

text/plain

Controls Accept header.

Example Value   Schema

[  
  {  
    "id": 0,  
    "userName": "string"  
  }  
]

POST   /Users   This endpoint creates a user for the provided application

^

Requires an API Header to determine if your app is authorized

Parameters

Try it out

Name	Description
x-api-key String (header)	<div>x-api-key</div>

Request body

application/json

Example Value

Schema

```
{  "userName": "string"}  
```

Responses

Code	Description	Links
201	<div>Success</div> <div>Media type</div> <div>text/plain</div> <div>Controls Accept header.</div> <div>Example Value</div> <div>Schema</div> <div>0</div>	No links

DELETE

/Users/{id}

This endpoint deletes a user

Requires an API Header to determine if your app is authorized

Parameters

Try it out

Name	Description
<div>id * required</div> <div>integer(\$int32)</div> <div>(path)</div>	<div>id</div>

Name	Description
------	-------------

x-api-key  
String  
(header)

x-api-key

## Responses

Code	Description	Links
204	Success	No links
404	Not Found	No links

Media type

text/plain

Example Value Schema

string

## Schemas



## CreateHighScoreAPIRequest

## CreateUserAPIRequest

## HighScore

User

