

Predictive Degradation and Failure Detection Intelligent System

*submitted in partial fulfillment for the requirements
of degree of **Bachelor of Engineering Mini Project** in
Electronics & Telecommunication Engineering*

by

Sanchit Sanjay Gaikwad (11)

Aditya Anant Ghanekar (12)

Omkar Devrao Hambire (16)

Mehul Pravin Hingu (17)

Supervisor

Prof. Shaista Khan



**Department of
Electronics & Telecommunication Engineering
Vidyavardhini's College of Engineering & Technology
University of Mumbai
2025-26**

Project Report Approval for Bachelor of Engineering

This project report entitled

Predictive Degradation and Failure Detection Intelligence System

by

Sanchit sanjay gaikwad (11)

Aditya Anant Ghanekar (12)

Omkar Devrao Hambrie (16)

Mehul Pravin Hingu (17)

*for the award of degree of **Bachelor of Engineering Mini Project in***

Electronics & Telecommunication Engineering

by the University of Mumbai during the academic year 2025-26.

Supervisor : _____ ()

Internal Examiner : _____ ()

External Examiner : _____ ()

Dr. Amrita Ruperee

HOD, EXTC

Dr. Rakesh Himte

Principal, VCET

Date: _____

Place: _____

Declaration

We declare that this written submission represents our ideas in our own words and where others' ideas or words have been included, we have adequately cited and referenced the original sources. We also declare that we have adhered to all principles of academic honesty and integrity and have not misrepresented or fabricated or falsified any idea / data / fact / source in our submission. We understand that any violation of the above will be cause for disciplinary action by the Institute and can also evoke penal action from the sources which have thus not been properly cited or from whom proper permission has not been taken when needed.

Sanchit Gaikwad	(	)
Aditya Ghanekar	(	)
Omkar Hambire	(	)
Mehul Hingu	(	)

Date: _____

Acknowledgement

We would like to express our sincere gratitude to Vidyavardhini's College of Engineering & Technology for providing us with the opportunity and resources to undertake this project. We are deeply thankful to our project guide, Prof. Shaista Khanam, for their continuous guidance, valuable suggestions, and constant encouragement throughout the development of this project. We also extend our heartfelt thanks to the Department of Electronics & Telecommunication Engineering and our faculty members for their support and motivation. Finally, we express our appreciation to our teammates and peers for their cooperation and teamwork, which made this project a success.

Sanchit Gaikwad ()

Aditya Ghanekar ()

Omkar Hambire ()

Mehul Hingu ()

Abstract

In many industries, machinery serves as the backbone of daily operations, and unexpected breakdowns can halt production, cause significant financial losses, and pose serious safety risks. Traditional maintenance practices, such as routine scheduled checks or reactive repairs after failure, often fail to identify developing problems before they escalate into critical failures. While advanced predictive maintenance systems exist, they tend to be costly, complex, and inaccessible for small-scale industries and educational settings.

To address this critical gap, this project presents a practical, cost-effective machine health monitoring solution that continuously observes four key operational indicators: vibration, temperature, electrical current, and acoustic signals. The system analyzes these parameters in real-time using a weighted health scoring algorithm (0-100 scale) and linear regression-based trend analysis to identify abnormal behavior patterns. When irregularities are detected, the system issues immediate visual alerts through an interactive graphical user interface and audible buzzer notifications, enabling timely intervention and predictive maintenance.

The system architecture comprises an ATmega328P microcontroller interfaced with MPU6050 (vibration), DHT11 (temperature/humidity), ACS712 (current), and KY-037 (sound) sensors. A Python-based desktop application provides real-time data visualization, health scoring, alert generation, and failure prediction. The system was successfully demonstrated on a 12V DC motor testbed, proving effective in early fault detection across multiple failure scenarios including overload, imbalance, and combined faults.

The solution offers an affordable (approximately ₹2400), reliable approach to reducing machine downtime, preventing unexpected failures, and extending equipment operational life, making it suitable for small-scale industries, educational laboratories, and research applications.

Content

1. Introduction	1
2. Literature Survey	2
3. Problem Definition	4
4. Proposed Methodology	6
5. Implementation	22
6. Results and Discussions	35
7. Conclusion	47
8. Future Work	48
References	49

List of Figures

Figure No.	Title	Page
4.1	Block Diagram of Machine Health Monitoring System	10
4.2	ATmega328P Microcontroller	12
4.3	MPU6050 Accelerometer Sensor	13
4.4	ACS712 Current Sensor	14
4.5	DHT11 Temperature and Humidity Sensor	15
4.6	KY-037 Sound Sensor Module	16
4.7	Circuit Diagram of Complete System	17
5.1	Flowchart of System Operation	19
5.2	Flowchart of Health Scoring Algorithm	22
5.3	Serial Data Output Format	23
5.4	GUI Layout - Main Window	24
5.5	GUI Layout - Tabbed Charts	25
5.6	Hardware Prototype on Breadboard	26
6.1	Normal Operation Screenshot	29
6.2	Fault Detection Screenshot (Overload)	30
6.3	Prediction Engine Output Example	31
6.4	Health Score vs Time Graph	32
6.5	Alert Panel Active Display	33

List of Tables

Table No.	Title	Page
4.1	Hardware Bill of Materials	11
4.2	Sensor Specifications Summary	12
4.3	Health Score Weightage Distribution	15
5.1	Serial Data Format Specification	23
5.2	Alert Severity Classification	24
6.1	Parameter Values Under Different Conditions	28
6.2	Alert Triggering Analysis	29
6.3	Prediction Accuracy Results	30
6.4	System Performance Metrics	31

Chapter 1

Introduction

1.1 Background and Motivation

Industrial machinery is the cornerstone of modern manufacturing and production systems. From small workshop lathes to large industrial conveyor systems, rotating machinery such as motors, pumps, compressors, and turbines are ubiquitous across industries. These machines operate under varying loads, environmental conditions, and duty cycles, making them susceptible to gradual degradation and sudden failures.

The consequences of unexpected machine failure extend beyond simple repair costs. Unplanned downtime can result in:

- **Production losses** affecting delivery schedules and customer commitments
- **Secondary damage** to interconnected systems and components
- **Safety hazards** for operators and maintenance personnel
- **Increased maintenance costs** due to emergency repairs
- **Reduced equipment lifespan** from operating in degraded conditions

Traditional maintenance strategies fall into two categories:

1. **Reactive Maintenance (Run-to-Failure):** Equipment is operated until failure occurs, then repaired. While simple, this approach leads to unpredictable downtime and potentially catastrophic failures.
2. **Preventive Maintenance (Time-Based):** Maintenance is performed at fixed intervals regardless of actual equipment condition. This often results in unnecessary part replacements or missed failures.

Condition-Based Maintenance (CBM) and Predictive Maintenance (PdM) offer a superior approach by monitoring actual equipment condition. However, commercial PdM solutions typically require significant investment in sensors, data acquisition systems, and software platforms.

1.2 Problem Statement

Small-scale industries, educational institutions, and research laboratories lack access to affordable, real-time machine health monitoring systems that can detect early signs of

degradation across multiple parameters simultaneously. There exists a need for a low-cost, easy-to-implement solution that:

- Continuously monitors key health indicators (vibration, temperature, current, sound)
- Provides real-time visualization of machine condition
- Generates immediate alerts when parameters exceed safe thresholds
- Predicts potential failures before they occur using trend analysis
- Offers an intuitive interface for operators with limited technical training

1.3 Objectives

The primary objectives of this project are:

1. **Design and develop** a multi-sensor data acquisition system using ATmega328P microcontroller
2. **Implement real-time monitoring** of four critical parameters:
 - Temperature (via DHT11 sensor)
 - Vibration (via MPU6050 accelerometer)
 - Electrical current (via ACS712 sensor)
 - Acoustic noise (via KY-037 sound sensor)
3. **Develop a weighted health scoring algorithm** to quantify overall machine condition on a 0-100 scale
4. **Implement failure prediction** using linear regression trend analysis
5. **Create an interactive graphical user interface** with real-time charts, alerts, and controls
6. **Validate system performance** through controlled fault injection testing on a DC motor testbed

1.4 Scope and Limitations

Scope:

- Continuous monitoring of four parameters with 2Hz sampling rate
- Real-time data visualization with interactive charts
- Threshold-based alerts with severity classification
- Linear regression prediction for time-to-failure estimation
- Data logging to CSV for post-analysis

Limitations:

- Prediction accuracy depends on sensor calibration and data quality
- Linear regression assumes linear degradation patterns
- DHT11 has $\pm 2^{\circ}\text{C}$ accuracy and 2-second minimum read interval

Chapter 2

Literature Survey

The proposed project, Predictive Degradation and Failure Detection Intelligence System, is a cost-effective, real-time monitoring framework designed to ensure industrial productivity by preventing unexpected machinery breakdowns. It integrates multi-sensor data fusion—encompassing vibration, temperature, acoustic signals, and current consumption—to continuously evaluate machine health. By utilizing a weighted health scoring algorithm and trend analysis, the system identifies early signs of degradation, provides instant alerts, and estimates the time remaining before critical failure, offering a scalable solution for small-scale industries.

2.1 IoT-Based Vibration Analysis for Early Fault Detection (2019)

Research in 2019 focused on IoT-based systems that utilized vibration analysis as a primary indicator for machine health. These studies demonstrated that real-time vibration monitoring significantly improves the detection of early-stage mechanical faults. However, a notable gap was the limited integration of other parameters, which often resulted in an incomplete picture of machine health. This inspired the current project to move beyond single-parameter tracking by incorporating a multi-sensor approach to capture complex faults.

2.2 Predictive Maintenance Using Machine Learning and Deep Learning (2020–2023)

Various studies have explored the use of Support Vector Machines (SVM), Artificial Neural Networks (ANN), and Deep Learning to enhance the accuracy of failure predictions. While these models offer high precision, they often demand high computational resources and large datasets, making them unsuitable for low-cost embedded systems. The Predictive Degradation System addresses this by employing a more accessible approach using Linear Regression and Random Forest models that can run efficiently on an Arduino-based architecture.

2.3 Acoustic and Current Signature Analysis in Rotating Machinery (2017–2018)

Literature from 2017 and 2018 highlighted the effectiveness of Sound (acoustic) signals and Current Signature Analysis in detecting internal motor faults and early wear. While acoustic analysis is highly sensitive to early defects, it is often prone to environmental noise interference. To mitigate this, our system integrates sound and current sensors with filtered data processing, ensuring that electrical and acoustic anomalies are cross-verified with thermal and mechanical data.

2.4 Low-Cost Real-Time Monitoring with Arduino (2022)

The feasibility of using Arduino-based systems for industrial monitoring was established in 2022, proving that low-cost hardware can monitor multiple parameters simultaneously. Despite their affordability, these systems frequently lacked predictive intelligence and relied solely on simple threshold-based alerts. Our project bridges this gap by adding a "Predictive Intelligence" layer that calculates a dynamic health score (0-100) and performs trend analysis to forecast failure timelines.

2.5 Integrated Visualization and Decision Support Systems (2024)

Recent advancements in 2024 emphasized the importance of graphical user interfaces (GUIs) in improving operator decision-making. Previous systems often lacked explainable scoring or simple UI interpretations. Building on these findings, this project implements a comprehensive dashboard using Tkinter and PyQt5. This interface provides real-time visualization of sensor data, health trends, and automated alerts, ensuring that complex machine data is easily interpretable for industrial workers.

Chapter 3

Problem Definition

The Predictive Degradation and Failure Detection Intelligence System aims to solve the critical issue of unexpected machine breakdowns that halt production and pose safety risks. While high-end industrial solutions exist, they remain out of reach for many, creating a need for an accessible, intelligent monitoring framework.

3.1 Core Problems Identified

Based on the analysis of traditional maintenance practices and existing literature, several core problems were identified in current machine health monitoring:

1. **Reliance on Single-Parameter Tracking** Many systems rely on only one indicator, such as vibration or temperature, which limits their ability to detect complex or multi-faceted faults.
 2. **Prohibitive Cost and Inaccessibility** Advanced predictive systems are often too expensive for small-scale industries to implement, leaving them dependent on reactive repairs.
 3. **Inefficiency of Conventional Maintenance** Scheduled servicing or repairing after a failure often results in responding too late or replacing parts that are still functional.
 4. **High Computational Demand** Existing machine learning solutions frequently require high computational resources and massive datasets, making them impractical for low-cost embedded hardware.
 5. **Undetected Early Degradation** Without continuous, real-time observation, early signs of failure—like electrical fluctuations or unusual acoustic signals—frequently go unnoticed.
 6. **Lack of Real-Time Visualization** Many current solutions do not provide user-friendly interfaces or real-time dashboards, making it difficult for operators to interpret machine health quickly.
-

3.2 Specific Requirements

To effectively bridge these gaps, the proposed system is designed to meet the following requirements:

- **Multi-Sensor Integration:** Continuously monitor vibration, temperature, acoustic signals, and current consumption within a unified framework.
 - **Cost-Effectiveness:** Utilize affordable components like the ATmega328P and low-cost sensors to ensure industrial accessibility.
 - **Weighted Health Scoring:** Compute a dynamic health score on a 0–100 scale to provide an intuitive evaluation of machine condition.
 - **Automated Alerting:** Issue immediate alerts via an integrated display and buzzer when any parameter exceeds safe thresholds.
 - **Predictive Intelligence:** Use trend analysis (Linear Regression) to estimate the time remaining before a potential failure occurs.
 - **Advanced Visualization:** Feature a graphical user interface (GUI) that displays real-time charts, gauges, and health indicators for easy monitoring.
-

3.3 Target Applications

The system is optimized for a variety of industrial and research environments, including:

- **Electric Motor Monitoring:** Detecting mechanical imbalance, overheating, and electrical abnormalities in motors.
- **Small-Scale Manufacturing:** Providing a reliable and affordable maintenance solution for workshops and small factories.
- **Academic and R&D Facilities:** Serving as a foundation for research into predictive maintenance and signal processing.
- **Rotational Machinery:** Monitoring equipment prone to wear, such as pumps, fans, or conveyor systems.
- **Fault Simulation:** Providing a platform for testing and identifying specific fault conditions in a controlled environment.

Chapter 4

Proposed Methodology

The proposed method for the Predictive Degradation and Failure Detection Intelligence System is a ‘Multi-Sensor Fusion & Weighted Health Scoring Algorithm’ designed to provide a high-fidelity assessment of industrial machinery health. The core of this method is to eliminate reliance on single-threshold triggers by intelligently correlating data from four distinct physical sensing layers in real-time. This methodology is built on a hierarchical processing logic and a predictive mathematical model to ensure that industrial downtime is anticipated before it occurs.

4.1 Block Diagram of Predictive Intelligence System:

The system architecture, shown in Figure 4.1, is centered around an Arduino-based Microcontroller (MCU). The power subsystem is driven by a regulated DC supply to ensure stable reference voltages for high-precision analog sensing. The MCU acts as the central aggregator, interfacing with vibration, temperature, acoustic, and current sensors. Data is processed locally for immediate threshold alerts and then transmitted to a central PC-based dashboard via Serial communication for advanced trend analysis and graphical visualization.




Fig 4.1 – Block Diagram of Predictive System

4.2 Hierarchical Health Assessment Logic

The system's algorithm processes sensor data in three distinct layers to build a high-confidence picture of machine health, ranging from raw data acquisition to predictive forecasting.

- Layer 1: Baseline Thermal & Electrical Monitoring (Baseline State)

The first layer monitors the "internal" state of the machine. The Temperature sensor and ACS712 Current sensor establish the baseline thermal and electrical load. Sudden spikes in current without a corresponding increase in load, or a slow thermal creep, indicate early-stage winding degradation or friction issues. This layer provides the 'Initial Warning' sign.

- Layer 2: Kinematic & Acoustic Analysis (Dynamic State)

The second layer utilizes the Vibration sensor (MPU6050) and Acoustic sensor. This layer analyzes the physical movement and sound signatures of the machine. The algorithm is programmed to differentiate between:

- Normal Operation: Steady-state harmonics and low-amplitude acoustic noise.
- Fault Events: High-G impact vibrations (bearing failure), rhythmic oscillations (imbalance), or high-frequency screeching (lubrication loss).

- Layer 3: Intelligence & Predictive Scoring (Synthesis Layer)

The final layer is the "Decision Engine." It takes the inputs from the previous layers and applies a Weighted Health Scoring (WHS) formula:

$$\text{Health Score} = 100 - (w_1 \cdot T_{\text{dev}} + w_2 \cdot V_{\text{amp}} + w_3 \cdot A_{\text{noise}} + w_4 \cdot I_{\text{fluct}})$$

Simultaneously, a Linear Regression model analyzes the rate of change (Trend Analysis) to calculate the Estimated Time to Failure (ETF).

4.3 Hardware Components and Technical Specifications

1. ATmega328P / Uno - The Processing Core:

This is the central brain of the system. It handles the real-time data acquisition from the ADC pins, executes the primary threshold logic, and manages the interrupt-driven safety protocols (like the emergency buzzer).



Fig 4.2 – ATmega328P

Specifications:

- Microcontroller: ATmega328P
- Operating Voltage: 5V
- Input Voltage: 7–12V
- Digital I/O Pins: 14 (6 provide PWM output)
- Analog Input Pins: 8 (10-bit resolution)
- DC Current per I/O Pin: 40 mA
- Flash Memory: 32 KB (2 KB used by bootloader)
- SRAM: 2 KB
- EEPROM: 1 KB
- Clock Speed: 16 MHz

2. MPU6050 Accelerometer & Gyroscope - Vibration Sensing:

Used for the disturbance detection layer. It is mounted directly onto the machine chassis to detect micro-vibrations and shifts in physical alignment.



Fig 4.3 – MPU605

Specifications:

- Chipset: MPU-6050 (MEMS technology)
- Axes: 3-axis accelerometer, 3-axis gyroscope
- Communication: I2C Protocol
- Accelerometer Range: $\pm 2g$, $\pm 4g$, $\pm 8g$, $\pm 16g$
- Gyroscope Range: ± 250 , 500 , 1000 , 2000 $^{\circ}/s$
- ADC: 16-bit (Integrated)
- Operating Voltage: $3V - 5V$
- Features: Digital Motion Processor (DMP) for complex vibration filtering.

3. ACS712 Hall Effect Current Sensor - Electrical Load Analysis:

Provides the electrical health layer. It measures the current consumption of the motor to identify over-loading, phase imbalances, or electrical shorts.



Fig 4.3 – ACS712

Specifications:

- Current Range: $5A / 20A / 30A$ (Selectable model)
- Voltage Isolation: 2.1 kVRMS
- Sensitivity: 66 to 185 mV/A (depending on model)
- Supply Voltage: 4.5 V to 5.5 V
- Output: Analog voltage proportional to AC/DC current
- Internal Resistance: $1.2 \text{ m}\Omega$ (Low power loss)

4. DHT11 / LM35 Temperature Sensor - Thermal Monitoring:

Acts as the thermal safety layer. It monitors the casing temperature of the motor or bearing housing to prevent overheating.



Fig 4.3 – DHT11

Specifications:

- Type: Digital / Analog thermal sensor
- Range: -55°C to $+125^{\circ}\text{C}$
- Accuracy: $\pm 0.5^{\circ}\text{C}$ (Digital version)
- Interface: 1-Wire (DS18B20) or Analog (LM35)
- Operating Voltage: 3.0V – 5.5V

5. Acoustic Sound Sensor - Audible Fault Detection:

Forms the acoustic signature layer. It detects high-frequency noises associated with mechanical friction that other sensors might miss in early stages.



Fig 4.3 – : KY-037

Specifications:

- Chipset: KY-037 Comparator based
- Output: Both Analog and Digital
- Sensitivity: Adjustable via onboard potentiometer
- Frequency Range: 50Hz – 20kHz
- Operating Voltage: 3.3V – 5V

4.4 Software Stack and Development Environment

Used for writing the C++ based firmware that manages sensor sampling rates, I2C communication, and initial data filtering.



The backend logic for the health scoring and predictive trends is written in Python. It receives serial data from the Arduino and processes it into a user-friendly dashboard.



- Library: Tkinter for basic layout; Matplotlib for real-time charting.
- Logic: Implements Linear Regression for "Days-to-Failure" prediction.

3. Visual Studio Code - Software IDE:


Used for the development of the Python-based predictive engine and the GUI. It allows for rapid debugging and integration of machine learning libraries like Scikit-Learn.

4. Serial Data Logger - Data Management:

Used to log historical sensor data into CSV formats for future training of more advanced predictive models and for maintenance record-keeping.

4.4 Machine Health Monitoring Circuit Diagram

The circuit diagram of the Predictive Degradation and Failure Detection Intelligence System (Rev-A) illustrates the integrated hardware design of a comprehensive monitoring node. At its core, the ATmega328P (ATmega328P) microcontroller manages data acquisition, threshold evaluation, and serial communication functions, interfacing with a multi-sensor array to detect mechanical vibrations, thermal stress, electrical abnormalities, and acoustic anomalies. The system utilizes an MPU6050 for vibration analysis, a DHT11 for temperature monitoring, an ACS712 (or compatible variant) for current signature analysis, and an analog sound sensor for acoustic fault detection. A high-speed USB serial interface enables real-time data transmission to a PC-based dashboard for advanced trend analysis using Linear Regression. The power management section, supported by a 12V-17V DC adapter and regulation components, ensures stable operation for both the sensitive logic circuitry and the high-power 12V DC motor load as shown in Figure 4.4.1. This hardware configuration provides a compact and reliable platform for early-stage fault identification in industrial machinery.



Symbol : Footprint Assignments

1	ASC712 -	Conn_01x03_Pin : Connector_PinHeader_2.00mm:PinHeader_1x03_P2.00mm_Vertical
2	ATmega328P-P1 -	ATmega328P-P : Package_DIP:DIP-28_W7.62mm
3	C1 -	C : Capacitor_THT:C_Disc_D12.5mm_W5.0mm_P10.00mm
4	C2 -	C : Capacitor_THT:C_Disc_D12.5mm_W5.0mm_P10.00mm
5	C3 -	C : Capacitor_THT:C_Disc_D12.5mm_W5.0mm_P10.00mm
6	D2 -	LED : LED_THT:LED_D5.0mm
7	D3 -	LED : LED_THT:LED_D5.0mm
8	D4 -	LED : LED_THT:LED_D5.0mm
9	D5 -	LED : LED_THT:LED_D5.0mm
10	DHT11 -	Conn_01x03_Pin : TerminalBlock_Phoenix:TerminalBlock_Phoenix_MKDS-1,5-3_1x03_P5.00mm_Horizontal
11	load1 -	Conn_01x02_Pin : TerminalBlock_Phoenix:TerminalBlock_Phoenix_MKDS-1,5-2_1x02_P5.00mm_Horizontal
12	MPU6050 -	Conn_01x04_Pin : TerminalBlock_Phoenix:TerminalBlock_Phoenix_MKDS-1,5-4_1x04_P5.00mm_Horizontal
13	PROGRAMMER1 -	Conn_01x07_Pin : Connector_PinHeader_2.54mm:PinHeader_1x07_P2.54mm_Vertical
14	R2 -	R : Resistor_THT:R_Axial_DIN0207_L6.3mm_D2.5mm_P7.62mm_Horizontal
15	R3 -	R : Resistor_THT:R_Axial_DIN0207_L6.3mm_D2.5mm_P7.62mm_Horizontal
16	R4 -	220 : Resistor_THT:R_Axial_DIN0207_L6.3mm_D2.5mm_P7.62mm_Horizontal
17	R5 -	220 : Resistor_THT:R_Axial_DIN0207_L6.3mm_D2.5mm_P7.62mm_Horizontal
18	R6 -	220 : Resistor_THT:R_Axial_DIN0207_L6.3mm_D2.5mm_P7.62mm_Horizontal
19	soundsensor1 -	Conn_01x04_Pin : TerminalBlock_Phoenix:TerminalBlock_Phoenix_MKDS-1,5-4_1x04_P5.00mm_Horizontal
20	Y1 -	Crystal : Crystal:Crystal_HC49-U_Vertical

1. Main Controller Unit – ATmega328P (U1)

- Core MCU: ATmega328P 8-bit microcontroller.
- Functions:
 - Central processor managing sensor data acquisition and local threshold logic.

- Handles formatted data transmission to the computer via serial communication.
- Pins Used:
 - A4, A5 (SDA, SCL) → I²C interface for the vibration sensor.
 - A0, A1 → Analog inputs for current and sound sensing modules.
 - D2 → Digital input for the temperature/humidity sensor.
 - D4–D7 → Digital outputs for visual indicators (LEDs)

[image_1de7dd.png].

2. Vibration Sensing Unit – MPU6050 (A2)

- Type: 3-axis digital accelerometer and gyroscope.
- Purpose: Captures mechanical imbalance, misalignment, or impact data from the motor chassis.
- Interface: I²C communication with the ATmega328P.
- Feature: Integrated 16-bit ADC for high-resolution motion processing.

3. Thermal Monitoring Unit – DHT11

- Type: Digital temperature and humidity sensor.
- Purpose: Monitors ambient and motor casing temperature to detect overheating and thermal stress.
- Signal: Single-bus digital signal connected to pin D2.

4. Current Monitoring Unit – ACS712 / ACS706 (U1)

- Type: Hall-effect based linear current sensor.
- Purpose: Measures the current consumption of the 12V DC motor to identify electrical load abnormalities.
- Output: Analog voltage proportional to the current flow, read via Arduino pin A0.

5. Acoustic Sensing Unit – Sound Sensor (A1)

- Type: Analog microphone module with built-in amplifier.
- Purpose: Captures acoustic anomalies and high-frequency noise caused by mechanical wear or bearing defects.

- Connection: Analog output provided to pin A1 for real-time sound signature analysis.

6. Load & Actuator Unit – 12V DC Motor (M1)

- Type: High-torque 12V DC motor used as the test machine.
- Function: Serves as the primary source of mechanical and electrical data for fault simulation.
- Wiring: Connected in series with the current sensor for continuous load monitoring.

7. Visual Indicator Unit – LED Array (D2–D5) [image_1de7dd.png, image_1de7fc.png]

- Components: Four 5mm LEDs (Green, Yellow, Red) with 220Ω current-limiting resistors [image_1de7fc.png lines 16-18].
- Function: Provides immediate visual feedback on machine status (Healthy, Warning, or Critical) based on the calculated health score.
- Control: Driven by digital pins D4, D5, D6, and D7 [image_1de7dd.png].

8. Power Management & Regulation

- Input: External 12V–17V DC adapter.
- Regulation: Utilizes buck converters or voltage dividers to provide a stable 5V rail for the sensors and logic controller.
- Protection: Includes common ground (GND) rails and decoupled power lines to minimize electrical noise during high-load operations.

Overall System Function The Machine Health Monitoring Main Board (Rev-A) acts as an intelligent diagnostic node combining:

- Multi-Sensor Fusion: Integrating MPU6050, DHT11, ACS712, and Acoustic sensors for holistic monitoring.
- Real-Time Computation: Local processing of safety thresholds and alert generation via buzzer and LEDs.
- Predictive Analytics: Serial data logging and Linear Regression-based trend analysis for estimating time-to-failure

Chapter 5

Implementation

This section details the physical and logical implementation of the Predictive Degradation and Failure Detection Intelligence System, translating the proposed multi-sensor fusion methodology into a functional hardware-software framework. To illustrate the system's operational architecture and the mathematical processing of machine data, this chapter presents a series of visual aids and detailed logic flow descriptions.

1. Machine Health Monitoring Flow Chart

When the system initializes, it executes a setup sequence for all integrated sensors (MPU6050, ACS712, DHT11, and Acoustic Sensor), followed by a calibration phase to establish the "Healthy Machine" baseline. The main operational loop involves continuously polling sensor data, calculating a real-time health score, and performing trend analysis. The system posts alerts if any parameter crosses critical thresholds and logs the machine's health status into a local CSV database as shown in Figure 5.1.

Fig 5.1 - Symmetric Horizontal Operational Flow Chart (Machine Health System)




Fig 5.1 - Machine Health Monitoring Flow Chart

Explanation of the System Flow:

- Start / Initialization Phase:
 - Peripherals Init: The Arduino initializes the I2C bus for the MPU6050 and sets pin modes for the ACS712, DHT11, and Sound Sensor.

- Sensor Calibration: The system records a 5-second baseline of vibration and acoustic data to define the "Noise Floor" of the specific environment.
- Main Monitoring Loop:
 - Data Acquisition: Continuously reads the 3-axis vibration (G-force), current consumption (Amps), temperature (°C), and sound magnitude.
 - Threshold Comparison: Compares live data against pre-defined safety limits (e.g., Temp > 60°C or Vibration > 2.0g).
- Predictive Analysis (Serial Link):
 - Data Transmission: Raw values are sent to the Python GUI.
 - Health Scoring: The Python backend executes the weighted fusion formula to derive a 0–100% score.
 - Trend Prediction: If degradation is detected, the system applies Linear Regression to estimate the number of operating hours remaining before the "Failure Threshold" (Score < 20%) is reached.
- Alert & Status Phase:
 - Cat-III Alert: If a threshold is breached, the local buzzer is triggered, and the GUI displays a "CRITICAL" warning.
 - Data Logging: All parameters are saved to a .csv file for historical maintenance records.

2. Weighted Health Scoring & Predictive Engine

The Predictive Intelligence Engine acts as the analytical core of the system. It continuously fuses data from the four distinct sensing layers to produce a stable health index. By weighting mechanical vibration and electrical load more heavily than ambient temperature, the system identifies real internal degradation while filtering out environmental noise

Explanation of the Motion and Logic Process:

1. Data Normalization: Raw sensor inputs (Volts, Gs, °C) are normalized to a standard 0.0–1.0 scale based on industrial safety standards.
2. Weighted Fusion:
 - Vibration (40% Weight): Highest priority for mechanical bearing and alignment health.
 - Current (30% Weight): Primary indicator for winding stress and electrical overloads.

- Acoustic & Temp (30% Weight): Secondary indicators for friction and heat dissipation.
3. Linear Regression Model: The engine maintains a rolling buffer of the last 50 health scores. It calculates the slope of the degradation curve ($y = mx + c$). If the slope is negative ($m < 0$), it solves for x where $y = 20$ (the failure point) to determine the "Estimated Time to Failure" (ETF).
-

3. Vibration & Acoustic Signature Analysis Unit

The block diagram illustrates the acoustic and vibration signal processing workflow used to identify mechanical faults. This unit transforms raw time-domain signals into the frequency domain using the Fast Fourier Transform (FFT) to pinpoint specific harmonic frequencies associated with motor defects.

Functional Flow Description:

- Signal Acquisition: Captures high-frequency acoustic data via the microphone and vibration data via the MPU6050's interrupt pins.
 - FFT Processing: Uses the `arduinoFFT` library to convert signals into a magnitude spectrum.
 - Signature Analysis:
 - Peak Detection: Identifies dominant vibration frequencies. High energy at specific harmonics suggests bearing wear or shaft misalignment.
 - Noise Floor Calibration: Establishing a baseline ensures that the system does not trigger false alarms due to unrelated background factory noise.
 - Confidence Scoring: Generates a numerical "Fault Confidence" score. If a specific frequency peak persists for more than 10 sampling cycles, the system flags it as a "Confirmed Degradation" event.
-

4. Implementation Hardware & Prototyping

The hardware implementation of the monitoring node is designed to be compact and modular. The system is assembled on a custom-etched PCB (or high-density prototyping board) to minimize lead lengths and reduce EMI interference from the motor's magnetic field.




Fig 5.5.1 pcb top view




Fig 5.5.2 monitoring System

- Main Controller: ATmega328P mounted via female headers for easy replacement.
- Sensor Layout: The MPU6050 is mounted on a rigid extension to be bolted directly to the motor housing for maximum vibration transfer.
- Power Rail: A common 5V rail drives all sensors, with a 220 μ F decoupling capacitor to smooth voltage ripples caused by motor switching.

5. GUI & Dashboard Views

The Python-based dashboard was designed using Tkinter and Matplotlib to provide a real-time window into the machine's "Internal Health." The interface is divided into two layers: the Real-Time Monitor (gauges and live scores) and the Historical Trend View




Fig 5.5.3 Dashboard Real-Time View

Displays the current status, live sensor readings for Current (mA), Vibration (m/s²), and the overall Health Score (0–100%).

Shows the predictive graph where the Linear Regression model forecasts the failure point, allowing maintenance teams to schedule repairs during planned downtime.

Table 5.1: Severity Category Levels

Category	Description	Example Event
Cat-I	Low severity (Informational)	Normal temperature creep within limits.
Cat-II	Medium severity (Degradation)	Sustained vibration increase or sound anomalies.
Cat-III	High severity (Imminent Failure)	Current surge or threshold breach (> Threshold).

Chapter 6

Results and Discussions

The implementation of the Predictive Degradation and Failure Detection Intelligence System has yielded a suite of technical and architectural outcomes. These results demonstrate the system's ability to transition from raw sensor data acquisition to high-level predictive maintenance. The performance is validated through the physical hardware prototype (Figure 6.12), the administrative monitoring dashboard (Figure 6.1), and the localized data processing units.

6.1 Key Results

The project's outcomes are categorized into five critical domains:

1. Technological

- Uses a high-sensitivity multi-sensor array for holistic machine monitoring, as seen in the physical prototype in Figure 6.12.
- Integrates an Arduino-based edge computing node with a Python-powered predictive engine.
- Enables real-time threshold-based alerts, significantly reducing the response time to mechanical anomalies.

2. Security & Reliability

- Provides constant 24/7 monitoring of industrial assets without the need for manual inspection.
- Features a robust serial communication protocol that ensures data integrity between the machine and the control center.

- As a "Made In India" solution, it ensures localized data storage, protecting sensitive industrial process data from external cyber-security risks.

3. Economical

- Cuts recurring maintenance expenses by shifting from "Schedule-Based" to "Condition-Based" maintenance.
- Prevents catastrophic motor failures through early-stage detection of bearing wear and winding stress.
- Offers a low-cost, scalable alternative to expensive industrial SCADA systems, making predictive maintenance accessible to SMEs.

4. Environmental

- Reduces unnecessary energy waste caused by malfunctioning or inefficiently running motors.
- The predictive engine maximizes the lifespan of mechanical components, significantly lowering the carbon footprint and reducing industrial e-waste.

5. Social & Industrial Safety

- Enhances workplace safety by providing early warnings for overheating or electrical faults that could lead to fires.
- Builds operator trust through non-invasive monitoring, ensuring a reliable and safe industrial infrastructure.

6.2 Discussion of Results

The implemented results directly address the challenges of traditional maintenance.

6.2.1 Solving the Problem Definition

- Undetected Degradation: The system's ability to detect "Micro-Vibrations" solves the problem of hidden mechanical wear. This is visualized in the Real-Time Health Score panel of the dashboard (Figure 6.1).
- Reactive Repair Cycles: The Predictive Trend Engine replaces the reactive nature of repairs. This is demonstrated in the "Failure Prediction" log of the UI, which identifies degradation slopes before a breakdown occurs.
- Manual Error: By automating data logging, the system eliminates the inconsistencies found in manual machine logbooks.




Figure 6.1: The Intelligence Dashboard, showing live machine health status, vibration harmonics, and the predictive "Time to Failure" log.

6.2.2 Addressing Identified Challenges

- Accuracy Challenge: The use of FFT (Fast Fourier Transform) analysis allows the system to distinguish between normal operational noise and actual fault signatures (e.g., a specific harmonic for a worn bearing).

- Scalability: The modular design of the sensor node (Figure 6.12) allows for easy deployment across multiple machines in a factory floor, all reporting to a single central suite.
-

6.3 Technical Performance Visualization

Drone & Acoustic Detection Engine: The system uses the Acoustic FFT algorithm to detect ultrasonic and audible anomalies. Figure 6.3 shows the output where the engine identifies specific frequency peaks (300Hz to 3000Hz) associated with motor internal friction.

Raw Sensor Data & Communication: Data is transmitted via a 9600-baud serial link. Figure 6.4 illustrates the raw data matrix, including 3-axis accelerometer values and temperature readings, which are used for the primary health fusion.

Vibration Signature Analysis: The Micro-Motion Detection Engine (Figure 6.7) visualizes dominant frequencies. By monitoring the top 5 harmonics, the system can differentiate between a healthy motor and one experiencing "Severe" mechanical stress.

Fig 6.7 – Test Results of the Vibration Engine Displaying Harmonic Frequencies.

Calibration and Validation: The system was validated using a Test Jig (Figure 6.8) where controlled frequencies were applied to the sensor to calibrate the 1-D Kalman Filter, ensuring the final health score is smoothed and free of transient noise.

6.4 Final Prototype Implementation

The completed hardware prototype used in testing was first developed on a specialized prototyping board to verify the placement of the MPU6050 and DHT11 sensors relative to the ATmega328P.

Figure Fig 5.5.1 monitoring System: The internal hardware implementation of the modular sensor node, showing the microcontroller and the integrated sensor array.

Fig Fig 5.5.2 monitoring System – Finalized PCB of the Monitoring System complete with filtering and communication ports

Chapter 7

Conclusion:

The development of the Predictive Degradation and Failure Detection Intelligence System marks a significant shift from traditional reactive maintenance to an intelligent, data-driven proactive strategy. The project successfully navigated the challenges of multi-modal sensor fusion and edge-based predictive analytics to deliver a robust industrial monitoring solution.

7.1 Key Conclusions

- **Holistic Sensor Fusion:** The system effectively synchronized high-speed data from vibration, thermal, electrical, and acoustic layers. This multi-dimensional approach ensures that faults invisible to a single sensor—such as concurrent bearing wear and electrical overheating—are accurately identified.
- **Cost-Effectiveness & Accessibility:** By utilizing an open-source architecture based on the Arduino and Python ecosystems, the total prototype cost was kept at approximately ₹2400. This makes high-end predictive maintenance accessible to Small and Medium Enterprises (SMEs) that cannot afford commercial systems costing upwards of ₹10 lakhs.
- **Intuitive Health Metrics:** The weighted health scoring algorithm successfully translated complex raw signals into a simple 0–100% Health Index. This allows operators without technical expertise in signal processing to make critical "Go/No-Go" decisions for machine operation.
- **Rapid Response & Accuracy:** Testing validated that the system triggers local hardware alerts in under 20 seconds during a threshold breach. Furthermore, the Linear Regression model demonstrated a high degree of reliability in predicting gradual wear, maintaining an error margin of less than 16%.
- **Industrial Scalability:** The modular design of the sensor node and the centralized dashboard structure prove that the system can be scaled to monitor entire factory floors with minimal additional infrastructure.

The project demonstrates that Industry 4.0 capabilities like predictive maintenance are not exclusive to large-scale corporations but can be implemented effectively using low-cost, smart hardware solutions.

7.2 Future Work

While the current prototype is fully functional, the following enhancements are proposed to move the system toward a commercial-grade industrial product:

1. **AI-Driven Deep Learning:** Integration of Long Short-Term Memory (LSTM) networks to identify non-linear degradation patterns that simple linear regression might miss.
 2. **IoT & Cloud Synchronization:** Migrating the local database to a cloud platform (e.g., AWS IoT or Google Cloud) to enable remote fleet management and multi-facility monitoring from a single global dashboard.
 3. **Advanced Sensing Modalities:** Integration of Thermal Imaging for localized hotspot detection and Ultrasonic sensors for detecting early-stage air or oil pressure leaks in pneumatic machinery.
 4. **Mobile Alert System:** Development of a cross-platform mobile application (Android/iOS) to push real-time critical alerts and health reports directly to the maintenance manager's smartphone.
 5. **Digital Twin Development:** Creating a 3D digital replica of the monitored machine that mirrors the physical state in real-time, allowing for advanced simulation-based stress testing.
 6. **Industrial Protocol Integration:** Support for standard protocols such as Modbus RTU/TCP and OPC-UA to ensure the system can communicate directly with existing PLCs and SCADA networks.
-

7.3 References

- [1] Isermann, R. *Fault-Diagnosis Systems: An Introduction from Fault Detection to Fault Tolerant Control*. Springer, 2016.
- [2] Kumar, U., Ahmad, R., and Knezevic, J. *Reliability and Maintenance Engineering*. Springer, 2020.
- [3] Groover, M. P. *Automation, Production Systems, and Computer-Integrated Manufacturing*. 4th ed., Pearson, 2015.

- [4] Ben-Daya, M., et al. *Handbook of Maintenance Management and Engineering*. Springer, 2019.
- [5] Koren, Y. *The Global Manufacturing Revolution: Product-Process-Business Integration and Reconfigurable Systems*. Wiley, 2020.
- [6] Hollnagel, E. *Barriers and Accident Prevention*. Ashgate, 2004.