

## Join GitHub today

[Dismiss](#)

GitHub is home to over 50 million developers working together to host and review code, manage projects, and build software together.

[Sign up](#)Branch: **master** ▼[Find file](#)[Copy path](#)[pysheet](#) / [docs](#) / [notes](#) / **python-sqlalchemy.rst****Gavinkaa** Reflect=True is depreciated, now use reflect()

c51ac7c on 4 Oct 2019

[4 contributors](#)[Raw](#)[Blame](#)[History](#)

1612 lines (1224 sloc) 39.5 KB

# SQLAlchemy

## Table of Contents

- [Set a database URL](#)
- [Sqlalchemy Support DBAPI - PEP249](#)
- [Transaction and Connect Object](#)
- [Metadata - Generating Database Schema](#)
- [Inspect - Get Database Information](#)
- [Reflection - Loading Table from Existing Database](#)
- [Get Table from MetaData](#)
- [Create all Tables Store in "MetaData"](#)
- [Create Specific Table](#)
- [Create table with same columns](#)
- [Drop a Table](#)
- [Some Table Object Operation](#)
- [SQL Expression Language](#)

- [insert\(\)](#) - Create an "INSERT" Statement
- [select\(\)](#) - Create a "SELECT" Statement
- [join\(\)](#) - Joined Two Tables via "JOIN" Statement
- [Delete Rows from Table](#)
- [Check Table Existing](#)
- [Create multiple tables at once](#)
- [Create tables with dynamic columns \(Table\)](#)
- [Object Relational add data](#)
- [Object Relational update data](#)
- [Object Relational delete row](#)
- [Object Relational relationship](#)
- [Object Relational self association](#)
- [Object Relational basic query](#)
- [mapper: Map Table to class](#)
- [Get table dynamically](#)
- [Object Relational join two tables](#)
- [join on relationship and group\\_by count](#)
- [Create tables with dynamic columns \(ORM\)](#)
- [Close database connection](#)
- [Cannot use the object after close the session](#)

## Set a database URL

---

```
from sqlalchemy.engine.url import URL

postgres_db = {'drivername': 'postgres',
               'username': 'postgres',
               'password': 'postgres',
               'host': '192.168.99.100',
               'port': 5432}
print(URL(**postgres_db))

sqlite_db = {'drivername': 'sqlite', 'database': 'db.sqlite'}
print(URL(**sqlite_db))
```

output:

```
$ python sqlalchemy_url.py
postgres://postgres:postgres@192.168.99.100:5432
sqlite:///db.sqlite
```

## Sqlalchemy Support DBAPI - PEP249

---

```
from sqlalchemy import create_engine

db_uri = "sqlite:///db.sqlite"
engine = create_engine(db_uri)

# DBAPI - PEP249
# create table
engine.execute('CREATE TABLE "EX1" ('
                'id INTEGER NOT NULL, '
                'name VARCHAR, '
                'PRIMARY KEY (id));')

# insert a row
engine.execute('INSERT INTO "EX1" '
                '(id, name) '
                'VALUES (1,"raw1")')

# select *
result = engine.execute('SELECT * FROM '
                          '"EX1"')

for _r in result:
    print(_r)

# delete *
engine.execute('DELETE from "EX1" where id=1;')
result = engine.execute('SELECT * FROM "EX1"')
print(result.fetchall())
```

## Transaction and Connect Object

---

```
from sqlalchemy import create_engine

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

# Create connection
conn = engine.connect()
# Begin transaction
trans = conn.begin()
conn.execute('INSERT INTO "EX1" (name) '
              'VALUES ("Hello")')
trans.commit()
# Close connection
conn.close()
```

## Metadata - Generating Database Schema

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer, String

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

# Create a metadata instance
metadata = MetaData(engine)
# Declare a table
table = Table('Example', metadata,
              Column('id', Integer, primary_key=True),
              Column('name', String))
# Create all tables
metadata.create_all()
for _t in metadata.tables:
    print("Table: ", _t)
```

## Inspect - Get Database Information

---

```
from sqlalchemy import create_engine
from sqlalchemy import inspect

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

inspector = inspect(engine)

# Get table information
print(inspector.get_table_names())

# Get column information
print(inspector.get_columns('EX1'))
```

## Reflection - Loading Table from Existing Database

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

# Create a MetaData instance
metadata = MetaData()
print(metadata.tables)
```

```
# reflect db schema to MetaData
metadata.reflect(bind=engine)
print(metadata.tables)
```

## Get Table from MetaData

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

# Create MetaData instance
metadata = MetaData(engine).reflect()
print(metadata.tables)

# Get Table
ex_table = metadata.tables['Example']
print(ex_table)
```

## Create all Tables Store in "MetaData"

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer, String

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)
meta = MetaData(engine)

# Register t1, t2 to metadata
t1 = Table('EX1', meta,
           Column('id', Integer, primary_key=True),
           Column('name', String))

t2 = Table('EX2', meta,
           Column('id', Integer, primary_key=True),
           Column('val', Integer))

# Create all tables in meta
meta.create_all()
```

## Create Specific Table

---

```

from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer, String

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

meta = MetaData(engine)
t1 = Table('Table_1', meta,
          Column('id', Integer, primary_key=True),
          Column('name', String))
t2 = Table('Table_2', meta,
          Column('id', Integer, primary_key=True),
          Column('val', Integer))
t1.create()

```

## Create table with same columns

---

```

from sqlalchemy import (
    create_engine,
    inspect,
    Column,
    String,
    Integer)

from sqlalchemy.ext.declarative import declarative_base

db_url = "sqlite://"
engine = create_engine(db_url)

Base = declarative_base()

class TemplateTable(object):
    id = Column(Integer, primary_key=True)
    name = Column(String)
    age = Column(Integer)

class DowntownAPeople(TemplateTable, Base):
    __tablename__ = "downtown_a_people"

class DowntownBPeople(TemplateTable, Base):
    __tablename__ = "downtown_b_people"

Base.metadata.create_all(bind=engine)

# check table exists
ins = inspect(engine)
for _t in ins.get_table_names():
    print(_t)

```

## Drop a Table

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import inspect
from sqlalchemy import Table
from sqlalchemy import Column, Integer, String
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}
engine = create_engine(URL(**db_url))
m = MetaData()
table = Table('Test', m,
              Column('id', Integer, primary_key=True),
              Column('key', String, nullable=True),
              Column('val', String))

table.create(engine)
inspector = inspect(engine)
print('Test' in inspector.get_table_names())

table.drop(engine)
inspector = inspect(engine)
print('Test' in inspector.get_table_names())
```

output:

```
$ python sqlalchemy_drop.py
$ True
$ False
```

## Some Table Object Operation

---

```
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer, String

meta = MetaData()
t = Table('ex_table', meta,
          Column('id', Integer, primary_key=True),
          Column('key', String),
          Column('val', Integer))
```

```
# Get Table Name
print(t.name)

# Get Columns
print(t.columns.keys())

# Get Column
c = t.c.key
print(c.name)
# Or
c = t.columns.key
print(c.name)

# Get Table from Column
print(c.table)
```

## SQL Expression Language

---

```
# Think Column as "ColumnElement"
# Implement via overwrite special function
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer, String
from sqlalchemy import or_

meta = MetaData()
table = Table('example', meta,
              Column('id', Integer, primary_key=True),
              Column('l_name', String),
              Column('f_name', String))

# sql expression binary object
print(repr(table.c.l_name == 'ed'))
# exhibit sql expression
print(str(table.c.l_name == 'ed'))

print(repr(table.c.f_name != 'ed'))

# comparison operator
print(repr(table.c.id > 3))

# or expression
print((table.c.id > 5) | (table.c.id < 2))
# Equal to
print(or_(table.c.id > 5, table.c.id < 2))

# compare to None produce IS NULL
print(table.c.l_name == None)
# Equal to
print(table.c.l_name.is_(None))

# + means "addition"
```



```
print(table.c.id + 5)
# or means "string concatenation"
print(table.c.l_name + "some name")

# in expression
print(table.c.l_name.in_(['a', 'b']))
```

## insert() - Create an "INSERT" Statement

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer
from sqlalchemy import String

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

# create table
meta = MetaData(engine)
table = Table('user', meta,
              Column('id', Integer, primary_key=True),
              Column('l_name', String),
              Column('f_name', String))
meta.create_all()

# insert data via insert() construct
ins = table.insert().values(
    l_name='Hello',
    f_name='World')
conn = engine.connect()
conn.execute(ins)

# insert multiple data
conn.execute(table.insert(), [
    {'l_name': 'Hi', 'f_name': 'bob'},
    {'l_name': 'yo', 'f_name': 'alice'}])
```

## select() - Create a "SELECT" Statement

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import select
from sqlalchemy import or_

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)
```

```
conn = engine.connect()

meta = MetaData(engine).reflect()
table = meta.tables['user']

# select * from 'user'
select_st = select([table]).where(
    table.c.l_name == 'Hello')
res = conn.execute(select_st)
for _row in res:
    print(_row)

# or equal to
select_st = table.select().where(
    table.c.l_name == 'Hello')
res = conn.execute(select_st)
for _row in res:
    print(_row)

# combine with "OR"
select_st = select([
    table.c.l_name,
    table.c.f_name]).where(or_(
    table.c.l_name == 'Hello',
    table.c.l_name == 'Hi'))
res = conn.execute(select_st)
for _row in res:
    print(_row)

# combine with "ORDER_BY"
select_st = select([table]).where(or_(
    table.c.l_name == 'Hello',
    table.c.l_name == 'Hi')).order_by(table.c.f_name)
res = conn.execute(select_st)
for _row in res:
    print(_row)
```

## join() - Joined Two Tables via "JOIN" Statement

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import Column
from sqlalchemy import Integer
from sqlalchemy import String
from sqlalchemy import select

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)

meta = MetaData(engine).reflect()
email_t = Table('email_addr', meta,
```

```

    Column('id', Integer, primary_key=True),
    Column('email', String),
    Column('name', String))
meta.create_all()

# get user table
user_t = meta.tables['user']

# insert
conn = engine.connect()
conn.execute(email_t.insert(), [
    {'email': 'ker@test', 'name': 'Hi'},
    {'email': 'yo@test', 'name': 'Hello'}])
# join statement
join_obj = user_t.join(email_t,
                        email_t.c.name == user_t.c.l_name)
# using select_from
sel_st = select(
    [user_t.c.l_name, email_t.c.email]).select_from(join_obj)
res = conn.execute(sel_st)
for _row in res:
    print(_row)

```

## Delete Rows from Table

---

```

from sqlalchemy import create_engine
from sqlalchemy import MetaData

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)
conn = engine.connect()

meta = MetaData(engine).reflect()
user_t = meta.tables['user']

# select * from user_t
sel_st = user_t.select()
res = conn.execute(sel_st)
for _row in res:
    print(_row)

# delete l_name == 'Hello'
del_st = user_t.delete().where(
    user_t.c.l_name == 'Hello')
print('----- delete -----')
res = conn.execute(del_st)

# check rows has been delete
sel_st = user_t.select()
res = conn.execute(sel_st)
for _row in res:
    print(_row)

```

## Check Table Existing

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Column
from sqlalchemy import Integer, String
from sqlalchemy import inspect
from sqlalchemy.ext.declarative import declarative_base

Modal = declarative_base()
class Example(Modal):
    __tablename__ = "ex_t"
    id = Column(Integer, primary_key=True)
    name = Column(String(20))

db_uri = 'sqlite:///db.sqlite'
engine = create_engine(db_uri)
Modal.metadata.create_all(engine)

# check register table exist to Modal
for _t in Modal.metadata.tables:
    print(_t)

# check all table in database
meta = MetaData(engine).reflect()
for _t in meta.tables:
    print(_t)

# check table names exists via inspect
ins = inspect(engine)
for _t in ins.get_table_names():
    print(_t)
```

## Create multiple tables at once

---

```
from sqlalchemy import create_engine
from sqlalchemy import MetaData
from sqlalchemy import Table
from sqlalchemy import inspect
from sqlalchemy import Column, String, Integer
from sqlalchemy.engine.url import URL

db = {'drivername': 'postgres',
      'username': 'postgres',
      'password': 'postgres',
      'host': '192.168.99.100',
      'port': 5432}
```

```

url = URL(**db)
engine = create_engine(url)

metadata = MetaData()
metadata.reflect(bind=engine)

def create_table(name, metadata):
    tables = metadata.tables.keys()
    if name not in tables:
        table = Table(name, metadata,
                       Column('id', Integer, primary_key=True),
                       Column('key', String),
                       Column('val', Integer))
        table.create(engine)

tables = ['table1', 'table2', 'table3']
for _t in tables: create_table(_t, metadata)

inspector = inspect(engine)
print(inspector.get_table_names())

```

output:

```

$ python sqlalchemy_create.py
[u'table1', u'table2', u'table3']

```

## Create tables with dynamic columns (Table)

---

```

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String
from sqlalchemy import Table
from sqlalchemy import MetaData
from sqlalchemy import inspect
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}

engine = create_engine(URL(**db_url))

def create_table(name, *cols):
    meta = MetaData()
    meta.reflect(bind=engine)
    if name in meta.tables: return

    table = Table(name, meta, *cols)
    table.create(engine)

```

```

create_table('Table1',
             Column('id', Integer, primary_key=True),
             Column('name', String))
create_table('Table2',
             Column('id', Integer, primary_key=True),
             Column('key', String),
             Column('val', String))

inspector = inspect(engine)
for _t in inspector.get_table_names():
    print(_t)

```

output:

```

$ python sqlalchemy_dynamic.py
Table1
Table2

```

## Object Relational add data

---

```

from datetime import datetime

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String, DateTime
from sqlalchemy.orm import sessionmaker
from sqlalchemy.exc import SQLAlchemyError
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}
engine = create_engine(URL(**db_url))

Base = declarative_base()

class TestTable(Base):
    __tablename__ = 'Test Table'
    id = Column(Integer, primary_key=True)
    key = Column(String, nullable=False)
    val = Column(String)
    date = Column(DateTime, default=datetime.utcnow)

# create tables
Base.metadata.create_all(bind=engine)

# create session

```

```

Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

data = {'a': 5566, 'b': 9527, 'c': 183}
try:
    for _key, _val in data.items():
        row = TestTable(key=_key, val=_val)
        session.add(row)
    session.commit()
except SQLAlchemyError as e:
    print(e)
finally:
    session.close()

```

## Object Relational update data

---

```

from datetime import datetime

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String, DateTime
from sqlalchemy.orm import sessionmaker
from sqlalchemy.exc import SQLAlchemyError
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}
engine = create_engine(URL(**db_url))
Base = declarative_base()

class TestTable(Base):
    __tablename__ = 'Test Table'
    id = Column(Integer, primary_key=True)
    key = Column(String, nullable=False)
    val = Column(String)
    date = Column(DateTime, default=datetime.utcnow)

# create tables
Base.metadata.create_all(bind=engine)

# create session
Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

try:
    # add row to database
    row = TestTable(key="hello", val="world")

```

```

session.add(row)
session.commit()

# update row to database
row = session.query(TestTable).filter(
    TestTable.key == 'hello').first()
print('original:', row.key, row.val)
row.key = "Hello"
row.val = "World"
session.commit()

# check update correct
row = session.query(TestTable).filter(
    TestTable.key == 'Hello').first()
print('update:', row.key, row.val)
except SQLAlchemyError as e:
    print(e)
finally:
    session.close()

```

output:

```

$ python sqlalchemy_update.py
original: hello world
update: Hello World

```

## Object Relational delete row

```

from datetime import datetime

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String, DateTime
from sqlalchemy.orm import sessionmaker
from sqlalchemy.exc import SQLAlchemyError
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}
engine = create_engine(URL(**db_url))
Base = declarative_base()

class TestTable(Base):
    __tablename__ = 'Test Table'
    id = Column(Integer, primary_key=True)
    key = Column(String, nullable=False)

```



```

val = Column(String)
date = Column(DateTime, default=datetime.utcnow)

# create tables
Base.metadata.create_all(bind=engine)

# create session
Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

row = TestTable(key='hello', val='world')
session.add(row)
query = session.query(TestTable).filter(
    TestTable.key=='hello')
print(query.first())
query.delete()
query = session.query(TestTable).filter(
    TestTable.key=='hello')
print(query.all())

```

output:

```

$ python sqlalchemy_delete.py
<__main__.TestTable object at 0x104eb8f50>
[]

```

## Object Relational relationship

```

from sqlalchemy import Column, String, Integer, ForeignKey
from sqlalchemy.orm import relationship
from sqlalchemy.ext.declarative import declarative_base

Base = declarative_base()

class User(Base):
    __tablename__ = 'user'
    id = Column(Integer, primary_key=True)
    name = Column(String)
    addresses = relationship("Address", backref="user")

class Address(Base):
    __tablename__ = 'address'
    id = Column(Integer, primary_key=True)
    email = Column(String)
    user_id = Column(Integer, ForeignKey('user.id'))

u1 = User()
a1 = Address()
print(u1.addresses)

```

```
print(a1.user)

u1.addresses.append(a1)
print(u1.addresses)
print(a1.user)
```

output:

```
$ python sqlalchemy_relationship.py
[]
None
[<__main__.Address object at 0x10c4edb50>]
<__main__.User object at 0x10c4ed810>
```

## Object Relational self association

```
import json

from sqlalchemy import (
    Column,
    Integer,
    String,
    ForeignKey,
    Table)

from sqlalchemy.orm import (
    sessionmaker,
    relationship)

from sqlalchemy.ext.declarative import declarative_base

base = declarative_base()

association = Table("Association", base.metadata,
    Column('left', Integer, ForeignKey('node.id'), primary_key=True),
    Column('right', Integer, ForeignKey('node.id'), primary_key=True))

class Node(base):
    __tablename__ = 'node'
    id = Column(Integer, primary_key=True)
    label = Column(String)
    friends = relationship('Node',
        secondary=association,
        primaryjoin=id==association.c.left,
        secondaryjoin=id==association.c.right,
        backref='left')

    def to_json(self):
        return dict(id=self.id,
            friends=[_.label for _ in self.friends])
```

```

nodes = [Node(label='node_{}'.format(_)) for _ in range(0, 3)]
nodes[0].friends.extend([nodes[1], nodes[2]])
nodes[1].friends.append(nodes[2])

print('----> right')
print(json.dumps([_.to_json() for _ in nodes], indent=2))

print('----> left')
print(json.dumps([_n.to_json() for _n in nodes[1].left], indent=2))

```

output:

```

----> right
[
  {
    "friends": [
      "node_1",
      "node_2"
    ],
    "id": null
  },
  {
    "friends": [
      "node_2"
    ],
    "id": null
  },
  {
    "friends": [],
    "id": null
  }
]
----> left
[
  {
    "friends": [
      "node_1",
      "node_2"
    ],
    "id": null
  }
]

```

## Object Relational basic query

```

from datetime import datetime

from sqlalchemy import create_engine
from sqlalchemy import Column, String, Integer, DateTime
from sqlalchemy import or_

```

```
from sqlalchemy import desc
from sqlalchemy.orm import sessionmaker
from sqlalchemy.exc import SQLAlchemyError
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.engine.url import URL

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}

Base = declarative_base()

class User(Base):
    __tablename__ = 'User'
    id = Column(Integer, primary_key=True)
    name = Column(String, nullable=False)
    fullname = Column(String, nullable=False)
    birth = Column(DateTime)

# create tables
engine = create_engine(URL(**db_url))
Base.metadata.create_all(bind=engine)

users = [
    User(name='ed',
          fullname='Ed Jones',
          birth=datetime(1989, 7, 1)),
    User(name='wendy',
          fullname='Wendy Williams',
          birth=datetime(1983, 4, 1)),
    User(name='mary',
          fullname='Mary Contrary',
          birth=datetime(1990, 1, 30)),
    User(name='fred',
          fullname='Fred Flinstone',
          birth=datetime(1977, 3, 12)),
    User(name='justin',
          fullname="Justin Bieber")]

# create session
Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

# add_all
session.add_all(users)
session.commit()

print("----> order_by(id):")
query = session.query(User).order_by(User.id)
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)
```

```
print("\n----> order_by(desc(id)):")
query = session.query(User).order_by(desc(User.id))
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> order_by(date):")
query = session.query(User).order_by(User.birth)
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> EQUAL:")
query = session.query(User).filter(User.id == 2)
_row = query.first()
print(_row.name, _row.fullname, _row.birth)

print("\n----> NOT EQUAL:")
query = session.query(User).filter(User.id != 2)
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> IN:")
query = session.query(User).filter(User.name.in_(['ed', 'wendy']))
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> NOT IN:")
query = session.query(User).filter(~User.name.in_(['ed', 'wendy']))
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> AND:")
query = session.query(User).filter(
    User.name=='ed', User.fullname=='Ed Jones')
_row = query.first()
print(_row.name, _row.fullname, _row.birth)

print("\n----> OR:")
query = session.query(User).filter(
    or_(User.name=='ed', User.name=='wendy'))
for _row in query.all():
    print(_row.name, _row.fullname, _row.birth)

print("\n----> NULL:")
query = session.query(User).filter(User.birth == None)
for _row in query.all():
    print(_row.name, _row.fullname)

print("\n----> NOT NULL:")
query = session.query(User).filter(User.birth != None)
for _row in query.all():
    print(_row.name, _row.fullname)

print("\n----> LIKE")
query = session.query(User).filter(User.name.like('%ed%'))
```

```
for _row in query.all():  
    print(_row.name, _row.fullname)
```

output:

```
----> order_by(id):  
ed Ed Jones 1989-07-01 00:00:00  
wendy Wendy Williams 1983-04-01 00:00:00  
mary Mary Contrary 1990-01-30 00:00:00  
fred Fred Flinstone 1977-03-12 00:00:00  
justin Justin Bieber None  
  
----> order_by(desc(id)):  
justin Justin Bieber None  
fred Fred Flinstone 1977-03-12 00:00:00  
mary Mary Contrary 1990-01-30 00:00:00  
wendy Wendy Williams 1983-04-01 00:00:00  
ed Ed Jones 1989-07-01 00:00:00  
  
----> order_by(date):  
fred Fred Flinstone 1977-03-12 00:00:00  
wendy Wendy Williams 1983-04-01 00:00:00  
ed Ed Jones 1989-07-01 00:00:00  
mary Mary Contrary 1990-01-30 00:00:00  
justin Justin Bieber None  
  
----> EQUAL:  
wendy Wendy Williams 1983-04-01 00:00:00  
  
----> NOT EQUAL:  
ed Ed Jones 1989-07-01 00:00:00  
mary Mary Contrary 1990-01-30 00:00:00  
fred Fred Flinstone 1977-03-12 00:00:00  
justin Justin Bieber None  
  
----> IN:  
ed Ed Jones 1989-07-01 00:00:00  
wendy Wendy Williams 1983-04-01 00:00:00  
  
----> NOT IN:  
mary Mary Contrary 1990-01-30 00:00:00  
fred Fred Flinstone 1977-03-12 00:00:00  
justin Justin Bieber None  
  
----> AND:  
ed Ed Jones 1989-07-01 00:00:00  
  
----> OR:  
ed Ed Jones 1989-07-01 00:00:00  
wendy Wendy Williams 1983-04-01 00:00:00  
  
----> NULL:  
justin Justin Bieber
```

```
----> NOT NULL:
ed Ed Jones
wendy Wendy Williams
mary Mary Contrary
fred Fred Flinstone
```

```
----> LIKE
ed Ed Jones
fred Fred Flinstone
```

## mapper: Map Table to class

---

```
from sqlalchemy import (
    create_engine,
    Table,
    MetaData,
    Column,
    Integer,
    String,
    ForeignKey)

from sqlalchemy.orm import (
    mapper,
    relationship,
    sessionmaker)

# classical mapping: map "table" to "class"
db_url = 'sqlite://'
engine = create_engine(db_url)

meta = MetaData(bind=engine)

user = Table('User', meta,
             Column('id', Integer, primary_key=True),
             Column('name', String),
             Column('fullname', String),
             Column('password', String))

addr = Table('Address', meta,
             Column('id', Integer, primary_key=True),
             Column('email', String),
             Column('user_id', Integer, ForeignKey('User.id')))

# map table to class
class User(object):
    def __init__(self, name, fullname, password):
        self.name = name
        self.fullname = fullname
        self.password = password

class Address(object):
```

```
def __init__(self, email):
    self.email = email

mapper(User, user, properties={
    'addresses': relationship(Address, backref='user')})
mapper(Address, addr)

# create table
meta.create_all()

# create session
Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

u = User(name='Hello', fullname='HelloWorld', password='ker')
a = Address(email='hello@hello.com')
u.addresses.append(a)
try:
    session.add(u)
    session.commit()

    # query result
    u = session.query(User).filter(User.name == 'Hello').first()
    print(u.name, u.fullname, u.password)

finally:
    session.close()
```

output:

```
$ python map_table_class.py
Hello HelloWorld ker
```

## Get table dynamically

---

```
from sqlalchemy import (
    create_engine,
    MetaData,
    Table,
    inspect,
    Column,
    String,
    Integer)

from sqlalchemy.orm import (
    mapper,
    scoped_session,
    sessionmaker)
```



```

db_url = "sqlite://"
engine = create_engine(db_url)
metadata = MetaData(engine)

class TableTemp(object):
    def __init__(self, name):
        self.name = name

def get_table(name):
    if name in metadata.tables:
        table = metadata.tables[name]
    else:
        table = Table(name, metadata,
                      Column('id', Integer, primary_key=True),
                      Column('name', String))
        table.create(engine)

    cls = type(name.title(), (TableTemp,), {})
    mapper(cls, table)
    return cls

# get table first times
t = get_table('Hello')

# get table secone times
t = get_table('Hello')

Session = scoped_session(sessionmaker(bind=engine))
try:
    Session.add(t(name='foo'))
    Session.add(t(name='bar'))
    for _ in Session.query(t).all():
        print(_.name)
except Exception as e:
    Session.rollback()
finally:
    Session.close()

```

output:

```

$ python get_table.py
foo
bar

```

## Object Relational join two tables

```

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String, ForeignKey
from sqlalchemy.orm import relationship
from sqlalchemy.engine.url import URL

```

```
from sqlalchemy.orm import sessionmaker
from sqlalchemy.ext.declarative import declarative_base

Base = declarative_base()

class User(Base):
    __tablename__ = 'user'
    id = Column(Integer, primary_key=True)
    name = Column(String)
    addresses = relationship("Address", backref="user")

class Address(Base):
    __tablename__ = 'address'
    id = Column(Integer, primary_key=True)
    email = Column(String)
    user_id = Column(Integer, ForeignKey('user.id'))

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}

# create engine
engine = create_engine(URL(**db_url))

# create tables
Base.metadata.create_all(bind=engine)

# create session
Session = sessionmaker()
Session.configure(bind=engine)
session = Session()

user = User(name='user1')
mail1 = Address(email='user1@foo.com')
mail2 = Address(email='user1@bar.com')
user.addresses.extend([mail1, mail2])

session.add(user)
session.add_all([mail1, mail2])
session.commit()

query = session.query(Address, User).join(User)
for _a, _u in query.all():
    print(_u.name, _a.email)
```

output:

```
$ python sqlalchemy_join.py
user1 user1@foo.com
user1 user1@bar.com
```

## join on relationship and group\_by count

```
from sqlalchemy import (
    create_engine,
    Column,
    String,
    Integer,
    ForeignKey,
    func)

from sqlalchemy.orm import (
    relationship,
    sessionmaker,
    scoped_session)

from sqlalchemy.ext.declarative import declarative_base

db_url = 'sqlite://'
engine = create_engine(db_url)

Base = declarative_base()

class Parent(Base):
    __tablename__ = 'parent'
    id          = Column(Integer, primary_key=True)
    name        = Column(String)
    children    = relationship('Child', back_populates='parent')

class Child(Base):
    __tablename__ = 'child'
    id          = Column(Integer, primary_key=True)
    name        = Column(String)
    parent_id   = Column(Integer, ForeignKey('parent.id'))
    parent      = relationship('Parent', back_populates='children')

Base.metadata.create_all(bind=engine)
Session = scoped_session(sessionmaker(bind=engine))

p1 = Parent(name="Alice")
p2 = Parent(name="Bob")

c1 = Child(name="foo")
c2 = Child(name="bar")
c3 = Child(name="ker")
c4 = Child(name="cat")

p1.children.extend([c1, c2, c3])
p2.children.append(c4)

try:
    Session.add(p1)
    Session.add(p2)
    Session.commit()
```

```

# count number of children
q = Session.query(Parent, func.count(Child.id))\
    .join(Child)\
    .group_by(Parent.id)

# print result
for _p, _c in q.all():
    print('parent: {}, num_child: {}'.format(_p.name, _c))
finally:
    Session.remove()

```

output:

```

$ python join_group_by.py
parent: Alice, num_child: 3
parent: Bob, num_child: 1

```

## Create tables with dynamic columns (ORM)

---

```

from sqlalchemy import create_engine
from sqlalchemy import Column, Integer, String
from sqlalchemy import inspect
from sqlalchemy.engine.url import URL
from sqlalchemy.ext.declarative import declarative_base

db_url = {'drivername': 'postgres',
          'username': 'postgres',
          'password': 'postgres',
          'host': '192.168.99.100',
          'port': 5432}

engine = create_engine(URL(**db_url))
Base = declarative_base()

def create_table(name, cols):
    Base.metadata.reflect(engine)
    if name in Base.metadata.tables: return

    table = type(name, (Base,), cols)
    table.__table__.create(bind=engine)

create_table('Table1', {
    '__tablename__': 'Table1',
    'id': Column(Integer, primary_key=True),
    'name': Column(String)})

create_table('Table2', {
    '__tablename__': 'Table2',
    'id': Column(Integer, primary_key=True),

```

```
'key': Column(String),
'val': Column(String)})

inspector = inspect(engine)
for _t in inspector.get_table_names():
    print(_t)
```

output:

```
$ python sqlalchemy_dynamic_orm.py
Table1
Table2
```

## Close database connection

---

```
from sqlalchemy import (
    create_engine,
    event,
    Column,
    Integer)

from sqlalchemy.orm import sessionmaker
from sqlalchemy.ext.declarative import declarative_base

engine = create_engine('sqlite://')
base = declarative_base()

@event.listens_for(engine, 'engine_disposed')
def receive_engine_disposed(engine):
    print("engine dispose")

class Table(base):
    __tablename__ = 'example table'
    id = Column(Integer, primary_key=True)

base.metadata.create_all(bind=engine)
session = sessionmaker(bind=engine)()

try:
    try:
        row = Table()
        session.add(row)
    except Exception as e:
        session.rollback()
        raise
    finally:
        session.close()
finally:
    engine.dispose()
```

output:

```
$ python db_dispose.py
engine dispose
```

## Warning

Be careful. Close *session* does not mean close database connection. SQLAlchemy *session* generally represents the *transactions*, not connections.

## Cannot use the object after close the session

---

```
from __future__ import print_function

from sqlalchemy import (
    create_engine,
    Column,
    String,
    Integer)

from sqlalchemy.orm import sessionmaker
from sqlalchemy.ext.declarative import declarative_base

url = 'sqlite:///'
engine = create_engine(url)
base = declarative_base()

class Table(base):
    __tablename__ = 'table'
    id = Column(Integer, primary_key=True)
    key = Column(String)
    val = Column(String)

base.metadata.create_all(bind=engine)
session = sessionmaker(bind=engine)()

try:
    t = Table(key="key", val="val")
    try:
        print(t.key, t.val)
        session.add(t)
        session.commit()
    except Exception as e:
        print(e)
        session.rollback()
    finally:
        session.close()

    print(t.key, t.val) # exception raise from here
```

```
except Exception as e:  
    print("Cannot use the object after close the session")  
finally:  
    engine.dispose()
```

output:

```
$ python sql.py  
key val  
Cannot use the object after close the session
```