



CONTINUOUS
INKJET PRINTER

RE 2000

CONTINUOUS INKJET PRINTER

RE 2000

Independent research Flexible application
Industrial-grade main board Stable and reliable
Double stirring system Anti precipitation
Smooth gemstone nozzle Better inkjet effect
Gear pump Stable pressure

Print Head Duct

3MTR

Nozzle Specification

70um

Printing Height

2mm to 20mm

Print Distance

3mm to 30mm

Machine Material

Stainless Steel 304

Display Screen

10.1 inch colour display,
Industrial touch screen

Machine Dimension

337X316X561(L*B*H*)

Working Environment

Temperature 40 - 105° F (10 - 40°C)
Humidity 10% - 90%, Non Condensing

Operating System

Embedded Linux security operating system

Motherboard Memory

256M

Machine Dimension

337X316X561(L*B*H*)

Printing Lines

1 to 4 Lines

Printing Speed

528 m/min

Counter

Up to 24 Counters

Protection Level

Ip65

INK Colour

Black, Red, Blue, Green, Sky Blue, Brown,

Related Certificate

CE, EAC, BIS

INK Type

High adhesion, high temperature resistance,
Special for glass, permeability, food grade,
Oil resistance

Electric Requirement

220 - 240 ACV, 5A, 50/60Hz, 1PH



Printing Material

Carton, Plastic, Metal, Boarding, Pipe, Cable
Stone, Glass, Electronic components, Food,
Auto parts, Industrial chemical packaging

Communication Interface

RS232, Network interface, connection to enterprise
EMS Management system
(Various external equipment protocols can be added)

Print Content

Text, Time, Date, Logo, Shift, SN, Dynamic QR Code,
Dynamic Serial Data, Dynamic Database

PRINT HEAD

Aluminum alloy material Flip design for easy
daily maintenance.



INK SYSTEM

The double stirring ink system design of the
white ink machine and the automatic stirring
mode of software sleep can better solve the
problem of pigment and special ink precipitation,
to ensure the stable operation of the machine

Support Language


Support more than 40 national languages
Chinese, English, Arabic, Danish, German,
Russian, French, Finnish, Korean, Norwegian,
Portuguese, Japanese, Spanish, Italian, etc.

External Interface

Optical Sensor, Encoder, Signal Light Alarm Output,
Information Selection and Control, Reset Switch.

Main Hardware

U.S. TI AM3358 industrial-grade CPU,
U.S. Xilinx Spant6 industrial-grade FPGA,
ASIC chip



PRINTER CHASSIS

Robust and durable stainless steel.



Print Sample



Like us on :



RADHE
ENTERPRISE

Plot No. 36, Sr.No. 277/1,
Opp. Kaneriya oil Mill,
Rani Ind. Area, Shapar (Veraval),
Dist. Rajkot, INDIA.

T. 02827 252232

M. +91 99099 81123, +91 99136 31412

E. info@rejettech.com

w. www.rejettech.com

Ahmedabad | Morbi | Gandhidham | Surat | Vapi
Rajasthan | Maharashtra | Madhya Pradesh | West Bengal
Karnataka | Andhra Pradesh | Panjab | Delhi | Uttar Pradesh