




RE 200+

**CONTINUES
INKJET
PRINTER**



Re 200 plus series continuous small character inkjet printer is designed for high quality printing and improving production line effectively.

Its print head adopts independent structure design, and the stainless-steel chassis, which can maintain reliable operation in harsh production environment as well as improve the production line effectively.



Printing Parameters:

Print Head Duct	: 3MTR
Nozzle Specification	: 60um
Printing Height	: 2mm to 14mm
Printing Distance	: 1mm to 15mm
Printing Lines	: 1 to 5 Lines
Printing Speed	: 450 m/min
Counter	: More than 20 Independent Counter
Ink Colour	: Black, Red, Brown, Royal Blue, Sky Blue, Green,
Font	: 5x6L 7x6L 7x10L 9x8L 9x11L 11x11L 16x16L 24x24L 32x32L 11x11B 16x16B 24x24B 32x32B
Printing Material	: Carton, Plastic, Metal, Boarding, Pipe, Stone, Cable, Glass, Electronic components, Auto parts, Industrial chemical packaging Medical, Food
Print Content	: Text, Time, Date (Julian Year), Logo, Shift, SN, Dynamic Barcode/QR Code, Dynamic Serial Data, Dynamic Database.



MACHINE PARAMETERS

Operating System	: Embedded Linux security operating system
Display Screen	: 10.1-inch colour display, industrial touchscreen
Communication Interface	: Network port, USB, RS232
Protection Level	: IP55
Power Parameters	: Input 220-240V
Rated Power	: 150W
Memory	: 256M
Machine Material	: 304 stainless steel
Machine Specifications	: 447mmx242mmx650mm (L X W X H)
Working Environment	: Temperature 0-45°C/Humidity 30-70%Rh
Related Certification	: RoHS. CE. BIS
Net Weight	: 30Kg
Main Hardware	: American TIAM3358 industrial grade CPU, American Xilinx Spartan-6 industrial grade FPGA
External Interface	: Optical sensor, Encoder, Reverse and upside down control, Signal light alarm output, Serial number output control, External printing information selection.
Support Language	: Support more than 40 national languages (Chinese, English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc).

Font	Print Sample
7 X 5 One Line	
9 X 7 One Line	
12 X 12 One Line	
16 X 14 One Line	
24 X 22 One Line	
32 X 30 One Line	
7 X 5 Two line	
7 X 5 Three Line	
5 X 5 Five Line	



PRINT HEAD

The nozzle valve adopts direct sealing nozzle hole structure, effectively prevent the ink leakage.

INK SYSTEM





Double-head pump design makes more stable and durable. White ink machine has double mixing system to prevent the pigment ink precipitation.

MAIN HARDWARE

The main board with newest structure has superior performance of function and stability, and the EHT is dustproof and waterproof, better to deal with the harsh and complex environment.

EXTERNAL FACE

With grade of IP68, the interface not only supports RS232, network port, but also the counter reset, information control and other functions.



RADHE
ENTERPRISE



Like us on :



Plot No. 36, Sr.No. 277/1, Opp. Kaneriya oil Mill,
Rani Ind. Area, Shapar (Veraval), Dist. Rajkot.

+91 99099 81123, +91 99136 31412

info@rejettech.com | www.rejettech.com