

SELECT MODEL**1 Series****DGC 320****2 Type**

G Gauge
GS Gauge + Switch(std.)

3 Body material

A Aluminum(std.)
S SS-316

B Brass

4 Dial size

2.0 2.0" (50 mm)(std.)
2.5 2.5" (63 mm)

Connection

8N 1/8" NPT (F) (Std.)

6 Porting

2 Rear / Back
3 Bottom (std.)

7 Case

SS SS 304 (Std.)
SD Engineering polymer(2.5" only)

8 Window

F Glass (Std.)
T Toughened glass

A Acrylic
L Safety glass

9 Seals/Diaphragm

B Buna-N (Std.)
V Viton

E EPDM

10 Switch

Select option & Specifications

0	None
1	One SPST, with a DIN plug
3	Two SPSTs, with a DIN plug

+

SPST Specifications (AC/DC max)

1 Standard	2	3	4
10 VA	40 VA	100 VA	60VA
100 V	230 V	300 V	240V
0.5 Amp	1 Amp	1 Amp	3 Amp
Factory set fixed			

5	One SPDT, with a DIN plug
---	---------------------------

+

SPDT Specifications (AC/DC max)

1 Standard	2	3	-
3 VA	5 VA	5 VA	-
30 V	125 V	175 V	-
0.3 Amp	0.25 Amp	0.25 Amp	-
Factory set fixed			

11 Range**Standard ranges :****320 DGC**


Kg/cm ²	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
bar	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
mbar	75	250	-	-	750	-	-	-	-	-	-	-	-
psi	1	-	5	8	-	15	20	25	30	-	40	50	60
kPa	-	25	-	50	75	100	-	160	200	250	300	-	400

12 Options

0 None
C Customer Logo
F Filter mesh in (+) connection

Ordering code sequence

Before creating ordering code, please refer model wise notes above.



Contact factory for special execution.