SELECT MODEL

1 Series   **CZ 300 DGC**

Type
G	Gauge	S	Switch
GS	Gauge + Switch		

3 Body material
A	Aluminum	B	Brass
S	SS-316	M	Monel

4 Dial size
2.0	2.0" (50 mm)	4.0	4.0" (100 mm)
2.5	2.5" (63 mm)	4.5	4.5" (115 mm)
3.5	3.5" (80 mm)	6.0	6.0" (150 mm)

5 Connection
4N	1/4" NPT (F) (Std.)	4B	1/4" BSP (F) (with adaptor)
ZZ	Special connection sizes using adaptor		

6 Porting
1	In-line (Std.)	4	Bottom & Vent
2	Rear / Back	5	Inline & Vent
3	Bottom	6	Inline & Bottom

7 Case
SS	SS 304 (Std.)	SF	SS 304 flange

8 Window
F	Glass (Std.)	A	Acrylic
T	Toughened glass	L	Safety glass

9 Seals/Diaphragm
B	Buna-N (Std.)	E	EPDM
V	Viton		

10 Switch   Select option & Specifications

5	One SPDT, with a DIN plug †
6	One SPDT, with a terminal strip
7	Two SPDTs, with two DIN plugs
8	Two SPDTs, with a terminal strip

† DIN plug mounted on the top.

+

SPDT Specifications (AC/DC max)

1 Standard	2	3
3 VA	5 VA	5 VA
30 V	125 V	175 V
0.3 Amp	0.25 Amp	0.25 Amp
Adjustable	Adjustable	Adjustable

Advantages :
Instrument automatically resets after line surges and cold start.
This eliminates balancing of differential pressure instrument after such events.

Model	Notes
CZ 300	Switch option not available with inline vent / bottom vent porting.

11 Range   **Standard ranges : (Other ranges on request)**

Kg/cm²	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
bar	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
mbar	75	250	-	-	750	-	-	-	-	-	-	-	-
psi	1	-	5	8	-	15	20	25	30	-	40	50	60
kPa	-	25	-	50	75	100	-	160	200	250	300	-	400

12 Options

0	None
A	Glycerine*
B	Red follower pointer on acrylic window *
C	Customer Logo
D	Dual scale
E	Colour band
F	Filter mesh in (+) connection
N	NACE
S	Silicone oil*
I	Oxygen service (Contact factory)
M1	2" horizontal pipe mounting bracket
M2	Surface mounting bracket
M3	2" vertical pipe mounting bracket

* Affects accuracy

Ordering code sequence

Before creating ordering code, please refer notes above.

- Series
- Type
- Body material
- Dial size
- Connection
- Porting
- Case
- Window
- Seal / Diaphragm
- Switch
- Range
- Options

XXXXXX- XX- X- XX- XX- X- XX- X- X- XX-(Range)- X
   1   2   3   4   5   6   7   8 9 10   11   12

Contact factory for special execution.