SELECT MODEL

1 Series — DX 10

2 Basic options
F Float glass (std.)	A Acrylic
H Hardened glass	

3 Liquid filling — G Glycerine *   S Silicone *

4 Dial size — 3.5 3.5″ (80mm)   4.0 4.0″ (100 mm)

5 Case type — SS SS 304 (Std.)   SF SS 304 flange ***

6 Ranges — Standard ranges (Other ranges on request)

DX 10 bar	0.25	0.4	0.6	1.0	1.6	2.0	2.5	3.0	4.0	6.0	10.0
psi	3.5	6.0	9.0	15	24	30	36	45	60	90	140

DX 20 bar	0.16	0.2	0.25	0.4	0.6	1.0	1.6	2.0
psi	2.4	3.0	3.5	6.0	9.0	15	24	30

7 Porting
1 In-line (Std.)	2 Rear / Back***
3 Bottom***	

8 Port threading 2x
4B 1/4″ BSP (F) (Std.)	4N 1/4″ NPT (F)
ZZ Special connection sizes using adaptor	

9 Seals — B Buna-N   V Viton

10 Pressure
100 100bar	250 250 bar***
400 400 bar***	

11 Connection — 0 + left / - right   R + right / - left *** **

12 Mounting
0 None	M1 2″ horizontal pipe mounting bracket
M2 Surface mounting	M3 2″ vertical pipe mounting bracket
M4 Engg. polymer mounting bracket	

13 Switch — Select option and specifications

0	None	
S1	One SPST, with a DIN plug	
S4	Two SPSTs, with DIN plug	

+

SPST Specifications (AC/DC max)

1 Standard	2	3
10 VA	40 VA	100 VA
100 V	230 V	300 V
0.5 Amp	1 Amp	1 Amp
Adjustable	Adjustable	Adjustable

S2	One SPDT, with a DIN plug
S3	Two SPDTs, with DIN plug

+

SPDT Specifications (AC/DC max)

1 Standard	2	3
3 VA	5 VA	5 VA
30 V	125 V	175 V
0.3 Amp	0.25 Amp	0.25 Amp
Adjustable	Adjustable	Adjustable

14 Wiring options
W1 DIN plug at top	W2 DIN plug on LP side
W3 DIN plug at back	W4 2 DIN plugs for 2 SPDTs (1 on LP side and other on top)

15 Other options
0	None
F	Follower pointer on acrylic window*
S	Filter mesh in (+) connection
C	Customer logo
E	Color band (Available in single scale only)

16 Certifications
0	None	C1	Certificate of conformance
C2	Accuracy and class	C3	Material test certificate
C4	Pressure test		

* Affects accuracy
** Pointer moves from right to left
*** Only in DX 10