

CrowdStrike CCFA

CrowdStrike Certified Falcon Administrator · 248 questions (with answers)

QUESTION 1

Issued to hiroko@hirokoymj.com · September 26, 2026

What is the function of a single asterisk (*) in an ML exclusion pattern?

- A The single asterisk will match any number of characters, including none. It does include separator characters, such as \ or /, which separate portions of a file path
- B The single asterisk will match any number of characters, including none. It does not include separator characters, such as \ or /, which separate portions of a file path** ✓ CORRECT
- C The single asterisk is the insertion point for the variable list that follows the path
- D The single asterisk is only used to start an expression, and it represents the drive letter

SUGGESTED ANSWER

The suggested answer is B.

A single asterisk (*) in an ML exclusion pattern will match any number of characters, including none. This does not include separator characters, such as backslashes (\) or forward slashes (/), which are used to separate portions of a file path.

You have determined that you have numerous Machine Learning detections in your environment that are false positives. They are caused by a single binary that was custom written by a vendor for you and that binary is running on many endpoints. What is the **BEST** way to prevent these in the future?

- A Contact support and request that they modify the Machine Learning settings to no longer include this detection
- B Using IOC Management, add the hash of the binary in question and set the action to "Allow"** ✓ CORRECT
- C Using IOC Management, add the hash of the binary in question and set the action to "Block, hide detection"
- D Using IOC Management, add the hash of the binary in question and set the action to "No Action"

SUGGESTED ANSWER

The suggested answer is B.

The best way to prevent future false positives caused by the custom binary is to use IOC (Indicator of Compromise) Management to add the hash of the binary and set the action to 'Allow'. This will ensure that the binary is recognized as safe and will not trigger false positives in the Machine Learning detections. This approach directly addresses the issue by specifying that this particular binary should be allowed, thus preventing further false alarms.

What is the purpose of a containment policy?

- A To define which Falcon analysts can contain endpoints
- B To define the duration of Network Containment
- C To define the trigger under which a machine is put in Network Containment (e.g. a critical detection)
- D To define allowed IP addresses over which your hosts will communicate when contained** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The purpose of a containment policy is to define allowed IP addresses over which your hosts will communicate when contained. This ensures that even when a machine is put in Network Containment, it can still communicate with specific IP addresses or IP ranges as defined by the policy.

An administrator creating an exclusion is limited to applying a rule to how many groups of hosts?

- A File exclusions are not aligned to groups or hosts
- B There is a limit of three groups of hosts applied to any exclusion
- C There is no limit and exclusions can be applied to any or all groups** ✓ CORRECT
- D Each exclusion can be aligned to only one group of hosts

SUGGESTED ANSWER

The suggested answer is C.

There is no limit and exclusions can be applied to any or all groups. Administrators are not restricted to a specific number of groups, allowing flexibility in managing exclusions across various hosts.

Even though you are a Falcon Administrator, you discover you are unable to use the "Connect to Host" feature to gather additional information which is only available on the host. Which role do you need added to your user account to have this capability?

A Real Time Responder

✓ CORRECT

B Endpoint Manager

C Falcon Investigator

D Remediation Manager

SUGGESTED ANSWER

The suggested answer is A.

To use the 'Connect to Host' feature and gather additional information directly from the host in Falcon, the user needs the 'Real Time Responder' role. This role specifically grants the necessary permissions for real-time response actions, including connecting to a host for further investigation.

What must an admin do to reset a user's password?

- A From User Management, open the account details for the affected user and select "Generate New Password"
- B From User Management, select "Reset Password" from the three dot menu for the affected user account** ✓ CORRECT
- C From User Management, select "Update Account" and manually create a new password for the affected user account
- D From User Management, the administrator must rebuild the account as the certificate for user specific private/public key generation is no longer valid

SUGGESTED ANSWER

The suggested answer is B.

To reset a user's password, the administrator should go to User Management, select the affected user account, and use the 'Reset Password' option from the three-dot menu. This method is direct and aligns with typical user management interfaces, offering a straightforward and practical approach to password reset.

Your organization has a set of servers that are not allowed to be accessed remotely, including via Real Time Response (RTR). You already have these servers in their own Falcon host group. What is the next step to disable RTR only on these hosts?

- A Edit the Default Response Policy, toggle the "Real Time Response" switch off and assign the policy to the host group
- B Edit the Default Response Policy and add the host group to the exceptions list under "Real Time Functionality"
- C Create a new Response Policy, toggle the "Real Time Response" switch off and assign the policy to the host group** ✓ CORRECT
- D Create a new Response Policy and add the host name to the exceptions list under "Real Time Functionality"

SUGGESTED ANSWER

The suggested answer is C.

To disable Real Time Response (RTR) only on specific hosts within a host group, you need to create a new Response Policy, toggle the 'Real Time Response' switch off, and assign this newly created policy to the host group. This method ensures that only the designated hosts in the host group will have RTR disabled, without affecting other configurations or host groups.

When creating new IOCs in IOC management, which of the following fields must be configured?

- ☐ A Hash, Description, Filename
- ☐ B Hash, Action and Expiry Date
- ☐ C Filename, Severity and Expiry Date
- ☒ D Hash, Platform and Action

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

When creating new IOCs in IOC management, the fields Hash, Platform, and Action must be configured. The Hash uniquely identifies the indicator, the Platform specifies the operating systems the IOC applies to, and the Action determines the response when the IOC is detected.

Your CISO has decided all Falcon Analysts should also have the ability to view files and file contents locally on compromised hosts, but without the ability to take them off the host. What is the **MOST** appropriate role that can be added to fulfill this requirement?

- A Remediation Manager
- B Real Time Responder – Read Only Analyst** ✓ CORRECT
- C Falcon Analyst – Read Only
- D Real Time Responder – Active Responder

SUGGESTED ANSWER

The suggested answer is B.

To view files and file contents locally on compromised hosts without the ability to extract them, the 'Real Time Responder – Read Only Analyst' role is the most appropriate. This role grants permissions to run specific commands such as viewing file contents without permitting file extraction, which aligns with the requirement of being able to view files without the ability to take them off the host.

One of your development teams is working on code for a new enterprise application but Falcon continually flags the execution as a detection during testing. All development work is required to be stored on a file share in a folder called "devcode." What setting can you use to reduce false positives on this file path?

A USB Device Policy

B Firewall Rule Group

C Containment Policy

D Machine Learning Exclusions

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To reduce false positives on a specific file path for development work, such as the 'devcode' folder mentioned, adjusting the Machine Learning Exclusions is the appropriate setting. This allows you to exclude specific files or directories from being flagged by machine learning algorithms, thus minimizing false positives during development testing.

How do you disable all detections for a host?

- A Create an exclusion rule and apply it to the machine or group of machines
- B Contact support and provide them with the Agent ID (AID) for the machine and they will put it on the Disabled Hosts list in your Customer ID (CID)
- C You cannot disable all detections on individual hosts as it would put them at risk
- D In Host Management, select the host and then choose the option to Disable Detections** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

In Host Management, select the host and then choose the option to Disable Detections. This allows for centralized control and is a direct way to manage the security settings for specific hosts.

To enhance your security, you want to detect and block based on a list of domains and IP addresses. How can you use IOC management to help this objective?

- A** Blocking of Domains and IP addresses is not a function of IOC management. A Custom IOA Rule should be used instead ✓ CORRECT
- B** Using IOC management, import the list of hashes and IP addresses and set the action to Detect Only
- C** Using IOC management, import the list of hashes and IP addresses and set the action to Prevent/Block
- D** Using IOC management, import the list of hashes and IP addresses and set the action to No Action

SUGGESTED ANSWER

The suggested answer is A.

Blocking of domains and IP addresses is not a function of IOC management. Instead, a Custom IOA Rule should be used to block processes associated with specific domains or IP addresses. IOC management primarily supports actions like Detect Only or No Action for domains and IP addresses, and block actions are generally limited to hash indicators.

Which role is required to manage groups and policies in Falcon?

A Falcon Host Analyst

B Falcon Host Administrator

✓ CORRECT

C Prevention Hashes Manager

D Falcon Host Security Lead

SUGGESTED ANSWER

The suggested answer is B.

To manage groups and policies in Falcon, the role of Falcon Host Administrator is required. This role has the necessary permissions to handle the administration and management tasks associated with groups and policies within the Falcon platform.

Which of the following can a Falcon Administrator edit in an existing user's profile?

A First or Last name

✓ CORRECT

B Phone number

C Email address

D Working groups

SUGGESTED ANSWER

The suggested answer is A.

A Falcon Administrator can edit the first or last name in an existing user's profile. This is a common feature in many administrative interfaces to allow for corrections or updates to a user's basic personal information.

You want the Falcon Cloud to push out sensor version changes but you also want to manually control when the sensor version is upgraded or downgraded. In the Sensor Update policy, which is the best Sensor version option to achieve these requirements?

A Specific sensor version number

✓ CORRECT

B Auto - TEST-QA

C Sensor version updates off

D Auto - N-1

SUGGESTED ANSWER

The suggested answer is A.

To manually control when the sensor version is upgraded or downgraded while still allowing the Falcon Cloud to push out sensor version changes, selecting a specific sensor version number is ideal. This way, you can set the version you want and update it manually when needed.

What is the goal of a **Network Containment Policy**?

A Increase the aggressiveness of the assigned prevention policy

B Limit the impact of a compromised host on the network

✓ CORRECT

C Gain more visibility into network activities

D Partition a network for privacy

SUGGESTED ANSWER

The suggested answer is B.

The goal of a Network Containment Policy is to limit the impact of a compromised host on the network. This policy is designed to isolate or contain any threats or compromised devices to prevent them from spreading and affecting other parts of the network. It helps in mitigating the damage and maintaining network integrity.

Which of the following applies to Custom Blocking Prevention Policy settings?

- ☒ A Hashes must be entered on the Prevention Hashes page before they can be blocked via this policy ✓ CORRECT
- ☐ B Blocklisting applies to hashes, IP addresses, and domains
- ☐ C Executions blocked via hash blocklist may have partially executed prior to hash calculation process remediation may be necessary
- ☐ D You can only blocklist hashes via the API

SUGGESTED ANSWER

The suggested answer is A.

Hashes must be entered on the Prevention Hashes page before they can be blocked via this policy. Custom blocking in prevention policies refers to blocklisting hashes through the IOC Management, and hashes need to be added here first. There is no mention of blocklisting IP addresses and domains under custom blocking settings, nor the necessity for remediation after partial executions.

How many "Auto" sensor version update options are available for Windows Sensor Update Policies?

A 1

B 2

C 0

D 3

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Windows Sensor Update Policies provide three 'Auto' sensor version update options: Auto - Latest, Auto - N-1, and Auto - N-2. This ensures that users can select from the latest version or one of the two prior versions for updates.

The alignment of a particular prevention policy to one or more host groups can be completed in which of the following locations within Falcon?

- A Policy alignment is configured in the "Host Management" section in the Hosts application
- B Policy alignment is configured only once during the initial creation of the policy in the "Create New Policy" pop-up window
- C Policy alignment is configured in the General Settings section under the Configuration menu
- D Policy alignment is configured in each policy in the "Assigned Host Groups" tab** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Policy alignment is configured in each policy in the 'Assigned Host Groups' tab. This allows for specific control and customization of which host groups a particular prevention policy applies to, providing flexibility in managing different sets of hosts within Falcon.

How long are detection events kept in Falcon?

- A Detection events are kept for 90 days
- B Detections events are kept for your subscribed data retention period** ✓ CORRECT
- C Detection events are kept for 7 days
- D Detection events are kept for 30 days

SUGGESTED ANSWER

The suggested answer is B.

Detection events in Falcon are kept for the duration of your subscribed data retention period. This means the retention period can vary depending on the specific terms of the subscription agreement with Falcon. Different customers could have different data retention periods, tailored to their needs and the service level they have subscribed to.

What information is provided in Logan Activities under Visibility Reports?

- A A list of all logons for all users
- B A list of last endpoints that a user logged in to** ✓ CORRECT
- C A list of users who are remotely logged on to devices based on local IP and local port
- D A list of unique users who are remotely logged on to devices based on the country

SUGGESTED ANSWER

The suggested answer is B.

In Logan Activities under Visibility Reports, the information provided includes a list of the last endpoints that a user logged in to. This aligns with the function of tracking and summarizing the last logon activity of users to keep track of their most recent access points.

What can the Quarantine Manager role do?

- A Manage and change prevention settings
- B Manage quarantined files to release and download**
- C Manage detection settings
- D Manage roles and users

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is B.

The Quarantine Manager role is responsible for handling quarantined files, including managing, releasing, and downloading them. This role is specifically focused on dealing with items that have been flagged and isolated, ensuring appropriate actions are taken regarding these files.

What command should be run to verify if a Windows sensor is running?

A regedit myfile.reg

B sc query csagent

✓ CORRECT

C netstat -f

D ps -ef | grep falcon

SUGGESTED ANSWER

The suggested answer is B.

To verify if a Windows sensor is running, the command 'sc query csagent' is appropriate. 'sc' is a command-line utility in Windows used to communicate with the Service Control Manager and services, 'query' asks for the status, and 'csagent' is the typical name of the sensor service. This command will return the current status of the service.

When configuring a specific prevention policy, the admin can align the policy to two different types of groups, Host Groups and which other?

A Custom IOA Rule Groups

✓ CORRECT

B Custom IOC Groups

C Enterprise Groups

D Operating System Groups

SUGGESTED ANSWER

The suggested answer is A.

When configuring a specific prevention policy, the admin can align the policy to two different types of groups, Host Groups, and Custom IOA Rule Groups. Custom IOA Rule Groups allow administrators to define and apply specific Indicators of Attack (IOA) that help in detecting and preventing suspicious activities, making them essential in the configuration of prevention policies.

Which role allows a user to connect to hosts using Real-Time Response?

- A Endpoint Manager
- B Falcon Administrator
- C Real Time Responder – Active Responder**
- D Prevention Hashes Manager

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

The role that allows a user to connect to hosts using Real-Time Response is 'Real Time Responder – Active Responder'. This role specifically grants the permissions needed for real-time interaction with endpoints, which includes executing commands and performing investigative tasks. Other roles like 'Endpoint Manager', 'Falcon Administrator', and 'Prevention Hashes Manager' do not provide the specific permissions needed for real-time response activities.

You are attempting to install the Falcon sensor on a host with a slow Internet connection and the installation fails after 20 minutes. Which of the following parameters can be used to override the 20 minute default provisioning window?

A ExtendedWindow=1

B Timeout=0

C ProvNoWait=1

✓ CORRECT

D Timeout=30

SUGGESTED ANSWER

The suggested answer is C.

To override the 20-minute default provisioning window during the installation of the Falcon sensor on a host with a slow internet connection, you can use the parameter 'ProvNoWait=1'. This parameter prevents the sensor from aborting the installation if it can't connect to the CrowdStrike cloud within the default 20-minute window.

How can you find a list of hosts that have not communicated with the CrowdStrike Cloud in the last 30 days?

- A** Under Dashboards and reports, choose the Sensor Report. Set the "Last Seen" dropdown to 30 days and reference the Inactive Sensors widget ✓ CORRECT
- B** Under Host setup and management, choose the Host Management page. Set the group filter to "Inactive Sensors"
- C** Under Host setup and management > Managed endpoints > Inactive Sensors. Change the time range to 30 days
- D** Under Host setup and management, choose the Disabled Sensors Report. Change the time range to 30 days

SUGGESTED ANSWER

The suggested answer is A.

To find a list of hosts that have not communicated with the CrowdStrike Cloud in the last 30 days, you should navigate to Dashboards and reports and choose the Sensor Report. Set the 'Last Seen' dropdown to 30 days and reference the Inactive Sensors widget. This helps in getting a precise list of hosts based on their last communication date.

In order to quarantine files on the host, what prevention policy settings must be enabled?

- A Malware Protection and Custom Execution Blocking must be enabled
- B Next-Gen Antivirus Prevention sliders and "Quarantine & Security Center Registration" must be enabled** ✓ CORRECT
- C Malware Protection and Windows Anti-Malware Execution Blocking must be enabled
- D Behavior-Based Threat Prevention sliders and Advanced Remediation Actions must be enabled

SUGGESTED ANSWER

The suggested answer is B.

To quarantine files on the host, it is essential to have the Next-Gen Antivirus Prevention sliders enabled as they provide the core protection against threats. Additionally, the 'Quarantine & Security Center Registration' must be enabled to manage and register quarantined files effectively. This combination ensures a comprehensive approach to identifying, blocking, and isolating malicious files.

Why is it critical to have separate sensor update policies for Windows/Mac/*nix?

A There may be special considerations for each OS

✓ CORRECT

B To assist with testing and tracking sensor rollouts

C The network protocols are different for each host OS

D It is an auditing requirement

SUGGESTED ANSWER

The suggested answer is A.

Each operating system has unique characteristics, security requirements, and potential vulnerabilities. Customizing sensor update policies for each OS allows for addressing these specific needs effectively, ensuring optimal performance and security.

How do you assign a policy to a specific group of hosts?

- A** Create a group containing the desired hosts using "Static Assignment." Go to the Assigned Host Groups tab of the desired policy and click "Add groups to policy." Select the desired Group(s). ✓ CORRECT
- B** Assign a tag to the desired hosts in Host Management. Create a group with an assignment rule based on that tag. Go to the Assignment tab of the desired policy and click "Add Groups to Policy." Select the desired Group(s).
- C** Create a group containing the desired hosts using "Dynamic Assignment." Go to the Assigned Host Groups tab of the desired policy and select criteria such as OU, OS, Hostname pattern, etc.
- D** On the Assignment tab of the desired policy, select "Static" assignment. From the next window, select the desired hosts (using filters if needed) and click Add.

SUGGESTED ANSWER

The suggested answer is A.

To assign a policy to a specific group of hosts, you should create a group containing the desired hosts using "Static Assignment." Once the group is created, navigate to the Assigned Host Groups tab of the desired policy and click on "Add Groups to Policy." From there, select the desired group(s). This approach ensures the policy is applied to a defined set of hosts, which does not change dynamically.

You want to create a detection-only policy. How do you set this up in your policy's settings?

- A Enable the detection sliders and disable the prevention sliders. Then ensure that Next Gen Antivirus is enabled so it will disable Windows Defender.
- B Select the "Detect-Only" template. Disable hash blocking and exclusions.
- C You can't create a policy that detects but does not prevent. Use Custom IOA rules to detect.
- D Set the Next-Gen Antivirus detection settings to the desired detection level and all the prevention sliders to disabled. Do not activate any of the other blocking or malware prevention options.** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To create a detection-only policy, you should set the Next-Gen Antivirus detection settings to the desired detection level and disable all the prevention sliders. Additionally, it is important to not activate any other blocking or malware prevention options. This ensures that the policy will detect potential threats without taking any preventive measures against them.

Which of the following is an effective Custom IOA rule pattern to kill any process attempting to access www.badguydomain.com?

A *.badguydomain\com.*

✓ CORRECT

B \Device\HarddiskVolume2*.exe -SingleArgument www.badguydomain.com /kill

C badguydomain\com.*

D Custom IOA rules cannot be created for domains

SUGGESTED ANSWER

The suggested answer is A.

An effective Custom IOA rule pattern to kill any process attempting to access www.badguydomain.com should be able to capture any instance of the domain within various processes or commands. The pattern '*.badguydomain\com.*' uses regular expressions to match any string containing 'badguydomain.com', regardless of what comes before or after it. This ensures that any process attempting to access www.badguydomain.com or any subdomains will be detected and handled appropriately.

Where can you modify settings to permit certain traffic during a containment period?

A Prevention Policy

B Host Settings

C Containment Policy

✓ CORRECT

D Firewall Settings

SUGGESTED ANSWER

The suggested answer is C.

To modify settings to permit certain traffic during a containment period, you would use the Containment Policy. This policy is specifically designed for managing network traffic and implementing controls during containment scenarios, allowing selective permissions and adjustments to traffic flow in response to incidents.

Which option allows you to exclude behavioral detections from the detections page?

A Machine Learning Exclusion

B IOA Exclusion

✓ CORRECT

C IOC Exclusion

D Sensor Visibility Exclusion

SUGGESTED ANSWER

The suggested answer is B.

Behavioral detections are related to Indicators of Attack (IOA) exclusions. IOA exclusions stop all behavioral detections and preventions for an IOA that's based on a CrowdStrike-generated detection. This means that choosing the IOA exclusion option will allow you to exclude behavioral detections from the detections page.

What are custom alerts based on?

- A Custom workflows
- B Custom event based triggers
- C Predefined alert templates**
- D User defined Splunk queries

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

Custom alerts are based on predefined alert templates. This is because custom alerts often utilize pre-existing templates that can be configured to meet specific needs, rather than creating entirely new event triggers from scratch.

When creating an API client, which of the following must be saved immediately since it cannot be viewed again after the client is created?

A Base URL

B Secret

✓ CORRECT

C Client ID

D Client name

SUGGESTED ANSWER

The suggested answer is B.

When creating an API client, the 'Secret' must be saved immediately since it cannot be viewed again after the client is created. The Base URL, Client ID, and Client name can be viewed or retrieved later if needed, but the Secret is typically shown only during the initial creation process.

You notice there are multiple Windows hosts in Reduced functionality mode (RFM). What is the most likely culprit causing these hosts to be in RFM?

- A A Sensor Update Policy was misconfigured
- B A host was offline for more than 24 hours
- C A patch was pushed overnight to all Windows systems
- D A host was placed in network containment from a detection**

✓ CORRECT**SUGGESTED ANSWER**

The suggested answer is D.

Reduced Functionality Mode (RFM) typically occurs when a host cannot verify its license or activation status with a Key Management Service (KMS) server. This situation often arises when a host is placed in network containment, preventing it from communicating with the KMS server. Therefore, the most likely culprit causing these hosts to be in RFM is that the host was placed in network containment from a detection.

Which of the following is **TRUE** of the Logon Activities Report?

A Shows a graphical view of user logon activity and the hosts the user connected to

✓ CORRECT

B The report can be filtered by computer name

C It gives a detailed list of all logon activity for users

D It only gives a summary of the last logon activity for users

SUGGESTED ANSWER

The suggested answer is A.

The Logon Activities Report shows a graphical view of user logon activity and the hosts the user connected to. This feature provides a visual representation of the logon events which helps in easily understanding the user's logon patterns and the devices they have accessed, making it the most accurate statement among the options.

Which of the following roles allows a Falcon user to create Real Time Response Custom Scripts?

A Real Time Responder – Administrator

✓ CORRECT

B Real Time Responder – Read Only Analyst

C Real Time Responder – Script Developer

D Real Time Responder – Active Responder

SUGGESTED ANSWER

The suggested answer is A.

The role that allows a Falcon user to create Real Time Response Custom Scripts is 'Real Time Responder – Administrator'. This role has the necessary permissions to create custom scripts, upload files to hosts using the put command, and directly run executables using the run command. Other roles do not have these capabilities.

What model is used to create workflows that would allow you to create custom notifications based on particular events which occur in the Falcon platform?

A For - While statement(s)

B Trigger, condition(s) and action(s)

✓ CORRECT

C Event trigger(s)

D Predefined workflow template(s)

SUGGESTED ANSWER

The suggested answer is B.

The model that is used to create workflows in the Falcon platform, which allows for custom notifications based on particular events, is comprised of triggers, conditions, and actions. This structure enables the system to respond to specific events by checking certain conditions and then performing designated actions.

An analyst is asked to retrieve an API client secret from a previously generated key. How can they achieve this?

- A The API client secret can be viewed from the Edit API client pop-up box
- B Enable the Client Secret column to reveal the API client secret
- C Re-create the API client using the exact name to see the API client secret

D The API client secret cannot be retrieved after it has been created

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The API client secret cannot be retrieved after it has been created. This is a common security practice to ensure that sensitive credentials are not exposed or reused improperly. If the secret is lost or forgotten, the recommended approach is to generate a new client secret.

Which port and protocol does the sensor use to communicate with the CrowdStrike Cloud?

A TCP port 22 (SSH)

B TCP port 443 (HTTPS)

✓ CORRECT

C TCP port 80 (HTTP)

D TCP UDP port 53 (DNS)

SUGGESTED ANSWER

The suggested answer is B.

The sensor communicates with the CrowdStrike Cloud using TCP port 443 (HTTPS). HTTPS is a protocol used for secure communication over a computer network, widely used on the internet. Port 443 is specifically designated for HTTPS traffic, ensuring encrypted and secure data transmission between the sensor and the CrowdStrike Cloud.

Where do you obtain the Windows sensor installer for CrowdStrike Falcon?

- ☒ A Sensors are downloaded from the Hosts > Sensor Downloads ✓ CORRECT
- ☐ B Sensor installers are unique to each customer and must be obtained from support
- ☐ C Sensor installers are downloaded from the Support section of the CrowdStrike website
- ☐ D Sensor installers are not used because sensors are deployed from within Falcon

SUGGESTED ANSWER

The suggested answer is A.

The Windows sensor installer for CrowdStrike Falcon is downloaded from the Hosts > Sensor Downloads section within the Falcon console. This is the designated location for users to obtain their sensor installers.

What is the most common cause of a Windows Sensor entering Reduced Functionality Mode (RFM)?

- ☐ A Falcon console updates are pending
- ☐ B Falcon sensors installing an update
- ☐ C Notifications have been disabled on that host sensor
- ☒ D Microsoft updates

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The most common cause of a Windows Sensor entering Reduced Functionality Mode (RFM) is due to Microsoft updates. When Microsoft releases updates, the kernel needs to be verified and certified for the new sensor version. If this verification process fails or is pending, the sensor runs in RFM.

On which page of the Falcon console would you create sensor groups?

A User management

B Sensor update policies

C Host management

D Host groups

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

In the Falcon console, sensor groups are created under the Host groups page. The user management page is typically used for managing user permissions and roles, while the sensor update policies page is used for configuring update policies for existing sensor groups. Host management generally involves managing individual hosts rather than groups. Therefore, the correct option is the Host groups page.

While a host is Network contained, you need to allow the host to access internal network resources on specific IP addresses to perform patching and remediation. Which configuration would you choose?

A Configure a Real Time Response policy allowlist with the specific IP addresses

B Configure a Containment Policy with the specific IP addresses

✓ CORRECT

C Configure a Containment Policy with the entire internal IP CIDR block

D Configure the Host firewall to allowlist the specific IP addresses

SUGGESTED ANSWER

The suggested answer is B.

When a host is network contained and needs to access specific internal IP addresses for patching and remediation, the correct approach is to configure a Containment Policy with the specific IP addresses. This policy manages the rules and exceptions that apply specifically to contained hosts, ensuring they can communicate with necessary IPs while remaining contained from other network traffic.

Which of the following is **TRUE** regarding Falcon Next-Gen AntiVirus (NGAV)?

- ☐ A Falcon NGAV relies on signature-based detections
- ☐ B Activating Falcon NGAV will also enable all detection and prevention settings in the entire policy
- ☒ C The Detection sliders cannot be set to a value less aggressive than the Prevention sliders ✓ CORRECT
- ☐ D Falcon NGAV is not a replacement for Windows Defender or other antivirus programs

SUGGESTED ANSWER

The suggested answer is C.

The Detection sliders in Falcon Next-Gen AntiVirus (NGAV) cannot be set to a value less aggressive than the Prevention sliders, ensuring that the detection of threats is prioritized equally or more stringently than their prevention.

What is the purpose of using groups with Sensor Update policies in CrowdStrike Falcon?

- A To group hosts with others in the same business unit
- B To group hosts according to the order in which Falcon was installed, so that updates are installed in the same order every time
- C To prioritize the order in which Falcon updates are installed, so that updates are not installed all at once leading to network congestion
- D To allow the controlled assignment of sensor versions onto specific hosts** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The purpose of using groups with Sensor Update policies in CrowdStrike Falcon is to allow the controlled assignment of sensor versions onto specific hosts. This ensures that updates can be managed and deployed in a systematic and controlled manner, reducing the risk of untested updates being installed across the entire network simultaneously, which could potentially cause issues or disruptions.

What impact does disabling detections on a host have on an API?

- ☐ A Endpoints with detections disabled will not alert on anything until detections are enabled again
- ☐ B Endpoints cannot have their detections disabled individually
- ☒ C DetectionSummaryEvent stops sending to the Streaming API for that host ✓ CORRECT
- ☐ D Endpoints with detections disabled will not alert on anything for 24 hours (by default) or longer if that setting is changed

SUGGESTED ANSWER

The suggested answer is C.

Disabling detections on a host means that the DetectionSummaryEvent stops sending to the Streaming API for that host. This directly impacts the API's functionality related to detection events, as these events will no longer be communicated while detections are disabled.

Under which scenario can Sensor Tags be assigned?

- A While triaging a detection
- B While managing hosts in the Falcon console
- C While updating a sensor in the Falcon console
- D While installing a sensor**

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Sensor Tags can be assigned while installing a sensor. This is because the configuration of these tags typically occurs during the installation process, where specific parameters, such as sensor grouping tags, are set and applied. Adjustments to Sensor Tags after installation typically require registry key updates and a system reboot or sensor upgrade.

Custom IOA rules are defined using which syntax?

A Glob

B PowerShell

C Yara

D Regex

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Custom IOA (Indicator of Attack) rules are defined using Regex syntax. Regex, or regular expressions, are a sequence of characters that define a search pattern, which is commonly used for string matching within texts. This allows for specific and complex pattern matching necessary for defining security rules and detections accurately.

With Custom Alerts, it is possible to _____.

A schedule the alert to run at any interval

B receive an alert in an email

✓ CORRECT

C configure prevention actions for alerting

D be alerted to activity in real-time

SUGGESTED ANSWER

The suggested answer is B.

With Custom Alerts, it is possible to receive an alert in an email. Custom alerts are typically used to notify users about specific activities or changes, and these notifications are often delivered via email. Scheduling alerts to run at a specific interval usually refers to scheduled reports, not custom alerts, and configuring prevention actions or real-time alerting typically falls under different functionalities or systems.

How do you assign a Prevention policy to one or more hosts?

- A Create a new policy and assign it directly to those hosts on the Host Management page
- B Modify the users roles on the User Management page
- C Ensure the hosts are in a group and assign that group to a custom Prevention policy
- D Create a new policy and assign it directly to those hosts on the Prevention policy page** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To assign a Prevention policy to one or more hosts, you must create a new policy and assign it directly to those hosts on the Prevention policy page. This ensures precise control over which hosts receive the specific policy without needing to group them first.

You have been provided with a list of 100 hashes that are not malicious but your company has deemed to be inappropriate for work computers. They have asked you to ensure that they are not allowed to run in your environment. You have chosen to use Falcon to do this. Which is the best way to accomplish this?

- A Using the Support Portal, create a support ticket and include the list of binary hashes, asking support to create an "Execution Prevention" rule to prevent these processes from running
- B Using Custom Alerts in the Investigate App, create a new alert using the template "Process Execution" and within that rule, select the option to "Block Execution"
- C Using IOC Management, gather the list of SHA256 or MD5 hashes for each binary and then upload them. Set all hashes to "Block" and ensure that the prevention policy these computers are using includes the option for "Custom Blocking" under Execution Blocking.** ✓ CORRECT
- D Using the API, gather the list of SHA256 or MD5 hashes for each binary and then upload them, setting them all to "Never Allow"

SUGGESTED ANSWER

The suggested answer is C.

To ensure that the inappropriate hashes are not allowed to run in your environment using Falcon, you should utilize IOC Management. By gathering the list of SHA256 or MD5 hashes for each binary and uploading them, you can set these hashes to 'Block'. This method also requires that the prevention policy applied to the computers includes the 'Custom Blocking' option under Execution Blocking. This approach leverages Falcon's capabilities to block specific binaries based on their hashes effectively and manage the environment according to the company's requirements.

Which exclusion pattern will prevent detections on a file at C:\Program Files\My Program\My Files\program.exe?

A \Program Files\My Program\My Files*

✓ CORRECT

B \Program Files\My Program*

C *.*

D *.*\Program Files\My Program*\

SUGGESTED ANSWER

The suggested answer is A.

The exclusion pattern that will prevent detections on a file at C:\Program Files\My Program\My Files\program.exe is \\Program Files\\My Program\\My Files*. This pattern specifically targets all files in the My Files directory within My Program folder in Program Files.

When a host is placed in Network Containment, which of the following is **TRUE**?

- ☐ A The host machine is unable to send or receive network traffic outside of the local network
- ☐ B The host machine is unable to send or receive network traffic except to/from the Falcon Cloud and traffic allowed in the Firewall Policy
- ☐ C The host machine is unable to send or receive any network traffic
- ☒ D The host machine is unable to send or receive network traffic except to/from the Falcon Cloud and any resources allowlisted in the Containment Policy ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

When a host is placed in Network Containment, it is unable to send or receive network traffic except to/from the Falcon Cloud and any resources allowlisted in the Containment Policy. This ensures necessary communications for security management while isolating the machine from other network interactions.

When would the No Action option be assigned to a hash in IOC Management?

- A** When you want to save the indicator for later action, but do not want to block or allow it at this time ✓ CORRECT
- B Add the indicator to your allowlist and do not detect it
- C There is no such option as No Action available in the Falcon console
- D Add the indicator to your blocklist and show it as a detection

SUGGESTED ANSWER

The suggested answer is A.

The No Action option would be assigned to a hash in IOC Management when you want to save the indicator for later action but do not want to block or allow it at this time. This allows for flexibility in deciding the appropriate action at a later point without enforcing any current restrictions or permissions.

Why is it important to know your company's event data retention limits in the Falcon platform?

- ☐ A This is not necessary; you simply select "All Time" in your query to search all data
- ☒ B You will not be able to search event data into the past beyond your retention period ✓ CORRECT
- ☐ C Data such as process records are kept for a shorter time than event data
- ☐ D Your query will require you to specify the data pool associated with the date you wish to search

SUGGESTED ANSWER

The suggested answer is B.

Knowing your company's event data retention limits in the Falcon platform is important because you will not be able to search event data into the past beyond your retention period. This limitation means that once the data retention period is exceeded, the event data is no longer available for queries, making it crucial to understand and manage these limits effectively.

What is the purpose of precedence with respect to the Sensor Update policy?

- A Precedence applies to the Prevention policy and not to the Sensor Update policy
- B Hosts assigned to multiple policies will assume the highest ranked policy in the list (policy with the lowest number) ✓ CORRECT**
- C Hosts assigned to multiple policies will assume the lowest ranked policy in the list (policy with the highest number)
- D Precedence ensures that conflicting policy settings are not set in the same policy

SUGGESTED ANSWER

The suggested answer is B.

Hosts assigned to multiple policies will assume the highest ranked policy in the list (policy with the lowest number). The concept of precedence dictates that when a host is subject to multiple policies, the one with the highest precedence (numerically lowest number) takes effect.

When uninstalling a sensor, which of the following is required if the 'Uninstall and maintenance protection' setting is enabled within the Sensor Update Policies?

A Maintenance token

✓ CORRECT

B Customer ID (CID)

C Bulk update key

D Agent ID (AID)

SUGGESTED ANSWER

The suggested answer is A.

When the 'Uninstall and maintenance protection' setting is enabled within the Sensor Update Policies, a maintenance token is required to uninstall the sensor. This token ensures that only authorized individuals can perform the uninstallation, providing an additional layer of security.

How can a Falcon Administrator configure a pop-up message to be displayed on a host when the Falcon sensor blocks, kills or quarantines an activity?

- A By ensuring each user has set the "pop-ups allowed" in their User Profile configuration page
- B By enabling "Upload quarantined files" in the General Settings configuration page
- C By turning on the "Notify End Users" setting at the top of the Prevention policy details configuration page** ✓ CORRECT
- D By selecting "Enable pop-up messages" from the User configuration page

SUGGESTED ANSWER

The suggested answer is C.

The correct way to configure a pop-up message to be displayed on a host when the Falcon sensor blocks, kills, or quarantines an activity is by turning on the 'Notify End Users' setting at the top of the Prevention policy details configuration page. This setting directly addresses the need to inform end-users about actions taken by the Falcon sensor.

Where in the Falcon console can information about supported operating system versions be found?

A Configuration module

B Intelligence module

C Support module

✓ CORRECT

D Discover module

SUGGESTED ANSWER

The suggested answer is C.

The information about supported operating system versions can typically be found in the Support module of most software consoles, including the Falcon console. This module is generally where users can find documentation, technical support, and specifics about the software, including what operating systems are supported.

What is the name for the unique host identifier in Falcon assigned to each sensor during sensor installation?

A Endpoint ID (EID)

B Agent ID (AID)

✓ CORRECT

C Security ID (SID)

D Computer ID (CID)

SUGGESTED ANSWER

The suggested answer is B.

The unique host identifier in Falcon assigned to each sensor during sensor installation is known as the Agent ID (AID). This identifier is automatically generated and linked to each installed sensor, serving as a unique identifier for the host in the system.

Which of the following is a valid step when troubleshooting sensor installation failure?

A Confirm all required services are running on the system

✓ CORRECT

B Enable the Windows firewall

C Disable SSL and TLS on the host

D Delete any available application crash log files

SUGGESTED ANSWER

The suggested answer is A.

Confirming that all required services are running on the system is a valid step when troubleshooting sensor installation failure. Ensuring that necessary services are operational can help diagnose issues related to sensor installation, as these services might be crucial for the proper functioning and communication of the sensor software. The other options, such as enabling the Windows firewall, disabling SSL and TLS, or deleting application crash log files, are not typically relevant or recommended actions in this context.

You need to export a list of all detections for a specific Host Name in the last 24 hours. What is the best way to do this?

- A Go to Host Management in the Host page. Select the host and use the Export Detections button
- B Utilize the Detection Resolution Dashboard. Use the filters to focus on the appropriate hostname and time, then export the results from the "Detection Resolution History" section
- C In the Investigate module, access the Detection Activity page. Use the filters to focus on the appropriate hostname and time, then export the results** ✓ CORRECT
- D Utilize the Detection Activity Dashboard. Use the filters to focus on the appropriate hostname and time, then export the results from the "Detections by Host" section

SUGGESTED ANSWER

The suggested answer is C.

The best way to export a list of all detections for a specific Host Name in the last 24 hours is by using the filters in the Investigate module on the Detection Activity page. Once you have filtered the results to focus on the appropriate hostname and time, you can then export the relevant detections.

Which role will allow someone to manage quarantine files?

A Falcon Security Lead

✓ CORRECT

B Detections Exceptions Manager

C Falcon Analyst – Read Only

D Endpoint Manager

SUGGESTED ANSWER

The suggested answer is A.

The Falcon Security Lead is the role that typically has the necessary permissions to manage quarantine files. This role generally includes comprehensive access to security functions and the ability to interact with quarantined items.

What is the maximum number of patterns that can be added when creating a new exclusion?

A.10

B 0

C 1

✓ CORRECT

D 5

SUGGESTED ANSWER

The suggested answer is C.

The maximum number of patterns that can be added when creating a new exclusion is 1. Exclusions typically allow only a single pattern per rule to maintain system efficiency and clarity.

You are evaluating the **most** appropriate Prevention Policy Machine Learning slider settings for your environment. In your testing phase, you configure the Detection slider as **Aggressive**. After running the sensor with this configuration for 1 week of testing, which Audit report should you review to determine the best Machine Learning slider settings for your organization?

- A Prevention Policy Audit Trail
- B Prevention Policy Debug
- C Prevention Hashes Ignored
- D Machine-Learning Prevention Monitoring**

✓ CORRECT**SUGGESTED ANSWER**

The suggested answer is D.

To determine the best Machine Learning slider settings for your organization after configuring the Detection slider as Aggressive and testing for a week, you should review the Machine-Learning Prevention Monitoring report. This dashboard allows you to view malware that would have been blocked over the selected timeframe based on different Machine Learning Prevention settings (Cautious, Moderate, Aggressive, or Extra Aggressive). It provides insights into ML expected detections and helps in deciding the optimal settings for your environment.

In order to exercise manual control over the sensor upgrade process, as well as prevent unauthorized users from uninstalling or upgrading the sensor, which settings in the Sensor Update Policy would meet this criteria?

- A Sensor version set to N-1 and Bulk maintenance mode is turned on
- B Sensor version fixed and Uninstall and maintenance protection turned on** ✓ CORRECT
- C Sensor version updates off and Uninstall and maintenance protection turned off
- D Sensor version set to N-2 and Bulk maintenance mode is turned on

SUGGESTED ANSWER

The suggested answer is B.

To exercise manual control over the sensor upgrade process and prevent unauthorized users from uninstalling or upgrading the sensor, it is essential to fix the sensor version and enable uninstall and maintenance protection. Fixing the sensor version ensures that updates are not performed automatically, allowing for manual control over the process. Enabling uninstall and maintenance protection prevents unauthorized users from tampering with the sensor. Therefore, the settings 'Sensor version fixed' and 'Uninstall and maintenance protection turned on' meet these criteria.

Once an exclusion is saved, what can be edited in the future?

- ☒ A All parts of the exclusion can be changed ✓ CORRECT
- ☐ B Only the selected groups and hosts to which the exclusion is applied can be changed
- ☐ C Only the options to "Detect/Block" and/or "File Extraction" can be changed
- ☐ D The exclusion pattern cannot be changed

SUGGESTED ANSWER

The suggested answer is A.

Once an exclusion is saved, all parts of the exclusion can be changed. This means any aspect of the exclusion can be edited later as needed.

Which of the following options is a feature found **ONLY** with the Sensor-based Machine Learning (ML)?

- A Next-Gen Antivirus (NGAV) protection
- B Adware and Potentially Unwanted Program detection and prevention
- C Real-time offline protection** ✓ CORRECT
- D Identification and analysis of unknown executables

SUGGESTED ANSWER

The suggested answer is C.

Real-time offline protection is a feature found only with sensor-based machine learning. While other features can also be achieved through various methods, real-time offline protection specifically relies on the local sensor's capability to work without an active internet connection, which is unique to sensor-based ML systems.

How do you find a list of inactive sensors?

- ☐ A The Falcon platform does not provide reporting for inactive sensors
- ☐ B A sensor is always considered active until removed by an Administrator
- ☒ C Run the Inactive Sensor Report in the Host setup and management option ✓ CORRECT
- ☐ D Run the Sensor Aging Report within the Investigate option

SUGGESTED ANSWER

The suggested answer is C.

To find a list of inactive sensors, run the Inactive Sensor Report in the Host setup and management option. This report is specifically designed to identify sensors that are no longer active.

Which report can assist in determining the appropriate Machine Learning levels to set in a Prevention Policy?

- A Sensor Report
- B Machine Learning Prevention Monitoring**

✓ CORRECT

C Falcon UI Audit Trail

D Machine Learning Debug

SUGGESTED ANSWER

The suggested answer is B.

The right report for determining the appropriate Machine Learning levels to set in a Prevention Policy is the Machine Learning Prevention Monitoring report. This report typically includes data and metrics on how different Machine Learning models perform under various scenarios and settings, allowing administrators to fine-tune the prevention policy settings for optimal performance.

Why is the ability to disable detections helpful?

A It gives users the ability to set up hosts to test detections and later remove them from the console

✓ CORRECT

B It gives users the ability to uninstall the sensor from a host

C It gives users the ability to allowlist a false positive detection

D It gives users the ability to remove all data from hosts that have been uninstalled

SUGGESTED ANSWER

The suggested answer is A.

The ability to disable detections is helpful because it gives users the ability to set up hosts to test detections and later remove those test detections from the console. This functionality is particularly useful in testing environments where users need to validate their detection rules and then clean up after those tests without leaving unnecessary data behind.

The Logon Activities Report includes all of the following information for a particular user EXCEPT _____.

- A the account type for the user (e.g. Domain Administrator, Local User)
- B all hosts the user logged into
- C the logon type (e.g. interactive, service)
- D the last time the user's password was set**

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The Logon Activities Report typically includes information such as the account type for the user, all hosts the user logged into, and the logon type. This is crucial for tracking and auditing user activities related to logon sessions. However, the last time the user's password was set is not directly related to logon activities and is more likely found in account settings reports or user profile details, rather than a logon activity report.

An analyst has reported they are not receiving workflow triggered notifications in the past few days. Where should you first check for potential failures?

A Custom Alert History

B Workflow Execution log

C Workflow Audit log

✓ CORRECT

D Falcon UI Audit Trail

SUGGESTED ANSWER

The suggested answer is C.

When addressing issues related to workflow notifications, it is crucial to review the Workflow Audit log. This log provides detailed information on the history and actions within the workflow, allowing you to identify any failures or reasons why notifications are not being triggered.

You have an existing workflow that is triggered on a critical detection that sends an email to the escalation team. Your CISO has asked to also be notified via email with a customized message. What is the best way to update the workflow?

A Clone the workflow and replace the existing email with your CISO's email

B Add a sequential action to send a custom email to your CISO

C Add a parallel action to send a custom email to your CISO

✓ CORRECT

D Add the CISO's email to the existing action

SUGGESTED ANSWER

The suggested answer is C.

To ensure that the CISO receives the email with a customized message regardless of the status of the existing action and without disrupting the original workflow's sequence, adding a parallel action is the most efficient approach. This way, both the escalation team and the CISO will receive their respective emails simultaneously, ensuring prompt notification.

Which of the following is **NOT** an available filter on the Hosts Management page?

A Hostname

B Username

✓ CORRECT

C Group

D OS Version

SUGGESTED ANSWER

The suggested answer is B.

Username is not an available filter on the Hosts Management page. Typically, filters on such pages include hostname, group, and OS version, and not individual user details.

What is the primary purpose of using glob syntax in an exclusion?

- A To specify a Domain be excluded from detections
- B To specify exclusion patterns to easily exclude files and folders and extensions from detections** ✓ CORRECT
- C To specify exclusion patterns to easily add files and folders and extensions to be prevented
- D To specify a network share be excluded from detections

SUGGESTED ANSWER

The suggested answer is B.

Glob syntax is primarily used for specifying exclusion patterns to easily exclude files, folders, and extensions from detections. This allows for pattern matching to include or exclude specific items based on their names and extensions efficiently.

How are user permissions set in Falcon?

- A Permissions are assigned to a User Group and then users are assigned to that group, thereby inheriting those permissions
- B Pre-defined permissions are assigned to sets called roles. Users can be assigned multiple roles based on job function and they assume a cumulative set of permissions based on those assignments** ✓ CORRECT
- C An administrator selects individual granular permissions from the Falcon Permissions List during user creation
- D Permissions are token-based. Users request access to a defined set of permissions and an administrator adds their token to the set of permissions

SUGGESTED ANSWER

The suggested answer is B.

User permissions in Falcon are set by assigning pre-defined permissions to sets called roles. Users can then be assigned multiple roles based on their job function, and they assume a cumulative set of permissions based on those role assignments.

Which of the following is **NOT** a way to determine the sensor version installed on a specific endpoint?

- A Use the Sensor Report to filter to the specific endpoint
- B Use Host Management to select the desired endpoint. The agent version will be listed in the columns and details
- C From a command line, run the `sc query csagent -version` command
- D Use the Investigate > Host Search to filter to the specific endpoint** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To determine the sensor version installed on a specific endpoint: (A) Using the Sensor Report to filter to the specific endpoint, (B) Using Host Management to select the desired endpoint where the agent version is listed in the columns and details, and (C) From a command line, running the `sc query csagent -version` command, are all methods that can provide information about the sensor version. Using the Investigate > Host Search to filter to the specific endpoint (D) is not a method for determining the sensor version, but rather for locating and investigating specific host information.

Which is the correct order for manually installing a Falcon Package on a macOS system?

A Install the Falcon package, then register the Falcon Sensor via the registration package

B Install the Falcon package, then register the Falcon Sensor via command line

✓ CORRECT

C Register the Falcon Sensor via command line, then install the Falcon package

D Register the Falcon Sensor via the registration package, then install the Falcon package

SUGGESTED ANSWER

The suggested answer is B.

To manually install a Falcon Package on a macOS system, the correct order is to first install the Falcon package and then register the Falcon Sensor via command line. This sequence ensures that the necessary software is in place before registration, allowing the system to properly recognize and register the Falcon Sensor.

You are beginning the rollout of the Falcon Sensor for the first time side-by-side with your existing security solution. You need to configure the Machine Learning levels of the Prevention Policy so it does not interfere with existing solutions during the testing phase. What settings do you choose?

- A
- Detection slider: Extra Aggressive
 - Prevention slider: Cautious

- B
- Detection slider: Moderate
 - Prevention slider: Disabled

✓ CORRECT

- C
- Detection slider: Cautious
 - Prevention slider: Cautious

- D
- Detection slider: Disabled
 - Prevention slider: Disabled

SUGGESTED ANSWER

The suggested answer is B.

To ensure that the Falcon Sensor does not interfere with the existing security solution during the testing phase, it is important to disable prevention. This way, new detections will be reported without taking any preventive action that could conflict with the current solution. Hence, the prevention slider should be set to Disabled. Additionally, setting the detection slider to Moderate ensures that relevant detections are still noted without being overly aggressive, which is suitable for a testing phase where you want to observe the behavior and stability of the new solution without causing disruptions.

How does the Unique Hosts Connecting to Countries Map help an administrator?

- A It highlights countries with known malware
- B It helps visualize global network communication**
- C It identifies connections containing threats
- D It displays intrusions from foreign countries

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is B.

The Unique Hosts Connecting to Countries Map helps an administrator visualize global network communication. This type of map usually displays the geographical locations of connections to the network, giving the administrator an overview of where connections are coming from worldwide. This is useful for monitoring and analyzing network traffic and ensuring secure communication channels.

On a Windows host, what is the **best** command to determine if the sensor is currently running?

A `sc query csagent`

✓ CORRECT

B `netstat -a`

C This cannot be accomplished with a command

D `ping falcon.crowdstrike.com`

SUGGESTED ANSWER

The suggested answer is A.

To determine if a sensor is running on a Windows host, the most appropriate command is 'sc query csagent'. This command queries the service control manager for the status of the 'csagent' service, which is typically the service name for the sensor. This will provide detailed information on whether the service is running, stopped, or in another state. The other options such as 'netstat -a', 'This cannot be accomplished with a command', and 'ping falcon.crowdstrike.com' do not directly verify the status of a specific service in the system.

The Falcon sensor uses certificate pinning to defend against man-in-the-middle attacks. Which statement is **TRUE** concerning Falcon sensor certificate validation?

- A SSL inspection should be configured to occur on all Falcon traffic
- B Some network configurations, such as deep packet inspection, interfere with certificate validation** ✓ CORRECT
- C HTTPS interception should be enabled to proceed with certificate validation
- D Common sources of interference with certificate pinning include protocol race conditions and resource contention

SUGGESTED ANSWER

The suggested answer is B.

Deep packet inspection and other network configurations can interfere with certificate validation because they intercept and analyze the content of data packets, which can disrupt the certificate pinning process essential for verifying the authenticity of the communication. Certificate pinning is designed to ensure that the client is communicating with a legitimate server, and any interception can break this validation.

Which is a filter within the Host setup and management > Host management page?

A User name

B OU

✓ CORRECT

C BIOS Version

D Locality

SUGGESTED ANSWER

The suggested answer is B.

Within the Host setup and management > Host management page, OU (Organizational Unit) is a relevant filter. It allows the administrator to manage hosts based on their organizational structure.

When creating a Host Group for all Workstations in an environment, what is the **BEST** method to ensure all workstation hosts are added to the group?

A Create a Dynamic Group with Type=Workstation Assignment

✓ CORRECT

B Create a Dynamic Group and Import All Workstations

C Create a Static Group and Import all Workstations

D Create a Static Group with Type=Workstation Assignment

SUGGESTED ANSWER

The suggested answer is A.

The best method to ensure all workstation hosts are added to a Host Group for workstations in an environment is to create a dynamic group with the Type filter set to Workstation Assignment. This approach automatically updates the group by including any new workstation hosts that meet the specified criteria, ensuring comprehensive and up-to-date coverage of all workstations.

When the Notify End Users policy setting is turned on, which of the following is **TRUE**?

- ☐ A End users will not be notified as we would not want to notify a malicious actor of a detection. This setting does not exist
- ☐ B End users will be immediately notified via a pop-up that their machine is in-network isolation
- ☒ C End-users receive a pop-up notification when a prevention action occurs ✓ CORRECT
- ☐ D End users will receive a pop-up allowing them to confirm or refuse a pending quarantine

SUGGESTED ANSWER

The suggested answer is C.

When the Notify End Users policy setting is turned on, end-users receive a pop-up notification when a prevention action occurs. This ensures that users are aware of any protective measures being executed on their system.

If a user wanted to install an older version of the Falcon sensor, how would they find the older installer file?

- A Older versions of the sensor are not available for download
- B By emailing CrowdStrike support at support@crowdstrike.com
- C By installing the current sensor and clicking the "downgrade" button during the install

D By clicking on "Older versions" links under the Host setup and management > Deploy > Sensor downloads

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To find an older version of the Falcon sensor, users should click on the 'Older versions' links under the Host setup and management > Deploy > Sensor downloads section. This is where CrowdStrike provides the option to download supported previous versions of the sensor.

Which of the following best describes the Default Sensor Update policy?

- ☐ A The Default Sensor Update policy does not have the "Uninstall and maintenance protection" feature
- ☐ B The Default Sensor Update policy is only used for testing sensor updates
- ☒ C The Default Sensor Update policy is a "catch-all" policy ✓ CORRECT
- ☐ D The Default Sensor Update policy is disabled by default

SUGGESTED ANSWER

The suggested answer is C.

The Default Sensor Update policy is a 'catch-all' policy. This means it is a comprehensive policy designed to ensure that all necessary updates are applied across various systems or sensors without the need for individualized policies.

Under the "Next-Gen Antivirus: Cloud Machine Learning" setting there are two categories, one of them is "Cloud Anti-Malware" and the other is:

A Adware & PUP

✓ CORRECT

B Advanced Machine Learning

C Sensor Anti-Malware

D Execution Blocking

SUGGESTED ANSWER

The suggested answer is A.

Under the 'Next-Gen Antivirus: Cloud Machine Learning' setting, 'Adware & PUP' is the correct category alongside 'Cloud Anti-Malware'. This is verified through the dashboard and documentation, where these specific categories are listed prominently.

You have created a Sensor Update Policy for the Mac platform. Which other operating system(s) will this policy manage?

A *nix

B Windows

C Both Windows and *nix

D Only Mac

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

A Sensor Update Policy created specifically for the Mac platform will only manage Mac systems. Each policy is typically designed to target a specific operating system and will not manage other operating systems such as Windows or *nix.

Which of the following Machine Learning (ML) sliders will only detect or prevent high confidence malicious items?

A Aggressive

B Cautious

✓ CORRECT

C Minimal

D Moderate

SUGGESTED ANSWER

The suggested answer is B.

The 'Cautious' setting for Machine Learning (ML) sliders is designed to detect or prevent only when there is high confidence that an item is malicious. This minimizes false positives by ensuring that only items identified with a high degree of certainty are acted upon.

What type of information is found in the Linux Sensors Dashboard?

- ☒ A Hosts by Kernel Version, Shells spawned by Root, Wget/Curl Usage ✓ CORRECT
- ☐ B Hidden File execution, Execution of file from the trash, Versions Running with Computer Names
- ☐ C Versions running, Directory Made Invisible to Spotlight, Logging/Auditing Referenced, Viewed, or Modified
- ☐ D Private Information Accessed, Archiving Tools – Exfil, Files Made Executable

SUGGESTED ANSWER

The suggested answer is A.

The Linux Sensors Dashboard typically includes information on active hosts and their kernel versions, instances of shells spawned by the root user, and the usage of commands like Wget and Curl. These metrics are crucial for monitoring system activity and detecting potential security threats.

Why would you assign hosts to a static group instead of a dynamic group?

A You do not want the group membership to change automatically

✓ CORRECT

B You are managing more than 1000 hosts

C You need hosts to be automatically assigned to a group

D You want the group to contain hosts from multiple operating systems

SUGGESTED ANSWER

The suggested answer is A.

Assigning hosts to a static group means that you do not want the group membership to change automatically. Static groups are manually managed, and the membership remains constant unless altered by the user. This is in contrast to dynamic groups, where hosts are automatically added or removed based on predefined criteria.

What can exclusions be applied to?

A Individual hosts selected by the administrator

B Either all hosts or specified groups

✓ CORRECT

C Only the default host group

D Only the groups selected by the administrator

SUGGESTED ANSWER

The suggested answer is B.

Exclusions can be applied either to all hosts or to specified groups. This means that administrators have the flexibility to either exclude every single host in the network or to target exclusions to specific groups of hosts based on the requirements.

You have a Windows host on your network in Reduced functionality mode (RFM). While the system is in RFM, which of the following is **TRUE**?

- A System monitoring will be unavailable
- B Event reporting will be unavailable
- C Prevention patterns will not be triggered
- D Some detection patterns and preventions will not be triggered**

✓ CORRECT**SUGGESTED ANSWER**

The suggested answer is D.

When a Windows host is in Reduced Functionality Mode (RFM), some detection patterns and preventions will not be triggered. This is a designed behavior to ensure minimal functionality and to prompt resolution of the underlying issue causing RFM without completely compromising the security posture.

A sensor that has not contacted the Falcon cloud will be automatically deleted from the hosts list after how many days?

A 45 Days

✓ CORRECT

B 60 Days

C 30 Days

D 90 Days

SUGGESTED ANSWER

The suggested answer is A.

A sensor that has not contacted the Falcon cloud will be automatically deleted from the hosts list after 45 days.

When a host belongs to more than one host group, how is sensor update precedence determined?

- A Groups have no impact on sensor update policies
- B Sensors of hosts that belong to more than one group must be manually updated
- C The highest precedence policy from the most important group is applied to the host
- D All of the host's groups are examined in aggregate and the policy with highest precedence is applied to the host** ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

When a host belongs to more than one host group, the policies from all groups are evaluated, and the policy with the highest precedence is applied to the host. This ensures that the most critical and specific update requirements take priority, maintaining consistency and effectiveness in sensor updates.

What may prevent a user from logging into Falcon via single sign-on (SSO)?

A The SSO username doesn't match their email address in Falcon

✓ CORRECT

B The maintenance token has expired

C Falcon is in reduced functionality mode

D The user never configured their security questions

SUGGESTED ANSWER

The suggested answer is A.

The Single Sign-On (SSO) process typically relies on the username or email address to authenticate the user. If the SSO username does not match the email address registered in Falcon, the user will be unable to log in. This discrepancy prevents the user from being properly identified and authenticated by the system.

The Customer ID (CID) is important in which of the following scenarios?

A When adding a user to the Falcon console under the Users application

B When performing the sensor installation process

✓ CORRECT

C When setting up API keys

D When performing a Host Search

SUGGESTED ANSWER

The suggested answer is B.

The Customer ID (CID) is crucial during the sensor installation process. It uniquely identifies the customer's instance and ensures that the installed sensor communicates with the correct Falcon instance. This is an essential step to properly enroll and configure a new endpoint in the security platform.

Which statement describes what is recommended for the Default Sensor Update policy?

- A** The Default Sensor Update policy should align to an organization's overall sensor updating practice while leveraging Auto N-1 and Auto N-2 configurations where possible ✓ CORRECT
- B** The Default Sensor Update should be configured to always automatically upgrade to the latest sensor version
- C** Since the Default Sensor Update policy is pre-configured with recommend settings out of the box, configuration of the Default Sensor Update policy is not required
- D** No configuration is required. Once a Custom Sensor Update policy is created the Default Sensor Update policy is disabled

SUGGESTED ANSWER

The suggested answer is A.

The Default Sensor Update policy should align to an organization's overall sensor updating practice while leveraging Auto N-1 and Auto N-2 configurations where possible. This ensures that the sensor updates are in line with the organization's policies and practices, providing a balance between keeping the software up-to-date and maintaining stability.

You need to have the ability to monitor suspicious VBA macros. Which Sensor Visibility setting should be turned on within the Prevention policy settings?

A Script-based Execution Monitoring

✓ CORRECT

B Interpreter-Only

C Additional User Mode Data

D Engine (Full Visibility)

SUGGESTED ANSWER

The suggested answer is A.

To monitor suspicious VBA macros, the correct Sensor Visibility setting to enable is Script-based Execution Monitoring. This setting allows the monitoring of scripts and macros, including VBA macros, which are often used to execute malicious code.

What is the purpose of the Machine-Learning Prevention Monitoring Report?

- ☐ A It is designed to give an administrator a quick overview of machine-learning aggressiveness settings as well as the numbers of items actually quarantined
- ☐ B It is the dashboard used by an analyst to view all items quarantined and to release any items deemed non-malicious
- ☐ C It is the dashboard used to see machine-learning preventions, and it is used to identify spikes in activity and possible targeted attacks
- ☒ D It is designed to show malware that would have been blocked in your environment based on different Machine-Learning Prevention settings

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The purpose of the Machine-Learning Prevention Monitoring Report is to show malware that would have been blocked in your environment based on different Machine-Learning Prevention settings. This report helps in analyzing the effectiveness of various prevention settings like Cautious, Moderate, Aggressive, or Extra Aggressive by viewing what potential threats could have been prevented over a selected timeframe.

The Remote Access Graph in Visibility Reports displays:

A a bar chart where a bar represents a daily count of remote connections

✓ CORRECT

B a geographical chart showing the geo-location of remote IP address

C a graph showing connections between hosts and users

D a pie chart showing a count per remote logon type

SUGGESTED ANSWER

The suggested answer is A.

The Remote Access Graph in Visibility Reports displays a bar chart where a bar represents a daily count of remote connections. This type of graph is instrumental in providing a clear visual representation of the frequency of remote access events over time, which is critical for monitoring and analyzing remote access activity.

What internet domain needs to be added to any required allowlists to allow sensors to communicate with the CrowdStrike Cloud?

A falconcloud.net

✓ CORRECT

B cloudprotect-cs.net

C cloudsink.net

D csfalcon.net

SUGGESTED ANSWER

The suggested answer is A.

The correct internet domain that needs to be added to any required allowlists to allow sensors to communicate with the CrowdStrike Cloud is falconcloud.net. CrowdStrike uses this domain for communication between sensors and their cloud infrastructure.

Why would you use the Prevention Policy Debug Report?

- ☐ A To confirm that prevention policy precedence was applied to hosts
- ☐ B To confirm the number of detections on a host
- ☒ C To confirm that prevention policy settings were applied to a host ✓ CORRECT
- ☐ D To confirm the number of host groups to which a policy was applied

SUGGESTED ANSWER

The suggested answer is C.

The Prevention Policy Debug Report is used to confirm that prevention policy settings were applied to a host. This report helps to ensure that the intended security settings are correctly implemented and active on the host, which is crucial for maintaining the desired level of protection.

What is the earliest version of Windows Server that a Sensor is compatible with?

A Server 2012

B Server 2003

C Server 2008 R2 SP1

✓ CORRECT

D Server 2008

SUGGESTED ANSWER

The suggested answer is C.

The earliest version of Windows Server that a Sensor is compatible with is Server 2008 R2 SP1.

Which command would tell you if a Falcon Sensor was running on a Windows host?

A netstat.exe -f

B cswinddiag.exe -status

C sc.exe query falcon

D sc.exe query csagent

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

After Network Containing a host, your Incident Response team states they are unable to remotely connect to the host. Which of the following would need to be configured to allow remote connections from specified IP's?

A Response Policy

B IP Allowlist Management

✓ CORRECT

C Maintenance Token

D Containment Policy

SUGGESTED ANSWER

The suggested answer is B.

To allow remote connections from specified IP addresses, IP Allowlist Management needs to be configured. This mechanism ensures that only the IP addresses on the allowlist are permitted to connect remotely to the host, thereby enhancing security by restricting access to authorized IPs.

On which page of the Falcon console can one locate the Customer ID (CID)?

A API Clients and Keys

B Sensor Dashboard

C Hosts Management

D Sensor Downloads

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The Customer ID (CID) can be located on the Sensor Downloads page. This page provides the necessary details and identifiers required for downloading and configuring sensors, including the Customer ID which is a unique identifier assigned to the customer.

The Falcon sensor uses certificate pinning to defend against man-in-the-middle attacks. What must you ensure is disabled for the sensor to communicate with the CrowdStrike Cloud?

A Proxy information

B Deep packet inspection

✓ CORRECT

C NMAP scanning

D TCP inspection

SUGGESTED ANSWER

The suggested answer is B.

The Falcon sensor uses certificate pinning to secure communication channels by ensuring that only trusted certificates are accepted. Deep packet inspection (DPI) can intercept and examine data packets, potentially interfering with the secure communication. Therefore, disabling DPI is necessary to ensure the sensor can communicate effectively with the CrowdStrike Cloud without disrupting the certificate pinning process.

Which of the following tools developed by CrowdStrike is intended to help with removal of the CrowdStrike Windows Falcon Sensor?

A CSUninstallTool.exe

✓ CORRECT

B UninstallTool.exe

C CrowdStrikeRemovalTool.exe

D FalconUninstall.exe

SUGGESTED ANSWER

The suggested answer is A.

The tool developed by CrowdStrike for removing the CrowdStrike Windows Falcon Sensor is CSUninstallTool.exe. This tool is specifically mentioned in CrowdStrike documentation and is designed to assist users in the uninstallation process.

Assume the **Falcon Sensor** was installed on a Virtual Machine template using the installation parameter **NO_START=1**. Afterward, the Virtual Machine template is rebooted. What is the effect on the Falcon Sensor after reboot?

A The Falcon Sensor would start, but only send a heartbeat to the Falcon console

B The Falcon Sensor would not automatically start on reboot. It would have to be manually started

✓ CORRECT

C The Falcon Sensor would disable BIOS checks at startup

D The Falcon Sensor would start at reboot and generate an Agent ID

SUGGESTED ANSWER

The suggested answer is B.

The **NO_START=1** parameter is typically used to prevent the Falcon Sensor from starting automatically. This can be useful in situations where the sensor is installed on a Virtual Machine template, ensuring that it does not start and generate an Agent ID before the template is converted to individual VMs. Given that the parameter **NO_START=1** was used, after rebooting the Virtual Machine template, the Falcon Sensor would not automatically start. It would require manual intervention to start the Falcon Sensor. This prevents the creation of multiple VMs with the same Agent ID from the template.

What should be disabled on firewalls so that the sensor's man-in-the-middle attack protection works properly?

- A Windows Proxy
- B Deep packet inspection**

✓ CORRECT

C Linux Sub-System

D PowerShell

SUGGESTED ANSWER

The suggested answer is B.

Which option best describes the general process for a manual installation of the Falcon Sensor on MacOS?

- A Grant the Falcon package Full Disk Access, install the Falcon package, load the Falcon Sensor with the command 'falconctl stats'
- B Install the Falcon package passing it the installation token in the command line
- C Install the Falcon package, use falconctl to license the sensor, approve the system extension, grant the sensor Full Disk Access** ✓ CORRECT
- D Grant the Falcon package Full Disk Access, install the Falcon package, use falconctl to license the sensor

SUGGESTED ANSWER

The suggested answer is C.

The best general process for manually installing the Falcon Sensor on MacOS includes several key steps: installing the Falcon package, using `falconctl` to license the sensor, approving the system extension, and granting the sensor Full Disk Access. These steps ensure that the sensor is properly installed, authorized, and has the necessary permissions to function correctly on the MacOS system.

Where can you find your company's Customer ID (CID)?

- ☒ A The CID is located at Hosts setup and management > Deploy > Sensor Downloads and is listed along with the checksum ✓ CORRECT
- ☐ B The CID is located at Hosts > Host Management
- ☐ C The CID is only available by calling support
- ☐ D The CID is a secret key used for Falcon communication and is never shared with the customer

SUGGESTED ANSWER

The suggested answer is A.

Which of the following best describes what the Uninstall and Maintenance Protection setting controls within your Sensor Update Policy?

A Prevents the sensor from entering Reduced Functionality Mode

B Prevents unauthorized uninstallation of the sensor

✓ CORRECT

C Prevents automatic updates of the sensor

D Prevents modification of sensor update policy

SUGGESTED ANSWER

The suggested answer is B.

A Falcon Administrator is trying to use Real-Time Response to start a session with a host that has a sensor installed but they are unable to connect. What is the **MOST** likely cause?

- A The host has a user logged into it
- B The domain controller is preventing the connection
- C They do not have an RTR role assigned to them**
- D There is another analyst connected into it

✓ CORRECT**SUGGESTED ANSWER**

The suggested answer is C.

How can a API client secret be viewed after it has been created?

- A Selecting "show secret" within the 3-dot dropdown menu will reveal the secret for the selected api client
- B Within the API management page, API client secrets can be accessed within the "edit client" functionality
- C The API client secret must be reset or a new client created as the secret cannot be viewed after it has been created** ✓ CORRECT
- D The API client secret can be provided by support via direct email request from a Falcon Administrator

SUGGESTED ANSWER

The suggested answer is C.

Which of the following is **NOT** an available action for an API Client?

A Reset an API Client Secret

B Retrieve an API Client Secret

✓ CORRECT

C Edit an API Client

D Delete an API Client

SUGGESTED ANSWER

The suggested answer is B.

An API client secret is intended to be secure information that should not be retrievable for security reasons once it has been generated. While resetting, editing, or deleting an API client are valid actions to manage the API client, retrieving the secret directly is not a typically supported action due to potential security risks.

The Falcon Administrator has created a new prevention policy to apply to the **Servers** group; however, when applying the new prevention policy this group is not appearing in the list of available groups. What is the **most** likely issue?

A The "Servers" group already has a policy applied to it

✓ CORRECT

B The "Servers" group must be disabled first

C The new prevention policy should be enabled first

D Host type was not defined correctly within the prevention policy

SUGGESTED ANSWER

The suggested answer is A.

What critical prevention policy setting prevents sensor-related files, folders, and registry objects from being renamed or deleted?

A Sensor Modification Protection

B System Configuration Protection

C Sensor Tampering Protection

✓ CORRECT

D Host Modification Protection

SUGGESTED ANSWER

The suggested answer is C.

When editing an existing IOA exclusion, what can NOT be edited?

- A The exclusion name
- B All parts of the exclusion can be changed
- C The IOA name
- D The hosts groups

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

When editing an existing IOA exclusion, the IOA name cannot be changed. The exclusion name, the host groups, and other parts of the exclusion can be modified, but the IOA name remains fixed once set.

After enabling an IOA rule and its respective rule group, what else must be done for an IOA to be fully functional?

- A Nothing else needs to be done; the rule should start working
- B The rule group must be assigned to one or more prevention policies** ✓ CORRECT
- C The rule needs to be manually triggered to ensure it works as intended
- D You must individually select which hosts you would like to apply to rule to

SUGGESTED ANSWER

The suggested answer is B.

After enabling an IOA rule and its respective rule group, the rule group must be assigned to one or more prevention policies for the IOA to be fully functional. This ensures that the rule is applied within the scope of specific security policies that manage prevention measures across different hosts and environments.

Which of the following uses Regex to create a detection or take a preventative action?

A Machine Learning Exclusion

B Custom IOA

✓ CORRECT

C Custom IOC

D Sensor Visibility Exclusion

SUGGESTED ANSWER

The suggested answer is B.

Custom IOA (Indicator of Attack) is typically where regular expressions (Regex) are employed to create detections or take preventative actions. IOAs are behavioral indicators of an attack, and they often utilize pattern matching and advanced techniques like Regex to identify malicious activity.

When creating a custom IOA for a specific domain, which syntax would be best for detecting or preventing on all subdomains as well?

A *.baddomain\.xyz|baddomain\.xyz

✓ CORRECT

B **.baddomain\.xyz|baddomain\.xyz**

C *.baddomain\.xyz|baddomain\.xyz.*

D Custom IOA rules cannot be created for domains

SUGGESTED ANSWER

The suggested answer is A.

The best syntax for detecting or preventing a specific domain and all its subdomains in this context is '*.baddomain\.xyz|baddomain\.xyz'. This pattern utilizes a regular expression where '.*\.' matches any subdomain and 'baddomain\.xyz' matches the domain itself. It ensures that both the main domain and any subdomains are covered, which precisely fits the requirement of the question.

Which Real Time Response role will allow you to see all analyst session details?

A None of the Real Time Response roles allows this

B Real Time Response - Active Responder

C Real Time Response - Read-Only Analyst

D Real Time Response - Administrator

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

How do user permissions function in Falcon?

- ☐ A Custom user role permission sets are shared with all CrowdStrike customers globally
- ☐ B Each Falcon permission needs to be selected when the user account is created
- ☐ C User permissions grow more restrictive, the more roles assigned to a user the less capabilities they would potentially have
- ☒ D User permissions are cumulative, the more roles assigned to a user the more capabilities they would potentially have

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

If you are not able to update your Falcon sensors on a regular basis, what is the maximum recommended aging period before updating your sensors?

A 7 days

B 60 days

✓ CORRECT

C 90 days

D There is no maximum aging period

SUGGESTED ANSWER

The suggested answer is B.

The maximum recommended aging period before updating your Falcon sensors is 60 days. This period ensures that the sensors remain effective and updated with the latest features and security patches. Extending beyond this period can increase the risk of vulnerabilities and decrease the efficacy of the sensors.

What is the purpose of the "Auto - Latest" setting in a sensor update policy?

- ☐ A This setting overrides any user confirmation/interaction and applies the selected policy
- ☐ B This setting automatically assigns the latest Indicator of Attack (IOA) profiles and Next-Gen Antivirus (NGAV) machine learning to the selected endpoints ensuring the highest level of security
- ☐ C This setting automatically assigns new hosts that come online to this policy
- ☒ D This setting will cause all assigned hosts to be updated to the most current version as soon as it becomes available ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Which of the following steps are required to delete a sensor update policy?

- ☐ A Remove the policy from all assigned host groups, disable the policy, then click Delete from the policy's settings
- ☐ B From the policy's settings, disable all toggles first, then click Delete
- ☐ C Remove the policy from all assigned host groups, then click Delete from the policy's settings
- ☒ D From the policy's settings, disable the policy, then click Delete ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To delete a sensor update policy, the necessary steps are to first disable the policy and then proceed to delete it from the policy's settings. By disabling the policy, it ensures that the policy stops affecting any online hosts or any offline hosts that come back online. This makes option D the correct choice.

What best describes the relationship between Sensor Update policies and Operating Systems?

- A Sensor Update policies are not Operating System specific. One policy can be applied to all Operating Systems
- B A Sensor Update policy must be configured for each Operating System (Windows, Mac, Linux) ✓ CORRECT**
- C Windows and Mac share Sensor Update policies. Linux requires its own set of policies based on the different kernel versions
- D Windows has its own Sensor Update policies. But Mac and Linux share Sensor Update policies

SUGGESTED ANSWER

The suggested answer is B.

A Sensor Update policy must be configured for each Operating System (Windows, Mac, Linux). This means that policies are not universal and require specific configurations tailored to each operating system to ensure proper functionality and compatibility.

Which of the following pages provides a count of sensors in Reduced Functionality Mode (RFM) by Operating System?

A Sensor Health

✓ CORRECT

B Support and resources

C Activity Overview

D Hosts Overview

SUGGESTED ANSWER

The suggested answer is A.

What best describes what happens to detections in the console after clicking "Disable Detections" for a host from within the Host Management page?

- A Preventions will be disabled for the host
- B You cannot disable detections for a host
- C The detections for the host are removed from the console immediately and no new detections will display in the console going forward** ✓ CORRECT
- D Existing detections for the host remain, but no new detections will display in the console going forward

SUGGESTED ANSWER

The suggested answer is C.

When detections are disabled for a host from within the Host Management page, the detections for the host are removed from the console immediately, and no new detections will display in the console going forward.

An inactive host that does not contact the Falcon cloud will be automatically removed from the Host Management and Trash pages after how many days?

A 75 Days

B 45 Days

✓ CORRECT

C 60 Days

D 90 Days

SUGGESTED ANSWER

The suggested answer is B.

An inactive host that does not contact the Falcon cloud will be automatically removed from the Host Management and Trash pages after 45 days. This is the defined duration for considering a host as inactive and subsequently removing it from the specified pages.

Which statement is **TRUE** regarding disabling detections on a host?

- A Hosts with detections disabled will not alert on anything for 24 hours (by default) or longer if that setting is changed
- B Hosts with detections disabled will not alert on anything until detections are enabled again** ✓ CORRECT
- C Hosts with detections disabled will not alert on blocklisted hashes or machine learning detections, but will still alert on IOA-based detections. It will remain that way until detections are enabled again
- D Hosts cannot have their detections disabled individually

SUGGESTED ANSWER

The suggested answer is B.

What is likely the reason your Windows host would be in Reduced Functionality Mode (RFM)?

A A misconfiguration in your prevention policy for the host

B The host lost internet connectivity

C A Sensor Update Policy was misconfigured

D Microsoft updates altering the kernel

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

How many days will an inactive host remain visible within the Host Management or Trash pages?

A 90 days

✓ CORRECT

B 120 days

C 15 days

D 45 days

SUGGESTED ANSWER

The suggested answer is A.

An inactive host typically remains visible within the Host Management or Trash pages for 90 days. This is a common practice to allow administrators ample time to review and take necessary actions on inactive hosts before they are permanently removed.

Which of the following is **TRUE** regarding disabling detections for a host?

- ☐ A The DetectionSummaryEvent continues being sent to the Streaming API for that host
- ☐ B After disabling detections, the host will operate in Reduced Functionality Mode (RFM) until detections are enabled
- ☒ C The detections for that host are removed from the console immediately. No new detections will display in the console going forward unless detections are enabled ✓ CORRECT
- ☐ D After disabling detections, the data for all existing detections prior to disabling detections is removed from the Event Search

SUGGESTED ANSWER

The suggested answer is C.

On the Host management page which filter could be used to quickly identify all devices categorized as a "Workstation" by the Falcon Platform?

A Status

B Platform

C Hostname

D Type

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To identify all devices categorized as a 'Workstation' by the Falcon Platform on the Host management page, the most relevant filter to use would be 'Type'. This is because 'Type' directly refers to the classification or category of the device, such as 'Workstation'. Other filters like 'Status', 'Platform', or 'Hostname' do not specifically relate to categorizing devices as 'Workstations'.

Where in the console can you find a list of all hosts in your environment that are in Reduced Functionality Mode (RFM)?

A Containment Policy

B Inactive Sensor Report

C Host Dashboard

D Host Management > Filter for RFM

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To find a list of all hosts in your environment that are in Reduced Functionality Mode (RFM), you should go to Host Management and use the filter for RFM. This will give you a comprehensive list of all such hosts.

How can you find a list of hosts that have not communicated with the CrowdStrike Cloud in the last 30 days?

A Disabled Sensors

B Inactive Sensors

✓ CORRECT

C Custom Reports

D Sensor Report

SUGGESTED ANSWER

The suggested answer is B.

Which of the following would give you information about inactive sensors within the Falcon console?

A Sensor Coverage Lookup

B Sensor Health

✓ CORRECT

C Sensor Update Policies

D Sensor Downloads

SUGGESTED ANSWER

The suggested answer is B.

What best describes what happens to detections in the console after clicking "Enable Detections" for a host which previously had its detections disabled?

- A Enables custom detections for the host
- B New detections will start appearing in the console, and all retroactive stored detections will be restored to the console for that host** ✓ CORRECT
- C New detections will start appearing in the console immediately. Previous detections will not be restored to the console for that host
- D Preventions will be enabled for the host

SUGGESTED ANSWER

The suggested answer is B.

When a Linux host is in Reduced Functionality Mode (RFM) what telemetry and protection is still offered?

- A The sensor would provide minimal protection
- B The sensor provides no protection, and only collects Sensor Heart Beat events** ✓ CORRECT
- C The sensor would function as normal
- D The sensor would provide protection as normal, without event telemetry

SUGGESTED ANSWER

The suggested answer is B.

When a Linux host is in Reduced Functionality Mode (RFM), the sensor provides no protection and only collects Sensor Heart Beat events. This mode indicates that the sensor is still installed on the host but does not perform its usual detection and protection functions.

What kind of hosts can be contained in Falcon?

- ☐ A Only Windows hosts running the Falcon sensor
- ☐ B Only Windows and Linux hosts running the Falcon sensor
- ☐ C Only Windows and MacOS hosts running the Falcon sensor
- ☒ D Any host running the Falcon sensor

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Which of the following policies allowlist network traffic even while a host is Network Contained?

A Firewall Policy

B IP Allowlist Policy

✓ CORRECT

C Response Policy

D Containment Policy

SUGGESTED ANSWER

The suggested answer is B.

IP Allowlist Policy allows network traffic even while a host is Network Contained. This policy is specifically designed to permit traffic from pre-approved IP addresses, thereby ensuring essential communications are maintained even during containment.

Where should you look to find the history of the successes and failures for any Falcon Fusion workflows?

A Custom Alert History

B Workflow Execution log

✓ CORRECT

C Workflow Audit log

D Falcon UI Audit Trail

SUGGESTED ANSWER

The suggested answer is B.

What three things does a workflow condition consist of?

- A Notifications, alerts, and API's
- B Triggers, actions, and alerts
- C A parameter, an operator, and a value**
- D A beginning, a middle, and an end

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

A workflow condition consists of a parameter, an operator, and a value. The parameter is the attribute or field being evaluated, the operator is the method of comparison (such as equals, greater than, or less than), and the value is the specific criteria the parameter is compared against. This tripartite structure forms the basis for evaluating conditions within workflows.

Which of the following can be found in the Falcon UI Audit Trail Report?

- A Audit records of Falcon instance billing
- B Audit records of actions taken by both users and API clients** ✓ CORRECT
- C Audit records of actions taken by only APIs
- D Audit records of actions taken by only users

SUGGESTED ANSWER

The suggested answer is B.

What information does the API Audit Trail Report provide?

- A A list of specific changes to prevention policy
- B A list of actions taken via Falcon OAuth2-based APIs**

✓ CORRECT

- C A list of newly added hosts

- D A list of analyst login activity

SUGGESTED ANSWER

The suggested answer is B.

Which user role will NOT enable the user to connect to a host using Real Time Response?

- A Real Time Response -Administrator
- B Real Time Response - Active Responder
- C Real Time Response - Read-Only Analyst
- D Falcon Administrator**

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

The Falcon Administrator role does not specifically involve Real Time Response capabilities. Real Time Response roles are explicitly designed to enable users to connect and respond to hosts, such as the Real Time Response - Administrator and Real Time Response - Active Responder roles. While a Falcon Administrator has administrative privileges, this role is not primarily focused on Real Time Response activities.

Which report lists counts of sensors in Reduced Functionality Mode (RFM) for all operating system types, and tracks how long a sensor version will be supported?

A Reduce Functionality Audit Report

B Inactive Sensor Report

C Sensor Health Report

✓ CORRECT

D Sensor Coverage Lookup

SUGGESTED ANSWER

The suggested answer is C.

The Sensor Health Report is designed to provide information about sensors in Reduced Functionality Mode (RFM) across all operating system types. It also includes details on how long specific sensor versions will be supported, making it the most appropriate report for the given requirements.

You have a new patch server that should be reachable while hosts in your environment are network contained. The server's IP address is static and does not change. Which of the following is the best approach to updating the Containment Policy to allow this?

A Add an allowlist entry containing CIDR notation for the /24 network the server belongs to

B Add an allowlist entry containing the host group that the server belongs to

C Add an allowlist entry for the individual server's MAC address

D Add an allowlist entry for the individual server's IP address

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

What will happen to a host that is not part of any group which has a prevention policy assigned to it?

A The host will apply the default prevention policy

✓ CORRECT

B The host will apply a sensor-based policy to prevent a majority of known threats

C The host will send a notification to the Falcon Administrator to assign a prevention policy

D The host will disable the falcon sensor

SUGGESTED ANSWER

The suggested answer is A.

If a host is not part of any group which has a prevention policy assigned to it, the host will apply the default prevention policy. This ensures that all hosts have some level of protection even if they are not explicitly assigned to a specific group with a dedicated policy.

Which of the following controls the speed in which your sensors will receive automatic sensor updates?

A Maintenance Tokens

B Sensor Update Policy

C Channel File Update Throttling

D Sensor Update Throttling

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Sensor Update Throttling directly controls the speed and frequency at which your sensors receive automatic updates. It manages the rate of updates to avoid overwhelming the network and to ensure that updates are distributed in a controlled manner.

After agent installation, an agent opens a permanent ____ connection over port 443 and keeps that connection open until the endpoint is turned off or the network connection is terminated.

A HTTP

B SSH

C TLS

✓ CORRECT

D TCP

SUGGESTED ANSWER

The suggested answer is C.

After the installation of an agent, it establishes a permanent TLS connection over port 443. TLS (Transport Layer Security) is a protocol that ensures privacy between communicating applications and their users on the Internet. This connection remains open until the endpoint is either turned off or the network connection is terminated.

When troubleshooting the Falcon Sensor on Windows, what is the correct parameter to output the log directory to a specified file?

A LOG=log.txt

B /log log.txt

✓ CORRECT

C C:\CSSensorInstall\LogFiles

D \log log.txt

SUGGESTED ANSWER

The suggested answer is B.

The correct parameter to output the log directory to a specified file when troubleshooting the Falcon Sensor on Windows is /log log.txt. This follows the format specified in the Falcon Sensor documentation for Windows.

During a sensor installation, what unique identifier is given to each sensor?

A Agent ID (AID)

✓ CORRECT

B Security ID (SID)

C Computer ID (CID)

D Endpoint ID (EID)

SUGGESTED ANSWER

The suggested answer is A.

During a sensor installation, the unique identifier that is given to each sensor is called the Agent ID (AID). This identifier helps in uniquely identifying and managing the sensors within a network.

Where can you find information about all supported operating systems for the Falcon sensor?

A Documentation

✓ CORRECT

B News

C Sensor Release Notes

D Sensor Downloads

SUGGESTED ANSWER

The suggested answer is A.

The correct option is 'Documentation' because the documentation typically contains comprehensive and detailed information about all supported environments, including operating systems. It serves as the main reference for understanding all aspects and requirements of the software, ensuring users can find necessary information regarding compatibility and support.

What sensor update policy will a sensor receive if it does not have a host group assignment?

- A Auto N-2 policy
- B They don't get a policy
- C The default policy**
- D Auto N-1 policy

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

If a sensor does not have a host group assignment, it will receive the default policy. This is a standard approach to ensure that all sensors have a base level of configuration and updates, even if they are not explicitly assigned to a specific host group or policy.

What information is provided in "Remote or network Logon Activities" under Visibility Reports?

- A A list of all logons for all users
- B A list of last endpoints that a user logged in to** ✓ CORRECT
- C A list of users who are remotely logged on to devices based on local IP and local port
- D A list of unique users who are remotely logged on to devices based on the country

SUGGESTED ANSWER

The suggested answer is B.

How would an installation token be configured if the Falcon Sensor was installed on a Red Hat Enterprise Linux host?

- A You will be prompted to enter the installation token during the install if it is required
- B `sudo yum install --cid= --provisioning-token=ABCD1234`
- C `sudo /opt/CrowdStrike/falconctl -s -t ABCD1234`
- D `sudo /opt/CrowdStrike/falconctl -s --cid= --provisioning-token=ABCD1234` ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

To configure an installation token for the Falcon Sensor on a Red Hat Enterprise Linux host, the command should include both the CID (Customer ID) and the provisioning token. The correct format for this would be 'sudo /opt/CrowdStrike/falconctl -s --cid= --provisioning-token=ABCD1234'. This ensures that both critical pieces of information are provided during the installation process.

What is the **best** way to write an ML exclusion for any executable file at "C:\Program Files\Software\"?

A You cannot. You must list a specific file in an exclusion rule

B Program Files\Software**

C Program Files\Software\.*

D Program Files\Software*.exe

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Your development team is working on a new enterprise application, but Falcon starts creating alerts during testing. The alert points to, "C:\Users\Bob\DevCode\felix.dll". In the detection, you see that it's triggering only on a specific Falcon IOA. What would be the best course of action for this situation?

- A Create a sensor visibility exclusion for "C:\Users\Bob\DevCode\felix.dll"
- B Create an IOA exclusion for "C:\Users\Bob\DevCode\felix.dll"** ✓ CORRECT
- C Create a Custom IOC and set it to "Allow" for "C:\Users\Bob\DevCode\felix.dll"
- D Manually turn off the built-in IOA through prevention policies

SUGGESTED ANSWER

The suggested answer is B.

Creating an IOA exclusion for "C:\Users\Bob\DevCode\felix.dll" is the best course of action in this situation. Since the alert is triggered specifically by a Falcon IOA, an IOA exclusion will effectively prevent the detection for this particular file without affecting other types of detections. Custom IOCs are more appropriate for handling detections based on indicators of compromise (IOCs) like file hashes and won't address IOA-based triggers.

Why do Sensor Update policies need to be configured for each OS (Windows, Mac, Linux)?

A Sensor Update policies are OS dependent

✓ CORRECT

B This is false. One policy can be applied to all Operating Systems

C To assist with auditing and change management

D To bundle the Sensor and Prevention policies together into a deployment package

SUGGESTED ANSWER

The suggested answer is A.

What is the purpose of the Default Sensor Policy?

- ☐ A Used to reset all sensor settings to Default.
- ☒ B Acts as a "catch all" policy if no other Sensor Policies are applied. ✓ CORRECT
- ☐ C Tests the sensor configuration settings before deployment.
- ☐ D A mechanism to deploy the oldest supported version of the Falcon Sensor.

SUGGESTED ANSWER

The suggested answer is B.

What will happen to a host if it is not assigned a Sensor Update policy?

- ☐ A The host will automatically create a custom Sensor Update policy
- ☐ B The host will uninstall the Sensor and provide an alert to the installation team
- ☒ C The host will use the Default Sensor Update policy ✓ CORRECT
- ☐ D The host will automatically update to the newest sensor version and auto-update to future release

SUGGESTED ANSWER

The suggested answer is C.

When deploying the Falcon Sensor alongside an existing security solution, you enable the **Quarantine** prevention setting in Falcon. What is the recommended configuration for both solutions?

- A Disable or remove the other AV solution and configure ODS Cloud Anti-Malware prevention in Falcon to Moderate or higher
- B Disable or remove the other AV solution and configure NGAV Sensor Machine Learning prevention in Falcon to Moderate or higher** ✓ CORRECT
- C Disable or remove the other AV solution and configure NGAV Sensor Machine Learning prevention in Falcon to Cautious
- D Disable or remove the other AV solution and configure NGAV Cloud Machine Learning prevention in Falcon to Extra-Aggressive

SUGGESTED ANSWER

The suggested answer is B.

What are the two triggers that cause a fusion workflow to run?

A Fusion workflows are manually ran

B Event and scheduled triggers

✓ CORRECT

C Condition and action triggers

D Incident and detections triggers

SUGGESTED ANSWER

The suggested answer is B.

What default roles can view, create, and edit workflows?

- A Falcon Administrator, Falcon Security Lead
- B Falcon Administrator, Workflow Author** ✓ CORRECT
- C Falcon Administrator, Falcon Security Lead, Workflow Author
- D Falcon Administrator, Workflow Author, Falcon Security Lead, Falcon Investigator

SUGGESTED ANSWER

The suggested answer is B.

When performing targeted filtering for a host on the Host Management Page, which filter bar attribute is **NOT** case-sensitive?

A Username

B Hostname

✓ CORRECT

C Domain

D Model

SUGGESTED ANSWER

The suggested answer is B.

What are the three configurable parts of a machine learning exclusion?

A File paths, names, and extensions

✓ CORRECT

B Drive letters, directories, and patterns

C Parameters, operators, and values

D Triggers, actions and alerts

SUGGESTED ANSWER

The suggested answer is A.

Where in the Falcon platform can you confirm the sensor build version installed on a particular host?

- ☒ A Host Management page by filtering for and selecting the host ✓ CORRECT
- ☐ B Dashboards by viewing the Executive Summary Dashboard
- ☐ C Tool Downloads page by downloading the Sensor Reporting Tool
- ☐ D Sensor Downloads page by filtering for a sensor build and selecting the host

SUGGESTED ANSWER

The suggested answer is A.

When a user initiates a sensor install, where can the logs be found?

A %LOCALAPPDATA%\Logs

B %SYSTEMROOT%\Logs

C %LOCALAPPDATA%\Temp

✓ CORRECT

D %SYSTEMROOT%\Temp

SUGGESTED ANSWER

The suggested answer is C.

Certain services are required to be running to install the Windows Falcon sensor. What may cause the **LMHost** service to be disabled?

A Windows Base Filtering Engine

B WinHTTP AutoProxy

C TCP/IP NetBIOS Helper

✓ CORRECT

D DHCP Client

SUGGESTED ANSWER

The suggested answer is C.

Which of the follow should be used with **extreme** caution because it may introduce additional security risks such as malware or other attacks which would not be recorded, detected, or prevented based on the exclusion syntax?

A IOA Exclusions

B Sensor Visibility Exclusion

✓ CORRECT

C Machine Learning Exclusions

D IOC Exclusions

SUGGESTED ANSWER

The suggested answer is B.

You have been asked to troubleshoot why Script Based Execution Monitoring (SBEM) is not enabled on a Falcon host. Which report can be used to determine if this is an issue with an old prevention policy?

A Custom Alerting Audit Trail

B SBEM Debug Report

C Prevention Policy Debug

✓ CORRECT

D Host Update Status Report

SUGGESTED ANSWER

The suggested answer is C.

Which of the following scenarios best describes when you would add IP addresses to the containment policy?

- A You want to automate the Network Containment process based on the IP address of a host
- B A new group of analysts need to be able to place hosts under Network Containment
- C Your organization has resources that need to be accessible when hosts are network contained** ✓ CORRECT
- D Your organization has additional IP addresses that need to be able to access the Falcon console

SUGGESTED ANSWER

The suggested answer is C.

What would be the most appropriate action to take if you wanted to prevent a folder from being uploaded to the cloud without disabling uploads globally?

A A Sensor Visibility exclusion

B An IOA exclusion

C Custom IOC entry

D A Machine Learning exclusion

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You have a member of your **SECOPS** team that is building custom scripts for your environment and they cannot save or share them in Falcon. What additional role do they need to be able accomplish this?

A Real Time Response - Active Responder

B All Real Time Response roles can do this

C Falcon Scripts Manager

D Real Time Response - Administrator

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

A member of your SECOPS team currently has the role of Falcon Security Lead to be able to Manage detections, quarantine files and reset user credentials. Which additional role is required to also allow them to view and modify remediation actions?

A Detections Exception Manager

B Remediation Manager

✓ CORRECT

C Endpoint Manager

D Quarantine Manager

SUGGESTED ANSWER

The suggested answer is B.

Which of the following includes all that can be configured to alert as a Custom IOC (Indicator of Compromise) in IOC Management?

A Hash, Domain, Filename

B Hash

C Hash, Domain

D Hash, Domain, IP Address

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You are the Falcon Administrator for your organization, and you want to ensure you have accountability for the actions your Falcon users take.

What is the retention period of the audit logs within Falcon?

A 30 days

B One year

C 90 days

✓ CORRECT

D 180 days

SUGGESTED ANSWER

The suggested answer is C.

When creating your own Fusion SOAR workflow based on an Event trigger, which additional option will refine the trigger?

A Option

B Filter

C Condition

✓ CORRECT

D Trigger Details

SUGGESTED ANSWER

The suggested answer is C.

Your leadership wants controls in place for immediate action on any Overwatch detections.

What should you do to ensure the host is contained quickly and notifies the appropriate staff?

- A** Create a Fusion SOAR workflow using the Overwatch playbook to contain the host and email the SOC team ✓ CORRECT
- B** Create a Fusion SOAR workflow to create a detection for Overwatch and email the SOC team
- C** Create a Fusion SOAR workflow to contain the host and email the Overwatch team
- D** Create a Fusion SOAR workflow to trigger on an Overwatch detection and set it to block the detection

SUGGESTED ANSWER

The suggested answer is A.

During a Windows system investigation via Real Time Response (RTR), an RTR Active Responder is unable to execute a custom powershell script for finding specific system artifacts.

What is likely restricting the responder from executing the powershell script?

A Script-Based Execution Monitoring is not enabled in the prevention policy

B Custom Scripts is not enabled in the response policy

✓ CORRECT

C The responder requires the RTR Administrator role

D Put-and-Run is not enabled in the response policy

SUGGESTED ANSWER

The suggested answer is B.

What least privilege role should be given to a user who needs to extract files with RTR?

A Real Time Responder - Active Responder

✓ CORRECT

B Falcon Analyst

C Falcon Security Lead

D Real Time Responder - Administrator

SUGGESTED ANSWER

The suggested answer is A.

In order to prevent duplicate Agent IDs, what install parameter should be used on VMs to be used as persistent clones?

A ProvNoWait=1

B /quiet

C VM=True

✓ CORRECT

D NO_START=1

SUGGESTED ANSWER

The suggested answer is C.

Your organization wants to monitor the use of remote access software that is currently authorized. The executable is called remote.exe.

How would you trigger a detection for review of any process named remote.exe?

- ☐ A Create an exclusion for remote.exe and set a workflow to email you every time the exclusion is used
- ☐ B Assign an aggressive detection level machine-learning prevention policy to the applicable hosts
- ☒ C Write an IOA rule to monitor process creation of .*\remote\.exe ✓ CORRECT
- ☐ D Write a scheduled search looking for ProcessRollup2 events for remote.exe

SUGGESTED ANSWER

The suggested answer is C.

Which report in Falcon can be used to determine the volume of blocked activity at a different prevention policy setting?

- A Prevention Policy Audit Trail
- B Sensor Visibility Exclusions Audit
- C Machine Learning Prevention Monitoring**
- D Falcon Prevention Policy Debug

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

Your organization has determined that your cybersecurity architect needs to be notified via email whenever Falcon generates detections of a **medium** severity or higher. Additionally, the architect should be notified about any incidents with a **CrowdScore** of **1.0** or higher.

What can the Falcon Administrator do to ensure the architect is properly alerted?

- A Create a new Falcon user for the architect then create and assign a custom Falcon user role so they are automatically notified for the new detections and emails
- B Add the architect's email address to the manage list for detection and incident emails from the General settings menu** ✓ CORRECT
- C Create a new Falcon user for the architect and assign the Detections and Exceptions Manager role so they are automatically notified for the new detections and incidents
- D Create a custom Fusion SOAR workflow to send an email every time a new detection or incident is created

SUGGESTED ANSWER

The suggested answer is B.

What is an example of when you will need to refer to your Customer ID+ Checksum (CIDC)?

A When you need to find a specific host in Host Management

B When defining host group assignment criteria

C When uninstalling a Falcon Sensor

D When installing a new Falcon Sensor

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You are tasked with creating a group for hosts running Windows 10.

What kind of group should you create to make sure all applicable hosts are included in your environment?

- ☐ A Create a static group with the assignment rule criteria set to OS Type Workstation
- ☐ B Create a static group with the assignment rule criteria for OS Version set to Windows 10
- ☐ C Create a dynamic group with the assignment rule criteria set to OS Type Workstation
- ☒ D Create a dynamic group with the assignment rule criteria for OS Version set to Windows 10 ✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Which report would show you an overview of the top ten most-applied policies by sensors in your environment?

A Scheduled reports

B Sensor policy daily report

✓ CORRECT

C Sensor report dashboard

D Executive summary

SUGGESTED ANSWER

The suggested answer is B.

There are a significant number of false positive detections from your developers that are getting blocked and quarantined by Falcon.

What Indicator of Compromise (IOC) action would be the best option?

- A No_action (displayed as None in the console)
- B Allow (displayed as Allow in the console)
- C Detect Only (displayed as Detect only in the console)**
- D Prevent (displayed as Blocked in the console)

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

From the Host management page, what is the **best** field to filter by for Domain Controllers to obtain sensor version information?

A OS Version

B Platform

C Sensor Version

D Type

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You have been asked by your Server management team to provide a list of all Servers that have a "TIER3" Sensor grouping tag.

What method will allow you to export a .csv file with the results?

- A On the Host management page filter by OS Version - Server, and Tags - SensorGroupingTags/TIER3, then export the results
- B On the Host management page filter by Platform - Server, then export the results
- C On the Host management page filter by Type - Server, and Tags - SensorGroupingTags/TIER3, then export the results** ✓ CORRECT
- D On the Host dashboard select the OS platform - Server, and the Tag - SensorGroupingTags/TIER3, then export the results

SUGGESTED ANSWER

The suggested answer is C.

Which default user role will allow you to see all analyst session details?

A Falcon Administrator

✓ CORRECT

B Real Time Response - Active Responder

C Real Time Response - Read-Only Analyst

D Real Time Response - Administrator

SUGGESTED ANSWER

The suggested answer is A.

Where would you apply a configuration to allow IP addresses over which your hosts will always be allowed to communicate, even if a host is contained?

A Containment Policy

✓ CORRECT

B Maintenance Token

C IP Allowlist Management

D Response Policies

SUGGESTED ANSWER

The suggested answer is A.

Which ML exclusion pattern would be the most accurate for all .exe binaries in "C:\Program Files\Software/", including any subfolders of Software?

A Program Files\Software*.exe

B ***.exe

C Program Files\Software**.*.exe

✓ CORRECT

D Program Files\Software***.*.exe

SUGGESTED ANSWER

The suggested answer is C.

You can create Fusion SOAR workflows to precisely define the actions you want Falcon to perform in response to incidents.

Which three items must be defined in every trigger so that it executes successfully?

A Trigger, Condition, Action

✓ CORRECT

B Rule Type, Condition, Action

C Trigger, Filter, Objective

D Rule Type, Filter, Objective

SUGGESTED ANSWER

The suggested answer is A.

When an API client is created, what two pieces of information must be generated as a pair to successfully identify and validate your API integrations?

A Client ID and Secret

✓ CORRECT

B Client ID and OAuth2 ID

C Customer ID and Secret

D Customer ID and Integration ID

SUGGESTED ANSWER

The suggested answer is A.

You will be testing detections with pentest and security tooling on your host.

How can a workflow be created to automatically assign any detection related to your pentest to yourself in real time?

- A Create a workflow to disable detections for your host until testing is done
- B Create an Event trigger workflow that triggers on an EPP Detection with an action to assign the detection to yourself
- C Create an Event trigger workflow that triggers on an EPP Detection with conditions looking for the desired hostname. The Action will then assign the detection to yourself.** ✓ CORRECT
- D Create a scheduled workflow to run once a day that triggers on an EPP Detection with conditions looking for the desired hostname. The Action will then assign the detection to yourself.

SUGGESTED ANSWER

The suggested answer is C.

What best describes the effect of disabling detections for a host?

- A** Detections for the host are removed from the console immediately and no new detections display in the console going forward until re-enabled ✓ CORRECT
- B** Existing detections for the host remain, but no new detections will be presented in the console going forward until re-enabled
- C** Detections for the host are removed from the console immediately and cannot be restored unless the sensor is reinstalled
- D** You cannot disable detections for a single host and are only able to prevent detections via allowlisting

SUGGESTED ANSWER

The suggested answer is A.

To improve the organization's security posture, you are designing a Fusion SOAR workflow to generate an alert when critical vulnerabilities are detected by Falcon.

When creating a new workflow from scratch, what component of the workflow must be configured first?

A Action

B Workflow Name

C Trigger

✓ CORRECT

D Condition

SUGGESTED ANSWER

The suggested answer is C.

What log would you use to investigate unusual activity involved with a script interfacing with the Falcon platform?

A Prevention policy debug

B RTR session audit

C API audit

✓ CORRECT

D Falcon UI audit

SUGGESTED ANSWER

The suggested answer is C.

What happens to detections in the console after clicking "Disable Detections" for a host from within the Host Management page?

- A Detections from the host are paused for 7 days. Existing detections from the host are removed from the console within 24 hours.
- B The detections for the host are removed from the console immediately. No new detections will display in the console going forward. ✓ CORRECT**
- C Existing detections for the host remain. No new detections will display in the console going forward.
- D Existing detections for the host are removed from the console. The process that triggered them is allow-listed to prevent future alerts. Detections for other alerts are unaffected.

SUGGESTED ANSWER

The suggested answer is B.

You are tasked with creating a "Workstations" host group to encompass ALL workstations in your environment.

Which dynamic grouping criteria would best accomplish this task?

A Grouping Tags: Workstation

B Type: Workstation

✓ CORRECT

C Platform: Windows

D Site: Workstation

SUGGESTED ANSWER

The suggested answer is B.

How can you search for multiple hostnames at the same time via Host Management?

- A Add the Multiple Hostnames filter and enter your list of hostnames
- B Enter the multiple hostnames in the Hostname filter separating each by a comma** ✓ CORRECT
- C Add the Hostname filter multiple times and enter separate hostnames into each filter
- D Enter the multiple hostnames in the Hostname filter separating each by a decimal

SUGGESTED ANSWER

The suggested answer is B.

Which setting inside the Sensor Update Policy prevents unauthorized uninstallation?

- A Sensor Version Control Protection
- B Installation and Maintenance Protection
- C Uninstall and Maintenance Protection
- D Update and Management Protection

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

As a Falcon Administrator, you would like to tune your Prevention Policies and compare the number of detections that would have resulted in the last 30 days depending on which detection level was used (Cautious, Moderate, Aggressive or Extra Aggressive).

Which audit logs would best help you evaluate the appropriate setting to use?

A Machine-learning prevention monitoring

✓ CORRECT

B Prevention policy

C Policy efficacy monitoring

D Prevention policy debug

SUGGESTED ANSWER

The suggested answer is A.

What happens when a Falcon Sensor on a Linux host enters Reduced Functionality Mode (RFM)?

- ☐ A RFM sensors on Linux hosts only send detection information to the Falcon Console. Event processing is disabled.
- ☒ B RFM sensors on Linux hosts stop processing both events and detections. Sensors send basic status information to the Falcon Console. ✓ CORRECT
- ☐ C RFM sensors on Linux hosts stop processing events and detections but continue to send log data into Falcon
- ☐ D RFM sensors on Linux hosts continue to process events and detections for existing policies but cannot get policy updates from the Falcon Console

SUGGESTED ANSWER

The suggested answer is B.

A server was added to a new host group that has a different sensor update and prevention policy applied. Even though the server has been online for more than 30 minutes, the policies have still not been applied.

Why have the policies not applied?

- ☐ A Any changes to groups requires a host reboot for policy changes to take effect
- ☐ B The new group should be prioritized by reordering groups and placing the new group in PRECEDENCE 1
- ☐ C The new group has not been enabled and the host is currently applying default policies
- ☒ D Hosts can reside in multiple groups and the server is currently assigned policies with higher precedences

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

By default, how many days without successful communication must pass before a host no longer appears in the Falcon console?

A The exact number of days is set by your data retention period

B 60

C 30

D 45

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

After successfully installing Falcon on a new employee's laptop, you notice that the machine is assigned the default prevention policy instead of the custom prevention policy you created. You verify that the Falcon sensor is functioning properly, and you confirm that the custom policy is enabled and successfully running on more than 1,000 other Falcon hosts.

What is the likely cause of this issue?

A Falcon requires a 24- hour waiting period to apply custom policies to newly installed hosts

B The laptop is not a member of a host group assigned to the custom policy

✓ CORRECT

C A host-based firewall rule is preventing the custom policy from applying successfully

D A prompt to apply the new prevention policy was manually declined

SUGGESTED ANSWER

The suggested answer is B.

You are creating a new host group that needs to contain all of the servers in your environment regardless of the installed operating system.

Which filter should be applied to the group's assignment rule to accomplish this task?

A Build - Server

B Manufacturer-All

C Type - Server

✓ CORRECT

D Model - Server

SUGGESTED ANSWER

The suggested answer is C.

Which report provides a filterable high-level overview of host information such as OS version, Device Type and Machine Domain, and also provides an active sensor heat map for a quick environment review?

A Sensor Status Report

B Sensor Policy Daily Report

C Sensor Report

✓ CORRECT

D Sensor Overview Report

SUGGESTED ANSWER

The suggested answer is C.

Which statement best describes user permissions in Falcon?

- ☐ A Each Falcon permission needs to be selected when the user account is created
- ☐ B Users can only have predefined default roles assigned to them before using a custom role
- ☒ C User permissions can be defined by default or custom roles as needed ✓ CORRECT
- ☐ D Custom user role permission sets can be shared with all CrowdStrike customers globally

SUGGESTED ANSWER

The suggested answer is C.

Detections related to a penetration test on a particular server are currently generating thousands of entries in the console. Your leadership does not need to track the detections in Falcon.

What should you do to allow your team to focus on more relevant detections?

- ☐ A Delete the detections in the console and contain the server undergoing the test
- ☐ B Permanently disable detections for the server in Host Management
- ☒ C Temporarily disable detections for the server in Host Management and re-enable after the test is done ✓ CORRECT
- ☐ D Create a Fusion Workflow to email the SOC team every time the penetration test generates a detection

SUGGESTED ANSWER

The suggested answer is C.

What could cause your Windows host to be in Reduced Functionality Mode (RFM)?

A Crowdstrike has not certified the latest Windows update

✓ CORRECT

B A sensor update policy was misconfigured

C A misconfiguration in your prevention policy

D The host lost internet connectivity

SUGGESTED ANSWER

The suggested answer is A.

What are the three required parts of a Fusion SOAR workflow condition?

- A Notifications, alerts, and APIs
- B Triggers, actions, and alerts
- C A parameter, an operator, and a value**
- D A value, a trigger, and a constraint

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

What is the primary concern with Windows sensors going into Reduced Functionality Mode (RFM)?

- ☐ A The operating systems on these hosts have crashed
- ☒ B The sensors do not have full visibility into all events occurring on the host ✓ CORRECT
- ☐ C The sensors are unable to report any of their recorded events
- ☐ D The hosts have been powered off or otherwise cannot communicate with the Falcon cloud

SUGGESTED ANSWER

The suggested answer is B.

What information can be found in the Real Time Response (RTR) Audit Log?

- ☐ A IP Address, Prevention Policy, recent detections, and host group assignment
- ☐ B Real Time Response (RTR) information is not collected via audit logs
- ☐ C Session end time, command return results, and file activity
- ☒ D Session start time, duration, user, hostname, commands used, and retrieved files

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You are deploying the **Falcon** sensor to a total of 500 hosts. Hosts in an Organizational Unit (OU) will need a specific exclusion that was previously identified. This OU is expected to add members over the next quarter.

What is the best way to create a host group for this OU?

- A Create a dynamic group with an assignment rule that excludes the OU
- B Create a static group with from list of all 500 host names.
- C Create a static group with from list of host names in the OU
- D Create a dynamic group with an assignment rule that filters for the OU**

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Using Host setup and management inside the Falcon Console, how can you display sensors in Reduced Functionality Mode (RFM)?

- A From Sensor status, click on the widget: RFM
- B From Host status, filter for RFM
- C From Host management, filter for RFM**
- D From Sensor health, sort using the column heading: Sensor status

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

What default user role can manage API credentials?

A Falcon Security Lead

B Falcon Administrator

✓ CORRECT

C Endpoint Manager

D Falcon API Manager

SUGGESTED ANSWER

The suggested answer is B.

A host has been **Network** contained with **Falcon** and you have been asked to update the **Operating** System with zero day patches. You have tried using your patch update systems for this task, but the jobs fail.

Which configuration steps in the **Falcon** UI will allow these activities?

A Create a Containment Policy that allow lists the specific IP addresses of your patch management tools

✓ CORRECT

B Create a Containment Policy that allow lists the Fully Qualified name of your patch management tools

C Remove Host containment and update the host with all patches

D Create a Firewall Policy that allow lists your patch management tools

SUGGESTED ANSWER

The suggested answer is A.

You want to add an additional layer of security to high-risk RTR commands for your environment.

Where would you configure MFA for RTR within the UI?

A Containment policy

B General settings

✓ CORRECT

C Host group

D Response policies

SUGGESTED ANSWER

The suggested answer is B.

Your security team is noticing that certain privacy-sensitive information such as the URL, HTTP Header and POST bodies are missing from HTTP related detections.

What is likely the cause for this?

- ☐ A The prevention policy was never configured to generate HTTP detections
- ☒ B The prevention policy has been configured to redact HTTP detection details ✓ CORRECT
- ☐ C The prevention policy was configured to have an aggressive prevention setting, but only a cautious detection setting
- ☐ D The network perimeter firewall blocked the HTTP connection attempts so there was nothing for Falcon to detect

SUGGESTED ANSWER

The suggested answer is B.

When creating a machine learning exclusion with glob syntax, what are the three items you can target for exclusion?

A File path, name, or type (extension)

✓ CORRECT

B Drive letters, directories, or patterns

C Triggers, actions or alerts

D Parameters, operators, or values

SUGGESTED ANSWER

The suggested answer is A.

Where can you find hosts that have been offline for ten minutes or longer?

A Host Management

✓ CORRECT

B Sensor Report

C Host Groups

D Sensor Coverage Dashboard

SUGGESTED ANSWER

The suggested answer is A.

What are the two automated triggers that cause a Fusion SOAR workflow to run?

A Incident and detections triggers

B Event and scheduled triggers

✓ CORRECT

C Event and action triggers

D Condition and action triggers

SUGGESTED ANSWER

The suggested answer is B.

What are the required components to manually install Falcon Sensor on MacOS?

- ☐ A Falcon package, system extension, Full Disk Access
- ☒ B Falcon package, system extension, Full Disk Access, network filter extension ✓ CORRECT
- ☐ C System extension, Full Disk Access, network filter extension
- ☐ D Falcon package, Full Disk Access, network filter extension

SUGGESTED ANSWER

The suggested answer is B.

You need to create a rule to block all process executions of Telegram in your environment.

Which custom IOA rule configuration would accomplish this?

A Custom IOA rule configuration cannot block non-malicious binaries from executing

B Custom IOA rule set to Block Execution on an Image Filename of .*Telegram.*

✓ CORRECT

C Custom IOA rule set to Monitor on an Image Filename of .*Telegram.*

D Custom IOA rule set to Detect on an Image Filename of .*Telegram.*

SUGGESTED ANSWER

The suggested answer is B.

What is true about User Accounts created by the Falcon Administrator?

- ☐ A By default, all User Accounts are created with the Falcon Analyst role
- ☐ B All new User Accounts are created using an employee identification number (EID)
- ☐ C All User Accounts must start with the domain identifier and number
- ☒ D All User Accounts must be created with an email address from the list of approved domains

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You have created a new static host group to test a newly created sensor update policy, and need to add 500 servers into the group. You want to upload a list of hosts to Falcon for automatic addition into the group.

What file format must the list be for this to be successfully accomplished?

A PDF

B XLSX

C JSON

D TXT

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

Leadership has asked for a monthly report on number of hosts by OS version, device type, and geographic location.

What dashboard option includes this information?

A Billing dashboard

B Sensor Health

C Executive summary

D Sensor report

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is D.

You need to be aware of which policies are the most used as new hosts are being added to your CID.

Where could you easily find a review of the top ten sensor update, prevention, and device control policies?

A Managed Assets dashboard

B Executive Summary

C Sensor Policy Daily report

✓ CORRECT

D Sensor Subscription licenses

SUGGESTED ANSWER

The suggested answer is C.

Your incident responder team is in the process of migrating their existing workflows into Fusion SOAR workflows so that they will execute natively in Falcon. The team reports the workflow imports are failing.

What format must the workflows be in order to successfully import them into Fusion SOAR?

A JSON

B CSV

C YAML

✓ CORRECT

D SOAR

SUGGESTED ANSWER

The suggested answer is C.

To test a new Falcon sensor version, you have created a new sensor update policy and two separate dynamic host groups. One group contains all test Windows servers. The other group contains all of your Windows servers. The new policy was applied to only the test Windows servers host group.

What is required to safely and successfully test your new sensor update policy on only your test Windows servers?

- A The new Falcon sensor version should be manually installed by you on every test Windows server before ever enabling and assigning the new policy
- B The new policy must be enabled and assigned a precedence that is higher when compared to the policy assigned to all Windows servers** ✓ CORRECT
- C The new policy must be enabled and assigned a precedence that is lower when compared to the policy assigned to all Windows servers
- D The new Falcon sensor version should be manually uninstalled by you on every test Windows server before ever enabling and assigning the new policy

SUGGESTED ANSWER

The suggested answer is B.

How would you reset an API secret?

- A Create a support ticket requesting a reset
- B Via the three-dot menu on the API client**
- C A new API client is required as you are unable to reset a secret
- D Via General Settings

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is B.

During a simulated training exercise with your security team, an analyst used Falcon to network contain a host. It was then discovered that containing this specific host interrupted some key business processes and resulted in lost revenue.

As the Falcon Administrator, what can be done to prevent this interruption in the future?

- A Collaborate with the firewall engineers so that in the future, network containment would only deny external IP addresses and no internal IP addresses
- B Configure your containment policy to allow the IP addresses for those key business processes so that your hosts will be allowed to communicate with them, even if those hosts are contained** ✓ CORRECT
- C Add this Falcon host to your deny list so that it is never able to be network contained again
- D Educate the analyst so they can understand and memorize which hosts are safe to network contain, and which would cause harm if contained

SUGGESTED ANSWER

The suggested answer is B.

Which prevention policy setting monitors contents of scripts and shells for execution of malicious content?

- A FileSystem Visibility
- B Engine (Full Visibility)
- C Script-based Execution Monitoring**
- D Suspicious Scripts and Commands

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is C.

You have 100 hashes that have been prohibited by management and need to be blocked within your organization.

Using Falcon, what is the best way to accomplish this?

- A Navigate to Configure > IOC Management. Inside this dashboard, add a custom Prevention Policy. Add the list of hashes. Set the action to Block. Verify the policy includes Custom Execution Blocking.
- B Navigate to Configure > Prevention policies. Inside this dashboard, add an IOC Policy. Add the list of hashes as CSV file. Set the action to "Block." Verify the option for Custom Execution Blocking is active.
- C** Navigate to Configure > IOC Management. Inside this dashboard, add a custom IOAdd the list of hashes. Set the action to Block. Verify the prevention policy includes Custom Blocking under Execution Blocking. ✓ CORRECT
- D Navigate to Configure > Prevention policies. Inside this dashboard, add an IOC Policy. Add the list of hashes as a CSV file. Set the action to "Block and Alert." Verify the option for Custom Blocking inside Execution Blocking is active.

SUGGESTED ANSWER

The suggested answer is C.

Excluding mobile devices, what kind of hosts can be contained in Falcon?

- ☒ A Windows, Linux, or MacOS hosts running the Falcon sensor
- ☐ B Windows and Linux hosts running the Falcon sensor
- ☐ C Windows and MacOS hosts running the falcon sensor
- ☐ D Windows, Linux, and container hosts running the Falcon sensor

✓ CORRECT

SUGGESTED ANSWER

The suggested answer is A.