
MATLAB programming course for beginners, supported by Wagatsuma Lab@Kyutech

Table of Contents

Specifications and requirements	1
Main program	1

/* The MIT License (MIT): Copyright (c) 2021 Hiroaki Wagatsuma and Wagatsuma Lab@Kyutech

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE. */

Specifications and requirements

1. @Time : 2021-5-26
2. @Author : Hiroaki Wagatsuma
3. @Site : https://github.com/hirowgit/1B1_matlab_signal_analysis_course
4. @IDE : MATLAB R2018a
5. @File : lec2D_A1_lineHough_Plus.m

Main program

```
clear all

a=1; b=2;
% dT=0.25;
dT=0.75;
rdN=100;
dN=100;
% dNs=100;
```

```
dNs=20;
t=0:pi/dN:pi;
gridP=0:dNs;

rangeXY=[0 20; 0 20]; %[xmin, xmax; ymin, ymax];
labelF={'line','random','line+random','hough trans. for
line','discrete vote','voting contour map'};
fignum=1;

x=0:dT:rangeXY(1,2);
lgen=@(x) a*x+b;

figure(fignum); clf
set(fignum,'name',labelF{fignum},'Position',[500 920 550 500]);
plot(x,lgen(x),'b.','MarkerSize',24);
title(labelF{fignum});
grid on;
axis equal;
fignum=fignum+1;

rdPos=repmat(diff(rangeXY'),[rdN
1]).*rand(rdN,2)+repmat(rangeXY(:,1)',[rdN 1]);

figure(fignum); clf
set(fignum,'name',labelF{fignum},'Position',[1050 850 550 500]);

plot(rdPos(:,1),rdPos(:,2),'r.','MarkerSize',24);
set(gca,'xlim',rangeXY(1,:), 'ylim',rangeXY(2,:));
title(labelF{fignum});
grid on;
axis equal;
fignum=fignum+1;

% mD=[x',lgen(x'); rdPos];
mD=[x',lgen(x'); ];

figure(fignum); clf
set(fignum,'name',strrep(labelF{fignum},'+','_'),'Position',[1600
850 550 500]);

plot(mD(:,1),mD(:,2),'k.','MarkerSize',24);
set(gca,'xlim',rangeXY(1,:), 'ylim',rangeXY(2,:));
title(labelF{fignum});
grid on;
axis equal;
fignum=fignum+1;

houghLD=repmat(mD(:,1)',[size(t,2) 1]).*repmat(sin(t'),[1
size(mD,1)])+repmat(mD(:,2)',[size(t,2) 1]).*repmat(cos(t'),[1
size(mD,1)]);
thetaD=repmat((t'),[1 size(mD,1)]);
mD2=[thetaD(:) houghLD(:)];
```

```
voteD(:,1)=floor(dNs.*(mD2(:,1)-min(mD2(:,1)))./(max(mD2(:,1))-  
min(mD2(:,1))))+1;  
voteD(:,2)=floor(dNs.*(mD2(:,2)-min(mD2(:,2)))./(max(mD2(:,2))-  
min(mD2(:,2))))+1;  
countD=zeros(dNs+1,dNs+1);  
for i=1:size(voteD,1)  
    countD(voteD(i,2),voteD(i,1))=countD(voteD(i,2),voteD(i,1))+1;  
end  
  
grX=((max(mD2(:,1))-min(mD2(:,1))).*(gridP)./dNs)+min(mD2(:,1));  
grY=((max(mD2(:,2))-min(mD2(:,2))).*(gridP)./dNs)+min(mD2(:,2));  
  
grXP=repmat(grX,[dNs+1 1]);  
grYP=repmat(grY',[1 dNs+1]);  
  
% disD=(sqrt(power(repmat(mD2(:,1),[1,size(mD2,1)])-repmat(mD2(:,1)',  
[size(mD2,1),1]),2)+power(repmat(mD2(:,1),[1,size(mD2,1)])-  
repmat(mD2(:,1)',[size(mD2,1),1]),2)));  
% disD2=triu(disD)-triu(ones(size(disD)))';  
% disD2f=disD2(:);  
% key=find(disD2f>=0);  
% sortedDis=sortrows([key disD2f(key)],2);  
  
figure(fignum); clf  
labelF2=strrep(labelF{fignum},'.','');  
labelF2=strrep(labelF2,' ','_');  
set(fignum,'name',labelF2,'Position',[500 270 550 500]);  
  
plot(mD2(:,1),mD2(:,2),'k.');
```

xtickpoint=0:pi/4:2*pi;
xlabel={'0','\pi/4','\pi/2','3\pi/4','\pi','5\pi/4','3\pi/2','7\pi/4','2\pi'};
set(gca,'xtick',xtickpoint,'xticklabel',xlabel)
title(labelF{fignum});
grid on;
fignum=fignum+1;

```
figure(fignum); clf  
labelF2=strrep(labelF{fignum},'.','');  
labelF2=strrep(labelF2,' ','_');  
set(fignum,'name',labelF2,'Position',[1050 270 550 500]);  
  
plot(voteD(:,1),voteD(:,2),'k.'),hold on;  
contour(countD);  
% contourf(countD);  
xtickpoint=0:pi/4:2*pi;  
title(labelF{fignum});  
grid on;  
fignum=fignum+1;  
  
figure(fignum); clf  
labelF2=strrep(labelF{fignum},'.','');  
labelF2=strrep(labelF2,' ','_');  
set(fignum,'name',labelF2,'Position',[1600 270 550 500]);
```

```
contour3(grXP,grYP,countD,50,'lineWidth',3);  
set(gca,'xtick',xtickpoint,'xticklabel',xlabel)  
title(labelF{fignum});  
grid on;  
fignum=fignum+1;
```

```
% datafname='pict_res';  
% save_fig;
```

Unable to perform assignment because the indices on the left side are not compatible with the size of the right side.

Error in lec2D_A1_lineHough_Plus (line 92)
voteD(:,1)=floor(dNs.(mD2(:,1)-min(mD2(:,1)))/(max(mD2(:,1))-min(mD2(:,1))))+1;*

Published with MATLAB® R2018a