


The 3 Musketeers of Web Dev


HTML
(structure)



CSS
(style)



JS
(logic)



Starter Code

<style> tag connects HTML with CSS

<script> tag connects HTML with JS

Apna College

```
<html>
```

```
  <head>
```

```
    <title> Website Name </title>
```

```
  </head>
```

```
  <body>
```

```
    <!-- Content Tags -->
```

```
  </body>
```

```
</html>
```

Apna College

Window Object

The window object represents an open window in a browser. It is browser's object (not JavaScript's) & is automatically created by browser.


It is a **global** object with lots of properties & methods.

What is DOM?

console.log() - Displays something written inside bracket
console.dir() - Displays properties and methods of special objects like html

When a web page is loaded, the browser creates a **Document Object Model (DOM)** of the page

DOM does Dynamic Changes/Manipulations on HTML.



DOM Manipulation

Selecting with id

document.getElementById("myId")

for every element ID is unique. So it returns only 1 Object

Selecting with class

document.getElementsByClassName("myClass")

Selecting with tag

document.getElementsByTagName("p")

DOM Manipulation

Query Selector

document.querySelector("#myId / .myClass / tag")
//returns first element

Use # for ID and .(dot) for class as
.myClass and #myId

document.querySelectorAll("#myId / .myClass / tag")
//returns a NodeList

HTML or Document

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
  <link rel="stylesheet" href="/JavaScript/first.css">
</head>

<body>
  <h1>DOM: Document Object Model</h1>

  <div class="myClass">
    Hello from Div
    <p>Hello from P1</p>
    <p style="visibility: hidden;">Hello from P2</p>
    <p>Hello from P3</p>
    <p>Hello from P4</p>
  </div>
  <div class="myBox">Box 1</div>
  <div class="myBox">Box 2</div>
  <div class="myBox">Box 3</div>
  <p></p>
  <p>This is P1</p>
  <p>This is P2</p>
  <div id="id1">This is id1</div>
  <div id="id2">This is id2</div>
  <div id="id3">This is id3</div>
  <div id="id4">This is id4</div>
  <script src="first.js"></script>
</body>
</html>
```

CSS

```
#id1 {
  background-color: yellow;
}

.myBox {
  background-color:
  pink;
}
```

JavaScript

Do one by one by commenting others. otherwise it will create issues.

```
console.log(document);
console.dir(document.getElementsByTagName("p"));
let firstEl = document.querySelector(".myBox");
let allEl = document.querySelectorAll(".myBox");
console.log(firstEl);
console.log(allEl);
console.log(firstEl.tagName);
let inText = document.querySelector("div");
console.log(document.querySelector("div").innerText);
console.log(document.querySelector("div").innerHTML);
console.log(document.querySelector("div").textContent);
console.dir(document.body.children[0]);
console.dir(document.body.firstChild);
console.dir(document.body.lastElementChild);
```

DOM Manipulation


Properties

- **tagName** : returns tag for element nodes
- **innerText** : returns the text content of the element and all its children
Returns pure textual content of the element and its children.
- **innerHTML** : returns the plain text or HTML contents in the element
Returns text of the element and its children with their HTML tag.
- **textContent** : returns textual content even for hidden elements

suppose if <div style="visibility: hidden"> This is Hidden </div>
Though textContent will return the content of div tag.

Homework

DOM Tree has 3 types of nodes:
--> Text node
--> Comment Node
--> Element Node



Let's Practice

Qs. Create a H2 heading element with text - “Hello JavaScript”. Append “from Apna College students” to this text using JS.

Qs. Create 3 divs with common class name - “box”. Access them & add some unique text to each of them.

DOM Manipulation

Attributes

- `getAttribute(attr)` //to get the attribute value
- `setAttribute(attr, value)` //to set the attribute value

Style

- `node.style`

DOM Manipulation

Insert Elements

let el = document.createElement("div")

- `node.append(el)` //adds at the end of node (inside)
- `node.prepend(el)` //adds at the start of node (inside)
- `node.before(el)` //adds before the node (outside)
- `node.after(el)` //adds after the node (outside)

Delete Element

- `node.remove()` //removes the node

Let's Practice

Qs. Create a new button element. Give it a text “click me”, background color of red & text color of white.

Insert the button as the first element inside the body tag.

Qs. Create a `<p>` tag in html, give it a class & some styling.

Now create a new class in CSS and try to append this class to the `<p>` element.

**Did you notice, how you overwrite the class name when you add a new one?
Solve this problem using classList.**