

# Basic Data Structures: Arrays and Linked Lists

Neil Rhodes

Department of Computer Science and Engineering  
University of California, San Diego

Data Structures  
Data Structures and Algorithms

# Outline

1 Arrays

2 Linked Lists

```
long arr[] = new long[5];
```

```
long arr[5];
```

```
arr = [None] * 5
```

1	5	17	3	25
---	---	----	---	----

1	5	17	3	25
8	2	36	5	3

# Definition

Array:


Contiguous area of memory



# Definition

## Array:


Contiguous area of memory consisting of equal-size elements




## Definition

### Array:

Contiguous area of memory consisting of equal-size elements indexed by contiguous integers.




# What's Special About Arrays?



# What's Special About Arrays?

Constant-time access






# What's Special About Arrays?

Constant-time access


array\_addr



# What's Special About Arrays?

Constant-time access


$\text{array\_addr} + \text{elem\_size} \times ( \quad )$



# What's Special About Arrays?

Constant-time access

$\text{array\_addr} + \text{elem\_size} \times (i - \text{first\_index})$



# Multi-Dimensional Arrays


# Multi-Dimensional Arrays

(1, 1)					

# Multi-Dimensional Arrays

			(3,4)		

# Multi-Dimensional Arrays

			(3,4)		

$$(3 - 1) \times 6$$

# Multi-Dimensional Arrays

			(3,4)		

$$(3 - 1) \times 6 + (4 - 1)$$



# Multi-Dimensional Arrays

			(3,4)		

$$\text{elem\_size} \times ((3 - 1) \times 6 + (4 - 1))$$

# Multi-Dimensional Arrays

			(3,4)		

$$\text{array\_addr} + \\ \text{elem\_size} \times ((3 - 1) \times 6 + (4 - 1))$$

$(1, 1)$
$(1, 2)$
$(1, 3)$
$(1, 4)$
$(1, 5)$
$(1, 6)$
$(2, 1)$
$\vdots$

Row-major

$(1, 1)$
$(1, 2)$
$(1, 3)$
$(1, 4)$
$(1, 5)$
$(1, 6)$
$(2, 1)$
$\vdots$

Row-major

$(1, 1)$
$(1, 2)$
$(1, 3)$
$(1, 4)$
$(1, 5)$
$(1, 6)$
$(2, 1)$
$\vdots$

$(1, 1)$
$(2, 1)$
$(3, 1)$
$(1, 2)$
$(2, 2)$
$(3, 2)$
$(1, 3)$
$\vdots$

Row-major

$(1, 1)$
$(1, 2)$
$(1, 3)$
$(1, 4)$
$(1, 5)$
$(1, 6)$
$(2, 1)$
$\vdots$

Column-major

$(1, 1)$
$(2, 1)$
$(3, 1)$
$(1, 2)$
$(2, 2)$
$(3, 2)$
$(1, 3)$
$\vdots$

# Times for Common Operations

	Add	Remove
Beginning		
End		
Middle		

# Times for Common Operations

	Add	Remove
Beginning		
End		
Middle		

5	8	3	12			
---	---	---	----	--	--	--



# Times for Common Operations

	Add	Remove
Beginning	$O(1)$	
End		
Middle		

5	8	3	12	4		
---	---	---	----	---	--	--

# Times for Common Operations

	Add	Remove
Beginning	$O(1)$	
End		
Middle		

5	8	3	12	4		
---	---	---	----	---	--	--

# Times for Common Operations

	Add	Remove
Beginning		
End	$O(1)$	$O(1)$
Middle		

5	8	3	12			
---	---	---	----	--	--	--

# Times for Common Operations

	Add	Remove
Beginning		$O(n)$
End	$O(1)$	$O(1)$
Middle		

	8	3	12			
--	---	---	----	--	--	--

# Times for Common Operations

	Add	Remove
Beginning		$O(n)$
End	$O(1)$	$O(1)$
Middle		

8		3	12			
---	--	---	----	--	--	--

# Times for Common Operations

	Add	Remove
Beginning		$O(n)$
End	$O(1)$	$O(1)$
Middle		

8	3		12			
---	---	--	----	--	--	--

# Times for Common Operations

	Add	Remove
Beginning		$O(n)$
End	$O(1)$	$O(1)$
Middle		

8	3	12				
---	---	----	--	--	--	--

# Times for Common Operations

	Add	Remove
Beginning	$O(n)$	$O(n)$
End	$O(1)$	$O(1)$
Middle		

8	3	12				
---	---	----	--	--	--	--



# Times for Common Operations

	Add	Remove
Beginning	$O(n)$	$O(n)$
End	$O(1)$	$O(1)$
Middle	$O(n)$	$O(n)$

8	3	12				
---	---	----	--	--	--	--

# Summary

# Summary

- Array: contiguous area of memory consisting of equal-size elements indexed by contiguous integers.

# Summary

- Array: contiguous area of memory consisting of equal-size elements indexed by contiguous integers.
- Constant-time access to any element.

# Summary

- Array: contiguous area of memory consisting of equal-size elements indexed by contiguous integers.
- Constant-time access to any element.
- Constant time to add/remove at the end.

# Summary


- Array: contiguous area of memory consisting of equal-size elements indexed by contiguous integers.
- Constant-time access to any element.
- Constant time to add/remove at the end.
- Linear time to add/remove at an arbitrary location.

# Outline

1 Arrays

2 Linked Lists

# Singly-Linked List



Node contains:

- key
- next pointer



# List API

PushFront(Key)                      add to front

## List API

PushFront(Key)	add to front
Key TopFront()	return front item

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
	also known as Append

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
Key TopBack()	return back item

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
Key TopBack()	return back item
PopBack()	remove back item

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
Key TopBack()	return back item
PopBack()	remove back item
Boolean Find(Key)	is key in list?

## List API

PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
Key TopBack()	return back item
PopBack()	remove back item
Boolean Find(Key)	is key in list?
Erase(Key)	remove key from list



## List API

<code>PushFront(Key)</code>	add to front
<code>Key TopFront()</code>	return front item
<code>PopFront()</code>	remove front item
<code>PushBack(Key)</code>	add to back
<code>Key TopBack()</code>	return back item
<code>PopBack()</code>	remove back item
<code>Boolean Find(Key)</code>	is key in list?
<code>Erase(Key)</code>	remove key from list
<code>Boolean Empty()</code>	empty list?


## List API

<code>PushFront(Key)</code>	add to front
<code>Key TopFront()</code>	return front item
<code>PopFront()</code>	remove front item
<code>PushBack(Key)</code>	add to back
<code>Key TopBack()</code>	return back item
<code>PopBack()</code>	remove back item
<code>Boolean Find(Key)</code>	is key in list?
<code>Erase(Key)</code>	remove key from list
<code>Boolean Empty()</code>	empty list?
<code>AddBefore(Node, Key)</code>	adds key before node

## List API


PushFront(Key)	add to front
Key TopFront()	return front item
PopFront()	remove front item
PushBack(Key)	add to back
Key TopBack()	return back item
PopBack()	remove back item
Boolean Find(Key)	is key in list?
Erase(Key)	remove key from list
Boolean Empty()	empty list?
AddBefore(Node, Key)	adds key before node
AddAfter(Node, Key)	adds key after node

# Times for Some Operations




# Times for Some Operations

PushFront




# Times for Some Operations

PushFront




# Times for Some Operations

PushFront



# Times for Some Operations


PushFront  $O(1)$






# Times for Some Operations

PopFront




# Times for Some Operations

PopFront




# Times for Some Operations

PopFront  $O(1)$




# Times for Some Operations

PushBack  
(no tail)




# Times for Some Operations

PushBack  $O(n)$   
(no tail)




# Times for Some Operations

PopBack  
(no tail)




# Times for Some Operations

PopBack  $O(n)$   
(no tail)




# Times for Some Operations






# Times for Some Operations

PushBack  
(with tail)




# Times for Some Operations

PushBack  
(with tail)




# Times for Some Operations

PushBack  
(with tail)




# Times for Some Operations

PushBack  $O(1)$   
(with tail)




# Times for Some Operations

PopBack  
(with tail)




# Times for Some Operations

PopBack  
(with tail)




# Times for Some Operations

PopBack  
(with tail)



# Times for Some Operations

PopBack  $O(n)$   
(with tail)





# Singly-linked List

## PushFront(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*

*node.next*  $\leftarrow$  *head*

*head*  $\leftarrow$  *node*

if *tail* = nil:

*tail*  $\leftarrow$  *head*

# Singly-linked List

## PopFront()

```
if head = nil:  
    ERROR: empty list  
head  $\leftarrow$  head.next  
if head = nil:  
    tail  $\leftarrow$  nil
```

# Singly-linked List

PushBack(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*

*node.next* = nil

# Singly-linked List

## PushBack(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*

*node.next* = nil

if *tail* = nil:

*head*  $\leftarrow$  *tail*  $\leftarrow$  *node*

# Singly-linked List

## PushBack(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*

*node.next* = nil

if *tail* = nil:

*head*  $\leftarrow$  *tail*  $\leftarrow$  *node*

else:

*tail.next*  $\leftarrow$  *node*

*tail*  $\leftarrow$  *node*

# Singly-linked List

PopBack()

# Singly-linked List

PopBack()

```
if head = nil:  ERROR: empty list
```

# Singly-linked List

## PopBack()

```
if head = nil:  ERROR: empty list
if head = tail:
    head  $\leftarrow$  tail  $\leftarrow$  nil
```



# Singly-linked List

## PopBack()

```
if head = nil:  ERROR: empty list
if head = tail:
    head  $\leftarrow$  tail  $\leftarrow$  nil
else:
    p  $\leftarrow$  head
    while p.next.next  $\neq$  nil:
        p  $\leftarrow$  p.next
```

# Singly-linked List

## PopBack()

```
if head = nil:  ERROR: empty list
if head = tail:
    head  $\leftarrow$  tail  $\leftarrow$  nil
else:
    p  $\leftarrow$  head
    while p.next.next  $\neq$  nil:
        p  $\leftarrow$  p.next
    p.next  $\leftarrow$  nil; tail  $\leftarrow$  p
```

# Singly-linked List

AddAfter(*node*, *key*)

*node2*  $\leftarrow$  new node

*node2.key*  $\leftarrow$  *key*

*node2.next* = *node.next*

*node.next* = *node2*

if *tail* = *node*:

*tail*  $\leftarrow$  *node2*

Singly-Linked List	no tail	with tail
--------------------	---------	-----------

PushFront(Key)	$O(1)$	
----------------	--------	--

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$



Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	


Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	
Empty()	$O(1)$	


Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	
Empty()	$O(1)$	
AddBefore(Node, Key)	$O(n)$	

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	
Empty()	$O(1)$	
AddBefore(Node, Key)	$O(n)$	
AddAfter(Node, Key)	$O(1)$	

# Doubly-Linked List




# Doubly-Linked List






# Doubly-Linked List



Node contains:


- key
- next pointer
- prev pointer

# Doubly-Linked List




PopBack

# Doubly-Linked List




PopBack

# Doubly-Linked List




PopBack

# Doubly-Linked List



PopBack

# Doubly-Linked List



PopBack  $O(1)$

# Doubly-linked List

PushBack(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*; *node.next* = nil

# Doubly-linked List

## PushBack(*key*)

*node*  $\leftarrow$  new node

*node.key*  $\leftarrow$  *key*; *node.next* = nil

if *tail* = nil:

*head*  $\leftarrow$  *tail*  $\leftarrow$  *node*

*node.prev*  $\leftarrow$  nil



# Doubly-linked List

## PushBack(*key*)

```
node ← new node  
node.key ← key; node.next = nil  
if tail = nil:  
    head ← tail ← node  
    node.prev ← nil  
else:  
    tail.next ← node  
    node.prev ← tail  
    tail ← node
```

# Doubly-linked List

PopBack()

# Doubly-linked List

PopBack()

```
if head = nil:  ERROR: empty list
```

# Doubly-linked List

## PopBack()

```
if head = nil:  ERROR: empty list
if head = tail:
    head  $\leftarrow$  tail  $\leftarrow$  nil
```

# Doubly-linked List

## PopBack()

```
if head = nil:  ERROR: empty list
if head = tail:
    head  $\leftarrow$  tail  $\leftarrow$  nil
else:
    tail  $\leftarrow$  tail.prev
    tail.next  $\leftarrow$  nil
```

# Doubly-linked List

## AddAfter(*node*, *key*)

```
node2 ← new node  
node2.key ← key  
node2.next ← node.next  
node2.prev ← node  
node.next ← node2  
if node2.next ≠ nil:  
    node2.next.prev ← node2  
if tail = node:  
    tail ← node2
```

# Doubly-linked List

## AddBefore(*node*, *key*)

```
node2 ← new node  
node2.key ← key  
node2.next ← node  
node2.prev ← node.prev  
node.next ← node2  
if node2.next ≠ nil:  
    node2.prev.next ← node2  
if head = node:  
    head ← node2
```

Singly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	$O(n)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	
Empty()	$O(1)$	
AddBefore(Node, Key)	$O(n)$	
AddAfter(Node, Key)	$O(1)$	



Doubly-Linked List	no tail	with tail
PushFront(Key)	$O(1)$	
TopFront()	$O(1)$	
PopFront()	$O(1)$	
PushBack(Key)	$O(n)$	$O(1)$
TopBack()	$O(n)$	$O(1)$
PopBack()	<del><math>O(n)</math></del> $O(1)$	
Find(Key)	$O(n)$	
Erase(Key)	$O(n)$	
Empty()	$O(1)$	
AddBefore(Node, Key)	<del><math>O(n)</math></del> $O(1)$	
AddAfter(Node, Key)	$O(1)$	

# Summary

- Constant time to insert at or remove from the front.

# Summary

- Constant time to insert at or remove from the front.
- With tail and doubly-linked, constant time to insert at or remove from the back.

# Summary

- Constant time to insert at or remove from the front.
- With tail and doubly-linked, constant time to insert at or remove from the back.
- $O(n)$  time to find arbitrary element.

# Summary

- Constant time to insert at or remove from the front.
- With tail and doubly-linked, constant time to insert at or remove from the back.
- $O(n)$  time to find arbitrary element.
- List elements need not be contiguous.

# Summary

- Constant time to insert at or remove from the front.
- With tail and doubly-linked, constant time to insert at or remove from the back.
- $O(n)$  time to find arbitrary element.
- List elements need not be contiguous.
- With doubly-linked list, constant time to insert between nodes or remove a node.