


図面／規格
【Uボルト（鋼管用）】



単位:mm

ねじ径		M4 ※1			M5 ※1			W1/4-M6			W5/16-M8			W3/8-M10			W1/2-M12		
呼び寸法		3.5			4.37			5.23			6.80-7.03			8.25-8.85			11.20-10.65		
鋼管外径		P	H	E	P	H	E	P	H	E	P	H	E	P	H	E	P	H	E
6A	10.5							18※1	24※1	15※1									
8A	13.8				20	27	15	21	27	15	鉄 ステン レス	23 23	30 32	20 18					
10A	17.3	23	40	22				25	33	18	27	38	24	28	43	28			
15A	21.7	28	47	30	29	47	30	29.5	36	18	31	42	24	34	46	30			
20A	27.2	34	53	30	35	53	30	34	42	18	37	48	24	40	51	30	42	61	35
25A	34.0	40	60	30	41	60	30	41	49	25	44	54	25	46	59	30	48	68	35
32A	42.7				51	69	30	50.5	57	25	52	62	30	56	68	30	57	70	35
40A	48.6				57	74	30	57	68	25	59	67	30	62	74	30	63	81	35
50A	60.5	W5/8-M16			69	86	30	70	80	30	72	80	30	74	85	30	76	90	35
65A	76.3	d=14.20-14.56						84	96	30	86	96	30	88	107	35	90	107	45
80A	89.1	109	126	60				97	107	30	99	109	30	101	117	35	103	119	45
90A	101.6	122	138	60							112	130	35	115	132	35	116	131	45
100A	114.3	134	151	60	M20						124	142	35	126	145	35	129	150	45
125A	139.8	160	175	60	d=18.2						150	168	40	152	175	40	154	175	45
150A	165.2	186	202	60	190	212	70				176	194	40	180	200	40	182	201	45
175A	190.7	212	228	60										205	225	40	207	227	45
200A	216.3	236	254	60	239	263	70	M24						230	250	50	232	252	45
250A	267.4	286	308	60	289	315	70	d=21.80						280	305	50	282	308	50
300A	318.5	341	368	70	344	371	80	346	363	80				331	358	50	332	360	50
350A	355.6	376	401	70	377	403	80	383	399	80	M30※2			369	395	50	372	397	60
400A	406.4	426	454	70	429	455	80	434	446	80	d=27.50			420	446	50	422	448	60
450A	457.2	478	508	75	481	507	80	484	508	80	496	535	115	471	497	50			
500A	508.0	529	560	80	532	560	80	539	572	110	548	586	115						
550A	558.8							591	624	110	598	636	115						
600A	609.6	631	662	80	635	665	80	642	675	110	650	688	115						
650A	660.4							693	726	110	700	738	115						
700A	711.2							744	776	110									

※1 M4、M5、M6×6Aはステンレスのみ。 ※2 M30は鉄のみ