


図面／規格
【六角ナット（１種鉄M 2 5 以上黒皮）】



呼び	並目	m		s	
		基準寸法	許容差	基準寸法	許容差
M2	0.4	1.6	0 -0.25	4	0 -0.2
M2.3	0.4	1.8		4.5	
M2.5	0.45	2		5	
M2.6	0.45	2		5	
M3	0.5	2.4	0 -0.30	5.5	
M3.5	0.6	2.8		6	
M4	0.7	3.2	0 -0.30	7	0 -0.25
M4.5	0.75	3.6	±0.15	8	
M5	0.8	4	0 -0.30	8	
M6	1.0	5		10	
M7	1.0	5.5	0 -0.58	11	0 -0.8
M8	1.25	6.5		13	0 -0.7
M9	1.25	8	±0.8	17	0 -1.4
M10	1.5	8		17	
M12	1.75	10	±0.9	19	0 -1.2
M14	2.0	11	±0.9	22	

呼び	並目	m		s	
		基準寸法	許容差	基準寸法	許容差
M16	2.0	13	±0.9	24	0 -0.8
M18	2.5	15		27	
M20	2.5	16		30	
M22	2.5	18		32	
M24	3.0	19	±1.0	36	0 -1.0
M25	3.0	19		36	
M27	3.0	22		41	
M30	3.5	24		46	
M33	3.5	26	±1.2	50	0 -1.2
M36	4.0	29		55	
M39	4.0	31		60	
M42	4.5	34		65	
M45	4.5	36	±1.5	70	0 -1.4
M48	5.0	38		75	
M52	5.0	42		80	
M56	5.5	45		85	
M60	5.5	48	±1.5	90	0 -1.4
M64	6.0	51		95	
M68	6.0	54		100	