

PROGRAM NO-10

Develop a JavaScript program with Ajax (with HTML/CSS) for:

- a. Use ajax() method (without JQuery) to add the text content from the text file by sending ajax request.**
- b. Use ajax() method (with JQuery) to add the text content from the text file by sending ajax request.**
- c. Illustrate the use of getJSON() method in jQuery**
- d. Illustrate the use of parseJSON() method to display JSON values.**

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>AJAX Example</title>
  <link rel="stylesheet" href="styles.css">
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
    }

    button {
      padding: 10px 15px;
      font-size: 16px;
      margin-right: 10px;
    }

    #content {
      margin-top: 20px;
      border: 1px solid #ccc;
      padding: 10px;
      background-color: #f9f9f9;
    }
  </style>
</head>
<body>
  <h1>AJAX Example: Load Text Content</h1>
  <h2>a. AJAX without jQuery</h2>
  <button id="loadTextBtn">Load Text Content (Vanilla JS)</button>
  <div id="content-vanilla"></div>
```

```
<h2>b. AJAX with jQuery</h2>
<button id="loadTextBtnjQuery">Load Text Content (jQuery)</button>
<div id="content-jquery"></div>
```

<h1>jQuery JSON Example</h1>

```
<h2>c. Using getJSON()</h2>
<button id="loadJsonBtn">Load JSON Data</button>
<div id="content-json"></div>
```

```
<h2>d. Using parseJSON()</h2>
<button id="parseJsonBtn">Parse JSON Data</button>
<div id="content-parsed"></div>
```

```
<script>
    // AJAX without jQuery
    document.getElementById("loadTextBtn").addEventListener("click", function() {
        var xhr = new XMLHttpRequest();
        xhr.open("GET", "content.txt", true);
        xhr.onreadystatechange = function() {
            if (xhr.readyState === 4 && xhr.status === 200) {
                document.getElementById("content-vanilla").innerText = xhr.responseText;
            }
        };
        xhr.send();
    });
```

```
    // AJAX with jQuery
    $(document).ready(function() {
        $("#loadTextBtnjQuery").click(function() {
            $.ajax({
                url: "content.txt",
                method: "GET",
                success: function(data) {
                    $("#content-jquery").text(data);
                },
                error: function(jqXHR, textStatus, errorThrown) {
                    console.error("Error loading content: ", textStatus, errorThrown);
                }
            });
        });
    });

    // Using getJSON() to fetch JSON data
    $("#loadJsonBtn").click(function() {
```

```

$.getJSON("data.json", function(data) {
    let output = "<h3>Fetched JSON Data:</h3><pre>" + JSON.stringify(data,
null, 2) + "</pre>";
    $("#content-json").html(output);
}).fail(function() {
    $("#content-json").html("<p>Error loading JSON data.</p>");
});
});

```

```

// Using parseJSON() to parse JSON string and display values
$("#parseJsonBtn").click(function() {
    const jsonString = '{"name": "John", "age": 30, "city": "New York"}';
    const parsedData = $.parseJSON(jsonString);
    let output = `<h3>Parsed JSON Data:</h3>
        <p>Name: ${parsedData.name}</p>
        <p>Age: ${parsedData.age}</p>
        <p>City: ${parsedData.city}</p>`;
    $("#content-parsed").html(output);
});

```

```

</script>
</body>
</html>

```

content.txt

This is a sample text file content loaded via AJAX.

data.json

```

{
  "employees": [
    { "name": "Alice", "age": 28, "city": "Los Angeles" },
    { "name": "Bob", "age": 34, "city": "Chicago" },
    { "name": "Charlie", "age": 25, "city": "New York" }
  ]
}

```