GNU/Linux System Management Pardus Solution: COMAR COMAR Features Current State

COMAR: A new approach to System Management

gokmen@pardus.org.tr

Center of Research For Advanced Technologies Of Informatics And Information Security
TÜBİTAK/BİLGEM

Brussels, Belgium February 05, 2011



Basics

- Package Management
- Service Management
- Network Management
- Boot Management
- Disk Management
- User Management
- Firewall Management
- o ...





Current Problems

- Each library has different API and it is not easy to make universal interfaces for the same purposes
- ② GUI or CLI code includes operational code so its hard to use operational code from different apps
- 3 Application base authentication (GUI or Cli) and it is not possbile to set privileges atomically
- Different apps can modify same data and syncronization between these apps is not an easy issue to solve



Current Problems








What is COMAR?

What is COMAR?

Comar (pronounced chow-mar), is the COnfiguration MAnageR that helps the installed software operate flawlessly. Comar knows the tasks that can be provided by each application, together with the functionality they depend on and other information. Different applications may adapt themselves according to the presence and capability of their peers.



What is COMAR?





Shared Models

Different scripts for same model Language independent usage Authentication using Polkit Applications are synced


Shared Models

```
<comarModel>
  <interface name="Disk.Manager">
    <method name="getDevices" access_label="get">
      <arg name="devices" type="as" direction="out"/>
    </method>
    <method name="mount" access label="mount">
      <arg name="device" type="s" direction="in"/>
      <arg name="path" type="s" direction="in"/>
    </method>
    <method name="umount" access_label="mount">
      <arg name="device" type="s" direction="in"/>
    </method>
  </interface>
</comarModel>
```



Different scripts for same model

Each package can provide different script for the same model





Using D-Bus



Using Python

```
import comar
link = comar.Link()
link.Disk.Manager["mudur"].getDevices()
dbus.Array([dbus.String(u'/dev/sda'), ..))
```



Using Shell

```
~ > hav call mudur Disk.Manager getDevices
dbus.Array([dbus.String(u'/dev/sda'), ..))
```



Provides atomic privileges

```
> cat /usr/share/polkit-1/actions/tr.org.pardus.comar.user.manager.policy
. . .
<policyconfig>
    <vendor>Pardus</vendor>
    <vendor_url>http://www.pardus.org.tr</vendor_url>
    <icon_name>system-users</icon_name>
    <action id="tr.org.pardus.comar.user.manager.adduser">
        <description>Add user</description>
        <message>System policy prevents adding new user
       <defaults>
            <allow_any>auth_admin_keep</allow_any>
            <allow_active>auth_admin_keep</allow_active>
            <allow_inactive>auth_admin_keep</allow_inactive>
       </defaults>
    </action>
</policyconfig>
```


COMAR call Polkit agent when necessary

~ > hav call openssh System.Service stop






Managing privileges over User Manager






When you change a service state everybody knows it



System Management in Pardus 2011





Thanks

- Questions ?
- Demo ?
- Home Page: http://www.pardus.org.tr
- Developer Page: http://developer.pardus.org.tr
- E-Mail Lists: http://lists.pardus.org.tr
- Bugzilla: http://bugs.pardus.org.tr
- Wiki: http://en.pardus-wiki.org

