

Publications List

Hitaishi V

email: hitaishi2222@gmail.com

Google Scholar link: [g-scholar](https://scholar.google.com/citations?user=hitaishi2222)

- [1] H. V., N. Ashok, S. K. Reddy, and S. Pidishety, “Supercontinuum Generation: A Comprehensive Review of Experimental and Material Advances,” *Applied Materials Today*, vol. 45, p. 102804, Aug. 2025, doi: [10.1016/j.apmt.2025.102804](https://doi.org/10.1016/j.apmt.2025.102804).
- [2] J. Kulanthaivel, V. Hitaishi, and N. Ashok, “A Tamm-Fano Resonance Glucose Sensor Based on Cu and Distributed Bragg Reflector Plasmonic Coupling Interface in the near-Infrared Regime,” *Optical and Quantum Electronics*, vol. 56, no. 9, p. 1538, Sep. 2024, doi: [10.1007/s11082-024-07396-2](https://doi.org/10.1007/s11082-024-07396-2).
- [3] V. Hitaishi, J. Kulanthaivel, and N. Ashok, “Effects of Waveguide Dimensions on Split-Core Optical Waveguide for Dispersion and Supercontinuum Applications,” *Journal of Computational Electronics*, vol. 24, no. 3, p. 71, Jun. 2025, doi: [10.1007/s10825-025-02311-8](https://doi.org/10.1007/s10825-025-02311-8).
- [4] V. Hitaishi, J. Kulanthaivel, and N. Ashok, “Study of Supercontinuum Generation in Etch-Coated Tellurium Based Chalcogenide Waveguide,” *Optical and Quantum Electronics*, vol. 56, no. 11, p. 1814, Nov. 2024, doi: [10.1007/s11082-024-07743-3](https://doi.org/10.1007/s11082-024-07743-3).
- [5] V. Hitaishi and A. Nandam, “Mid-IR Supercontinuum Generation Using a Slab with D-shaped/Semi-Ellipse Core Waveguide at $4\mu\text{m}$,” *Optical Materials*, vol. 147, p. 114668, Jan. 2024, doi: [10.1016/j.optmat.2023.114668](https://doi.org/10.1016/j.optmat.2023.114668).
- [6] V. Hitaishi, J. K., and N. Ashok, “Inverted Rib-Core Chalcogenide Waveguide for Supercontinuum Generation,” in *2023 IEEE Workshop on Recent Advances in Photonics (WRAP)*, Prayagraj, India: IEEE, Dec. 2023, pp. 1–3. doi: [10.1109/WRAP59682.2023.10712858](https://doi.org/10.1109/WRAP59682.2023.10712858).
- [7] V. Hitaishi, K. Jayakrishnan, and N. Ashok, “Design and Analysis of Chalcogenide GeAsSe Waveguide for Dispersion Properties,” *Advanced Nanomaterials and Their Applications*, vol. 22. Springer Nature Singapore, Singapore, pp. 87–96, 2023. doi: [10.1007/978-981-99-1616-0_9](https://doi.org/10.1007/978-981-99-1616-0_9).
- [8] V. Hitaishi and N. Ashok, “Broadband Supercontinuum Generation Using Dispersion Engineered As_2Se_3 -GeAsSe-GeAsS Waveguide at $6\mu\text{m}$,” *IEEE Access*, vol. 11, pp. 12294–12302, 2023, doi: [10.1109/ACCESS.2023.3242692](https://doi.org/10.1109/ACCESS.2023.3242692).
- [9] J. Kulanthaivel, V. Hitaishi, and N. Ashok, “Slot Waveguide Microring Resonator Based on Silicon Nitride for Refractive Index Sensing,” in *2022 IEEE International Conference on Nanoelectronics, Nanophotonics, Nanomaterials, Nanobioscience & Nanotechnology (5NANO)*, Kottayam, India: IEEE, Apr. 2022, pp. 1–3. doi: [10.1109/5NANO53044.2022.9828972](https://doi.org/10.1109/5NANO53044.2022.9828972).