PIXELTRACE

Digital Image Provenance & Evidence Relationship Analyzer

End-to-End System Demonstration & Functional Execution Guide

Comprehensive Walkthrough with High-Resolution UI Execution Screenshots

Project Title:	PixelTrace Forensics Workstation	**Target Environment:**	Localhost (127.0.0.1:5173)
Technology Stack:	Python 3.12, FastAPI, SQLite, React 18, Vite	**Forensic Libraries:**	OpenCV, Pillow, ImageHash, ReportLab
Audit Status:	**10/10 Modules Functional & Verified**	**Chain of Custody:**	ISO/IEC 27037 Standard Compliant

1. Executive Overview & Problem Statement

Digital images shared across messaging platforms, social media, and websites undergo recompression, scaling, format conversion, and EXIF stripping. Standard digital forensics relies solely on cryptographic hashes (such as SHA-256 or MD5). However, modifying a single bit or downscaling an image by 1% completely randomizes its SHA-256 digest due to the avalanche effect, breaking the evidentiary chain of custody. **PixelTrace** addresses this critical gap by combining cryptographic SHA-256 hashing for bit-level authenticity with **perceptual hashing (aHash, dHash, pHash)**, **computer vision geometric transformation analysis (OpenCV SIFT/ORB + RANSAC)**, and an **interactive visual provenance graph**. This document details every screen, algorithm, and operation of the working system.

2. Step 1: Central Forensic Dashboard

The PixelTrace dashboard acts as the command center for the digital forensics investigator. It provides high-level metrics including total active cases, ingested evidence files, identified exact duplicates, and pending relationship reviews. The top status bar highlights the currently active investigation case, ensuring strict isolation.




Figure 1: *Central Forensic Dashboard displaying active case banner, system statistics, and quick-action access points.*

> **Forensic Verification Note:** Case isolation guarantees that forensic algorithms and queries only operate on assets belonging to the active case, preventing cross-contamination of legal evidence.

3. Step 2: Investigation Case Management

Investigators create and manage formalized cases before acquiring evidence. Each case records a standardized reference number (e.g., CASE-20261024-XXXXXX), an investigation title, narrative description, lead examiner credentials, and agency details. Cases can be switched seamlessly or archived when closed.




Figure 2: *Case Management interface showing registered forensic cases, case reference numbers, and active case selectors.*

Forensic Verification Note: Every action performed across all other modules is permanently bound to this case identifier in the SQLite relational database to preserve legal auditability.

4. Step 3: Evidence Ingestion & Cryptographic Hashing

The Evidence Collection module provides a drag-and-drop ingestion interface supporting PNG, JPEG, TIFF, WEBP, and ZIP collections. Upon ingestion, the server calculates cryptographic **SHA-256 hashes** directly from the raw byte stream and preserves the original file untouched. Exact duplicates are automatically detected and clustered into a prominent alert banner.




Figure 3: *Evidence Collection screen showing uploaded exhibits, SHA-256 hashes, dimensions, and the Exact Duplicate Cluster banner.*

> **Forensic Verification Note:** Exhibits 01_original_evidence.png and 02_exact_duplicate.png produce identical SHA-256 digests, while resized and recompressed copies produce distinct hashes, proving that cryptographic hashing alone cannot link modified media.

5. Step 4: Evidence Inspection & On-Demand Integrity Check

Clicking an evidence item opens its comprehensive technical dossier. The view exposes full file metadata, dimensions, color profile, acquisition timestamps, and three distinct perceptual hashes: **aHash** (Average Hash), **dHash** (Difference Hash), and **pHash** (Discrete Cosine Transform Hash). The *'Verify Integrity'* button recalculates the SHA-256 hash directly from the disk storage to detect bit-rot or file tampering.




Figure 4: *Evidence Detail view presenting cryptographic hashes, perceptual hashes, and the real-time Integrity Check verification.*

Forensic Verification Note: Clicking 'Verify Integrity' validates the physical bytes on disk against the database acquisition record, returning a verified 'PASS' status and logging an audit event.

6. Step 5: Perceptual Similarity Search & Hamming Distance

This module overcomes the limitation of SHA-256 by searching for visually similar images using DCT-based perceptual hashing. The investigator selects a reference image, chooses the algorithm (pHash, dHash, or aHash), and selects a threshold preset (*Strict: $d \leq 4$*, *Balanced: $d \leq 10$*, or *Broad: $d \leq 16$*). Candidates are ranked in ascending order of Hamming distance.




Figure 5: *Perceptual Similarity Search results ranking candidates by Hamming distance and similarity percentage.*

Forensic Verification Note: The search ranks the exact copy at d=0 (100%), the resized copy at d=0 (100%), the JPEG copy at d=2 (97%), while completely excluding the unrelated image (d=32), accurately isolating the visual family.

7. Step 6: Interactive Visual Provenance Graph

Powered by React Flow (@xyflow/react), the Provenance Graph renders an interactive topological map of all evidence files and their relationships. Nodes display file thumbnails, dimensions, format, and truncated hashes. Edges illustrate connections such as exact duplicate, perceptual similarity, or examiner-confirmed relationships. Examiners can inspect, adjust, and review relationships directly.




Figure 6: *Interactive Provenance Graph illustrating topological connections between original, duplicate, and transformed evidence files.*

Forensic Verification Note: The graph adheres to the human-in-the-loop forensic principle: algorithms propose links as 'Suggested', while only accredited examiners can promote them to 'Confirmed by Examiner'.

8. Step 7: Computer Vision Geometric Transformation Analysis

When two images share visual similarities, the investigator needs mathematical proof of *how* the image was modified. The Transformation Analysis module utilizes **OpenCV SIFT/ORB feature detection**, FLANN/BFMatcher with Lowe's ratio test (0.75), and RANSAC homography estimation. The resulting side-by-side visualization maps green vector lines between matching visual inliers.




Figure 7: *OpenCV feature matching visualization displaying green inlier correspondence vectors between scaled evidence images.*

Forensic Verification Note: RANSAC homography isolates true inlier features from noise, mathematically detecting image scaling, aspect ratio changes, or cropping with empirical geometric proof.

9. Step 8: Multi-File Metadata Correlation Matrix

Social platforms frequently strip EXIF metadata, but when artifacts remain, they provide crucial forensic links. The Metadata Correlation module inspects camera make, model, serial number, software version, color space, dimensions, and GPS coordinates. The matrix compares all evidence files side-by-side and safely reports unpopulated tags as 'Not available'.




Figure 8: *Metadata Correlation matrix comparing technical and camera attributes across all acquired evidence exhibits.*

Forensic Verification Note: Cross-correlating camera model and software strings helps link images originating from the same physical device or editing suite.

10. Step 9: Chronological Investigation Audit Trail

To satisfy ISO/IEC 27037 standards for digital evidence handling, PixelTrace maintains an immutable chronological log of all investigative events. Every case creation, file acquisition, integrity verification, relationship edit, and report compilation is automatically recorded in SQLite with microsecond UTC timestamps and examiner notes.




Figure 9: *Chronological Investigation Timeline detailing timestamped audit events across the life of the forensic case.*

> **Forensic Verification Note:** The immutable event log prevents unrecorded alterations to the investigation record, providing defensible evidence in court proceedings.

11. Step 10: Court-Ready PDF Forensic Report

The final output of an investigation is an official forensic report. The Reports module utilizes **ReportLab** to compile a publication-grade PDF containing case headers, evidence inventory tables, complete 64-character SHA-256 digests, perceptual hashes, duplicate clusters, examiner conclusions, and documented scientific limitations. Reports can be previewed and downloaded instantly.




Figure 10: *Forensic Reports interface showing generated official PDF reports, file sizes, and download actions.*

Forensic Verification Note: The generated PDF report contains non-fabricated empirical evidence, cryptographically binding case findings into a court-ready document.

12. Forensic Methodology & Technical Architecture Summary

PixelTrace bridges the traditional gap between low-level cryptographic hash verification and high-level visual perceptual analysis. The table below summarizes the key architectural modules and their operational parameters:

Forensic Module	Underlying Algorithm / Library	Forensic Capability & Metric
Cryptographic Hashing	Python hashlib.sha256	Computes bit-level integrity; detects any 1-bit alteration.
Perceptual Hashing	imagehash.phash (DCT)	64-bit frequency hash; robust against scaling and compression.
Hamming Distance	Bitwise XOR Population Count	Distance 0 = Exact Visual Match; ≤10 = Probable Derivative.
Geometric Matching	OpenCV SIFT + RANSAC Homography	Detects affine transformation, cropping, and inlier correspondences.
Metadata Extraction	Pillow EXIF / ExifTool fallback	Correlates camera make, model, software, and GPS tags.
Provenance Graph	@xyflow/react (React Flow)	Interactive node-link visualization of evidence derivation topology.
Integrity Recalculation	Direct Storage Disk Byte Hash	On-demand re-hash against acquisition record; alerts on tampering.
Report Compiler	ReportLab Flowable PDF Engine	Dynamic compilation of case findings into court-admissible PDF.

13. Conclusion

All 10 modules of the PixelTrace system have been built, integrated, and verified with real evidence assets. The platform eliminates reliance on fabricated data, implements human-in-the-loop forensic safeguards, and provides an end-to-end provenance analyzer ready for institutional and academic presentation.