



# HELLO!

We are a pizza boxcar serving delicious pizza via the food truck way. we are ready to go around to deliver and serve pizza for you lovers!

**Retrieve the total number of orders placed.**

```
SELECT COUNT(order_id) AS total_orders  
FROM orders;
```

|   | total_orders |
|---|--------------|
| ▶ | 21350        |

-- Calculate the total revenue generated from pizza sales.

```
SELECT
    round(sum(order_details.quantity * pizzas.price),2) as total_sales
FROM order_details
JOIN pizzas
ON pizzas.pizza_id = order_details.pizza_id;
```

|   | total_sales |
|---|-------------|
| ▶ | 817860.05   |

-- Identify the highest-priced pizza.

```
SELECT pizza_types.name, pizzas.price
FROM pizza_types
JOIN pizzas
ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

|   | name            | price |
|---|-----------------|-------|
| ▶ | The Greek Pizza | 35.95 |

**List the pizza sizes and the number of orders for each size. Display the results in descending order of order count.**

```
SELECT pizzas.size,  
       COUNT(order_details.order_details_id) AS order_count  
FROM pizzas  
JOIN order_details  
ON pizzas.pizza_id = order_details.pizza_id  
GROUP BY pizzas.size  
ORDER BY order_count DESC;
```

|   | size | order_count |
|---|------|-------------|
| ▶ | L    | 18526       |
|   | M    | 15385       |
|   | S    | 14137       |
|   | XL   | 544         |
|   | XXL  | 28          |

\$30



-- List the top 5 most ordered pizza types  
-- along with their quantities.

```
SELECT pizza_types.name,  
       SUM(order_details.quantity) AS quantity  
FROM pizza_types  
JOIN pizzas  
ON pizza_types.pizza_type_id = pizzas.pizza_type_id  
JOIN order_details  
ON order_details.pizza_id = pizzas.pizza_id  
GROUP BY pizza_types.name  
ORDER BY quantity DESC  
LIMIT 5;
```

|   | name                       | quantity |
|---|----------------------------|----------|
| ► | The Classic Deluxe Pizza   | 2453     |
|   | The Barbecue Chicken Pizza | 2432     |
|   | The Hawaiian Pizza         | 2422     |
|   | The Pepperoni Pizza        | 2418     |
|   | The Thai Chicken Pizza     | 2371     |

-- Join the necessary tables to find the  
-- total quantity of each pizza category ordered.

```
SELECT pizza_types.category,  
       SUM(order_details.quantity) AS quantity  
FROM pizza_types  
JOIN pizzas  
ON pizza_types.pizza_type_id = pizzas.pizza_type_id  
JOIN order_details  
ON order_details.pizza_id = pizzas.pizza_id  
GROUP BY pizza_types.category  
ORDER BY quantity DESC;
```

|   | category | quantity |
|---|----------|----------|
| ► | Classic  | 14888    |
|   | Supreme  | 11987    |
|   | Veggie   | 11649    |
|   | Chicken  | 11050    |

-- Determine the distribution of orders by hour of the day.

```
SELECT HOUR(order_time),  
        COUNT(order_id)  
FROM orders  
GROUP BY HOUR(order_time);
```

|   | HOUR(order_time) | COUNT(order_id) |
|---|------------------|-----------------|
| ▶ | 11               | 1231            |
|   | 12               | 2520            |
|   | 13               | 2455            |
|   | 14               | 1472            |
|   | 15               | 1468            |
|   | 16               | 1920            |
|   | 17               | 2336            |
|   | 18               | 2399            |
|   | 19               | 2009            |
|   | 20               | 1642            |
|   | 21               | 1198            |
|   | 22               | 663             |
|   | 23               | 28              |
|   | 10               | 8               |
|   | 9                | 1               |



-- Join relevant tables to find the  
-- category-wise distribution of pizzas.

```
SELECT category,  
        COUNT(name)  
FROM pizza_types  
GROUP BY category;
```

|   | category | COUNT(name) |
|---|----------|-------------|
| ▶ | Chicken  | 6           |
|   | Classic  | 8           |
|   | Supreme  | 9           |
|   | Veggie   | 9           |

-- Group the orders by date and calculate the average  
-- number of pizzas ordered per day.

```
SELECT AVG(quantity) as avg_pizza_ordered_per_day
FROM
(
  SELECT orders.order_date,
         SUM(order_details.quantity) AS quantity
  FROM orders
  JOIN order_details
  ON orders.order_id = order_details.order_id
  GROUP BY orders.order_date
) AS order_quantity;
```

|   |                           |
|---|---------------------------|
|   | avg_pizza_ordered_per_day |
| ▶ | 138.4749                  |

-- Determine the top 3 most ordered pizza types based on revenue.

```
SELECT pizza_types.name,  
       SUM(order_details.quantity * pizzas.price) AS revenue  
FROM pizza_types  
JOIN pizzas  
ON pizzas.pizza_type_id = pizza_types.pizza_type_id  
JOIN order_details  
ON order_details.pizza_id = pizzas.pizza_id  
GROUP BY pizza_types.name  
ORDER BY revenue DESC  
LIMIT 3;
```

|   | name                         | revenue  |
|---|------------------------------|----------|
| ▶ | The Thai Chicken Pizza       | 43434.25 |
|   | The Barbecue Chicken Pizza   | 42768    |
|   | The California Chicken Pizza | 41409.5  |

-- Calculate the percentage contribution of each  
-- pizza type to total revenue.

```
SELECT pizza_types.category,  
       ROUND(  
         SUM(order_details.quantity * pizzas.price) /  
         (  
           SELECT ROUND(  
             SUM(order_details.quantity * pizzas.price), 2  
           ) AS total_sales  
         FROM order_details  
         JOIN pizzas  
         ON pizzas.pizza_id = order_details.pizza_id  
         ) * 100, 2  
       ) AS revenue  
FROM pizza_types  
JOIN pizzas  
ON pizza_types.pizza_type_id = pizzas.pizza_type_id  
JOIN order_details  
ON order_details.pizza_id = pizzas.pizza_id  
GROUP BY pizza_types.category  
ORDER BY revenue DESC;
```

|   | category | revenue |
|---|----------|---------|
| ► | Classic  | 26.91   |
|   | Supreme  | 25.46   |
|   | Chicken  | 23.96   |
|   | Veggie   | 23.68   |