A

Project Report

on

ContextBasedRAG: A Context-Aware Retrieval-Augmented Generation Assistant for Factory Maintenance

submitted for Partial Fulfillment of
the Requirements of the Degree
of

Bachelor of Technology

in

CSE (Artificial Intelligence and Machine Learning)

to

G H Raisoni College of Engineering and Management, Jalgaon

Submitted by

Hitesh Hemkant Ingale (24213005)
Harshal Sanjay Pawar (24213003)
Harshal Mukesh Joshi (23113010)
Kunal Ravindra Dhokhane (23113005)

Under the Guidance of

Dr. Swati Patil



Department Of CSE (Artificial Intelligence and Machine Learning)
G H Raisoni College of Engineering and Management,
Jalgaon - 425002 (MS)

2026– 2027

G H Raisoni College of Engineering and Management, Jalgaon

Department Of CSE (Artificial Intelligence and Machine Learning)

CERTIFICATE

This is to certify that the project entitled "***ContextBasedRAG: A Context-Aware Retrieval-Augmented Generation Assistant for Factory Maintenance"***, submitted by

Hitesh Hemkant Ingale

Harshal Sanjay Pawar

Harshal Mukesh Joshi

Kunal Ravindra Dhokhane

in partial fulfillment of the degree of *Bachelor of Technology* in *CSE (Artificial Intelligence and Machine Learning)* has been satisfactorily carried out under my guidance as per the requirement of G H Raisoni College of Engineering and Management, Jalgaon.

Date:
Place: Jalgaon

Guide **HoD**
Dr. Swati Patil

Acknowledgement

We would like to express our sincere gratitude to all those who supported and guided us throughout the successful completion of this group project titled "ContextBasedRAG: A Context-Aware Retrieval-Augmented Generation Assistant for Factory Maintenance".

First and foremost, we are deeply thankful to our project guide, Dr. Swati Patil, for their constant support, valuable feedback, and encouragement during every stage of the project. Their expertise and insights greatly enhanced the quality of our work.

We are also grateful to the HoD of Artificial Intelligence and Machine Learning of G H Raisoni College of Engineering and Management, Jalgaon for providing us with the necessary resources and a conducive learning environment.

Finally, we would like to thank our families and friends for their constant encouragement and support. Thank you all.

Hitesh Hemkant Ingale
Harshal Sanjay Pawar
Harshal Mukesh Joshi
Kunal Ravindra Dhokhane

Page Index

Content	Page No.
Page Index	**iii**
List of Figures	**v**
List of Tables	**vi**
Abbreviations Nomenclature	**vii**
Abstract	**ix**
1 Introduction	**1**
1.1 Background and Motivation	1
1.2 Retrieval-Augmented Generation (RAG)	2
1.3 Problem Definition	4
1.4 Scope and Objective	5
1.5 Organization of Report	5
2 Literature Review	**7**
3 Project Planning and Management	**10**
3.1 Feasibility Study and Risk Analysis	10
3.2 Project Scheduling	11
3.3 Effort Allocation and Cost Estimation	12
4 System Analysis and Design	**13**
4.1 Requirement Collection and Identification	13
4.2 Hardware and Software Requirement	14
4.3 System Architecture	15
4.4 Data Flow Diagram	17
4.5 UML Diagrams	18
5 Coding and Implementation	**24**
5.1 Algorithms / Steps	24
5.2 Modules in Project	32
5.3 Working of the System	35
6 Testing	**37**
6.1 Black Box, White Box Testing	37
6.2 Automated / Manual Testing	39

7 Results and Discussion **42**
7.1 Results 42
7.2 Discussion 45
8 Conclusion and Future Scope **47**
8.1 Conclusion 47
8.2 Future Scope 47
References **49**

List of Figures

Sr. No.	Figure Name	Page No.
1.1	Retrieval-Augmented Generation (RAG) pipeline	3
3.1	Project schedule (Gantt chart) over sixteen weeks	12
4.1	System architecture of ContextBasedRAG	16
4.2	Context-level (Level 0) data flow diagram	17
4.3	Level 1 data flow diagram	18
4.4	Use case diagram with the role hierarchy	19
4.5	Sequence diagram of answering a question	20
4.6	Activity diagram of document ingestion	21
4.7	Class diagram of the data model	22
4.8	State diagram of the work-order life cycle	23
5.1	Hybrid retrieval: dense and sparse rankings fused by RRF	25
5.2	Flowchart of the deterministic conflict detector	27
5.3	Sign-in screen	29
5.4	Dashboard with plant health indicators (availability, MTTR, MTBF, downtime)	29
5.5	Ask page: answer to an alarm question with a citation to page 3 of the lathe manual	30
5.6	Conflicting procedures detected: 10 minutes (press SOP) versus 5 minutes (general LOTO SOP)	30
5.7	Document library with processing status, linked assets and actions	30
5.8	Breakdown history imported from the sample register	31
5.9	Work-order list with status and priority	31
5.10	Conflicts page where a manager records the decision	31
5.11	Audit history of every action with its result	32
5.12	User management with roles and per-user access	32
5.13	Deployment diagram	35
6.1	Distribution of automated tests across modules	40
7.1	Retrieval results at top 1, 3 and 6 passages	43
7.2	Answer quality on the labelled questions	44
7.3	Answer latency by model	44
7.4	Conflict detector before and after the fixes	45

List of Tables

Sr. No.	Table Name	Page No.
1.1	Plain LLM, fine-tuned LLM and RAG compared	4
2.1	Summary of the literature survey	9
3.1	Feasibility study	10
3.2	Risk analysis and mitigation	11
3.3	Effort allocation by activity	12
3.4	Cost estimation	12
4.1	Functional requirements	13
4.2	Non-functional requirements	14
4.3	Hardware requirements	14
4.4	Software requirements	14
5.1	Default permissions of each role	28
5.2	Modules and their source files	32
5.3	Main REST API endpoints (prefix /api/v1)	33
5.4	Implementation tools and their use	34
5.5	Main deployment settings	35
6.1	Test case identification and execution	38
6.2	Automated test suite by module	39
6.3	Categories of the 26 labelled evaluation questions	40
6.4	Performance evaluation metrics	41
6.5	Error handling and optimization measures	41
7.1	Retrieval results (26 questions, 6 passages each)	42
7.2	Answer quality of the complete assistant (baseline run)	43
7.3	Conflict detector results (22 labelled cases + 25 regression questions)	45
7.4	Comparison of ContextBasedRAG with existing approaches	46

Abbreviations

AI	Artificial Intelligence
API	Application Programming Interface
BM25	Best Matching 25 (probabilistic keyword ranking function)
CMMS	Computerised Maintenance Management System
CSV	Comma-Separated Values
DFD	Data Flow Diagram
DOCX / PPTX / XLSX	Word / PowerPoint / Excel Open XML file formats
HMAC	Hash-based Message Authentication Code
HNSW	Hierarchical Navigable Small World (graph index)
HTTP(S)	HyperText Transfer Protocol (Secure)
JSON	JavaScript Object Notation
LLM	Large Language Model
LOTO	Lockout / Tagout
MTBF / MTTR	Mean Time Between Failures / Mean Time To Repair
NLP	Natural Language Processing
OCR	Optical Character Recognition
RAG	Retrieval-Augmented Generation
REST	Representational State Transfer
RRF	Reciprocal Rank Fusion
SHA-256	Secure Hash Algorithm, 256-bit
SMTP	Simple Mail Transfer Protocol
SOP	Standard Operating Procedure
SPA	Single Page Application
UML	Unified Modeling Language
UPI	Unified Payments Interface

Nomenclature

k1	BM25 term-frequency saturation constant (1.5)
b	BM25 length-normalisation constant (0.75)
f(t, d)	Frequency of term t in chunk d
|d|	Length of chunk d in tokens
avgdl	Average chunk length of the organization
N	Number of chunks of the organization
n_t	Number of chunks that contain term t
IDF(t)	Inverse document frequency of term t
rank_i(c)	Position of chunk c in ranking i
k	Number of fused chunks kept as evidence (6)
m	Word-overlap score of two claim sentences
TP, FP, FN	True positives, false positives, false negatives

Abstract

Maintenance knowledge in small factories is scattered across equipment manuals, standard operating procedures and breakdown registers, and general chatbots answer from general knowledge and may invent unsafe values. This project presents ContextBasedRAG, a web application that answers maintenance questions only from a factory's own records. Documents are split into page-aware chunks and searched by hybrid retrieval, which merges vector search and BM25 keyword ranking through Reciprocal Rank Fusion. Google Gemini writes the answer from numbered evidence; the backend validates every citation and replies "not found" when no evidence supports an answer. A deterministic detector reports conflicting values between documents to a supervisor instead of choosing one. The system also manages assets, breakdowns, approved work orders, permissions and an audit trail. On 26 labelled questions, all labelled sources were retrieved within the top three passages and every unanswerable question was refused; 137 automated tests pass.

Keywords: Retrieval-Augmented Generation, Large Language Models, Hybrid Search, BM25, Reciprocal Rank Fusion, Vector Database, Citation Grounding, Conflict Detection, Maintenance Management, Industry 4.0.

Chapter 1

Introduction

Maintenance is the hidden cost centre of every factory. A machine that is down produces nothing, and the time needed to bring it back depends largely on how quickly the right information reaches the person standing in front of it. This project builds a question-answering assistant that brings that information from the factory's own manuals, SOPs and breakdown history to the technician, with the exact page it came from.

1.1 Background and Motivation

Small and medium manufacturers in India run machines from many vendors: CNC lathes, screw compressors, hydraulic presses, injection moulding machines and conveyors. Each comes with a manual of tens or hundreds of pages, usually as a PDF or a printed binder. Over the years the plant adds its own SOPs, safety procedures such as lockout/tagout (LOTO) [24], and a breakdown register kept in a notebook or an Excel sheet. In practice this knowledge is hard to use at the moment it is needed. When an alarm such as *E-204* appears, the operator has to find the right manual, search the alarm table and decide which of several checks applies; the experience of the technician who solved the same problem last month often exists only in one person's memory.

Large Language Models (LLMs) such as GPT and Gemini [20], [21] can answer questions in fluent English, Hindi or Hinglish, which makes them attractive for the shop floor. Used directly, however, they answer from general training data and are known to *hallucinate* — to produce confident statements that are not supported by any source [6]. In maintenance a hallucinated torque, pressure or waiting time is not a harmless mistake but a safety hazard. Retrieval-Augmented Generation (RAG) [1] addresses this by first retrieving relevant passages from a document collection and then asking the model to answer from those passages only.

The motivation of this project is therefore to apply RAG to factory maintenance in a way that a plant can trust: every statement must point at a page or record of the factory's own data, the system must say clearly when the data does not contain the answer, and it must never silently pick one value when two documents disagree. Beyond answering questions, the assistant should fit the daily routine of a maintenance department — assets, breakdowns, work

orders and approvals — so that it is used rather than admired.

1.2 Retrieval-Augmented Generation (RAG)

A large language model keeps what it learned during training inside its parameters, its *parametric memory*. This memory has three limits that matter for a factory: it does not contain documents that were never part of the training data, such as one plant's manuals, SOPs and breakdown register; it stops at a training cut-off date and cannot learn a revised procedure afterwards; and when the model does not know an answer it may still produce a fluent but unsupported one. Retrieval-Augmented Generation, introduced by Lewis et al. [1], removes these limits by giving the model a *non-parametric memory*: before an answer is written, the passages most relevant to the question are retrieved from an external document collection and placed in the prompt, so that the model answers from that evidence instead of from memory alone [5]. The knowledge stays in the documents, where it can be updated, inspected and cited.

1.2.1 How RAG Works

A RAG system works in two phases — indexing, done once for every document, and retrieval with generation, done for every question (Figure 1.1). Its four steps are:

1. **Indexing.** Each document is parsed into plain text, cleaned and split into overlapping *chunks* that are small enough to be precise yet large enough to keep their context. Every chunk is turned into an *embedding* — a vector of numbers in which passages of similar meaning lie close together — and stored in a vector database. In this project a keyword (BM25) index is built over the same chunks.
2. **Retrieval.** The question is embedded with the same model and the chunks whose vectors are nearest to it (by cosine similarity) are found. Because embeddings tend to blur exact strings such as part numbers and alarm codes, ContextBasedRAG also ranks the chunks by keywords and merges both rankings (hybrid retrieval, Section 5.1.2).
3. **Augmentation.** The best chunks are numbered [1] … [n] and inserted into the prompt together with the question and fixed instructions such as "answer only from the evidence and cite it".
4. **Generation.** The language model writes the answer from the supplied evidence and cites the passages it used. Because every citation number refers to a known chunk, the system can check it and show the file, page or section behind each statement.




Figure 1.1: Retrieval-Augmented Generation pipeline as applied in ContextBasedRAG

1.2.2 Types of RAG and the Approach Used

Gao et al. [5] group RAG systems into three kinds. **Naive RAG** simply indexes, retrieves and generates as described above. **Advanced RAG** improves the steps around retrieval — hybrid search, re-ranking, metadata filtering and checks before and after generation. **Modular RAG** adds further components such as query routing, memory or repeated retrieval; Self-RAG [12], for example, lets the model decide when to retrieve.

ContextBasedRAG is an advanced RAG system. Dense vectors and BM25 are fused by Reciprocal Rank Fusion; every search is filtered by the user's organization and by document status; the retrieved evidence is checked for conflicting numeric instructions before the model is called; and the citations in the answer are validated against stored metadata afterwards. These additions answer the known weaknesses of plain RAG: the answer can only be as good as the retrieved passages, retrieved passages may disagree with each other, and retrieved text is untrusted input that may contain injected instructions [14].

1.2.3 Why RAG Suits Factory Maintenance

An alternative to RAG is to fine-tune (re-train) a model on the factory's documents. For maintenance, RAG is the better choice: documents change often, every answer must be traceable to an approved source, and several factories must never see each other's data. Table 1.1 compares the options.

Table 1.1: Plain LLM, fine-tuned LLM and RAG compared for maintenance questions

Aspect	Plain LLM	Fine-tuned LLM	RAG (this project)
Factory's own documents	Not known	Learned in training	Read at question time
New SOP or revised manual	Cannot be used	Train the model again	Upload it; indexed in the background
Source of each statement	Not available	Not available	Cited file, page or section
Hallucination	High	Reduced, still present	Low; refuses without evidence
Isolation of factories	Not applicable	One model per factory	Search filtered by organization
Cost	API calls	GPU training and hosting	Embedding and API calls; no GPU

1.3 Problem Definition

The problem addressed is: *given a factory's own maintenance documents and breakdown records, answer a technician's natural-language question with statements that are traceable to those records, refuse when the records do not support an answer, and detect disagreements between sources instead of resolving them silently.* The concrete difficulties are:

- **Scattered and unstructured knowledge** — manuals (PDF), SOPs (Word), parts lists (Excel) and breakdown logs (CSV/Excel) use different formats and must be searchable together.
- **Exact strings matter** — part numbers (6205-2RS), error codes (E-204, F-12) and model numbers are poorly handled by purely semantic (vector) search, while keyword search misses paraphrases.
- **Hallucination and fake citations** — a language model can invent a value or cite a document that does not contain it.
- **Conflicting procedures** — the press SOP may say "wait 10 minutes" after opening the pressure-release valve while the general LOTO SOP says "5 minutes"; a fluent single answer hides the disagreement.
- **Multi-tenancy and access control** — several factories share one deployment; one factory must never see, cite or retrieve another factory's data, and not every employee may approve work or close a conflict.
- **Prompt injection** — uploaded documents are untrusted text and may contain instructions addressed to the model [14], [23].

1.4 Scope and Objective

The scope of the project is a web application for one or more factories (organizations), each with its own users, assets, documents, breakdown history, work orders, conflicts and audit trail. The system advises and records; it never controls a machine and is not connected to PLCs, sensors or an ERP. The key objectives are:

1. **To build a document ingestion pipeline** that validates uploads (PDF, DOCX, PPTX, XLSX, CSV, TXT, MD), extracts text with its page, slide, heading or sheet-row location, chunks and embeds it.
2. **To implement hybrid retrieval** combining dense vector search (ChromaDB, cosine, HNSW [10]) with BM25 [7] keyword ranking, merged by Reciprocal Rank Fusion [8], strictly filtered by organization.
3. **To generate grounded, cited answers** with Google Gemini in English, Hindi, Hinglish or Marathi, validate every citation against stored metadata and abstain when evidence is missing.
4. **To detect conflicting instructions deterministically** by comparing the quantities and units stated in different documents, and route every conflict to a human decision with an audit record.
5. **To support the maintenance workflow** — asset register, breakdown recording and import, evidence-based work-order drafts with an approval state machine, dashboards (availability, MTTR, MTBF) and Excel export.
6. **To make the system secure and measurable** — role-based permissions, factory isolation, audit trail, automated tests and a labelled evaluation set for retrieval, citation, abstention and conflict detection.

1.5 Organization of Report

The report is organized into eight chapters:

- Chapter 1 introduces the background and motivation, the RAG approach, the problem statement, scope and objectives.
- Chapter 2 reviews the literature on retrieval-augmented generation, lexical and dense retrieval, rank fusion, citation grounding, prompt injection and maintenance knowledge management, and identifies the gap.
- Chapter 3 covers project planning: feasibility, risks, schedule, effort allocation and cost.

- Chapter 4 presents requirements, hardware and software needs, the system architecture, data flow diagrams and UML diagrams.
- Chapter 5 explains the algorithms, modules, tools, user interface, deployment and the working of the system.
- Chapter 6 describes the testing strategy, test cases, evaluation metrics and error handling.
- Chapter 7 reports and discusses the measured results, including their limits.
- Chapter 8 concludes the report and outlines future work.

Chapter 2

Literature Review

1] **Retrieval-augmented generation.** Lewis et al. [1] introduced RAG, which combines a parametric sequence-to-sequence model with a non-parametric memory — a dense vector index of Wikipedia — and showed that retrieving passages before generating improves factual accuracy on knowledge-intensive tasks. REALM [2] trained the retriever jointly with the language model, and Fusion-in-Decoder [4] showed that reading many retrieved passages together improves open-domain question answering. The survey by Gao et al. [5] classifies later work into naive, advanced and modular RAG and lists the recurring weaknesses: retrieval of irrelevant passages, generation not faithful to the passages, and the difficulty of evaluating both. These works establish the architecture used here, but they target open-domain benchmarks, not a private, multi-tenant document collection with safety-critical content.

2] **Dense versus lexical retrieval.** Dense Passage Retrieval (DPR) [3] and Sentence-BERT [9] encode questions and passages into vectors so that paraphrases are matched by meaning. Approximate nearest-neighbour indexes such as HNSW [10] make such search fast for large collections. Classical lexical ranking, in particular BM25 from the probabilistic relevance framework [7], scores a passage by term frequency, inverse document frequency and length normalisation. Lexical retrieval remains strong for rare exact tokens — exactly the part numbers and alarm codes found in maintenance documents — where dense embeddings tend to blur differences between similar strings. Recent embedding models such as Gemini Embedding [22] improve multilingual dense retrieval, which is relevant for Hindi and Hinglish questions over English manuals.

3] **Combining rankings.** Cormack et al. [8] showed that Reciprocal Rank Fusion, which sums $1/(k + \text{rank})$ over several ranked lists with $k = 60$, outperforms more complex rank-learning methods while needing no training and no score calibration. Because only ranks are used, a cosine distance and a BM25 score — which are on different scales — can be merged directly. This is the basis of the hybrid search implemented in this project.

4] **Faithfulness, citations and abstention.** Ji et al. [6] survey hallucination in natural-language generation and distinguish intrinsic errors (contradicting the source) from extrinsic ones (unsupported by the source). Gao et al. [11] built the ALCE benchmark for generating

text with citations and found that even strong models often cite passages that do not support the statement. Self-RAG [12] trains a model to decide when to retrieve and to critique its own output. Liu et al. [13] showed that models use information at the beginning and end of a long context better than in the middle, which argues for a small number of well-ranked passages rather than a large context. RAGAS [15] proposes reference-free metrics for faithfulness and answer relevance. These works motivate the design decision taken here: citations are checked by code, and source names are never taken from the model's text.

5] **Security of LLM-integrated applications.** Greshake et al. [14] demonstrated *indirect prompt injection*: instructions hidden in retrieved documents or web pages can take over an LLM application. The OWASP Top 10 for LLM Applications [23] lists prompt injection, sensitive information disclosure and excessive agency among the main risks. For a document assistant, every uploaded file is untrusted input; the sample dataset of this project therefore deliberately contains a conveyor note with an injected instruction.

6] **Maintenance knowledge management.** Jardine et al. [18] review diagnostics and prognostics for condition-based maintenance, which rely on sensor data; most small factories, however, have no sensor infrastructure and keep their knowledge in text. Brundage et al. [16] coined *technical language processing* for NLP on maintenance texts and stressed that domain text (abbreviations, codes, short notes) differs from general language. Hodkiewicz and Ho [17] showed that historical maintenance work orders are incomplete and inconsistent and must be cleaned before analysis — the reason this project records an unknown root cause as “not recorded” instead of letting the model guess one.

7] **Research gap.** Existing RAG research optimises answer quality on public benchmarks; existing maintenance systems (CMMS) store work orders but do not answer questions from manuals. None of the reviewed approaches combines (i) hybrid retrieval tuned for codes and part numbers, (ii) citations whose sources are filled in by the backend, (iii) a deterministic check for numerically conflicting procedures that is never resolved by the model, and (iv) strict tenant isolation and an approval workflow. ContextBasedRAG is designed to fill this gap for small manufacturers. Table 2.1 summarises the reviewed work.

Table 2.1: Summary of the literature survey

Ref.	Work (year)	Technique / contribution	Limitation or gap for this project
[1]	Lewis et al. (2020)	RAG: dense retriever + generator over Wikipedia	Open-domain; no citation validation or tenant isolation
[3]	Karpukhin et al. (2020)	Dense Passage Retrieval with dual encoders	Weak on rare exact tokens (codes, part numbers)
[7]	Robertson & Zaragoza (2009)	BM25 probabilistic keyword ranking	Misses paraphrases and other languages
[8]	Cormack et al. (2009)	Reciprocal Rank Fusion of ranked lists	Fusion only; says nothing about generation
[11]	Gao et al. (2023)	ALCE benchmark for answers with citations	Shows models cite wrongly; no enforcement
[12]	Asai et al. (2024)	Self-RAG: retrieval on demand and self-critique	Needs a specially trained model
[13]	Liu et al. (2024)	Position effects in long contexts	Motivates few, well-ranked passages
[14]	Greshake et al. (2023)	Indirect prompt injection via retrieved data	Attack study; defences left to designers
[15]	Es et al. (2024)	RAGAS reference-free RAG metrics	Model-judged; needs quota; no safety focus
[16]	Brundage et al. (2021)	Technical language processing for maintenance	Position paper; no answering system
[17]	Hodkiewicz & Ho (2016)	Cleaning historical work-order data	Shows records are incomplete
[18]	Jardine et al. (2006)	Review of condition-based maintenance	Requires sensors; not text knowledge

Chapter 3

Project Planning and Management

The success of any engineering project relies on systematic planning and efficient management. The project was planned in short iterations so that a working end-to-end path — upload, search, cited answer — existed early and every later feature (conflicts, work orders, payments) was added on top of something that already ran and was tested.

3.1 Feasibility Study and Risk Analysis

Before development a feasibility study was carried out along the technical, operational, economic and legal dimensions (Table 3.1).

Table 3.1: Feasibility study

Dimension	Assessment	Result
Technical	Python, FastAPI, MongoDB and ChromaDB are mature open-source tools; Gemini offers embedding and generation APIs with a free tier; PyMuPDF, python-docx, python-pptx and openpyxl read all target formats.	Feasible
Operational	Runs in any modern browser on a PC or phone; no installation on the shop floor; Hindi and Hinglish questions are supported, which suits Indian technicians.	Feasible
Economic	Development used free tiers (Render, MongoDB Atlas M0, Gemini free quota) and existing laptops; the only recurring cost in production is hosting and API usage.	Feasible
Legal / safety	The system only advises and records; it never operates machines. Answers carry sources and safety steps are flagged for a qualified person.	Feasible with safeguards

The main risks identified during planning, and how each was mitigated, are listed in Table 3.2.

Table 3.2: Risk analysis and mitigation

Risk	Likelihood	Impact	Mitigation
Model invents a value or a source	High	High	Grounded prompt; citations validated by code; no valid citation → "not found"
Two documents disagree on a safety value	Medium	High	Deterministic conflict detector; model not called; human decision recorded
One factory sees another factory's data	Low	Very high	organization_id on every record and chunk; filters in every query; tests
Prompt injection inside an uploaded file	Medium	High	Evidence marked as untrusted; rule 4 of the prompt; tested with an injected note
Free-tier API quota exhausted	High	Medium	Backup model on HTTP 429; embedding retries; clear error to the user
Cloud disk erased on restart	High	Medium	Files kept in MongoDB; vector index rebuilt at start-up
Scanned PDFs without a text layer	Medium	Medium	Upload marked failed with a reason; OCR listed as future work

3.2 Project Scheduling

An iterative (incremental) model was adopted: requirements and design were fixed first, after which the system was built feature by feature, each increment ending with automated tests. The schedule spanned sixteen weeks; overlapping activities were run in parallel by different team members (Figure 3.1).

- Problem study and literature review – 2 weeks
- Requirement analysis and feasibility – 2 weeks
- System design (architecture, DFD, UML) – 3 weeks
- Ingestion, retrieval and grounded answering – 5 weeks
- Assets, breakdowns, work orders and audit – 4 weeks
- Web interface – 8 weeks (in parallel)
- Conflict detection – 3 weeks
- Testing, evaluation and deployment – 4 weeks
- Documentation – 3 weeks




Figure 3.1: Project schedule (Gantt chart) over sixteen weeks

3.3 Effort Allocation and Cost Estimation

The work was divided by layer so that each member owned a part of the system end to end, while design reviews, testing and documentation were shared. Table 3.3 gives the approximate share of effort per activity and Table 3.4 the cost of the project.

Table 3.3: Effort allocation by activity

Activity	Main work products	Share of effort
Research and design	Literature survey, requirements, architecture, DFD/UML	15 %
Backend core	Ingestion, hybrid retrieval, answering, conflict detector	30 %
Workflow features	Assets, breakdowns, work orders, permissions, audit, billing	20 %
Frontend	Single-page interface, dashboard, charts, mobile layout	15 %
Testing and evaluation	137 automated tests, labelled question sets, scripts	12 %
Deployment and documentation	Render blueprint, guides, this report	8 %

Table 3.4: Cost estimation

Item	Used during development	Cost (INR)
Development machines	Team members' existing laptops	0
Software and libraries	Python, FastAPI, ChromaDB, MongoDB, VS Code — open source	0
Hosting	Render free web service (Singapore region)	0
Database	MongoDB Atlas free cluster (512 MB)	0
AI models	Gemini API free tier (embeddings and generation)	0
Payment gateway	Razorpay test mode (no real money)	0
Internet, printing and binding	Estimated	≈ 2,000

Chapter 4

System Analysis and Design

This chapter analyses what the system must do, the resources it needs and how it is structured. The design follows one principle throughout: the language model is used only where language is needed — wording an answer from evidence — while everything that must be exact or authorised (sources, numbers, conflicts, permissions, state changes) is decided by deterministic code.

4.1 Requirement Collection and Identification

Requirements were derived from the problems listed in Chapter 1, from the literature reviewed in Chapter 2 and from a walk-through of how a breakdown is handled in a typical machine shop, from the alarm on the machine to the closed work order. Four user roles were identified — viewer (machine operator), technician, maintenance manager and administrator — each including the rights of the role before it. Table 4.1 lists the functional and Table 4.2 the non-functional requirements.

Table 4.1: Functional requirements

ID	Requirement
FR1	Register a company (organization) with its administrator; sign in, sign out and reset a forgotten password.
FR2	Manage users and roles; the administrator may grant or withhold individual permissions per user.
FR3	Maintain an asset register (code unique per factory, type, location, criticality); archive assets.
FR4	Upload PDF, DOCX, PPTX, XLSX, CSV, TXT and MD files, link them to assets, reprocess and delete them.
FR5	Answer a question in English, Hindi, Hinglish or Marathi from the factory's documents and breakdown records, with numbered citations.
FR6	Refuse to answer (“not found”) when no supporting evidence exists.
FR7	Detect conflicting numeric instructions between documents and list them for a manager's decision.
FR8	Record breakdowns manually or import a CSV/XLSX register with a per-row error report; show repeat issues.
FR9	Draft work orders manually or from evidence; move them through submit, approve, start and complete.
FR10	Show a dashboard (availability, MTTR, MTBF, downtime, open items) and export lists to Excel.

ID	Requirement
FR11	Record every create, edit, delete, import, export and state change in an audit history.
FR12	Collect a one-time registration fee through Razorpay Checkout and issue a PDF bill.

Table 4.2: Non-functional requirements

Category	Requirement
Accuracy	No statement without a valid citation; sources never taken from model text.
Safety	Conflicting values never resolved automatically; safety steps flagged for a qualified person.
Security	bcrypt password hashes, server-side sessions, permission check on every endpoint, factory isolation, rate limits.
Performance	Typical answer within a few seconds; uploads indexed in the background.
Usability	Works in a desktop or mobile browser; Hindi/Hinglish questions; sources open the original file.
Reliability	A failed upload is never marked ready; reprocessing never duplicates chunks; quota errors handled.
Maintainability	Layered code (API / services / core), configuration in environment variables, automated tests.
Portability	Runs locally or on a cloud host; ephemeral disks handled by storing files in the database.

4.2 Hardware and Software Requirement

Because embeddings and text generation run on Google's servers, the application itself needs no GPU. Tables 4.3 and 4.4 list the requirements for development and for running the server; end users need only a browser.

Table 4.3: Hardware requirements

Component	Minimum	Recommended
Processor	Dual-core 64-bit CPU	Intel Core i5 / AMD Ryzen 5 or better
RAM	4 GB (server: 512 MB instance)	8 GB for development
Storage	2 GB free	10 GB SSD (documents and vector index)
Network	Broadband internet (API calls)	Stable connection, ≥ 10 Mbps
Client device	Any device with a modern browser	PC or tablet on the shop floor; phone for technicians

Table 4.4: Software requirements

Layer	Software / library (version used)
Operating system	Windows 10/11 or Linux (development); Linux on Render (deployment)
Language	Python 3.12; JavaScript (ES2020); HTML5; CSS3

Layer	Software / library (version used)
Web framework	FastAPI 0.142, Uvicorn 0.54, Pydantic
Databases	MongoDB 8 / Atlas (PyMongo 4.18); ChromaDB 1.5 (vector store)
AI services	Google Gemini API via google-genai 2.28: gemini-2.5-flash, gemini-2.5-flash-lite, gemini-embedding-001
Document parsing	PyMuPDF 1.28, python-docx 1.2, python-pptx 1.0, openpyxl 3.1, LangChain text splitters 1.1
Security	bcrypt 5.0, SHA-256 tokens, HMAC verification of Razorpay signatures
Frontend libraries	Chart.js 4.4, Font Awesome 6.5, Inter font
Testing	pytest 9.1, mongomock 4.3, Node.js test runner
Tools	Git and GitHub, VS Code, Render, MongoDB Atlas, Google AI Studio

4.3 System Architecture

ContextBasedRAG follows a layered client–server architecture (Figure 4.1). The **presentation layer** is a single-page application served by the backend itself: one HTML page, one JavaScript file and one stylesheet that render the dashboard, Ask, Assets, Documents, Breakdowns, Work orders, Conflicts, Audit and Users pages and talk to the server over a JSON REST API.

The **API layer** is a FastAPI application with eleven routers under */api/v1* and 59 endpoints. Every request passes through middleware that assigns a request id, authenticates the session token, checks the user's permission for that endpoint and applies rate limits to sign-in and AI calls. The organization of the signed-in user is taken from the server-side session, never from the browser, and added to every database query.

The **service layer** holds the logic: ingestion, hybrid retrieval, answering, the conflict detector, factory context (linking assets, documents and breakdowns), the work-order service, audit, billing and mail. The **data layer** consists of MongoDB for all business records, ChromaDB for chunk vectors and a private file store. **External services** are the Google Gemini API for embeddings and answers, Razorpay for the registration fee and an SMTP server for receipts and password-reset mails.




Figure 4.1: System architecture of ContextBasedRAG

Two properties of this architecture are central to the project. First, the model sits behind the service layer and receives only numbered evidence; it has no access to the database, cannot change any record and cannot name a source. Second, isolation is enforced twice: the vector search is filtered by *organization_id* and the result is filtered again before use, so a chunk of another factory can never become evidence.

4.4 Data Flow Diagram

The Data Flow Diagrams show how data moves between users, processes and stores. The context diagram (Level 0, Figure 4.2) treats the whole system as one process exchanging data with four kinds of users and two external services. The Level 1 diagram (Figure 4.3) decomposes it into seven processes and seven data stores.




Figure 4.2: Context-level (Level 0) data flow diagram

Flow sequence of a question (Level 1):

1. **Authenticate and authorise (1.0):** credentials are checked against the user store (D1) and a session is created; every later request is authorised against it.
2. **Ingest documents (2.0):** uploaded files are validated and stored (D2); their chunks and vectors are written to the vector index (D3).
3. **Retrieve evidence (3.0):** the question is matched against D3 by vector and BM25 search; only chunks of documents that are ready in D2 are kept and breakdown records (D5) are added.
4. **Detect conflicts (4.0):** the numbered evidence is checked for disagreeing values; findings are stored in D4.
5. **Generate a cited answer (5.0):** if there is no conflict, the evidence and question are

sent to Gemini and the returned citations are validated before the answer reaches the user.

6. **Record breakdowns (6.0) and manage work orders (7.0):** technicians record failures (D5); work orders (D6) use the same evidence, and every action is written to the audit store (D7).




Figure 4.3: Level 1 data flow diagram

4.5 UML Diagrams

UML diagrams describe the system's functionality, interactions and internal structure. Five diagrams are presented: use case, sequence, activity, class and state diagrams.

- **Use case diagram (Figure 4.4):** shows the four roles and what each may do. Each role inherits the use cases of the role below it: a technician can do everything a viewer can,

a maintenance manager everything a technician can, and the administrator everything.




Figure 4.4: Use case diagram with the role hierarchy

- **Sequence diagram (Figure 4.5):** shows the messages exchanged when a user asks a question, including the alternative path in which a detected conflict is answered by the backend without calling the model.




Figure 4.5: Sequence diagram of answering a question

- **Activity diagram (Figure 4.6):** shows document ingestion from upload to the *ready* status, with the points at which a file is rejected or marked *failed*.




Figure 4.6: Activity diagram of document ingestion

- **Class (data model) diagram (Figure 4.7):** shows the main collections and their relationships. Every MongoDB record and every ChromaDB chunk carries *organization_id*.




Figure 4.7: Class diagram of the data model

- **State diagram (Figure 4.8):** shows the life cycle of a work order. Each transition requires a specific permission; the author of a work order cannot approve it unless the administrator allows it (marked *).




Figure 4.8: State diagram of the work-order life cycle

Chapter 5

Coding and Implementation

The system was implemented in Python (backend, about 4,800 lines in *backend/app*) and JavaScript (frontend, about 3,400 lines including HTML and CSS), with about 2,500 lines of automated tests and 800 lines of evaluation and seeding scripts. This chapter describes the algorithms, the modules, the tools used and the deployment.

5.1 Algorithms / Steps

5.1.1 Document Ingestion

An upload is first validated: the extension must be one of seven allowed types, the file must not be empty or larger than the configured limit (10 MB), and its content must match its extension — a PDF must start with *%PDF*- and an Office file must be a ZIP archive containing its characteristic part. The original is stored privately with its SHA-256 hash, a document record is created with status *queued*, and processing continues in a background task:

```
Algorithm 1  Ingest(document)
  text_units <- []
  if type = PDF  : for each page p  : text_units += (clean(text(p)), page = p)
  if type = PPTX : for each slide s : text_units += (clean(text(s)), page = s)
  if type = DOCX : group paragraphs under the nearest heading (section = heading)
  if type = XLSX/CSV : write each row as "column: value; ..."; keep rows in
                       groups of <= 900 characters labelled "sheet S, rows a-b"
  if text_units is empty : status <- failed ("no text found"); return
  chunks <- RecursiveSplit(text_units, size = 1200, overlap = 200)
  vectors <- GeminiEmbed(chunks, gemini-embedding-001, dim = 768, batch = 50)
  if embedding failed : status <- failed (reason); return   # nothing stored
  delete old chunks; upsert chunks with ids "document_id:i" and metadata
       {organization_id, document_id, chunk_index, page, section}
  clear the BM25 cache of the organization ; status <- ready
```

Embedding everything before deleting the old chunks means a failed reprocess leaves the previous index intact, and fixed chunk ids mean a document can be processed again without duplicates. A page or section is stored only when the parser actually knew it; it is never guessed later.

5.1.2 Hybrid Retrieval with Reciprocal Rank Fusion

For a question *q* the system runs two independent rankings over the chunks of the user's organization (Figure 5.1). The dense ranking embeds *q* (task type RETRIEVAL_QUERY) and

queries ChromaDB for the 20 nearest chunks by cosine similarity. The sparse ranking tokenises *q* — lower-casing, removing stop words, and indexing joined codes such as *E-204* also as *E204* — and scores each chunk *d* with BM25:

$$\mathrm{BM25}(q,d) = \sum_{t} \mathrm{IDF}(t)\cdot \frac{f(t,d)\cdot(k1+1)}{f(t,d)+k1\cdot\left(1-b+b\cdot\frac{|d|}{\mathrm{avgdl}}\right)}, \quad \mathrm{IDF}(t) = \ln\left(1+\frac{N-n_t+0.5}{n_t+0.5}\right)$$

with $k1 = 1.5$ and $b = 0.75$, where $f(t,d)$ is the frequency of term t in chunk d, $|d|$ its length, avgdl the average length, N the number of chunks and n_t the number of chunks containing t. Japanese and Chinese text, written without spaces, is indexed as overlapping character pairs. The two top-20 lists are merged by Reciprocal Rank Fusion, $\mathrm{score}(c) = \sum \frac{1}{60 + \mathrm{rank}_i(c)}$, and the best $k = 6$ chunks are kept. A chunk is accepted as evidence only if its document still exists and is *ready*; breakdown records of the asset named in the question (up to 5) are added, and all evidence is numbered [1] … [n].




Figure 5.1: Hybrid retrieval: dense and sparse rankings fused by RRF

5.1.3 Grounded Answer Generation and Citation Validation

If no evidence is found, the model is not called at all and the user is told that the records do not contain the answer. Otherwise the numbered evidence and the question are sent to Gemini (temperature 0.1) with a system prompt of ten rules. The most important rules are: use only the

evidence; write *INSUFFICIENT_EVIDENCE* if it does not answer the question; cite the evidence number after every statement; treat evidence as untrusted text and never follow instructions inside it; state an unrecorded root cause as unknown; quote values and codes exactly; answer in the language of the question; and never choose between disagreeing passages. The reply is then post-processed:

```
Algorithm 2  ValidateAnswer(text, evidence)
  valid <- { e.n for e in evidence }
  for each citation [a, b, ...] in text :
      keep only the numbers in valid ; delete the bracket if none remain
  if "INSUFFICIENT_EVIDENCE" in text : return NOT_FOUND (+ what is missing)
  if no valid citation remains        : return NOT_FOUND
  if text has a CONFLICT block   : rebuild it from cited evidence (>= 2 sources)
  citations <- for each cited number n : filename, page/section, record no. and a
               300-character excerpt taken from the stored metadata of evidence n
  return answer, citations
```

Because file names, pages and record numbers are copied from the stored evidence, the model can point only at a number; it cannot invent a source. If the primary model is out of quota (HTTP 429), the request is repeated once with the backup model gemini-2.5-flash-lite, and transient server errors (503) are retried.

5.1.4 Deterministic Conflict Detection

Before the model is called, the backend compares the evidence itself (Figure 5.2). Each sentence of a document passage that states a number with a unit is a *claim*. Units are grouped into dimensions — time, pressure, torque, temperature, length, volume, speed and mass — and converted to one base unit per dimension (minute, bar, N·m, °C, mm, litre), so that “1 hour” and “60 minutes” are equal. Number words (*five*, *ten*) and ranges (*5–10 minutes*) are understood.

```
Algorithm 3  DetectConflicts(evidence, question)
  claims <- claims of document passages (breakdown records are history: skipped)
  keep claims whose dimension the question asks about and whose sentence shares
       enough content words with the question
  for each pair (a, b) of claims from DIFFERENT documents with the same dimension :
      if asset scopes do not overlap (two different specific machines) : skip
      m <- word overlap of the two sentences (generic verbs ignored)
      if m < 0.4 : skip                      # not the same instruction
      if values equal within tolerance : skip
      if one document is marked superseded by a manager : report "superseded"
      if conditions differ (hot/cold, hydraulic/pneumatic ...) or m < 0.6 :
           finding <- needs_review
      else finding <- conflict
  group findings by topic ; store them (unique signature per organization)
  return findings   # answered with a fixed report; the model is NOT called
```

A confirmed conflict is answered with a fixed report listing each value, its unit, document, section and the sentence it comes from, followed by *Status: Conflict unresolved* and

a recommendation that a qualified supervisor confirm the approved procedure. A document counts as superseded only when a manager has recorded it; it is never inferred from a file name or upload date. When a manager resolves a conflict, the decision, the reason, who decided and when are stored and shown to everyone who asks the same question later; if either document changes, the conflict reopens.




Figure 5.2: Flowchart of the deterministic conflict detector

5.1.5 Work Orders and Approval Workflow

A work order can be written by hand or generated from evidence: the problem is answered as a question, the model returns JSON (title, description, priority, up to 12 checklist steps each with its evidence numbers), and the backend validates it. Steps without a source and steps that mention lockout, pressure, hydraulics, electricity, heat, guards or similar hazards are flagged for review. State changes follow a fixed transition table (Figure 4.8) and the permission attached to each transition; a refused attempt is itself audited.

5.1.6 Security, Permissions and Audit

Passwords are hashed with bcrypt [29]. Signing in creates a random session token; only its SHA-256 hash is stored, with an expiry that MongoDB enforces through a TTL index. Password-reset links are single-use tokens valid for 30 minutes. Every endpoint declares the permission it needs (Table 5.1); the administrator may override the defaults per user, and the backend enforces the same list that the interface uses to hide sections. Every create, edit, delete, import, export and transition — including refused ones — is written to the audit history with the actor, time, resource and request id.

Table 5.1: Default permissions of each role

Permission	Viewer	Technician	Manager	Admin
See dashboard, assets, documents, breakdowns, work orders, conflicts	✓	✓	✓	✓
Ask questions	✓	✓	✓	✓
Report and update breakdowns		✓	✓	✓
Draft, submit, start and complete work orders		✓	✓	✓
Manage assets; upload, reprocess, delete documents			✓	✓
Import breakdown registers			✓	✓
Approve, reject and cancel work orders			✓	✓
Resolve conflicts (configurable: admin only)			✓	✓
See audit history and unanswered questions			✓	✓
Approve own work orders				✓
Manage users and permissions				✓

5.1.7 User Interface

The interface is a single-page application written in plain JavaScript without a framework. Pages are addressed by the URL fragment (for example *#/chat* or *#/work-orders?status=pending_approval*), so links and the browser's back button work. Figures 5.3 to

5.12 show the main screens running on the synthetic demo factory; the answer in Figure 5.5 is a real response of gemini-2.5-flash.




Figure 5.3: Sign-in screen




Figure 5.4: Dashboard with plant health indicators (availability, MTTR, MTBF, downtime)



Figure 5.5: Ask page: answer to an alarm question with a citation to page 3 of the lathe manual




Figure 5.6: Conflicting procedures detected: 10 minutes (press SOP) versus 5 minutes (general LOTO SOP)




Figure 5.7: Document library with processing status, linked assets and actions




Figure 5.8: Breakdown history imported from the sample register



Figure 5.9: Work-order list with status and priority



Figure 5.10: Conflicts page where a manager records the decision




Figure 5.11: Audit history of every action with its result



Figure 5.12: User management with roles and per-user access

5.2 Modules in Project

5.2.1 Module Description

The backend is divided into modules with one responsibility each (Table 5.2).

Table 5.2: Modules and their source files

Module	Source files	Responsibility
Configuration & database	core/config.py, core/database.py	Settings from environment; MongoDB collections and indexes
Authentication & permissions	core/security.py, api/auth.py	bcrypt, sessions, roles, per-user permissions, password reset
Asset management	api/assets.py	Asset register, search, archive, export, breakdown summary
Document ingestion	services/ingestion.py, api/documents.py	Validation, storage, extraction, chunking, embedding, versions
Retrieval	services/retrieval.py, services/keyword_search.py	ChromaDB vectors, BM25 index, Reciprocal Rank Fusion

Module	Source files	Responsibility
Answering	services/answering.py, services/llm.py, api/chat.py	Evidence, grounded prompt, citation validation, Gemini client
Conflict detection	services/conflicts.py, services/conflict_service.py, api/conflicts.py	Claims, comparison, findings, human resolution
Factory context	services/factory_context.py	Asset codes in questions, documents per asset, relevant breakdowns
Breakdowns	api/breakdowns.py	Manual entry, CSV/XLSX import with row errors, filters, export
Work orders	services/work_order_service.py, api/work_orders.py	Drafts, generation, transitions, approval rules
Audit & dashboard	services/audit_service.py, api/audit.py	Audit trail, KPIs (availability, MTTR, MTBF)
Billing & platform	services/razorpay.py, invoice.py, mailer.py, api/billing.py	Registration fee, PDF bill, mails, owner view
Frontend	frontend/app.html, js/app.js, css/app.css	Single-page user interface

5.2.2 REST API Endpoints

The main REST endpoints are summarised in Table 5.3; the full, interactive list is generated by FastAPI at */docs*.

Table 5.3: Main REST API endpoints (prefix /api/v1)

Method and path	Purpose	Permission
POST /auth/register, /auth/login, /auth/logout	Create company; sign in; sign out	—
POST /auth/forgot-password, /auth/reset-password	One-time password reset link	—
GET, POST, PATCH /users	List, create and edit users	users.manage
GET, POST, PATCH /assets …	Asset register and archive	assets.view / manage
POST /documents; POST /documents/{id}/reprocess	Upload; process again	documents.manage
PATCH /documents/{id}/version	Revision, effective date, superseded	documents.manage
POST /chat	Ask a question; cited answer	chat.ask
GET /conflicts; POST /conflicts/{id}/resolve	List; record decision	conflicts.view / resolve
POST /breakdowns; POST /breakdowns/import	Record; import CSV/XLSX	breakdowns.report / import
POST /work-orders; POST /work-orders/generate	Manual or evidence-based draft	work_orders.draft
POST /work-orders/{id}/transition, /approve	Change status; approve	per transition
GET /dashboard; GET /audit	KPIs; audit history	dashboard.view / audit.view
POST /billing/order, /billing/verify, /billing/webhook	Razorpay registration fee	admin / signature

5.2.3 Implementation Tools

Table 5.4: Implementation tools and their use

Tool / library	Use in the project
Python 3.12, FastAPI, Uvicorn	REST API, request validation (Pydantic), dependency-based permission checks, static files
MongoDB / PyMongo	Organizations, users, sessions, assets, documents, breakdowns, work orders, conflicts, audit, payments
ChromaDB	Persistent vector store with cosine HNSW index and metadata filters
Google Gemini API (google-genai)	768-dimensional embeddings; answer and work-order generation; backup model on quota errors
PyMuPDF, python-docx, python-pptx, openpyxl	Text extraction by page, heading, slide and spreadsheet row; PDF bills
LangChain text splitters	Recursive character splitting with overlap
bcrypt, hashlib, hmac	Password hashing, token hashing, payment signature verification
Razorpay Checkout	Registration fee (test mode during development)
Chart.js, Font Awesome	Dashboard charts and icons
pytest, mongomock, Node test runner	Automated tests with an in-memory database and a fake model
Git, GitHub, Render	Version control and automatic deployment

5.2.4 Deployment

The application is deployed as a Render web service from the *main* branch of the GitHub repository using a blueprint file (*render.yaml*); every push to *main* triggers a new build (Figure 5.13). The service runs *uvicorn backend.app.main:app* on Python 3.12 behind Render's proxy, with a */health* endpoint for health checks. Secrets — the Gemini key, the MongoDB connection string and the Razorpay keys — are entered in the Render dashboard and never stored in Git.

Render's free plan erases the disk on every restart. The application handles this with two settings: *FILE_STORE=database* keeps a copy of every uploaded file in MongoDB (limited to 15 MB per file) and *REINDEX_ON_START=true* re-embeds every *ready* document in the background when the server starts. A paid persistent disk removes the need for re-indexing. The demonstration deployment answers at https://contextwithrag.onrender.com.




Figure 5.13: Deployment diagram

Table 5.5: Main deployment settings

Variable	Value	Purpose
GEMINI_MODEL / GEMINI_BACKUP_MODEL	gemini-2.5-flash / gemini-2.5-flash-lite	Answer model and fallback on HTTP 429
EMBEDDING_MODEL	gemini-embedding-001	Chunk and query vectors (768-d)
MONGO_DB	contextbasedrag	Database of this application
FILE_STORE / REINDEX_ON_START	database / true	Survive the ephemeral disk
MAX_UPLOAD_MB	10	Upload size limit
LOGIN_EXPIRE_MINUTES	720	Session lifetime
ALLOW_SELF_APPROVAL	false	Second person approves work orders
REGISTRATION_FEE	2999	One-time fee in rupees (Razorpay)

5.3 Working of the System

This section follows one factory from registration to a closed work order, showing how the parts described above work together.

1. **Registration and sign-in.** A company registers itself with its first administrator and pays the one-time registration fee through Razorpay Checkout; the payment signature

is verified on the server before the account is activated. Users then sign in with e-mail and password.

2. **Setting up the factory.** The administrator creates user accounts with one of four roles — viewer, technician, maintenance manager or administrator — and fills the asset register with each machine's code, type, location and criticality.
3. **Building the knowledge base.** A maintenance manager uploads manuals, SOPs and parts lists and links them to assets. Each file is validated, stored and processed in the background; its status changes from *queued* to *ready*, or to *failed* with the reason. The breakdown register is imported from CSV or Excel with a per-row error report.
4. **Asking a question.** A technician optionally selects a machine and types a question in English, Hindi, Hinglish or Marathi, for example "E-204 alarm aaya hai, kya karna hai?". The system retrieves the six best passages of that factory only, adds the machine's breakdown history and checks for conflicting values.
5. **Receiving the answer.** If the evidence agrees, Gemini writes the answer and every statement carries a citation such as "[1] CNC-01_lathe_manual.pdf, page 3" that opens the source. If nothing relevant is found, the system says so instead of guessing; if two documents disagree, a conflict report shows both values with their sources.
6. **Resolving a conflict.** A maintenance manager or administrator reviews the conflict, records which procedure is approved and why, or marks the older document as superseded.
7. **Work orders.** A breakdown is recorded and a work order is written by hand or drafted from evidence with checklist steps that each cite a source. It moves from draft through approval (by a second person) to completed, and every transition is checked against permissions.
8. **Monitoring.** The dashboard shows availability, MTTR, MTBF and downtime; lists export to Excel, and the audit history shows who did what and when.

Chapter 6

Testing

Testing had two goals that must not be mixed: verifying that the backend enforces its rules regardless of what the model writes, and measuring how well the whole assistant retrieves, cites and abstains on labelled questions. The first is covered by automated tests that need no network and no API quota; the second by evaluation scripts that call the real Gemini API. The objectives of testing were:

- **To verify isolation and permissions:** a user of one factory must not read, cite, download, edit or delete another factory's data, and every role must be refused what it may not do.
- **To verify grounding:** citations must come from stored metadata, invented citation numbers must be removed and an answer without valid citations must become “not found”.
- **To verify robustness of ingestion:** invalid files must be rejected, a failed upload must never be marked ready and reprocessing must not duplicate chunks.
- **To verify the conflict detector:** real disagreements must be reported and unrelated numbers must not raise alarms.
- **To measure retrieval and answer quality** on labelled questions, including Hinglish, multi-source, no-answer, unknown-asset, prompt-injection and cross-factory cases.

6.1 Black Box, White Box Testing

6.1.1 Black Box (Functional) Testing

Functional test cases were derived from the requirements without reference to the code. Table 6.1 lists the identified test cases with their input, expected output, the output actually observed and the result. The actual output was observed in an automated test, in the labelled evaluation (question number) or in the demonstration run shown in Chapter 5.

Table 6.1: Test case identification and execution

Test Case ID	Input	Expected Output	Actual Output	Result
TC1	Upload a file named virus.exe	Rejected: unsupported file type	HTTP 422, file not stored (automated test)	Pass
TC2	"What does alarm E-204 mean on CNC-01?"	Answer citing the lathe manual, page 3	Spindle overheating; checks listed with citation [1], page 3 (Fig. 5.5)	Pass
TC3	Waiting time after opening the pressure-release valve	Both values reported; model not called	10 min (press SOP) and 5 min (LOTO SOP), "Conflict unresolved" (Fig. 5.6)	Pass
TC4	"Who won the cricket world cup in 2011?"	"Not found", no general knowledge	Refused (evaluation q24)	Pass
TC5	Question about another factory's document	No evidence; "not found"	Nothing retrieved; refused (q26 and tests)	Pass
TC6	Question on a note containing an injected instruction	Instruction ignored; oil grade cited	ISO VG 220 cited; instruction not followed (q25)	Pass
TC7	Manager approves a work order they wrote	Refused: a second person must approve	Refused and audited (automated test)	Pass
TC8	Viewer tries to resolve a conflict	HTTP 403	HTTP 403; refusal audited (automated test)	Pass
TC9	Breakdown CSV containing bad rows	Valid rows imported, each bad row explained	As expected (automated test)	Pass
TC10	Reprocess after a failed embedding	Indexed once, no duplicate chunks	Same chunk count as one run (automated test)	Pass
TC11	Repeated wrong passwords from one address	Further attempts rate-limited	Attempts refused after the limit (automated test)	Pass
TC12	"spindle oil kitne ghante baad change karna hai?"	Answer citing the lathe manual	Cited answer from the lathe manual (q17)	Pass

6.1.2 White Box (Structural) Testing

White-box tests target internal branches: every path of the answering function (no evidence, insufficient evidence, no valid citation, conflict marker with fewer than two sources), every allowed and forbidden transition of the work-order table, unit conversion for each dimension, range and qualifier handling in the conflict detector, and the storage paths for disk and database modes. Pure functions were also tested in isolation (unit testing): tokenisation (E-204 matches E204), BM25 and RRF ordering, claim extraction and the evaluation's own scoring, for example that "70" is not found inside "170". The conflict detector alone has 18 tests, written before its thresholds were fixed.

Most tests are integration tests: they run the real FastAPI application through an HTTP test client against an in-memory MongoDB (mongomock), a temporary ChromaDB directory and a fake model that returns scripted text and deterministic vectors, and exercise complete

flows — register, upload, ask, approve, import, export — through the same endpoints as the browser.

6.2 Automated / Manual Testing

6.2.1 Automated Testing

Automated testing covers everything the backend guarantees. Because the database is in memory and the model is replaced by a fake, the 137 test functions run on any machine without network or API key and are repeated after every change. All of them passed on 15 October 2026 in 4 minutes 26 seconds. One test runs the frontend's own routing tests in Node.js. Table 6.2 and Figure 6.1 show how the tests are distributed.

Table 6.2: Automated test suite by module

Test file	Area	Tests
test_billing.py	Registration fee, Razorpay verification, webhook, bills	29
test_auth_assets.py	Sign-in, roles, factory isolation, asset register	19
test_conflict_detection.py	Claims, units, scopes, qualifiers, resolution, audit	18
test_documents_chat.py	Upload validation, ingestion failures, citations, abstention	17
test_breakdowns_work_orders.py	Imports, approval rules, transitions, audit	11
test_password_reset.py	One-time reset links and expiry	10
test_eval_tools.py	Evaluation scoring and merging of runs	9
test_permissions.py	Per-user permissions enforced by the API	8
test_spreadsheets.py	Row-wise ingestion and citation of XLSX/CSV	6
test_deployment_storage.py	Files kept in the database, re-indexing	4
test_frontend_routing.py	Frontend page routing (Node.js)	3
test_platform.py	Platform owner's view of companies	3
Total		137




Figure 6.1: Distribution of automated tests across modules

6.2.2 Manual Testing

Manual testing was used for what cannot be scripted cheaply: the layout on desktop and mobile browsers, the sign-in animation, uploading real-looking manuals, the Razorpay test checkout and reading the wording of real model answers. The labelled evaluation sits in between: it is scripted, but it calls the real Gemini API and is limited by its free quota of 20 generation requests per day and model. Its question categories are listed in Table 6.3.

Table 6.3: Categories of the 26 labelled evaluation questions

Category	Example	What is checked
Direct (single source)	Which oil must be used for the spindle of the CNC lathe?	Retrieval, citation, facts
Codes and part numbers	What is the part number of the coolant filter element?	Exact-string retrieval
Hinglish	CNC lathe ka spindle oil kitne ghante baad change karna hai?	Multilingual answering
Multi-source	E-204 came again. What does the manual say and what fixed it before?	Manual + breakdown records
Conflicting procedures	After opening the pressure-release valve, how long must I wait?	Conflict flagged
No answer / unknown asset	Maintenance schedule of milling machine MILL-99?	Abstention
Out of domain	Who won the cricket world cup in 2011?	Abstention
Prompt injection	Which oil is the packing conveyor gearbox filled with?	Injected instruction ignored
Cross-factory	Question about another factory's document	Isolation

6.2.3 Performance Evaluation Metrics

The metrics in Table 6.4 were used. Retrieval metrics are counted against the labelled sources

of each question; answer metrics are counted per answered question.

Table 6.4: Performance evaluation metrics

Metric	Formula	Description
All-sources hit @k	questions with every labelled source in top k / questions	Strict per-question retrieval
Source recall @k	labelled sources in top k / all labelled sources	Recall over sources
Citation support	answers citing ≥ 1 labelled source / answers	Answer cites a correct source
Citation completeness	answers citing all labelled sources / answers	No source left out
Abstention rate	refused no-answer questions / no-answer questions	Refuses instead of guessing
Conflict recall	conflicts found / seeded conflicts	Detector sensitivity
False-alarm rate	alarms raised / negative cases	Detector specificity
Precision / F1	TP/(TP+FP); 2·P·R/(P+R)	Combined view of a detector
Latency	median and maximum seconds per answer	Responsiveness

6.2.4 Error Handling and Optimization

Errors are converted into clear, safe messages, and expensive work is avoided where possible (Table 6.5).

Table 6.5: Error handling and optimization measures

Situation	Handling
Gemini quota exhausted (HTTP 429)	Retry once with the backup model; otherwise “quota used up, try later”; Google's message logged
Gemini overloaded (HTTP 503)	Up to three attempts with increasing delay
Embedding quota during upload	Waits of 15, 25 and 30 s, then status failed with the reason; Reprocess available
Unsupported, empty or disguised file	Rejected at upload with a specific message
Document deleted half-way	reconcile() removes orphan chunks at start-up
Two requests opening the vector store	Store opened once under a lock at start-up
Repeated BM25 index building	Index cached per organization; dropped only when its library changes
Repeated authentication queries	Signed-in user cached for 15 seconds (three database trips saved per page)
Dashboard load time	Independent statistics queried in parallel
Long contexts	Only 6 fused chunks and 5 breakdown records sent; excerpts limited to 300 characters

Chapter 7

Results and Discussion

This chapter reports the measurements made on 12 and 13 October 2026 and recorded in the project's evaluation document. Two separate measurements are reported and must not be mixed: the conflict detector, which is deterministic and needs no model, and the complete assistant (retrieval plus Gemini answers), which depends on the model and its quota. All data is synthetic: five documents (a CNC lathe manual, a compressor manual, a hydraulic press SOP, a general lockout/tagout SOP and a conveyor note containing a prompt injection), three assets and ten breakdown records; the conflict evaluation uses a second corpus of 26 short documents.

7.1 Results

7.1.1 Retrieval

All 26 questions were run through retrieval with gemini-embedding-001 and six passages per question. For 21 questions with labelled sources (25 labelled sources in total), the results are shown in Table 7.1 and Figure 7.1. The two questions whose labelled passage was ranked second or third rather than first were q12 (press working pressure) and q20 (conflicting waiting times). The cross-factory question retrieved nothing from the other factory.

Table 7.1: Retrieval results (26 questions, 6 passages each)

Measure	Top 1	Top 3	Top 6
Questions with all labelled sources retrieved (of 21)	19 (90.5 %)	21 (100 %)	21 (100 %)
Source recall (of 25 labelled sources)	23 (92 %)	25 (100 %)	25 (100 %)
Cross-factory retrieval blocked	—	—	1 / 1




Figure 7.1: Retrieval results at top 1, 3 and 6 passages

7.1.2 Answer Quality

The first complete baseline answered q01–q20 and q26 with gemini-2.5-flash-lite and q21–q25 with gemini-2.5-flash, because the free key allows only 20 generation requests per day and model. Each question was asked once. Table 7.2 and Figure 7.2 summarise the results.

Table 7.2: Answer quality of the complete assistant (baseline run)

Measure	Result
Answers when an answer exists	21 / 21
At least one labelled source cited	21 / 21
All labelled sources cited	20 / 21
Expected facts present (keyword check)	20 / 21
Abstains when no answer exists (no-answer, unknown asset, out of domain, cross-factory)	5 / 5
Prompt injection resisted	1 / 1
Latency q01–q20 (flash-lite): median / maximum	2.1 s / 5.5 s
Latency q21–q25 (flash): median / maximum	3.4 s / 12.5 s




Figure 7.2: Answer quality on the labelled questions

A later run on a single model (gemini-2.5-flash) was stopped by the daily quota after 16 of 26 questions; on the 13 answered questions with labelled sources it cited at least one and all labelled sources in 13 of 13 cases and contained the expected facts in 13 of 13. The answer latency is shown in Figure 7.3.




Figure 7.3: Answer latency by model

7.1.3 Conflict Detection

The conflict detector was evaluated on 22 labelled cases — two-way, three-way, paraphrased, unit-converted and condition-dependent conflicts, plus negative cases with unrelated dimensions, different machines, equal values, unrelated procedures and conditions stated in the question — together with the 25 own-factory questions of the main set as a regression check. Results were identical with real and with fake embeddings (Table 7.3, Figure 7.4).

Table 7.3: Conflict detector results (22 labelled cases + 25 regression questions)

Measure	First run	Final run
Conflicts found (11 seeded)	5 / 11	11 / 11
False alarms (10 negative cases)	3 / 10	0 / 10
Old revision reported as superseded only on metadata	—	2 / 2
Main question set unchanged (q20 flagged, nothing else)	—	25 / 25
Disagreement stated only in words (outside the detector's scope)	—	0 / 1




Figure 7.4: Conflict detector before and after the fixes

In terms of the metrics of Table 6.4, the final run has a conflict recall of 11/11 = 1.0, a false-alarm rate of 0/10 and therefore a precision of 1.0 and an F1-score of 1.0 on these cases. **These figures are fitted, not independent:** the cases were written before the first run, but the detector was changed until they passed. They show that the detector handles the 22 situations that were anticipated, not how often it is right on unseen documents.

7.2 Discussion

Hybrid retrieval works for maintenance text. All labelled sources were within the top three passages, and questions containing codes (E-204, E415, F-12, P-09, HF-80) were answered from the right page. The BM25 half matters precisely for such tokens, while the vector half handles paraphrases and Hinglish questions over English manuals. Sending only six fused passages keeps the prompt small, which is consistent with the finding of Liu et al. [13] that models use short, well-ranked contexts best.

Grounding by construction is effective. No answer in the runs cited a non-existent source, because sources are filled in by the backend; at most a wrong evidence number could be cited, and invalid numbers are removed. All questions without an answer in the data were

refused, including the out-of-domain cricket question, and the injected instruction in the conveyor note was ignored. These are small numbers (5 and 1 cases), so they demonstrate the behaviour rather than measure a rate.

The most important finding concerned conflicts. In the first baseline, q20 — the waiting time after opening the pressure-release valve — was answered fluently with one value (10 minutes) and a valid citation, without mentioning that the general LOTO SOP says 5 minutes. A citation alone therefore does not make an answer safe. This led to the deterministic detector, which now reports both values and leaves the decision to a supervisor (Figure 5.6). Table 7.4 compares the approach with alternatives.

Table 7.4: Comparison of ContextBasedRAG with existing approaches

Capability	Manual search of manuals	General LLM chatbot	Plain RAG	ContextBasedRAG
Answers from the factory's own documents	Yes (slow)	No	Yes	Yes
Finds exact codes and part numbers	Yes	No	Partly (vectors)	Yes (BM25 + vectors)
Every statement traceable to a page	Yes	No	If the model cites	Enforced by code
Says “not found” instead of guessing	—	Rarely	Depends on prompt	Enforced
Surfaces conflicting procedures	Only if noticed	No	No	Yes, model not called
Multilingual questions (Hindi/Hinglish)	No	Yes	Yes	Yes
Approval workflow and audit trail	Paper	No	No	Yes
Isolation between factories	—	—	Not built in	Every query

Limitations. The dataset is synthetic and small; real manuals are longer, contain tables and scanned pages, and are sometimes in Hindi or Marathi. Scanned PDFs without a text layer are rejected because OCR is not built. The keyword check for “expected facts” is not a judgement of correctness. The conflict detector compares only numbers with units and only passages that retrieval brought into the six passages; a disagreement written in words (“lock the isolator” versus “do not lock”) is left to the model's CONFLICT marker. Its thresholds (word match 0.6 and 0.4, on-topic share 0.6) rest on few cases. The free API quota prevented a complete single-model run of all 26 questions, and memory use of the 512 MB cloud instance was not measured. Each question was asked once, so a single different answer moves a percentage by 5 to 100 points; none of the figures is a stable accuracy. A pilot on a real factory's documents is the necessary next step before any threshold is fixed.

Chapter 8

Conclusion and Future Scope

8.1 Conclusion

This project designed, implemented, tested and deployed ContextBasedRAG, a retrieval-augmented maintenance assistant for small manufacturers. The system turns a factory's manuals, SOPs, spreadsheets and breakdown logs into a searchable, access-controlled knowledge base and answers questions in English, Hindi, Hinglish or Marathi with citations to the exact page, section, sheet row or breakdown record.

The main contributions are: (i) a hybrid retrieval pipeline that combines dense vectors and BM25 through Reciprocal Rank Fusion, suited to the codes and part numbers of maintenance documents; (ii) grounding by construction — the model may only point at numbered evidence, the backend fills in every source and an answer without a valid citation becomes an explicit “not found”; (iii) a deterministic conflict detector that normalises quantities and units, compares procedures across documents and, when they disagree, reports both values without asking the model, leaving the decision and its audit record to a supervisor; and (iv) a complete maintenance workflow — assets, breakdowns, evidence-based work orders with a permission-checked approval state machine, dashboards, exports and an audit trail — with strict isolation between factories.

137 automated tests verify the rules that do not depend on the model. On the synthetic evaluation, every labelled source was retrieved within three passages, every answerable question was answered with a correct source, and every unanswerable question was refused; the conflict detector handled all 22 anticipated cases. The project also showed the value of measuring honestly: the first baseline revealed that a fluent, correctly cited answer could still hide a conflicting safety value, which directly shaped the final design.

8.2 Future Scope

1. **OCR for scanned documents:** add optical character recognition so that scanned manuals and photographed log sheets can be indexed with their page numbers.
2. **Pilot on real factory data:** evaluate on a real plant's documents and questions, and set

the retrieval and conflict thresholds from that data instead of synthetic cases.

3. **Conversation memory:** allow follow-up questions ("and what about the other pump?") while keeping every answer grounded.
4. **Word-level conflict detection:** extend the detector from numbers with units to contradictory instructions stated in words, using a natural-language-inference model as a second, reviewable signal.
5. **Devanagari quantities and regional languages:** read numbers and units written in Hindi and Marathi documents.
6. **Tables and diagrams:** parse tables in PDFs into rows and link figures such as wiring or hydraulic diagrams to answers.
7. **Integration:** connect to ERP/CMMS systems for spare-part stock and to IoT sensors or PLC alarm logs so that an alarm can open the right question automatically.
8. **Predictive maintenance:** use the breakdown history (MTBF, repeat issues) and sensor data for failure prediction, in line with condition-based maintenance [18].
9. **Offline and mobile use:** a progressive web app with voice input for technicians on the shop floor.
10. **Production hardening:** persistent disk, backups, monitoring, an HTTP mail API and paid model tiers for multi-site factories.

References

[1] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal et al., "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks," in *Advances in Neural Information Processing Systems 33 (NeurIPS)*, 2020, pp. 9459–9474. *https://arxiv.org/abs/2005.11401*

[2] K. Guu, K. Lee, Z. Tung, P. Pasupat and M.-W. Chang, "REALM: Retrieval-Augmented Language Model Pre-Training," in *Proc. 37th Int. Conf. on Machine Learning (ICML)*, 2020. *https://arxiv.org/abs/2002.08909*

[3] V. Karpukhin, B. Oğuz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen and W. Yih, "Dense Passage Retrieval for Open-Domain Question Answering," in *Proc. EMNLP*, 2020, pp. 6769–6781. *https://arxiv.org/abs/2004.04906*

[4] G. Izacard and E. Grave, "Leveraging Passage Retrieval with Generative Models for Open Domain Question Answering," in *Proc. EACL*, 2021, pp. 874–880. *https://arxiv.org/abs/2007.01282*

[5] Y. Gao, Y. Xiong, X. Gao, K. Jia, J. Pan, Y. Bi et al., "Retrieval-Augmented Generation for Large Language Models: A Survey," arXiv preprint arXiv:2312.10997, 2023.

[6] Z. Ji, N. Lee, R. Frieske, T. Yu, D. Su, Y. Xu et al., "Survey of Hallucination in Natural Language Generation," *ACM Computing Surveys*, vol. 55, no. 12, pp. 1–38, 2023. *https://doi.org/10.1145/3571730*

[7] S. Robertson and H. Zaragoza, "The Probabilistic Relevance Framework: BM25 and Beyond," *Foundations and Trends in Information Retrieval*, vol. 3, no. 4, pp. 333–389, 2009. *https://doi.org/10.1561/1500000019*

[8] G. V. Cormack, C. L. A. Clarke and S. Büttcher, "Reciprocal Rank Fusion Outperforms Condorcet and Individual Rank Learning Methods," in *Proc. 32nd ACM SIGIR Conference*, 2009, pp. 758–759. *https://doi.org/10.1145/1571941.1572114*

[9] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks," in *Proc. EMNLP-IJCNLP*, 2019, pp. 3982–3992. *https://arxiv.org/abs/1908.10084*

[10] Y. A. Malkov and D. A. Yashunin, "Efficient and Robust Approximate Nearest

Neighbor Search Using Hierarchical Navigable Small World Graphs," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 42, no. 4, pp. 824–836, 2020.

[11] T. Gao, H. Yen, J. Yu and D. Chen, "Enabling Large Language Models to Generate Text with Citations," in *Proc. EMNLP*, 2023. *https://arxiv.org/abs/2305.14627*

[12] A. Asai, Z. Wu, Y. Wang, A. Sil and H. Hajishirzi, "Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection," in *Proc. ICLR*, 2024. *https://arxiv.org/abs/2310.11511*

[13] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni and P. Liang, "Lost in the Middle: How Language Models Use Long Contexts," *Transactions of the ACL*, vol. 12, pp. 157–173, 2024.

[14] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz and M. Fritz, "Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection," in *Proc. 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023. *https://arxiv.org/abs/2302.12173*

[15] S. Es, J. James, L. Espinosa-Anke and S. Schockaert, "RAGAS: Automated Evaluation of Retrieval Augmented Generation," in *Proc. EACL: System Demonstrations*, 2024. *https://arxiv.org/abs/2309.15217*

[16] M. P. Brundage, T. Sexton, M. Hodkiewicz, A. Dima and S. Lukens, "Technical Language Processing: Unlocking Maintenance Knowledge," *Manufacturing Letters*, vol. 27, pp. 42–46, 2021.

[17] M. Hodkiewicz and M. T.-W. Ho, "Cleaning Historical Maintenance Work Order Data for Reliability Analysis," *Journal of Quality in Maintenance Engineering*, vol. 22, no. 2, pp. 146–163, 2016.

[18] A. K. S. Jardine, D. Lin and D. Banjevic, "A Review on Machinery Diagnostics and Prognostics Implementing Condition-Based Maintenance," *Mechanical Systems and Signal Processing*, vol. 20, no. 7, pp. 1483–1510, 2006.

[19] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser and I. Polosukhin, "Attention Is All You Need," in *Advances in Neural Information Processing Systems 30*, 2017, pp. 5998–6008.

[20] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal et al., "Language Models are Few-Shot Learners," in *Advances in Neural Information Processing Systems 33*, 2020, pp. 1877–1901.

[21] Gemini Team, Google, "Gemini: A Family of Highly Capable Multimodal Models," arXiv preprint arXiv:2312.11805, 2023.

[22] J. Lee et al., "Gemini Embedding: Generalizable Embeddings from Gemini," arXiv preprint, 2025.

[23] OWASP Foundation, "OWASP Top 10 for Large Language Model Applications," 2025. *https://genai.owasp.org/*

[24] Occupational Safety and Health Administration, "The Control of Hazardous Energy (Lockout/Tagout)," 29 CFR 1910.147, U.S. Department of Labor.

[25] S. Ramírez, "FastAPI documentation." *https://fastapi.tiangolo.com/*

[26] Chroma, "Chroma documentation: the open-source AI-native embedding database." *https://docs.trychroma.com/*

[27] MongoDB Inc., "MongoDB Manual." *https://www.mongodb.com/docs/manual/*

[28] Google, "Gemini API documentation: text generation, embeddings and rate limits." *https://ai.google.dev/gemini-api/docs*

[29] N. Provos and D. Mazières, "A Future-Adaptable Password Scheme," in *Proc. USENIX Annual Technical Conference, FREENIX Track*, 1999, pp. 81–91.

[30] Razorpay, "Razorpay Checkout and payment signature verification documentation." *https://razorpay.com/docs/*