

ASSIGNMENT-02

NAME:K.HITESH

Hall Ticket:2303A51291

Batch:05

Q) Task 1: Word Frequency from Text File

❖ Scenario:

You are analyzing log files for keyword frequency.

❖ Task:

Use Gemini to generate Python code that reads a text file and counts word frequency, then explains the code.

❖ Expected Output:


- Working code
- Explanation
- Screenshot

Solution:

PROMPT

Generate a Python program in Google Colab that reads a text file and counts the frequency of each word.

CODE:



```
word_frequency_colab.ipynb > M4 Lab 2: Task 1 - Word Frequency Counter > M4 Task Description: > # Display results
+ Code + Markdown | ▶ Run All ⏮ Restart ⏹ Clear All Outputs | 📄 Jupyter Variables 📖 Outline ... Python 3.9.6

# Import required libraries
import string
from collections import Counter

[17] ✓ 0.0s Python ▾

# Create or upload a sample text file
# You can either upload a file or create one programmatically
sample_text = """Python is a powerful programming language. Python is widely used for data science.
Many developers love Python because it is easy to learn. Python has excellent libraries
for machine learning and artificial intelligence.

Data science requires Python skills. Machine learning projects often use Python.
Python is versatile and can be used for web development, automation, and data analysis.

The Python community is large and supportive. Python code is readable and clean.
Many universities teach Python as the first programming language.

In this lab, we explore Python. We use Python for analysis. Python makes coding fun
and efficient. The future of programming includes Python. Learning Python opens many
opportunities for developers."""

# Save sample text to a file
with open('sample_text.txt', 'w', encoding='utf-8') as f:
    f.write(sample_text)

print("Sample text file created!")

[18] ✓ 0.0s Python ▾

... Sample text file created!
```

word_frequency_colab.ipynb > M* Lab 2: Task 1 - Word Frequency Counter > M* Task Description: > # Display results

+ Code + Markdown | ▶ Run All ↺ Restart ≡ Clear All Outputs | Jupyter Variables ≡ Outline ... Python 3.9.6

LAB@
LAB@

```
def count_word_frequency(filename):  
    """  
    Read a text file and count the frequency of each word.  
  
    Args:  
        filename (str): Path to the text file to analyze  
  
    Returns:  
        Counter: Counter object with words as keys and frequencies as values  
    """  
    try:  
        # Open and read the file  
        with open(filename, 'r', encoding='utf-8') as file:  
            text = file.read()  
  
        # Convert to lowercase and remove punctuation  
        translator = str.maketrans('', '', string.punctuation)  
        text = text.translate(translator).lower()  
  
        # Split text into words  
        words = text.split()  
  
        # Count word frequencies using Counter  
        word_freq = Counter[str](words)  
  
        return word_freq  
  
    except FileNotFoundError:  
        print(f"Error: File '{filename}' not found.")  
        return None  
    except Exception as e:  
        print(f"Error reading file: {e}")  
        return None
```

[19] ✓ 0.0s Python ▾

```
# Execute the word frequency analysis  
filename = 'sample_text.txt'  
word_freq = count_word_frequency(filename)
```

[20] ✓ 0.0s Python ▾

⌵ ▶ ⏪ ⏩ ⏹ ... 🗑

⌵ ▶ ⏪ ⏩ ⏹ ... 🗑

```
# Display results  
if word_freq:  
    print("\n" + "="*50)  
    print("WORD FREQUENCY ANALYSIS")  
    print("="*50)  
  
    # Display top 20 most common words  
    print("\nTop 20 Most Frequent Words:")  
    print("-"*50)  
    print(f"{'Word':<20} {'Frequency':<15} {'Percentage':<15}")  
    print("-"*50)  
  
    total_words = sum(word_freq.values())  
  
    for word, count in word_freq.most_common(20):  
        percentage = (count / total_words) * 100  
        print(f"{'word':<20} {'count':<15} {'percentage':.2f}%")  
  
    print("-"*50)  
    print(f"\nTotal unique words: {len(word_freq)}")  
    print(f"Total words: {total_words}")  
    print("-"*50)
```

Python ▾

OUTPUT:

```
...
=====
WORD FREQUENCY ANALYSIS
=====

Top 20 Most Frequent Words:
-----
Word                Frequency    Percentage
-----
python              15          13.64%
is                   6           5.45%
and                  6           5.45%
for                   5           4.55%
programming          3           2.73%
data                 3           2.73%
many                 3           2.73%
learning             3           2.73%
the                   3           2.73%
language             2           1.82%
used                 2           1.82%
science              2           1.82%
developers           2           1.82%
machine              2           1.82%
use                  2           1.82%
analysis             2           1.82%
...

Total unique words: 64
Total words: 110
=====

Output is truncated. View as a scrollable element or open in a text editor. Adjust cell output settings...
```

CODE Explanation:

This Python program works by first importing the required modules to handle punctuation removal and word counting. The text file is opened in read mode and its content is read completely. Then, all punctuation marks are removed and the text is converted to lowercase so that words are counted correctly without case differences. After that, the text is split into individual words. The Counter function is used to count the number of times each word appears in the file. The program also includes error handling to display a message if the file is not found or if any other error occurs. Finally, the word frequencies are displayed in an organized format, making the output easy to understand

Q) Task 2: File Operations Using Cursor AI

❖ Scenario:

You are automating basic file operations.

❖ Task:

Use Cursor AI to generate a program that:

- Creates a text file
- Writes sample text
- Reads and displays the content


❖ Expected Output:


- Functional code
- Cursor AI screenshots

PROMPT:


Generate a simple Python program that demonstrates basic file operations. The program should create a text file, write some sample text into it, then read the content from the file and display it on the screen.

CODE:





OUTPUT:



CODE EXPLANATION:

This Python program demonstrates basic file operations by creating a text file, writing sample content to it, and then reading and displaying that content on the screen. It uses separate functions for writing and reading files to keep the code organized and clear. The program also includes exception handling to manage errors such as file access issues, ensuring smooth execution. The main() function controls the overall flow, and the program runs only when executed directly, making it a simple and effective example of file handling in Python.

Q)Task 3: CSV Data Analysis

❖ Scenario:

You are processing structured data from a CSV file.

❖ Task:

Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

❖ Expected Output:


➤ Correct output

➤ Screenshot

PROMPT:

Write Python code in Google Colab to read a CSV file and calculate mean, minimum, and maximum values using pandas.

CODE:



```
# Install required packages
!pip install --q google-generativeai pandas numpy

[1] ✓ 25.2s

Step 2: Import Libraries and Setup

import pandas as pd
import numpy as np
import google.generativeai as genai
import os
from IPython.display import display, HTML

print("Libraries imported successfully!")

[2] ✓ 10.1s

/Users/bodla.manishwar/Downloads/AI Assistant coding/AIC/.venv/lib/python3.9/site-packages/google/api_core/_python_version_warning.py:35: FutureWarning:
/Users/bodla.manishwar/Downloads/AI Assistant coding/AIC/.venv/lib/python3.9/site-packages/google/auth/_init_.py:54: FutureWarning:
/Users/bodla.manishwar/Downloads/AI Assistant coding/AIC/.venv/lib/python3.9/site-packages/google/oauth2/_init_.py:4: FutureWarning:
Libraries imported successfully!
/Users/bodla.manishwar/Downloads/AI Assistant coding/AIC/.venv/lib/python3.9/site-packages/tqdm/auto.py:21: TqdmWarning:
from .autonotebook import tqdm as notebook_tqdm
/var/folders/2j/c3s_kn1515dcmqydtw38y4gc80080gn/T/ipykernel_60221/4255226943.py:3: FutureWarning:
Do you want to install the recommended
'Rainbow CSV' extension from mechatroner
for sample_data.csv?
Show Recommendations Install
https://github.com/google-generative-ai-examples/hub/main/README.md
Cursor Tab Spaces: 4 Cell 14 of 15
```


Search Agents...

New Agent

Agents

CSV file statistical an... 14m

Task 3: CSV Data Analysis

Scenario: You are processing structured data from a CSV file.

Task: Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

Expected Output: Correct output Screenshot

showing all results

Ready for Colab — can be uploaded and run directly

Expected Output: The notebook produces a final summary table like:

Column	Mean	Min	Max
Age	32.75	25	45
Salary	63750.00	50000	80000
Score	89.63	85	95

To Use:

1. Upload the notebook to Google Colab

2. Get your Gemini API key from Google AI Studio

3. Replace YOUR_API_KEY_HERE in the configuration cell

4. Run all cells — the notebook will calculate and display mean, min, and max values

The notebook is ready to use. Run it in Colab and take a screenshot of the final output showing the statistical analysis results.

3 Files

Task3_CSV_Data_An... +14 -0

sample_data.csv +9 -1

README_Task3.md +93 -1

Reject, suggest, follow up?

Auto

Task3_CSV_Data_Analysis.ipynb

Task 3: CSV Data Analysis with Gemini > M4 Step 7: Final Output Summary

Code Markdown Run All Restart Clear All Outputs Jupyter Variables Outline

.venv (Python 3.9.6)

Step 3: Configure Gemini API

Note: You need to get your Gemini API key from Google AI Studio

```
# Configure Gemini API
# Option 1: Set your API key here (replace with your actual key)
GEMINI_API_KEY = "YOUR_API_KEY_HERE"

# Option 2: Or use environment variable
# GEMINI_API_KEY = os.getenv("GEMINI_API_KEY")

# Configure the API
gemini.configure(api_key=GEMINI_API_KEY)

print("Gemini API configured successfully!")
```

0.0s

Gemini API configured successfully!

Step 4: Upload CSV File

Upload your CSV file using the file uploader below, or use a sample CSV file.

Read the CSV file

csv_file = 'sample_data.csv' # Change this to your uploaded file name

If you uploaded a file, uncomment and use:

csv_file = list(uploaded.keys()))[0]

df = pd.read_csv(csv_file)

print("CSV file loaded successfully!")

print(f"Shape: {df.shape}")

print(f"First few rows:")

display(df.head())

0.0s

CSV file loaded successfully!

Shape: (6, 4)

First few rows:

	Name	Age	Salary	Score
0	Alice	25	50000	85
1	Bob	30	60000	90
2	Charlie	35	70000	88
3	Diana	28	55000	92
4	Eve	32	65000	87

Step 5: Traditional Statistical Analysis (Baseline)

Search Agents...

New Agent

Agents

CSV file statistical an... 14m

Task 3: CSV Data Analysis

Scenario: You are processing structured data from a CSV file.

Task: Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

Expected Output: Correct output Screenshot

showing all results

Ready for Colab — can be uploaded and run directly

Expected Output: The notebook produces a final summary table like:

Column	Mean	Min	Max
Age	32.75	25	45
Salary	63750.00	50000	80000
Score	89.63	85	95

To Use:

1. Upload the notebook to Google Colab

2. Get your Gemini API key from Google AI Studio

3. Replace YOUR_API_KEY_HERE in the configuration cell

4. Run all cells — the notebook will calculate and display mean, min, and max values

The notebook is ready to use. Run it in Colab and take a screenshot of the final output showing the statistical analysis results.

3 Files

Task3_CSV_Data_An... +14 -6

sample_data.csv +9 -1

README_Task3.md +93 -1

Reject, suggest, follow up?

Auto

Task3_CSV_Data_Analysis.ipynb

Task 3: CSV Data Analysis with Gemini > M4 Step 7: Final Output Summary

Code Markdown Run All Restart Clear All Outputs Jupyter Variables Outline

.venv (Python 3.9.6)

Step 5: Traditional Statistical Analysis (Baseline)

First, let's calculate mean, min, and max using traditional methods for comparison.

Calculate statistics for numeric columns only

numeric_cols = df.select_dtypes(include=(np.number)).columns

print("n" * 60)

print("TRADITIONAL STATISTICAL ANALYSIS")

print("n" * 60)

stats_df = pd.DataFrame({

'Column': numeric_cols,

'Mean': [df[col].mean() for col in numeric_cols],

'Min': [df[col].min() for col in numeric_cols],

'Max': [df[col].max() for col in numeric_cols]

})

display(stats_df)

print("\nDetailed Statistics:")

print(df[numeric_cols].describe())

0.0s

TRADITIONAL STATISTICAL ANALYSIS

Column Mean Min Max

0 Age 32.750 25 45

1 Salary 63750.000 50000 80000

2 Score 89.625 85 95

Detailed Statistics:

Age Salary Score

count 6.000000 6.000000 6.000000

mean 32.750000 63750.000000 89.625000

std 6.408599 9895.886591 3.113909

min 25.000000 50000.000000 85.000000

25% 28.750000 57250.000000 87.750000

50% 31.000000 62500.000000 89.500000

75% 35.750000 76500.000000 91.250000

max 45.000000 80000.000000 95.000000

Search Agents...

New Agent

Agents

CSV file statistical an... 16m

Task 3: CSV Data Analysis

Scenario:
You are processing structured data from a CSV file.

Task:
Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

Expected Output:
> Correct output
> Screenshot

Auto

Salary 63750.00 50000 80000
Score 89.63 85 95

To Use:
1. Upload the notebook to Google Colab
2. Get your Gemini API key from Google AI Studio
3. Replace YOUR_API_KEY_HERE in the configuration cell
4. Run all cells — the notebook will calculate and display mean, min, and max values

The notebook is ready to use. Run it in Colab and take a screenshot of the final output showing the statistical analysis results.

3 Files
Task3_CSV_Data_An... +14 -6
sample_data.csv +9 -1
README_Task3.md +93 -1

Reject, suggest, follow up?

Auto

Task3_CSV_Data_Analysis.ipynb

Task 3: CSV Data Analysis with Gemini > M4 Step 7: Final Output Summary

Code + Markdown Run All Restart Clear All Outputs Jupyter Variables Outline

venv (Python 3.9.0)

Step 6: Gemini-Powered Analysis

Now, let's use Gemini to analyze the CSV data and calculate statistics.

markdown

Prepare data for Gemini
Convert DataFrame to string format
data_preview = df.head(10).to_string()
data_summary = f"\nData shape: {df.shape}\n"
data_summary += f"\nColumns: {list(df.columns)}\n"
data_summary += f"\nNumeric columns: {list(df.numeric_cols)}\n"
print("Data prepared for Gemini analysis")

0.0s Python

Data prepared for Gemini analysis

Step 7: Final Output Summary

Mean, Min, Max Values:

markdown

Final comprehensive summary
print("-" * 70)
print("FINAL STATISTICAL ANALYSIS - MEAN, MIN, MAX")
print("-" * 70)

final_stats = pd.DataFrame({
 'Column': numeric_cols,
 'Mean': [round(df[col].mean(), 2) for col in numeric_cols],
 'Min': [df[col].min() for col in numeric_cols],
 'Max': [df[col].max() for col in numeric_cols]
})

Display with better formatting
display(HTML(final_stats.to_html(index=False, classes='table table-striped')))

print("\n" + "-" * 70)
print("Detailed Statistics:")
print("-" * 70)
display(df[numeric_cols].describe())

print("\n" + "-" * 70)
print("ANALYSIS COMPLETE!")
print("-" * 70)

11s

Do you want to install the recommended 'Rainbow CSV' extension from mechatroner for sample_data.csv?
Show Recommendations Install

OUTPUT:

Search Agents...

New Agent

Agents

CSV file statistical an... 16m

Task 3: CSV Data Analysis

Scenario:
You are processing structured data from a CSV file.

Task:
Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

Expected Output:
> Correct output
> Screenshot

Auto

Salary 63750.00 50000 80000
Score 89.63 85 95

To Use:
1. Upload the notebook to Google Colab
2. Get your Gemini API key from Google AI Studio
3. Replace YOUR_API_KEY_HERE in the configuration cell
4. Run all cells — the notebook will calculate and display mean, min, and max values

The notebook is ready to use. Run it in Colab and take a screenshot of the final output showing the statistical analysis results.

3 Files
Task3_CSV_Data_An... +14 -6
sample_data.csv +9 -1
README_Task3.md +93 -1

Reject, suggest, follow up?

Auto

Task3_CSV_Data_Analysis.ipynb

Task 3: CSV Data Analysis with Gemini > M4 Step 7: Final Output Summary

Code + Markdown Run All Restart Clear All Outputs Jupyter Variables Outline

venv (Python 3.9.0)

=====

FINAL STATISTICAL ANALYSIS - MEAN, MIN, MAX

=====

Column Mean Min Max

Age 32.75 25 45

Salary 63750.00 60000 80000

Score 89.62 85 95

=====

Detailed Statistics:

=====

Age Salary Score

count 8.000000 8.000000 8.000000

mean 32.750000 63750.000000 89.625000

std 6.408699 9895.886591 3.113909

min 25.000000 50000.000000 85.000000

25% 28.750000 57250.000000 87.750000

50% 31.000000 62500.000000 89.500000

75% 35.750000 70500.000000 91.250000

max 45.000000 80000.000000 95.000000

=====

ANALYSIS COMPLETE!

=====

Do you want to install the recommended 'Rainbow CSV' extension from mechatroner for sample_data.csv?
Show Recommendations Install

CODE EXPLANATION:

This code performs statistical analysis on numeric columns of a DataFrame (df). First, it identifies all columns that contain numerical data using `select_dtypes(include=[np.number])`. Then, for each numeric column, it calculates the mean, minimum, and maximum values and stores them in a new DataFrame called `stats_df`. This DataFrame is displayed to show a clean summary of basic statistics.

Q)Task 4: Sorting Lists – Manual vs Built-in

❖ Scenario:

You are reviewing algorithm choices for efficiency.

❖ Task:

Use Gemini to generate:

- Bubble sort
- Python's built-in sort()
- Compare both implementations.

❖ Expected Output:

- Two versions of code
- Short comparison

PROMPT:

Generate Python code to sort a list using bubble sort and Python's built-in sort() method. Show both implementations clearly and provide a short comparison explaining their efficiency and usage.

CODE:

The screenshot shows a code editor with a task description on the left and two Python functions on the right. The task description is titled "Task 4: Sorting Lists – Manual vs Built-in" and includes a scenario, task, and expected output. The two Python functions are `bubble_sort(arr)` and `builtin_sort(arr)`. The `bubble_sort` function is a manual implementation of the bubble sort algorithm, and the `builtin_sort` function is a Python's built-in sort method. The `bubble_sort` function includes comments explaining its efficiency and usage. The `builtin_sort` function includes comments explaining its efficiency and usage.

```
Task 4: Sorting Lists – Manual vs Built-in
Scenario:
You are reviewing algorithm choices for efficiency.
Task:
Use Gemini to generate:
> Bubble sort
> Python's built-in sort()
> Compare both implementations.
Expected Output:
> Two versions of code
> Short comparison

Reviewing the existing task files to understand the project structure and format.
Explored 3 files.
Creating Task 4: Implementing Bubble sort, comparing it with Python's built-in sort(), and adding a README.
Task4_Sorting_Comparison.py +243

Task 4: Sorting Lists – Manual vs Built-in
This program compares two sorting algorithms: Bubble Sort and Python's built-in sort().

# Task 4: Sorting Lists – Manual vs Built-in
This project compares two sorting algorithms: Bubble Sort and Python's built-in sort().

Checking for linting issues:
No linting errors found in Task4_Sorting_Comparison.py.

Running the program to verify it works:
Auto-Run command in sandbox: cd, python
$ cd "/Users/boofa.manishwar/Downloads/AI Assistant coding/" && python Task4_Sorting_Comparison.py

def bubble_sort(arr):
    """
    Manual implementation of Bubble Sort algorithm.

    Bubble Sort is a simple sorting algorithm that repeatedly steps through the list,
    compares adjacent elements and swaps them if they are in the wrong order.
    The pass through the list is repeated until the list is sorted.

    Time Complexity: O(n^2) – Worst and Average case
    Space Complexity: O(1) – In-place sorting

    Args:
        arr (list): List of comparable elements to sort

    Returns:
        list: Sorted list (original list is also modified in-place)
    """
    # Create a copy to avoid modifying the original list
    arr = arr.copy()
    n = len(arr)

    # Outer loop: number of passes
    for i in range(n):
        # Flag to check if any swap occurred (optimization)
        swapped = False

        # Inner loop: compare adjacent elements
        # After each pass, the largest element bubbles to the end
        for j in range(0, n - i - 1):
            # If current element is greater than next, swap them
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
                swapped = True

        # If no swaps occurred, list is already sorted (optimization)
        if not swapped:
            break

    return arr



def builtin_sort(arr):
    """
    Python's built-in sort() method.

    Python's built-in sort() uses Timsort algorithm, which is a hybrid
    stable sorting algorithm derived from merge sort and insertion sort.

    Time Complexity: O(n log n) – Best, Average, and Worst case
    Space Complexity: O(n) – Requires additional space

    Args:
        arr (list): List of comparable elements to sort

    Returns:
        list: Sorted list
    """
    # Create a copy and sort it
    arr_copy = arr.copy()
    arr_copy.sort()
    return arr_copy
```



OUTPUT:

Agents

Bubble sort vs Python... 17m

Task 4: Sorting Lists – Manual vs Built-in

Scenario:

You are reviewing algorithm choices for efficiency.

Task:

Use Gemini to generate:

Bubble sort

Python's built-in sort()

Compare both implementations.

Expected Output:

Two versions of code

Short comparison

100%

Auto

Reviewing the existing task files to understand the project structure and format.

Explored 3 files

Creating Task 4: implementing Bubble sort, comparing it with Python's built-in sort(), and adding a README.

...k4_Sorting_Comparison.py +243

README_Task4.md (new) +198

Task 4: Sorting Lists – Manual vs Python's Built-in Sort

This project compares two sorting algorithms: Bubble Sort and Python's built-in sort().

Checking for linting issues:

No linting errors found in Task4_Sorting_Comparison.py

Running the program to verify it works:

Auto-Ran command in sandbox: cd, python

\$ cd "/Users/bodla.manishwar/Downloads/AI Assistant coding/AIC" && python Task4_Sorting_Comparison.py

=====

2 Files Undo All Keep All Review

Plan, @ for context, / for commands

100%

Auto

Problems

Output

Debug Console

Terminal

Ports

Jupyter

AIC

DEMONSTRATION: Sorting a Sample List

Original List: [64, 34, 25, 12, 22, 11, 98, 5]
Bubble Sort Result: [5, 11, 12, 22, 25, 34, 64, 98]
Built-in sort() Result: [5, 11, 12, 22, 25, 34, 64, 98]
Both methods produce identical results!

PERFORMANCE COMPARISON: Bubble Sort vs Built-in sort()

Array Size	Bubble Sort (s)	Built-in sort() (s)	Speedup
100	0.000309	0.000005	58.91 x
500	0.000075	0.000030	266.80 x
1000	0.039540	0.000070	566.02 x
5000	0.948191	0.000370	2548.88 x

ALGORITHM COMPARISON SUMMARY

BUBBLE SORT (Manual Implementation):

- Algorithm Type: Simple comparison-based sorting
- Time Complexity: $O(n^2)$ – Quadratic time
- Space Complexity: $O(1)$ – Constant space (in-place)
- Stability: Stable (equal elements maintain relative order)
- Best Case: $O(n)$ – When array is already sorted
- Worst Case: $O(n^2)$ – When array is reverse sorted
- Average Case: $O(n^2)$
- Use Case: Educational purposes, very small datasets
- Advantages:
 - Simple to understand and implement
 - In-place sorting (no extra memory needed)
 - Stable sorting algorithm
- Disadvantages:
 - Very slow for large datasets
 - Not practical for real-world applications

PYTHON'S BUILT-IN sort() (Timsort):

- Algorithm Type: Hybrid stable sorting (Merge + Insertion)
- Time Complexity: $O(n \log n)$ – Linearithmic time
- Space Complexity: $O(n)$ – Requires additional space
- Stability: Stable (equal elements maintain relative order)
- Best Case: $O(n \log n)$
- Worst Case: $O(n \log n)$
- Average Case: $O(n \log n)$
- Use Case: Production code, real-world applications
- Advantages:
 - Extremely fast and efficient
 - Optimized for real-world data patterns
 - Handles various edge cases
 - Well-tested and reliable
- Disadvantages:
 - Uses more memory than in-place algorithms
 - Less educational value (implementation is hidden)

KEY TAKEAWAY:

For educational purposes, implementing Bubble Sort helps understand algorithmic thinking. However, for practical applications, always use Python's built-in sort() as it's significantly faster and more reliable.

Performance Difference:

- Built-in sort() is typically 100-1000x faster than Bubble Sort
- The difference becomes exponentially larger as dataset size increases

Task 4 completed successfully!

Do you want to install the recommended "Rainbow CSV" extension from mechatroner for sample_data.csv?

Show Recommendations

Install

Cursor Tab Ln 243, Col 1 Spaces: 4 UTF-8 LF Python 3.9.6 (.venv) .venv

CODE EXPLANATION:

This program compares Bubble Sort and Python's built-in `sort()`. Bubble Sort manually compares and swaps elements to arrange them in order, but it is slow for large lists because it has $O(n^2)$ time complexity. Python's built-in `sort()` uses an efficient algorithm and sorts data much faster with $O(n \log n)$ time complexity. The program measures execution time for both methods and shows that the built-in sort is much faster and more suitable for real-world use.