Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

HV TEST SET · A.C. BREAKDOWN / WITHSTAND

CIE/5050A

A.C. HV breakdown / withstand test set · memory device · zero-start interlock

01 KEY FEATURES

- Zero-start interlocking
- Memory device retains breakdown reading
- Selectable tripping current
- Analog moving-iron kV meter and milliammeter
- Cast-resin H.V. transformer
- Powder-coated M.S. cabinet

02 WHAT'S IN THE BOX

✓ One pair of H.V. probe with cable

03 OPTIONS (extra cost)

\+ Alternate tripping current set point



CIE/5050A · HV TEST SET

04 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Input	230 V ±10%, 50 Hz, 1 phase A.C.
Capacity	50 mA maximum on H.V. side
Tripping Current	25 mA & 50 mA - toggle switch selectable (standard)
Duty Cycle	Intermittent - 5 min ON, 10 min OFF
Mode of Operation	Manual
Metering	Analog moving-iron - kV meter & milliammeter, per IS 1248:1983 (not digital)
Memory Device	Push-button switch retains breakdown reading after H.V. trip
Warranty	12 months against manufacturing defects only

Any tripping current setting apart from the standard 25mA/50mA above can be built to order.

05 AVAILABLE VARIANTS

VARIANT	OUTPUT RANGE	TRIPPING CURRENT
CIE/5050A (3 kV)	0–3 kV A.C.	25 mA & 50 mA, toggle selectable
CIE/5050A (5 kV)	0–5 kV A.C.	25 mA & 50 mA, toggle selectable

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/5050A Product Catalogue.