Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

EARTH TESTER · HAND-DRIVEN, METAL BODY

# CIE/222M

## 3-terminal · 0–3000 Ω

Hand-driven earth tester · 3-terminal and 4-terminal types

## 01 KEY FEATURES

- Hand-driven generator
- Centrifugal governor
- 3-terminal and 4-terminal types
- Anti-magnetic aluminium body
- Collapsible generator handle
- Protective flap over scale

Supplied as base instrument only - testing kit and carrying case available at extra cost.




CIE/222M · ILLUSTRATIVE IMAGE

## 02 OPTIONAL ACCESSORIES (extra cost)

+ Testing kit - 3-terminal: 2 spikes (45cm), 3 wire spools (10/20/30m), 1 hammer, bag
+ Testing kit - 4-terminal: 4 spikes (45cm), 4 wire spools (10/20/20/30m), 1 hammer, bag
+ Carrying case

## 03 TECHNICAL SPECIFICATIONS

| PARAMETER | SPECIFICATION |
|---|---|
| **CONFIGURATION** | |
| Terminal Type | 3-terminal (earth resistance) |
| Range Configuration | Single range |
| Measuring Range(s) | 0–3000 Ω |
| **MEASUREMENT** | |
| Accuracy | ±5% (as per IS: 9223/1979) |
| Scale Length | 80 mm (approx.) |
| **GENERATOR** | |
| Generator Type | Hand-driven generator, centrifugal governor |
| Rotation Speed | 160 r.p.m. |
| **TEST & SAFETY** | |
| High Voltage Test | 2 KV A.C. (r.m.s.), 1 min., circuit to containing case |
| Insulation Resistance Test | Better than 25 MΩ at 500V D.C. |
| **GENERAL** | |
| Body | Anti-magnetic aluminium |
| Dimensions (L×W×H) | 110 × 128 × 190 mm (approx.) |
| Weight | 2.5 kg (approx.) |
| Warranty | 12 months against manufacturing defects only |

*Other ranges can be built against specific requirements - enquire.*



All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/222M 3-terminal, 0–3000 Ω Product Catalogue.