Cambridge Instruments
& Engg. Co.

EST. 1963 · HOWRAH, INDIA

INSULATION TESTER · MULTIRANGE, METAL BODY

CIE/444/MR

Series MR-3 · 500 / 250 / 100 V

Multirange insulation tester · selectable voltage · built-in continuity range

01 KEY FEATURES

- Selectable multi-voltage operation
- Built-in continuity range
- Anti-magnetic aluminium, die-cast body

MR-5 to MR-8 are wooden-body only (see **CIE/666/MR**) - not available in this metal-body configuration.



CIE/444/MR · INSULATION TESTER · ILLUSTRATIVE IMAGE

02 OPTIONAL ACCESSORIES (extra cost)

+ Carrying case
+ Test leads, 1m
+ H.V. test leads, 2m (general)
+ H.V. test leads, 2m (special)

03 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Body	Anti-magnetic aluminium
Generator Type	Hand-driven
Series	MR-3
Continuity Range	Built-in as standard on all MR series
Warranty	12 months against manufacturing defects only

Any other configuration can be built to order - enquire.

04 SERIES SPECIFICATION - VOLTAGE, RANGE & CONTINUITY

SERIES	VOLTAGE & RESISTANCE RANGES	CONTINUITY RANGE
MR-3	500V/0–1000MΩ · 250V/0–500MΩ · 100V/0–200MΩ	0–5 KΩ

ISO 9001:2015 CERTIFIED

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/444/MR MR-3 Product Catalogue.