Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

OIL TEST SET · TRANSFORMER OIL BDV TESTER

CIE/7000 SERIES

0–50 kV to 0–120 kV · 8 models · manual / motorised · IS 6792:1992

01 KEY SPECIFICATIONS

OUTPUT	0–50 kV to 0–120 kV (8 models)
CAPACITY	500 VA to 1200 VA
DRIVE	Manual or motorised (approx. 2 kV/s)
METERING	96 mm² moving-iron kV meter, L.T. side
TEST VESSEL	Brass spheres · IS 6792:1992



CIE/7000 SERIES · OIL TEST SET

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
ELECTRICAL	
Output Voltage Range	0–50 kV to 0–120 kV (8 models, continuously variable)
Capacity Range	500 VA to 1200 VA (varies by model)
Input	230 V ±10%, 50 Hz, 1 phase A.C.
Duty	Intermittent
H.V. Winding	Cast-resin, graded insulation, centre point grounded
METERING & TEST VESSEL	
Metering	96 mm² A.C. moving-iron voltmeter, L.T. side, scaled in kV (analog)
Motorised Rate	Approx. 2 kV/second (motorised variant)
Test Vessel	Two brass spheres, 12.5–13 mm dia., 4mm or 2.5mm gap, per IS 6792:1992
GENERAL	
Warranty	12 months against manufacturing defects only

Any requirement apart from the standard voltage tiers & drive above can be built to order.

03 CIE/7000 SERIES - OUTPUT VOLTAGE & CAPACITY

OUTPUT VOLTAGE	CAPACITY	MANUAL MODEL	MOTORISED MODEL
0–50 kV	500 VA	CIE/7050	CIE/7050 MOT
0–60 kV	600 VA	CIE/7060	CIE/7060 MOT
0–70 kV	700 VA	CIE/7070	CIE/7070 MOT
0–75 kV	750 VA	CIE/7075	CIE/7075 MOT
0–80 kV	800 VA	CIE/7080	CIE/7080 MOT
0–90 kV	900 VA	CIE/7090	CIE/7090 MOT
0–100 kV	1000 VA	CIE/7100	CIE/7100 MOT
0–120 kV	1200 VA	CIE/7120	CIE/7120 MOT

04 APPLICATIONS

- Transformer oil dielectric strength testing before energisation
- Routine oil quality monitoring for distribution and power transformers
- Circuit breaker oil testing
- Power utility and substation maintenance laboratories

05 WHAT'S IN THE BOX

- ✓ Instruction manual with circuit diagram
- ✓ Input supply cable, minimum 2 metres, 3-pin plug
- ✓ Test vessel (oil cell) with electrode and gap-setting gauge

06 OPTIONAL ACCESSORIES

- + Alternate tripping current set point
- + 2-unit housing
- + Magnetic stirrer
- + Digital metering in place of analog
- + Double capacity, 20 mA (CIE/7050–7080 only)

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - CIE/7000 Series Product Catalogue.