Cambridge Instruments & Engg. Co.

EST. 1963 · HOWRAH, INDIA

DIGITAL EARTH RESISTANCE TESTER

DET-2000

4-terminal · earth resistance & soil resistivity · 3½-digit LCD

01 KEY SPECIFICATIONS

TERMINALS	4-terminal (E1, P1, P2, E2)
MEASURES	Earth resistance · soil resistivity
ACCURACY	±1.5% (10–90% of range) · IS 9223
DISPLAY	3½-digit LCD, Lo-Bat
POWER	Rechargeable Ni-Cd · 230 V / 50 Hz charging
WEIGHT	Approx. 575 g

Testing kit (spikes, cables, hammer) available at extra cost - not included standard.



DET-2000 · DIGITAL EARTH RESISTANCE TESTER

02 TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
MEASUREMENT	
Terminals	4-terminal (E1, P1, P2, E2)
Display	3½-digit LCD, with Lo-Bat indicator
Accuracy	±3% (0–10%, 90–100%); ±1.5% (10–90% of range)
Range Configuration	Multiple range options available - specify at order
TEST & SAFETY	
High Voltage Test	2kV A.C. r.m.s., 1 min, circuit to containing case
Insulation Resistance Test	More than 25 MΩ at 500V D.C.
GENERAL	
Power	Rechargeable Ni-Cd cells, 230 V/50 Hz charging cord
Dimensions (L×W×H)	172 × 98 × 38 mm
Weight	Approx. 575 g
Warranty	12 months against manufacturing defects only

Custom ranges and configurations can also be built against specific requirements.

03 APPLICATIONS

- Earth resistance testing - power, telecom, railway
- Domestic and industrial installation earthing checks
- Soil resistivity surveys for electrode positioning
- General non-inductive/non-capacitive resistance testing

04 WHAT'S IN THE BOX

- ✓ Carrying case
- ✓ Charging cord
- ✓ Instruction manual

All specifications are subject to change without prior notice. © Cambridge Instruments & Engg. Co. - DET-2000 Product Catalogue.